

The Architecture of the DecentVM

Towards a Decentralized Virtual Machine for Many-Core Computing


17 October 2010

*Annette Bieniusa, Johannes Eickhold,
and Thomas Fuhrmann*




*Department of Informatics, Self-Organizing Systems Group
Technische Universität München, Germany*


Design Goal of DecentVM




DecentVM's Origin – Modular Embedded Devices




Bluetooth Module




Ethernet Module




Power-over-Ethernet Module




LiPo Battery Module



Backplane Module



Access Adapter



I/O Module




Peripheral Module



Bundesministerium
für Bildung
und Forschung


Ambicomp Project,
2005-2009

Current Target Architecture and Prototype




Bundesministerium
für Bildung
und Forschung


J-Cell Project, 2009-2012



Objects in DecentVM




Access via Reference and via Name




Saballus, Fuhrmann. Maintaining Reference Graphs of Globally Accessible Objects in Fully Decentralized Distributed Systems . HPDC'09

Consistency with DecentSTM




Bieniusa, Fuhrmann. *Consistency in Hindsight, A Fully Decentralized STM Algorithm*. IPDPS'10

Exploit STM Left-Over State for Redundancy




*Posselt. Design of a Reliable,
Fully Decentralized Software
Transactional Memory Protocol.
Diploma Thesis, TUM, 2010*


DecentVM – Architecture Overview



Blobs as Suites of Classes



DecentVM's Memory Architecture



Summary

- Fully decentralized Virtual Machine
- Memory Access by Name and via References
- Software Transactional Memory for Consistency
- Exploit STM as Extra Redundancy for Reliability

- Research VM (ca. 2000 lines of code ANSI C)
 - Bare metal implementation, i.e. no OS required
 - Offline transcoder transforms Java bytecode into DecentVM code
 - Traps to system library for float arithmetic, etc.
- References, Class IDs, etc. only Locally Valid
 - Need to map class IDs and runtime type info (RTTI)
- Transactions Exploit Private Memory
 - References within a transaction become public only upon commit
 - References need to be resolved only upon numeric GETFIELD

Thank you!



Thomas Fuhrmann

*Department of Informatics
Self-Organizing Systems Group
Technische Universität München, Germany*

fuhrmann@in.tum.de