

Midwest Big Data Summer School: Machine Learning II: Basic to Advanced Methods

Kris De Brabanter


kbrabant@iastate.edu

Iowa State University
Department of Statistics
Department of Computer Science

June 24, 2016


- 1 Support vector machines
 - Linearly separable case
 - Overlapping classes
 - Nonlinearly separable case
- 2 k -means clustering

Why support vector machines?




How many neurons ?

cost function




weight space

Why support vector machines?




Main idea of support vector machines

Assume $\{X_i, Y_i\}_{i=1}^n$ with $X \in \mathbb{R}^p$ and $Y \in \{-1, 1\}$



Main idea of support vector machines


Assume $\{X_i, Y_i\}_{i=1}^n$ with $X \in \mathbb{R}^p$ and $Y \in \{-1, 1\}$




Need to solve the following constraint (convex) optimization problem

$$\min_w \frac{1}{2} w^T w \quad s.t. \quad Y_i(w^T X_i + b) \geq 1, i = 1, \dots, n$$


Example: classes are linearly separable




Overlapping classes



Slack variables



Slack variables



Need to solve the following constraint (convex) optimization problem

$$\min_w \frac{1}{2} w^T w + C \sum_{i=1}^n \epsilon_i \quad \text{s.t.} \quad Y_i(w^T X_i + b) \geq 1 - \epsilon_i, \quad \epsilon_i \geq 0, \quad i = 1, \dots, n$$


Nonlinearly separable

Solution: Map data into a higher dimensional (possibly infinite) space




Nonlinearly separable

Solution: Map data into a higher dimensional (possibly infinite) space



Nonlinearly separable


Solution: Map data into a higher dimensional (possibly infinite) space



Map data from 1D to 2D via the mapping $X \mapsto \varphi(X) = (X, X^2)$



Mapping to high(er) dimensional space

Data is linearly separable now. We can just use SVM in this new space





Mapping to high(er) dimensional space

$$(X_1, X_2) \mapsto \varphi(X_1, X_2) = (X_1, X_2, \sqrt{X_1^2 + X_2^2})$$



Mapping to high(er) dimensional space

$$(X_1, X_2) \mapsto \varphi(X_1, X_2) = (X_1, X_2, \sqrt{X_1^2 + X_2^2})$$





Need to solve the following constraint (convex) optimization problem

$$\min_w \frac{1}{2} w^T w + C \sum_{i=1}^n \varepsilon_i \quad s.t. \quad Y_i(w^T \varphi(X_i) + b) \geq 1 - \varepsilon_i, \quad \varepsilon_i \geq 0, \quad i = 1, \dots, n$$


More on this mapping...

- Surprisingly you do not need to specify this mapping beforehand (Mercer, 1909)
- The inner product $\varphi(X_i)^T \varphi(X_j) = K(X_i, X_j)$ with K a positive definite kernel function
- Choices for K include linear, polynomial, Gaussian (with bandwidth h), etc.
- SVMs for pattern recognition usually have 1 or 2 tuning parameters (cross-validation)
- Related to Reproducing Kernel Hilbert Spaces


Two more nonlinear examples



Importance of the tuning parameters



(i) h too small



(j) h too large

Definition

Clustering refers to a very broad set of techniques for finding subgroups or clusters in a data set. It belongs into the category of unsupervised learning

Definition

Clustering refers to a very broad set of techniques for finding subgroups or clusters in a data set. It belongs into the category of unsupervised learning

Given the total number of cluster K , let C_1, \dots, C_K denote sets containing indices of the observations in each cluster. These sets satisfy

- ① $C_1 \cup \dots \cup C_K = \{1, \dots, K\}$
- ② $C_k \cap C_{k'} = \emptyset$ for all $k \neq k'$

k -means clustering

Definition

Clustering refers to a very broad set of techniques for finding subgroups or clusters in a data set. It belongs into the category of unsupervised learning


Given the total number of cluster K , let C_1, \dots, C_K denote sets containing indices of the observations in each cluster. These sets satisfy

- ① $C_1 \cup \dots \cup C_K = \{1, \dots, K\}$
- ② $C_k \cap C_{k'} = \emptyset$ for all $k \neq k'$

The idea behind k -means clustering is that “good” clustering is one for which the within-cluster variation is as small as possible

This turns out to be computationally infeasible since there are almost K^n ways to partition n observations into K clusters. Solution: Iterative algorithm that finds a local optimum!


The k -means algorithm in action




Limitations of k -means

- k -means has problems when clusters are of different
 - sizes
 - densities
 - non-globular shapes
- problem with outliers
- empty clusters

Limitations of k -means: Different densities




(a) original data




(b) k -means clustering with $k = 3$

Limitations of k -means: Non-globular shapes



(c) original data



(d) k -means clustering with $k = 2$

How to determine k ?

How to determine k ?

- Silhouettes (Rousseeuw, 1986)
- Gap Statistic
- See Milligan & Cooper (1985) for a comprehensive simulation comparison of 30 different procedures











How to determine k ?

- Silhouettes (Rousseeuw, 1986)
- Gap Statistic
- See Milligan & Cooper (1985) for a comprehensive simulation comparison of 30 different procedures

Other clustering methods

- Hierarchical clustering (does not require a priori knowledge of the number of clusters)
- Spectral clustering
- Ward's method

References

-  Bühlmann, P & van de Geer S. (2011), *Statistics for High-Dimensional Data: Methods, Theory and Applications*, Springer
-  Devroye L., Györfi L. & Lugosi G. (1996). *A Probabilistic Theory of Pattern Recognition*, Springer
-  Gareth J., Witten D., Hastie T. & Tibshirani R. (2013). *An Introduction to Statistical Learning with Applications in R*, Springer
-  Hastie T., Tibshirani R. & Friedman J. (2009), *The Elements of Statistical Learning: Data Mining, Inference, and Prediction (2nd Ed.)*, Springer
-  Hoerl A.E. & Kennard R. (1974), Ridge regression: biased estimation for nonorthogonal problems, *Technometrics*, 12: 55-67
-  Milligan G.W. & Cooper M.C. (1985). An examination of procedures for determining the number of clusters in a data set, *Psychometrika* 50:159-179
-  Rousseeuw P. J. (1987). Silhouettes: a Graphical Aid to the Interpretation and Validation of Cluster Analysis. *Computational and Applied Mathematics* 20: 5365
-  Silverman B. W., *Density Estimation for Statistics and Data Analysis*, Chapman & Hall, 1986
-  R. Tibshirani (1996), Regression shrinkage and selection via the lasso, *J. Royal. Statist. Soc B.*, 58(1): 267-288
-  R. Tibshirani, G. Walther & T. Hastie (2001), Estimating the number of clusters in a data set via the gap statistic, *JB Statist. Soc. B.* 63(2): 411-423