

Next In Line, Please!

Exploiting the Indirect Benefits of Inlining by Accurately Predicting Further Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Next In Line, Please!

Exploiting the Indirect Benefits of Inlining by Accurately Predicting Further Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Efficiently Estimating and Exploiting the Indirect Benefits of Inlining

Master-Thesis von Jannik Jochem
Mai 2011



Fachbereich Informatik
Fakultät Softwaretechnik

Background: The Direct and Indirect Benefits of Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Background: The Direct and Indirect Benefits of Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Direct Benefits

- ▶ No stack frame creation
- ▶ No call/return overhead
- ▶ (Possibly) no dynamic dispatch

Background: The Direct and Indirect Benefits of Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Direct Benefits

- ▶ No stack frame creation
- ▶ No call/return overhead
- ▶ (Possibly) no dynamic dispatch

Indirect Benefits

- ▶ Constant folding
- ▶ Elimination of type checks
- ▶ Elimination of null checks
- ▶ Elimination of array bounds checks
- ▶ Further, guardless Inlining

Background: The Direct and Indirect Benefits of Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Direct Benefits

- ▶ No stack frame creation
- ▶ No call/return overhead
- ▶ (Possibly) no dynamic dispatch

Indirect Benefits

- ▶ Constant folding
- ▶ Elimination of type checks
- ▶ Elimination of null checks
- ▶ Elimination of array bounds checks
- ▶ Further, guardless Inlining

Background: When is Further, Guardless Inlining Possible?



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Precise Arguments

```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}  
  
class D extends C { ... }
```

Background: When is Further, Guardless Inlining Possible?



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Precise Arguments

```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```

```
class D extends C { ... }
```

Extant Arguments

```
class A2 {  
    void m(C c) {  
        B b = ...  
        // Argument exists before call  
        // to A2.m(C).  
        b.n(c);  
    }  
}
```


Background: When is Further, Guardless Inlining Possible? And When Obviously Not?



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Precise Arguments

```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```

```
class D extends C { void n(C c) { this.f = c; } }
```

Extant Arguments

```
class A2 {  
    void m(C c) {  
        B b = ...  
        // Argument exists before call  
        // to A2.m(C).  
        b.n(c);  
    }  
}
```

Background: The Inline Oracle of Jikes RVM



TECHNISCHE
UNIVERSITÄT
DARMSTADT



1. Reject @NoInline or native methods.

Background: The Inline Oracle of Jikes RVM



TECHNISCHE
UNIVERSITÄT
DARMSTADT

1. Reject @NoInline or native methods.
2. Accept trivial callees.



1. Reject @NoInline or native methods.
2. Accept trivial callees.
3. Identify targets in dynamic call graph.



1. Reject @NoInline or native methods.
2. Accept trivial callees.
3. Identify targets in dynamic call graph.
4. For each dynamic target, estimate its size and decide whether to inline.



1. Reject @NoInline or native methods.
2. Accept trivial callees.
3. Identify targets in dynamic call graph.
4. For each dynamic target, estimate its size and decide whether to inline.
5. Choose appropriate guards.



1. Reject @NoInline or native methods.
2. Accept trivial callees.
3. Identify targets in dynamic call graph.
4. For each dynamic target, **estimate its size** and decide whether to inline.
5. Choose appropriate guards.

Problem: Jikes RVM's Assumed Size Reductions



TECHNISCHE
UNIVERSITÄT
DARMSTADT

	Reduction
Reference argument of precise type	15 %
Reference argument pre-exists method call	5 %
Non-null object constant	10 %
null constant	10 %
Integer constant	5 %
Array argument of precise type	5 %
No astore check required	2 %

Problem: Jikes RVM's Assumed Size Reductions



TECHNISCHE
UNIVERSITÄT
DARMSTADT

	Reduction
Reference argument of precise type	15 %
Reference argument pre-exists method call	5 %
Non-null object constant	10 %
null constant	10 %
Integer constant	5 %
Array argument of precise type	5 %
No astore check required	2 %

Proposed Solution: Award Size Reductions Only When Further Inlining Likely

	Reduction
Reference argument of precise type	0 %
Reference argument pre-exists method call	0 %
Non-null object constant	10 %
null constant	10 %
Integer constant	5 %
Array argument of precise type	5 %
No astore check required	2 %

Proposed Solution: How to Determine Likelihood of Further Inlining?



TECHNISCHE
UNIVERSITÄT
DARMSTADT

1. Reject @NoInline or native methods.
2. Accept trivial callees.
3. Identify targets in **dynamic call graph**.
4. For each dynamic target, estimate its size and decide whether to inline.
5. Choose appropriate guards.


Proposed Solution: Identify Precise- and Extant-Induced Edges



TECHNISCHE
UNIVERSITÄT
DARMSTADT




```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```



Proposed Solution: Identify Precise- and Extant-Induced Edges

```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```




Proposed Solution: Identify Precise- and Extant-Induced Edges



TECHNISCHE
UNIVERSITÄT
DARMSTADT

```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```



Proposed Solution: Identify Precise- and Extant-Induced Edges




TECHNISCHE
UNIVERSITÄT
DARMSTADT



```
class A1 {  
    void m() {  
        B b = ...  
        C c = new D();  
        // Precise type of argument is D.  
        b.n(c);  
    }  
}
```

Extant-induced edges work similar.



Evaluation: The Prediction Problem of Further Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Problem

Given the decision to inline $B.n(C)$ into $A.m()$, predict whether further inlining of $C.o()$ into $B.n(C)$ will occur—and only then award a size reduction.

Evaluation: The Prediction Problem of Further Inlining



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Problem

Given the decision to inline `B.n(C)` into `A.m()`, predict whether further inlining of `C.o()` into `B.n(C)` will occur—and only then award a size reduction.

Evaluation: The Prediction Problem of Further Inlining




TECHNISCHE
UNIVERSITÄT
DARMSTADT


Problem

Given the decision to inline $B.n(C)$ into $A.m()$, predict whether further inlining of $C.o()$ into $B.n(C)$ will occur—and only then award a size reduction.

Evaluation: Per-Decision Quality of Inlining Heuristics (Precision)




Evaluation: Per-Decision Quality of Inlining Heuristics (Recall)



$$\frac{\text{true positives}}{\text{true positives} + \text{false negatives}}$$


Evaluation: Per-Decision Quality of Inlining Heuristics (F1-Measure)



$$2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

Evaluation: Performance Measurements with Replay-Compilation


bloat



► 10 Compilation Plans


Evaluation: Performance Measurements with Replay-Compilation

bloat



- ▶ 10 Compilation Plans
- ▶ Proposed Inlining Heuristic saves compile time


Evaluation: Performance Measurements with Replay-Compilation




- ▶ 10 Compilation Plans
- ▶ Proposed Inlining Heuristic saves compile time
- ▶ Proposed Inlining Heuristic (sometimes) increases program time

Evaluation: Performance Measurements with and without Replay-Compilation


bloat (with replay)



bloat (without replay)




Evaluation: Speed-up on different architectures

( AMD Athlon 64,  Intel Core i7)




TECHNISCHE
UNIVERSITÄT
DARMSTADT

With replay



Without replay



Open Questions and Future Work



TECHNISCHE
UNIVERSITÄT
DARMSTADT



- ▶ Assumption “ x -induced edge \Rightarrow call on x argument” valid?



- ▶ Assumption “ x -induced edge \Rightarrow call on x argument” valid? And is gathering exact information worth it?

Open Questions and Future Work



TECHNISCHE
UNIVERSITÄT
DARMSTADT

- ▶ Assumption “ x -induced edge \Rightarrow call on x argument” valid? And is gathering exact information worth it?
- ▶ Replay compilation right methodology?



- ▶ Assumption “ x -induced edge \Rightarrow call on x argument” valid? And is gathering exact information worth it?
- ▶ Replay compilation right methodology?
- ▶ How to account for other indirect benefits (checkcast, etc.)



- ▶ Assumption “ x -induced edge \Rightarrow call on x argument” valid? And is gathering exact information worth it?
- ▶ Replay compilation right methodology?
- ▶ How to account for other indirect benefits (checkcast, etc.)
- ▶ How to better spend compile time saved?



- ▶ Assumption “x-induced edge \Rightarrow call on x argument” valid? And is gathering exact information worth it?
- ▶ Replay compilation right methodology?
- ▶ How to account for other indirect benefits (checkcast, etc.)
- ▶ How to better spend compile time saved?

```
Collections.sort(list, new Comparator() {  
    int compare(Object lhs, Object rhs) {  
        ...  
    }  
});
```