

GRAVER BASIS

Francisco Javier Blázquez Martínez



ÉCOLE POLYTECHNIQUE FÉDÉRALE DE LAUSANNE

Mathematics section,
Chair of discrete optimization

Project director: Dr. Friedrich Eisenbrand

Project supervisor: Jana Cslovjecssek

January 2021

*To my brother Joaquín, for showing me what mathematics
were during dinners at home.*

*To my parents, for teaching me beyond the scope of
mathematics.*

Acknowledgements

First and foremost I would like to express my sincere thanks to Jana Cslovjecsek for helping me throughout the whole project as well as to Professor Friedrich Eisenbrand for giving me the opportunity of doing this. It has been a very didactic experience that I really appreciate.

Moreover, this project is one of my final steps for obtaining the Double degree in Mathematics-Computer Engineering at Complutense University of Madrid that, thanks to the help of many people, I have been able to carry out in this fantastic university that is the École Polytechnique Fédérale de Lausanne. I want to expressly thank Prof. Katzalin Olcoz and Prof. Daniel Chaver for all the facilities and help. I can't help but be grateful to the Complutense University and all the teachers I've had for everything I have learnt.

Finally I would like to thank my family for their unconditional support and also Luis Felipe (TODO), for advising me so well in the important decisions these last years.

Contents

Acknowledgements	ii
1 Introduction	1
2 Graver Basis	2
3 N-Fold	4
4 N-Fold augmentation algorithm	5
5 N-Fold via LP rounding	6
A Graver basis computation with 4ti2	8
B IP resolution with Graver Basis example	9
Bibliography	10

Chapter 1

Introduction

The underlying problem we try to solve is the classical *Integer program* (IP) that we formulate in the following way:

$$(IP) \equiv \max\{c^t x : Ax = b, l \leq x \leq u, x \in \mathbb{Z}^n\}$$

$A \in \mathbb{Z}^{m \times n}, b \in \mathbb{Z}^m, c \in \mathbb{Z}^n, l$ and u lower and upper bounds for x

Despite its simplicity, it's well known the importance of IP. Several problems in diverse fields of the mathematics and algorithms admit an IP equivalent formulation (examples?). Unfortunately, IP is NP-Complete. This means that there is no efficient (polynomial) algorithm for solving IP in the general case (say general techniques and complexity?) and, therefore, knowing their importance and the lack of a general efficient algorithm for their resolution, there has been a great interest in restricted formulations of the problem and their resolution techniques.

In this project we present the concept of **Graver Basis** and its applications for solving the IP with, of course, the theoretical justification of this based on its properties. We apply this to a concrete IP formulation, the N-Fold IP and prove that it leads to a polynomial and efficient algorithm for this case.

Chapter 2

Graver Basis

Definition 2.1. Two vectors $u, v \in \mathbb{R}^n$ are said to be **sign compatible** if $u_i \cdot v_i \geq 0$ for all $i \in \{1, \dots, n\}$.

Definition 2.2. A vector $u \in \ker(A)$ is **indecomposable** if it is not the sum of two sign compatible and non zero elements in $\ker(A)$.

Definition 2.3 (Graver basis). The Graver Basis of a given matrix $A \in \mathbb{Z}^{m \times n}$ is defined as the set of integral indecomposable elements in the kernel of A .
(Initially defined as *universal integral test set* in [Graver 1975])

Proposition 2.4. For every matrix A , $Gr(A)$ is a finite set.

Proposition 2.5. Every integral element in $\ker(A)$ can be expressed as positive integral linear combination of elements in $Gr(A)$.

Proposition 2.6. Given z in the feasible region of an IP, z is not optimum if and only if there exists $g \in Gr(A)$ s.t. $c^t g > 0$ and $l \leq z + g \leq u$

Proposition 2.7 (Graver basis bounds). Given $A \in \mathbb{Z}^{m \times n}$ and Δ an upper bound for the absolute value of each component of A , for every $g \in Gr(A)$:

- $\|g\|_1 \leq m^{m/2} \Delta^m \cdot (n - m)$ [Onn 2010]
- $\|g\|_1 \leq (2m\Delta + 1)^m$ [Eisenbrand, Hunkenschröder, Klein 2018]

Bases of augmentation algorithm

- If not optimal, an element in Graver basis is an improvement direction.

- If Graver basis bounded, we can restrict our improvement direction search.

General IP algorithm using Graver basis norm bound

1. From a feasible solution z_i
2. Find g^* optimum for the sub-problem:

$$\max\{c^t g : Ag = 0, l - z_i \leq g \leq u - z_i, g \in \mathbb{Z}^n, \|g\|_1 \leq \|Gr(A)\|\}$$

- $g^* = 0 \implies z_i$ optimal solution.
- $g^* \neq 0 \implies g^*$ improvement direction, loop back to 1 with $z_{i+1} = z_i + \lambda \cdot g^*$ with the biggest λ respecting the bounds.

[Hemmecke, Onn, Romanchuk 2013]

Chapter 3

N-Fold

A generalized N-Fold IP has constriction matrix A of the form ($A_i \in \mathbb{Z}^{xt}, B_i \in \mathbb{Z}^{st}$):

$$N = \begin{pmatrix} A_1 & A_2 & \cdots & A_n \\ B_1 & 0 & \cdots & 0 \\ 0 & B_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & B_n \end{pmatrix}$$

Chapter 4

N-Fold augmentation algorithm

- **Steinitz Lemma**

Let v_1, \dots, v_n be vectors with $\|v_i\| \leq \Delta$ for $i = 1, \dots, n$. If $\sum_{i=1}^n v_i = 0$, then there is a reordering $\pi \in S_n$ such that for each $k \in \{1, \dots, n\}$ the partial sum $p_k := \sum_{i=1}^k v_{\pi(i)}$ satisfies $\|p_k\| \leq n\Delta$.

It's possible (using Steinitz Lemma) to obtain a much tighter bound for the norm of the elements in the Graver basis than the ones mentioned before. This implies a restriction in the space of search for the improvement direction in the augmentation algorithm making it much faster.

- **N-Fold Graver basis bound**

For all $g \in Gr(N)$ $\|g\|_1 \leq L_B(2r\Delta L_B + 1)^r =: L_A$ where $L_B = (2s\Delta + 1)^s$

- **N-Fold augmentation algorithm complexity**

The N-Fold IP can be solved in time $(nt)^2 \log^2(nt) \cdot \varphi(rs\Delta)^{O(r^2s+rs^2)} + LP$

[Eisenbrand, Hunkenschröder, Klein 2018]

Chapter 5

N-Fold via LP rounding

N-Fold resolution via RLR

- **N-Fold RLR complexity**

The N-Fold IP restricted linear relaxation problem can be solved in time

$$O(nt \cdot \log^2(nt) \cdot \varphi p(r)(s\Delta)^{O(s^2)})$$

- **N-Fold RLR to optimum complexity**

Given an optimal vertex of an N-Fold RLR, the N-Fold IP can be solved in time

$$O(nt \cdot (rs\Delta)^{O(r^2s+s^2)})$$

[Cslovjecsek, Eisenbrand, Weismantel 2020]

N-Fold from RLR to optimum

- **N-Fold proximity to RLR**

Let x^* be an optimal vertex solution of a N-Fold RLR, then there exists an optimal solution z^* for the N-Fold IP verifying:

$$\|z^* - x^*\|_1 \leq (rs\Delta)^{O(rs)}$$

[Cslovjecsek, Eisenbrand, Weismantel 2020]

Facts for N-Fold complexity

- $|S_l| \leq (rs\Delta)^{O(r^2s)}$
- $|V| + |E| \leq O(n(rs\Delta)^{O(r^2s)})$
- The edge IP can be computed in time $t((r+s)\Delta)^{O(r+s)^2}$
- Longest path problem in a acyclic digraph can be solved in linear time.

N-Fold complexity

- **N-Fold complexity**
The N-Fold IP can be solved in time $nt(rs\Delta)^{O(r^2s+s^2)} + RLR$

[Cslovjecsek, Eisenbrand, Weismantel 2020]

Appendix A

Graver basis computation with 4ti2

Appendix B

IP resolution with Graver Basis example

Bibliography

- [1] Jack E. Graver. On the foundations of linear and integer linear programming i. 1975.
- [2] Bernd Sturmfels. Algebraic recipes for integer programming. 2003.
- [3] Elisabeth Finhold and Raymond Hemmecke. Lower bounds on the graver complexity of m -fold matrices. 2013.
- [4] Friedrich Eisenbrand, Christoph Hunkenschroder, and Kim-Manuel Klein. Faster algorithms for integer programs with block structure. 2018.
- [5] Jana Cslovjcek, Friedrich Eisenbrand, and Robert Weismantel. N -fold integer programming via lp rounding. 2020.
- [6] Raymond Hemmecke, Shmuel Onn, and Lyubov Romanchuk. N -fold integer programming in cubic time. 2011.
- [7] Friedrich Eisenbrand and Robert Weismantel. Proximity results and faster algorithms for integer programming using the steinitz lemma. 2019.
- [8] Jesús A. De Loera, Raymond Hemmecke, Shmuel Onn, and Robert Weismantel. N -fold integer programming. 2006.
- [9] Raymond Hemmecke. Exploiting symmetries in the computation of graver bases. 2004.
- [10] Elisabeth Finhold and Raymond Hemmecke. Lower bounds on the graver complexity of m -fold matrices. 2013.