BOARD CHARACTERISTICS


Copper Layer Count: Board Thickness: 62.99 mils

Board overall dimensions: 783.63 mils x 1096.00 mils

10.00 mils / 9.50 mils Min track/spacing: Min hole diameter: 10.00 mils ENIG Copper Finish: Impedance Control: No Castellated pads: Plated Board Edge: No

Edge card connectors: No

Layer Name	Туре	Material	Thickness (mils)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Not specified	0 mils	Not specified	1	0
F.Paste	Top Solder Paste		0 mils		1	0
F.Mask	Top Solder Mask	Not specified	0.3937 mils	Green	3.3	0
F.Cu	copper		1.37795 mils		1	0
Dielectric 1	prepreg	FR4	3.93701 mils	Not specified	4.5	0.02
In1.Cu	copper		1.37795 mils		1	0
Dielectric 2	core	FR4	48.8189 mils	Not specified	4.5	0.02
In2.Cu	copper		1.37795 mils		1	0
Dielectric 3	prepreg	FR4	3.93701 mils	Not specified	4.5	0.02
B.Cu	copper		1.37795 mils		1	0
B.Mask	Bottom Solder Mask	Not specified	0.3937 mils	Green	3.3	0
B.Paste	Bottom Solder Paste		0 mils		1	0
B.Silkscreen	Bottom Silk Screen	Not specified	0 mils	Not specified	1	0



Drill Map:

- x 0.200mm / 0.0079" (2 holes)

 o 0.300mm / 0.0118" (31 holes)

 + 0.305mm / 0.0120" (9 holes)

 □ 1.000mm / 0.0394" (6 holes)

 ◇ 3.000mm / 0.1181" (2 holes)

 Ø 3.400mm / 0.1339" (2 holes) (not plated)

NOTES:

- 1. LAYERS: 4 2. PCB THICKNESS: 1.6mm 3. PCB COLOR: GREEN

- 3. PCB COLOR: GREEN
 4. SILKSCREEN: WHITE
 5. MATERIAL TYPE: FR4 TG-155
 6. SURFACE FINISH: ENIG
 7. OUTER COPPER WEIGHT: 1oz
 8. INNER COPPER WEIGHT: 0.5oz
 9. IMPEDANCE CONTROL: NO
 10. VIA COVERING: PLUGGED
 11. MIN VIA HOLE DIA: 0.2mm
- 12. BOARD OUTLINE TOLERANCE: +/-0.2mm



971 Spartan Robotics

File: mag-encoder.kicad_pcb

Title: Mag Encoder

Size: B Date: 2024-11-25 KiCad E.D.A. 8.0.6 Rev: 4 Page: 1/1