



# Cyber Planner Code Report

## v0.1.0 (C++ Version)

Zirui Zhang<sup>1</sup>, Yan Chen, and Ruoqi Xu

**Abstract**—The code report is abstract enough that no additional abstract is needed

### I. INTRODUCTION

WHAT can I say? What can I say? What can I say?  
What can I say? What can I say?

Fujun Ruan  
January 31, 2025

### II. PATH PLANNING

#### A. Improved A\* Algorithm

As Image ?? shown, the original A\* algorithm may always find a path that very close to the obstacles. This is often led by the heuristic function. However, if any errors occurred in estimate or control, the robot may collide with the obstacles. To avoid this, we introduce artificial potential field to the cost function.

Every grid in the map has a potential value. The potential value is calculated by the distance to the obstacles in a dynamic programming way. It can find us a heuristic path, but it is still discrete. To make the path continuous, we need to interpolate the path.


#### B. Polynomial Curve

The key idea of a polynomial curve is to make the discrete path continuous, not only in position but also in velocity and acceleration.


$$\begin{aligned} p_i &\in \mathcal{P} \\ p_i &= [x_i, y_i], \forall i \in [0, n] \\ q_{i,x}(s) &= a_{i,x}s^3 + b_{i,x}s^2 + c_{i,x}s^1 + d_{i,x} \\ &\forall i \in [0, n-1], s \in [0, 1] \end{aligned} \quad (1)$$

$s$  is the normalized representation of the arc length. The minimum order of polynomial to make the path continuous

Z. Zhang, Y. Chen and R. Xu are with Next Innovation STEM Center (see <https://nifornextinnovation.com/>).  
See Z. Zhang from <https://github.com/zhangzrjerry>  
See Y. Chen from <https://github.com/mirrorcy>  
See R. Xu from <https://github.com/rockyxrq>



(a) Original A\* Algorithm



(b) Improved A\* Algorithm

Fig. 1: Difference between original and improved A\* algorithm




Fig. 2: 3D Cubic Spline

in position, velocity, and acceleration is 3. And to ensure the continuous, we need

$$\begin{cases} q_{i-1,x}(1) = q_{i,x}(0) = x_i \\ q'_{i-1,x}(1) = q'_{i,x}(0) \\ q''_{i-1,x}(1) = q''_{i,x}(0) \end{cases}, \forall i \in [1, n] \quad (2)$$

If the object is stationary in the beginning and at the

end, the velocity should be  $q'_0(0) = q'_n(1) = 0$ . By solving these equations we can uniquely determine a polynomial to fit those points.

$$\begin{cases} a_i = x_{i+2} - 2x_{i+1} + x_i \\ b_i = -x_{i+2} + 2x_{i+1,k} - x_i \\ c_i = x_{i+1} - x_i \\ d_i = x_i \end{cases}, \forall i \in [1, n-1] \quad (3)$$

In natural form [?].

$$\begin{bmatrix} 2 & 1 & & & \\ 1 & 4 & 1 & & \\ & \ddots & \ddots & \ddots & \\ & & 1 & 4 & 1 \\ & & & 1 & 2 \end{bmatrix} \begin{bmatrix} D_0 \\ D_1 \\ \vdots \\ D_{m-1} \\ D_m \end{bmatrix} = \begin{bmatrix} 3(x_1 - x_0) \\ 3(x_2 - x_0) \\ \vdots \\ 3(x_m - x_{m-2}) \\ 3(x_m - x_{m-1}) \end{bmatrix} \quad (4)$$

In case,

$$\begin{cases} a_i = 2(x_i - x_{i+1}) + D_i + D_{i+1} \\ b_i = 3(x_{i+1} - x_i) - 2D_i - D_{i+1} \\ c_i = D_i \\ d_i = x_i \end{cases} \quad (5)$$

### C. Continuous Potential Field

In section II.A, we proposed a method to calculate the approximate and discrete potential field. However, the potential field often cause the path a severe shaking. Although you can set the potential field below a certain threshold to zero, this still does not make the system satisfactory.




Fig. 3: The path is not smooth and has sharp jitters.

1) *Convex Polygon*: Any object can be represented by a set of convex polygons. The potential energy of a certain point is the minimum distance from the point to the edge of the polygon. In robot arm case, the certain point represent a kind of configuration of the robot arm. The potential energy is the minimum distance between the set of polygons that make up the current configuration of the robot and the set of polygons that make up the environmental obstacles.

If the point is inside the polygon, the distance is the minimum distance to the edge of the polygon. If the point is outside the polygon, the distance can be obtained by solving the Low Dimensional Quadratic Programming (LDQP) problem.

$$\begin{aligned} \min_x & \|x - p\|^2 \\ \text{s.t.} & Ax \leq b \end{aligned} \quad (6)$$

$p$  is the given point, and  $x$  is the point inside the polygon.

If the polygon is intersect or overlap with the other polygon, the distance is the distance is defined as the minimum distance from a vertex of a polygon contained by another polygon to an edge of that polygon. If the two polygons are not intersect, the distance can also be obtained by solving the LDQP problem.

$$\begin{aligned} \min_{x,y} & \|x - y\|^2 \\ \text{s.t.} & Ax \leq b \\ & Cy \leq d \end{aligned} \quad (7)$$

By doing so, we can get a lipshitz continuous potential field. We can optimize the path by the gradient descent method. A probable object function is



Fig. 4: The difference between the discrete and continuous potential field.

$$\begin{aligned} & \sum_{i=0}^n \|\exp(-d_{x_i})\|^2 \\ & + \sum_{i=0}^n \|x_i - \bar{x}_i\|_{\Sigma}^2 \\ & + \sum_{i=0}^{n-1} \|x_i - x_{i+1}\|_{\Sigma}^2 \\ & + \sum_{i=1}^{n-1} \|x_{i-1} - 2x_i + x_{i+1}\|_{\Sigma}^2 \end{aligned} \quad (8)$$

$\|x_i - \bar{x}_i\|_1^2$  is the prior regularization term obtained by A\* search. The Mahalanobis distance is used because the units of each dimension are different, making the L2 norm meaningless. Squaring ensures differential flatness.

### III. TRAJECTORY PLANNING

Classical method to deal with the time parameterization problem in FRC is called forward and backward pass. Its essence is based on the trapezoidal curve or S-curve model, adjusting the time scale so that the motion planning meets the given constraints. However, it is only able to deal with 1 DOF planning problem. It has difficulty in multi-DOF trajectory planning, especially when it is not in Cartesian space [?], [?].




Fig. 5: Phase-plane trajectory[?]

Team 6328 proposed a Kairos solver in 2023. In their 23 season machine and code, they used an intake active avoidance strategy to avoid anti-collision. This allowed their solver to complete planning in a simpler way. They use linear interpolation as the initial position of waypoints, and then adjusts the position of waypoints to make the speed, acceleration, and torque meet the constraints based on the assumption that the time interval between each waypoint remains unchanged[?].

Our approach is very different from that of Team 6328. Instead of globally adjusting the time scale by assuming that the time intervals between points are consistent, we express the function of time with respect to arc length in a discretized form and parameter.




Fig. 6: The curve is uniquely determined by the arc length[?].

#### A. Time Optimal Path Parameterization

The total time of the trajectory is given by the integration of the whole path.

$$T = \int_0^T 1dt = \int_0^L \frac{1}{\frac{ds}{dt}} ds \quad (9)$$

Velocity and acceleration constraints at elevator position  $x$  and arm radian  $\theta$  are

$$\begin{aligned} -v_{x,\max} &\leq v_x \leq v_{x,\max} \\ -a_{x,\max} &\leq a_x \leq a_{x,\max} \\ -v_{\theta,\max} &\leq v_{\theta} \leq v_{\theta,\max} \\ -a_{\theta,\max} &\leq a_{\theta} \leq a_{\theta,\max} \end{aligned} \quad (10)$$

Given by chain rules, we have

$$\begin{aligned} \frac{dx}{dt} &= \frac{dx}{ds} \cdot \frac{ds}{dt} \\ \frac{d^2x}{dt^2} &= \frac{d^2x}{ds^2} \cdot \frac{ds}{dt} + \frac{dx}{ds} \cdot \frac{d^2s}{dt^2} \\ \frac{d\theta}{dt} &= \frac{d\theta}{ds} \cdot \frac{ds}{dt} \\ \frac{d^2\theta}{dt^2} &= \frac{d^2\theta}{ds^2} \cdot \frac{ds}{dt} + \frac{d\theta}{ds} \cdot \frac{d^2s}{dt^2} \end{aligned} \quad (11)$$

Denote

$$a(s) = \frac{d^2s}{dt^2}, b(s) = \left(\frac{ds}{dt}\right)^2 \quad (12)$$

The problem is described by

$$\begin{aligned} \min_{a(s), b(s)} \quad & \int_0^L \frac{1}{\sqrt{b(s)}} ds \\ \text{s.t.} \quad & b'(s) = 2a(s) \\ & x'(0)\sqrt{b(0)} = 0 \\ & x'(L)\sqrt{b(L)} = 0 \\ & \theta'(0)\sqrt{b(0)} = 0 \\ & \theta'(L)\sqrt{b(L)} = 0 \\ & -b(s) \leq 0 \\ & [x'(s)]^2 b(s) \leq v_{x,\max}^2 \\ & [\theta'(s)]^2 b(s) \leq v_{\theta,\max}^2 \\ & x''(s)b(s) + x'(s)a(s) \leq a_{x,\max} \\ & -x''(s)b(s) + x'(s)a(s) \leq a_{x,\max} \\ & \theta''(s)b(s) + \theta'(s)a(s) \leq a_{\theta,\max} \\ & -\theta''(s)b(s) + \theta'(s)a(s) \leq a_{\theta,\max} \end{aligned} \quad (13)$$

1) *Discrete Case*: Considering the problem in discrete case, we have

We obtain the discretized object function




Fig. 7: Discrete function of time with respect to arc length[?].

$$\begin{aligned}
 \min_{a,b} \quad & \sum_{k=1}^K \frac{2(s^{k+1} - s^k)}{\sqrt{b^{k+1}} + \sqrt{b^k}} \\
 \text{s.t.} \quad & \frac{b^{k+1} - b^k}{s^{k+1} - s^k} = 2a^k \quad \forall k \in [0, K-1] \\
 & x'(s^0)\sqrt{b^0} = 0 \\
 & x'(s^K)\sqrt{b^K} = 0 \\
 & \theta'(s^0)\sqrt{b^0} = 0 \\
 & \theta'(s^K)\sqrt{b^K} = 0 \\
 & -b^k \leq 0 \quad \forall k \in [0, K] \\
 & [x'(s^k)]^2 b^k \leq v_{x,\max}^2 \quad \forall k \in [0, K] \\
 & [\theta'(s^k)]^2 b^k \leq v_{\theta,\max}^2 \quad \forall k \in [0, K] \\
 & x''(s^k)b^k + x'(s^k)a^k \leq a_{x,\max} \quad \forall k \in [0, K-1] \\
 & -x''(s^k)b^k + x'(s^k)a^k \leq a_{x,\max} \quad \forall k \in [0, K-1] \\
 & \theta''(s^k)b^k + \theta'(s^k)a^k \leq a_{\theta,\max} \quad \forall k \in [0, K-1] \\
 & -\theta''(s^k)b^k + \theta'(s^k)a^k \leq a_{\theta,\max} \quad \forall k \in [0, K-1]
 \end{aligned} \tag{14}$$

2) *Second-Order Cone*: To rewrite the problem to a second-order conic programming form, we first try to bound nonlinear term  $\sqrt{b^k}$  with  $c^k$ , such that  $\sqrt{b^k} \geq c^k, k \in [0, K]$ . Going a step further, we introduce one more slack variable  $d^k$ , which satisfies  $\frac{1}{c^{k+1} + c^k} \leq d^k, k \in [0, K-1]$ .

$$\begin{aligned}
 \left\| \frac{b^k - 1}{2c^k} \right\|_2 \leq b^k + 1 &\Leftrightarrow \begin{bmatrix} b^k + 1 \\ b^k - 1 \\ 2c^k \end{bmatrix} \in \mathcal{Q}^3 \\
 \left\| \frac{c^k + c^{k+1} - d^k}{2} \right\|_2 &\leq c^k + c^{k+1} + d^k \\
 &\Leftrightarrow \begin{bmatrix} c^k + c^{k+1} + d^k \\ c^k + c^{k+1} - d^k \\ 2 \end{bmatrix} \in \mathcal{Q}^3
 \end{aligned} \tag{15}$$

$$\begin{aligned}
 \min_{a,b} \sum_{k=1}^K \frac{2(s^{k+1} - s^k)}{\sqrt{b^{k+1}} + \sqrt{b^k}} &\Leftrightarrow \\
 \min_{a,b,c,d} \sum_{k=1}^K 2d^k(s^{k+1} - s^k) & \\
 \text{s.t.} \quad \left\| \frac{c^k + c^{k+1} - d^k}{2} \right\|_2 &\leq c^k + c^{k+1} + d^k \\
 \left\| \frac{b^k - 1}{2c^k} \right\|_2 &\leq b^k + 1
 \end{aligned} \tag{16}$$

Rewriting the constraints of the optimization problem, especially the nonlinear terms  $\sqrt{b_k}$ , we get the final objective function [?].

$$\min_{a,b,c,d} \sum_{k=1}^K 2(s^{k+1} - s^k)d^k$$

Subject to

$$\begin{aligned}
 \begin{bmatrix} c^k + c^{k+1} + d^k \\ c^k + c^{k+1} - d^k \\ 2 \end{bmatrix} &\in \mathcal{Q}^3 \quad \forall k \in [0, K-1] \\
 \begin{bmatrix} b^k + 1 \\ b^k - 1 \\ 2c^k \end{bmatrix} &\in \mathcal{Q}^3 \quad \forall k \in [0, K] \\
 2(s^{k+1} - s^k)a^k + b^k - b^{k+1} &= 0 \quad \forall k \in [0, K-1] \\
 [x'(s^0)]^2 b^0 &= 0 \\
 [x'(s^K)]^2 b^K &= 0 \\
 [\theta'(s^0)]^2 b^0 &= 0 \\
 [\theta'(s^K)]^2 b^K &= 0 \\
 -b^k &\leq 0, \quad \forall k \in [0, K] \\
 [x'(s^k)]^2 b^k &\leq v_{x,\max}^2 \quad \forall k \in [0, K] \\
 [\theta'(s^k)]^2 b^k &\leq v_{\theta,\max}^2 \quad \forall k \in [0, K] \\
 x''(s^k)b^k + x'(s^k)a^k &\leq a_{x,\max} \quad \forall k \in [0, K-1] \\
 -x''(s^k)b^k + x'(s^k)a^k &\leq a_{x,\max} \quad \forall k \in [0, K-1] \\
 \theta''(s^k)b^k + \theta'(s^k)a^k &\leq a_{\theta,\max} \quad \forall k \in [0, K-1] \\
 -\theta''(s^k)b^k + \theta'(s^k)a^k &\leq a_{\theta,\max} \quad \forall k \in [0, K-1]
 \end{aligned} \tag{17}$$

All constraints are divided into second-order cone constraints, equality constraints and inequality constraints [?].

$$\begin{aligned}
 \min_x \quad & c^T x \\
 \text{s.t.} \quad & A_i x + b_i \in \mathcal{K}_i \\
 & Gx = h \\
 & Px \leq q
 \end{aligned} \tag{18}$$

3) *Augmented Lagrangian Method*: Therefore, we can reformulate the problem using the Augmented Lagrangian method for Symmetric Cones.

$$\begin{aligned} \mathcal{L}_\rho(x, \mu, \lambda, \eta) = & c^T x + \\ & \frac{\rho}{2} \sum_{i=1}^m \|P_{\mathcal{K}_i}(\frac{\mu_i}{\rho} - A_i x - b_i)\|^2 + \\ & \frac{\rho}{2} \|Gx - h + \frac{\lambda}{\rho}\|^2 + \\ & \frac{\rho}{2} \|\max[Px - q + \frac{\eta}{\rho}, 0]\|^2 \end{aligned} \quad (19)$$

$P_{\mathcal{K}}$  is the projection of a vector on a symmetric cone

$$P_{\mathcal{K}}(v) = \arg \min_{x \in \mathcal{K}} \|v - x\|^2 \quad (20)$$

In second order cone case,

$$P_{\mathcal{K}=\mathcal{Q}^n}(v) = \begin{cases} 0, & v_0 \leq -\|v_1\|_2 \\ \frac{v_0 + \|v_1\|_2}{2\|v_1\|_2} (\|v_1\|_2, v_1)^T, & |v_0| < \|v_1\|_2 \\ v, & v_0 \geq \|v_1\|_2 \end{cases} \quad (21)$$

And the gradient of the augmented Lagrangian function is given by

$$\begin{aligned} \nabla \mathcal{L}_\rho(x, \mu, \lambda, \eta) = & c - \rho \sum_{i=1}^m A_i^T P_{\mathcal{K}_i}(\frac{\mu_i}{\rho} - A_i x - b_i) + \\ & \rho G^T (Gx - h + \frac{\lambda}{\rho}) + \\ & \rho P^T \{\max[Px - q + \frac{\eta}{\rho}, 0]\} \end{aligned} \quad (22)$$

So we can use a L-BFGS method to solve this convex and unconstrained function [?], [?], [?].


$$\begin{aligned} x & \leftarrow \arg \min_x \mathcal{L}_\rho(x, \mu, \lambda, \eta) \\ \mu_i & \leftarrow P_{\mathcal{K}_i}(\mu_i - \rho(A_i x + b_i)) \\ \lambda & \leftarrow \lambda + \rho(Gx - h) \\ \eta & \leftarrow \max[\eta + \rho(Px - q), 0] \\ \rho & \leftarrow \min[(1 + \gamma)\rho, \beta] \end{aligned} \quad (23)$$

$\gamma$  is the growth rate of  $\rho$  and  $\beta$  is the upper bound of  $\rho$ , which is typically  $10^3$ .


### B. Constraints on voltage and current

Can we go one step further? Although we can set constraints for speed and acceleration in segments instead of setting a global maximum value, it is difficult to exhaust all possibilities and enumerate all the required constraints. A conservative constraint will waste control resources.

On the contrary, under the guidance of the feedforward model, speed and acceleration together constitute a feasible control domain. Under the guidance of the theory of control allocation, we redesign the speed and acceleration constraints into voltage and current constraints. Doing so enables the model to dynamically adjust the energy distribution on speed and acceleration, maximize the use of control resources on the field.



(a) The corresponding path



(b) Velocity and acceleration under constraints

Fig. 8: Our previous work showing constraints on velocity and acceleration[?].

Elevator feedforward model,  $i_e$  means the ratio from motor radian to elevator position meter:

$$V_E = K_g + K_S \cdot \text{sign}(\dot{d}) + \frac{K_v}{i_e} \cdot \dot{d} + \frac{K_a}{i_e} \cdot \ddot{d} \quad (24)$$

Arm feedforward model,  $i_a$  means the ratio from motor radian to arm radian:

$$V_A = K_g \cdot \cos(\theta) + K_S \cdot \text{sign}(\dot{\theta}) + \frac{K_v}{i_a} \cdot \dot{\theta} + \frac{K_a}{i_a} \cdot \ddot{\theta} \quad (25)$$

The motor current at a given voltage and speed is:

$$I = -\frac{K_v}{R} \cdot \omega + \frac{1}{R} \cdot V \quad (26)$$

Notice that we used  $c^k$  to bound the lower side of  $\sqrt{b^k}$ . This is because

$$\frac{2(s^{k+1} - s^k)}{\sqrt{b^{k+1}} + \sqrt{b^k}} \leq \frac{2(s^{k+1} - s^k)}{c^{k+1} + c^k} \leq 2(s^{k+1} - s^k)d^k \quad (27)$$

In case, we introduce a second order cone to handle the chain constraints. The equality stands only when  $\sqrt{b^k} = c^k$ . How about directly let  $\sqrt{b^k} = c^k$  instead of  $\sqrt{b^k} \geq c^k$ ? So that,

$$\frac{2(s^{k+1} - s^k)}{\sqrt{b^{k+1}} + \sqrt{b^k}} = \frac{2(s^{k+1} - s^k)}{c^{k+1} + c^k} \leq 2(s^{k+1} - s^k)d^k \quad (28)$$

We introduce a dual variable  $\nu$ , to bound the quadratic term. The problem is modeled by the following.

$$\begin{aligned} \mathcal{L}_\rho(x, \mu, \nu, \lambda, \eta) = & c^T x + \\ & \frac{\rho}{2} \sum_{i=1}^m \|P_{\mathcal{K}_i}(\frac{\mu_i}{\rho} - A_i x - b_i)\|^2 + \\ & \frac{\rho}{2} \sum_{j=1}^q \|x^T J_j x - r_j^T x + \frac{\nu_j}{\rho}\|^2 + \\ & \frac{\rho}{2} \|Gx - h + \frac{\lambda}{\rho}\|^2 + \\ & \frac{\rho}{2} \|\max[Px - q + \frac{\eta}{\rho}, 0]\|^2 \end{aligned} \quad (29)$$

$$\begin{aligned} \nabla \mathcal{L}_\rho(x, \mu, \nu, \lambda, \eta) = & c - \rho \sum_{i=1}^m A_i^T P_{\mathcal{K}_i}(\frac{\mu_i}{\rho} - A_i x - b_i) + \\ & \rho \sum_{j=1}^q (x^T J_j - r_j^T + \frac{\nu_j}{\rho}) [(J_j^T + J_j)x - r_j] + \\ & \rho G^T (Gx - h + \frac{\lambda}{\rho}) + \\ & \rho P^T \{\max[Px - q + \frac{\eta}{\rho}, 0]\} \end{aligned} \quad (30)$$

In case  $J$  is symmetric,  $J^T + J = 2J$ .

$$\begin{aligned} x & \leftarrow \arg \min_x \mathcal{L}_\rho(x, \mu, \nu, \lambda, \eta) \\ \mu_i & \leftarrow P_{\mathcal{K}_i}(\mu_i - \rho(A_i x + b_i)) \\ \nu_j & \leftarrow \nu_j + \rho(x^T J_j x - r_j^T x) \\ \lambda & \leftarrow \lambda + \rho(Gx - h) \\ \eta & \leftarrow \max[\eta + \rho(Px - q), 0] \\ \rho & \leftarrow \min[(1 + \gamma)\rho, \beta] \end{aligned} \quad (31)$$

Till now, we obtain all the math tools to solve our problem.

## REFERENCES

- [1] D. C. Liu and J. Nocedal, "On the limited memory BFGS method for large scale optimization," *Mathematical Programming*, vol. 45, no. 1-3, pp. 503-528, Aug. 1989, doi: 10.1007/BF01589116.
- [2] D. Verscheure, B. Demeulenaere, J. Swevers, J. De Schutter, and M. Diehl, "Time-Optimal Path Tracking for Robots: A Convex Optimization Approach," *IEEE Trans. Automat. Contr.*, vol. 54, no. 10, pp. 2318-2327, Oct. 2009, doi: 10.1109/TAC.2009.2028959.
- [3] D.-H. Li and M. Fukushima, "On the Global Convergence of the BFGS Method for Nonconvex Unconstrained Optimization Problems," *SIAM J. Optim.*, vol. 11, no. 4, pp. 1054-1064, Jan. 2001, doi: 10.1137/S1052623499354242.
- [4] F. Alizadeh and D. Goldfarb, "Second-order cone programming," *Mathematical Programming*, vol. 95, no. 1, pp. 3-51, Jan. 2003, doi: 10.1007/s10107-002-0339-5.
- [5] F.-G. Declan, "A Dive into WPILib Trajectories," Dec. 2019. [Online]. Available: <https://pietroglyph.github.io/trajectory-presentation>
- [6] G. Blekherman, P. A. Parrilo, and R. R. Thomas, Eds., *Semidefinite Optimization and Convex Algebraic Geometry*. Philadelphia, PA: Society for Industrial and Applied Mathematics, 2012. doi: 10.1137/1.9781611972290.
- [7] J. Russell, T. Bottiglieri, and A. Schuh, "Motion Planning and Control in FRC," May 2015.
- [8] J. Ji, X. Zhou, C. Xu, and F. Gao, "CMPCC: Corridor-Based Model Predictive Contouring Control for Aggressive Drone Flight," in *Experimental Robotics*, B. Siciliano, C. Laschi, and O. Khatib, Eds., Cham: Springer International Publishing, 2021, pp. 37-46.
- [9] L. Dong, Z. He, C. Song, and C. Sun, "A review of mobile robot motion planning methods: from classical motion planning workflows to reinforcement learning-based architectures," *Journal of Systems Engineering and Electronics*, vol. 34, no. 2, pp. 439-459, 2023, doi: 10.23919/JSEE.2023.000051.
- [10] Mechanical Advantage, Robot Code 2023. (2023). [Online]. Available: <https://github.com/Mechanical-Advantage/RobotCode2023>
- [11] R. E. Banchs, "Natural Quartic Spline," presented at the Research progress report #07 on Time Harmonic Field Electric Logging, The University of Texas at Austin, 1996.
- [12] R. H. Bartels, J. C. Beatty, and B. A. Barsky, *An introduction to splines for use in computer graphics and geometric modeling*. San Francisco, CA, USA: Morgan Kaufmann Publishers Inc., 1987.
- [13] R. M. Freund, "Introduction to Semidefinite Programming (SDP)".
- [14] R. Madani, M. Ashraphijuo, M. Kheirandishfard, and A. Atamturk, "Parabolic Relaxation for Quadratically-constrained Quadratic Programming - Part I: Definitions & Basic Properties," Aug. 07, 2022, arXiv: arXiv:2208.03622. doi: 10.48550/arXiv.2208.03622.
- [15] T. Kunz and M. Stilman, "Time-Optimal Trajectory Generation for Path Following with Bounded Acceleration and Velocity".
- [16] W. Zhepei, LBFSGS-Lite. (2021). [Online]. Available: <https://github.com/ZJU-FAST-Lab/LBFSGS-Lite>
- [17] X. Zhou, Z. Wang, H. Ye, C. Xu, and F. Gao, "EGO-Planner: An ESDF-Free Gradient-Based Local Planner for Quadrotors," *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 478-485, 2021, doi: 10.1109/LRA.2020.3047728.
- [18] Y. Wu, Z. Ding, C. Xu, and F. Gao, "External Forces Resilient Safe Motion Planning for Quadrotor," *IEEE Robotics and Automation Letters*, vol. 6, no. 4, pp. 8506-8513, 2021, doi: 10.1109/LRA.2021.3110316.
- [19] Z. Zirui, CoTiMo. (2024). [Online]. Available: <https://github.com/zhangzrjerry/cotimo>
- [20] Z. Zirui, FRC Auto Driver. (2022). [Online]. Available: [https://github.com/ZhangzrJerry/FRC\\_AutoDriver](https://github.com/ZhangzrJerry/FRC_AutoDriver)
- [21] Z. Zirui and P. Yue, FRC Scouting. (2022). [Online]. Available: [https://github.com/frc8811/FRC\\_SCOUTING](https://github.com/frc8811/FRC_SCOUTING)