

```
<style>
body, table, th, td, p, li, h1, h2, h3, h4, h5, h6, code, pre {
font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
}
</style>
```

Asset Management System - API Documentation

Version: 2.3
Last Updated: June 13, 2026
Base URL: /api

Quick Reference - All Endpoints

Authentication Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/auth/register	Register new user	Admin
POST	/api/auth/login	User login	No
POST	/api/auth/logout	User logout	Yes
POST	/api/auth/refresh-token	Refresh access token	Refresh Token
GET	/api/auth/roles	Get all user roles	Yes
PUT	/api/auth/update-user/:id	Update user	Yes

Asset Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/assets/	Get all assets	Admin, Standard User
GET	/api/assets/:id	Get asset by ID	Admin, Standard User
GET	/api/assets/search	Search assets	Admin, Standard User
GET	/api/assets/statuses/list	Get status list	Admin, Standard User
POST	/api/assets/	Create asset	Admin
PUT	/api/assets/:id	Update asset	Admin
DELETE	/api/assets/:id	Delete asset	Admin

Asset Type Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/asset-types/create	Create asset type	Admin
GET	/api/asset-types	Get all asset types	Yes
GET	/api/asset-types/:id	Get asset type by ID	Yes
PUT	/api/asset-types/:id	Update asset type	Admin
DELETE	/api/asset-types/:id	Delete asset type	Admin
POST	/api/assets/asset-types/create	Create asset type (alt)	Admin
GET	/api/assets/asset-types/all	Get all asset types (alt)	Yes

Asset Status Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/assets/asset-statuses/create	Create status	Admin, Super Admin
GET	/api/assets/asset-statuses/all	Get all statuses	Yes
GET	/api/assets/asset-statuses/:id	Get status by ID	Yes
PUT	/api/assets/asset-statuses/:id	Update status	Admin, Super Admin
DELETE	/api/assets/asset-statuses/:id	Delete status	Admin, Super Admin

Asset Attachment Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/asset-attachments/:assetId/attachments	Upload attachment	Admin, Standard User
GET	/api/asset-attachments/:assetId/attachments	Get attachments	Admin, Standard User
DELETE	/api/asset-attachments/attachments/:id	Delete attachment	Admin

Assignment Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/assignments/	Assign asset	Admin
GET	/api/assignments/:id	Get assignment by ID	Admin, Standard User
PUT	/api/assignments/:id/return	Return asset	Admin
GET	/api/assignments/asset/:assetId/history	Get asset history	Yes

Assignment Attachment Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/assignment-attachments/:assignmentId/attachments	Upload attachment	Admin, Standard User
GET	/api/assignment-attachments/:assignmentId/attachments	Get attachments	Admin, Standard User
DELETE	/api/assignment-attachments/attachments/:id	Delete attachment	Admin

Employee Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/employees/:id	Get employee by ID	Yes
GET	/api/employees/:employeeId/assets	Get employee assets	Yes

Expense Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/expenses/:id	Get expense by ID	Yes
POST	/api/expenses/	Add expense	Admin
PUT	/api/expenses/:id	Update expense	Admin
DELETE	/api/expenses/:id	Delete expense	Admin

Expense Type Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/expenses/expense-types/create	Create expense type	Admin
GET	/api/expenses/expense-types/all	Get all expense types	Yes
GET	/api/expenses/expense-types/:id	Get expense type by ID	Yes
PUT	/api/expenses/expense-types/:id	Update expense type	Admin
DELETE	/api/expenses/expense-types/:id	Delete expense type	Admin

Expense Attachment Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/expense-attachments/:expenseId/attachments	Upload attachment	Admin, Standard User
GET	/api/expense-attachments/:expenseId/attachments	Get attachments	Admin, Standard User
DELETE	/api/expense-attachments/attachments/:id	Delete attachment	Admin

Department Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/departments/	Get all departments	No
GET	/api/departments/:id	Get department by ID	No
POST	/api/departments/	Create department	Admin
PUT	/api/departments/:id	Update department	Admin
DELETE	/api/departments/:id	Delete department	Admin

Branch Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/branches/	Get all branches	No
GET	/api/branches/:id	Get branch by ID	No
POST	/api/branches/	Create branch	No
PUT	/api/branches/:id	Update branch	No
DELETE	/api/branches/:id	Delete branch	No

User Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/users/:id	Get user by ID	Yes
PUT	/api/users/profile	Update profile	Yes
POST	/api/users/change-password	Change password	Yes
POST	/api/users/reset-password/:id	Reset password	Yes
POST	/api/users/toggle-status/:id	Toggle user status	Yes

Report Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/reports/assets	Get filtered assets report	Yes
GET	/api/reports/assets/all	Get all assets report	Yes
GET	/api/reports/assets/assignments	Get assets assignments	Yes
GET	/api/reports/assets/export	Export assets to Excel	Yes
GET	/api/reports/assets/employee/:employeeId	Get assets by employee	Yes
GET	/api/reports/assets/branch/:location	Get assets by branch	Yes
GET	/api/reports/expenses	Get expenses report	Yes
GET	/api/reports/expenses/all	Get all expenses	Yes
GET	/api/reports/expenses/export	Export expenses to Excel	Yes
GET	/api/reports/expenses/time-period	Get expenses by period	Admin
GET	/api/reports/assignments	Get assignments report	Yes
GET	/api/reports/assignments/export	Export assignments to Excel	Yes
GET	/api/reports/action-logs	Get action logs report	Yes
GET	/api/reports/action-logs/export	Export action logs to Excel	Yes

Repair Request Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/repair-requests/	Get all repair requests	Yes
GET	/api/repair-requests/:id	Get repair request by ID	Yes
POST	/api/repair-requests/	Create repair request	Yes
PUT	/api/repair-requests/:id	Update repair request	Yes
DELETE	/api/repair-requests/:id	Delete repair request	Admin
POST	/api/repair-requests/:id/workflow/:action	Execute workflow action	Yes
GET	/api/repair-requests/:id/history	Get request history	Yes
GET	/api/repair-requests/stats	Get repair statistics	Yes

Repair Request Configuration Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/repair-requests/types	Get repair types	Yes
POST	/api/repair-requests/types	Create repair type	Admin
PUT	/api/repair-requests/types/:id	Update repair type	Admin
DELETE	/api/repair-requests/types/:id	Delete repair type	Admin
GET	/api/repair-requests/priorities	Get priorities	Yes
POST	/api/repair-requests/priorities	Create priority	Admin
PUT	/api/repair-requests/priorities/:id	Update priority	Admin
DELETE	/api/repair-requests/priorities/:id	Delete priority	Admin
GET	/api/repair-requests/statuses	Get statuses	Yes
POST	/api/repair-requests/statuses	Create status	Admin
PUT	/api/repair-requests/statuses/:id	Update status	Admin
DELETE	/api/repair-requests/statuses/:id	Delete status	Admin

Repair Workflow Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/repair-requests/workflow/stages	Get workflow stages	Yes
POST	/api/repair-requests/workflow/stages	Create workflow stage	Admin
PUT	/api/repair-requests/workflow/stages/:id	Update workflow stage	Admin
DELETE	/api/repair-requests/workflow/stages/:id	Delete workflow stage	Admin
GET	/api/repair-requests/workflow/permissions	Get workflow permissions	Admin
POST	/api/repair-requests/workflow/permissions	Set workflow permissions	Admin

Bulk Upload Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/upload/assets	Bulk upload assets	Admin

Bulk User Import Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/bulk-user-import/upload	Upload user import file	Admin
GET	/api/bulk-user-import/history	Get import history	Admin
GET	/api/bulk-user-import/:batchId	Get batch details	Admin
GET	/api/bulk-user-import/:batchId/users	Get imported users	Admin
POST	/api/bulk-user-import/:batchId/resend-password/:userId	Resend password	Admin

Role Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/roles/	Get all roles	Yes
GET	/api/roles/:id	Get role by ID	Yes
POST	/api/roles/	Create role	Admin
PUT	/api/roles/:id	Update role	Admin
DELETE	/api/roles/:id	Delete role	Admin
PATCH	/api/roles/:id/toggle	Toggle role active status	Admin

Permission Module Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/permissions/modules	Get all modules	Yes
GET	/api/permissions/modules/:id	Get module by ID	Yes
POST	/api/permissions/modules	Create module	Admin
PUT	/api/permissions/modules/:id	Update module	Admin
DELETE	/api/permissions/modules/:id	Delete module	Admin
PATCH	/api/permissions/modules/:id/toggle	Toggle module active status	Admin

Permission Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/permissions/	Get all permissions	Yes
GET	/api/permissions/by-module/:moduleId	Get permissions by module	Yes
POST	/api/permissions/	Create permission	Admin
POST	/api/permissions/bulk/:moduleId	Bulk create permissions	Admin
PATCH	/api/permissions/:id/toggle	Toggle permission active status	Admin

Role Permission Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/permissions/my-permissions	Get current user permissions	Yes
GET	/api/permissions/roles/:roleId	Get role permissions	Yes
GET	/api/permissions/roles/:roleId/check	Check if role has permission	Yes
GET	/api/permissions/roles/:roleId/routes	Get role accessible routes	Yes
POST	/api/permissions/roles/:roleId	Assign permission to role	Admin
PUT	/api/permissions/roles/:roleId/bulk	Bulk assign role permissions	Admin
POST	/api/permissions/roles/:roleId/clone	Clone role permissions	Admin
DELETE	/api/permissions/roles/:roleId/:permissionId	Remove role permission	Admin

Company Access Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/permissions/roles/:roleId/company-access	Get role company access	Yes
PUT	/api/permissions/roles/:roleId/company-access	Update role company access	Admin
GET	/api/companies	Get all companies	Yes

System Configuration Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/system-config/	Get system config	Admin
GET	/api/system-config/public	Get public config	No
PUT	/api/system-config/	Update system config	Admin
POST	/api/system-config/upload-logo	Upload company logo	Admin

Table of Contents

1. [System Overview](#)
 2. [Application Architecture](#)
 3. [Folder Structure](#)
 4. [Database Structure](#)
 5. [Setup Guide](#)
 6. [Authentication](#)
 7. [Assets](#)
 8. [Asset Types](#)
 9. [Asset Statuses](#)
 10. [Asset Attachments](#)
 11. [Assignments](#)
 12. [Assignment Attachments](#)
 13. [Employees](#)
 14. [Expenses](#)
 15. [Expense Types](#)
 16. [Expense Attachments](#)
 17. [Departments](#)
 18. [Branches](#)
 19. [Users](#)
 20. [Roles](#)
 21. [Permissions](#)
 22. [Repair Requests](#)
 23. [Repair Workflow](#)
 24. [Reports](#)
 25. [Bulk Upload](#)
 26. [System Configuration](#)
-

System Overview

The Asset Management System is a comprehensive web-based application designed to manage organizational assets throughout their lifecycle. The system provides functionality for:


- **Asset Management:** Track, categorize, and manage all organizational assets
- **Assignment Tracking:** Assign assets to employees and track assignment history
- **Expense Management:** Record and track expenses related to assets (purchases, repairs, logistics)
- **Repair Request Workflow:** Multi-stage approval workflow for repair requests
- **Reporting:** Generate reports on assets, assignments, expenses, and action logs
- **User Management:** Role-based access control with configurable permissions
- **Permission Management:** Granular module-based permissions with company access control
- **Bulk Operations:** Import assets and users in bulk via Excel files
- **Attachments:** Upload and manage documents/files for assets, assignments, and expenses

Technology Stack

Component	Technology
Backend Runtime	Node.js
Language	TypeScript
Web Framework	Express.js
Database	PostgreSQL
Template Engine	EJS (Embedded JavaScript)
Authentication	JWT (JSON Web Tokens)
File Storage	Local Server / Firebase (configurable)
Process Manager	PM2 (ecosystem.config.js)

Application Architecture

The application follows a **layered MVC (Model-View-Controller) architecture** with service layer separation:



Request Flow

1. **Client Request** → HTTP request from browser or API client
2. **Middleware** → Authentication verification, logging, system config loading
3. **Routes** → Match URL pattern to appropriate controller
4. **Controller** → Validate input, call service methods, format response
5. **Service** → Execute business logic, call model methods
6. **Model** → Execute database queries, return raw data
7. **Response** → JSON for API or rendered EJS template for views

Folder Structure

```
asset-manager/
├── src/                # Source code directory
│   ├── app.ts         # Express application setup
│   ├── server.ts      # Server entry point
│   └── types.d.ts     # TypeScript type declarations
├── assets/            # Static assets
│   ├── css/           # Stylesheets
│   └── js/            # Client-side JavaScript
```

```

└─ config/                                # Configuration files
└─ database.ts                            # PostgreSQL connection config
└─ index.ts                               # Config exports
└─ jwt.ts                                 # JWT configuration

└─ controllers/                           # Request handlers
└─ asset.controller.ts                    # Asset CRUD operations
└─ assetAttachment.controller.ts          # Asset file attachments
└─ assetStatus.controller.ts              # Asset status management
└─ assetType.controller.ts                # Asset type management
└─ assignment.controller.ts               # Asset assignments
└─ assignmentAttachment.controller.ts
└─ auth.controller.ts                     # Authentication
└─ branch.controller.ts                   # Branch management
└─ bulkUpload.controller.ts               # Bulk asset upload
└─ bulkUserImport.controller.ts           # Bulk user import
└─ department.controller.ts               # Department management
└─ employee.controller.ts                 # Employee management
└─ expense.controller.ts                  # Expense tracking
└─ expenseAttachment.controller.ts
└─ expenseType.controller.ts              # Expense type management
└─ permission.controller.ts               # Permission management
└─ repairRequest.controller.ts             # Repair request handling
└─ repairRequestAttachment.controller.ts
└─ repairRequestPriority.controller.ts
└─ repairRequestStatus.controller.ts
└─ repairRequestType.controller.ts
└─ repairWorkflow.controller.ts           # Workflow management
└─ report.controller.ts                   # Report generation
└─ role.controller.ts                     # Role management
└─ systemConfiguration.controller.ts
└─ user.controller.ts                     # User management
└─ view.controller.ts                     # View rendering
└─ index.ts                               # Controller exports

└─ middlewares/                           # Express middlewares
└─ auth.middleware.ts                     # JWT authentication
└─ currentPath.middleware.ts
└─ errorHandler.ts                       # Global error handling
└─ logger.middleware.ts                   # Request logging
└─ systemConfig.middleware.ts
└─ index.ts

└─ models/                                # Database models
└─ asset.model.ts                         # Asset queries
└─ assetAttachment.model.ts
└─ assetReport.model.ts
└─ assetStatus.model.ts
└─ assetTagPrefix.model.ts
└─ assetType.model.ts
└─ assignment.model.ts
└─ assignmentAttachment.model.ts
└─ assignmentReport.model.ts
└─ branch.model.ts
└─ bulkUserImport.model.ts
└─ department.model.ts
└─ employee.model.ts
└─ expense.model.ts
└─ expenseAttachment.model.ts
└─ expenseReport.model.ts
└─ expenseType.model.ts
└─ module.model.ts
└─ permission.model.ts
└─ rolePermission.model.ts
└─ actionLog.model.ts
└─ actionLogReport.model.ts
└─ lookup.model.ts
└─ refreshToken.model.ts
└─ repairRequest.model.ts

```

- └─ repairRequestAttachment.model.ts
- └─ repairRequestPriority.model.ts
- └─ repairRequestStatus.model.ts
- └─ repairRequestType.model.ts
- └─ repairWorkflow.model.ts
- └─ report.model.ts
- └─ role.model.ts
- └─ systemConfiguration.model.ts
- └─ user.model.ts
- └─ index.ts

- └─ routes/ # Route definitions
 - └─ asset.routes.ts # /api/assets/*
 - └─ assetAttachment.routes.ts
 - └─ assetType.routes.ts # /api/asset-types/*
 - └─ assignment.routes.ts # /api/assignments/*
 - └─ assignmentAttachment.routes.ts
 - └─ auth.routes.ts # /api/auth/*
 - └─ branches.routes.ts # /api/branches/*
 - └─ bulkUserImport.routes.ts
 - └─ departments.routes.ts # /api/departments/*
 - └─ employee.routes.ts # /api/employees/*
 - └─ expense.routes.ts # /api/expenses/*
 - └─ expenseAttachment.routes.ts
 - └─ permission.routes.ts # /api/permissions/*
 - └─ repairRequest.routes.ts
 - └─ report.routes.ts # /api/reports/*
 - └─ role.routes.ts # /api/roles/*
 - └─ systemConfiguration.routes.ts
 - └─ upload.routes.ts # /api/upload/*
 - └─ user.routes.ts # /api/users/*
 - └─ views.routes.ts # View routes
 - └─ main.routes.ts
 - └─ index.ts


- └─ services/ # Business logic
 - └─ actionLog.service.ts
 - └─ asset.service.ts
 - └─ assetAttachment.service.ts
 - └─ assetStatus.service.ts
 - └─ assetType.service.ts
 - └─ assignment.service.ts
 - └─ assignmentAttachment.service.ts
 - └─ auth.service.ts
 - └─ branch.service.ts
 - └─ bulkUpload.service.ts
 - └─ bulkUserImport.service.ts
 - └─ department.service.ts
 - └─ email.service.ts # Email notifications
 - └─ employee.service.ts
 - └─ expense.service.ts
 - └─ expenseAttachment.service.ts
 - └─ expenseType.service.ts
 - └─ lookup.service.ts
 - └─ module.service.ts # Module management
 - └─ permission.service.ts # Permission management
 - └─ rolePermission.service.ts # Role permission management
 - └─ repairRequest.service.ts
 - └─ repairRequestPriority.service.ts
 - └─ repairRequestStatus.service.ts
 - └─ repairRequestType.service.ts
 - └─ repairWorkflow.service.ts
 - └─ report.service.ts
 - └─ reportExport.service.ts
 - └─ role.service.ts
 - └─ sms.service.ts # SMS notifications
 - └─ systemConfiguration.service.ts
 - └─ user.service.ts
 - └─ index.ts

types/	# TypeScript type definitions
├─ index.ts	
└─ user.ts	
utils/	# Utility functions
├─ dateFormatter.ts	# Date formatting helpers
├─ logger.ts	# Logging utility
├─ response.ts	# Response formatting
├─ storage.ts	# File storage handling
└─ index.ts	
views/	# EJS templates
├─ partials/	# Reusable template parts
│ └─ header.ejs	
│ └─ footer.ejs	
│ └─ navbar.ejs	
│ └─ sidebar.ejs	
│ └─ attachments.ejs	
│ └─ asset-assignments.ejs	
├─ login.ejs	
├─ dashboard.ejs	
├─ view-assets.ejs	
├─ create-assets.ejs	
├─ assign-assets.ejs	
├─ create-expenses.ejs	
├─ repair-requests.ejs	
├─ manage-*.ejs	# Management pages
├─ *-report.ejs	# Report pages
└─ 404.ejs	
uploads/	# File upload directory
├─ assets/	# Asset attachments
├─ assignments/	# Assignment attachments
├─ expenses/	# Expense attachments
├─ logos/	# Company logos
└─ repair-requests/	# Repair request attachments
db_backup/	# Database backup files
└─ *.sql	# SQL backup/restore scripts
logs/	# Application logs
package.json	# NPM dependencies
tsconfig.json	# TypeScript configuration
ecosystem.config.js	# PM2 process configuration
API_DOCUMENTATION.md	# This documentation file
README.md	# Project readme

Database Structure

The system uses **PostgreSQL** as its database with 27 tables organized into functional groups.

Entity Relationship Overview



Database Tables

User & Authentication Tables

Table	Description	Key Columns
users	System users with login credentials	id, email, password, role_id, employee_id, is_active
employees	Employee records	id, first_name, last_name, department_id, branch_id, company
roles	User roles (Admin, Standard User)	id, name, description, is_active
refresh_tokens	JWT refresh token storage	id, token, user_id, expires_at
session	Express session storage	sid, sess, expire

Asset Management Tables

Table	Description	Key Columns
assets	Core asset records	id, asset_tag, asset_type_id, asset_status_id, serial_number, purchase_price
asset_types	Asset categories	id, name, description
asset_statuses	Asset availability states	id, name, is_available, description
asset_tag_prefixes	Auto-generate asset tags	id, asset_type_id, prefix, last_sequence
asset_attachments	Files attached to assets	id, asset_id, file_name, file_path, storage_type

Assignment Tables

Table	Description	Key Columns
assignments	Asset-to-employee assignments	id, asset_id, employee_id, assignment_date, return_date
assignment_attachments	Assignment documentation	id, assignment_id, file_name, file_path

Expense Tables

Table	Description	Key Columns
expenses	Asset-related expenses	id, asset_id, expense_type_id, amount, vendor, date
expense_types	Expense categories	id, name, description
expense_attachments	Expense receipts/invoices	id, expense_id, file_name, file_path

Repair Request Tables

Table	Description	Key Columns
repair_requests	Main repair request records	id, request_number, asset_id, status_id, priority_id, title, description
repair_request_statuses	Workflow statuses	id, name, color_code, is_terminal
repair_request_priorities	Priority levels	id, name, color_code, display_order
repair_request_types	Repair categories	id, name, description
repair_request_history	Audit trail	id, repair_request_id, action_type, from_status_id, to_status_id
repair_request_attachments	Repair documentation	id, repair_request_id, attachment_type, file_path
repair_workflow_stages	Workflow configuration	id, stage_key, from_status_id, to_status_id, action_type
repair_workflow_permissions	Role-based workflow access	id, workflow_stage_id, role_id, can_execute

Organization Tables

Table	Description	Key Columns
-------	-------------	-------------

branches	Office locations	id, name, location
departments	Organizational departments	id, name
companies	Company entities	id, name, is_active

Permission Tables

Table	Description	Key Columns
modules	Permission modules/functional areas	id, name, code, description, parent_id, icon, route, display_order, is_active
permissions	Individual permissions	id, module_id, action, description, is_active
role_permissions	Role-permission assignments	id, role_id, permission_id, branch_level_access
role_company_access	Company access per role	id, role_id, company_id

System Tables

Table	Description	Key Columns
system_configuration	App settings, storage config, SMTP	id, app_name, storage_type, smtp_*
action_logs	User activity audit trail	id, user_id, action_type, entity_type, details
bulk_user_imports	Bulk import batch records	id, batch_id, imported_by, total_records
bulk_imported_users	Individual import records	id, bulk_import_id, user_id, auto_generated_password

Database Views

View	Description
repair_request_stats	Aggregated repair request statistics

Database Functions & Triggers

Function	Description
generate_repair_request_number()	Auto-generates REQ-001, REQ-002 format
update_repair_request_timestamp()	Updates timestamp on record modification

Key Relationships

- users → employees (1:1) - Each user is linked to an employee record
- users → roles (N:1) - Each user has one role
- roles → role_permissions (1:N) - Each role can have multiple permissions
- permissions → modules (N:1) - Each permission belongs to a module
- role_permissions → permissions (N:1) - Links roles to permissions
- assets → asset_types (N:1) - Each asset has one type
- assets → asset_statuses (N:1) - Each asset has one status
- assignments → assets (N:1) - Assets can be assigned multiple times
- assignments → employees (N:1) - Employees can have multiple assignments
- expenses → assets (N:1) - Assets can have multiple expenses
- repair_requests → assets (N:1) - Assets can have multiple repair requests
- repair_requests → repair_request_statuses (N:1) - Each request has one status

Default Data

The system includes pre-configured lookup data:

Asset Statuses: In Use, Under Repair, In Stock, Disposed

Asset Types: Laptop, Router, Printer, Projector

Expense Types: Purchase, Repair, Logistics

Repair Priorities: Low, Medium, High, Critical

Repair Statuses: Pending, ICT Approved, ICT Rejected, In Repair, Awaiting Invoice, Invoice Submitted, Finance Approved, Finance Rejected, Completed, Cancelled

Permission Actions: view, create, edit, delete, export, import, approve

Roles: Admin (full access), Standard User (limited access)

Authentication

Register User

Endpoint: POST /api/auth/register

Authorization: Required (Admin)

Description: Register a new user in the system

Request Body:

```
{
  "first_name": "Caleb",
  "middle_name": "Kiprop",
  "last_name": "Kiprono",
  "email": "caleb.kiprono@freestylecodetechnologies.com",
  "password": "securePassword123",
  "phone": "+254712345678",
  "role_id": 2,
  "department_id": 1,
  "department": "Information Technology",
  "branch_id": 1,
  "branch_location": "Nairobi"
}
```

Success Response:

```
{
  "success": true,
  "message": "User registered successfully",
  "data": {
    "id": 2,
    "employee_id": 2,
    "first_name": "Caleb",
    "middle_name": "Kiprop",
    "last_name": "Kiprono",
    "email": "caleb.kiprono@freestylecodetechnologies.com",
    "phone": "+254712345678",
    "company_id": null
  }
}
```

Note: This endpoint creates both an employee record and a user account in a single transaction.

Login

Endpoint: POST /api/auth/login

Authorization: None

Description: Authenticate user and receive access tokens

Request Body:

```
{
  "email": "fredrick.mbugua@freestylecodetechnologies.com",
  "password": "securePassword123"
}
```

Success Response:

```
{
  "success": true,
  "message": "Logged in successfully",
  "data": {
    "user": {
      "id": 1,
      "employee_id": 1,
      "first_name": "Fredrick",
      "middle_name": "Mwangi",
      "last_name": "Mbugua",
      "email": "fredrick.mbugua@freestylecodetechnologies.com",
      "password": "$2a$10$pvN0OKHi7HAFYAoid6F3.e9ag3r57KvmPL/tezhi6zubmPPAlFp.C",
      "role_id": 1,
      "department_id": 1,
      "phone": "+254793577021",
      "branch_id": 1,
      "is_active": true,
      "role": "Admin"
    },
    "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "returnTo": "/dashboard"
  }
}
```

Note: The password field in the response contains the hashed password. For security, this should not be exposed in production environments.

Cookies Set:

- accessToken - HTTP-only, 30 minutes expiry
- refreshToken - HTTP-only, 7 days expiry

Refresh Token

Endpoint: POST /api/auth/refresh-token

Authorization: Refresh token in cookies

Description: Refresh the access token using refresh token

Success Response:

```
{
  "success": true,
  "message": "Token refreshed successfully"
}
```

Logout

Endpoint: POST /api/auth/logout

Authorization: Required

Description: Logout user and clear authentication cookies

Success Response:

```
{
  "success": true,
  "message": "Logged out successfully"
}
```

Get All User Roles

Endpoint: GET /api/auth/roles

Authorization: Required

Description: Retrieve all available user roles

Success Response:

```
{
  "success": true,
  "message": "All user roles fetched successfully",
  "data": {
    "roles": [
      {
        "id": 1,
        "name": "Admin",
        "description": "Full system access",
        "is_active": true,
        "created_at": "2025-01-01T10:00:00.000Z",
        "updated_at": "2025-01-01T10:00:00.000Z"
      },
      {
        "id": 2,
        "name": "Standard User",
        "description": "Limited access to view and basic operations",
        "is_active": true,
        "created_at": "2025-01-01T10:00:00.000Z",
        "updated_at": "2025-01-01T10:00:00.000Z"
      }
    ]
  }
}
```

Update User

Endpoint: PUT /api/auth/update-user/:id

Authorization: Required

Description: Update user information

URL Parameters:

- id - User ID

Request Body:

```
{
  "email": "newemail@freestylecodetechnologies.com",
  "first_name": "Jane",
  "last_name": "Smith",
  "role_id": 2
}
```

Assets

Get All Assets

Endpoint: GET /api/assets/

Authorization: Required (Admin, Standard User)

Description: Retrieve all assets in the system

Success Response:

```
{
  "success": true,
  "message": "Assets retrieved successfully",
  "data": {
    "assets": [
      {
        "id": 1,
        "asset_tag": "ASSET-001",
        "asset_type": "Laptop",
        "manufacturer": "Dell",
        "model": "Latitude 5420",
        "serial_number": "SN123456",
        "status": "In Use",
        "purchase_date": "2025-01-01",
        "purchase_price": 120000.00,
        "notes": "Assigned to IT department",
        "type_name": "Computer Equipment",
        "status_name": "In Use",
        "location": "Nairobi"
      }
    ],
    "total": 150,
    "page": 1,
    "itemsPerPage": 20,
    "totalPages": 8
  }
}
```

Get Asset By ID

Endpoint: GET /api/assets/:id

Authorization: Required (Admin, Standard User)

Description: Retrieve a specific asset by ID

URL Parameters:

- id - Asset ID

Success Response:

```
{
  "success": true,
  "message": "Asset retrieved successfully",
  "data": {
    "id": 1,
    "asset_tag": "ASSET-001",
    "asset_type": "Laptop",
    "manufacturer": "Dell",
    "model": "Latitude 5420",
    "serial_number": "SN12345678",
    "status": "In Use",
    "purchase_date": "2025-01-01",
    "purchase_price": 1200.00,
    "notes": "Assigned to IT department",
    "asset_type_id": 1,
    "asset_status_id": 1,
    "branch_id": 1,
    "type_name": "Computer Equipment",
    "status_name": "In Use",
    "branch_name": "Head Office",
    "location": "Nairobi"
  }
}
```

Search Assets

Endpoint: GET /api/assets/search

Authorization: Required (Admin, Standard User)

Description: Search assets with query parameters

Query Parameters:

- asset_tag - Asset tag (partial match)
- asset_name - Asset name (partial match)
- status_id - Status ID
- asset_type_id - Asset type ID
- branch_id - Branch ID
- department_id - Department ID

Example: GET /api/assets/search?asset_name=laptop&status_id=1

Get Asset Statuses List

Endpoint: GET /api/assets/statuses/list

Authorization: Required (Admin, Standard User)

Description: Get list of all asset statuses

Success Response:

```
{
  "success": true,
  "message": "Assets statuses retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "In Stock",
      "is_available": true,
      "description": "Asset is available for assignment"
    },
    {
      "id": 2,
      "name": "In Use",
      "is_available": false,
      "description": "Asset is currently assigned"
    },
    {
      "id": 3,
      "name": "Under Repair",
      "is_available": false,
      "description": "Asset is being repaired"
    },
    {
      "id": 4,
      "name": "Disposed",
      "is_available": false,
      "description": "Asset has been disposed"
    }
  ]
}
```

Create Asset

Endpoint: POST /api/assets/

Authorization: Required (Admin)

Description: Create a new asset

Request Body:


```
{
  "asset_tag": "ASSET-002",
  "asset_type": "Laptop",
  "manufacturer": "HP",
  "model": "EliteBook 840",
  "serial_number": "HP98765432",
  "status": "In Stock",
  "purchase_date": "2025-01-05",
  "purchase_price": 150000.00,
  "notes": "New HP laptop for development team",
  "asset_type_id": 1,
  "asset_status_id": 1,
  "branch_id": 1
}
```

Success Response:

```
{
  "success": true,
  "message": "Asset created successfully",
  "data": {
    "id": 2,
    "asset_tag": "ASSET-002",
    "asset_type": "Laptop",
    "manufacturer": "HP",
    "model": "EliteBook 840",
    "serial_number": "HP98765432",
    "status": "In Stock",
    "purchase_date": "2025-01-05",
    "purchase_price": 150000.00,
    "notes": "New HP laptop for development team",
    "asset_type_id": 1,
    "asset_status_id": 1,
    "branch_id": 1
  }
}
```

Update Asset

Endpoint: PUT /api/assets/:id

Authorization: Required (Admin)

Description: Update an existing asset

URL Parameters:

- id - Asset ID

Request Body: Same as Create Asset

Delete Asset

Endpoint: DELETE /api/assets/:id

Authorization: Required (Admin)

Description: Delete an asset

URL Parameters:

- id - Asset ID

Success Response:

```
{
  "success": true,
  "message": "Asset deleted successfully"
}
```

Asset Types

Create Asset Type

Endpoint: POST /api/asset-types/create or POST /api/assets/asset-types/create

Authorization: Required (Admin)

Description: Create a new asset type

Request Body:

```
{
  "name": "Office Furniture",
  "description": "Desks, chairs, and cabinets"
}
```

Success Response:

```
{
  "success": true,
  "message": "Asset type created successfully",
  "data": {
    "id": 5,
    "name": "Office Furniture",
    "description": "Desks, chairs, and cabinets",
    "created_at": "2025-01-05T10:00:00Z",
    "updated_at": "2025-01-05T10:00:00Z"
  }
}
```

Get All Asset Types

Endpoint: GET /api/asset-types or GET /api/assets/asset-types/all

Authorization: Required

Description: Retrieve all asset types

Success Response:

```
{
  "success": true,
  "message": "Asset types retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "Computer Equipment",
      "description": "Laptops, desktops, monitors",
      "created_at": "2025-01-01T10:00:00Z",
      "updated_at": "2025-01-01T10:00:00Z"
    }
  ]
}
```

Get Asset Type By ID

Endpoint: GET /api/asset-types/:id

Authorization: Required

Description: Retrieve a specific asset type with its details

URL Parameters:

- id - Asset type ID

Success Response:

```
{
  "success": true,
  "message": "Asset type retrieved successfully",
  "data": {
    "id": 1,
    "name": "Computer Equipment",
    "description": "Laptops, desktops, monitors, and peripherals",
    "created_at": "2025-01-01T10:00:00Z",
    "updated_at": "2025-01-01T10:00:00Z"
  }
}
```

Update Asset Type

Endpoint: PUT /api/asset-types/:id

Authorization: Required (Admin)

Description: Update an asset type

URL Parameters:

- id - Asset type ID

Request Body:

```
{
  "name": "Updated Type Name",
  "description": "Updated description"
}
```

Delete Asset Type

Endpoint: DELETE /api/asset-types/:id

Authorization: Required (Admin)

Description: Delete an asset type

URL Parameters:

- id - Asset type ID

Asset Statuses

Create Asset Status

Endpoint: POST /api/assets/asset-statuses/create

Authorization: Required (Admin, Super Admin)

Description: Create a new asset status

Request Body:

```
{
  "name": "Under Repair",
  "is_available": false,
  "description": "Asset is being repaired"
}
```

Success Response:

```
{
  "success": true,
  "message": "Asset status created successfully",
  "data": {
    "id": 5,
    "name": "Under Repair",
    "is_available": false,
    "description": "Asset is being repaired"
  }
}
```

Get All Asset Statuses

Endpoint: GET /api/assets/asset-statuses/all

Authorization: Required

Description: Retrieve all asset statuses

Get Asset Status By ID

Endpoint: GET /api/assets/asset-statuses/:id

Authorization: Required

Description: Retrieve a specific asset status with its details

URL Parameters:

- id - Asset status ID

Success Response:

```
{
  "success": true,
  "message": "Asset status retrieved successfully",
  "data": {
    "id": 1,
    "name": "In Stock",
    "is_available": true,
    "description": "Asset is available for assignment"
  }
}
```

Update Asset Status

Endpoint: PUT /api/assets/asset-statuses/:id

Authorization: Required (Admin, Super Admin)

Description: Update an asset status

URL Parameters:

- id - Asset status ID
-

Delete Asset Status

Endpoint: DELETE /api/assets/asset-statuses/:id

Authorization: Required (Admin, Super Admin)

Description: Delete an asset status

URL Parameters:

- id - Asset status ID
-

Asset Attachments

Upload Asset Attachment

Endpoint: POST /api/asset-attachments/:assetId/attachments

Authorization: Required (Admin, Standard User)

Description: Upload an attachment for an asset

Content-Type: multipart/form-data

URL Parameters:

- assetId - Asset ID

Form Data:

- file - File to upload (max 10MB)

Supported File Types:

- Documents: PDF, DOC, DOCX, XLS, XLSX
- Images: JPG, JPEG, PNG, GIF, BMP
- Archives: ZIP, RAR
- Text: TXT, CSV

Success Response:

```
{
  "success": true,
  "message": "Attachment uploaded successfully",
  "data": {
    "id": 1,
    "asset_id": 1,
    "file_name": "invoice.pdf",
    "file_path": "/uploads/assets/invoice.pdf",
    "file_size": 102400,
    "mime_type": "application/pdf",
    "uploaded_by": 5,
    "uploaded_at": "2026-01-08T10:30:00Z"
  }
}
```

Error Response (File Too Large):

```
{
  "success": false,
  "message": "File size exceeds maximum limit of 10MB"
}
```

Get Asset Attachments

Endpoint: GET /api/asset-attachments/:assetId/attachments

Authorization: Required (Admin, Standard User)

Description: Get all attachments for an asset

URL Parameters:

- `assetId` - Asset ID

Success Response:

```
{
  "success": true,
  "message": "Attachments retrieved successfully",
  "data": [
    {
      "id": 1,
      "asset_id": 1,
      "file_name": "invoice.pdf",
      "file_path": "/uploads/assets/invoice.pdf",
      "file_size": 102400,
      "uploaded_at": "2026-01-08T10:30:00Z"
    }
  ]
}
```

Delete Asset Attachment

Endpoint: DELETE /api/asset-attachments/attachments/:id

Authorization: Required (Admin)

Description: Delete an asset attachment

URL Parameters:

- `id` - Attachment ID

Success Response:

```
{
  "success": true,
  "message": "Attachment deleted successfully"
}
```

Error Response (Not Found):

```
{
  "success": false,
  "message": "Attachment not found"
}
```

Assignments

Assign Asset

Endpoint: POST /api/assignments/

Authorization: Required (Admin)

Description: Assign an asset to an employee

Request Body:

```
{
  "asset_id": 1,
  "employee_id": 5,
  "assigned_date": "2026-01-08",
  "notes": "Laptop for development work"
}
```

Success Response:

```
{
  "success": true,
  "message": "Asset assigned successfully",
  "data": {
    "id": 10,
    "asset_id": 1,
    "employee_id": 5,
    "assigned_date": "2026-01-08",
    "return_date": null,
    "notes": "Laptop for development work"
  }
}
```

Get Assignment By ID

Endpoint: GET /api/assignments/:id

Authorization: Required (Admin, Standard User)

Description: Retrieve assignment details

URL Parameters:

- id - Assignment ID

Return Asset

Endpoint: PUT /api/assignments/:id/return

Authorization: Required (Admin)

Description: Mark an asset as returned

URL Parameters:

- id - Assignment ID

Request Body:

```
{
  "return_date": "2026-01-08",
  "return_notes": "Asset returned in good condition"
}
```

Success Response:

```
{
  "success": true,
  "message": "Asset returned successfully",
  "data": {
    "id": 10,
    "asset_id": 1,
    "employee_id": 5,
    "assigned_date": "2026-01-01",
    "return_date": "2026-01-08",
    "return_notes": "Asset returned in good condition"
  }
}
```

Get Asset Assignment History

Endpoint: GET /api/assignments/asset/:assetId/history

Authorization: Required

Description: Get assignment history for a specific asset

URL Parameters:

- assetId - Asset ID

Success Response:

```
{
  "success": true,
  "message": "Asset history retrieved successfully",
  "data": [
    {
      "id": 10,
      "asset_id": 1,
      "asset_tag": "ASSET-001",
      "employee_id": 5,
      "first_name": "Caleb",
      "middle_name": null,
      "last_name": "Kiprono",
      "assigned_date": "2026-01-01",
      "return_date": "2026-01-08",
      "notes": "Laptop for development work"
    }
  ]
}
```

Assignment Attachments

Upload Assignment Attachment

Endpoint: POST /api/assignment-attachments/:assignmentId/attachments

Authorization: Required (Admin, Standard User)

Description: Upload an attachment for an assignment

Content-Type: multipart/form-data

URL Parameters:

- assignmentId - Assignment ID

Form Data:

- file - File to upload (max 10MB)

Success Response:

```
{
  "success": true,
  "message": "Attachment uploaded successfully",
  "data": {
    "id": 5,
    "assignment_id": 10,
    "file_name": "handover_form.pdf",
    "file_path": "/uploads/assignments/handover_form.pdf",
    "file_size": 85000,
    "mime_type": "application/pdf",
    "uploaded_by": 5,
    "uploaded_at": "2026-01-08T10:30:00Z"
  }
}
```

Get Assignment Attachments

Endpoint: GET /api/assignment-attachments/:assignmentId/attachments

Authorization: Required (Admin, Standard User)

Description: Get all attachments for an assignment

URL Parameters:

- assignmentId - Assignment ID

Success Response:

```
{
  "success": true,
  "message": "Attachments retrieved successfully",
  "data": [
    {
      "id": 5,
      "assignment_id": 10,
      "file_name": "handover_form.pdf",
      "file_path": "/uploads/assignments/handover_form.pdf",
      "file_size": 85000,
      "mime_type": "application/pdf",
      "uploaded_by": 5,
      "uploaded_at": "2026-01-08T10:30:00Z"
    }
  ]
}
```

Delete Assignment Attachment

Endpoint: DELETE /api/assignment-attachments/attachments/:id

Authorization: Required (Admin)

Description: Delete an assignment attachment

URL Parameters:

- id - Attachment ID

Success Response:

```
{
  "success": true,
  "message": "Attachment deleted successfully"
}
```

Employees

Get Employee By ID

Endpoint: GET /api/employees/:id

Authorization: Required

Description: Retrieve employee details including personal information and employment data

URL Parameters:

- id - Employee ID

Success Response:

```
{
  "success": true,
  "message": "Employee retrieved successfully",
  "data": {
    "id": 5,
    "first_name": "Caleb",
    "middle_name": null,
    "last_name": "Kiprono",
    "department_id": 1,
    "department": "IT",
    "branch_id": 1,
    "branch_location": "Head Office",
    "hire_date": "2024-06-01",
    "status": "Active"
  }
}
```

Error Response:

```
{
  "success": false,
  "message": "Employee not found"
}
```

Get Employee Assets

Endpoint: GET /api/employees/:employeeId/assets

Authorization: Required

Description: Get all assets assigned to an employee

URL Parameters:

- employeeId - Employee ID

Success Response:

```
{
  "success": true,
  "message": "Employee assets retrieved successfully",
  "data": [
    {
      "asset_id": 1,
      "asset_tag": "ASSET-001",
      "asset_name": "Dell Laptop",
      "assigned_date": "2026-01-01",
      "assignment_id": 10
    }
  ]
}
```

Expenses

Get Expense By ID

Endpoint: GET /api/expenses/:id

Authorization: Required

Description: Retrieve expense details

URL Parameters:

- id - Expense ID

Add Expense

Endpoint: POST /api/expenses/

Authorization: Required (Admin)

Description: Record a new expense

Request Body:

```
{
  "asset_id": 1,
  "expense_type_id": 2,
  "expense_date": "2026-01-08",
  "amount": 250.00,
  "description": "Screen replacement",
  "vendor": "Tech Repairs Inc"
}
```

Success Response:

```
{
  "success": true,
  "message": "Expense added successfully",
  "data": {
    "id": 15,
    "asset_id": 1,
    "expense_type_id": 2,
    "expense_date": "2026-01-08",
    "amount": 25000.00,
    "description": "Screen replacement",
    "vendor": "Nairobi Tech Solutions"
  }
}
```

Update Expense

Endpoint: PUT /api/expenses/:id

Authorization: Required (Admin)

Description: Update an existing expense record

URL Parameters:

- id - Expense ID

Request Body:

```
{
  "amount": 28000.00,
  "notes": "Updated Screen replacement including shipping costs"
}
```

Success Response:

```
{
  "success": true,
  "message": "Expense updated successfully",
  "data": {
    "id": 15,
    "asset_id": 1,
    "expense_type_id": 2,
    "expense_date": "2026-01-08",
    "amount": 28000.00,
    "notes": "Updated Screen replacement including shipping costs"
  }
}
```

Delete Expense

Endpoint: DELETE /api/expenses/:id

Authorization: Required (Admin)

Description: Delete an expense record. Clears referencing `repair_requests.expense_id` first to prevent foreign key violations.

URL Parameters:

- `id` - Expense ID

Success Response:

```
{
  "success": true,
  "message": "Expense deleted successfully."
}
```

Expense Types

Create Expense Type

Endpoint: POST /api/expenses/expense-types/create

Authorization: Required (Admin)

Description: Create a new expense type

Request Body:

```
{
  "name": "Upgrade",
  "description": "Hardware or software upgrades"
}
```

Get All Expense Types

Endpoint: GET /api/expenses/expense-types/all

Authorization: Required

Description: Retrieve all expense types

Get Expense Type By ID

Endpoint: GET /api/expenses/expense-types/:id

Authorization: Required

Description: Retrieve a specific expense type with its details

URL Parameters:

- `id` - Expense type ID

Success Response:

```
{
  "success": true,
  "message": "Expense type retrieved successfully",
  "data": {
    "id": 2,
    "name": "Repair",
    "description": "Maintenance and repair costs",
    "created_at": "2025-01-01T10:00:00Z",
    "updated_at": "2025-01-01T10:00:00Z"
  }
}
```

Update Expense Type

Endpoint: PUT /api/expenses/expense-types/:id

Authorization: Required (Admin)

Description: Update an expense type

URL Parameters:

- id - Expense type ID
-

Delete Expense Type

Endpoint: DELETE /api/expenses/expense-types/:id

Authorization: Required (Admin)

Description: Delete an expense type

URL Parameters:

- id - Expense type ID
-

Expense Attachments

Upload Expense Attachment

Endpoint: POST /api/expense-attachments/:expenseId/attachments

Authorization: Required (Admin, Standard User)

Description: Upload an attachment for an expense (e.g., receipt, invoice)

Content-Type: multipart/form-data

URL Parameters:

- expenseId - Expense ID

Form Data:

- file - File to upload (max 10MB)

Success Response:

```
{
  "success": true,
  "message": "Attachment uploaded successfully",
  "data": {
    "id": 8,
    "expense_id": 15,
    "file_name": "repair_receipt.jpg",
    "file_path": "/uploads/expenses/repair_receipt.jpg",
    "file_size": 245000,
    "mime_type": "image/jpeg",
    "uploaded_by": 5,
    "uploaded_at": "2026-01-08T10:30:00Z"
  }
}
```

Get Expense Attachments

Endpoint: GET /api/expense-attachments/:expenseId/attachments

Authorization: Required (Admin, Standard User)

Description: Get all attachments for an expense

URL Parameters:

- expenseId - Expense ID

Success Response:

```
{
  "success": true,
  "message": "Attachments retrieved successfully",
  "data": [
    {
      "id": 8,
      "expense_id": 15,
      "file_name": "repair_receipt.jpg",
      "file_path": "/uploads/expenses/repair_receipt.jpg",
      "file_size": 245000,
      "mime_type": "image/jpeg",
      "uploaded_by": 5,
      "uploaded_at": "2026-01-08T10:30:00Z"
    }
  ]
}
```

Delete Expense Attachment

Endpoint: DELETE /api/expense-attachments/attachments/:id

Authorization: Required (Admin)

Description: Delete an expense attachment

URL Parameters:

- id - Attachment ID

Success Response:

```
{
  "success": true,
  "message": "Attachment deleted successfully"
}
```

Departments

Get All Departments

Endpoint: GET /api/departments/

Authorization: None

Description: Retrieve all departments

Success Response:

```
{
  "success": true,
  "message": "Departments retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "IT",
      "created_at": "2025-01-01T10:00:00Z",
      "updated_at": "2025-01-01T10:00:00Z"
    }
  ]
}
```

Get Department By ID

Endpoint: GET /api/departments/:id

Authorization: None

Description: Retrieve a specific department with its details

URL Parameters:

- id - Department ID

Success Response:

```
{
  "success": true,
  "message": "Department retrieved successfully",
  "data": {
    "id": 1,
    "name": "IT",
    "created_at": "2025-01-01T10:00:00Z",
    "updated_at": "2025-01-01T10:00:00Z"
  }
}
```

Create Department

Endpoint: POST /api/departments/

Authorization: Required (Admin)

Description: Create a new department

Request Body:

```
{
  "name": "Marketing"
}
```

Update Department

Endpoint: PUT /api/departments/:id

Authorization: Required (Admin)

Description: Update a department's information

URL Parameters:

- id - Department ID

Request Body:

```
{
  "name": "Information Technology"
}
```

Success Response:

```
{
  "success": true,
  "message": "Department updated successfully",
  "data": {
    "id": 1,
    "name": "Information Technology",
    "created_at": "2025-01-01T10:00:00.000Z",
    "updated_at": "2025-01-15T14:30:00.000Z"
  }
}
```

Delete Department

Endpoint: DELETE /api/departments/:id

Authorization: Required (Admin)

Description: Delete a department (only if no employees are assigned)

URL Parameters:

- id - Department ID

Success Response:

```
{
  "success": true,
  "message": "Department deleted successfully"
}
```

Error Response (Has Dependencies):

```
{
  "success": false,
  "message": "Cannot delete department. It has assigned employees."
}
```

Branches

Get All Branches

Endpoint: GET /api/branches/

Authorization: None

Description: Retrieve all branches

Success Response:

```
{
  "success": true,
  "message": "Branches retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "Head Office",
      "location": "Nairobi",
      "created_at": "2025-01-15T10:30:00.000Z",
      "updated_at": "2025-01-15T10:30:00.000Z"
    },
    {
      "id": 2,
      "name": "Mombasa Branch",
      "location": "Mombasa",
      "created_at": "2025-01-15T10:30:00.000Z",
      "updated_at": "2025-01-15T10:30:00.000Z"
    }
  ]
}
```

Get Branch By ID

Endpoint: GET /api/branches/:id

Authorization: None

Description: Retrieve a specific branch

URL Parameters:

- id - Branch ID

Create Branch

Endpoint: POST /api/branches/

Authorization: None

Description: Create a new branch

Request Body:

```
{
  "name": "Eldoret Branch",
  "location": "Eldoret"
}
```

Success Response:

```
{
  "success": true,
  "message": "Branch created successfully",
  "data": {
    "id": 3,
    "name": "Eldoret Branch",
    "location": "Eldoret",
    "created_at": "2026-01-15T10:30:00.000Z",
    "updated_at": "2026-01-15T10:30:00.000Z"
  }
}
```

Update Branch

Endpoint: PUT /api/branches/:id

Authorization: None

Description: Update a branch's information

URL Parameters:

- id - Branch ID

Request Body:

```
{
  "name": "Mombasa Regional Office",
  "location": "Mombasa CBD"
}
```

Success Response:

```
{
  "success": true,
  "message": "Branch updated successfully",
  "data": {
    "id": 2,
    "name": "Mombasa Regional Office",
    "location": "Mombasa CBD",
    "created_at": "2025-01-15T10:30:00.000Z",
    "updated_at": "2025-01-20T14:45:00.000Z"
  }
}
```

Delete Branch

Endpoint: DELETE /api/branches/:id

Authorization: None

Description: Delete a branch (only if no assets or employees are assigned)

URL Parameters:

- id - Branch ID

Success Response:

```
{
  "success": true,
  "message": "Branch deleted successfully"
}
```

Error Response (Has Dependencies):

```
{
  "success": false,
  "message": "Cannot delete branch. It has assigned assets or employees."
}
```

Users

Get User By ID

Endpoint: GET /api/users/:id

Authorization: Required

Description: Retrieve user details including profile and role information

URL Parameters:

- id - User ID

Success Response:

```
{
  "success": true,
  "message": "User retrieved successfully",
  "data": {
    "id": 1,
    "employee_id": 1,
    "first_name": "Fredrick",
    "middle_name": "Mwangi",
    "last_name": "Mbugua",
    "email": "fredrick.mbugua@freestylecodetechnologies.com",
    "password": "$2a$10$pvN0OKHi7HafYAoid6F3.e9ag3r57KVmPL/tezhi6zubmPPAlFp.C",
    "role_id": 1,
    "department_id": 1,
    "phone": "+254793577021",
    "branch_id": 1,
    "is_active": true,
    "branch_name": "Head Office",
    "location": "Nairobi",
    "role_name": "Admin",
    "department_name": "Information Technology",
    "employee_first_name": "Fredrick",
    "employee_middle_name": "Mwangi",
    "employee_last_name": "Mbugua",
    "departmnt_id": 1,
    "company_id": 1,
    "company_name": "Jirani Smart Systems"
  }
}
```

Note: Response includes joined data from branches, roles, employees, departments, and companies tables.

Update User Profile

Endpoint: PUT /api/users/profile

Authorization: Required

Description: Update current user's profile information

Request Body:

```
{
  "first_name": "Benson",
  "last_name": "Wambua",
  "email": "benson.wambua@freestylecodetechnologies.com",
  "phone": "+254723456789"
}
```

Success Response:

```
{
  "success": true,
  "message": "Profile updated successfully",
  "data": {
    "id": 5,
    "email": "benson.wambua@freestylecodetechnologies.com",
    "first_name": "Benson",
    "last_name": "Wambua",
    "phone": "+254723456789"
  }
}
```

Error Response (Email Already Exists):

```
{
  "success": false,
  "message": "Email already in use"
}
```

Change Password

Endpoint: POST /api/users/change-password

Authorization: Required

Description: Change current user's password

Request Body:

```
{
  "current_password": "oldPassword123",
  "new_password": "newSecurePassword456",
  "confirm_password": "newSecurePassword456"
}
```

Success Response:

```
{
  "success": true,
  "message": "Password changed successfully"
}
```

Reset Password

Endpoint: POST /api/users/reset-password/:id

Authorization: Required (Admin)

Description: Reset a user's password (Admin function - used to set temporary password)

URL Parameters:

- id - User ID

Request Body:

```
{
  "password": "TempPassword@123"
}
```

Success Response:

```
{
  "success": true,
  "message": "Password reset successfully"
}
```

Note: User should be prompted to change this temporary password on next login.

Toggle User Status

Endpoint: POST /api/users/toggle-status/:id

Authorization: Required (Admin)

Description: Activate or deactivate a user account (prevents login when deactivated)

URL Parameters:

- id - User ID

Request Body:

```
{
  "is_active": false
}
```

Success Response:

```
{
  "success": true,
  "message": "User status updated successfully",
  "data": {
    "id": 8,
    "email": "user@freestylecodetechnologies.com",
    "is_active": false
  }
}
```

Note: Deactivated users cannot log in but their data is preserved in the system.

Roles

Get All Roles

Endpoint: GET /api/roles/

Authorization: Required

Description: Retrieve all roles in the system

Success Response:

```
{
  "success": true,
  "message": "Roles retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "Admin",
      "description": "Full system access",
      "is_active": true,
      "created_at": "2026-01-01T00:00:00Z",
      "updated_at": "2026-01-01T00:00:00Z"
    },
    {
      "id": 2,
      "name": "Standard User",
      "description": "Limited access for regular users",
      "is_active": true,
      "created_at": "2026-01-01T00:00:00Z",
      "updated_at": "2026-01-01T00:00:00Z"
    }
  ]
}
```

Get Role By ID

Endpoint: GET /api/roles/:id

Authorization: Required

Description: Retrieve a specific role by ID

URL Parameters:

- id - Role ID

Success Response:

```
{
  "success": true,
  "message": "Role retrieved successfully",
  "data": {
    "id": 1,
    "name": "Admin",
    "description": "Full system access",
    "is_active": true,
    "created_at": "2026-01-01T00:00:00Z",
    "updated_at": "2026-01-01T00:00:00Z"
  }
}
```

Create Role

Endpoint: POST /api/roles/

Authorization: Required (Admin)

Description: Create a new role

Request Body:

```
{
  "name": "Finance Manager",
  "description": "Access to finance and expense modules"
}
```

Success Response:

```
{
  "success": true,
  "message": "Role created successfully",
  "data": {
    "id": 3,
    "name": "Finance Manager",
    "description": "Access to finance and expense modules",
    "is_active": true,
    "created_at": "2026-01-24T10:00:00Z"
  }
}
```

Update Role

Endpoint: PUT /api/roles/:id

Authorization: Required (Admin)

Description: Update an existing role

URL Parameters:

- id - Role ID

Request Body:

```
{
  "name": "Finance Admin",
  "description": "Full access to finance and expense modules"
}
```

Success Response:

```
{
  "success": true,
  "message": "Role updated successfully",
  "data": {
    "id": 3,
    "name": "Finance Admin",
    "description": "Full access to finance and expense modules",
    "is_active": true,
    "updated_at": "2026-01-24T12:00:00Z"
  }
}
```

Delete Role

Endpoint: DELETE /api/roles/:id

Authorization: Required (Admin)

Description: Delete a role

URL Parameters:

- id - Role ID

Success Response:

```
{
  "success": true,
  "message": "Role deleted successfully"
}
```

Error Response (Role In Use):

```
{
  "success": false,
  "message": "Cannot delete role that is assigned to users"
}
```

Toggle Role Active Status

Endpoint: PATCH /api/roles/:id/toggle

Authorization: Required (Admin)

Description: Toggle the active status of a role

URL Parameters:

- id - Role ID


Success Response:

```
{
  "success": true,
  "message": "Role status toggled successfully",
  "data": {
    "id": 3,
    "name": "Finance Admin",
    "is_active": false
  }
}
```

Permissions

The permission system provides granular access control through modules and permissions. Each module represents a functional area (e.g., Assets, Expenses, Reports), and permissions define specific actions (View, Create, Edit, Delete) within those modules.

Permission Architecture



Module Endpoints

Get All Modules

Endpoint: GET /api/permissions/modules

Authorization: Required

Description: Retrieve all permission modules

Query Parameters:

- include_inactive - Include inactive modules (default: false)
- hierarchy - Return modules in hierarchical structure (default: false)

Success Response:

```
{
  "success": true,
  "message": "Modules retrieved successfully",
  "data": [
    {
      "id": 1,
      "name": "Assets",
      "code": "ASSETS",
      "description": "Asset management module",
      "icon": "fa-box",
      "route": "/assets",
      "display_order": 1,
      "is_active": true,
      "parent_id": null
    },
    {
      "id": 2,
      "name": "Expenses",
      "code": "EXPENSES",
      "description": "Expense tracking module",
      "icon": "fa-receipt",
      "route": "/expenses",
      "display_order": 2,
      "is_active": true,
      "parent_id": null
    }
  ]
}
```

Get Module By ID

Endpoint: GET /api/permissions/modules/:id

Authorization: Required

Description: Retrieve a specific module with its child modules

URL Parameters:

- id - Module ID

Success Response:

```
{
  "success": true,
  "message": "Module retrieved successfully",
  "data": {
    "id": 1,
    "name": "Assets",
    "code": "ASSETS",
    "description": "Asset management module",
    "icon": "fa-box",
    "route": "/assets",
    "display_order": 1,
    "is_active": true,
    "parent_id": null,
    "children": []
  }
}
```

Create Module

Endpoint: POST /api/permissions/modules

Authorization: Required (Admin)

Description: Create a new permission module

Request Body:

```
{
  "name": "Inventory",
  "code": "INVENTORY",
  "description": "Inventory management module",
  "icon": "fa-warehouse",
  "route": "/inventory",
  "display_order": 10,
  "parent_id": null,
  "is_active": true
}
```

Success Response:

```
{
  "success": true,
  "message": "Module created successfully",
  "data": {
    "id": 15,
    "name": "Inventory",
    "code": "INVENTORY",
    "description": "Inventory management module",
    "icon": "fa-warehouse",
    "route": "/inventory",
    "display_order": 10,
    "is_active": true,
    "parent_id": null
  }
}
```

Update Module

Endpoint: PUT /api/permissions/modules/:id

Authorization: Required (Admin)

Description: Update an existing module

URL Parameters:

- id - Module ID
-

Delete Module

Endpoint: DELETE /api/permissions/modules/:id

Authorization: Required (Admin)

Description: Delete a module

URL Parameters:

- id - Module ID
-

Toggle Module Active Status

Endpoint: PATCH /api/permissions/modules/:id/toggle

Authorization: Required (Admin)

Description: Toggle the active status of a module

URL Parameters:

- id - Module ID
-

Permission Endpoints

Get All Permissions

Endpoint: GET /api/permissions/

Authorization: Required

Description: Retrieve all permissions

Success Response:

```
{
  "success": true,
  "message": "Permissions retrieved successfully",
  "data": [
    {
      "id": 1,
      "module_id": 1,
      "module_name": "Assets",
      "module_code": "ASSETS",
      "action": "view",
      "description": "View assets",
      "is_active": true
    },
    {
      "id": 2,
      "module_id": 1,
      "module_name": "Assets",
      "module_code": "ASSETS",
      "action": "create",
      "description": "Create new assets",
      "is_active": true
    }
  ]
}
```

Get Permissions By Module

Endpoint: GET /api/permissions/by-module/:moduleId

Authorization: Required

Description: Get all permissions for a specific module

URL Parameters:

- moduleId - Module ID
-

Create Permission

Endpoint: POST /api/permissions/

Authorization: Required (Admin)

Description: Create a new permission

Request Body:

```
{
  "module_id": 1,
  "action": "export",
  "description": "Export assets to Excel"
}
```

Bulk Create Permissions

Endpoint: POST /api/permissions/bulk/:moduleId

Authorization: Required (Admin)

Description: Create multiple permissions for a module at once

URL Parameters:

- moduleId - Module ID

Request Body:

```
{
  "actions": ["view", "create", "edit", "delete", "export"]
}
```

Toggle Permission Active Status

Endpoint: PATCH /api/permissions/:id/toggle

Authorization: Required (Admin)

Description: Toggle the active status of a permission

URL Parameters:

- id - Permission ID
-

Role Permission Endpoints

Get Current User Permissions

Endpoint: GET /api/permissions/my-permissions

Authorization: Required

Description: Get the current authenticated user's permissions

Success Response:

```
{
  "success": true,
  "message": "User permissions retrieved successfully",
  "data": {
    "role_id": 1,
    "role_name": "Admin",
    "permissions": {
      "ASSETS": {
        "actions": ["view", "create", "edit", "delete"],
        "branch_level_access": false
      },
      "EXPENSES": {
        "actions": ["view", "create", "edit", "delete"],
        "branch_level_access": false
      }
    }
  }
}
```

Get Role Permissions

Endpoint: GET /api/permissions/roles/:roleId

Authorization: Required

Description: Get all permissions assigned to a role

URL Parameters:

- roleId - Role ID

Success Response:

```
{
  "success": true,
  "message": "Role permissions retrieved successfully",
  "data": [
    {
      "permission_id": 1,
      "module_name": "Assets",
      "module_code": "ASSETS",
      "action": "view",
      "branch_level_access": false
    },
    {
      "permission_id": 2,
      "module_name": "Assets",
      "module_code": "ASSETS",
      "action": "create",
      "branch_level_access": false
    }
  ]
}
```

Check Role Permission

Endpoint: GET /api/permissions/roles/:roleId/check

Authorization: Required

Description: Check if a role has a specific permission

URL Parameters:

- roleId - Role ID

Query Parameters:

- module_code - Module code (e.g., "ASSETS")
- action - Action to check (e.g., "view", "create", "edit", "delete")

Example: GET /api/permissions/roles/1/check?module_code=ASSETS&action=create

Success Response:

```
{
  "success": true,
  "message": "Permission check completed",
  "data": {
    "has_permission": true,
    "branch_level_access": false
  }
}
```

Get Role Accessible Routes

Endpoint: GET /api/permissions/roles/:roleId/routes

Authorization: Required

Description: Get all routes/menus accessible by a role

URL Parameters:

- roleId - Role ID

Assign Permission To Role

Endpoint: POST /api/permissions/roles/:roleId

Authorization: Required (Admin)

Description: Assign a permission to a role

URL Parameters:

- roleId - Role ID

Request Body:

```
{
  "permission_id": 5,
  "branch_level_access": false
}
```

Bulk Assign Permissions To Role

Endpoint: PUT /api/permissions/roles/:roleId/bulk

Authorization: Required (Admin)

Description: Assign multiple permissions to a role at once

URL Parameters:

- roleId - Role ID

Request Body:

```
{
  "permissions": [
    { "permission_id": 1, "branch_level_access": false },
    { "permission_id": 2, "branch_level_access": false },
    { "permission_id": 3, "branch_level_access": true }
  ]
}
```

Clone Role Permissions

Endpoint: POST /api/permissions/roles/:roleId/clone

Authorization: Required (Admin)

Description: Clone permissions from one role to another

URL Parameters:

- roleId - Target role ID (role to copy permissions to)

Request Body:

```
{
  "source_role_id": 1
}
```

Remove Permission From Role**Endpoint:** DELETE /api/permissions/roles/:roleId/permissionId**Authorization:** Required (Admin)**Description:** Remove a permission from a role**URL Parameters:**

- roleId - Role ID
- permissionId - Permission ID

Company Access Endpoints

Company access control allows restricting users to data from specific companies.

Get Role Company Access**Endpoint:** GET /api/permissions/roles/:roleId/company-access**Authorization:** Required**Description:** Get company access settings for a role**URL Parameters:**

- roleId - Role ID

Success Response:

```
{
  "success": true,
  "message": "Role company access retrieved successfully",
  "data": {
    "role_id": 2,
    "companies": [
      { "id": 1, "name": "freestylecodetechnologies systems", "has_access": true },
      { "id": 2, "name": "Jirani Smart", "has_access": true },
      { "id": 3, "name": "Tech Solutions", "has_access": false }
    ]
  }
}
```

Update Role Company Access**Endpoint:** PUT /api/permissions/roles/:roleId/company-access**Authorization:** Required (Admin)**Description:** Update company access settings for a role**URL Parameters:**

- roleId - Role ID

Request Body:

```
{
  "company_ids": [1, 2, 4]
}
```

Get All Companies**Endpoint:** GET /api/companies**Authorization:** Required**Description:** Get all companies for access control configuration

Success Response:

```
{
  "success": true,
  "data": [
    { "id": 1, "name": "freestylecodetechnologies systems", "is_active": true },
    { "id": 2, "name": "Jirani Smart", "is_active": true },
    { "id": 3, "name": "Tech Solutions", "is_active": true }
  ]
}
```

Reports

Get All Assets Report

Endpoint: GET /api/reports/assets/all

Authorization: Required

Description: Get all assets without filters

Success Response:

```
{
  "success": true,
  "message": "Assets report generated successfully",
  "data": [
    {
      "id": 1,
      "asset_tag": "ASSET-001",
      "asset_name": "Dell Laptop",
      "asset_type": "Computer Equipment",
      "status": "In Use",
      "branch": "Head Office",
      "department": "Information Technology",
      "purchase_price": 120000.00,
      "current_value": 100000.00
    }
  ]
}
```

Get Filtered Assets Report

Endpoint: GET /api/reports/assets

Authorization: Required

Description: Get filtered assets report with pagination

Query Parameters:

- `asset_tag` - Filter by asset tag (partial match)
- `asset_name` - Filter by asset name (partial match)
- `status_id` - Filter by status ID
- `asset_type_id` - Filter by asset type ID
- `branch_id` - Filter by branch ID
- `department_id` - Filter by department ID
- `limit` - Number of records per page (default: 20)
- `offset` - Starting record number (default: 0)

Example: GET /api/reports/assets?status_id=1&limit=50&offset=0

Success Response:

```
{
  "success": true,
  "message": "Filtered assets report generated successfully",
  "data": {
    "items": [
      {
        "id": 1,
        "asset_tag": "ASSET-001",
        "asset_name": "Dell Laptop",
        "asset_type": "Computer Equipment",
        "status": "In Use",
        "branch": "Head Office",
        "department": "Information Technology"
      }
    ],
    "total": 150,
    "limit": 50,
    "offset": 0
  }
}
```

Get Assets Assignments Report

Endpoint: GET /api/reports/assets/assignments

Authorization: Required

Description: Get assets with their assignment information

Success Response:

```
{
  "success": true,
  "message": "Assets by employee report generated successfully",
  "data": [
    {
      "asset_id": 1,
      "asset_tag": "ASSET-001",
      "asset_name": "Dell Laptop",
      "employee_id": 5,
      "first_name": "Caleb",
      "middle_name": null,
      "last_name": "Kiprono",
      "assignment_date": "2026-01-01",
      "status": "Assigned"
    }
  ]
}
```

Get All Expenses Report

Endpoint: GET /api/reports/expenses/all

Authorization: Required

Description: Get all expenses without filters

Success Response:

```
{
  "success": true,
  "message": "Expenses report generated successfully",
  "data": [
    {
      "expense_id": 1,
      "asset_tag": "ASSET-001",
      "expense_type": "Repair",
      "amount": 25000.00,
      "expense_date": "2026-01-05",
      "vendor": "Nairobi Tech Solutions"
    }
  ]
}
```

Export Assets Report

Endpoint: GET /api/reports/assets/export

Authorization: Required

Description: Export assets report to Excel

Query Parameters: Same as Get Filtered Assets Report

Response: Excel file download

Get Assets By Employee

Endpoint: GET /api/reports/assets/employee/:employeeId

Authorization: Required

Description: Get all assets assigned to a specific employee

URL Parameters:

- employeeId - Employee ID
-

Get Assets By Branch

Endpoint: GET /api/reports/assets/branch/:location

Authorization: Required

Description: Get all assets at a specific branch

URL Parameters:

- location - Branch location or ID
-

Get Expense Report Data

Endpoint: GET /api/reports/expenses

Authorization: Required

Description: Get filtered expenses report with pagination

Query Parameters:

- asset_id - Filter by asset ID
- asset_tag - Filter by asset tag
- expense_type_id - Filter by expense type ID
- expense_type - Filter by expense type name
- from_date - Start date (YYYY-MM-DD)
- to_date - End date (YYYY-MM-DD)
- min_amount - Minimum amount
- max_amount - Maximum amount
- vendor - Filter by vendor name
- limit - Number of records per page (default: 20)
- offset - Starting record number (default: 0)

Example: GET /api/reports/expenses?from_date=2025-01-01&to_date=2026-01-08&expense_type=Repair&limit=50&offset=0

Success Response:

```
{
  "success": true,
  "message": "Expense report data retrieved successfully",
  "data": {
    "expenses": [
      {
        "expense_id": 15,
        "asset_id": 1,
        "asset_tag": "ASSET-001",
        "asset_name": "Dell Laptop",
        "expense_type": "Repair",
        "expense_type_id": 2,
        "amount": "KES 25,000.00",
        "date": "2026-01-08",
        "description": "Screen replacement",
        "vendor": "Nairobi Tech Solutions"
      }
    ],
    "totalCount": 145
  }
}
```

Export Expenses Report

Endpoint: GET /api/reports/expenses/export

Authorization: Required

Description: Export expenses report to Excel

Query Parameters: Same as Get Expense Report Data (all filters supported)

- asset_id - Filter by asset ID
- asset_tag - Filter by asset tag
- expense_type_id - Filter by expense type ID
- expense_type - Filter by expense type name
- from_date - Start date (YYYY-MM-DD)
- to_date - End date (YYYY-MM-DD)
- min_amount - Minimum amount
- max_amount - Maximum amount
- vendor - Filter by vendor name

Example: GET /api/reports/expenses/export?from_date=2025-01-01&to_date=2026-01-08

Response: Excel file download (Content-Type: application/vnd.openxmlformats-officedocument.spreadsheetml.sheet)

Filename: Expense_Report_YYYY-MM-DD.xlsx

Get Expenses By Time Period

Endpoint: GET /api/reports/expenses/time-period

Authorization: Required (Admin)

Description: Get expenses within a specific time period with statistical analysis

Query Parameters:

- startDate - Start date (YYYY-MM-DD) **Required**
- endDate - End date (YYYY-MM-DD) **Required**

Example: GET /api/reports/expenses/time-period?startDate=2025-01-01&endDate=2026-01-08

Success Response:


```
{
  "success": true,
  "message": "Expenses report generated successfully",
  "data": {
    "expenses": [
      {
        "expense_id": 15,
        "asset_tag": "ASSET-001",
        "expense_type": "Repair",
        "amount": 25000.00,
        "expense_date": "2026-01-08",
        "vendor": "Nairobi Tech Solutions"
      }
    ],
    "summary": {
      "total_expenses": 542050.00,
      "expense_count": 23,
      "average_expense": 23567.39
    }
  }
}
```

Get Assignment Report Data

Endpoint: GET /api/reports/assignments

Authorization: Required

Description: Get filtered assignments report with pagination

Query Parameters:

- **asset_tag** - Filter by asset tag (partial match)
- **employee_id** - Filter by employee ID
- **employee_name** - Filter by employee name (partial match)
- **from_date** - Filter assignments from this date (YYYY-MM-DD)
- **to_date** - Filter assignments to this date (YYYY-MM-DD)
- **is_returned** - Filter by return status (true/false)
- **branch_id** - Filter by branch ID
- **department_id** - Filter by department ID
- **limit** - Number of records per page (default: 20)
- **offset** - Starting record number (default: 0)

Example: GET /api/reports/assignments?is_returned=false&from_date=2025-01-01&limit=20&offset=0

Success Response:

```
{
  "success": true,
  "message": "Assignments retrieved successfully",
  "data": {
    "assignments": [
      {
        "assignment_id": 10,
        "asset_id": 1,
        "asset_tag": "ASSET-001",
        "asset_name": "Dell Laptop",
        "employee_id": 5,
        "employee_name": "Caleb Kiprono",
        "first_name": "Caleb",
        "middle_name": "Kiprop",
        "last_name": "Kiprono",
        "assignment_date": "2026-01-01",
        "return_date": null,
        "status": "Active",
        "notes": "Laptop for development",
        "branch": "Head Office",
        "department": "Information Technology"
      }
    ],
    "totalCount": 87
  }
}
```

Export Assignment Report

Endpoint: GET /api/reports/assignments/export

Authorization: Required

Description: Export assignments report to Excel

Query Parameters: Same as Get Assignment Report Data (all filters supported)

- `asset_tag` - Filter by asset tag
- `employee_id` - Filter by employee ID
- `employee_name` - Filter by employee name
- `from_date` - Start date (YYYY-MM-DD)
- `to_date` - End date (YYYY-MM-DD)
- `is_returned` - Filter by return status (true/false)
- `branch_id` - Filter by branch ID
- `department_id` - Filter by department ID

Example: GET /api/reports/assignments/export?is_returned=false&from_date=2025-01-01

Response: Excel file download (Content-Type: application/vnd.openxmlformats-officedocument.spreadsheetml.sheet)

Filename: Assignments_Report_YYYY-MM-DD.xlsx

Get Action Log Report Data

Endpoint: GET /api/reports/action-logs

Authorization: Required

Description: Get filtered action logs report with pagination

Query Parameters:

- `action_type` - Filter by action type (e.g., "CREATE", "UPDATE", "DELETE", "ASSIGN", "RETURN")
- `user_id` - Filter by user who performed action
- `entity_type` - Filter by entity type (e.g., "Asset", "Assignment", "Expense", "User")
- `entity_id` - Filter by specific entity ID
- `from_date` - Start date (YYYY-MM-DD)
- `to_date` - End date (YYYY-MM-DD)
- `limit` - Number of records per page (default: 20)
- `offset` - Starting record number (default: 0)

Example: GET /api/reports/action-logs?action_type=CREATE&entity_type=Asset&limit=50&offset=0

Success Response:

```
{
  "success": true,
  "message": "Action logs retrieved successfully",
  "data": {
    "logs": [
      {
        "id": 100,
        "action_type": "CREATE",
        "entity_type": "Asset",
        "entity_id": 1,
        "user_id": 5,
        "user_name": "Caleb Kiprono",
        "user_email": "caleb.kiprono@freestylecodetechnologies.com",
        "created_at": "2026-01-08T10:30:00.000Z",
        "description": "Created new asset ASSET-001",
        "details": "{\"asset_tag\":\"ASSET-001\",\"asset_name\":\"Dell Laptop\"}",
        "ip_address": "192.168.1.100"
      }
    ],
    "totalCount": 523
  }
}
```

Note: The details field contains JSON string with additional information about the action performed.

Action Types:

- CREATE - New record created
- UPDATE - Record modified
- DELETE - Record deleted
- ASSIGN - Asset assigned to employee
- RETURN - Asset returned from employee
- LOGIN - User login activity
- LOGOUT - User logout activity
- UPLOAD - File/bulk upload
- EXPORT - Report exported

Entity Types:

- Asset - Asset records
- Assignment - Assignment records
- Expense - Expense records
- User - User accounts
- Employee - Employee records
- Department - Department records
- Branch - Branch records
- AssetType - Asset type records
- ExpenseType - Expense type records
- AssetStatus - Asset status records

Export Action Log Report

Endpoint: GET /api/reports/action-logs/export

Authorization: Required

Description: Export action logs report to Excel

Query Parameters: Same as Get Action Log Report Data (all filters supported)

- action_type - Filter by action type
- user_id - Filter by user ID
- entity_type - Filter by entity type
- entity_id - Filter by entity ID
- from_date - Start date (YYYY-MM-DD)
- to_date - End date (YYYY-MM-DD)

Example: GET /api/reports/action-logs/export?action_type=CREATE&from_date=2025-01-01&to_date=2026-01-08

Response: Excel file download (Content-Type: application/vnd.openxmlformats-officedocument.spreadsheetml.sheet)

Filename: Action_Logs_Report_YYYY-MM-DD.xlsx

Bulk Upload

Bulk Upload Assets

Endpoint: POST /api/upload/assets

Authorization: Required (Admin)

Description: Upload multiple assets via Excel file

Content-Type: multipart/form-data

Form Data:

- file - Excel file (.xlsx) with asset data

Excel File Format:

Required columns:

- asset_tag - Unique asset identifier
- asset_name - Name of the asset
- asset_type_id - Asset type ID
- purchase_date - Date (YYYY-MM-DD)
- purchase_price - Decimal number
- status_id - Status ID
- branch_id - Branch ID
- department_id - Department ID

Optional columns:

- description - Asset description
- serial_number - Serial number
- current_value - Current value
- warranty_expiry_date - Date (YYYY-MM-DD)

Success Response:

```
{
  "success": true,
  "message": "Assets uploaded successfully",
  "data": {
    "total": 50,
    "successful": 48,
    "failed": 2,
    "errors": [
      {
        "row": 5,
        "error": "Duplicate asset tag"
      },
      {
        "row": 12,
        "error": "Invalid asset type ID"
      }
    ]
  }
}
```

System Configuration

Get System Configuration

Endpoint: GET /api/system-config/

Authorization: Required (Admin)

Description: Retrieve system configuration settings

Success Response:

```
{
  "success": true,
  "message": "Configuration retrieved successfully",
  "data": {
    "id": 1,
    "company_name": "Jirani Smart Systems",
    "company_email": "info@freestylecodetechnologies.com",
    "company_phone": "+254740790088",
    "company_address": "Westlands, Nairobi, Kenya",
    "logo_url": "/uploads/logos/company-logo.png",
    "currency": "KES",
    "date_format": "YYYY-MM-DD",
    "timezone": "Africa/Nairobi"
  }
}
```

Get Public Configuration

Endpoint: GET /api/system-config/public

Authorization: None

Description: Retrieve public system configuration (for login page, etc.)

Success Response:

```
{
  "success": true,
  "message": "Public configuration retrieved successfully",
  "data": {
    "company_name": "Jirani Smart Systems",
    "logo_url": "/uploads/logos/company-logo.png"
  }
}
```

Update System Configuration

Endpoint: PUT /api/system-config/

Authorization: Required (Admin)

Description: Update system configuration settings

Request Body:

```
{
  "company_name": "Jirani Smart Systems Ltd",
  "company_email": "support@freestylecodetechnologies.com",
  "company_phone": "+254740790088",
  "company_address": "Westlands Commercial Center, Nairobi, Kenya",
  "currency": "KES",
  "date_format": "DD/MM/YYYY",
  "timezone": "Africa/Nairobi"
}
```

Success Response:

```
{
  "success": true,
  "message": "Configuration updated successfully",
  "data": {
    "id": 1,
    "company_name": "Jirani Smart Systems Ltd",
    "company_email": "support@freestylecodetechnologies.com",
    "company_phone": "+254740790088",
    "company_address": "Westlands Commercial Center, Nairobi, Kenya",
    "currency": "KES",
    "date_format": "DD/MM/YYYY",
    "timezone": "Africa/Nairobi"
  }
}
```

Upload Company Logo

Endpoint: POST /api/system-config/upload-logo

Authorization: Required (Admin)

Description: Upload or update company logo

Content-Type: multipart/form-data

Form Data:

- logo - Image file (max 5MB, image formats only)

Success Response:

```
{
  "success": true,
  "message": "Logo uploaded successfully",
  "data": {
    "logo_url": "/uploads/logos/company-logo-1704715800000.png"
  }
}
```

Error Responses

All endpoints may return error responses in the following format:

400 Bad Request

```
{
  "success": false,
  "message": "Invalid request data",
  "error": "Detailed error message"
}
```

401 Unauthorized

```
{
  "success": false,
  "message": "Authentication required",
  "error": "No token provided"
}
```

403 Forbidden

```
{
  "success": false,
  "message": "Access denied",
  "error": "Insufficient permissions"
}
```

404 Not Found

```
{
  "success": false,
  "message": "Resource not found",
  "error": "Asset with ID 999 not found"
}
```

500 Internal Server Error

```
{
  "success": false,
  "message": "Internal server error",
  "error": "Database connection failed"
}
```

Authentication & Authorization

Authentication Method

The API uses **JWT (JSON Web Tokens)** for authentication. Tokens are stored in HTTP-only cookies:

- **Access Token:** Valid for 30 minutes
- **Refresh Token:** Valid for 7 days

Cookie Names

- `accessToken` - Used for API authentication
- `refreshToken` - Used for token refresh

Authorization Roles

The system supports role-based access control:

1. **Admin** - Full system access
2. **Standard User** - Limited access to view and basic operations
3. **Super Admin** - System-level configuration access (specific endpoints)

Making Authenticated Requests

Authentication is handled automatically via cookies. For external API clients:

1. Login via `/api/auth/login` to receive tokens
2. Tokens are automatically sent with subsequent requests via cookies
3. When access token expires, use `/api/auth/refresh-token` to get a new one
4. Logout via `/api/auth/logout` to clear tokens

Data Formats

Date Format

All dates should be in ISO 8601 format: `YYYY-MM-DD`

Example: `2026-01-08`

DateTime Format

All timestamps are in ISO 8601 format with timezone: `YYYY-MM-DDTHH:mm:ssZ`

Example: `2026-01-08T10:30:00Z`

Currency

All monetary values are decimal numbers with 2 decimal places.

Example: `1299.99`

Pagination

Endpoints that support pagination use the following query parameters:

- `limit` - Number of records per page (default: 20, max: 100)
- `offset` - Starting record number (default: 0)

Example:

```
GET /api/reports/assets?limit=50&offset=100
```

Response includes pagination metadata:

```
{
  "success": true,
  "message": "Assets retrieved successfully",
  "data": {
    "items": [...],
    "total": 500,
    "limit": 50,
    "offset": 100,
    "hasMore": true
  }
}
```

File Upload Limits

- **Asset Attachments:** 10MB max
 - **Assignment Attachments:** 10MB max
 - **Expense Attachments:** 10MB max
 - **Company Logo:** 5MB max (images only)
 - **Bulk Upload Excel:** Size depends on data volume
-

API Testing Examples

Using cURL

Login Example

```
curl -X POST http://localhost:3000/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{
    "email": "fredrick.mbugua@freestylecodetechnologies.com",
    "password": "password123"
  }' \
  -c cookies.txt
```

Get Assets with Authentication

```
curl -X GET http://localhost:3000/api/assets/ \
  -H "Content-Type: application/json" \
  -b cookies.txt
```

Create Asset

```
curl -X POST http://localhost:3000/api/assets/ \
  -H "Content-Type: application/json" \
  -b cookies.txt \
  -d '{
    "asset_tag": "ASSET-100",
    "asset_name": "MacBook Pro",
    "asset_type_id": 1,
    "purchase_date": "2026-01-08",
    "purchase_price": 250000.00,
    "status_id": 1,
    "branch_id": 1,
    "department_id": 1
  }'
```

Upload Asset Attachment

```
curl -X POST http://localhost:3000/api/asset-attachments/1/attachments \
  -H "Content-Type: multipart/form-data" \
  -b cookies.txt \
  -F "file=@/path/to/invoice.pdf"
```

Search Assets


```
curl -X GET "http://localhost:3000/api/assets/search?asset_name=laptop&status_id=1" \
-H "Content-Type: application/json" \
-b cookies.txt
```

Export Report

```
curl -X GET "http://localhost:3000/api/reports/assets/export?status_id=1" \
-b cookies.txt \
--output Asset_Report.xlsx
```

Using Postman

1. **Set Base URL:** Create an environment variable `base_url = http://localhost:3000/api`
2. **Login:** POST to `{{base_url}}/auth/login` - Cookies will be saved automatically
3. **Make Requests:** Use `{{base_url}}/assets/` for subsequent requests
4. **File Upload:** Use form-data with file field for attachment endpoints

Using JavaScript (Fetch API)

```
// Login
const login = async () => {
  const response = await fetch('http://localhost:3000/api/auth/login', {
    method: 'POST',
    headers: { 'Content-Type': 'application/json' },
    credentials: 'include',
    body: JSON.stringify({
      email: 'fredrick.mbugua@freestylecodetechnologies.com',
      password: 'password123'
    })
  });
  return await response.json();
};

// Get Assets
const getAssets = async () => {
  const response = await fetch('http://localhost:3000/api/assets/', {
    method: 'GET',
    credentials: 'include'
  });
  return await response.json();
};

// Create Asset
const createAsset = async (assetData) => {
  const response = await fetch('http://localhost:3000/api/assets/', {
    method: 'POST',
    headers: { 'Content-Type': 'application/json' },
    credentials: 'include',
    body: JSON.stringify(assetData)
  });
  return await response.json();
};

// Upload File
const uploadFile = async (assetId, file) => {
  const formData = new FormData();
  formData.append('file', file);

  const response = await fetch(`http://localhost:3000/api/asset-attachments/${assetId}/attachments`, {
    method: 'POST',
    credentials: 'include',
    body: formData
  });
  return await response.json();
};
```

Common Integration Patterns

Workflow 1: Complete Asset Lifecycle

1. POST `/api/auth/login`
→ Login and receive cookies
2. POST `/api/assets/`
→ Create **new** asset
3. POST `/api/asset-attachments/:assetId/attachments`
→ Upload invoice/receipt
4. POST `/api/assignments/`
→ Assign asset to employee
5. POST `/api/assignment-attachments/:assignmentId/attachments`
→ Upload handover documents
6. GET `/api/reports/assignments`
→ Monitor active assignments
7. PUT `/api/assignments/:id/return`
→ **Return** asset when done
8. POST `/api/expenses/`
→ Record **any** maintenance expenses
9. GET `/api/reports/assets/:id`
→ View complete asset history

Workflow 2: Monthly Reporting

1. POST `/api/auth/login`
→ Authenticate
2. GET `/api/reports/assets?limit=100&offset=0`
→ Get assets report data (paginated)
3. GET `/api/reports/expenses?from_date=2026-01-01&to_date=2026-01-31`
→ Get monthly expenses
4. GET `/api/reports/assignments?from_date=2026-01-01`
→ Get monthly assignments
5. GET `/api/reports/assets/export`
→ Export full report **to** Excel
6. GET `/api/reports/expenses/export?from_date=2026-01-01&to_date=2026-01-31`
→ Export expenses **to** Excel
7. GET `/api/reports/action-logs?from_date=2026-01-01`
→ Audit trail **for** the month

Workflow 3: Bulk Operations

1. POST `/api/auth/login`
→ Authenticate as Admin
2. POST `/api/upload/assets`
→ Bulk upload assets **from** Excel
3. GET `/api/assets/`
→ Verify uploaded assets
4. GET `/api/reports/assets?limit=1000`
→ Review all assets
5. POST `/api/assets/:id` (**for each** correction needed)
→ Fix **any** data issues

Rate Limiting

Currently, there are no explicit rate limits implemented. However, it is recommended to:

- Avoid excessive concurrent requests
 - Implement client-side throttling
 - Use pagination for large datasets
-

Troubleshooting

Common Issues

1. Authentication Failures

Problem: 401 Unauthorized

```
{
  "success": false,
  "message": "Authentication required"
}
```

Solutions:

- Ensure you've logged in via `/api/auth/login`
 - Check that cookies are being sent with requests (`credentials: 'include' in fetch`)
 - Verify access token hasn't expired (30 min lifetime)
 - Try refreshing token via `/api/auth/refresh-token`
-

2. File Upload Failures

Problem: File too large or invalid format

```
{
  "success": false,
  "message": "File size exceeds maximum limit of 10MB"
}
```

Solutions:

- Compress large files before upload
 - Verify file format is supported
 - Check Content-Type is `multipart/form-data`
 - Ensure field name is correct (`file` for attachments, `logo` for company logo)
-

3. Pagination Issues

Problem: Missing or incorrect pagination

```
{
  "success": false,
  "message": "Invalid pagination parameters"
}
```

Solutions:

- Ensure `limit` is a positive integer
 - Ensure `offset` is 0 or positive
 - Don't exceed limit of 100 per request
 - Use correct query string format: `?limit=20&offset=0`
-

4. Foreign Key Violations

Problem: Referenced entity doesn't exist

```
{
  "success": false,
  "message": "Invalid asset_type_id: Asset type with ID 99 not found"
}
```

Solutions:

- Verify the referenced entity exists (e.g., asset type, department, branch)
 - Get valid IDs from lookup endpoints first
 - Check for typos in ID values
-

5. Duplicate Entries

Problem: Unique constraint violation

```
{
  "success": false,
  "message": "Asset tag 'ASSET-001' already exists"
}
```

Solutions:

- Use unique asset tags
 - Check existing records before creating new ones
 - Use search endpoint to verify uniqueness
-

6. Permission Denied

Problem: 403 Forbidden

```
{
  "success": false,
  "message": "Access denied. Admin role required."
}
```

Solutions:

- Verify user has correct role for the operation
 - Check authorization requirements in documentation
 - Contact administrator to update user role if needed
-

Debug Mode

For development, you can enable detailed error logging:

1. Set environment variable: `NODE_ENV=development`
 2. Check server logs for detailed stack traces
 3. Use browser DevTools Network tab to inspect requests/responses
-

Getting Help

If you encounter issues not covered here:

1. Check the server logs for detailed error messages
 2. Verify all required fields are included in request body
 3. Test with a simple cURL command first
 4. Contact support at: fmbugua@freestylecodetechnologies.com
-

Changelog

Version 2.0 (January 8, 2026)

- Complete API documentation update with all endpoints
- Added comprehensive Quick Reference table with all 90+ endpoints
- Added System Configuration endpoints
- Added Action Log reporting with entity and action type details
- Enhanced filtering and pagination across all report endpoints

- Added attachment support for assets, assignments, and expenses
- Improved authentication with refresh token mechanism
- Added bulk upload functionality for assets
- Added detailed request/response examples for every endpoint
- Added cURL, JavaScript, and Postman usage examples
- Added common integration workflow patterns
- Added comprehensive troubleshooting guide
- Added error handling examples for each endpoint
- Documented all query parameters and filters
- Added file upload specifications and limits

Version 1.0 (September 20, 2025)

- Initial API release
- Basic CRUD operations for assets, assignments, and expenses
- User authentication and authorization
- Basic reporting functionality

Glossary

Asset - Physical or digital resource owned by the organization (laptops, furniture, software licenses, etc.)

Asset Tag - Unique identifier assigned to each asset for tracking purposes

Assignment - Record of an asset being allocated to an employee with assignment and return dates

Attachment - File (document, image, receipt) associated with an asset, assignment, or expense

Authentication - Process of verifying user identity via login credentials

Authorization - Process of determining if authenticated user has permission for requested action

Branch - Physical location or office of the organization

Bulk Upload - Process of importing multiple records at once via Excel file

Department - Organizational unit grouping employees by function (IT, HR, Finance, etc.)

Expense - Cost incurred for maintaining, repairing, or upgrading an asset

Expense Type - Category of expense (Repair, Maintenance, Upgrade, etc.)

JWT (JSON Web Token) - Secure token used for authentication, stored in HTTP-only cookies

Pagination - Technique to retrieve large datasets in smaller chunks using limit/offset parameters

Refresh Token - Long-lived token used to obtain new access tokens without re-login

Role - User permission level (Admin, Standard User, Super Admin)

Status - Current state of an asset (Available, In Use, Under Repair, Retired, etc.)

API Limits & Constraints

Request Limits

- **Maximum Upload Size:** 10MB for attachments, 5MB for company logo
- **Pagination Limit:** Maximum 100 records per request
- **Query String Length:** 2048 characters maximum
- **Request Timeout:** 30 seconds for standard requests, 120 seconds for export operations

Data Constraints

- **Asset Tag:** 50 characters maximum, must be unique
- **Email:** 255 characters maximum, must be valid format
- **Password:** Minimum 8 characters, must contain letters and numbers
- **Phone Number:** 20 characters maximum
- **Description Fields:** 1000 characters maximum
- **File Names:** 255 characters maximum

Rate Limits

- Currently no explicit rate limits implemented
 - Recommended: Maximum 100 requests per minute per user
 - Bulk operations should be performed during off-peak hours
-

Security Best Practices

For API Consumers

1. Protect Credentials

- Never commit credentials to version control
- Use environment variables for sensitive data
- Rotate passwords regularly

2. Token Management

- Store tokens securely (HTTP-only cookies recommended)
- Implement token refresh logic
- Clear tokens on logout

3. Input Validation

- Validate all input on client side before sending
- Sanitize user input to prevent injection attacks
- Use parameterized queries

4. HTTPS

- Always use HTTPS in production
- Verify SSL certificates
- Don't expose API over HTTP

5. Error Handling

- Don't expose sensitive information in errors
- Log errors for debugging
- Provide user-friendly error messages

For API Administrators

1. Access Control

- Follow principle of least privilege
- Regularly review user permissions
- Disable inactive accounts

2. Monitoring

- Log all API requests
- Monitor for unusual activity
- Set up alerts for failed authentication attempts

3. Backups

- Regular database backups
- Test restore procedures
- Keep backups encrypted and off-site

4. Updates

- Keep dependencies updated
 - Apply security patches promptly
 - Review security advisories
-

Setup Guide

This section provides step-by-step instructions for setting up and testing the Asset Management System locally.

Prerequisites

Before starting, ensure you have the following installed:

Software	Version	Purpose
Node.js	v18.x or higher	JavaScript runtime
npm	v9.x or higher	Package manager
PostgreSQL	v14.x or higher	Database server
Git	Latest	Version control

Step 1: Clone the Repository

```
git clone https://github.com/fred-mbugua/company-asset-manager
cd asset-manager
```

Step 2: Install Dependencies

```
npm install
```

This will install all required packages including:

- **Express.js** - Web framework
- **pg** - PostgreSQL client
- **jsonwebtoken** - JWT authentication
- **bcryptjs** - Password hashing
- **multer** - File uploads
- **exceljs** - Excel report generation
- **nodemailer** - Email notifications
- **ejs** - Template engine

Step 3: Environment Configuration

Create a `.env` file in the root directory with the following variables:

```
# Server Configuration
PORT=3000
NODE_ENV=development

# Database Configuration
DATABASE_URL=postgresql://username:password@localhost:5432/asset_manager

# JWT Configuration
JWT_ACCESS_SECRET=your-secure-access-token-secret-key
JWT_REFRESH_SECRET=your-secure-refresh-token-secret-key

# Email Configuration (Optional - for notifications)
MAIL_SERVICE=gmail
MAIL_USER=your-email@gmail.com
MAIL_PASS=your-app-password

# SMS Configuration (Optional)
SMS_API_KEY=your-sms-api-key
```

Environment Variables Explained:

Variable	Required	Description
PORT	No	Server port (default: 3000)
NODE_ENV	No	Environment: development, production
DATABASE_URL	Yes	PostgreSQL connection string
JWT_ACCESS_SECRET	Yes	Secret for signing access tokens
JWT_REFRESH_SECRET	Yes	Secret for signing refresh tokens
MAIL_SERVICE	No	Email service provider
MAIL_USER	No	Email account username
MAIL_PASS	No	Email account password/app password
SMS_API_KEY	No	SMS service API key

Step 4: Database Setup

4.1 Create the Database

```
# Connect to PostgreSQL
psql -U postgres

# Create database
CREATE DATABASE asset_manager;

# Exit psql
\q
```

4.2 Initialize Database Schema

Use the clean database script to set up tables with default data:

```
psql -U postgres -d asset_manager -f db_backup/clean_db_17012026.sql
```

This script creates:

- All required tables (27 tables)
- Default lookup data (asset types, statuses, departments, etc.)
- Default admin user for testing
- Database functions and triggers

Default Login Credentials

After running the clean database script:

Field	Value
Email	dev@system.local
Password	Dev@123
Role	Admin

Step 5: Build the Application

Compile TypeScript to JavaScript:

```
npm run build
```

This compiles the source files from `/src` to `/dist`.

Step 6: Run the Application

Development Mode (with hot reload)

```
npm run dev
```

Production Mode

```
npm start
```

The application will start at `http://localhost:3000`

Step 7: Verify Installation

7.1 Access the Web Interface

Open your browser and navigate to:

- **Login Page:** `http://localhost:3000/login`
- **Dashboard:** `http://localhost:3000/dashboard` (after login)

7.2 Test API Endpoints

Using curl or Postman:


```
# Test login endpoint
curl -X POST http://localhost:3000/api/auth/login \
  -H "Content-Type: application/json" \
  -d '{"email": "dev@system.local", "password": "Dev@123"}'

# Expected response:
{
  "success": true,
  "message": "Login successful",
  "data": {
    "id": 1,
    "email": "dev@system.local",
    "role": "Admin"
  }
}
```

7.3 Check System Health

```
# Get public system configuration
curl http://localhost:3000/api/system-config/public
```

Available NPM Scripts

Command	Description
npm start	Run production server
npm run dev	Run development server with nodemon
npm run build	Compile TypeScript to JavaScript
npm run docs:word	Generate Word documentation

File Upload Configuration

Uploaded files are stored in the /uploads directory:

```
uploads/
├─ assets/           # Asset attachments
├─ assignments/      # Assignment documents
├─ expenses/         # Expense receipts/invoices
├─ logos/           # Company logos
└─ repair-requests/ # Repair request files
```

Note: Ensure the /uploads directory has proper write permissions.

Production Deployment with PM2

The application includes PM2 configuration for production:

```
# Install PM2 globally
npm install -g pm2

# Start with PM2
pm2 start ecosystem.config.js

# View logs
pm2 logs asset-manager

# Restart application
pm2 restart asset-manager

# Stop application
pm2 stop asset-manager
```

Troubleshooting

Database Connection Issues

Error: Database connection failed

Solution:

1. Verify PostgreSQL is running: `pg_isready`
2. Check DATABASE_URL format
3. Ensure database exists
4. Verify user credentials and permissions

Port Already in Use

```
Error: EADDRINUSE: address already in use :::3000
```

Solution:

1. Change PORT in `.env` file
2. Or kill the process using the port:
 - Windows: `netstat -ano | findstr :3000` then `taskkill /PID <PID> /F`
 - Linux/Mac: `lsof -i :3000` then `kill -9 <PID>`

TypeScript Compilation Errors

```
# Clean and rebuild
rm -rf dist
npm run build
```

Missing Environment Variables

```
Error: JWT_ACCESS_SECRET is not defined
```

Solution: Ensure all required variables are set in `.env` file.

Testing Checklist

After setup, verify these features work:

- ☐ User login/logout
- ☐ Dashboard loads with statistics
- ☐ Create new asset
- ☐ Assign asset to employee
- ☐ Upload attachment to asset
- ☐ Create expense record
- ☐ Generate asset report
- ☐ Export report to Excel
- ☐ Create repair request
- ☐ Execute repair workflow actions
- ☐ Manage system configuration
- ☐ Create and manage roles
- ☐ Configure module permissions
- ☐ Assign permissions to roles
- ☐ Set company access controls

Support

For API support or questions, please contact:

Technical Support:

- **Email:** fmbugua@freestylecodetechnologies.com
- **Phone:** +254 740 790 088
- **Hours:** Monday - Friday, 8:00 AM - 5:00 PM EAT

Documentation:

- **API Docs:** This file (`API_DOCUMENTATION.md`)
- **GitHub:** <https://github.com/fred-mbugua/company-asset-manager>

Environment URLs:

- **Development:** <http://localhost:3000/api>
- **Staging:**
- **Production:**

Additional Resources:

- Database Schema Documentation
- System Architecture Diagram
- Deployment Guide
- User Manual

Last Updated: January 24, 2026

Document Version: 2.2

API Version: 2.2

Note: This documentation is based on the current implementation as of January 24, 2026. Always refer to the latest version of this document for accurate API information. For the most up-to-date endpoint specifications, consult the source code in the `/src/routes` directory.