

ExtraordinaryMe: Project Documentation

Updated Documentation: Setup, Mobile-First Constraints & Express 5 Routing

1. Mobile-First Architecture Directive

The application is strictly constrained to a mobile-first design targeting iOS and Android devices. All frontend modules must adhere to:

- **Fluid Layouts:** Strict usage of CSS Flexbox and Grid.
- **Touch-Optimized Targets:** Minimum 44x44 pixel tap areas for interactive elements.
- **Viewport Scaling:** Mandatory inclusion of viewport meta tags for native-like scaling.

2. Project Initialization & Directory Scaffolding

The following sequence initializes the Node.js environment and rapidly scaffolds the exact folder structure established in the architecture spec.

```
# 1. Initialize the project directory
mkdir extraordinaryme
cd extraordinaryme
npm init -y

# 2. Scaffold the src directory and all domain sub-folders
mkdir -p src/{views,modules/
{shared,health,productivity,finance,reports,profiles,messaging,hirecoach,help,coach,a
dmin}}

# 3. Create the core SPA files
touch src/index.html src/app.js src/router.js

# 4. Create the view orchestrators
touch src/views/
{home,health,productivity,finance,reports,profiles,messaging,hirecoach,help,coach,adm
in}.js

# 5. Create the shared infrastructure modules
touch src/modules/shared/{api,store,dateUtils}.js
```

3. Core Dependency Installation

Install the foundational backend packages. Express is required for the local server and the PostgreSQL client guarantees the local environment can interface exactly like the AWS production database.

```
npm install express pg dotenv
```

4. Backend Boilerplate (Express 5 Compatible)

Create a `server.js` file in the root directory. This serves the static ES modules and acts as the local API gateway, utilizing a standard middleware catch-all for single-page routing to avoid Express 5 wildcard errors.

```
// server.js
const express = require('express');
const path = require('path');
const app = express();
const PORT = process.env.PORT || 3000;

// Serve the static SPA files
app.use(express.static(path.join(__dirname, 'src')));

// SPA Fallback - route all non-API requests to index.html (Express 5 safe)
app.use((req, res) => {
  res.sendFile(path.join(__dirname, 'src', 'index.html'));
});

app.listen(PORT, () => {
  console.log(`ExtraordinaryMe local server running on http://localhost:${PORT}`);
});
```