
```
train cifar10.ison
 Oct 08, 2025 16:33
                                                                         Page 1/4
    I deleted all the training log (train loss) since there were too many and ju
st leave the validation loss log
    It should be easier to see the train/validation loss graph to see the traini
ng summary
    Test set result is at the very bottom
    To be honest, I think I can get better result with better blocks_per_stage a
nd layer_depths (more like resnet-18 or resnet-34 that I used for CIFAR-100) but
I didn't have time to re-train it.
                    2025-10-04T23:02:32.478968Z
    Started:
                    2025-10-05T03:43:35.804946Z
    Ended:
* /
{"settings": {"debug": false, "random_seed": 31415, "model": {"input_depth": 3,
"layer_depths": [16, 32, 64], "blocks_per_stage": [3, 3, 3], "num_classes": 10},
 "data": {"batch_size": 64, "validation_size": 5000, "shuffle_buffer": 10000},
training": {"num_epochs": 40, "learning_rate": 0.001, "weight_decay": 0.0001, "l
og_interval": 100, "final_test": false, "checkpoint_dir": "PosixPath('hw04/check points')"}, "plotting": {"output_dir": "PosixPath('hw04/artifacts')", "figsize":
[5, 3], "dpi": 200}}, "event": "Settings loaded", "logger": "hw04", "level": "i
nfo", "timestamp": "2025-10-04T23:01:52.118846Z"}
{"event": "Variant folder /root/tensorflow_datasets/cifar10/3.0.2 has no dataset
_info.json"}
{"event": "Generating dataset cifar10 (/root/tensorflow_datasets/cifar10/3.0.2)"
{"event": "Downloading https://www.cs.toronto.edu/~kriz/cifar-10-binary.tar.gz i
nto /root/tensorflow_datasets/downloads/cifar10/cs.toronto.edu_kriz_cifar-10-bin
aryODHPtIjLh3oLcXirEISTO7dkzyKjRCuol6lV8Wc6C7s.tar.gz.tmp.e1cbf29ba6684e91b56e41
462da23de0..."}
{"event": "Done writing /root/tensorflow_datasets/cifar10/incomplete.4A5IR3_3.0.
2/cifar10-train.tfrecord*. Number of examples: 50000 (shards: [50000])"}
{"event": "Done writing /root/tensorflow_datasets/cifar10/incomplete.4A5IR3_3.0.
2/cifar10-test.tfrecord*. Number of examples: 10000 (shards: [10000])"}
{"event": "Creating a tf.data.Dataset reading 1 files located in folders: /root/
tensorflow_datasets/cifar10/3.0.2."}
{"event": "Constructing tf.data.Dataset cifar10 for split train, from /root/tens
orflow datasets/cifar10/3.0.2"}
{"event": "Load dataset info from /root/tensorflow_datasets/cifar10/3.0.2"}
{"event": "Creating a tf.data.Dataset reading 1 files located in folders: /root/
tensorflow_datasets/cifar10/3.0.2."}
{"event": "Constructing tf.data.Dataset cifar10 for split test, from /root/tenso
rflow_datasets/cifar10/3.0.2"}
{"event": "Unable to initialize backend 'tpu': INTERNAL: Failed to open libtpu.s
o: libtpu.so: cannot open shared object file: No such file or directory"}
{"num_params": 272938, "event": "Model created", "logger": "hw04", "level": "inf
o", "timestamp": "2025-10-04T23:02:32.478968Z"}
{"epoch": 1, "step": 704, "val_loss": 1.6888156540786163, "val_acc": 0.388844936
7088608, "event": "epoch_summary", "logger": "hw04.training", "level": "info", "
timestamp": "2025-10-04T23:04:50.694858Z"}
{"epoch": 2, "step": 1408, "val_loss": 1.317224457294126, "val_acc": 0.517207278
4810127, "event": "epoch_summary", "logger": "hw04.training", "level": "info", '
timestamp": "2025-10-04T23:07:19.472678Z"}
{"epoch": 3, "step": 2112, "val_loss": 1.2149084308479405, "val_acc": 0.55992879
74683544, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-04T23:09:49.454928Z"}
{"epoch": 4, "step": 2816, "val_loss": 1.088192823566968, "val_acc": 0.612737341
7721519, "event": "epoch_summary", "logger": "hw04.training", "level": "info", "
timestamp": "2025-10-04T23:43:07.676783Z"}
{"event": "Finished blocking save. Time taken: 0.397554s. Continuing background
save to /work/hw04/checkpoints/best_state_epoch_5."}
{"epoch": 5, "step": 3520, "val_loss": 0.9746726042107691, "val_acc": 0.65031645
56962026, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-05T00:24:08.390924Z"}
{"epoch": 6, "step": 4224, "val_loss": 1.0020704873000519, "val_acc": 0.64477848
10126582, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-05T01:12:26.285167Z"}
{"epoch": 7, "step": 4928, "val_loss": 0.8331410703779776, "val_acc": 0.71182753
16455697, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
```

Oct 08, 2025 16:33	train cifar10.json	Page 2/4
"timestamp": "2025-10-05"		9-
	2, "val_loss": 0.8326036997988254, "val	
88607594, "event": "epoc "timestamp": "2025-10-05	h_summary", "logger": "hw04.training", T02:23:58.9508637"}	"level": "info",
{"epoch": 9, "step": 633	6, "val_loss": 0.8269730994973001, "val	
	h_summary", "logger": "hw04.training",	"level": "info",
"timestamp": "2025-10-05"	TU2:25:53./343312"} king save. Time taken: 0.291334s. Conti	nuing background
save to /work/hw04/check	points/best_state_epoch_10."}	-
	40, "val_loss": 0.7053691990013364, "va	
"timestamp": "2025-10-0	<pre>ch_summary", "logger": "hw04.training", 5T02:28:01.743996Z"}</pre>	"level": "Inlo",
{"epoch": 11, "step": 77	44, "val_loss": 0.7308083606671684, "va	al_acc": 0.7488132
911392406,	ch_summary", "logger": "hw04.training",	"level": "info",
{"epoch": 12, "step": 84	48, "val_loss": 0.6420914360994026, "va	
	ch_summary", "logger": "hw04.training",	"level": "info",
"timestamp": "2025-10-0 {"epoch": 13, "step": 91	5102:32:36.5191622"} 52,	al acc ": 0.7650316
	ch_summary", "logger": "hw04.training",	
"timestamp": "2025-10-0		1 1 0 7006566
	56, "val_loss": 0.6394457692586923, "vach_summary", "logger": "hw04.training",	
"timestamp": "2025-10-0	5T02:37:23.746143Z"}	
{"epoch": 15, "step": 10	560, "val_loss": 0.7071164020254642, "v	val_acc": 0.756329
, "timestamp": "2025-10-	och_summary", "logger": "hw04.training" 05T02:39:50.385917Z"}	, "level": "Inlo"
{"event": "Finished asyn	c_save (blocking + background). Time ta	ken: 0.507577s. d
irectory=/work/hw04/chec		d dono Timo tako
n: 0.422445s."}	hread=async_save] Background save threa	
{"epoch": 16, "step": 11	264, "val_loss": 0.6119468215900131, "v	
5316455697, "event": "ep , "timestamp": "2025-10-	och_summary", "logger": "hw04.training"	', "level": "info"
	968, "val_loss": 0.5802336259733273, "v	al_acc": 0.801424
0506329114, "event": "ep	och_summary", "logger": "hw04.training"	', "level": "info"
, "timestamp": "2025-10-	05T02:45:14.1323292"} 672, "val_loss": 0.5539602588249158, "v	ral acc": 0 815466
7721518988, "event": "ep	och_summary", "logger": "hw04.training"	
, "timestamp": "2025-10-		3 " 0 000507
	376, "val_loss": 0.5059745707843877, "v och_summary", "logger": "hw04.training"	
, "timestamp": "2025-10-	05T02:50:45.324890Z"}	
	king save. Time taken: 0.045058s. Conti	nuing background
	points/best_state_epoch_20."} 080, "val_loss": 0.5034029578106313, "v	ral acc": 0.824960
4430379747, "event": "ep	och_summary", "logger": "hw04.training"	
, "timestamp": "2025-10-		.l.a 0 EC110Ea al
	<pre>c_save (blocking + background). Time ta kpoints/best_state_epoch_20"}</pre>	iken: 0.5611958. a
{"event": "[process=0][t	hread=async_save] Background save threa	d done. Time take
n: 0.509544s."}	784, "val_loss": 0.4975973575175563, "v	0 020002
9873417721, "event": "ep	och_summary", "logger": "hw04.training"	', "level": "info"
, "timestamp": "2025-10-	05T02:55:42.652465Z"}	
{"epoch": 22, "step": 15	488, "val_loss": 0.5027272561682931, "v och_summary", "logger": "hw04.training"	val_acc": 0.830300
, "timestamp": "2025-10-	05T02:57:59.114260Z"}	, level : IIIIO
{"epoch": 23, "step": 16	192, "val_loss": 0.5082427591462678, "v	al_acc": 0.827136
0759493671, "event": "ep , "timestamp": "2025-10-	och_summary", "logger": "hw04.training"	', "level": "info"
	896, "val_loss": 0.4491530262593982, "v	al_acc": 0.842167
7215189873, "event": "ep	och_summary", "logger": "hw04.training"	
, "timestamp": "2025-10-	05T03:02:49.746914Z"} king save. Time taken: 0.070533s. Conti	nuing background
save to /work/hw04/check	points/best state epoch 25."}	
{"epoch": 25, "step": 17	600, "val_loss": 0.45212958206104326, "	val_acc": 0.84276
", "timestamp": "2025-10	<pre>poch_summary", "logger": "hw04.training -05T03:05:19.481743Z"}</pre>	, "level": "info

Oct 08, 2025 16:33	train_cifar10.json	Page 3/4
{"event": "Finished async_save irectory=/work/hw04/checkpoints		Time taken: 0.538781s. d
{"event": "[process=0][thread=a		ve thread done. Time take
n: 0.454450s."} {"epoch": 26, "step": 18304, "v		
90506329114, "event": "epoch_su ", "timestamp": "2025-10-05T03:	mmary", "logger": "hw04. 08:14.108608Z"}	training", "level": "info
{"epoch": 27, "step": 19008, "v 68987341772, "event": "epoch_su	al_loss": 0.438959172820	74315, "val_acc": 0.85027
", "timestamp": "2025-10-05T03:	10:33.586123Z"}	
{"epoch": 28, "step": 19712, "v 1518987342, "event": "epoch_sum	mary", "logger": "hw04.t:	
<pre>, "timestamp": "2025-10-05T03:1 {"epoch": 29, "step": 20416, "v</pre>		7291, "val_acc": 0.857594
9367088608, "event": "epoch_sum , "timestamp": "2025-10-05T03:1		raining", "level": "info"
{"event": "Finished blocking sa save to /work/hw04/checkpoints/	ve. Time taken: 0.114508	s. Continuing background
{"epoch": 30, "step": 21120, "v	ral_loss": 0.439604811464	
1329113924, "event": "epoch_sum , "timestamp": "2025-10-05T03:1		raining", "level": "info"
{"event": "Finished async_save irectory=/work/hw04/checkpoints	(blocking + background).	Time taken: 0.500118s. d
{"epoch": 31, "step": 21824, "v	al_loss": 0.417560879376	
05696202531, "event": "epoch_su ", "timestamp": "2025-10-05T03:		training", "level": "info
{"epoch": 32, "step": 22528, "v 4683544303, "event": "epoch_sum		
, "timestamp": "2025-10-05T03:2 {"epoch": 33, "step": 23232, "v	2:51.6489317"}	_
39240506329, "event": "epoch_su	mmary", "logger": "hw04.	training", "level": "info
", "timestamp": "2025-10-05T03: {"epoch": 34, "step": 23936, "v		4268, "val acc": 0.862737
3417721519, "event": "epoch_sum , "timestamp": "2025-10-05T03:2	mary", "logger": "hw04.t:	
{"epoch": 35, "step": 24640, "v	ral_loss": 0.416779228026	35387, "val_acc": 0.86115
50632911392, "event": "epoch_su ", "timestamp": "2025-10-05T03:	30:31.283716Z"}	
{"event": "Finished async_save irectory=/work/hw04/checkpoints		Time taken: 0.437339s. d
{"epoch": 36, "step": 25344, "v 17088607594, "event": "epoch_su	al_loss": 0.4113709777593	36127, "val_acc": 0.86056
", "timestamp": "2025-10-05T03:	33:27.668778Z"}	_
{"epoch": 37, "step": 26048, "v 29746835443, "event": "epoch_su		
", "timestamp": "2025-10-05T03: {"epoch": 38, "step": 26752, "v		8129. "val acc": 0.865110
7594936709, "event": "epoch_sum	mary", "logger": "hw04.t:	raining", "level": "info"
<pre>, "timestamp": "2025-10-05T03:3 {"epoch": 39, "step": 27456, "v</pre>	ral_loss": 0.403041482914	
9620253164, "event": "epoch_sum , "timestamp": "2025-10-05T03:4		raining", "level": "info"
{"event": "Finished blocking sa save to /work/hw04/checkpoints/		s. Continuing background
{"epoch": 40, "step": 28160, "v	ral_loss": 0.404538533166	
594936709, "event": "epoch_summ"	:35.801138Z " }	_
{"event": "Training finished. G ng", "level": "info", "timestam	p": "2025-10-05T03:43:35	.804946Z"}
{"settings": {"debug": false, " "layer_depths": [16, 32, 64], "	random_seed": 31415, "mod	del": {"input_depth": 3,
"data": {"batch_size": 64, "va	lidation_size": 5000, "sl	huffle_buffer": 10000, "c
<pre>ifar100": false}, "training": { _decay": 0.0001, "log_interval" ixPath('hw04/checkpoints_cifar1</pre>	: 100, "final_test": true	e, "checkpoint_dir": "Pos
<pre>ixPath('hw04/checkpoints_cifar1 4/artifacts')", "figsize": [5,</pre>	0')"}, "plotting": {"out] 3], "dpi": 200}}, "event	<pre>put_dir": "PosixPath('hw0 ": "Settings loaded", "lo</pre>
<pre>4/artifacts')", "figsize": [5, gger": "hw04", "level": "info", {"event": "Variant folder /root</pre>	"timestamp": "2025-10-03	8T20:07:20.965938Z"}
_info.json"}		no to a no databet

Oct 08, 2025 16:33	train_cifar10.json	Page 4/4
{"event": "Generating data	aset cifar10 (/root/tensorflow_dataset	s/cifar10/3.0.2)"
nto /root/tensorflow_datas	ps://www.cs.toronto.edu/~kriz/cifar-1 sets/downloads/cifar10/cs.toronto.edu_ kzyKjRCuo161V8Wc6C7s.tar.gz.tmp.f8979	kriz_cifar-10-bin
<pre>2/cifar10-train.tfrecord*. {"event": "Done writing /r 2/cifar10-test.tfrecord*.</pre>	coot/tensorflow_datasets/cifar10/incom . Number of examples: 50000 (shards: [coot/tensorflow_datasets/cifar10/incom . Number of examples: 10000 (shards: [1 . data.Dataset reading 1 files located i . 10/3.0.2."	50000])"} plete.DJLYYH_3.0. 0000])"}
{"event": "Constructing tf orflow_datasets/cifar10/3.	<pre>f.data.Dataset cifar10 for split train 0.2"}</pre>	, from /root/tens
	nfo from /root/tensorflow_datasets/cif data.Dataset reading 1 files located i 10/3.0.2."}	
	f.data.Dataset cifar10 for split test,	from /root/tenso
{"event": "Unable to inition libtpu.so: cannot open {"num_params": 272938, "ex	lalize backend 'tpu': INTERNAL: Failed shared object file: No such file or d vent": "Model created", "logger": "hw0	irectory"}
o", "timestamp": "2025-10- {"event": "Starting final tamp": "2025-10-08T20:08:0 {"event": "orbax-checkpoir	testing", "logger": "hw04", "level 06.201148Z"}	": "info", "times
<pre>"event": "Created BasePy1 pytree_metadata_options=F metadata_store=<orbax.chec 0x7f2ffefd9b90="" at="">, enabl 6000000000 (89.4 GiB), res {"event": "[thread=MainThr</orbax.chec></pre>	TreeCheckpointHandler: use_ocdbt=True, PyTreeMetadataOptions(support_rich_typ ckpointsrc.metadata.array_metadata_s le_pinned_host_transfer=False, save_co store_concurrent_bytes: 96000000000 (8 read] Failed to get flag value for EXP	es=False), array_ tore.Store object ncurrent_bytes: 9 9.4 GiB)"}
arrier_sync_fn. <locals>.<lr>y_host=0 for async checkpo</lr></locals>	read=MainThread] Using barrier_sync_fn Lambda> at 0x7f2f7a966160> timeout: 60	0 secs and primar
	ax/checkpoint/read/gbytes_per_sec: 0 Bed: 296 milliseconds) (per-host)"}	ytes/s (total gby
<pre>ints_cifar10/best_state_er {"test_loss": 1.4637850788</pre>	ring checkpoint in 0.30 seconds from / ooch_40."} 3748188, "test_acc": 0.857683121019108 1.training", "level": "info", "timesta	3, "event": "test
	3748188, "test_acc": 0.857683121019108 : "hw04", "level": "info", "timestamp"	

Loss and Accuracy Graphs for CIFAR-10 Training




```
train cifar100.json
 Oct 08, 2025 16:42
                                                                         Page 1/4
    I deleted all the training log (train loss) since there were too many and ju
st leave the validation loss log
    It should be easier to see the train/validation loss graph to see the traini
ng summary
    I see some overfitting from the validation loss graphs.
    Stronger augmentation and Dropout could be helpful
    Test set result is at the very bottom
    I tried to use renet-34 like structure but with less layer depths.
    Training took about 7 hours in my cpu.
                2025-10-08T02:04:23.076490Z
    Started:
    Ended:
                2025-10-08T09:18:38.831492Z
{"settings": {"debug": false, "random_seed": 31415, "model": {"input_depth": 3,
"layer_depths": [32, 64, 128, 256], "blocks_per_stage": [3, 4, 6, 3], "num_class
es": 100}, "data": {"batch_size": 64, "validation_size": 5000, "shuffle_buffer":
10000, "cifar100": true}, "training": {"num_epochs": 40, "learning_rate": 0.001
, "weight_decay": 0.0001, "log_interval": 100, "final_test": false, "checkpoint_
dir": "PosixPath('hw04/checkpoints')"}, "plotting": {"output_dir": "PosixPath('h
w04/artifacts')", "figsize": [5, 3], "dpi": 200}, "event": "Settings loaded", "logger": "hw04", "level": "info", "timestamp": "2025-10-08T02:03:14.897531Z"}
{"event": "Variant folder /root/tensorflow_datasets/cifar100/3.0.2 has no datase
t_info.json"}
{"event": "Generating dataset cifar100 (/root/tensorflow_datasets/cifar100/3.0.2
{"event": "Downloading https://www.cs.toronto.edu/~kriz/cifar-100-binary.tar.gz
into /root/tensorflow_datasets/downloads/cifar100/cs.toronto.edu_kriz_cifar-100-
binaryzK0jb7CkNxmV4pH2clu5WdAlIotsP1ZhrMxx9-DELEk.tar.gz.tmp.05f7acbe3c27433ab9d
9a7be715a262a..."}
{"event": "Done writing /root/tensorflow_datasets/cifar100/incomplete.CJ1809_3.0
.2/cifar100-train.tfrecord*. Number of examples: 50000 (shards: [50000])"}
{"event": "Done writing /root/tensorflow datasets/cifar100/incomplete.CJ1809 3.0
.2/cifar100-test.tfrecord*. Number of examples: 10000 (shards: [10000])"}
{"event": "Creating a tf.data.Dataset reading 1 files located in folders: /root/
tensorflow datasets/cifar100/3.0.2."}
{"event": "Constructing tf.data.Dataset cifar100 for split train, from /root/ten
sorflow_datasets/cifar100/3.0.2"}
{"event": "Load dataset info from /root/tensorflow_datasets/cifar100/3.0.2"}
{"event": "Creating a tf.data.Dataset reading 1 files located in folders: /root/
tensorflow_datasets/cifar100/3.0.2."}
{"event": "Constructing tf.data.Dataset cifar100 for split test, from /root/tens
orflow datasets/cifar100/3.0.2"}
{"event": "Unable to initialize backend 'tpu': INTERNAL: Failed to open libtpu.s
o: libtpu.so: cannot open shared object file: No such file or directory"}
{"num_params": 5352484, "event": "Model created", "logger": "hw04", "level": "in
fo", "timestamp": "2025-10-08T02:04:23.076490Z"}
{"epoch": 1, "step": 704, "val_loss": 3.976373268079154, "val_acc": 0.1097705696
2025317, "event": "epoch_summary", "logger": "hw04.training", "level": "info", "
timestamp": "2025-10-08T02:12:48.870353Z"}
{"epoch": 2, "step": 1408, "val_loss": 3.725985680954366, "val_acc": 0.164556962
02531644, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-08T02:23:02.027043Z"}
{"epoch": 3, "step": 2112, "val_loss": 3.4336151533488986, "val_acc": 0.22329905
06329114, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-08T02:35:52.401048Z"}
{"epoch": 4, "step": 2816, "val_loss": 3.315141044085539, "val_acc": 0.244066455
69620253, "event": "epoch_summary", "logger": "hw04.training", "level": "info",
"timestamp": "2025-10-08T02:49:28.374315Z"}
{"event": "Finished blocking save. Time taken: 0.405937s. Continuing background
save to /work/hw04/checkpoints/best_state_epoch_5."}
{"epoch": 5, "step": 3520, "val_loss": 3.023668651339374, "val_acc": 0.341969936
7088608, "event": "epoch_summary", "logger": "hw04.training", "level": "info", "
timestamp": "2025-10-08T03:03:20.608685Z"}
{"epoch": 6, "step": 4224, "val_loss": 2.891840086707586, "val_acc": 0.368473101
2658228, "event": "epoch_summary", "logger": "hw04.training", "level": "info", "
timestamp": "2025-10-08T03:15:15.281783Z"}
```

Oct 08, 2025 16:42	train_cifar100.json	Page 2/4
1898733, "event": "e	: 4928, "val_loss": 2.80468063716647, "val_acc": 0 epoch_summary", "logger": "hw04.training", "level" 0-08T03:30:54.135918Z"}	
{"epoch": 8, "step": 962025317, "event":	: 5632, "val_loss": 2.8846074689792682, "val_acc": "epoch_summary", "logger": "hw04.training", "leve	
{"epoch": 9, "step": 8734177, "event": "6	-10-08T03:43:39.004092Z"} : 6336, "val_loss": 2.644265703008145, "val_acc": @ epoch_summary", "logger": "hw04.training", "level"	0.442840189 : "info", "
{"event": "Finished	D-08T03:57:08.722001Z"} blocking save. Time taken: 0.287610s. Continuing Deckpoints/best_state_epoch_10."}	packground
{"epoch": 10, "step' 012658228, "event":	": 7040, "val_loss": 2.5681378705592097, "val_acc" "epoch_summary", "logger": "hw04.training", "leve	: 0.4622231 l": "info",
{"epoch": 11, "step'	-10-08T04:11:06.506207Z"} ": 7744,	0.47072784 l": "info",
"timestamp": "2025- {"epoch": 12, "step'	-10-08T04:24:44.379628Z"} ": 8448, "val_loss": 2.5028848678250855, "val_acc"	: 0.4827927
, "timestamp": "2025	: "epoch_summary", "logger": "hw04.training", "levo 5-10-08T04:37:42.487969Z"} ": 9152, "val_loss": 2.4689806473406057, "val_acc"	
0253164556, "event": , "timestamp": "2025	: "epoch_summary", "logger": "hw04.training", "leve 5-10-08T04:51:23.553805Z"}	el": "info"
164556962, "event":	": 9856, "val_loss": 2.3596031695981567, "val_acc" "epoch_summary", "logger": "hw04.training", "leve -10-08T05:05:20.270818Z"}	: 0.5245253 l": "info",
save to /work/hw04/d	blocking save. Time taken: 0.353670s. Continuing lockeckpoints/best_state_epoch_15."} ": 10560, "val_loss": 2.3550007765806176, "val_acc	-
582278481, "event": "timestamp": "2025-	<pre>"epoch_summary", "logger": "hw04.training", "level -10-08T05:18:59.185930Z"}</pre>	l": "info",
835443038, "event":	": 11264, "val_loss": 2.332110721853715, "val_acc" "epoch_summary", "logger": "hw04.training", "leve: -10-08T05:31:56.445378Z"}	
{"epoch": 17, "step" 5316455697, "event":	": 11968, "val_loss": 2.3060759547390517, "val_acc : "epoch_summary", "logger": "hw04.training", "leve 5-10-08T05:42:01.686646Z"}	
{"epoch": 18, "step" ": "train_iter", "lo	": 12000, "loss": 2.1541953086853027, "acc": 0.546 ogger": "hw04.training", "level": "info", "timesta	375, "event mp": "2025-
: "train_iter", "log	": 12100, "loss": 1.9982845783233643, "acc": 0.593 gger": "hw04.training", "level": "info", "timestam	
	l2"} ": 12200, "loss": 1.9845942258834839, "acc": 0.562 ger": "hw04.training", "level": "info", "timestamp	
-08T05:44:54.0064602 {"epoch": 18, "step"	½"} ": 12300, "loss": 2.2072534561157227, "acc": 0.593	75, "event"
0-08T05:46:06.017281	gger": "hw04.training", "level": "info", "timestam Z"} ": 12400, "loss": 1.6721937656402588, "acc": 0.75,	
train_iter", "logger 8T05:47:17.964478Z"]	r": "hw04.training", "level": "info", "timestamp":	"2025-10-0
train_iter", "logger 8T05:48:27.335253Z"]	r": "hw04.training", "level": "info", "timestamp":	"2025-10-0
	": 12600, "loss": 1.895101547241211, "acc": 0.6406: gger": "hw04.training", "level": "info", "timestam 72"}	
{"epoch": 18, "step' 329113924, "event":	": 12672, "val_loss": 2.2927366072618507, "val_acc" epoch_summary", "logger": "hw04.training", "leve: -10-08T05:50:42.2736082"}	": 0.553006 l": "info",
{"epoch": 19, "step' 55696202, "event": '	": 13376, "val_loss": 2.25943695442586, "val_acc": "epoch_summary", "logger": "hw04.training", "level	
{"event": "Finished	<pre>10-08T06:02:30.057835Z"} blocking save. Time taken: 0.302445s. Continuing l checkpoints/best_state_epoch_20."}</pre>	packground
{"epoch": 20, "step' 0759493671, "event":	": 14080, "val_loss": 2.2340246137184434, "val_acc : "epoch_summary", "logger": "hw04.training", "levo	": 0.577136 el": "info"
, timestamp": "2023	5-10-08T06:13:47.481533Z"}	

Oct 08, 2025 16:42	train_cifar100.json	Page 3/4
{"epoch": 21, "step": 14784, "va	al_loss": 2.243983276282685, "val_acc":	0.5674446
	ary", "logger": "hw04.training", "level	L": "info",
"timestamp": "2025-10-08T06:23:	34.818738Z"}	
{"epoch": 22, "step": 15488, "va	al_loss": 2.2258135306684275, "val_acc'	': 0.579707
	mary", "logger": "hw04.training", "leve	el": "info"
, "timestamp": "2025-10-08T06:32		. 0 5707102
[{ "epoch": 23, "Step": 16192, "Va	ll_loss": 2.222693950315065,	". "info"
"timestamp": "2025-10-08T06:42:	14.8728087"}	
{"epoch": 24, "step": 16896, "va	al_loss": 2.243938494332229, "val_acc":	0.5801028
481012658, "event": "epoch_summa	ary", "logger": "hw04.training", "level	l": "info",
"timestamp": "2025-10-08T06:52:	52.934472Z " }	
	re. Time taken: 0.174913s. Continuing k	packground
save to /work/hw04/checkpoints/b		. 0 5042562
	al_loss": 2.224066859559168, "val_acc": ry", "logger": "hw04.training", "level"	
"timestamp": "2025-10-08T07:02:5		• 11110 ,
	al_loss": 2.2172716629656057, "val_acc'	. 0.590981
	mary", "logger": "hw04.training", "leve	
, "timestamp": "2025-10-08T07:13		-
	al_loss": 2.2137932611417166, "val_acc'	
	nary", "logger": "hw04.training", "leve	el": "info"
, "timestamp": "2025-10-08T07:22		
	al_loss": 2.216762476329562, "val_acc":	
"timestamp": "2025-10-08T07:32:	ary", "logger": "hw04.training", "level 24 9582807":	mio'
	al_loss": 2.2051513798629183, "val_acc'	': 0.598694
	nary", "logger": "hw04.training", "leve	
, "timestamp": "2025-10-08T07:42		
	al_loss": 2.2079105467735967, "val_acc'	
	ary", "logger": "hw04.training", "level	L": "info",
"timestamp": "2025-10-08T07:52:		100641
irectory=/work/hw04/checkpoints/	(blocking + background). Time taken: 1.	.100041S. a
	sync_save] Background save thread done.	. Time take
n: 0.928715s."}	• - •	
{"epoch": 31, "step": 21824, "va	al_loss": 2.1937194051621836, "val_acc'	': 0.605023
	mary", "logger": "hw04.training", "leve	el": "info"
, "timestamp": "2025-10-08T08:02	::25.8950552"} al_loss": 2.1885239006597783, "val_acc'	· n 600068
	nary", "logger": "hw04.training", "leve	
, "timestamp": "2025-10-08T08:12		
{"epoch": 33, "step": 23232, "va	al loss": 2.186336153670202, "val acc":	: 0.6087816
455696202, "event": "epoch_summa	ary", "logger": "hw04.training", "level	L": "info",
"timestamp": "2025-10-08T08:23:		
	al_loss": 2.1903039745137662, "val_acc'	
5569620253, "event": "epoch_summ , "timestamp": "2025-10-08T08:31	nary", "logger": "hw04.training", "leve	er.: "INIO"
	re. Time taken: 0.171701s. Continuing k	packground
save to /work/hw04/checkpoints/b		
{"epoch": 35, "step": 24640, "va	al loss": 2.183525858046133, "val acc":	: 0.6101661
392405063, "event": "epoch_summa	ary", "logger": "hw04.training", "level	L": "info",
"timestamp": "2025-10-08T08:39:	03.468770Z " }	
	al_loss": 2.197526878948453, "val_acc":	
	ry", "logger": "hw04.training", "level	": "info",
"timestamp": "2025-10-08T08:46:	58.6799132"} al_loss": 2.1875499139858197, "val_acc'	. 0.614912
		el": "info"
, "timestamp": "2025-10-08T08:54	!:52.045278Z " }	
{"epoch": 38, "step": 26752, "va	al_loss": 2.171840216540083, "val_acc":	
	ary", "logger": "hw04.training", "level	l": "info",
"timestamp": "2025-10-08T09:02:		. 0 601005
	al_loss": 2.1635287939747676, "val_acc'	
, "timestamp": "2025-10-08T09:10	nary", "logger": "hw04.training", "leve	=TITO
	re. Time taken: 0.342879s. Continuing k	packground
save to /work/hw04/checkpoints/b		
{"epoch": 40, "step": 28160, "va	al_loss": 2.158977393862567, "val_acc":	: 0.6214398
734177216, "event": "epoch_summa	ary", "logger": "hw04.training", "level	l": "info",

train cifar100.json Oct 08, 2025 16:42 Page 4/4 "timestamp": "2025-10-08T09:18:38.831492Z"} {"num params": 5352484, "event": "Model created", "logger": "hw04", "level": "in fo", "timestamp": "2025-10-08T19:58:42.569048Z"} {"event": "Starting final testing...", "logger": "hw04", "level": "info", "times tamp": "2025-10-08T19:58:42.898115Z"} {"event": "orbax-checkpoint version: 0.11.25"} {"event": "Created BasePyTreeCheckpointHandler: use_ocdbt=True, use_zarr3=False, pytree_metadata_options=PyTreeMetadataOptions(support_rich_types=False), array_ metadata_store=<orbax.checkpoint._src.metadata.array_metadata_store.Store object at 0x7f589abd6790>, enable_pinned_host_transfer=False, save_concurrent_bytes: 9 6000000000 (89.4 GiB), restore_concurrent_bytes: 96000000000 (89.4 GiB)"} {"event": "[thread=MainThread] Failed to get flag value for EXPERIMENTAL_ORBAX_U SE_DISTRIBUTED_PROCESS_ID."} {"event": "[process=0][thread=MainThread] Using barrier_sync_fn: <function get_b arrier_sync_fn.<locals>.<lambda> at 0x7f5816f520c0> timeout: 600 secs and primar y_host=0 for async checkpoint writes"} {"event": "Restoring checkpoint from /work/hw04/checkpoints/best_state_epoch_40. {"event": "[process=0] /jax/checkpoint/read/gbytes_per_sec: 0 Bytes/s (total gby tes: 20.4 MiB) (time elapsed: 549 milliseconds) (per-host)"} {"event": "Finished restoring checkpoint in 0.56 seconds from /work/hw04/checkpo ints/best_state_epoch_40."} {"test_loss": 2.175596616830036, "test_acc": 0.6136544585987261, "event": "test_ results", "logger": "hw04.training", "level": "info", "timestamp": "2025-10-08T1 9:59:12.667384Z"} {"test_loss": 2.175596616830036, "test_acc": 0.6136544585987261, "event": "Final Test Results", "logger": "hw04", "level": "info", "timestamp": "2025-10-08T19:5 9:12.705750Z"}

Loss and Accuracy Graphs for CIFAR-100 Training



```
pyproject.toml
 Sep 28, 2025 17:36
                                                                            Page 1/1
# pyproject.toml.jinja
[project]
name = "hw04"
version = "0.1.0"
description = "CIFARIO"
readme = "README.md"
authors = [
    { name = "Wongee (Freddy) Hong", email = "wongee.hong@cooper.edu" }
requires-python = ">=3.11"
dependencies = [
    "structlog",
   "numpy",
"tensorflow",
    "tensorflow_datasets",
    "pydantic-settings",
"matplotlib",
    "tqdm",
    "jax",
    "jaxlib",
    "flax",
"optax",
    "scikit-learn",
[project.scripts]
hw04 = "hw04:main"
[build-system]
requires = ["uv_build>=0.8.3,<0.9.0"]
build-backend = "uv_build"
```

```
Oct 04, 2025 17:22
                                       logging.py
                                                                        Page 1/2
import logging
import os
import sys
from pathlib import Path
import jax
import numpy as np
import structlog
class FormattedFloat(float):
    def __repr__(self) -> str:
        return f"{self:.4g}"
def custom_serializer_processor(logger, method_name, event_dict):
    for key, value in event_dict.items():
       if hasattr(value, "numpy"):
            value = value.numpy()
        if isinstance(value, jax.Array):
            value = np.array(value)
        if isinstance(value, (np.generic, np.ndarray)):
            value = value.item() if value.size == 1 else value.tolist()
        if isinstance(value, float):
            value = FormattedFloat(value)
        if isinstance (value, Path):
           value = str(value)
        event_dict[key] = value
    return event_dict
def configure_logging(log_dir: Path = Path("hw04/artifacts"), log_name: str = "train.jso
    log_dir.mkdir(parents=True, exist_ok=True)
    log_file = log_dir / log_name
    log_level = os.environ.get("LOG_LEVEL", "INFO").upper()
    shared_processors = [
        structlog.stdlib.add logger name,
        structlog.stdlib.add_log_level,
        structlog.stdlib.PositionalArgumentsFormatter(),
        structlog.processors.TimeStamper(fmt="iso"),
        structlog.processors.StackInfoRenderer(),
        structlog.processors.format_exc_info,
        structlog.processors.UnicodeDecoder(),
        custom_serializer_processor,
    structlog.configure(
       processors=shared_processors + [
            structlog.stdlib.ProcessorFormatter.wrap_for_formatter,
        logger_factory=structlog.stdlib.LoggerFactory(),
        wrapper_class=structlog.stdlib.BoundLogger,
        cache_logger_on_first_use=True,
    console_renderer = structlog.dev.ConsoleRenderer(
        colors=sys.stdout.isatty(),
        exception_formatter=structlog.dev.RichTracebackFormatter(),
    console_handler = logging.StreamHandler(sys.stdout)
    console_handler.setFormatter(
        structlog.stdlib.ProcessorFormatter(
                structlog.stdlib.ProcessorFormatter.remove_processors_meta,
                console_renderer
```

```
Oct 04, 2025 17:22
                                     logging.py
                                                                       Page 2/2
  file_renderer = structlog.processors.JSONRenderer()
   file_handler = logging.FileHandler(log_file, mode="w")
  file_handler.setFormatter(
       structlog.stdlib.ProcessorFormatter(
          processors=[
               structlog.stdlib.ProcessorFormatter.remove_processors_meta,
               file renderer
  root_logger = logging.getLogger()
  root_logger.addHandler(console_handler)
  root_logger.addHandler(file_handler)
  root_logger.setLevel(log_level)
  logging.getLogger("matplotlib").setLevel(logging.WARNING)
  logging.getLogger("PIL").setLevel(logging.WARNING)
  return log_file
```

```
config.py
 Oct 08, 2025 16:42
                                                                           Page 1/1
from pathlib import Path
from typing import Tuple
from pydantic import BaseModel
from pydantic_settings import BaseSettings
class ModelSettings(BaseModel):
    input_depth: int = 3
    layer_depths: list[int] = [32, 64, 128, 256]
    blocks_per_stage: list[int] = [3, 4, 6, 3]
    num_classes: int = 100
class DataSettings(BaseModel):
   batch_size: int = 64
    validation_size: int = 5000
    shuffle_buffer: int = 10000
    cifar100: bool = True
class TrainingSettings(BaseModel):
    """Settings for model training."""
    num_epochs: int = 40
    learning_rate: float = 0.001
    weight_decay: float = 1e-4
                                                   # L2 penalty
    log_interval: int = 100
    final_test: bool = True
    checkpoint_dir: Path = Path("hw04/checkpoints")
class PlottingSettings(BaseModel):
    """Settings for logging and saving artifacts."""
    output_dir: Path = Path("hw04/artifacts")
    figsize: Tuple[int, int] = (5, 3)
    dpi: int = 200
class AppSettings(BaseSettings):
    """Main application settings."""
    debug: bool = False
    random_seed: int = 31415
    model: ModelSettings = ModelSettings()
    data: DataSettings = DataSettings()
    training: TrainingSettings = TrainingSettings()
    plotting: PlottingSettings = PlottingSettings()
def load_settings() -> AppSettings:
    """Load application settings."""
    return AppSettings()
```

```
Oct 08, 2025 16:47
                                          init
                                               .py
                                                                         Page 1/2
import optax
import structlog
from flax import nnx
import jax
import pathlib as Path
import orbax.checkpoint as ocp
from .config import load settings
from .logging import configure_logging
from .model import Classifier
from .training import train, test_evaluation, load_checkpoint
from .data import load_CIFAR10, load_CIFAR100
def main() -> None:
    settings = load_settings()
    log_file = configure_logging()
    log = structlog.get_logger()
    log.info("Settings loaded", settings=settings.model_dump())
   print (f"Logs are being saved to {log_file}")
    if settings.data.cifar100:
        ds_train, ds_val, ds_test = load_CIFAR100(
       batch_size=settings.data.batch_size,
        validation_size=settings.data.validation_size,
    else:
        ds_train, ds_val, ds_test = load_CIFAR10(
            batch_size=settings.data.batch_size,
            validation_size=settings.data.validation_size,
    rngs = nnx.Rngs(params=settings.random_seed)
    model = Classifier(
        rngs=rngs,
        input_depth=settings.model.input_depth,
        layer depths=settings.model.layer depths.
        blocks_per_stage=settings.model.blocks_per_stage,
       layer_kernel_sizes=[(3,3)] * len(settings.model.layer_depths),
       num classes=settings.model.num classes,
    params = nnx.state(model, nnx.Param)
    num_params = sum(p.size for p in jax.tree_util.tree_leaves(params))
    log.info("Model created", num_params=num_params)
    # LR schedule and optimizer
    train_size
                 = 50000
    steps_per_epoch = train_size // settings.data.batch_size
                  = settings.training.num_epochs * steps_per_epoch
    lr_schedular = optax.schedules.cosine_decay_schedule(
        init_value=settings.training.learning_rate,
        decay_steps=decay_steps,
    optimizer = nnx.Optimizer(
        model,
        optax.adamw(
            learning_rate=lr_schedular,
            weight_decay=settings.training.weight_decay,
        wrt=nnx.Param,
    if settings.training.final_test:
       log.info("Starting final testing...")
        model_kwargs = dict(
            input_depth=settings.model.input_depth,
            layer_depths=settings.model.layer_depths,
            blocks_per_stage=settings.model.blocks_per_stage,
            layer_kernel_sizes=[(3, 3)] * len(settings.model.layer_depths),
```

```
Oct 08, 2025 16:47
                                         init
                                                .py
                                                                         Page 2/2
           num_classes=settings.model.num_classes,
       model = load_checkpoint(
           Classifier,
           model_kwargs
       test_loss, test_acc = test_evaluation(model, ds_test, rngs)
       log.info("Final Test Results", test_loss=test_loss, test_acc=test_acc)
       _ = train(model, optimizer, ds_train, ds_val, rngs)
```

```
Oct 08, 2025 16:47
                                       model.pv
                                                                        Page 1/3
# Deleted dropout to implement checkpoint
import jax
import jax.numpy as jnp
from flax import nnx
class Conv2d(nnx.Module):
    def init (
        self,
        in_channels: int,
        out channels: int,
        kernel size,
        strides=(1, 1),
        padding="SAME",
        use_bias=True,
        rngs: nnx.Rngs,
   ):
        self.conv = nnx.Conv(
            in_channels, out_channels, kernel_size,
            strides=strides, padding=padding, use_bias=use_bias, rngs=rngs
    def __call__(self, x, *, rngs: nnx.Rngs):
        x = self.conv(x)
        return x
class ResidualBlock (nnx.Module):
    """Basic residual block."""
    def __init__(
        self,
        in channels: int.
        out_channels: int,
        stride=(1, 1),
        rngs: nnx.Rngs,
   ):
        self.norm1 = nnx.GroupNorm(num_features=in_channels, num_groups=8, rngs=
rngs)
        self.conv1 = Conv2d(
            in_channels, out_channels, (3, 3),
            strides=stride, rngs=rngs,
        self.norm2 = nnx.GroupNorm(num_features=out_channels, num_groups=8, rngs
=rngs)
        self.conv2 = Conv2d(
            out_channels, out_channels, (3, 3),
            strides=(1, 1), rngs=rngs,
        self.shortcut = (
            Conv2d(
                in_channels, out_channels, (1, 1),
                strides=stride, rngs=rngs,
            if in_channels != out_channels or stride != (1, 1)
            else None
    def __call__(self, x, *, rngs: nnx.Rngs):
       out = self.norm1(x)
        out = nnx.relu(out)
       out = self.conv1(out, rngs=rngs)
        out = self.norm2(out)
       out = nnx.relu(out)
        out = self.conv2(out, rngs=rngs)
```

```
model.pv
 Oct 08, 2025 16:47
                                                                           Page 2/3
        identity = x if self.shortcut is None else self.shortcut(x, rngs=rngs)
        return out + identity
class ResidualStage(nnx.Module):
    def __init__(
        self,
        in_channels: int,
        out channels: int,
        num_blocks: int,
        stride=(1, 1),
        rngs: nnx.Rngs,
   ):
        blocks = []
        blocks.append(
            ResidualBlock (
                in channels.
                out_channels,
                stride=stride.
                rngs=rngs,
        # Rest keep stride = (1,1)
        for _ in range(1, num_blocks):
            blocks.append(
                ResidualBlock (
                     out_channels,
                     out_channels,
                     stride=(1, 1),
                     rngs=rngs,
        self.blocks = nnx.List(blocks)
    def __call__(self, x, *, rngs: nnx.Rngs):
    for block in self.blocks:
            x = block(x, rngs=rngs)
        return x
class Classifier(nnx.Module):
    """Residual network classifier for MNIST."""
    def __init__(
        self,
        input_depth: int,
        layer_depths: list[int],
        blocks_per_stage,
        layer_kernel_sizes: list[tuple[int, int]],
        num_classes: int,
        rngs: nnx.Rngs,
   ):
        assert len(layer_depths) == len(layer_kernel_sizes), \
             "layer_depths and layer_kernel_sizes must match in length"
        self.init_conv = Conv2d(input_depth, layer_depths[0],
                                  kernel_size=layer_kernel_sizes[0],
                                  strides=(1, 1), rngs=rngs)
        # Build stages
        stages = []
        self.blocks_per_stage = blocks_per_stage
        in_ch = layer_depths[0]
        for i, out_ch in enumerate(layer_depths):
            stride = (2, 2) if i > 0 else (1, 1) # downsample at stage boundari
es
            num_blocks = (self.blocks_per_stage[i]
                       if self.blocks_per_stage is not None
                       else 1)
            stage = ResidualStage(
```

```
model.py
Oct 08, 2025 16:47
                                                                          Page 3/3
               in_channels=in_ch,
               out_channels=out_ch,
               num_blocks=num_blocks,
               stride=stride,
               rngs=rngs,
           stages.append(stage)
           in_ch = out_ch
       self.stages = nnx.List(stages)
       # Final classifier head
       self.fc = nnx.Linear(in_ch, num_classes, rngs=rngs)
   def __call__(self, x, *, rngs: nnx.Rngs):
       x = self.init_conv(x, rngs=rngs)

for stage in self.stages:
           x = stage(x, rngs=rngs)
       x = jnp.mean(x, axis=(1, 2))
       # Final logits
       return self.fc(x)
```

```
training.py
 Oct 08, 2025 16:46
                                                                        Page 1/3
import jax
import jax.numpy as jnp
import optax
from flax import nnx
import matplotlib.pyplot as plt
import structlog
import orbax.checkpoint as ocp
from pathlib import Path
import os
from .config import load_settings
log = structlog.get_logger()
def cross_entropy_loss(logits, labels, num_classes, smoothing = 0.1):
    one_hot = jax.nn.one_hot(labels, num_classes)
    smoothed = one_hot * (1 - smoothing) + smoothing / num_classes # Implemeted
label smoothing for CIFAR-100 training.
   loss = optax.softmax_cross_entropy(logits, smoothed).mean()
    return loss
def compute_accuracy(logits, labels):
    preds = jnp.argmax(logits, axis=-1)
    return jnp.mean(preds == labels)
def _loss_fn(model, batch, rngs):
    settings = load_settings()
    images, labels = batch
   labels = labels.ravel()
   logits = model(images, rngs=rngs)
    loss = cross_entropy_loss(logits, labels, settings.model.num_classes)
   return loss, logits
@nnx.jit
def train step (model, optimizer, batch, rngs):
    grad_fn = nnx.value_and_grad(_loss_fn, has_aux=True)
    (loss, logits), grads = grad_fn(model, batch, rngs)
    optimizer.update(model, grads)
    return loss, logits
def eval_step(model, batch, rngs):
    loss, logits = _loss_fn(model, batch, rngs)
    return loss, logits
def evaluate(model, dataset, rngs):
    total_loss, total_acc, n_batches = 0.0, 0.0, 0
    for batch in dataset.as_numpy_iterator():
       loss, logits = eval_step(model, batch, rngs)
        _, labels = batch
       labels = labels.ravel()
       acc = compute_accuracy(logits, labels)
       loss = float(loss)
       acc = float(acc)
       total_loss += loss
       total_acc += float(acc)
       n_batches += 1
    return total_loss / max(n_batches, 1), total_acc / max(n_batches, 1)
def train(model, optimizer, train_ds, val_ds, rngs):
    settings = load_settings()
    output_dir = settings.plotting.output_dir
    output_dir.mkdir(parents=True, exist_ok=True)
    checkpoint_dir = settings.training.checkpoint_dir.resolve()
    checkpoint_dir.mkdir(parents=True, exist_ok=True)
```

```
training.py
Oct 08, 2025 16:46
                                                                          Page 2/3
   checkpoint_dir = ocp.test_utils.erase_and_create_empty(checkpoint_dir)
   log_interval = settings.training.log_interval
   num_epochs = settings.training.num_epochs
   metrics_history = {
   "train_steps": [],
   "train loss": [],
   "train_accuracy": [],
   "val_steps": [],
   "val_loss": [],
   "val_accuracy": [],
   qlobal_step = 0
   best_val_acc = 0.0
   best_ckpt_path = None
   for epoch in range(1, num_epochs + 1):
       for batch in train_ds.as_numpy_iterator():
           loss, logits = train_step(model, optimizer, batch, rngs)
           if global_step % log_interval == 0:
               images, labels = batch
               labels = labels.ravel()
               acc = compute_accuracy(logits, labels)
               loss_val = float(loss)
               acc_val = float(acc)
               metrics_history["train_steps"].append(global_step)
               metrics_history["train_loss"].append(loss_val)
               metrics_history["train_accuracy"].append(acc_val)
               log.info(
                    "train iter",
                    epoch=epoch,
                    step=global_step,
                    loss=loss_val,
                    acc=acc val,
           global_step += 1
       # Create checkpoint every 5 epoch. Compare with previous best validation
accuracy and save best checkpoint.
       val_loss, val_acc = evaluate(model, val_ds, rngs)
       if epoch % 5 == 0 or epoch == num_epochs:
           checkpointer = ocp.StandardCheckpointer()
           if val_acc > best_val_acc:
               best_val_acc = val_acc
               best_ckpt_path = checkpoint_dir / f"best_state_epoch_{epoch}"
               _, state = nnx.split(model)
               checkpointer.save(best_ckpt_path, state)
           else:
                _, state = nnx.split(model)
               ckpt_path = checkpoint_dir / f"state_epoch_{epoch}"
               checkpointer.save(ckpt_path, state)
       metrics_history["val_steps"].append(global_step)
       metrics_history["val_loss"].append(val_loss)
       metrics_history["val_accuracy"].append(val_acc)
       log.info(
            "epoch_summary",
           epoch=epoch,
           step=global_step,
           val_loss=val_loss,
           val_acc=val_acc,
```

```
training.py
 Oct 08, 2025 16:46
                                                                            Page 3/3
    log.info("Training finished. Generating final plots...")
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(15, 6))
    ax1.set_title("Loss vs. Steps")
    ax2.set_title("Accuracy vs. Steps")
    ax1.plot(metrics_history["train_steps"], metrics_history["train_loss"], label="train"
, alpha=0.7)
    ax2.plot(metrics_history["train_steps"], metrics_history["train_accuracy"], label="t
rain", alpha=0.7)
    ax1.plot(metrics_history["val_steps"], metrics_history["val_loss"], label="val", m
arker='o', linestyle='--')
    ax2.plot(metrics_history["val_steps"], metrics_history["val_accuracy"], label="val
", marker='o', linestyle='--')
    ax1.set_xlabel("Step")
    ax1.set_ylabel("Loss")
    ax1.legend()
    ax1.grid(True, which='both', linestyle='--', linewidth=0.5)
    ax2.set_xlabel("Step")
    ax2.set_ylabel("Accuracy")
    ax2.grid(True, which='both', linestyle='--', linewidth=0.5)
    fig.tight_layout()
    fig.savefig(output_dir / "final_training_metrics.png", dpi=settings.plotting.dpi)
    plt.close(fig)
    return metrics_history
def test_evaluation(model, test_ds, rngs):
    settings = load_settings()
    output_dir = settings.plotting.output_dir
    output_dir.mkdir(parents=True, exist_ok=True)
    test_loss, test_acc = evaluate(model, test_ds, rngs)
    log.info("test_results", test_loss=test_loss, test_acc=test_acc)
    return test_loss, test_acc
def load_checkpoint(model_cls, model_kwargs: dict):
    settings = load_settings()
    checkpoint_dir = settings.training.checkpoint_dir.resolve()
    checkpointer = ocp.StandardCheckpointer()
    ckpts = sorted(checkpoint_dir.glob("best_state_epoch_*"), key=os.path.getmtime)
    if not ckpts:
        raise FileNotFoundError (f"No checkpoints found in {checkpoint_dir}")
    latest\_ckpt = ckpts[-1]
    print (f"Loading checkpoint from: {latest_ckpt}")
    abstract_model = nnx.eval_shape(lambda: model_cls(**model_kwargs, rngs=nnx.R
ngs(0)))
    graphdef, abstract_state = nnx.split(abstract_model)
    # restore parameters
    state_restored = checkpointer.restore(latest_ckpt, abstract_state)
    model = nnx.merge(graphdef, state_restored)
    print ("Checkpoint successfully restored!")
    return model
```

```
Oct 05, 2025 21:56
                                        data.py
                                                                        Page 1/2
import tensorflow_datasets as tfds
import tensorflow as tf
def load_CIFAR10(batch_size=128, validation_size=5000, seed=0):
   ds_train = tfds.load("cifar10", split="train", shuffle_files=True, as_supervised
=True)
    ds_test = tfds.load("cifar10", split="test", as_supervised=True)
    def _preprocess(image, label):
        image = tf.cast(image, tf.float32) / 255.0
       label = tf.cast(label, tf.int32)
       return image, label
    ds_train = ds_train.map(_preprocess, num_parallel_calls=tf.data.AUTOTUNE)
    ds_test = ds_test.map(_preprocess, num_parallel_calls=tf.data.AUTOTUNE)
    ds_val = ds_train.take(validation_size)
    ds_train = ds_train.skip(validation_size)
    def augmentation(image, label):
       image = tf.image.resize_with_crop_or_pad(image, 40, 40)
        image = tf.image.random_crop(image, size=[32, 32, 3])
        image = tf.image.random_flip_left_right(image)
        image = tf.image.random_brightness(image, max_delta=0.2)
        image = tf.image.random_contrast(image, 0.8, 1.2)
        image = tf.image.random_saturation(image, 0.8, 1.2)
        return image, label
    ds_train = ds_train.map(augmentation, num_parallel_calls=tf.data.AUTOTUNE)
    ds_train = ds_train.shuffle(10 * batch_size, seed=seed).batch(batch_size).pr
efetch(tf.data.AUTOTUNE)
    ds_val = ds_val.batch(batch_size).prefetch(tf.data.AUTOTUNE)
    ds_test = ds_test.batch(batch_size).prefetch(tf.data.AUTOTUNE)
    return ds_train, ds_val, ds_test
def load CIFAR100 (batch size=128, validation size=5000, seed=0):
    ds_train = tfds.load("cifar100", split="train", shuffle_files=True, as_supervise
d=True)
   ds_test = tfds.load("cifar100", split="test", as_supervised=True)
    def _preprocess(image, label):
       image = tf.cast(image, tf.float32) / 255.0
       label = tf.cast(label, tf.int32)
       return image, label
    ds_train = ds_train.map(_preprocess, num_parallel_calls=tf.data.AUTOTUNE)
    ds_test = ds_test.map(_preprocess, num_parallel_calls=tf.data.AUTOTUNE)
    ds_val = ds_train.take(validation_size)
    ds_train = ds_train.skip(validation_size)
    def augmentation(image, label):
       image = tf.image.resize_with_crop_or_pad(image, 40, 40)
        image = tf.image.random_crop(image, size=[32, 32, 3])
        image = tf.image.random_flip_left_right(image)
        image = tf.image.random_brightness(image, max_delta=0.2)
        image = tf.image.random_contrast(image, 0.8, 1.2)
        image = tf.image.random_saturation(image, 0.8, 1.2)
        return image, label
    ds_train = ds_train.map(augmentation, num_parallel_calls=tf.data.AUTOTUNE)
    ds_train = ds_train.shuffle(10 * batch_size, seed=seed).batch(batch_size).pr
efetch (tf.data.AUTOTUNE)
   ds_val = ds_val.batch(batch_size).prefetch(tf.data.AUTOTUNE)
    ds_test = ds_test.batch(batch_size).prefetch(tf.data.AUTOTUNE)
```

```
Oct 05, 2025 21:56
                                        data.py
                                                                       Page 2/2
   return ds_train, ds_val, ds_test
```