Azure AI Foundry Agents & MCP Tools

Prompt vs Hosted — Integration Guide

2025

Contents

0.1 Table of Contents . . . 1
0.2 Overview . . . 1
0.3 Architecture . . . 2
0.3.1 Prompt Agent Flow . . . 2
0.3.2 Hosted Agent Flow . . . 2
0.4 Prompt Agent with MCP Tool . . . 2
0.4.1 Prerequisites . . . 2
0.4.2 Code Example . . . 3
0.5 Hosted Agent with MCP Tool . . . 5
0.5.1 Prerequisites . . . 5
0.5.2 Code Example . . . 5
0.5.3 Dockerfile . . . 6
0.5.4 Deploy . . . 7
0.6 Comparison . . . 7
0.7 MCP Authentication via Project Connection . . . 7
0.8 References . . . 9

How to integrate MCP (Model Context Protocol) tools — such as MongoDB — with Azure AI Foundry agents.
Covers both **Prompt Agents** (managed by Foundry) and **Hosted Agents** (your own containerized code).

0.1 Table of Contents

- Overview
- Architecture
- Prompt Agent with MCP Tool
- Hosted Agent with MCP Tool
- Comparison
- MCP Authentication via Project Connection
- References

0.2 Overview

Azure AI Foundry Agent Service supports two agent hosting models, each with a different way to consume MCP tools:

Model	Description	MCP Integration
Prompt Agent	Declarative agent defined via SDK. Foundry orchestrates everything.	`MCPTool()` in `PromptAgentDefinition` — Foundry manages MCP calls

Model	Description	MCP Integration
Hosted Agent	Your own code (Agent Framework, LangGraph, custom) packaged in a container.	You call the MCP server directly from your code via the `mcp` Python client

---

0.3 Architecture

0.3.1 Prompt Agent Flow



Figure 1: Diagram 1

0.3.2 Hosted Agent Flow

0.4 Prompt Agent with MCP Tool

The simplest approach — Foundry handles the MCP orchestration, including tool discovery and approval flow.

0.4.1 Prerequisites

```
pip install azure-ai-projects azure-identity
```



Figure 2: Diagram 2

0.4.2 Code Example

```
import json
from azure.identity import DefaultAzureCredential
from azure.ai.projects import AIProjectClient
from azure.ai.projects.models import PromptAgentDefinition, MCPTool
from openai.types.responses.response_input_param import McpApprovalResponse

PROJECT_ENDPOINT = "https://<resource>.ai.azure.com/api/projects/<project>"
MCP_CONNECTION_NAME = "mongo-mcp-connection"  # Project Connection name

project = AIProjectClient(
    endpoint=PROJECT_ENDPOINT,
    credential=DefaultAzureCredential(),
)
openai = project.get_openai_client()

# Declare the MCP tool — Foundry handles discovery & invocation
tool = MCPTool(
    server_label="mongodb",
    server_url="https://<your-mcp-mongo-server>/mcp",
    require_approval="always",
    project_connection_id=MCP_CONNECTION_NAME,
    allowed_tools=["find", "aggregate", "insertOne"],
)

# Create the agent
agent = project.agents.create_version(
```

```
    agent_name="MongoAnalyst",
    definition=PromptAgentDefinition(
        model="gpt-4.1",
        instructions="You are a data analyst. Use MongoDB tools to answer
 ↪  questions.",
        tools=[tool],
    ),
)

# Conversation
conversation = openai.conversations.create()
response = openai.responses.create(
    conversation=conversation.id,
    input="How many documents are in the hotels collection?",
    extra_body={"agent_reference": {"name": agent.name, "type":
 ↪  "agent_reference"}},
)

# Handle MCP approval requests
input_list = []
for item in response.output:
    if item.type == "mcp_approval_request":
        print(f"  Tool: {getattr(item, 'name', '?')}")
        print(f"  Args: {json.dumps(getattr(item, 'arguments', None),
         ↪  indent=2)}")
        input_list.append(McpApprovalResponse(
            type="mcp_approval_response",
            approve=True,
            approval_request_id=item.id,
        ))

if input_list:
    response = openai.responses.create(
        input=input_list,
        previous_response_id=response.id,
        extra_body={"agent_reference": {"name": agent.name, "type":
 ↪  "agent_reference"}},
    )

print(response.output_text)

# Cleanup
project.agents.delete_version(agent_name=agent.name,
 ↪  agent_version=agent.version)
```

0.5 Hosted Agent with MCP Tool

For full control — you bring your own code, call the MCP server directly, and deploy as a container.

0.5.1 Prerequisites

```
pip install azure-ai-agentserver-agentframework agent-framework mcp
↪ azure-identity
```

0.5.2 Code Example

```
import os, json
from dotenv import load_dotenv
load_dotenv(override=True)

from agent_framework import ai_function, ChatAgent
from agent_framework.azure import AzureAIAgentClient
from azure.ai.agentserver.agentframework import from_agent_framework
from azure.identity import DefaultAzureCredential
from mcp import ClientSession
from mcp.client.streamable_http import streamablehttp_client

PROJECT_ENDPOINT = os.getenv("PROJECT_ENDPOINT")
MODEL = os.getenv("MODEL_DEPLOYMENT_NAME", "gpt-4.1")
MONGO_MCP_URL = os.getenv("MONGO_MCP_URL")


@ai_function
async def query_mongodb(collection: str, filter_json: str) -> str:
    """Query a MongoDB collection via MCP server.

    Args:
        collection: Collection name (e.g. "hotels")
        filter_json: JSON filter (e.g. '{"city": "Paris"}')
    """
    async with streamablehttp_client(MONGO_MCP_URL) as (r, w, _):
        async with ClientSession(r, w) as session:
            await session.initialize()
            result = await session.call_tool(
                "find",
                arguments={"collection": collection, "filter": filter_json},
            )
            return str(result.content)


@ai_function
async def aggregate_mongodb(collection: str, pipeline_json: str) -> str:
```

```
    """Run an aggregation pipeline on a MongoDB collection via MCP.

    Args:
        collection: Collection name
        pipeline_json: JSON aggregation pipeline
    """
    async with streamablehttp_client(MONGO_MCP_URL) as (r, w, _):
        async with ClientSession(r, w) as session:
            await session.initialize()
            result = await session.call_tool(
                "aggregate",
                arguments={"collection": collection, "pipeline":
↪   pipeline_json},
            )
            return str(result.content)


agent = ChatAgent(
    chat_client=AzureAIAgentClient(
        project_endpoint=PROJECT_ENDPOINT,
        model_deployment_name=MODEL,
        credential=DefaultAzureCredential(),
    ),
    instructions=(
        "You are a data analyst. Use query_mongodb and aggregate_mongodb "
        "to answer user questions about data stored in MongoDB."
    ),
    tools=[query_mongodb, aggregate_mongodb],
)

if __name__ == "__main__":
    # Hosting adapter exposes agent on localhost:8088
    from_agent_framework(agent).run()
```

0.5.3 Dockerfile

```
FROM python:3.12-slim
WORKDIR /app
COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt
COPY . .
EXPOSE 8088
CMD ["python", "agent.py"]
```

0.5.4 Deploy

```
# Build & push to ACR
az acr build --registry <your-acr> --image mongo-agent:v1 .

# Create hosted agent via Azure Developer CLI
azd ai agent create \
    --name MongoAnalyst \
    --image <your-acr>.azurecr.io/mongo-agent:v1 \
    --project <project-name>
```

0.6 Comparison

Aspect	Prompt Agent	Hosted Agent
MCP declaration	`MCPTool()` in SDK	`mcp` Python client in your code
Orchestration	Foundry manages	You manage
Approval flow	Built-in (`mcp_approval_request`)	Custom implementation
Deployment	API call only	Container → ACR → Foundry
Frameworks	N/A (declarative)	Agent Framework, LangGraph, custom
Networking	Standard or Basic setup	Preview (no VNet yet)
Complexity	Low	Medium-High
Flexibility	Limited to SDK features	Full control
Best for	Quick integrations, simple tools	Complex logic, multi-tool orchestration

---

0.7 MCP Authentication via Project Connection

Both approaches can leverage Foundry **Project Connections** for secure MCP authentication:

1. **Azure Portal** → Microsoft Foundry → Management Center → Connected Resources
2. Create a **Custom Keys** connection
3. Set key = `Authorization`, value = `Bearer <your_mcp_server_token>`
4. Name it (e.g., `mongo-mcp-connection`)

- **Prompt Agent**: pass `project_connection_id="mongo-mcp-connection"` in `MCPTool()`
- **Hosted Agent**: retrieve the connection secret via Foundry SDK or environment variable

  Never hard-code secrets in your container image or code. Use managed identities and Project Connections.





Figure 3: Diagram 3

0.8 References

Resource	Link
Official docs — MCP tool for agents	learn.microsoft.com
Official docs — Hosted agents	learn.microsoft.com
MCP authentication	learn.microsoft.com
Sample: Foundry + MCP Python	github.com/Azure-Samples
Sample: AI Foundry Agent MCP	github.com/ccoellomsft
MongoDB + Foundry blog	mongodb.com
MCP for Beginners	github.com/microsoft

Generated on 2026-03-17