Network Configurations in Microsoft Fabric

Architecture, Security & Best Practices

April 2026

Contents

1 Overview **2**

2 Secure by Default **3**

3 Inbound Protection **3**
3.1 Tenant Setting: Workspace-Level Inbound Network Rules . . . 3
3.1.1 Interaction Between Tenant and Workspace Network Settings . . . 4
3.2 Entra Conditional Access . . . 5
3.2.1 Zero Trust Identity Best Practices . . . 5
3.3 Tenant-Level Private Link . . . 6
3.4 Workspace-Level Private Link . . . 7
3.5 Workspace IP Firewall . . . 9
3.6 Inbound Options Comparison . . . 9

4 Secure Outbound Access **10**
4.1 Trusted Workspace Access . . . 10
4.2 Managed Private Endpoints . . . 12
4.3 Managed Virtual Networks . . . 12
4.4 Data Gateways . . . 13
4.4.1 On-Premises Data Gateway . . . 13
4.4.2 VNet Data Gateway . . . 13
4.5 Eventstream Private Network Support . . . 13
4.6 Service Tags . . . 14
4.6.1 Using Service Tags with Network Security Groups (NSG) . . . 14
4.6.2 Centralizing Outbound Traffic with Azure Firewall . . . 15
4.7 Secure Outbound Connectors Matrix . . . 15

5 Outbound Protection **16**
5.1 Outbound Access Policies . . . 16
5.2 Data Exfiltration Protection (DEP) . . . 16
5.3 Advanced Data Exfiltration Controls . . . 17

6 Data Security **17**
6.1 Encryption . . . 17
6.2 Customer Managed Keys (CMK) . . . 19

7 Data Residency and Multi-Geo **19**

8 DNS Configuration for Private Link **19**
8.1 Required Private DNS Zones . . . 19
8.2 DNS Architecture Patterns . . . 20
8.3 IP Address Planning . . . 20
8.4 DNS Best Practices Checklist . . . 20

9 Monitoring, Logging and Auditing **21**
9.1 Diagnostic Logging . . . 21
9.2 Azure Monitor Integration . . . 21

9.3 Microsoft Sentinel Integration . . . 22
9.4 Audit Best Practices . . . 22

10 Testing and Validation **22**
10.1 Connectivity Validation . . . 22
10.2 Performance Validation . . . 23
10.3 Periodic Reviews . . . 23

11 Compliance and Certifications **23**

12 Decision Guide **24**

13 Feature Summary and Status **24**

14 Feature Dependencies **25**

15 End-to-End Network Architecture **26**

16 Known Limitations by Item Type **28**

17 Recommended Architectures by Scenario **29**
17.1 Scenario 1 — Regulated Enterprise (GDPR / HIPAA / PCI DSS) . . . 29
17.2 Scenario 2 — Data Platform Team with Mixed Sensitivity . . . 29
17.3 Scenario 3 — Small Team / Startup (Cost-Optimized) . . . 30
17.4 Scenario 4 — Multi-Region Global Deployment . . . 30

18 References **30**

1 Overview

Microsoft Fabric is a unified SaaS platform for analytics and AI, bringing together Data Factory, Data Engineering, Data Science, Data Warehousing, Real-Time Intelligence and Power BI around a single data lake: **OneLake**.

Network security in Fabric is built around three fundamental pillars:

Pillar	Objective	Key Features
Inbound Protection	Control who accesses Fabric	Conditional Access, Private Links (tenant/workspace), IP Firewall
Secure Outbound Access	Connect Fabric to protected data sources	Trusted Workspace Access, Managed Private Endpoints, VNet/On-prem Gateways
Outbound Protection	Prevent data exfiltration	Outbound Access Policies, allowed destination rules

Combining **Inbound + Outbound Protection** provides complete **Data Exfiltration Protection (DEP)**.



Figure 1: Diagram 1

2 Secure by Default

Microsoft Fabric is **secure by default** without any additional configuration:

- **Authentication**: Every interaction is authenticated via **Microsoft Entra ID**
- **Encryption in transit**: All traffic is encrypted using **TLS 1.2** minimum (TLS 1.3 negotiation when available)
- **Encryption at rest**: All data in OneLake is automatically encrypted
- **Microsoft backbone network**: Internal communications between Fabric experiences travel through the Microsoft private network, never over the public internet
- **Secure endpoints**: The Fabric backend is protected by a virtual network and is not directly accessible from the public internet



Figure 2: Diagram 2

3 Inbound Protection

Inbound protection controls traffic entering Fabric from the internet or corporate networks.

3.1 Tenant Setting: Workspace-Level Inbound Network Rules

Before workspace administrators can configure Private Link or IP Firewall at the workspace level, a **tenant administrator** must enable the **"Workspace-level inbound network rules"** setting in the

Fabric Admin portal (under **Tenant settings > Network security**).

When this setting is **disabled** (default), workspace-level Private Link and IP Firewall options are hidden from workspace administrators. Enabling it delegates inbound network control to individual workspace admins, allowing them to restrict public access independently per workspace.

> **Important:** This tenant setting does not enforce any network restriction by itself — it only **unlocks** the capability for workspace admins. Each workspace admin must then explicitly configure Private Link or IP Firewall rules on their workspace.

3.1.1 Interaction Between Tenant and Workspace Network Settings

The tenant-level public access setting and workspace-level inbound rules interact as follows:

Tenant Public Access	Workspace Private Link	Workspace IP Firewall	Portal Access	API Access	Notes
Allowed	Not configured	Not configured	Public	Public	Default — no restriction
Allowed	Configured (public disabled)	—	Via WS Private Link only	Via WS Private Link only	Workspace locked down
Allowed	—	Configured	From allowed IPs only	From allowed IPs only	IP-based restriction
Restricted (Block Public Access)	Not configured	Not configured	Via Tenant PL only	Via Tenant PL only	Tenant-wide lockdown
Restricted (Block Public Access)	Configured	—	Via Tenant PL only	Via WS Private Link or Tenant PL	Portal requires tenant PL; API can use workspace PL
Restricted (Block Public Access)	—	Configured	Via Tenant PL only	Via Tenant PL only	IP firewall rules are overrid-den by tenant restriction

> **Key takeaway:** When tenant-level public access is **restricted**, the tenant Private Link takes precedence for portal access. Workspace-level Private Link provides additional API-level access paths but does not bypass the tenant restriction for the Fabric portal.

3.2 Entra Conditional Access

Microsoft Entra ID Conditional Access is the **Zero Trust** approach for securing access to Fabric. Access decisions are made at authentication time by evaluating contextual signals.

Evaluated signals:

Signal	Policy examples
Users and groups	Target specific populations
Location / IP	Allow only certain IP ranges or countries
Devices	Require compliant devices (Intune)
Applications	Apply rules per Fabric application
Sign-in risk	Block high-risk sign-ins

Possible decisions: Block, Grant, Require MFA, Require compliant device.

Prerequisites: Microsoft Entra ID P1 license (often included in Microsoft 365 E3/E5).

> **Note:** Conditional Access policies apply to Fabric and related Azure services (Power BI, Azure Data Explorer, Azure SQL Database, Azure Storage). This may be considered too broad for some scenarios.

3.2.1 Zero Trust Identity Best Practices

As a SaaS service, Microsoft Fabric relies on **identity as the primary security perimeter**. Network controls complement but do not replace a robust identity strategy. The following practices should form the foundation of any Fabric security posture:

Practice	Description
Phishing-resistant MFA	Enforce multi-factor authentication using FIDO2 keys, Windows Hello for Business or certificate-based methods. Avoid SMS-based MFA where possible.
Device Compliance	Require managed or compliant devices (via Microsoft Intune) in Conditional Access policies to prevent access from untrusted endpoints.
Privileged Identity Management (PIM)	Use Entra PIM for just-in-time, time-limited elevation of Fabric admin and workspace admin roles. Avoid permanent high-privilege assignments.
Service Principal Governance	Audit and restrict Service Principal and Managed Identity access to Fabric APIs. Apply Conditional Access workload identity policies (Entra Workload ID Premium) to limit tokens to known IP ranges.
Continuous Access Evaluation (CAE)	Enable CAE so that revoked sessions, changed locations and risk events trigger near-real-time re-evaluation of Fabric access tokens.

> **Recommendation:** Start with identity controls (MFA, Conditional Access, PIM) before

layering network controls. This ensures baseline protection regardless of the user's network path.



Figure 3: Diagram 3

3.3 Tenant-Level Private Link

Tenant-level Private Link provides **perimeter-based protection** for the entire Fabric tenant.

Concept: An Azure Private Endpoint is created in the customer's VNet, establishing a private tunnel to Fabric via the Microsoft backbone. Fabric becomes inaccessible from the public internet.

Two key settings:

Setting	Effect
Azure Private Links (enabled)	Traffic from the VNet to supported endpoints goes through the Private Link
Block Public Internet Access (enabled)	Fabric is no longer accessible from the public internet; only Private Link is allowed

Configuration scenarios:

Private Link	Block Public Access	Behavior
Yes	Yes	Access only via Private Endpoint. Unsupported endpoints blocked.
Yes	No	VNet traffic via Private Link. Public internet traffic allowed.
No	-	Standard access via public internet.

Considerations:

- **All users** must connect through the private network (VPN, ExpressRoute)

- **Bandwidth** impact: static resources (CSS, images) also transit through the Private Endpoint
- Some features have **limitations** (Publish to Web disabled, Copilot not supported, Power BI PDF/PowerPoint export disabled)
- **Spark Starter Pools** are disabled (replaced by custom pools in the managed VNet)
- **Cross-tenant access is not supported:** a Private Endpoint cannot be used to reach a Fabric tenant different from the one associated with the Private Link Service. This limitation is by design and applies to both tenant-level and workspace-level Private Link.
- **Private DNS Zone required:** to resolve Fabric public FQDNs (e.g., `*.fabric.microsoft.com`, `*.pbidedicated.windows.net`, `*.analysis.windows.net`) to private IP addresses, an Azure Private DNS Zone must be created and linked to the VNet. Without proper DNS configuration, clients will continue resolving public IPs and bypass the Private Endpoint. Use Azure Private DNS Zones or configure conditional DNS forwarding from on-premises DNS servers.

3.4 Workspace-Level Private Link

Workspace-level Private Link offers **granular** control: specific workspaces are protected by Private Link while others remain publicly accessible.

Key characteristics:

- **1:1** relationship between a workspace and its Private Link Service
- A Private Link Service can have **multiple Private Endpoints** (from different VNets)
- A VNet can connect to **multiple workspaces** via separate Private Endpoints
- Public access can be restricted **independently** per workspace
- Public workspaces can be secured with Entra Conditional Access or IP Filtering

Supported items (GA since September 2025): Lakehouse, Shortcut, Notebook, ML Experiment/Model, Pipeline, Warehouse, Dataflows, Eventstream, Mirrored DB. Access to workspace-level Private Link workspaces is available via both the Fabric portal and API.

> **Limitation — Unsupported item types:** Power BI reports/dashboards, Fabric databases, Data Activator, deployment pipelines, and default semantic models are **not yet covered** by workspace-level Private Link. These items remain accessible via public endpoints unless the entire tenant is secured with tenant-level Private Link or Microsoft Entra Conditional Access is used. Support for these item types is on the roadmap.
>
> **DNS configuration:** As with tenant-level Private Link, each workspace Private Endpoint requires a matching Azure Private DNS Zone record so that the workspace-specific FQDN resolves to the Private Endpoint's private IP. When connecting multiple VNets to multiple workspaces, plan the DNS zone topology carefully — a single centralized Private DNS Zone linked to all VNets is recommended over per-VNet zones to avoid resolution conflicts.
>
> **Key difference from Tenant-Level Private Link:** Workspace-level Private Link allows you to protect only sensitive workspaces without impacting the entire tenant. This is the recommended approach for organizations that cannot force all users onto a private network.



Figure 4: Diagram 4
Network Configurations in Microsoft Fabric



Figure 5: Diagram 5

3.5 Workspace IP Firewall

The workspace IP firewall is the simplest solution to restrict access to a workspace from specific public IP ranges.

Concept: Only explicitly allowed IP addresses or IP ranges can access the workspace. No Azure network infrastructure is required.

Supported items (GA since Q1 2026): Lakehouse, Shortcut, Notebook, ML Experiment/Model, Pipeline, Warehouse, Dataflows, Eventstream, Mirrored DB. Both API and UI configuration are supported.

> **Limitation — Unsupported item types:** Power BI reports/dashboards, Fabric databases, Data Activator, deployment pipelines, and default semantic models are **not covered** by workspace IP Firewall rules. Traffic to these items bypasses the IP firewall and remains accessible from any network unless the entire tenant is locked down with tenant-level Private Link or Microsoft Entra Conditional Access. Support for these items is on the roadmap.
>
> **Note — API access:** Even with strict IP firewall rules, the **Fabric REST API** remains accessible for rule management. Administrators can create, update and delete IP firewall rules via the API regardless of their client IP. This is by design to prevent accidental lockout, but it means API-level governance (Conditional Access, Service Principal restrictions) is essential to avoid unauthorized rule changes.

3.6 Inbound Options Comparison

Criteria	Conditional Access	Private Link Tenant	Private Link Workspace	IP Firewall
Granularity	Tenant (per policy)	Tenant	Workspace	Workspace
Azure infrastructure required	No	VNet + PE	VNet + PE per WS	No
Complexity	Low	High	Medium	Low
Approach	Zero Trust (identity)	Perimeter (network)	Perimeter (network)	IP-based

Criteria	Conditional Access	Private Link Tenant	Private Link Workspace	IP Firewall
User impact	Transparent (MFA)	VPN/ER mandatory	VPN/ER for protected WS	None if IP allowed
Additional cost	Entra ID P1	VNet + PE + ER/VPN	VNet + PE	None
Status	GA	GA	GA	GA

4 Secure Outbound Access

Secure outbound access allows Fabric to connect to data sources protected by firewalls or private networks.

4.1 Trusted Workspace Access

Trusted Workspace Access allows specific Fabric workspaces to securely access **firewall-enabled ADLS Gen2 accounts**.

Concept: The Fabric workspace has a **workspace identity** (managed identity). **Resource Instance Rules** are configured on the storage account to authorize only specified workspaces.

Prerequisites: - Workspace associated with a **Fabric F SKU** capacity (not supported on Trial or Power BI Premium P SKU) - **Workspace Identity** created and configured as Contributor on the workspace - Authentication principal (user or service principal) with an **Azure RBAC data-plane role** on the ADLS Gen2 storage account: `Storage Blob Data Contributor`, `Storage Blob Data Owner`, or `Storage Blob Data Reader` depending on the operation - **Resource Instance Rule** configured on the storage account's firewall to allow the specific Fabric workspace. This rule references the **Entra tenant ID** and the **workspace resource ID** and must be deployed via **ARM Template**, **Bicep**, or **PowerShell** (the Azure portal does not support resource instance rules natively)

> **Checklist:** If Trusted Workspace Access is not working, verify: (1) the workspace identity exists and is not disabled, (2) the RBAC role is assigned at the storage account or container level (not the resource group), (3) the resource instance rule uses the correct workspace resource ID (not just the workspace name), and (4) the storage account firewall allows "trusted Microsoft services" access.

Supported scenarios:

Method	Description
OneLake Shortcut	ADLS Gen2 shortcut in a Lakehouse
Pipeline	Data copy from firewall-enabled ADLS Gen2
T-SQL COPY INTO	Ingestion into a Warehouse
Semantic Model (import)	Model connected to ADLS Gen2
AzCopy	High-performance load to OneLake



Figure 6: Diagram 6



Figure 7: Diagram 7

4.2 Managed Private Endpoints

Managed Private Endpoints enable secure, private connections to Azure data sources from Fabric workloads without exposing them to the public network.

Concept: Microsoft Fabric creates and manages Private Endpoints in a **managed VNet** dedicated to the workspace. Workspace admins specify the resource ID of the source, the target sub-resource, and a justification.

Supported sources: Azure Storage, Azure SQL Database, Azure Cosmos DB, Azure Key Vault, and many more.

Supported items: - Data Engineering (Spark/Python Notebooks, Lakehouses, Spark Job Definitions) - Eventstream

Prerequisites: - Supported on Fabric Trial and all F SKU capacities - Data Engineering workload must be available in both the tenant region AND the capacity region

Limitations: - OneLake shortcuts do not yet support ADLS Gen2 / Blob Storage connections via MPE - Cross-region workspace migration not supported - FQDN-based creation (Private Link Service) only via REST API



Figure 8: Diagram 8

4.3 Managed Virtual Networks

Managed VNets are virtual networks created and managed by Fabric for each workspace. They provide network isolation for Spark workloads.

Automatically provisioned when: 1. **Managed Private Endpoints** are added to the workspace 2. The **Private Link** setting is enabled and a Spark job is executed

Characteristics: - Complete Spark cluster isolation (dedicated network) - No need to size subnets (managed by Fabric) - **Starter Pools** are disabled (on-demand Custom Pools, 3-5 min startup) - Not supported in Switzerland West and West Central US regions

4.4 Data Gateways

4.4.1 On-Premises Data Gateway

A gateway installed on a server within the corporate network, acting as a bridge between on-premises data sources and Fabric.

Characteristic	Detail
Installation	Windows server in the internal network
Protocol	Secure outbound channel (no inbound port opening)
Sources	Any source accessible from the gateway server
Management	Manual (updates, high availability)

4.4.2 VNet Data Gateway

A managed gateway deployed into a customer's Azure VNet, enabling connections to Azure services within the VNet without an on-premises gateway.

Characteristic	Detail
Deployment	Injection into an existing Azure VNet
Management	Managed by Microsoft
Sources	Azure services in the VNet or peered VNets
Workloads	Dataflows Gen2, Semantic Models
Enterprise proxy & cert auth	**GA** — supports enterprise HTTP/HTTPS proxy servers and certificate-based authentication, allowing the gateway to route traffic through corporate proxies and authenticate with client certificates. Essential for organizations with mandatory proxy inspection policies.

Reference: VNet Data Gateway documentation

4.5 Eventstream Private Network Support

Preview — Q1 2026

Fabric Eventstreams can now ingest data from private networks via a **managed VNet** and a **streaming data gateway**, enabling secure real-time data ingestion without exposing source endpoints to the public internet. This allows organizations to stream events from Azure Event Hubs, IoT Hub, or custom sources within a VNet directly into Fabric, with traffic routed entirely through the Microsoft backbone.



Figure 9: Diagram 9

Key points: - Eventstreams leverage the workspace's managed VNet for network isolation - A streaming data gateway bridges the private network to the Eventstream ingestion endpoint - Supports managed private endpoints for source connectivity - Custom Endpoint as source/destination and Eventhouse direct ingestion remain unsupported

4.6 Service Tags

Azure Service Tags are automatically managed groups of IP addresses, usable in NSGs, Azure Firewall and user-defined routes.

Tag	Service	Direction	Regional
`Power BI`	Power BI and Microsoft Fabric	Inbound/Outbound	Yes
`DataFactory`	Azure Data Factory	Inbound/Outbound	Yes
`DataFactoryManagement`	On-premises pipeline	Outbound	No
`EventHub`	Azure Event Hubs	Outbound	Yes
`KustoAnalytics`	Real-Time Analytics	Inbound/Outbound	No
`SQL`	Warehouse	Outbound	Yes
`PowerQueryOnline`	Power Query Online	Inbound/Outbound	No

> **Tip:** When using regional tags, add the tag for the tenant's home region **and** the capacity region (if different), as well as the corresponding paired regions.

4.6.1 Using Service Tags with Network Security Groups (NSG)

NSGs can leverage Fabric-related service tags to enforce fine-grained inbound and outbound rules on subnets hosting Private Endpoints, VNet Data Gateways, or on-premises gateway servers.

Example NSG rules:

Priority	Direction	Source/Destination	Service Tag	Action	Purpose
100	Outbound	VNet	`PowerBI`	Allow	Allow traffic to Fabric/Power BI endpoints
110	Outbound	VNet	`DataFactory`	Allow	Allow pipeline orchestration traffic
120	Outbound	VNet	`SQL`	Allow	Allow Warehouse connectivity
200	Outbound	VNet	`Internet`	Deny	Block all other internet-bound traffic

4.6.2 Centralizing Outbound Traffic with Azure Firewall

For organizations that require centralized egress control, logging and static IP addresses:

- Deploy an **Azure Firewall** (or third-party NVA) in a hub VNet and route traffic from spoke VNets (hosting Private Endpoints or VNet Data Gateways) through the firewall via User Defined Routes (UDR).
- Use **application rules** with service tag-based FQDN filtering to allow only Fabric-related traffic.
- A **NAT Gateway** attached to the firewall subnet provides a **static outbound IP** — useful when external partners or data sources require IP whitelisting.
- All outbound connections are logged in Azure Firewall Diagnostics, enabling centralized auditing and threat detection.

4.7 Secure Outbound Connectors Matrix

Connection Method	Supported Sources	Fabric Workloads
Trusted Workspace Access	ADLS Gen2 (firewall)	Shortcuts, Pipelines, COPY INTO, Semantic Models
Managed Private Endpoints	Azure SQL, ADLS Gen2, Cosmos DB, Key Vault…	Spark Notebooks, Lakehouses, Spark Jobs, Eventstream
VNet Data Gateway	Azure services in a VNet	Dataflows Gen2, Semantic Models

Connection Method	Supported Sources	Fabric Workloads
On-Premises Gateway	SQL Server, Oracle, files, SAP...	Dataflows Gen2, Semantic Models, Pipelines
Service Tags	Azure SQL VM, SQL MI, REST APIs	Pipelines, network integration

5 Outbound Protection

5.1 Outbound Access Policies

Outbound Access Policies allow you to **restrict outbound connections** from a Fabric workspace to unauthorized destinations.

Objective: Prevent malicious users from exfiltrating data to unapproved destinations.

Characteristics: - **Workspace-level** control - Destinations are allow-listed via **Managed Private Endpoints** or **Data Connections** - Any connection to a destination not explicitly allowed is **blocked**

Status (as of April 2026):

Item Type	Status
Lakehouse, Spark Notebooks, Spark Jobs	**GA** (since Sept 2025)
Dataflows, Pipelines, Copy Jobs, Warehouse, Mirrored DBs	**GA** (since Nov 2025)
Power BI, Databases	Planned (roadmap)



Figure 10: Diagram 10

5.2 Data Exfiltration Protection (DEP)

Complete **DEP** is achieved by combining inbound AND outbound protection:

Component	Role
Inbound (Private Link / IP Firewall / Conditional Access)	Controls **who** can access data and **from where**

Component	Role
Outbound (Outbound Access Policies)	Prevents authorized users from **exfiltrating** data to unapproved destinations

5.3 Advanced Data Exfiltration Controls

Network-level DEP should be complemented by **data-level** controls to achieve defense in depth:

Control	Mechanism	Scope
Microsoft Purview Information Protection	Classify and label sensitive data (sensitivity labels). Labels flow with data across Fabric items (Lakehouses, Warehouses, Semantic Models, Reports).	Tenant
Data Loss Prevention (DLP)	Define policies in Microsoft Purview DLP to detect and block sharing or export of items containing sensitive information (e.g., prevent download of datasets labeled "Highly Confidential").	Tenant
Power BI Export Restrictions	Disable or restrict exports to Excel, CSV, PowerPoint, PDF and printing via tenant settings. When tenant-level Private Link is enabled, several export options are automatically disabled.	Tenant
Endpoint DLP	Use Microsoft Purview Endpoint DLP on managed devices to prevent copy/paste of Fabric data to USB drives, unauthorized cloud apps or personal email.	Device
Conditional Access — Session Controls	Leverage Defender for Cloud Apps session policies to monitor, block or limit downloads of sensitive content from the Fabric web portal in real time.	Session

> **Recommendation:** Combine **Outbound Access Policies** (network) with **Purview sensitivity labels + DLP policies** (data) for a layered approach. Network controls prevent unauthorized destinations; data controls prevent unauthorized actions even on authorized destinations.

6 Data Security

6.1 Encryption



Figure 11: Diagram 11
Network Configurations in Microsoft Fabric

Type	Mechanism	Detail
In transit	TLS 1.2 / 1.3	All client-to-Fabric and inter-experience traffic
At rest	Microsoft-managed keys (default)	Automatic encryption of all data in OneLake
At rest (advanced)	Customer Managed Keys (CMK)	Second layer of encryption with customer-managed Azure Key Vault keys
Power BI	BYOK	Bring Your Own Key for Power BI datasets

6.2 Customer Managed Keys (CMK)

CMK allows organizations to add an **additional encryption layer** with keys they manage themselves in Azure Key Vault.

Status (as of April 2026):

Item Type	Status
Lakehouse, Spark Job, Environment, Pipeline, Dataflow, API for GraphQL, ML Model/Experiment	**GA** (since Oct 2025)
Data Warehouse	**GA** (since Oct 2025)
Databases, Mirrored Experiences, Power BI	Planned (roadmap)

7 Data Residency and Multi-Geo

Microsoft Fabric supports **multi-geo** deployment with capacities spread across **54 data centers** worldwide.

Characteristics: - Workspaces in different regions are still part of the same OneLake data lake - The query execution layer, caches, and data remain in the Azure geography where they were created - Some metadata and processing is stored at rest in the tenant's home geography - **Data Residency compliant** by default

8 DNS Configuration for Private Link

Proper DNS resolution is critical for Private Link deployments. Without correct DNS, clients resolve Fabric FQDNs to public IPs and bypass Private Endpoints entirely.

8.1 Required Private DNS Zones

DNS Zone	Used By
`privatelink.analysis.windows.net`	Power BI / Semantic Models
`privatelink.pbidedicated.windows.net`	Dedicated capacity endpoints

DNS Zone	Used By
`privatelink.prod.powerapps.com`	Dataflows
`privatelink.blob.core.windows.net`	OneLake (ADLS Gen2 storage)
`privatelink.dfs.core.windows.net`	OneLake (DFS endpoint)
`privatelink.servicebus.windows.net`	Event Hubs / Eventstream
`privatelink.web.core.windows.net`	Fabric portal static content

8.2 DNS Architecture Patterns

Pattern	Description	Best For
Centralized Private DNS Zone	Single zone linked to all VNets (hub-spoke topology). Managed in the hub subscription.	Multi-VNet environments with centralized IT
Azure DNS Private Resolver	Enables on-premises DNS servers to resolve Azure Private DNS Zones via conditional forwarding (forwarders pointing to 168.63.129.16 through the resolver's inbound endpoint).	Hybrid environments with on-premises DNS
Conditional forwarders	On-premises DNS forwards specific zones (e.g., `*.analysis.windows.net`) to Azure DNS. Requires VPN/ER connectivity.	Simple hybrid setups

8.3 IP Address Planning

When deploying multiple Private Endpoints (tenant-level + workspace-level), plan subnet sizing carefully:

- Each Private Endpoint consumes **one private IP** from the subnet
- Workspace-level Private Link requires **one PE per workspace** per VNet
- Reserve at least a **`/27`** (32 IPs) subnet for Fabric Private Endpoints to allow growth
- Use separate subnets for Fabric PEs and other Azure service PEs for clear NSG rule application

Common pitfall: Forgetting to create or link Private DNS Zones is the most frequent cause of Private Link connectivity failures. Always verify with `nslookup` or `Resolve-DnsName` that Fabric FQDNs resolve to `10.x.x.x` (private IPs) rather than public IPs from the client's network.

8.4 DNS Best Practices Checklist

DNS Quick Validation Guide

1. **Create all required Private DNS Zones** listed above and link them to every VNet that hosts a Private Endpoint or from which users connect to Fabric.
2. **Test resolution before go-live** — from a VM inside the VNet, run:
   - `nslookup <your-workspace>.fabric.microsoft.com` (Windows)

- `Resolve-DnsName <your-workspace>.pbidedicated.windows.net` (PowerShell)
- Expected: a `10.x.x.x` private IP, **not** a public IP.

3. **Hybrid DNS:** If using on-premises DNS servers, configure **conditional forwarders** for each `privatelink.*` zone pointing to Azure DNS (`168.63.129.16`) via an Azure DNS Private Resolver or a DNS forwarder VM in the VNet.
4. **Automate DNS record lifecycle:** Use Azure Policy (e.g., `Deploy-DINE-PrivateDNSZoneGroup`) to automatically create DNS records when new Private Endpoints are provisioned — manual record management is error-prone at scale.
5. **Monitor for DNS drift:** Periodically re-run resolution tests after infrastructure changes (VNet peering, new PEs, zone re-linking). A broken DNS zone link silently reverts traffic to the public path.

9 Monitoring, Logging and Auditing

Network security controls are only effective if monitored. Fabric integrates with Azure's monitoring ecosystem to provide visibility into access patterns, threats and configuration drift.

9.1 Diagnostic Logging

Log Source	Destination	Key Signals
Microsoft Entra ID Sign-in Logs	Log Analytics	Failed/successful sign-ins, MFA challenges, Conditional Access policy hits, risky sign-ins
Fabric Admin Audit Logs	Log Analytics / Event Hub	Workspace creation, sharing changes, data exports, gateway operations
Azure Private Link Metrics	Azure Monitor	Bytes in/out through Private Endpoints, connection counts, NAT port utilization
NSG Flow Logs	Storage Account / Traffic Analytics	Source/dest IPs, ports, protocols, allow/deny decisions on PE subnets
Azure Firewall Logs	Log Analytics	Application/network rule hits, threat intelligence matches, DNS queries

9.2 Azure Monitor Integration

- Create **alerts** on Fabric capacity metrics (CU utilization, throttling events) and network metrics (PE connection failures, dropped packets)
- Use **Workbooks** to visualize Private Endpoint traffic patterns, top source IPs and blocked connections
- Set up **diagnostic settings** on Private Link Scopes and NSGs to stream logs to a central Log Analytics workspace

9.3 Microsoft Sentinel Integration

For security-focused organizations, integrate Fabric signals with **Microsoft Sentinel**:

- **Data connectors:** Ingest Entra ID sign-in/audit logs, Fabric admin audit logs, and NSG flow logs into Sentinel
- **Analytics rules:** Detect anomalies such as logins from unexpected geolocations, sudden data export spikes, bulk permission changes, or sign-ins bypassing Conditional Access
- **Automated response:** Use Sentinel playbooks (Logic Apps) to respond to alerts — e.g., disable a compromised service principal, notify the SOC, or quarantine a workspace
- **Hunting queries:** Proactively search for lateral movement between workspaces, unusual API call patterns or data exfiltration indicators

9.4 Audit Best Practices

- Review IP Firewall and Outbound Access Policy rules **quarterly** to remove stale entries
- Monitor Entra Conditional Access policy evaluation logs for unexpected "Not Applied" results
- Track Private Endpoint approval/rejection events on target Azure resources
- Validate that DNS resolution returns private IPs periodically (regression detection)

10 Testing and Validation

After deploying network security controls, validate that they work as intended and do not introduce unacceptable latency or block legitimate traffic.

10.1 Connectivity Validation

Test	Tool	Expected Result
DNS resolution for Private Endpoint	`nslookup <workspace>.fabric.microsoft.com` or `Resolve-DnsName`	Returns private IP (10.x.x.x)
Fabric portal access via PE	Browser from within VNet or VPN-connected client	Portal loads; no public IP fallback
IP Firewall block test	Access from an IP not in the allow list	HTTP 403 Forbidden
Managed PE to Azure SQL	Run a notebook query from Fabric against a firewall-enabled SQL DB	Query succeeds; SQL audit log shows private IP source
Outbound policy block test	Attempt to connect to a non-allowed destination from a notebook	Connection refused / timed out

10.2 Performance Validation

- **Baseline first:** Measure query and pipeline performance **before** enabling Private Link or Managed VNets to establish a reference point
- **Spark startup time:** Custom pools in a Managed VNet take 3–5 minutes to start (vs. seconds for Starter Pools). Factor this into SLAs and user expectations
- **Private Endpoint throughput:** Monitor PE metrics for saturation. A single PE supports up to 8 Gbps; for high-throughput scenarios, verify that bandwidth is not a bottleneck
- **Cross-region latency:** When capacities and Private Endpoints are in different regions (multi-geo), measure added latency and consider co-locating PEs with capacities

10.3 Periodic Reviews

Review	Frequency	Responsible
IP Firewall rules accuracy	Monthly	Workspace admin
Outbound policy allowed destinations	Quarterly	Security team
Private Endpoint approvals on target resources	Quarterly	Azure subscription owner
Conditional Access policy effectiveness	Quarterly	Identity team
DNS zone records and VNet links	Semi-annually	Network team
Penetration testing (Fabric-adjacent infrastructure)	Annually	Security team

11 Compliance and Certifications

Microsoft Fabric supports a wide range of compliance standards:

Certification	Date
ISO 27001, 27701, 27017, 27018	December 2023
HIPAA	January 2024
Australian IRAP	February 2024
SOC 1 & 2 Type 2, SOX, CSA STAR	May 2024
HITRUST	September 2024
FedRAMP (Azure Commercial)	November 2024
PCI DSS	January 2025
K-ISMS	May 2025
GDPR, EUDB	Supported

Fabric is a core **Microsoft Online Service**.

12 Decision Guide



Figure 12: Diagram 12

13 Feature Summary and Status

Updated as of April 2026

Feature	Level	Direction	Status	Primary Use Case
Entra Conditional Access	Tenant	Inbound	**GA**	Zero Trust, MFA, IP filtering
Private Link Tenant	Tenant	Inbound	**GA**	Full tenant network isolation
Private Link Workspace	Workspace	Inbound	**GA**	Granular per-workspace network isolation
Workspace IP Firewall	Workspace	Inbound	**GA**	IP-based restriction without VNet infrastructure
Trusted Workspace Access	Workspace	Outbound	**GA**	Firewall-enabled ADLS Gen2 access
Managed Private Endpoints	Workspace	Outbound	**GA**	Private connection to Azure sources
Managed VNets	Workspace	Outbound	**GA**	Spark isolation + MPE support

Feature	Level	Direction	Status	Primary Use Case
VNet Data Gateway	Org	Outbound	**GA**	Managed connection to Azure services in VNet; enterprise proxy & cert auth support
On-Premises Gateway	Org	Outbound	**GA**	Connection to on-premises sources
Service Tags	NSG/Firewall	Both	**GA**	Azure network rules
Outbound Access Policies	Workspace	Outbound	**GA**	Data exfiltration prevention
Customer Managed Keys	Workspace	Data	**GA**	Dual-layer encryption
Eventstream Private Network	Workspace	Outbound	**Preview**	Secure real-time ingestion from private networks
Power BI Network Isolation	Workspace	Inbound	**Planned**	WS-level Private Link and IP Firewall for Power BI items
Fabric Databases Network Isolation	Workspace	Inbound	**Planned**	WS-level Private Link and IP Firewall for Fabric databases

14 Feature Dependencies

The following diagram shows how Fabric network features depend on each other. Understanding these dependencies is critical to avoid misconfiguration.

Key dependency chains:

Chain	Steps	Notes
Managed Private Endpoints	F SKU → Managed VNet (auto-provisioned) → MPE created → Source owner approves PE	Managed VNet is provisioned on first MPE creation or first Spark job with Private Link enabled
Trusted Workspace Access	F SKU → Workspace Identity → RBAC role on ADLS Gen2 → Resource Instance Rule on storage firewall	All 4 steps required; failure at any step silently blocks access
Workspace Private Link	Tenant admin enables WS inbound rules → VNet + PE + Private DNS Zone → WS admin disables public access	DNS zone is often forgotten — verify with nslookup

Chain	Steps	Notes
Outbound Access Policies	Managed VNet + MPE (or Data Connections) → Enable outbound policy → Non-listed destinations blocked	Must declare all legitimate destinations before enabling
Full DEP	Inbound (PL or IPFW or CA) + Outbound (OAP)	Both sides required for complete exfiltration protection

How to read this diagram:

- **Orange boxes (top)** are prerequisites that must be in place before any feature can be enabled: a Fabric F SKU capacity, the tenant-level toggle for workspace inbound rules, or an Entra ID P1 license.
- **Arrows** represent "requires" relationships — follow them top-down to see what each feature depends on. For example, *Managed Private Endpoints* (green) require a *Managed VNet* (green), which itself requires an *F SKU* (orange).
- **Teal boxes** are Azure infrastructure components (VNet, Private Endpoints, DNS Zones, ExpressRoute/VPN) that must be provisioned in the customer's subscription.
- **Purple boxes** are identity prerequisites specific to Trusted Workspace Access (Workspace Identity, RBAC role, Resource Instance Rule).
- **The dashed arrow** from MPE to Managed VNet indicates that the VNet is auto-provisioned when the first MPE is created — you don't need to create it manually.
- **Red box** (Outbound Access Policies) sits at the end of the chain: it requires both Managed VNet and MPE to be in place, since it blocks all destinations not explicitly declared.

15 End-to-End Network Architecture

The following diagram provides a consolidated view of the complete Fabric network security architecture — inbound protection, outbound connectivity, data exfiltration prevention, DNS resolution and monitoring.

> **Legend:** Green = protected workspaces (covered by WS Private Link / IP Firewall). Yellow = Power BI items (not yet covered by workspace-level network controls — use tenant-level PL or Conditional Access).

How to read this diagram:

The diagram is organized in **7 horizontal layers**, top to bottom, following the path of a request from user to data source:

1. **Clients** (top, purple): Three types of callers — corporate users on VPN/ExpressRoute, remote users on the internet, and automated service principals. All must authenticate.
2. **Identity Layer** (purple): Microsoft Entra ID evaluates every request. Conditional Access policies (MFA, device compliance, location) decide whether access is granted or blocked. This is the first gate.
3. **Inbound Network Layer** (blue): Requests that pass identity checks are then filtered by network controls — Tenant Private Endpoint (entire tenant), Workspace Private Endpoints (specific



Figure 13: Diagram 13



Figure 14: Diagram 14

workspaces), or IP Firewall rules. The dashed red arrow shows that remote users are blocked if PL/IPFW is enforced.

4. **DNS Resolution** (teal, left): Private DNS Zones and DNS Private Resolvers ensure that Fabric FQDNs resolve to private IPs rather than public ones. Without this layer, Private Endpoints are bypassed.
5. **Microsoft Fabric Tenant** (blue, center): Contains two workspace groups — *Protected Workspaces* (green, covered by WS-level network controls) and *Power BI Workspaces* (yellow, not yet covered — network protection planned). OneLake sits below both.
6. **Secure Outbound** (green) and **Outbound Protection** (red): When Fabric needs external data, it uses Managed VNets → Managed Private Endpoints (to Azure SQL, Cosmos DB), Trusted Workspace Access (to ADLS Gen2) or Gateways (to on-premises). Outbound Access Policies block any destination not explicitly allowed.
7. **Monitoring & Audit** (cyan, bottom): Azure Monitor, Microsoft Sentinel and Fabric Admin Audit Logs receive telemetry from the entire tenant for threat detection and compliance reporting.

Key insight: A fully secured Fabric environment activates all 7 layers. Most organizations start with layers 1–2 (identity) and progressively add layers 3–7 as maturity increases.

16 Known Limitations by Item Type

The following table consolidates all known limitations for workspace-level network protection features as of April 2026.

Item Type	WS Private Link	WS IP Firewall	Managed VNet / MPE	Outbound Access Policies	CMK
Lakehouse	**GA**	**GA**	**GA**	**GA**	**GA**
Warehouse	**GA**	**GA**	—	**GA**	**GA**
Notebook / Spark Job	**GA**	**GA**	**GA**	**GA**	**GA**
Pipeline / Dataflow	**GA**	**GA**	—	**GA**	**GA**
Eventstream	**GA**	**GA**	**GA**	**GA**	**GA**
ML Experiment / Model	**GA**	**GA**	**GA**	—	**GA**
Mirrored Database	**GA**	**GA**	—	**GA**	—
Shortcut (OneLake)	**GA**	**GA**	—	—	—
API for GraphQL	—	—	—	—	**GA**
Power BI Reports	**Planned**	**Planned**	—	**Planned**	**Planned**
Power BI Dashboards	**Planned**	**Planned**	—	**Planned**	**Planned**
Semantic Models	**Planned**	**Planned**	—	**Planned**	**Planned**
Fabric Databases	**Planned**	**Planned**	—	**Planned**	**Planned**
Data Activator	**Planned**	**Planned**	—	—	—
Deployment Pipelines	**Planned**	**Planned**	—	—	—
Default Semantic Models	**Planned**	**Planned**	—	—	—

Key takeaway: Power BI items (reports, dashboards, semantic models), Fabric Databases, Data Activator, deployment pipelines and default semantic models are **not**

yet protected by workspace-level network controls. Until roadmap items ship, protect them with **tenant-level Private Link** (blocks all public access) or **Entra Conditional Access** (identity-based restriction).

17 Recommended Architectures by Scenario

17.1 Scenario 1 — Regulated Enterprise (GDPR / HIPAA / PCI DSS)

Profile: Multi-tenant organization with strict data residency requirements, sensitive PII/PHI data, mandatory audit trails.

Layer	Recommendation
Inbound	Tenant-level Private Link + Block Public Access. All users connect via ExpressRoute or VPN.
Outbound	Managed VNets + Managed Private Endpoints for all Azure data sources. Outbound Access Policies enabled on every workspace.
Identity	Entra Conditional Access: require MFA (phishing-resistant), compliant devices only, block sign-ins from non-approved countries. PIM for admin roles.
Data	CMK for all supported items. Purview sensitivity labels + DLP policies. Power BI export restrictions (disable CSV/Excel export).
DNS	Centralized Private DNS Zones in hub subscription. Azure DNS Private Resolver for hybrid resolution.
Monitoring	All diagnostic logs to Log Analytics. Microsoft Sentinel with analytics rules for anomaly detection. Quarterly rule reviews.
Limitations	Power BI items not covered by WS-level PL — tenant-level PL provides coverage. Plan for migration when WS-level support ships.

17.2 Scenario 2 — Data Platform Team with Mixed Sensitivity

Profile: Central data team serving multiple business units. Some workspaces contain sensitive data, others are for self-service analytics.

Layer	Recommendation
Inbound	Workspace-level Private Link for sensitive workspaces (data engineering, warehouse). IP Firewall for semi-restricted workspaces. Public access for self-service BI.
Outbound	Trusted Workspace Access for ADLS Gen2. Managed Private Endpoints for Azure SQL and Cosmos DB. VNet Data Gateway for Dataflows Gen2.
Identity	Conditional Access: MFA for all users, device compliance for admin roles.
Data	CMK on sensitive workspaces. Sensitivity labels propagated to downstream reports.
DNS	Private DNS Zones linked to spoke VNets hosting PEs.

Layer	Recommendation
Monitoring	Fabric admin audit logs + Azure Monitor alerts on PE connection failures.

17.3 Scenario 3 — Small Team / Startup (Cost-Optimized)

Profile: Small team, limited Azure infrastructure, no VPN/ExpressRoute. Need basic protection without complexity.

Layer	Recommendation
Inbound	Entra Conditional Access (MFA required, block risky sign-ins). Workspace IP Firewall for production workspaces (office IP only).
Outbound	VNet Data Gateway if connecting to Azure SQL in a VNet. On-premises gateway for local data sources.
Identity	MFA for all users. PIM if Entra P2 available.
Data	Microsoft-managed encryption (default). Sensitivity labels if M365 E5 available.
DNS	Not applicable (no Private Link).
Monitoring	Entra sign-in logs. Fabric admin audit logs in default storage.

17.4 Scenario 4 — Multi-Region Global Deployment

Profile: Global organization with capacities across multiple Azure regions and strict data residency per region.

Layer	Recommendation
Inbound	Workspace-level Private Link per region (PE co-located with capacity). Conditional Access with named locations per country.
Outbound	Managed Private Endpoints per region. Regional Managed VNets (one per capacity region). Azure Firewall in each regional hub for centralized egress logging.
Identity	Conditional Access with location-based policies. PIM with regional admin scoping.
Data	CMK with regional Key Vault instances. Multi-geo capacities ensuring data stays in-region.
DNS	Per-region Private DNS Zones with global zone peering. Regional DNS Private Resolvers.
Monitoring	Regional Log Analytics workspaces feeding a global Sentinel instance. Cross-region correlation rules.

18 References

- Security overview - Microsoft Fabric
- Private Links overview

- Workspace-level Private Links
- Managed VNets overview
- Managed Private Endpoints
- Trusted Workspace Access
- Protect Inbound Traffic
- Conditional Access in Fabric
- IP Firewall Rules in Fabric
- Service Tags
- VNet Data Gateway
- Information Protection in Fabric
- Data Loss Prevention in Fabric
- Azure Private DNS Zones
- Microsoft Sentinel — Entra ID connector
- Fabric Security Whitepaper
- *End-to-end network security in Microsoft Fabric* – Arthi Ramasubramanian Iyer & Rick Xu, FabCon 2025