

Module 1

Intro to Nemo


OUTLINE

- Overview of NEMO – Simulation components
- User's interface: the parameter file & its syntax
- Population component
- Representation of space in Nemo
- Life cycle events (LCE)
- Traits, and their genetics
- References
- Resources

Overview of Nemo's features


Population	Spatially explicit meta-population framework Discrete space, ind. move between patches → space modeled via the migration matrix
Mating systems	Random mating/promiscuity, monogamy, polygyny, selfing, cloning, hermaphroditic, assortative
Life Cycle	Complete flexibility in the order of the events
Traits & genetics	<ul style="list-style-type: none">• neutral markers (μ-satellites, SNP)• deleterious mutations (di-allelic)• BDM incompatibility loci• quantitative traits: QTL with pleiotropy (n-traits)
Selection	spatially & temporally varying, multi-trait fitness
Demography	stochastic, stage-structured, d.d. regulation, fitness dpdt, etc.

Nemo: Life Cycle



- breed
- disperse
- selection
- aging
- extinction/harvesting
- cloning
- crossing (on a pedigree)
- mutator
- stats & files I/O

Simulation Components:



Nemo: components

Simulation Components:

- Each component defines a set of parameters
- A component is included in a simulation only if its parameters are set
- Two components are mandatory: `simulation` and `population`
- A minimum of one life cycle event (LCE) is required
- Individuals without trait (no genetics) can be simulated

Nemo: components

Simulation Components:

- Each component defines a set of parameters
- A component is included in a simulation only if its parameters are set
- Two components are mandatory: `simulation` and `population`
- A minimum of one life cycle event (LCE) is required
- Individuals without trait (no genetics) can be simulated

Program interface

A simple text file with the simulation's parameters and values

Nemo interface: a simple parameter file

```
## NEMO-AGE CONFIG FILE ##

## SIMULATION ##
run_mode overwrite

random_seed 2

root_dir examples

filename example3-evolution-popini

replicates 5
generations 20000

## POPULATION ##
patch_number 1
patch_capacity 10

### AGE STRUCTURE and LESLIE MATRIX ###
pop_age_structure {{0,1,2,3,4,5}}
pop_transition_matrix {{0, 0, 0, 0, 0, 124}
                       {0.83, 0, 0, 0, 0, 0}
                       {0, 0.92, 0, 0, 0, 0}
                       {0, 0, 0.93, 0, 0, 0}
                       {0, 0, 0, 0.26, 0, 0}
                       {0, 0, 0, 0, 0.43, 0.53}}

## LIFE CYCLE EVENTS ##
quanti_init 0
breed 1
save_stats 2
save_files 3
regulation 4
viability_selection 5
aging_multi 6
store 7

## MATING SYSTEM ##
mating_system 1 #random mating

## REGULATION ##
```


Syntax of the parameter file

Basic structure of the parameter file:

- a list of `parameter argument` pairs, separated by at least one space
- each pair on a single line.

Parameter specification:

```
replicates 10  
generations 100000
```

Comments:

```
# this is a one-line comment  
#!/ this is the start of a block comment  
text within a block comment  
text within a block comment  
text within a block comment  
/## this is the end of a block comment
```

Syntax of the parameter file: matrix

matrix arguments: comma separated elements within curly brackets

```
matrix_param {{row 1}{row 2}{col1, col2, col3}{m41,m42,m43}}
```

```
dispersal_matrix {{0.9,0.05,0.05}{0.05,0.9,0.05}{0.05,0.05,0.9}}
```

Syntax of the parameter file: matrix

matrix arguments: comma separated elements within curly brackets

```
matrix_param {{row 1}{row 2}{col1, col2, col3}{m41,m42,m43}}
```

```
dispersal_matrix {{0.9,0.05,0.05}{0.05,0.9,0.05}{0.05,0.05,0.9}}
```

matrix arguments can be split across multiple lines:

```
dispersal_matrix {{0.9,0.05,0.05}  
                  {0.05,0.9,0.05}  
                  {0.05,0.05,0.9}}
```

Syntax of the parameter file: types

Numbers

dispersal_rate	.001
delet_mutation_rate	2.35e-7
generations	1e5

Syntax of the parameter file: types

Numbers

```
dispersal_rate      .001
delet_mutation_rate 2.35e-7
generations         1e5
```

Booleans

Works on presence/absence basis: presence = TRUE, absence = FALSE. We add a parameter to select (turn-on) a feature.

```
delet_save_genotypes
quanti_freq_output
```

Syntax of the parameter file: types

Numbers

```
dispersal_rate      .001
delet_mutation_rate 2.35e-7
generations         1e5
```

Booleans

Works on presence/absence basis: presence = TRUE, absence = FALSE. We add a parameter to select (turn-on) a feature.

```
delet_save_genotypes
quanti_freq_output
```

Strings (un-quoted)

```
filename      10pop-N1000-disp0.1-mut0002
root_dir      simProjectA/model1
```

Syntax of the parameter file: macros

Macros are small functions that help write parameter arguments:

repeat: `rep(x, n, each=1, sep=",")`

```
quanti_random_genetic_map  {{rep(10,5)}}
```

```
quanti_pleio_matrix {rep("{0,1}{1,0}", 3, sep="")}
```

results in:

```
quanti_random_genetic_map  {{10,10,10,10,10}}
```

```
quanti_pleio_matrix {{0,1}{1,0}{0,1}{1,0}{0,1}{1,0}}
```

Syntax of the parameter file: macros

Macros are small functions that help write parameter arguments:

repeat: `rep(x, n, each=1, sep=",")`

```
quanti_random_genetic_map  {{rep(10,5)}}  
quanti_pleio_matrix {rep("{0,1}{1,0}", 3, sep="")}
```

results in:

```
quanti_random_genetic_map  {{10,10,10,10,10}}  
quanti_pleio_matrix {{0,1}{1,0}{0,1}{1,0}{0,1}{1,0}}
```

sequence: `seq(from, to, by, sep=",")`

```
quanti_genetic_map  {{seq(1,50,5)}}  
dispersal_rate      seq(0.01,0.1,0.01,sep=" ")
```

results in:

```
quanti_genetic_map  {{1,6,11,16,21,26,31,36,41,46}}  
dispersal_rate      0.01 0.02 0.03 0.04 0.05 0.06 ... 0.1
```


Running many simulations from a single file

```
## SIMULATION ##
random_seed 2131454
run_mode overwrite

logfile logfile.log
root_dir test
filename landscape1_m%'.3'1

replicates 10
generations 2000

## POPULATION ##
patch_number 10000
patch_capacity 500

## LIFE CYCLE EVENTS ##
breed 1
disperse 2
aging 3

## DISPERSAL ##
dispersal_model 4 # 2D lattice
dispersal_rate 0.001 0.005 0.01 0.05 0.1 0.15 0.2 0.4
dispersal_lattice_range 1
dispersal_border_model 3
```

Running many simulations from a single file

```
[fred@fred test]$ nemo2.3.46 demo-test.txt

N E M O 2.3.46r7 [09 Feb 2017]

Copyright (C) blablaba
http://nemo2.sourceforge.net

-----
reading parameters from "demo-test.txt"
setting random seed from input value: 2131454

--- SIMULATION 1/8 ---- [ landscape1_m001 ]

    start: 19-06-2017 17:40:19
    mode: overwrite
    traits:
    LCEs: breed(1), disperse(2), aging(3),
    outputs: test/{*.log}

    replicate 10/10 [17:41:50] 2000/2000

    end: 19-06-2017 17:42:01
--- done (CPU time: 00:01:41s)

--- SIMULATION 2/8 ---- [ landscape1_m005 ]

    start: 19-06-2017 17:42:01
    [...]

--- done (CPU time: 00:01:46s)

--- SIMULATION 3/8 ---- [ landscape1_m010 ]
```

Syntax of the parameter file

temporal arguments:

```
(@g0 initial_value, @g123 new_value1, @g456 new_value2)
```

Temporal arguments must be within '()', comma-separated, and start with @g0 for initialization at the first generation.

external file argument: &path/to/file.txt

The argument value in the file must be specified with the same format as if it were provided in the parameter file itself.


line continuation: character \

Arguments can spread over multiple lines when using the 'escape' character \. Example:

```
(@g0 initial_value, @g123 new_value1, @g456 new_value2, \  
@g789 new_value3)
```

Metapopulation framework

- can set the: number of patches & carrying capacities ($K_{\text{♀}}$, $K_{\text{♂}}$)
- patch size is dynamical: $N_t = \sum(\text{stochastic events})$
- extinction/colonisation events can occur
- can update the population structure (patch number & capacity)
- can set the age structure (overlapping generations)




Population component

Nemo

Components

Individuals

- are diploid
- have a gender and an age
- are a collection of traits



Population component

Population parameters

```
# setting 1:
patch_number      128
patch_capacity     1000 # will fill patches with 500 females and 500 males

#setting 2:
patch_number      128
patch_nbfem       1000 # only females if we model hermaphrodites (see mating system 4
patch_nbmal       0

#setting 3:
patch_capacity     {{10,0,23,50,1298,5,0,0,0,1000}} #patch_number = array size = 10
```

The parameter `patch_capacity` sets the *maximum patch size*, or its *carrying capacity* K .

Population component

Population parameters

```
# setting 1:
patch_number      128
patch_capacity     1000 # will fill patches with 500 females and 500 males

#setting 2:
patch_number      128
patch_nbfem       1000 # only females if we model hermaphrodites (see mating system 4)
patch_nbmal       0

#setting 3:
patch_capacity     {{10,0,23,50,1298,5,0,0,0,1000}} #patch_number = array size = 10
```

The parameter `patch_capacity` sets the *maximum patch size*, or its *carrying capacity* K .

If set to 0, the patch will be empty after *regulation* (see the `aging` LCE).

Population component

Population parameters

```
# setting 1:
patch_number      128
patch_capacity     1000 # will fill patches with 500 females and 500 males

#setting 2:
patch_number      128
patch_nbfem       1000 # only females if we model hermaphrodites (see mating system 4)
patch_nbmal       0

#setting 3:
patch_capacity     {{10,0,23,50,1298,5,0,0,0,1000}} #patch_number = array size = 10
```

The parameter `patch_capacity` sets the *maximum patch size*, or its *carrying capacity* K .

If set to 0, the patch will be empty after *regulation* (see the `aging` LCE).

Useful when one wants to “open” the patch at a later generation with a temporal arguments.

Dispersal and representation of Space

- spatially explicit, but no explicit x-y coordinates
- space abstracted into a migration matrix
- reduced (connectivity) matrices allow simulation of large landscapes

patches:

1	2	3
4	5	6
7	8	9

to

	1	2	3	4	5	6	7	8	9
1	1 → 1	1 → 2	1 → 3	1 → 4	1 → 5	1 → 6	1 → 7	1 → 8	1 → 9
2	2 → 1	2 → 2	2 → 3	2 → 4	2 → 5	2 → 6	2 → 7	2 → 8	2 → 9
3	3 → 1	3 → 2	3 → 3	3 → 4	3 → 5	3 → 6	3 → 7	3 → 8	3 → 9
4	4 → 1	4 → 2	4 → 3	4 → 4	4 → 5	4 → 6	4 → 7	4 → 8	4 → 9
5	5 → 1	5 → 2	5 → 3	5 → 4	5 → 5	5 → 6	5 → 7	5 → 8	5 → 9
6	6 → 1	6 → 2	6 → 3	6 → 4	6 → 5	6 → 6	6 → 7	6 → 8	6 → 9
7	7 → 1	7 → 2	7 → 3	7 → 4	7 → 5	7 → 6	7 → 7	7 → 8	7 → 9
8	8 → 1	8 → 2	8 → 3	8 → 4	8 → 5	8 → 6	8 → 7	8 → 8	8 → 9
9	9 → 1	9 → 2	9 → 3	9 → 4	9 → 5	9 → 6	9 → 7	9 → 8	9 → 9

from

$N_{patch} \times N_{patch}$ matrix


↓

$\{ \{0.2, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1\}$
 $\{0.1, 0.2, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1\}$
 $\{0.1, 0.1, 0.2, 0.1, 0.1, 0.1, 0.1, 0.1, 0.1\}$
 $\{0.1, 0.1, 0.1, 0.2, 0.1, 0.1, 0.1, 0.1, 0.1\}$
 $\{0.1, 0.1, 0.1, 0.1, 0.2, 0.1, 0.1, 0.1, 0.1\}$

Dispersal and representation of Space

- spatially explicit, but no explicit x-y coordinates
- space abstracted into a migration matrix
- reduced (connectivity) matrices allow simulation of large landscapes

patches:



```
connectivity_matrix {
  {1,2,4,5}
  {2,1,3,4,5,6}
  {3,2,5,6}
  ...
  {9,5,6,8}
}
```

N_{patch} rows

```
reduced_matrix {
  {0.7,0.1,0.1,0.1}
  {0.5,0.1,0.1,0.1,0.1,0.1}
  {0.7,0.1,0.1,0.1}
  ...
  {0.7,0.1,0.1,0.1}
}
```

```

## Simple simulation example ##

random_seed 2131454
run_mode      overwrite

logfile      test.log
roo_dir      test

filenames    landscape1_m0.005

replicates   10
generations  1000

## POPULATION ##
patch_number 200
patch_capacity 500

## LIFE CYCLE EVENT ##
breed        1
disperse     2
aging        3

## DISPERSAL LCE ##
# dispersal models:
# 1 = Island Model Migrant Pool
# 2 = Island Model Propagule Pool
# 3 = Stepping Stone Model 1D
# 4 = Lattice Model
dispersal_model 1
dispersal_rate  0.005

# lattice example:
dispersal_model 4
dispersal_rate  0.005
dispersal_lattice_range 1
dispersal_lattice_model 3

# using dispersal matrices:
dispersal_connectivity_matrix &Patch-connectivity.txt
dispersal_reduced_matrix      &Patch-dispersal-rates.txt

```

dispersal connectivity matrix:

[1, 2, 33, 34, 3, 65, 35, 66, 67, 4, 97, 36, 98, 68, 99, 5, 129, 37, 130, 100, 69, 131, 6, 101, 132, 161, 38, 162, 70, 133, 134, 71, 135, 136, 72, 137, 138, 73, 139, 140, 74, 141, 142, 75, 143, 144, 76, 145, 146, 77, 147, 148, 78, 149, 79, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200]

dispersal rate matrix:

```
{0.992589103853264, 0.0022272779649963, 0.0022272779649963, 0.000884553280134066, 0.000373286982200115, 0.000373286982200115, 0.000373286982200115, 0.000373286982200115, 0.000373286982200115, 0.000373286982200115}, {0.989153576982218, 0.00221956896107078, 0.00221956896107078, 0.00221956896107078, 0.00088149168440329, 0.00088149168440329, 0.00088149168440329, 0.00088149168440329, 0.00088149168440329, 0.00088149168440329}, {0.988369866206209, 0.00221781038671654, 0.00221781038671654, 0.00221781038671654, 0.000880793274623348, 0.000880793274623348, 0.000880793274623348, 0.000880793274623348, 0.000880793274623348, 0.000880793274623348}, {0.988103144984967, 0.00221721188901334, 0.00221721188901334, 0.00221721188901334, 0.0008805558399163, 0.0008805558399163, 0.0008805558399163, 0.0008805558399163, 0.0008805558399163, 0.0008805558399163}, {0.988018720346143, 0.00221702244794753, 0.00221702244794753, 0.00221702244794753, 0.0008804803833681, 0.0008804803833681, 0.0008804803833681, 0.0008804803833681, 0.0008804803833681, 0.0008804803833681}, {0.987994087279237, 0.00221696717362815, 0.00221696717362815, 0.00221696717362815, 0.000880458396393103, 0.000880458396393103, 0.000880458396393103, 0.000880458396393103, 0.000880458396393103, 0.000880458396393103}, {0.987986351609929, 0.0022169498155031, 0.0022169498155031, 0.0022169498155031, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947}, {0.987986351609929, 0.0022169498155031, 0.0022169498155031, 0.0022169498155031, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947}, {0.987986351609929, 0.0022169498155031, 0.0022169498155031, 0.0022169498155031, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947}, {0.987986351609929, 0.0022169498155031, 0.0022169498155031, 0.0022169498155031, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947, 0.000880451502692947}
```

Life-cycle events:

aging: increase the age of the individuals, perform patch regulation

breed: mate and breed, create new offspring generation

breed_wolbachia: breed and *Wolbachia* transmission/infection

cross: perform a half-sib, full-sib mating design (NCI)

disperse: offspring dispersal

disperse_evoldisp: offspring dispersal with evolving dispersal rates

extinction: random patch extinction or harvesting

regulation: patch regulation (to carrying capacity)

resize: modify population size (patch number and/or size)

save_files: write output files to disk

save_stats: record statistics

store: save simulation data to binary files

selection: perform viability selection on the offspring generation

breed_disperse: breed with backward migration (Wright-Fisher model)

breed_selection: breed with selection (faster)

breed_selection_disperse: all in one (Wright-Fisher with selection)

Life-cycle events:

→ effect on population composition:

LCE	Offspring	Adults
aging	<i>move to adults</i>	—
breed	+	<i>required</i>
cross	+	<i>required</i>
disperse	x (<i>required</i>)	
extinction	x	x
regulation	x	x
resize	x	x
selection	x (<i>required</i>)	

Table 4.1 in Nemo-manual p.33

Ordering of the LCEs

The LCEs can be set in *almost* any order in the life cycle. Some dependencies exist because the LCEs change the content of the age classes.

This works

breed	1	# adds offspring
viability_selection	2	
disperse	3	
aging	4	#removes offspring

This doesn't work

breed	1	
aging	2	#removes offspring
viability_selection	3	#no offspring
disperse	4	#no offspring

This works too

breed	1	
disperse	2	
viability_selection	3	# in arrival patch
aging	4	

Ordering of the LCEs

The LCEs can be set in *almost* any order in the life cycle. Some dependencies exist because the LCEs change the content of the age classes.

This works

breed	1	# adds offspring
viability_selection	2	
disperse	3	
aging	4	#removes offspring

This doesn't work

breed	1	
aging	2	#removes offspring
viability_selection	3	#no offspring
disperse	4	#no offspring

This works too

breed	1	
disperse	2	
viability_selection	3	# in arrival patch
aging	4	

The minimum life cycle

breed	1	
aging	2	

Ordering of the LCEs

The LCEs can be set in *almost* any order in the life cycle. Some dependencies exist because the LCEs change the content of the age classes.

This works

breed	1	# adds offspring
viability_selection	2	
disperse	3	
aging	4	#removes offspring

This doesn't work

breed	1	
aging	2	#removes offspring
viability_selection	3	#no offspring
disperse	4	#no offspring

This works too

breed	1	
disperse	2	
viability_selection	3	# in arrival patch
aging	4	

The minimum life cycle

breed	1	
aging	2	

This one is fine too!

patch_number	1	
patch_capacity	100	
source_pop	path/to/sim-P1-N100.bin	
## life cycle :		
save_stats	1	
save_files	2	

Traits:

sequence-based traits

ntrl : neutral markers (microsat, SNP)
delet : deleterious mutations (biallelic loci)
quanti : quantitative trait loci (continuous, biallelic)
dmi : Dobzhanski-Muller incompatibility loci
disp : dispersal locus (evolving dispersal rates)
wolb : *Wolbachia* infection status (endosymbiont with CI)

BUT, traits are **optional**, individuals may not carry any trait

Neutral trait ntr1

```
## NEUTRAL MARKER TRAIT ##  
# 1. microsatellites  
ntrl_locl          25  
ntrl_all           256  
ntrl_mutation_model 1      #1: single-step mutation, 2: k-allele model  
ntrl_mutation_rate  0.001  
ntrl_recombination_rate 0.5  
ntrl_save_genotype  FSTAT  
ntrl_save_freq       locus  
ntrl_output_dir      ntrl  
ntrl_output_logtime  {{1,50,1000}}
```

Neutral trait ntrl

```
## NEUTRAL MARKER TRAIT ##
# 1. microsatellites
ntrl_locl          25
ntrl_all           256
ntrl_mutation_model 1      #1: single-step mutation, 2: k-allele model
ntrl_mutation_rate 0.001
ntrl_recombination_rate 0.5
ntrl_save_genotype FSTAT
ntrl_save_freq      locus
ntrl_output_dir     ntrl
ntrl_output_logtime {{1,50,1000}}

# 2. SNPs
ntrl_locl          100000
ntrl_all           2
ntrl_mutation_model 2
ntrl_mutation_rate 1e-6
ntrl_random_genetic_map {{10}{10}{10}{10}{10}} # 5 linkage groups, 10cM each
ntrl_chromosome_num_locus {{1}{999}{24750}{24750}{24750}{24750}}
ntrl_genetic_map_resolution 0.001 #ie 10/10000: 10000 sites available per chromosome
ntrl_save_genotype PLINK
ntrl_output ...
```

Deleterious mutations trait delet

```
## DELET TRAIT ##
delet_loci          10000
delet_init_freq     0
delet_mutation_rate 1e-5
delet_backmutation_rate 1e-7
delet_fitness_model 1          # multiplicative across loci
delet_effects_mean  0.05      # mean (negative) fitness effect, s
delet_dominance_mean 0.36     # mean of the distribution of h
delet_effects_distribution lognormal # the DFE
delet_effects_dist_param1 -6.4
delet_effects_dist_param2 5.3
delet_save_genotype
...
```

Quantitative traits quant

```
## QUANT TRAIT ##

# 1. Gaussian additive model:
quanti_traits          1
quanti_loci            50      # additive loci
quanti_allele_model    continuous # mutations drawn from a normal distribution
quanti_mutation_variance 0.05   # a^2; variance of the normal distribution
quanti_mutation_rate   0.0001  # thus Vm = 2Lpa^2 = 0.0005
quanti_recombination_rate 0.5   # default
quanti_init_value      0        # initial trait phenotypic value is 0
quanti_init_model      1        # random mutations added
quanti_environmental_variance 0.1 # to set heritability < 1
```

Quantitative traits quant

```
## QUANT TRAIT ##
```

```
# 1. Gaussian additive model:
```

```
quanti_traits      1
quanti_loci        50          # additive loci
quanti_allele_model continuous # mutations drawn from a normal distribution
quanti_mutation_variance 0.05  # a^2; variance of the normal distribution
quanti_mutation_rate 0.0001    # thus Vm = 2Lpa^2 = 0.0005
quanti_recombination_rate 0.5  # default
quanti_init_value  0           # initial trait phenotypic value is 0
quanti_init_model   1           # random mutations added
quanti_environmental_variance 0.1 # to set heritability < 1
```

```
# 2. Discrete di-allelic model:
```

```
quanti_traits      1
quanti_loci        500        # additive loci
quanti_allele_model diallelic_HC # only 2 allele are segregating +a/-a
quanti_allele_value 0.01      # phenotypic range is [-10, +10], by step of 0.01
quanti_mutation_rate 0.0001   # switches between +a/-a states
quanti_recombination_rate {{1e-5}}{1e-5}}{1e-5}}{1e-5}}{1e-5}} # 5 chromosomes
quanti_init_model   4         # each locus is alternatively homozygote +a or -a
quanti_output       PLINK     # PLINK .ped, .fam, .map files
```

```
...
```

Pleiotropic traits with quant

```
# 3. Pleiotropy in the genotype-phenotype map
quanti_traits          3           # three phenotypic traits are modeled
quanti_loci            100         # loci fully pleiotropic, effect on all traits
quanti_allele_model    continuous  # mandatory for pleiotropic level > 2
quanti_mutation_rate   0.001
quanti_mutation_matrix {{0.05, 0, 0.025} # multivariate Gaussian distribution
                        {0, 0.05, 0.0125} # mutations have correlated effects on
                        {0.025, 0.0125, 0.05}} # traits 1&3 (0.5) and 2&3 (0.25)

quanti_init_model      0
...
```


Variable pleiotropy in the GP map with quant

```
## QUANTI TRAIT ##
quanti_traits      12
quanti_loci        120
quanti_pleio_matrix  {{1,1,1,0,0,0,0,0,0,0,0,0} # locus 1, pleio = 3
                       {0,0,0,1,1,1,0,0,0,0,0,0} # locus 2, pleio = 3
                       {1,0,1,0,1,0,1,0,1,0,1,0} # locus 3, pleio = 6
                       {0,1,0,1,0,1,0,1,0,1,0,1} # locus 4, pleio = 6
                       [...]}
quanti_mutation_matrix {{var1, var2, var3, cov12, cov13, cov23} # locus 1
                       {0.05, 0.05, 0.05, 0.45, 0.45, 0.45} # locus 2
                       {0.05, 0.15, 0.2, 0.05, 0.1, 0.45, ... } # locus 3
                       {0.05, 0.05, 0.05, 0.45, 0.45, 0.45, ... } # locus 4
                       [...]}
```



Jobran Chebib

Disponibile in nemo2.4.0!!!

Putting components together

```
## Simple simulation example ##

random_seed 2131454
run_mode      overwrite
logfile       test.log
root_dir      test

filename      landscape1_m0.005

replicates    10
generations   1000

## POPULATION ##
patch_number   200
patch_capacity  500

## LIFE CYCLE EVENT ##
breed          1
disperse       2
viability_selection 3
aging          4

## DISPERSAL LCE ##
dispersal_model 1 # island model
dispersal_rate   0.005

## BREED LCE ##
mating_system   1
mean_fecundity   4

## SELECTION LCE ##
selection_trait      quant
selection_model       gaussian
selection_trait_dimension 1
selection_variance    10
selection_local_optima {{0}{1}{2}{3}{4}{5}} # recycled across patches

## TRAITS ##
# NTRL
ntrl_loci      100000
ntrl_all       2
ntrl_mutation_model 2
ntrl_mutation_rate 1e-6
ntrl_random_genetic_map {{10}{10}{10}{10}{10}} # 5 linkage groups, 10cM each
ntrl_genetic_map_resolution 0.001 # 1e 10/10000: 10000 sites available per chromosome

# QUANTI
quanti_traits      1
quanti_loci        500 # additive loci
quanti_allele_model diallelic_HC # only 2 allele are segregating: +a/-a
quanti_allele_value 0.01 # phenotypic range is [-10, +10], by step of 0.01
quanti_mutation_rate 0.0001 # switches between +a/-a states
quanti_recombination_rate {{1e-5}{1e-5}{1e-5}{1e-5}} # 5 chromosomes
quanti_init_model    4 # each locus is alternatively homozygote +a or -a
quanti_output        PLINK # PLINK .ped, .fam, .map files
...
```

Other features

- Store and reload: use *store* LCE to save and load binary files
- Stage-structured populations: NEMO-AGE
- Multi-species simulations: *in development*
- Submit jobs on a cluster from an input file: NEMOSUB
- Parallelization: using MPI version to run replicates in parallel on a cluster

nemosub: submitting simulations to a job scheduler

```
## job scheduling parameters ## <-- nemosub
sub_program sbatch
sub_script_directive SBATCH
sub_parameters -mem-per-cpu=16000
sub_script_args nemo3.0.16
sub_jobname camp%.4'2g%1s%3

## dummy sequence parameters
scenario 0 1 2 3          # %3; env change scenario
grid 1 2 3 4 6 5 6 11    # %1; landscape grid

## NEMO PARAMS ##
filename campanula_mut%.4'2_g%1_s%3_VS50

## SOURCE POP ##
source_pop campanula_mut%.4'2_g%1_VS50
source_preserve
[...]

## POPULATION ##
patch_number 1024
patch_nbfem (@g0 &init_K_campanula_%1.txt, @g1 1000)

## RATE ENV CHANGE ##
rate_environmental_change (@g0 &nochange.txt, @g10 &rate_2020_s%3_%1.txt, @g21
&rate_2030_s%3_%1.txt, @g31 &rate_2040_s%3_%1.txt, @g41 [...] )
```

```
[fred@fred test]$ nemosub env-change.txt
```

Nemo: what have we done with it?

- Architecture of adaptive phenotypic divergence

Yeaman & Guillaume 2009 (Evolution); Yeaman & Whitlock 2011 (Evolution); Débarre et al. 2015 (Am Nat); Yeaman 2015 (Am Nat); **with phenotypic plasticity**: Schmidt & Guillaume 2017 (Heredity)

- Multivariate quantitative genetics models with pleiotropy

Guillaume & Whitlock 2007 (Evolution); Guillaume 2011 (Evolution); Guillaume & Otto 2012 (Genetics); Chebib & Guillaume 2017, 2021 (Evolution, Genetics)

- Eco-Evolutionary dynamics in heterogeneous environments

species' range evolution: Gilbert et al. 2017 (Am Nat); Cotto et al. 2017 (Nat Comm); Postuma et al. 2020 (Ecosphere) **with phenotypic plasticity**: Schmidt et al. 2019 (Am Nat)

- Reconstructing patterns of genetic variation from demographic scenarios

Dynamics of deleterious mutations during recolonization: Grossen et al. 2020 (Nat Comm); **Adaptive variation for genomic vulnerability analysis**: Dauphin et al. 2021 (Glob Change Biol)

- Multi-species eco-evo dynamics in changing environments

Species competition in space and time: Gidoïn et al. *in prep*

Resources

Nemo:

- homepage: <https://nemo2.sourceforge.io>
- info: [NemoSimul@twitter](#); <https://groups.google.com/g/nemo-announce>
- support & discussion: <https://groups.google.com/g/nemo-simul>
- **Nemo-age** (stage-structured version):
<https://bitbucket.org/ecoevo/nemo-age-release>

Papers:

Guillaume, F. and Rougemont, J. (2006) **Nemo: an evolutionary and population genetics programming framework**. *Bioinformatics* 22:2556-2557

Cotto, O., Schmid, M. and Guillaume, F. (2020) **Nemo-age: spatially explicit simulations of eco-evolutionary dynamics in stage-structured populations under changing environments**. *Methods in Ecology and Evolution* 11:1227-1236

Contributors: Jacques Rougemont, Samuel Neuenschwander, Alistair Blachford, Sam Yeaman, Kim Gilbert, Olivier Cotto, Max Schmid, Jobran Chebib, Champak Beeravolu, Stéphane Chantepie, Cindy Gidoin

Syntax of the parameter file: macros

Dealing with argument strings:

In example `rep("{0,1}{1,0}", 3, sep="")`, we added quotes "" to enclose the first argument to `rep()`.

- ⇒ Arguments to a macro must be quoted when they include *delimiters* (commas ',') or *enclosers* (parentheses: '()', '{}').
- ⇒ This is required to not interpret within-string elements as separate arguments to the macro.

Macros can be nested:

Example: `rep(seq(1,5,1), 2)`, but this will not work! Nemo will return:

```
***ERROR*** macro "rep" can have max 4 arguments: rep(x, n, each=1, sep=",")
```

This error is issued because `rep` was called as: `rep(1,2,3,4,5, 2)`.

- ⇒ Result of `seq(1,5,1)` must be quoted with macro `q()`:

```
rep(q(seq(1,5,1)),2)
```

- ⇒ the call to `rep` becomes: `rep("1,2,3,4,5",2)`