


PT Activity 8.5.3: Troubleshooting Enterprise Networks 3

Topology Diagram



Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
R1	Fa0/0	192.168.10.1	255.255.255.0	N/A
	Fa0/1	192.168.11.1	255.255.255.0	N/A
	S0/0/0	10.1.1.1	255.255.255.252	N/A
	S0/0/1	10.3.3.1	255.255.255.252	N/A
R2	Fa0/1	192.168.20.1	255.255.255.0	N/A
	S0/0/0	10.1.1.2	255.255.255.252	N/A
	S0/0/1	10.2.2.1	255.255.255.252	N/A
	Lo0	209.165.200.225	255.255.255.224	209.165.200.226

Addressing Table continued on the next page

Addressing Table continued

R3	Fa0/1	N/A	N/A	N/A
	Fa0/1.11	192.168.11.3	255.255.255.0	N/A
	Fa0/1.30	192.168.30.1	255.255.255.0	N/A
	S0/0/0	10.3.3.2	255.255.255.252	N/A
	S0/0/1	10.2.2.2	255.255.255.252	N/A
S1	VLAN10	DHCP	255.255.255.0	N/A
S2	VLAN11	192.168.11.2	255.255.255.0	N/A
S3	VLAN30	192.168.30.2	255.255.255.0	N/A
PC1	NIC	DHCP	DHCP	DHCP
PC2	NIC	192.168.11.10	255.255.255.0	192.168.11.1
PC3	NIC	192.168.30.10	255.255.255.0	192.168.30.1
TFTP Server	NIC	192.168.20.254	255.255.255.0	192.168.20.1

Learning Objectives

- Find and correct all network errors
- Verify that requirements are fully met
- Document the corrected network

Scenario

For this activity, do not use login or password protection on any console lines to prevent accidental lockout. Use **ciscococna** for all passwords in this activity.

Note: Because this activity is cumulative, you will be using all the knowledge and troubleshooting techniques that you have acquired from the previous material to successfully complete this activity.

Requirements

- S2 is the spanning-tree root for VLAN 11, and S3 is the spanning-tree root for VLAN 30.
- S3 is a VTP server with S2 as a client.
- The serial link between R1 and R2 is Frame Relay.
- The serial link between R2 and R3 uses HDLC encapsulation.
- The serial link between R1 and R3 is authenticated using CHAP.
- R2 must have secure login procedures because it is the Internet edge router.
- All vty lines, except those belonging to R2, allow connections only from the subnets shown in the topology diagram, excluding the public address.
- Source IP address spoofing should be prevented on all links that do not connect to other routers.
- Routing protocols must be used securely. OSPF is used in this scenario.
- R3 must not be able to telnet to R2 through the directly connected serial link.
- R3 has access to both VLAN 11 and 30 via its Fast Ethernet port 0/1.
- The TFTP server should not get any traffic that has a source address outside the subnet. All devices have access to the TFTP server.

- All devices on the 192.168.10.0 subnet must be able to get their IP addresses from DHCP on R1. This includes S1.
- All addresses shown in diagram must be reachable from every device.

Task 1: Find and Correct All Network Errors

Use a clock rate of **4000000** and VLAN priority of **24576** where needed.

Task 2: Verify that Requirements Are Fully Met

Because time constraints prevent troubleshooting a problem on each topic, only a select number of topics have problems. However, to reinforce and strengthen troubleshooting skills, you should verify that each requirement is met. To do this, present an example of each requirement (for example a **show** or **debug** command).

Task 3: Document the Corrected Network