


## Activity 2.5.3: Troubleshooting PPP Configuration

### Topology Diagram



### Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gateway
R1	Fa0/1	10.0.0.1	255.255.255.128	N/A
	S0/0/0	172.16.0.1	255.255.255.252	N/A
	S0/0/1	172.16.0.9	255.255.255.252	N/A
R2	Lo0	209.165.200.161	255.255.255.224	N/A
	S0/0/0	172.16.0.2	255.255.255.252	N/A
	S0/0/1	172.16.0.5	255.255.255.252	N/A
R3	Fa0/1	10.0.0.129	255.255.255.128	N/A
	S0/0/0	172.16.0.10	255.255.255.252	N/A
	S0/0/1	172.16.0.6	255.255.255.252	N/A
PC1	NIC	10.0.0.10	255.255.255.128	10.0.0.1
PC3	NIC	10.0.0.139	255.255.255.128	10.0.0.129

## Learning Objectives

- Find and correct network errors
- Document the corrected network

## Scenario

The routers at your company were configured by an inexperienced network engineer. Several errors in the configuration have resulted in connectivity issues. Your boss has asked you to troubleshoot and correct the configuration errors and document your work. Using your knowledge of PPP and standard testing methods, find and correct the errors. Make sure that all of the serial links use PPP CHAP authentication, and that all of the networks are reachable.

### Task 1: Find and Correct Network Errors

- Use **64000** for all clock rates.
- Use **cisco** for all CHAP passwords.

### Task 2: Document the Corrected Network