

TLP:CLEAR

INCIDENT REPORT

DarkSword "P7": a Leaked iOS Exploit Chain Repurposed for Crypto-Wallet Theft

iOS Exploit Chain • Drive-by • Keychain & Wallet Theft • DarkCoruna • Cybercrime

Parameter	Value
Analysis Date	10 October 2026
Classification	Drive-by iOS exploit chain (6 CVEs) + keychain / crypto-wallet stealer
Threat Level	HIGH
Threat Actor	Unattributed Chinese-speaking cybercrime cluster ("qqtime"), medium confidence
State Involvement	None indicated. Built on the March 2026 public leak of DarkSword
Malware	DarkSword exploit kit (leaked build), Coruna loader, P7 implant (GHOSTBLADE library + rewritten agent)
Targets	iPhone users visiting Chinese-language casino, crypto and "iOS service" lure sites
Affected Systems	iOS 18.4 – 18.7 (DarkSword); iOS 13 – 17.2.1 (Coruna, same page)
Patched In	iOS 18.7.3 / 26.2 (CVE-2026-20700: iOS 26.3)
CVEs	CVE-2025-31277, CVE-2025-43529, CVE-2026-20700, CVE-2025-14174, CVE-2025-43510, CVE-2025-43520
Sources	Public sandbox and passive-DNS data only (urlscan.io, tria.ge, MWDB, VirusTotal); iVerify and GTIG reporting

1. Executive Summary

DarkSword is a complete iOS exploit chain written in JavaScript: a single visit to a web page on iOS 18.4–18.7 leads to remote code execution, sandbox escape, kernel privilege escalation and the injection of a data-stealing implant into system processes. Google Threat Intelligence Group (GTIG) documented it in March 2026 in the hands of three espionage-style customers; on 22 March 2026 the source code of one build leaked on GitHub and the chain spread to cybercriminals. On 8 October 2026 iVerify described a criminal variant it calls "P7": an implant with a p7_ prefix, a bidirectional command channel and on-device keychain parsing, delivered from the domains gotoiphone[.]com and mzp030[.]cam.

This report adds what public data alone can show about P7 and the operation behind it. Working exclusively from passive sources — public urlscan.io scans, a public tria.ge submission, the CERT Polska MWDB repository and VirusTotal metadata — and without touching live attacker infrastructure, we recovered a third, previously undescribed P7 build, the full delivery chain, and a cluster of related deployments going back to July 2026.

Key findings:

- A third P7 build, dated 29 September 2026, was found in a public sandbox submission. It is served from a Chinese-language online-casino lure, [www.iospc8\[.\]com](http://www.iospc8[.]com), and reports to a new command-and-control (C2) server, [www.y21t8bcya6q9b7155a\[.\]cc](http://www.y21t8bcya6q9b7155a[.]cc). Neither is in the iVerify indicator list. The agent carries a "channel code", pointing to an affiliate-style distribution model.
- P7 is not a rewrite of DarkSword. Its low-level library and loader are byte-identical to the GHOSTBLADE implant that GTIG attributed to the original DarkSword developers; what is new is a fully rewritten command agent and a new keychain-decryption stage that turns the device's own AppleKeyStore into a decryption oracle.
- The iVerify-listed delivery host [cdn.gotoiphone\[.\]com](http://cdn.gotoiphone[.]com) serves not only DarkSword but also a Coruna loader for older iOS, from the same hidden iframe — a combined "DarkCoruna" deployment. The same loader, identified by a fixed salt and obfuscator, appears on five further hosts since 16 July 2026 under the project name "qqtime".
- Of the 185 file hashes in iVerify's DarkSword appendix only 38 (21%) exist on VirusTotal and none on MalwareBazaar. Hash-based blocking is not a viable defence against this family; detection must rely on file-system artefacts, network patterns and code strings, for which we provide draft YARA rules.
- Everything about the operation — casino and crypto lures, theft of imToken and TokenPocket wallet keys, visitor telemetry resembling an advertising tracker, channel codes, Chinese comments in the code — points to financially motivated crime. There is no indication of state tasking behind P7. The exploit chain it rides on, however, was state-grade before it leaked.

2. Background

2.1. DarkSword before the leak

GTIG's 18 March 2026 report "The Proliferation of DarkSword" describes the chain and three users: UNC6748 (Saudi Arabia, November 2025, GHOSTKNIFE backdoor), the Turkish commercial surveillance vendor PARS Defense (Turkey and Malaysia, GHOSTSABER backdoor) and UNC6353, a suspected Russian espionage group that ran watering-hole attacks against Ukrainian sites first with Coruna and, from December 2025, with DarkSword, dropping the GHOSTBLADE dataminer. GTIG assessed that GHOSTBLADE was likely written by the DarkSword developers themselves. The developer has not been publicly identified; the pattern of several unrelated customers is consistent with a product sold through an exploit broker or vendor.

The chain uses six vulnerabilities, three of them zero-days at the time: CVE-2025-31277 and CVE-2025-43529 (JavaScriptCore RCE for iOS below and above 18.6), CVE-2026-20700 (dyld PAC bypass), CVE-2025-14174 (ANGLE, WebContent to GPU process), CVE-2025-43510 (XNU, GPU to mediaplayerd) and CVE-2025-43520 (XNU VFS race, kernel). Apple patched them in iOS 18.7.2, 18.7.3, 26.1, 26.2 and 26.3.

2.2. The leak and the criminal wave

On 22 March 2026 a full build — the UNC6353 kit including GHOSTBLADE — was published on GitHub. Within days it was re-deployed by other actors, including the Russian state group TA446 / Star Blizzard against civil-society targets (our report of 28 March 2026). By September 2026 iVerify counted roughly 17,000 domains hosting second-generation DarkSword and Coruna variants, and introduced the term "DarkCoruna" for deployments that combine both chains to cover every iPhone from iOS 13 to 18.7.

2.3. P7 as described by iVerify

iVerify's 8 October 2026 post "Sleep, Beacon, Steal, Repeat" documents P7 from a customer device: an implant running in SpringBoard that beacons every 15 seconds over HTTP/1.0 to /beacon, accepts a sleep command, exfiltrates to /result, /a, /event, /u, /nb, /p and /war, uses a hard-coded iOS 18.5 user agent and a fixed multipart boundary, and parses the keychain into JSON on the device. Delivery hosts were cdn.gotoiphone[.]com and mzpo30[.]cam; command servers agdx53[.]cc and js.gotoiphone[.]com. iVerify published hashes for ten P7 components; at the time of our analysis only two of them were on VirusTotal and the agent itself was unavailable anywhere.

3. Scope and Method

All material in this report was obtained passively. We did not connect to any attacker host. Sources:

- urlscan.io: public scans of lure pages, with stored response bodies retrieved through the response-hash API. Recovered bodies were verified against independent crawl hashes where available.
- tria.ge: a public sandbox submission from 3 October 2026 containing a complete DarkSword kit archive.
- CERT Polska MWDB: the GHOSTBLADE sample published by GTIG and a September 2026 DarkSword kit from the MalwareBazaar feed, used as comparison baselines.
- VirusTotal, Hybrid Analysis, AlienVault OTX and Validin for metadata (first-seen dates, passive DNS, WHOIS, fuzzy hashes). No files were uploaded to any third-party service.

All code analysis was static, in an offline environment, without executing JavaScript in any WebKit- or JavaScriptCore-based runtime.

4. Finding 1: A Third P7 Build

A ZIP archive named test.zip (SHA-256 ef9263b1..., 437 KB) was submitted to the public tria.ge sandbox on 3 October 2026. It contains a complete DarkSword deployment whose files are dated 29 September 2026. The sandbox classified it generically; VirusTotal labels it trojan.darksword.

File	Size	Role
index.html	51,385 B	Lure: Chinese online casino "通博娱乐 – www.iospc8.com", links to ub555[.]net / ub11[.]org (casino browser brand)
jmp.html	2,215 B	Launcher: five hidden iframes started 1.5 s apart, sessionStorage locks (rce_locked, uid), automatic retry after 45 s
0kio7x2igj0bp79owd.html	836 B	Watchdog page: reloads if the exploit stalls
rce_loader.js	7,318 B	Stage selector, leaked-kit style with telemetry re-enabled (SERVER_LOG = true, /log.html) and a /406.html redirect for unsupported devices
rce_module.js	173,079 B	CVE-2025-31277 RCE module — SHA-256 92c7d246..., unchanged since the UNC6353 / TA446 / GitHub builds
rce_worker_18.4.js / 18.6.js	45 KB / 520 KB	Exploit workers for iOS 18.4–18.5 and 18.6–18.7
sbx0_main_18.4.js / sbx1_main.js	400 KB / 310 KB	Sandbox escapes
pe_main.js	793,879 B	Kernel exploit + implant bundle. 15 KB larger than the leaked original: this is where P7 lives

The lure domain iospc8[.]com was registered on 23 September 2026 (GoDaddy, Cloudflare DNS), six days before the kit was built. The command server www.y21t8bcya6q9b7155a[.]cc was registered on 25 May 2026 through Gname.com with China listed as the registrant country, sits behind Cloudflare, and briefly resolved to an Alibaba Cloud Hong Kong address before being moved behind the CDN. Neither domain appears in the iVerify indicators.

The agent's configuration header reads: "C2 Agent Payload – persistent loop in SpringBoard. Communicates with command.py via HTTP ... replaced by server.py at load time". The server side is

therefore a Python application that rewrites the C2 URL into the implant at delivery time. The configuration also carries a constant C2_CHANNEL_CODE, sent as the "source" field in every registration, heartbeat and inventory request. The same mechanism — a channelcode parameter in the loader URL — appears in the delivery cluster described in Section 6. Channel codes are how affiliate programmes account for traffic; their presence implies that the kit is operated as a service for several distributors rather than by a single end user.

5. Finding 2: What P7 Actually Changes

5.1. Module-by-module comparison with GHOSTBLADE

pe_main.js is a webpack bundle. Besides the exploit library it embeds four implant payloads as strings: loader.js, c2_agent.js, keychain_copier.js and MigFilterBypassThread.js. We extracted them and compared each with the corresponding payload inside the GHOSTBLADE sample published by GTIG (SHA-256 2e5a56be...).

Payload	GHOSTBLADE (GTIG)	P7 build 3	Verdict
loader.js	10,096 B	10,096 B, SHA-256 d554f534...	Byte-identical. The "P7 loader" in public hash lists is the original GHOSTBLADE loader, which explains its zero detections on VirusTotal
MigFilterBypassThread.js	3,797 lines	3,797 lines, SHA-256 48aacf46...	Identical code; only trailing bracket formatting differs. Same hash in both iVerify P7 builds
keychain_copier.js	350 lines	360 lines, SHA-256 f0f0aa82...	GHOSTBLADE version plus the keychain-2.db WAL/SHM files and the Apple Notes database
file_downloader.js → c2_agent.js	3,740 lines, one-shot exfiltration to sqwas.shapelie[.]com with X-Device-UUID	4,756 lines, SHA-256 38975537...	Rewritten: only the Native helper class survives (2.5% shared lines). GHOSTBLADE's Telegram, WhatsApp, iCloud, WiFi and SMS collectors are gone
wifi_password_dump.js, wifi_password_security_d.js, icloud_dumper.js	present	absent	Removed. With them go all the strings in GTIG's G_Datamine_GHOSTBLADE_1 YARA rule

In other words, P7's authors kept the hard part of DarkSword — the TaskRop remote-call library and the MIG filter bypass — untouched, and replaced the business logic. This is consistent with iVerify's observation that the changes show competence rather than machine-generated bulk, but it also means the "new" implant shares most of its bytes with the leaked one.

5.2. The command agent

c2_agent.js is injected into SpringBoard and runs until reboot. It registers the device (/a), then enters a loop: it sends a beacon every 15 seconds with {uuid, device_info, status: "idle"}, executes the returned

command, and posts the result to /result with the command and task identifiers. A sleep command changes the interval. Transport is HTTP/1.0 over CFStream with kCFStreamSSLValidatesCertificateChain set to false, so any certificate is accepted; the user agent is a hard-coded iOS 18.5 Safari string.

Dedicated handlers: basic_info, disk_scan, ios_app_data, wallet_extract, wallet_scan, memo_scan, photo_scan, photos, apps, download, upload, file_upload, exec, eval, execute_command, sleep, exit. The execute_command handler implements some fifty shell-like sub-commands (ls, cat, find, grep, ps, netstat, ifconfig, hexdump, memdump, httpspy and others), giving the operator interactive access to the file system, process list and network connections without a shell.

Wallet targeting is explicit. The agent locates application containers by bundle identifier for imToken, TokenPocket, Trust Wallet, Bitget / BitKeep, Phantom, Solflare, Uniswap, Tonhub, Bitpie and TronLink, reads React Native AsyncStorage databases, and for imToken decrypts the Ethereum keystore v3 on the device (PBKDF2, AES-CTR, HMAC-SHA256 implemented in JavaScript) using the password it finds in the decrypted keychain. The result is packaged with the keychain dump and sent to /war.

5.3. "P7 Phase 2": the keychain oracle

The genuinely new engineering is not in the agent but in pe_main.js itself, in a block the authors label "P7 Phase 2: V4 Local SQLite + Remote AKS Oracle Pipeline" (AKS is the AppleKeyStore). After the kernel exploit, pe_main.js injects keychain_copier.js into configd (which copies keychain-2.db and the keybags to /tmp) and loader.js plus c2_agent.js into SpringBoard. It then wakes securityd with three SecItemCopyMatching calls, establishes a remote-call channel into securityd, opens the AppleKeyStore IOKit service from securityd's context, and uses aks_unwrap as an oracle to unwrap the class keys of items read from its local copy of the keychain database. Decrypted items are written to /private/var/tmp/keychain_c2_dump.json, followed by a four-byte .done marker that the agent polls for up to 180 seconds before building the wallet package.

GHOSTBLADE only copied keychain files to the server. P7 decrypts them on the device, which is why its exfiltration can be small, targeted and immediately usable. This phase keeps its own log, /private/var/tmp/p7_debug.log, written through a buffered fopen/fwrite routine; the agent's wallet branch writes /private/var/tmp/c2_wallet_debug.log. iVerify's statement that P7 eliminated debug logging applies to HTTP and syslog logging only; file logging is deliberate and is a reliable forensic artefact.

5.4. Forensic artefacts

Path	Written by	Content
/private/var/tmp/keychain_c2_dump.json (.tmp, .done)	pe_main.js Phase 2	Decrypted keychain items as JSON; .done marker
/private/var/tmp/p7_debug.log	pe_main.js Phase 2	Progress journal of the keychain pipeline
/private/var/tmp/c2_wallet_debug.log	c2_agent.js	Wallet packaging / upload trace ("[WALLET-HQ]")
/private/var/tmp/imtoken_keychain.json	c2_agent.js	imToken keystore extraction output

TLP:CLEAR

/private/var/tmp/_hq_notestore (-wal, -shm); /private/var/tmp/notes.sqlite*	c2_agent.js; keychain_copier.js	Copies of the Apple Notes database
/private/var/tmp/keychain-2.db*, persona.kb, usersession.kb, System.keybag, Backup.keybag	keychain_copier.js	Keychain database and keybags (inherited from GHOSTBLADE)
/var/mobile/Library/Caches/ ios_disk_scan.txt; /var/mobile/ios_disk_scan.txt	c2_agent.js	disk_scan output, uploaded in chunks then unlinked

6. Finding 3: The "qqtime" Delivery Cluster

6.1. Recovering the live chain from urlscan

The crypto-news site cryptonewstrack[.]com was scanned publicly on urlscan.io on 17 July, 5 September and 15 September 2026. The two September scans captured the complete P7 delivery chain except the final stage, which is gated on an iOS 18 user agent. Response bodies were retrieved from urlscan's store; the SHA-1 of the recovered group.html matches the body hash recorded independently by Validin's crawler on 19 September.

- The page loads hxxps://oss.gotoiphone[.]com/alicdn/a5a62a47e2914d88ab7b34b2ebea8b25.js (2,660 B) from Alibaba Object Storage.
- That script creates a hidden 1×1 iframe pointing to hxxps://cdn.gotoiphone[.]com/group.html and, every five seconds, posts the visitor's public IP, operating-system version and page URL to hxxps://goo[.]wang/alicdn/a5a62a47.../visit. goo[.]wang resolves to the same Alibaba Cloud address as js.gotoiphone[.]com, iVerify's P7 command server.
- group.html (Chinese-language comments) loads loader.js for every visitor and, if the user agent contains "18", additionally rce_loader.js — the DarkSword entry point. The page reloads itself every 120 seconds.
- loader.js (47,605 B) is not DarkSword. It is an obfuscated Coruna loader: a module table keyed by SHA-1, modules fetched on demand under names derived as SHA-256(salt + name), the salt cecd08aa6ff548c2, version thresholds at iOS 13.0 and 16.0, and result codes 1000/1001/1003 reported back to the server.

cdn.gotoiphone[.]com is therefore a DarkCoruna deployment: Coruna for iOS 13–17.2.1, DarkSword for 18.x, from one iframe. The P7 post does not mention the Coruna half.

6.2. The same loader since July

The Coruna loader is unusual enough to pivot on. Searching urlscan for its page title, file name and salt yields the same build — identical function names, module table, salt and constants — on five further hosts:

First seen	Host / path	Observation
2026-07-16	iphone.apiforx[.]work/qqtime/qqtime.html; 1x8gmjbdq3tepgr[.]jicu/	Loader 34ef644f....js, results reported to 1x8gmjbdq3tepgr[.]jicu/api
2026-07-17	cryptonewstrack[.]com/qqtime/34ef644f....js	Loader hosted on the lure site itself, results to ipsadminuser[.]shop/api
2026-07-31	1.aivestorix[.]com/qqtime/qqtime.html	Same file as on cryptonewstrack
2026-08-04	billowing-truth-804c.pages[.]dev/1df7afe3.../foxtimes + routers.js	routers.js: iOS ≥ 18.4 → ds_rce_loader.js, otherwise Coruna loader with ? channelcode=1df7afe3... — first appearance of the DarkSword branch
2026-09-05 → 2026-10-03	cdn.gotoiphone[.]com	group.html → Coruna loader + rce_loader.js; from 28 September the index page is

		again titled "qqtime" and references routers.js
--	--	---

The operator's project name is visibly "qqtime" (directory, page title); one deployment is called "foxtimes". The channelcode parameter in routers.js equals the deployment directory name, i.e. each distributor gets its own path. gotoiphone[.]com itself was a dormant domain (last active 2020) re-registered on 28 July 2026 through Dominet (HK) with Alibaba DNS; the delivery subdomain moved to Alibaba OSS on 5 September. None of these hosts, nor cryptonewstrack[.]com, ipsadminuser[.]shop or goo[.]wang, appear in the iVerify or GTIG indicator lists, and none of the recovered files are on VirusTotal.

Whether cryptonewstrack[.]com (registered 18 May 2026, rated "phishing and fraud" by one vendor) is a compromised site or an operator-controlled lure could not be determined; it should be treated as a lure, not blocked as infrastructure.

6.3. A shared back end?

The root page of mzp030[.]cam — iVerify's second P7 delivery host — returns a 49-byte placeholder (<p>.</p>) with Server: openresty, Cache-Control: no-cache, no-store and Access-Control-Allow-Origin: *, behind CloudFront. The root of nuih22[.]cc, a DarkSword host that serves 14 different lure front-ends in iVerify's appendix, returns the identical body and headers behind Cloudflare, and both use the path /assets/js/group.html. A 49-byte placeholder is a weak fingerprint, so we rate a shared operator or shared kit template as medium confidence only.

7. Finding 4: The Wider DarkSword Ecosystem in Numbers

iVerify's appendix lists 229 pairs of lure front-end and DarkSword back-end, 185 component hashes and 48 command URLs collected through Validin. Clustering them:

- Lure hosts: 190 domain names and 39 bare IP addresses, 25 of them on non-standard ports (8080, 8000, 8888) — operator test systems. Top-level domains: .top 87, .com 36, .icu 12, .site 10, .cc 9.
- Names are pinyin keyword salad around Chinese consumer brands (guge = Google, youdao, sougou, meitu, qishui music, leidian, feiji = Telegram), a casino family (cgwin*, 10 domains), crypto (catcoinglobal[.]top, web3a[.]cc, hi-metaverse[.]online) and fake "iOS service" sites.
- Back ends: 114 lures host the kit themselves; 94 (41%) load it from one host, cf.r5dz2dz88wuideu[.]xyz, and 14 from nuih22[.]cc. Roughly half of the "17,000 domains" are disposable fronts for one or two shared back ends — a platform, not a crowd.
- Command URLs come in pairs, http on 8882 and https on 8881 — the port scheme of the leaked GHOSTBLADE server. P7 abandoned it for 443 behind Cloudflare.
- Public visibility: 38 of 185 hashes on VirusTotal (loaders 4 of 49, pe_main 6 of 35), submissions spread from March to October 2026; six of the 38 have zero detections. MalwareBazaar: none by tag. Hybrid Analysis: none. The kit is rebuilt per host; hash lists lag by months.

8. Attribution Assessment

We assess with medium confidence that P7 and the qqtime cluster are the work of a Chinese-speaking, financially motivated group operating an exploit-delivery service for several distributors. Supporting evidence: casino and crypto lures aimed at a Chinese-speaking audience; implant functionality centred on wallet seed and keychain theft; channel codes in both the loader and the implant; visitor telemetry typical of traffic brokers; Chinese comments in the delivery pages; disposable domains registered through Gname and GoDaddy and fronted by Cloudflare, CloudFront and Alibaba.

We find no indication of state involvement in P7. The argument "iOS malware is rare, therefore state-sponsored" no longer holds: since the Coruna and DarkSword leaks, full iOS exploit chains are a commodity, and iVerify measures infection traces on 5% of devices still on vulnerable versions. What is state-grade is the exploit chain itself, which three espionage-style customers used before it leaked; its original developer remains publicly unattributed.

A correction to our own 28 March 2026 report: the infrastructure static.cdncounter[.]net and sqwas.shapeliel[.]com, which we described as "original DarkSword infrastructure (UNC6748)", belongs per GTIG to UNC6353, and GHOSTBLADE is a GTIG designation, not a Proofpoint one. TA446 reused the leaked UNC6353 kit including its exfiltration server; the two groups are distinct.

9. Detection

9.1. YARA

GTIG's rule G_Hunting_DarkSwordExploitChain_ImplantLib_FilePaths_1 fires on the P7 pe_main.js bundle (the webpack source paths are intact) but not on the extracted agent; G_Datamine_GHOSTBLADE_1 does not fire on P7 at all. The following draft rules, tested against one P7 build with zero false positives on GHOSTBLADE, a September 2026 DarkSword kit and the recovered delivery pages, are provided for hunting. They should be re-validated against further builds before use in blocking mode.

P7_DarkSword_C2Agent_Strings — strings: "p7_" (count > 20), "-----HqBound", "/beacon", "/war", "/nb", "keychain_c2_dump", "p7_debug.log", "c2_wallet_debug.log", "_hq_notestore", "ios_disk_scan.txt", "wallet_scan", "memo_scan", "execute_command", "disk_scan", "iPhone OS 18_5 like Mac OS X".

Condition: file under 10 MB, not an archive or executable, and (p7_count > 20 or HqBound or two of the artefact paths) and three of the endpoint / command / UA strings.

P7_DarkSword_LocalStorage_Markers (delivery pages) — strings: "lab_device_uuid", "__ds_inflight_worker", "__ds_skip_workers", "_x_pe_done", "cecd08aa6ff548c2", "obChTK", "ds_rce_loader.js", "34ef644ff217a50beadde64dc8e23a7d". Condition: file under 2 MB and two of the localStorage keys or two of the qqtime markers.

9.2. Network

- HTTP/1.0 POST requests from an iPhone to /beacon every 15 seconds, and to /a, /event, /u, /nb, /p, /war on the same host; multipart boundary -----HqBound; JSON fields lhu, source (32-hex channel code), channel_code.
- TLS sessions from SpringBoard-context code that accept any certificate (no chain validation) to recently registered .cc / .cam / .lol domains behind Cloudflare.
- On the web side: hidden iframes to */group.html, scripts named rce_loader.js, ds_rce_loader.js, routers.js, requests to */api with a channelcode parameter, and periodic POSTs of visitorIp / deviceVersion / sourceUrl.

9.3. Host

The artefact paths in Section 5.4 survive until reboot or clean-up and are visible in a sysdiagnose or a file-system acquisition. Browser-side, the localStorage keys lab_device_uuid, __ds_inflight_worker, __ds_skip_workers (gotoiphone build) and _x_pe_done, _x_try, _x_ok (mzpo30 build) persist after the attack and identify which deployment the device visited.

10. Indicators of Compromise

Indicators marked "iVerify" are repeated from the vendor's publication for completeness; all others are original to this report. Shared cloud addresses are listed for context only and must not be blocked.

10.1. Domains and hosts

Indicator	Role	Notes
www.y21t8bcya6q9b7155a[.]cc	P7 C2 (build 3)	Gname, CN, 2026-05-25, Cloudflare; endpoints /beacon /result /a /event /u /nb /p /war
iospc8[.]com	P7 lure (build 3)	Casino "通博娱乐", GoDaddy, 2026-09-23, Cloudflare
agdx53[.]cc	P7 C2	iVerify; Gname, CN, 2026-06-09, Cloudflare
js.gotoiphone[.]com	P7 C2	iVerify; Alibaba Cloud 47.237.185.24
cdn.gotoiphone[.]com	DarkCoruna delivery	iVerify; Alibaba OSS; group.html, loader.js, rce_loader.js
mzpo30[.]cam	P7 delivery	iVerify; Gname, CN, 2026-08-17, CloudFront + openresty
oss.gotoiphone[.]com	Injector host	alicdn/a5a62a47e2914d88ab7b34b2eb ea8b25.js
gotoiphone[.]com	Cluster apex	Re-registered 2026-07-28, Dominet HK, alidns
goo[.]wang	Visitor telemetry	Same IP as js.gotoiphone[.]com
ipsadminuser[.]shop	Loader report endpoint (July build)	Cloudflare, since 2026-04-25
1x8gmjbdq3tepgr[.]icu	Coruna loader host + /api	2026-07-16
iphone.apiforx[.]work	Coruna loader host	2026-07-16, /qqtime/
1.aivestorix[.]com	Coruna loader host	2026-07-31, /qqtime/
billowing-truth-804c.pages[.]dev	DarkCoruna router ("foxtimes")	2026-08-04
cryptonewstrack[.]com	Lure site	Compromised or operator-owned — undetermined; do not block as C2
nuih22[.]cc	Shared DarkSword back end	iVerify appendix; same root fingerprint as mzpo30[.]cam
66ds[.]lol	Associated with P7 (OTX)	Unverified; NameSilo 2026-06-

10.2. URLs

URL	Role
hxxps://www.y21t8bcya6q9b7155a[.]cc/beacon	P7 tasking
hxxps://www.y21t8bcya6q9b7155a[.]cc/war	P7 keychain + wallet exfiltration
hxxps://oss.gotoiphone[.]com/alicdn/a5a62a47e2914d88ab7b34b2ebea8b25.js	Injector
hxxps://cdn.gotoiphone[.]com/group.html	DarkCoruna router page
hxxps://cdn.gotoiphone[.]com/loader.js	Coruna loader
hxxps://goo[.]wang/alicdn/a5a62a47e2914d88ab7b34b2ebea8b25/visit	Telemetry
hxxps://ipsadminuser[.]shop/api	Loader report endpoint
hxxps://1x8gmjbdq3tepgr[.]jicu/api	Loader report endpoint

10.3. IP addresses (context only)

IP	Context
47.237.185[.]24	Alibaba Cloud: gotoiphone[.]com, js.gotoiphone[.]com, goo[.]wang since 2026-08-10
47.79.48[.]200	Alibaba OSS shared endpoint (cdn.gotoiphone[.]com and ~60 unrelated domains) — do not block
47.242.129[.]133	Pre-Cloudflare origin of www.y21t8bcya6q9b7155a[.]cc, 2026-05-25 — historical

10.4. Files (SHA-256)

File	SHA-256	Notes
test.zip	ef9263b1a74e80d55331763335847017efba9018401b037c66729b265c255bb7	P7 build-3 kit archive
pe_main.js	57c3997642882815e02bcc50b60a63292dc3f5ed0337f2dd0c9c93b34a423a08	P7 build-3 implant bundle
c2_agent.js	38975537d2c66815484a1adb01b681bffa96168cd6e9474e24815ad4a4796127	P7 agent, build 3 (new)
loader.js	d554f534fad7822cbde9ca7d9f6e	= GHOSTBLADE loader; iVerify

TLP:CLEAR

	fe8a7e0f5786ccee60f8db6dad340a2a6f80	
keychain_copier.js	f0f0aa82a03bf4835864a5b7f7ba38e537f3f81e82b3db311ac0d80b4b4b022e	iVerify (mzpo30 build)
MigFilterBypassThread.js	48aacf46ad8b7f619d7f4346c330abfbda14a34ed3eb98c215a5ef5fb36e2171	Shared library; iVerify
rce_loader.js	443045e0c3ffdabddaf1fd2d88e93b0e6f614654788fbc1d4f646a4fdc736a6d	P7 build 3
rce_module.js	92c7d246d2c163c076f783dcc19f87f5b9b9ac301b106b87a7aaea9346ce0052	Unchanged since the leak
rce_worker_18.4.js	14882fb0baef0f6f45decc79e34d488cdccc15fda505e5b615c5c420a7a8826e	P7 build 3
rce_worker_18.6.js	2415b9273b37a04c63bb2e45e81aad86d1b6a7a64a385e0a21377b24e6525245	P7 build 3
sbx0_main_18.4.js	d4aa9a78c9e4fb050abdf15da3ae166564f2fda6de63412bac36bc01a0984c21	P7 build 3
sbx1_main.js	2748a8fd029c7a55f3107563c8f7993d3deb609d16c4898be0a5609e66a7163d	P7 build 3
jmp.html	cf2262d8d064fef3c0fd79018ddd3f2f0e5e827aabb20aa5b6abeebd890ca5f7	P7 build-3 launcher
group.html	fe767e3c7bcb5c9e241334054424333d95ce86fe0e07717ee9ca529dade6930d	cdn.gotoiphone[.]com router page
loader.js (Coruna)	20c49dd361181210fade5de43e1c8c4c59485b4f565007b4ca3552b71c7683be	cdn.gotoiphone[.]com, September build
a5a62a47e2914d88ab7b34b2eb ea8b25.js	b693b028e66e734b4552e0c95baf77d353f5fe178ba363594a157d6211751fdf	Injector

34ef644ff217a50beadde64dc8e2 3a7d.js	5bc7ce2af4fb5e62b801dec719c 0dc90b5deddf0ccd0ac1d6610f8 679d10fd47	Coruna loader, July (cryptonewstrack, aivestorix)
34ef644ff217a50beadde64dc8e2 3a7d.js	0d70b4c36967dc3740ee08993f9 abe43693c1e92c8a9c1f25c2183 57307ced82	Coruna loader, July (apiforx, 1x8gm...)
routers.js	2eb359647852ae87e4a4de7adc 741abb2889896bf9bda476c647f b075ffb967e	DarkCoruna router, pages.dev

10.5. Strings

Value	Meaning
f94ed1edc290119993125d85c1106796	P7 build-3 channel code
1df7afe33d3bf512f124136cf405f57a	qqtime channelcode (pages.dev deployment)
cecd08aa6ff548c2	Coruna loader salt, all qqtime builds
-----HqBound	P7 multipart boundary
obChTK, ds_rce_loader.js, qqtime, foxtimes	Loader global, DarkSword branch file, project names

11. Recommendations

- Update to iOS 18.7.3, or to iOS 26.3 or later; CVE-2026-20700 is fixed only in iOS 26.3. Devices on iOS 13–17.2.1 are exposed to the Coruna half of a DarkCoruna page, devices on iOS 18.4–18.7.2 to the DarkSword half.
- Enable Lockdown Mode for high-risk users; it blocks the JavaScriptCore entry points used by both chains.
- Hunt on managed devices for the artefacts in Section 5.4 and the browser localStorage keys in Section 9.3; a sysdiagnose is sufficient.
- On the network, alert on the HTTP/1.0 beacon pattern and the HqBound boundary rather than on domain lists; the domains rotate weekly, the protocol has not changed across three builds.
- Treat hash feeds for this family as low-value: rebuild-per-host means each deployment ships unique exploit files; only rce_module.js has stayed constant.
- Crypto-wallet users on iPhone should assume that any seed phrase or keystore held in imToken, TokenPocket, Trust Wallet, Bitget, Phantom, Solflare, Uniswap, Tonhub, Bitpie or TronLink on a device that visited one of these pages is compromised and should be rotated from a clean device.

12. References

- iVerify, "Sleep, Beacon, Steal, Repeat: P7 DarkSword Variant", 8 October 2026 (iverify.com/blog/darksword-variant-threat-research)
- iVerify, "Proliferation of Coruna and DarkSword", 15 September 2026 (iverify.com/blog/proliferation-of-coruna-and-darksword)
- Google Threat Intelligence Group, "The Proliferation of DarkSword", 18 March 2026 (cloud.google.com/blog/topics/threat-intelligence/darksword-ios-exploit-chain)
- Lookout, DarkSword iOS exploit chain research, March 2026
- FDC Threat Intelligence, "TA446 / Star Blizzard Deploys DarkSword iOS Exploit Kit", 28 March 2026
- urlscan.io scans 01a0a6ab-ccc6-772b-a3d1-7c4143af206a, 01a07386-7b25-7299-bfac-dc7cdf1bc5d, 019f71b4-d416-75a7-a8c2-96b4a1e31882, 019fce1d-6727-721e-9196-3446ba562239, 019f68b8-71b5-7707-b7fc-0d2b71a852dd, 019f6a90-cedb-701e-a9c3-c43bf7dbb731, 019fb9ec-10c8-717e-b4c2-d93a5776cbb4
- tria.ge sample 261003-v7ayastdmb (test.zip), submitted 3 October 2026
- CERT Polska MWDB, GHOSTBLADE sample 2e5a56beb63f21d9347310412ae6efb29fd3db2d3a3fc0798865a29a3c578d35
- AlienVault OTX pulses 6ac8ae8dadff0d3e088c3764, 6a95df86eed3f6fb54baef2d

TLP:CLEAR — This document may be distributed without restriction.