Run Code

Our Solution(s) Run

```
Run Code
```

Your Solutions

12px

Solution 1 Solution 2 Solution 3

```
Solution 1 Solution 2
 1 // Copyright © 2020 AlgoExpert, LLC. All rights reserved.
   class Program {
      static class BST {
       public int value;
       public BST left;
       public BST right;
       public BST(int value) {
         this.value = value;
13
        // Average: O(log(n)) time | O(log(n)) space
14
        // Worst: O(n) time | O(n) space
       public BST insert(int value) {
16
          if (value < this.value) {</pre>
           if (left == null) {
18
              BST newBST = new BST(value);
              left = newBST;
20
            } else {
              left.insert(value);
          } else {
           if (right == null) {
             BST newBST = new BST(value);
              right = newBST;
            } else {
              right.insert(value);
30
          return this;
34
        // Average: O(\log(n)) time | O(\log(n)) space
35
        // Worst: O(n) time | O(n) space
36
        public boolean contains(int value) {
          if (value < this.value) {</pre>
38
            if (left == null) {
39
              return false;
            } else {
41
              return left.contains(value);
43
          } else if (value > this.value) {
           if (right == null) {
45
              return false;
46
            } else {
47
             return right.contains(value);
48
49
          } else {
           return true:
50
        // Average: O(\log(n)) time | O(\log(n)) space
        // Worst: O(n) time | O(n) space
        public BST remove(int value) {
          remove(value, null);
          return this;
61
        public void remove(int value, BST parent) {
62
          if (value < this.value) {</pre>
63
           if (left != null) {
              left.remove(value, this);
65
66
          } else if (value > this.value) {
67
            if (right != null) {
68
              right.remove(value, this);
69
70
            if (left != null && right != null) {
              this.value = right.getMinValue();
73
              right.remove(this.value, this);
74
            } else if (parent == null) {
75
              if (left != null) {
76
                this.value = left.value;
77
                right = left.right;
78
                left = left.left;
79
              } else if (right != null) {
80
                this.value = right.value;
81
                left = right.left;
82
                right = right.right;
83
              } else {
84
                // This is a single-node tree; do nothing.
85
            } else if (parent.left == this) {
86
              parent.left = left != null ? left : right;
87
            } else if (parent.right == this) {
88
89
              parent.right = left != null ? left : right;
```

90

```
1 class Program {
      static class BST {
        public int value;
        public BST left;
        public BST right;
        public BST(int value) {
          this.value = value;
10
        public BST insert(int value) {
12
          // Write your code here.
13
          // Do not edit the return statement of this method.
14
          return this;
16
        public boolean contains(int value) {
18
          // Write your code here.
19
          return false:
20
        public BST remove(int value) {
          // Write your code here.
          \ensuremath{//} Do not edit the return statement of this method.
24
          return this;
26
27
28 }
```

Custom Output Raw Output

Submit Code

Run or submit code when you're ready.