AlgoExpert Quad Layout Java 12px Sublime Monokai 00:00:00

Prompt Scratchpad Our Solution(s) Video Explanation Run Code

Solution 1 Solution 2

39

```
1\, // Copyright @ 2020 AlgoExpert, LLC. All rights reserved.
   import java.util.*;
 5 class Program {
     // O(n^3 + m) time \mid O(n + m) space - where n is the number of digits in Pi and m is the number of
      public static int numbersInPi(String pi, String[] numbers) {
       Set<String> numbersTable = new HashSet<String>();
10
       for (String number : numbers) {
         numbersTable.add(number);
11
12
       Map<Integer, Integer> cache = new HashMap<Integer, Integer>();
13
       int minSpaces = getMinSpaces(pi, numbersTable, cache, 0);
14
       return minSpaces == Integer.MAX_VALUE ? -1 : minSpaces;
15
16
17
      public static int getMinSpaces(
18
         String pi, Set<String> numbersTable, Map<Integer, Integer> cache, int idx) {
19
20
       if (idx == pi.length()) return -1;
21
       if (cache.containsKey(idx)) return cache.get(idx);
22
       int minSpaces = Integer.MAX_VALUE;
23
        for (int i = idx; i < pi.length(); i++) {</pre>
24
         String prefix = pi.substring(idx, i + 1);
25
          if (numbersTable.contains(prefix)) {
26
           int minSpacesInSuffix = getMinSpaces(pi, numbersTable, cache, i + 1);
27
           // Handle int overflow.
28
           if (minSpacesInSuffix == Integer.MAX_VALUE) {
29
             minSpaces = Math.min(minSpaces, minSpacesInSuffix);
30
           } else {
31
              minSpaces = Math.min(minSpaces, minSpacesInSuffix + 1);
32
33
34
35
       cache.put(idx, minSpaces);
       return cache.get(idx);
36
37
38 }
```