AlgoExpert Quad Layout JavaScript 12px Sublime Monokai 00:00:00

Prompt Scratchpad Our Solution(s) Video Explanation Run Code

Solution 1 Solution 2

```
1\, // Copyright @ 2020 AlgoExpert, LLC. All rights reserved.
 3 // O(log(n)) time | O(log(n)) space
 4 function searchForRange(array, target) {
     const finalRange = [-1, -1];
     \verb|alteredBinarySearch(array, target, 0, array.length - 1, finalRange, true);|\\
     alteredBinarySearch(array, target, 0, array.length - 1, finalRange, false);
     return finalRange;
8
9 }
10
11 function alteredBinarySearch(array, target, left, right, finalRange, goLeft) {
     if (left > right) return;
13
     const mid = Math.floor((left + right) / 2);
      if (array[mid] < target) {</pre>
14
15
       alteredBinarySearch(array, target, mid + 1, right, finalRange, goLeft);
      } else if (array[mid] > target) {
16
17
       alteredBinarySearch(array, target, left, mid - 1, finalRange, goLeft);
18
      } else {
19
       if (goLeft) {
20
         if (mid === 0 || array[mid - 1] !== target) {
21
           finalRange[0] = mid;
22
          } else {
23
           alteredBinarySearch(array, target, left, mid - 1, finalRange, goLeft);
24
       } else {
25
26
          if (mid === array.length - 1 || array[mid + 1] !== target) {
27
           finalRange[1] = mid;
28
29
           alteredBinarySearch(array, target, mid + 1, right, finalRange, goLeft);
30
31
32
33 }
34
35 exports.searchForRange = searchForRange;
```