

Problems with PAKE protocols

Lars Mueller *Technical University Munich*
Munich, Germany
lars.mueller@tum.de

Abstract—In the last years data breaches in websites have become fairly common. This happens

Index Terms—

I. INTRODUCTION

notes

- normal password auth Vulnerable to offline Attacks
- motivation for development of pake protocl
- standardization
- Upcomming Questions, why not standard today only a few
- Topics of paper:
- Short Introduction to PAKE Protocols and their cryptography behind them
- The Usage of PAKE in applications today
- Attacks on PAKE
- Some other reasons PAKE isnt used widely

II. RELATED WORK

As PAKE protocols have a long history in somputer science terms, there is a lot of research already being done. There are a lot of different approaches on the topic and different ideas to solve different problems. The first appearance of Encrypted Key Exchange was 1992 in a paper which described a basic protocol secure against dictionary Attacks. The first standardization of PAKE Protocols came with IEEE P1363.2. This project was formed because of huge interest in Industry and Science in the theme During this first so called period of PAKE protocols these protocols where revised and reworked multiple times which extended the working period to 2008. However after the standardization was finisied it didnt lead to huge adoption in the industry as it was hoped. In the second phase of PAKE development some services adopted the PAKE protocl such as Apple Icloud or Mozzila Firefox. In 2018 WPA3 the replacement for WPA2, the protocol to secure wifi networks, was announced by the WIFI Alliance. It includes an PAKE protocol called Dragonfly to authenticate with the wifi router. The huge amount of PAKE protocols followed the problem

III. BACKGROUND

A. The basic security principls of PAKE

PAKE basicly allow 2 parties to establish a secure channel inwhich they can communicate without the fear of a 3rd partie to listen. The Requirements are the following

- Resistance against Dictonary Attacks:
The communittication between the two parties must not be

decryptable. This means that there is not data obtainable which allows an attacker to find the private secret. Especially if the guesses on the secret are run offline by a dictionary or another password-decryption like attack.

- On Password guess per Conection:
When establishing a new connection between two parties only one guess on the secret is possible. It isnt possible for an attacker to send for example 100 password in one connection attempt, the attacker needs 100 to try them out. Additionally these attempts should be visible and blockable to prevent further guessing the secret.
- forward secrecy:
Alice and Bob have established a protected session with their pre-shared secret, they both a session-secret which allows them to communicate securly. Eve gets to known the pre-shared secret. She can establish a new session with either Alice or Bob and impersonate the other, however she does not know the session-secret and can therefore not listen to what Bob and Alice are doing in their already established session.
- session-key security:
Additionally to the session of Alice and Bob there is another session between Alice and Charlie. Eve is now able to obtain the session-secret from Alice-Bob, this means she can listen to their communitication. The session between Alice and Charlie is still not compromised. This is the case for every other session.

A PAKE is a two stage protocol.

B. Basics of encrypted Communication

1) *Hashing*: A hash function takes a key as input. The output is a fixed size hashcode. These functions are used to map data to make it indexable That would be the case if the hashfunction was perfect which is physically not possible. Hashfunctions follow three principles to withstand different types of attacks

- Pre-Image resistance
It is difficult to find a corresponding message M to a given hash h , $h = \text{hash}(M)$. The function is a one-way function.
- Second Pre-Image resistance
It is difficult to find another message $M2$ getting the same hash as the first message $M1$. $\text{hash}(M1) = \text{hash}(M2)$.
- Collision resistance
Similar to second pre-image resistance, it should be difficult to find two message $M1, M2$ that have the same hash. $\text{hash}(M1) = \text{hash}(M2)$.

2) *Zero-Knowledge-Proof*: The Zero-Knowledge-Proof describes a way to prove someone else that you know a secret without ever telling the person the secret. The verifying person knows the secret as well. The verifier can ask you different questions which are conducted from the secret, which you can answer correct if you know the secret. This can be repeated until the verifier is convinced that you know the secret. An Abstract example would be Alice is colorblind and Bob is not. Bob has a red and a green ball. They seem identical to Alice so she is not sure if Bob is telling her the truth and they are different. She wants to prove Bob and holds one Ball in her left the other in her right hand. Bob knows in which hand they are currently. Alice decides, without Bob looking, if she wants to switch the balls or not after she's done that she asks Bob if she switched or not. Bob answers, if both balls have the same color Bob will eventually choose the wrong option. If they are differently colored Bob should be able to tell Alice if she switched or not. Like a lot of concepts in cryptography the zero-knowledge-proof has some properties which define it.

- completeness
if the proof is correct, the prover will convince the verifier that he is correct
- Soundness
if the proof is wrong, the verifier will not be convinced by the prover, however there is a small probability for error
- Zero-Knowledge
There is no secret leaked by proofing.

A famous Zero-Knowledge-Proof would be the Schnorr-Signature

- Group G of prime order q with generator g
- Hash function $H : \{0, 1\}^* \leftarrow \mathbb{Z}_q$
- ALICE
- Pick private random key a
- get public key $A = g^a$
- Sign Message $M : \{0, 1\}^*$
- 1. Pick Random number r
- 2. Compute $R = g^r$
- 3. Signature $E = H(M, R)$
- 4. Signature $S = r - a \cdot E$
- Send Bob Public Key A , Message M and Signature E, S
- Bob verifies $M : \{0, 1\}^*$
- derive $R' = g^S \cdot A^E = g^{r-aE} \cdot (g^a)^E = g^r$
- derive $E' = H(M, R')$
- Check $E' = E$

C. PAKE Handshake

1) *Balanced PAKE: DH-EKE*:

- Pre Shared Secret
- A gen. RNR(private key)- i public key - i encrypted with PSK
- A send $\text{Enc}[\text{PSK}](\text{public key})$
- B decrypt $\text{Enc}(A)$ with $\text{PSK}-i$
- B gen RNR(private key) - i public key
- B gen Sessionkey, random Challenge
- B send $\text{Enc}[\text{PSK}](\text{public key, Enc[Sessionkey](Challenge)})$

- A decrypt, receives Bob pub key
- A gen. Sessionkey with her private key and Bob's public key
- A decrypts 2nd part of message with sessionkey
- A generates challenge
- A sends $\text{Enc}[\text{Sessionkey}](\text{challengeA, challengeB})$
- B decrypts checks if challengeB is the same (if no session is dropped)
- B sends $\text{Enc}[\text{Sessionkey}](\text{challengeA})$
- A decrypts, checks if challengeA is the same as her
- Can send messages encrypted with sessionkey now

2) *Augmented PAKE: SRP*:

IV. USAGE OF PAKE

The newest Wifisecurity standard WPA3 introduced an Augmented PAKE Protocol to the authentication of secured Wifi networks. This protocol is called Dragonfly and is especially used in the Handshake process of the connection.

A. Problems with PAKE

V. ATTACKS ON PAKE

A. Time-Attack

B. Replay-Attack

C. Dictionary Attack

D. Impersonation Attack

The impersonation attack is applicable if two users have multiple sessions in parallel with each other.

E. Invalid-curve Attack

Especially the offline dictionary attack is a problem, happens to other services/protocols as well Asymmetric PAKE

VI. EVALUATION & DISCUSSION

- a lot of protocols have flaws even the used ones (WLAN)
- Normal password based protocols are easier to implement and have the same security for the user, if done right - patents have made it difficult to use PAKE protocols as they are all protected - Pseudo Randomness made it insecure in web browsers

VII. CONCLUSION

REFERENCES

- [1] G. Eason, B. Noble, and I. N. Sneddon, "On certain integrals of Lipschitz-Hankel type involving products of Bessel functions," *Phil. Trans. Roy. Soc. London*, vol. A247, pp. 529–551, April 1955.
- [2] J. Clerk Maxwell, *A Treatise on Electricity and Magnetism*, 3rd ed., vol. 2. Oxford: Clarendon, 1892, pp.68–73.
- [3] I. S. Jacobs and C. P. Bean, "Fine particles, thin films and exchange anisotropy," in *Magnetism*, vol. III, G. T. Rado and H. Suhl, Eds. New York: Academic, 1963, pp. 271–350.
- [4] K. Elissa, "Title of paper if known," unpublished.
- [5] R. Nicole, "Title of paper with only first word capitalized," *J. Name Stand. Abbrev.*, in press.
- [6] Y. Yorozu, M. Hirano, K. Oka, and Y. Tagawa, "Electron spectroscopy studies on magneto-optical media and plastic substrate interface," *IEEE Transl. J. Magn. Japan*, vol. 2, pp. 740–741, August 1987 [Digests 9th Annual Conf. Magnetism Japan, p. 301, 1982].

- [7] M. Young, *The Technical Writer's Handbook*. Mill Valley, CA: University Science, 1989.
- [8] <http://ijns.galaxy.com.tw/contents/ijns-v17-n5/ijns-2015-v17-n5-p629-636.pdf>
- [9] Mathy Vanhoef and Eyal Ronen, "Dragonblood: Analyzing the Dragonfly Handshake of WPA3 and EAP-pwd,"
- [10] <https://chunminchang.gitbooks.io/j-pake-over-tls/content/pake/balanced/dh-ek.html>
- [11] <https://www.dcs.warwick.ac.uk/fenghao/files/pw.pdf>
- [12] <https://eprint.iacr.org/2014/585.pdf>