

KYCON Mini-DIN Connectors

KYCON RIGHT ANGLE PCB RECEPTACLES

- Fully Shielded for good conductivity, grounding, and EMI/RFI protection
- Mates with standard and snap and lock plugs
- Body Material: PBT Thermoplastic, UL94V-0 rated
- Contact Material: Phosphor Bronze, Gold plated

- RoHS Compliance per Kycon Documentation
- Shield Material: Brass, Tin Plated
- Solder Tails: Tin Plated Over Nickel
- Operating Temperature: -25°C to +85°C

RoHS Compliant

KMDG Series

* Meets PC99 specifications

Pan = Pantone

For quantities of 1000 and up, call for quote.

MOUSER NON-ROHS STOCK NO.	MOUSER RoHS COMPLIANT STOCK NO.	Kycon Part No.	Fig.	Pin #	Color	Price Each			
						1	25	100	500
806-KMDG-3S-BS	806-KMDGX-3S-BS	KMDGX-3S-BS	A	3	Black	.87	.82	.74	.59
806-KMDG-4S-BS	806-KMDGX-4S-BS	KMDGX-4S-BS	A	4	Black	.87	.82	.74	.59
* 806-KMDG-4S-BS-99	* 806-KMDGX-4S-BS-99	KMDGX-4S-BS-99	A	4	Pan 123C Yellow	.97	.92	.82	.65
806-KMDG-5S-BS	806-KMDGX-5S-BS	KMDGX-5S-BS	A	5	Black	1.02	.07	.87	.69
806-KMDG-6S-BS	806-KMDGX-6S-BS	KMDGX-6S-BS	A	6	Black	.79	.75	.67	.53
* 806-KMDG-6S-BS-2715C	* 806-KMDGX-6S-BS2715C	KMDGX-6S-BS2715C	A	6	Pan 2715C Purple	1.04	.99	.88	.70
* 806-KMDG-6S-BS-3395C	* 806-KMDGX-6S-BS3395C	KMDGX-6S-BS3395C	A	6	Pan 3395C Green	1.04	.99	.88	.70
806-KMDG-7S-BS	806-KMDGX-7S-BS	KMDGX-7S-BS	A	7	Black	1.19	1.12	1.00	.80
806-KMDG-8S-BS	806-KMDGX-8S-BS	KMDGX-8S-BS	A	8	Black	1.11	1.05	.94	.74
806-KMDG-9S-BS	806-KMDGX-9S-BS	KMDGX-9S-BS	A	9	Black	1.19	1.12	1.00	.80
806-KMDG-10S-BS	806-KMDGX-10S-BS	KMDGX-10S-BS	A	10	Black	2.02	1.91	1.71	1.36
With GEO S-Video Port									
806-KMDG-GEO-7S-BS	806-KMDGX-GEO-7SBS	KMDGX-GEO-7S-BS	A	7	Black	1.19	1.12	1.00	.80

KYCON RIGHT ANGLE FERRITE FILTERED PCB RECEPTACLES

- Fully Shielded for good conductivity, grounding, and EMI/RFI protection
- Mates with standard and snap and lock plugs
- Body Material: PBT Thermoplastic, UL94V-0 rated
- Contact Material: Phosphor Bronze, Gold plated

- RoHS Compliance per Kycon Documentation
- Shield Material: Brass, Tin Plated
- Solder Tails: Tin Plated Over Nickel
- Operating Temperature: -25°C to +85°C

RoHS Compliant

KFMDG Series

For quantities of 1000 and up, call for quote.

MOUSER NON-ROHS STOCK NO.	MOUSER RoHS COMPLIANT STOCK NO.	Kycon Part No.	Fig.	Pin Count	Color	Price Each			
						1	25	100	500
806-KFMDG-3S-BS	806-KFMDGX-3S-BS	KFMDGX-3S-BS	A	3	Black	2.09	1.97	1.40	1.25
806-KFMDG-4S-BS	806-KFMDGX-4S-BS	KFMDGX-4S-BS	A	4	Black	2.05	1.94	1.37	1.23
806-KFMDG-5S-BS	806-KFMDGX-5S-BS	KFMDGX-5S-BS	A	5	Black	2.16	2.04	1.44	1.29
806-KFMDG-6S-BS	806-KFMDGX-6S-BS	KFMDGX-6S-BS	A	6	Black	2.12	2.00	1.42	1.27
806-KFMDG-7S-BS	806-KFMDGX-7S-BS	KFMDGX-7S-BS	A	7	Black	2.23	2.10	1.49	1.33
806-KFMDG-8S-BS	806-KFMDGX-8S-BS	KFMDGX-8S-BS	A	8	Black	2.16	2.04	1.44	1.29

KYCON RIGHT ANGLE STACKED PCB RECEPTACLES

- Fully Shielded for good conductivity, grounding, and EMI/RFI protection
- Mates with standard and snap and lock plugs
- Body Material: PBT Thermoplastic, UL94V-0 rated
- Contact Material: Phosphor Bronze, Gold plated

- RoHS Compliance per Kycon Documentation
- Shield Material: Brass, Tin Plated
- Solder Tails: Tin Plated Over Nickel
- Operating Temperature: -25°C to +85°C

RoHS Compliant

KMDG Series

* Meets PC99 Specifications

Pan = Pantone

For quantities of 1000 and up, call for quote.

MOUSER NON-ROHS STOCK NO.	MOUSER RoHS COMPLIANT STOCK NO.	Kycon Part No.	Fig.	Pin Count	Color	Price Each			
						1	25	100	500
806-KMDG-4S/4S-S4N	806-KMDGX-4S/4S-S4N	KMDGX-4S/4S-S4N	B	4 over 4	Black	1.82	1.72	1.22	1.09
806-KMDG-6S/6S-S4N	806-KMDGX-6S/6S-S4N	KMDGX-6S/6S-S4N	B	6 over 6	Black	1.74	1.65	1.17	1.05
* 806-KMDG-6SG/P-S4N	* 806-KMDGX-6SGP-S4N	KMDGX-6SG/P-S4N	B	6 over 6	Pan 3395C Green over Pan 2715C Purple	1.27	1.21	.86	.77

KYCON RIGHT ANGLE ROUNDED LOW PROFILE PCB RECEPTACLES

- Contacts: Phosphor Bronze
- Gold Flash on contacts
- Tin on termination

- Body: PBT Thermoplastic, UL94V-0 rated
- Shield: SPCC, Tin plated
- Operating Temperature: -25°C to +85°C

- RoHS Compliance per Kycon Documentation

RoHS Compliant

KMDR Series

For quantities of 1000 and up, call for quote.

MOUSER STOCK NO.	Kycon Part No.	Fig.	Pin Count	Color	Price Each			
					1	25	100	500
806-KMDRX-4S-BS	KMDRX-4S-BS	C	4	Black	1.12	1.06	.76	.67
806-KMDRX-6S-BS	KMDRX-6S-BS	C	6	Black	1.20	1.14	.81	.72
With GEO S-Video Port								
806-KMDRX-GEO-7S-BS	KMDRX-GEO-7S-BS	C	7	Black	1.28	1.21	.86	.77
806-KMDRX-GEO-9S-BS	KMDRX-GEO-9S-BS	C	9	Black	1.36	1.28	.91	.81

KYCON CABLE MOUNT PLUGS

- Insert Material: PBT Thermoplastic, UL94V-0 rated
- Shell Material: PVC, UL94V-0 rated
- Contact Material: Brass, Silver plated

- Shield Material: Nickel plated Iron sheet
- Durability: 1500 Cycles
- Operating Temperature: -25°C to +80°C

* 30µ" Gold Plated

RoHS Compliant

KMDA and KMDLA Series

For quantities of 1000 and up, call for quote.

806-KMDA-3P	806-KMDAX-3P	KMDAX-3P	D	3	Black	.92	.74	.56	.55
806-KMDA-4P	806-KMDAX-4P	KMDAX-4P	D	4	Black	1.06	.86	.65	.63
806-KMDA-5P	806-KMDAX-5P	KMDAX-5P	D	5	Black	1.20	.97	.73	.72
806-KMDA-6P	806-KMDAX-6P	KMDAX-6P	D	6	Black	1.27	1.03	.78	.76
806-KMDA-7P	806-KMDAX-7P	KMDAX-7P	D	7	Black	1.34	1.09	.82	.80
806-KMDA-8P	806-KMDAX-8P	KMDAX-8P	D	8	Black	1.41	1.14	.86	.85
* 806-KMDA-9P	* 806-KMDAX-9P	KMDAX-9P	D	9	Black	2.24	1.96	1.68	1.32
Snap and Lock									
806-KMDLA-3P	806-KMDLAX-3P	KMDLAX-3P	E	3	Black	2.97	2.60	2.23	1.75
806-KMDLA-4P	806-KMDLAX-4P	KMDLAX-4P	E	4	Black	3.14	2.75	2.36	1.84
806-KMDLA-5P	806-KMDLAX-5P	KMDLAX-5P	E	5	Black	3.31	2.89	2.48	1.94
806-KMDLA-6P	806-KMDLAX-6P	KMDLAX-6P	E	6	Black	3.48	3.05	2.61	2.04
806-KMDLA-7P	806-KMDLAX-7P	KMDLAX-7P	E	7	Black	3.65	3.19	2.74	2.14
806-KMDLA-8P	806-KMDLAX-8P	KMDLAX-8P	E	8	Black	3.82	3.34	2.87	2.24

