

There are four preferred pin combinations for UTMI signals. Chose one based on IO voltage bank and signal routing considerations.

Monahans L - UTMI Pin Mapping, Group 1

GPIO38	VCC_I03	CLKOUT
GPIO30	VCC_I03	DATA0
GPIO31	VCC_I03	DATA1
GPIO32	VCC_I03	DATA2
GPIO33	VCC_I03	DATA3
GPIO34	VCC_I03	DATA4
GPIO35	VCC_I03	DATA5
GPIO36	VCC_I03	DATA6
GPIO37	VCC_I03	DATA7
GPIO53	VCC_LCD	TXREADY
GPIO29	VCC_I03	TXVALID
GPIO25	VCC_I03	RXACTIVE
GPIO24	VCC_I03	RXVALID
GPIO26	VCC_I03	RXERROR
GPIO27	VCC_I03	OPMODE0
GPIO28	VCC_I03	OPMODE1
GPIO76	VCC_LCD	RESET
GPIO64	VCC_LCD	XCVRSELECT
GPIO65	VCC_LCD	TERMSELECT
GPIO66	VCC_LCD	SUSPENDN
GPIO67	VCC_LCD	LINESTATE0
GPIO68	VCC_LCD	LINESTATE1
*		VBUSDETECT

* VBUSDETECT can be placed on any available GPIO

Monahans L - UTMI Pin Mapping, Group 2

GPIO38	VCC_I03	CLKOUT
GPIO39	VCC_CI	DATA0
GPIO40	VCC_CI	DATA1
GPIO41	VCC_CI	DATA2
GPIO42	VCC_CI	DATA3
GPIO43	VCC_CI	DATA4
GPIO44	VCC_CI	DATA5
GPIO45	VCC_CI	DATA6
GPIO46	VCC_CI	DATA7
GPIO53	VCC_LCD	TXREADY
GPIO69	VCC_LCD	TXVALID
GPIO47	VCC_CI	RXACTIVE
GPIO48	VCC_CI	RXVALID
GPIO50	VCC_CI	RXERROR
GPIO51	VCC_CI	OPMODE0
GPIO52	VCC_CI	OPMODE1
GPIO95	VCC_I01	RESET
GPIO96	VCC_I01	XCVRSELECT
GPIO97	VCC_I01	TERMSELECT
GPIO98	VCC_I01	SUSPENDN
GPIO92	VCC_I01	LINESTATE0
GPIO93	VCC_I01	LINESTATE1
*		VBUSDETECT

* VBUSDETECT can be placed on any available GPIO

Monahans L - UTMI Pin Mapping, Group 3

GPIO38	VCC_I03	CLKOUT
GPIO30	VCC_I03	DATA0
GPIO31	VCC_I03	DATA1
GPIO32	VCC_I03	DATA2
GPIO33	VCC_I03	DATA3
GPIO34	VCC_I03	DATA4
GPIO35	VCC_I03	DATA5
GPIO36	VCC_I03	DATA6
GPIO37	VCC_I03	DATA7
GPIO53	VCC_LCD	TXREADY
GPIO85	VCC_MSL	TXVALID
GPIO49	VCC_CI	RXACTIVE
GPIO87	VCC_MSL	RXVALID
GPIO89	VCC_MSL	RXERROR
GPIO90	VCC_MSL	OPMODE0
GPIO106	VCC_I01	OPMODE1
GPIO100	VCC_I01	RESET
GPIO101	VCC_I01	XCVRSELECT
GPIO99	VCC_I01	TERMSELECT
GPIO103	VCC_I01	SUSPENDN
GPIO104	VCC_I01	LINESTATE0
GPIO105	VCC_I01	LINESTATE1
*		VBUSDETECT

* VBUSDETECT can be placed on any available GPIO

Monahans L - UTMI Pin Mapping, Group 4

GPIO38	VCC_I03	CLKOUT
GPIO39	VCC_CI	DATA0
GPIO40	VCC_CI	DATA1
GPIO41	VCC_CI	DATA2
GPIO42	VCC_CI	DATA3
GPIO43	VCC_CI	DATA4
GPIO44	VCC_CI	DATA5
GPIO45	VCC_CI	DATA6
GPIO46	VCC_CI	DATA7
GPIO53	VCC_LCD	TXREADY
GPIO69	VCC_LCD	TXVALID
GPIO49	VCC_CI	RXACTIVE
GPIO48	VCC_CI	RXVALID
GPIO50	VCC_CI	RXERROR
GPIO51	VCC_CI	OPMODE0
GPIO110	VCC_I01	OPMODE1
GPIO95	VCC_I01	RESET
GPIO96	VCC_I01	XCVRSELECT
GPIO102	VCC_I01	TERMSELECT
GPIO98	VCC_I01	SUSPENDN
GPIO109	VCC_I01	LINESTATE0
GPIO93	VCC_I01	LINESTATE1
*		VBUSDETECT

* VBUSDETECT can be placed on any available GPIO