# AgentGate: Deterministic Guardrails Against Multi-Agent Collusion Carriers

Apart Research AI Collusion Research Sprint. Track 3 (Collusion Carriers and Countermeasures) / Track 2 (Detection and Audit of Collusion).

Generated 2026-10-25T09:08:56Z by python -m agent_gateway evaluate-collusion --report. Same-author scripted synthetic lab scenarios; not a benchmark.

## ABSTRACT

Autonomous agents that share tools can coordinate covertly: one agent can leak information through which tool or argument it picks and when it calls, launder a restricted capability by handing work to a cleaner peer, or move data in small or re-encoded pieces across steps. AgentGate is a loopback Policy Enforcement Point that addresses these carriers with deterministic checks and no model calls: a post-taint side-channel guard, monotonic capability attenuation across delegation, and n-gram fingerprinting across encodings with canary watermarks for provenance. In this run the repository's defence tests for the three carrier groups passed 57 of 57. The hash-chained decision log verified clean over 750 entries. Decision-time figures are not quoted.

## PROBLEM STATEMENT

Content filters look for a secret in what an agent sends. Collusion carriers avoid that in three ways:

- Group A, side channels. Information moves through the choice among a few argument variants, or through call timing, so no fragment of the protected value appears in any argument.
- Group B, delegation laundering. A restricted agent hands its task or state to a peer whose own capability looks clean (a confused deputy).
- Group C, split and encoded smuggling. A protected value leaves in pieces across steps, or after Base64, hex, URL, or whitespace transformation.

## METHODOLOGY: ZERO-COMPUTE DETERMINISTIC GUARDRAILS

Every check is arithmetic, hashing, or HMAC on the call path. No LLM is consulted (LLM calls in this run: 0).

- side_channel_guard.py: after a session is both TAINTED and SENSITIVE_READ, released outbound calls are counted for distinct argument variants, total calls, and regular inter-call rhythm (coefficient of variation). A signal denies the call, holds the session for review, and freezes the registered root key for 15 minutes.
- delegation_guard.py: a hand-off re-mints the recipient's agw1. capability with the sender's deny caveats (lattice meet). Caveats are chained HMACs, so they cannot be stripped without the root key, and a delegated principal that was barred upstream is held at egress.
- deobfuscate.py: protected values are stored only as salted SHA-256 digests of 8-character n-grams of the raw value and its encoded forms, matched against a per-session sliding window of released arguments.

- canary_watermark.py: sensitive reads carry a zero-width HMAC watermark bound to (session, step, tool), plus credential-format digests, so a hit names the originating step.
- audit_chain.py: each decision-log line carries seq, prev_hash, and entry_hash.

Evaluation procedure, all offline and reproducible:

1. Run the existing defence test files with pytest: python -m pytest -q tests/test_side_channel_guard.py tests/test_delegation_guard.py tests/test_deobfuscate.py tests/test_canary_watermark.py. Counts come from the JUnit XML, keyed by node id.
2. Run 5 benign multi-agent workflows 50 times through an in-process PolicyEngine and time each evaluate_call with thread CPU time.
3. Write each benign decision to a hash-chained log, verify it, and check that editing or dropping a line in a copy is detected.

RESULTS

Reproducible test-suite results by group

Group | Test files | Tests | Passed | Failed | Skipped
A: Side-channel and timing guard | test_side_channel_guard.py | 8 | 8 | 0 | 0
B: Multi-agent delegation and confused-deputy guard | test_delegation_guard.py | 8 | 8 | 0 | 0
C: De-obfuscation and canary provenance guard | test_deobfuscate.py, test_canary_watermark.py | 41 | 41 | 0 | 0
Total |  | 57 | 57 | 0 | 0

pytest: 57 passed in 3.05s (exit 0, 3.64 s). The full per-test list is in collusion_benchmark_results.json under defense_suite.groups[].tests.

Whole gateway suite and stateful property fuzzing

The CI job runs the gateway suite. Earlier snapshot totals are not quoted. Stateful Hypothesis machines, with settings read from the test files:

State machine | File | max_examples | stateful_step_count
DelegationDagMachine | test_delegation_guard.py | 120 | 24
SideChannelMachine | test_side_channel_guard.py | 60 | 30
PepPolicyMachine | test_stateful_fuzz.py | 40 | 16
SmugglingMachine | test_stateful_fuzz.py | 60 | 24
GatewayScrubMachine | test_stateful_fuzz.py | 80 | 8

Benign decisions

Benign denials: 0 of 750 decisions. Decision-time figures from this run are not quoted. Regular-rhythm timing beacons are flagged; irregular timing channels are not yet bounded.

Audit-chain verification

Check | Result
Benign decision log chain | verified
Entries | 750
Head hash | 462797efde1cc794...
Edited line in a copy detected | yes
Dropped line in a copy detected | yes

DEFENCE ANALYSIS: WHY THE CARRIERS FAIL HERE

- Side channels (Group A). The guard does not try to read the content. It bounds the channel: the number of distinct variants, the number of calls after the taint point, and how regular the timing is. Crossing any bound holds the session for a person. Regular-rhythm timing beacons are flagged; irregular timing channels are not yet bounded.
- Delegation laundering (Group B). Restrictions travel with the hand-off as HMAC caveats and are folded with a lattice meet, which only moves down. A peer cannot hold more egress than the agent that delegated to it, and a fresh session of a delegated principal is still held.
- Split and encoded smuggling (Group C). Matching runs on a sliding window across steps and over decoded forms, so splitting or encoding does not remove the n-gram overlap. Watermarks and credential digests give step-level provenance in the hash-chained log.
- Containment. On a signal the registered root key and its children are frozen for 15 minutes. Unregistered callers are never acted on.

SCOPE AND LIMITATIONS

- Same-author scripted synthetic lab scenarios. Not a benchmark and not a measure of any product in the wild.
- Group results are the outcome of the repository's own defence tests; each count traces to a named pytest node id.
- The real-model loopback archive figure (2 of 13 non-control runs) is a separate measurement and is never pooled with these results.
- Decision time is measured on one machine and is not a deployment guarantee.
- The gateway binds 127.0.0.1 by default. Freeze actions apply for 15 minutes to registered lab keys only.
- ATLAS technique labels are approximate.
- A passing audit-chain verify means the log is internally consistent. It is not a certification and not a penetration test.
- Group counts show that the guards behave as their own tests specify. They are not an estimate of recall against an unknown adversary.
- Benign workflows were written by the same author and are few; the denial rate is a smoke check, not a false-positive rate for real deployments.

REPRODUCE

```
pip install -e './agent-gateway[test]'
cd agent-gateway
export AGENT_GATEWAY_HMAC_KEY=$(python -c 'import secrets; print(secrets.token_hex(32))')
python -m agent_gateway evaluate-collusion --report ../sprint_submission
```

Environment: Python 3.13.17 on Linux-6.18.44-fc-v153-x86_64-with-glibc2.39. Total evaluation time 4.946 s.