



Protocol Audit Report

Version 1.0

Freeman

April 14, 2025

Contents

1	Protocol Summary	2
2	Disclaimer	2
3	Risk Classification	2
4	Audit Details	2
4.1	Scope	3
4.2	Roles	3
5	Executive Summary	3
5.1	Issues found	3
6	Findings	3
6.1	High	3
6.1.1	[H-1] Storing the password on-chain makes it visible to everyone	3
6.1.2	[H-2] <code>PasswordStore::setPassword</code> has no access controls, meaning a non-owner could change the password	4
6.2	Informational	5
6.2.1	[I-1] The <code>PasswordStore::getPassword</code> natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect	5

Prepared by

[Freeman](#)

Lead Auditors:

- Freeman

1 Protocol Summary

PasswordStore is a protocol dedicated to storage and retrieval of a user's passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

2 Disclaimer

The Chain Sentinel team makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

3 Risk Classification

	Impact		
	High	Medium	Low
Likelihood			
High	H	H/M	M
Medium	H/M	M	M/L
Low	M	M/L	L

We use the [CodeHawks](#) severity matrix to determine severity. See the documentation for more details.

4 Audit Details

The findings described in this document correspond to the following commit hash:

2e8f81e263b3a9d18fab4fb5c46805ffc10a9990

4.1 Scope

```
src/  
@> PasswordStore.sol
```

4.2 Roles

- **Owner:** Is the only one who should be able to set and access the password.

For this contract, only the owner should be able to interact with the contract.

5 Executive Summary

5.1 Issues found

Severity	Number of issues found
High	2
Medium	0
Low	1
Info	1
Gas Optimizations	0
Total	0

6 Findings

6.1 High

6.1.1 [H-1] Storing the password on-chain makes it visible to everyone

Description: All data stored on chain is public and visible to anyone. The `PasswordStore::s_password` variable is intended to be hidden and only accessible by the owner through the `PasswordStore::getPassword` function.

We show one such method of reading any data off chain below.

Impact: Anyone can read the private password, severely breaking down the functionality of the protocol.

Proof of Concept:

The below test case shows how anyone can read the password from the blockchain.

1. Create a locally running chain

```
make anvil
```

2. Deploy the contract to the chain

```
make deploy
```

3. Run the storage tool

We use 1 because that's the storage slot of `s_password` in the contract.

```
cast storage <ADDRESS_HERE> 1 --rpc-url http://127.0.0.1:8545
```

You'll get an output that looks like this:

```
0
x6d7950617373776f726440000000000000000000000000000000000000000000000014
```

You can then parse that hex to a string with:

```
cast parse-bytes32-string 0
x6d7950617373776f726440000000000000000000000000000000000000000000000014
```

And get an output of:

```
myPassword
```

Recommended Mitigation: Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password off-chain to decrypt the stored password. However, you're also likely to want to remove the view function as you wouldn't want the user to accidentally send a transaction with this decryption key.

6.1.2 [H-2] `PasswordStore::setPassword` has no access controls, meaning a non-owner could change the password

Description: The `PasswordStore::setPassword` function is set to be an external function, however the purpose of the smart contract and function's natspec indicate that "This function allows only the owner to set a new password."

```
function setPassword(string memory newPassword) external {
    // @Audit - There are no Access Controls.
    s_password = newPassword;
    emit SetNewPassword();
}
```

Impact: Anyone can set/change the password of the contract, severely breaking the contract's intended functionality.

Proof of Concept: Add the following to the `PasswordStore.t.sol` test file:

```
function test_anyone_can_set_password(address randomAddress) public {
    vm.assume(randomAddress != owner);
    vm.startPrank(randomAddress);
    string memory expectedPassword = "myNewPassword";
    passwordStore.setPassword(expectedPassword);

    vm.startPrank(owner);
    string memory actualPassword = passwordStore.getPassword();
    assertEq(actualPassword, expectedPassword);
}
```

Recommended Mitigation: Add an access control conditional to `PasswordStore::setPassword`.

```
if(msg.sender != s_owner){
    revert PasswordStore__NotOwner();
}
```

6.2 Informational

6.2.1 [I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect

Description:

```
/*
 * @notice This allows only the owner to retrieve the password.
 @> * @param newPassword The new password to set.
 */
function getPassword() external view returns (string memory) {}
```

The `PasswordStore::getPassword` function signature is `getPassword()` while the natspec says it should be `getPassword(string)`.

Impact: The natspec is incorrect.

Recommended Mitigation:

- @param newPassword The new password to set.