

		Initial Assumption: 1 Minimum allowed: 1 Maximum allowed: VU
MaxMethods	(M) 1 minimum	(M) Initial Assumption: 1 Minimum allowed: 1 Maximum allowed: VU
MaxSessions	(M) 1 minimum	N/A – not a host property
MaxAuthentications	(M) 2 minimum	N/A – not a host property
MaxTransactionLimit	(M) 1 minimum	N/A – not a host property
DefSessionTimeout	(M) VU	N/A – not a host property

4.1.1.2 StartSession (M)

An Opal SSC compliant Storage Device SHALL support the following parameters for the StartSession method:

- HostSessionID
- SPID
- Write
- HostChallenge
- HostSigningAuthority

For an Opal SSC compliant Storage Device, a value of “True” for the Write parameter SHALL be supported.

For an Opal SSC compliant Storage Device, a value of “False” (i.e. read only session) for the Write parameter may or may not be supported.

The SessionTimeout parameter of the StartSession method is optional. It may be used by the host to specify a timeout value for the session. Refer to [2] for details.

If a TPer supports the optional SessionTimeout parameter and the parameter is included in the invocation of the StartSession method, then its value is permitted if it satisfies the following conditions:

- It is less than or equal to the TPer’s MaxSessionTimeout property, the property is zero, or the property is not defined.
- It is less than or equal to the value of the SPSessionTimeout column in the SP’s SPInfo table, the value is zero, or the column is empty; and
- It is greater than or equal to the TPer’s MinSessionTimeout property, or the property is not defined.

If the specified SessionTimeout parameter value does not satisfy conditions a), b), and c) above, the TPer SHALL fail the StartSession method as defined in [2].

4.1.1.3 SyncSession (M)

An Opal SSC compliant Storage Device SHALL support the following parameters for the SyncSession method:

- HostSessionID
- SPSessionID

4.1.1.4 CloseSession (O)

An Opal SSC compliant Storage Device MAY support the CloseSession method.

4.2 Admin SP

The Admin SP includes the Base Template and the Admin Template.

4.2.1 Base Template Tables

All tables included in the following subsections are Mandatory.

4.2.1.1 SPInfo (M)

The SPInfo table is defined in [2], and Table 18 defines the Preconfiguration Data for the SPInfo table.

Table 18 - Admin SP - SPInfo Table Preconfiguration

UID	SPID	Name	Size	SizeInUse	SPSessionTimeout	Enabled
00 00 00 02 00 00 00 01	00 00 02 05 00 00 00 01	"Admin"				T

As specified in [2], a TPer SHALL ignore the value of SPSessionTimeout column if:

- no value exists in SPSessionTimeout column; or
- SPSessionTimeout column is zero.

4.2.1.2 SPTemplates (M)

The SPTemplates table is defined in [2], and Table 19 defines the Preconfiguration Data for the SPTemplates table.

*ST1 means this version number or any version number that complies with this SSC.

Table 19 - Admin SP - SPTemplates Table Preconfiguration

UID	TemplateID	Name	Version
00 00 00 03 00 00 00 01	00 00 02 04 00 00 00 01	"Base"	00 00 00 02 *ST1

00 00 00 03 00 00 00 02	00 00 02 04 00 00 00 02	"Admin"	00 00 00 02 *ST1
----------------------------	-------------------------	---------	---------------------

4.2.1.3 Table (M)

The Table table is defined in [2], and Table 20 defines the Preconfiguration Data for the Table table.

Refer to section 5.3 for a description and requirements of the MandatoryWriteGranularity and RecommendedAccessGranularity columns.

If the Data Removal Mechanism feature descriptor is not supported, then the DataRemovalMechanism row SHALL NOT exist.

Table 20 - Admin SP - Table Table Preconfiguration

UID	Name	CommonName	TemplateID	Kind	Column	NumColumns	Rows	RowsFree	RowBytes	LastID	MinSize	MaxSize	MandatoryWriteGranularity	RecommendedAccessGranularity
00 00 00 01 00 00 00 01	"Table"			Object									0	0
00 00 00 01 00 00 00 02	"SPInfo"			Object									0	0
00 00 00 01 00 00 00 03	"SPTemplates"			Object									0	0
00 00 00 01 00 00 00 06	"MethodID"			Object									0	0
00 00 00 01 00 00 00 07	"AccessControl"			Object									0	0