

# 810

## Invoice

Functional Group=IN

This Draft Standard for Trial Use contains the format and establishes the data contents of the Invoice Transaction Set (810) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the billing for goods and services provided.

### Not Defined:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

### Heading:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
010	ST	Transaction Set Header	M	1			Must use
020	BIG	Beginning Segment for Invoice	M	1			Must use
050	REF	Reference Identification	O	12			Used
<b>LOOP ID - N1</b>					<b>200</b>		
070	N1	Name	O	1			Used
080	N2	Additional Name Information	O	2			Used
090	N3	Address Information	O	2			Used
100	N4	Geographic Location	O	1			Used

### Detail:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
<b>LOOP ID - IT1</b>					<b>200000</b>		
010	IT1	Baseline Item Data (Invoice)	O	1			Used
<b>LOOP ID - PID</b>					<b>1000</b>		
060	PID	Product/Item Description	O	1			Used
110	ITD	Terms of Sale/Deferred Terms of Sale	O	2			Used

### Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
010	TDS	Total Monetary Value Summary	M	1			Must use
020	TXI	Tax Information	O	10			Used
<b>LOOP ID - SAC</b>					<b>25</b>		
040	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
<b>LOOP ID - ISS</b>					<b>&gt;1</b>		
060	ISS	Invoice Shipment Summary	O	1			Used
070	CTT	Transaction Totals	O	1		N3/070	Used
080	SE	Transaction Set Trailer	M	1			Must use

### Not Defined:

Pos	Id	Segment Name	Req	Max Use	Repeat	Notes	Usage
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

### Notes:

3/070 Number of line items (CTT01) is the accumulation of the number of IT1 segments. If used, hash total (CTT02) is the sum of the value of quantities invoiced (IT102) for each IT1 segment.

# ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements:
	16

**User Option (Usage):** Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	<b>Authorization Information Qualifier</b> <b>Description:</b> Code identifying the type of information in the Authorization Information <u>Code</u> <u>Name</u> 00 No Authorization Information Present (No Meaningful Information in I02)	M	ID	2/2	Must use
ISA02	I02	<b>Authorization Information</b> <b>Description:</b> Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	M	AN	10/10	Must use
ISA03	I03	<b>Security Information Qualifier</b> <b>Description:</b> Code identifying the type of information in the Security Information <u>Code</u> <u>Name</u> 00 No Security Information Present (No Meaningful Information in I04)	M	ID	2/2	Must use
ISA04	I04	<b>Security Information</b> <b>Description:</b> This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	M	AN	10/10	Must use
ISA05	I05	<b>Interchange ID Qualifier</b> <b>Description:</b> Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified <u>Code</u> <u>Name</u> 16 Duns Number With 4-Character Suffix	M	ID	2/2	Must use
ISA06	I06	<b>Interchange Sender ID</b> <b>Description:</b> Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element	M	AN	15/15	Must use
ISA07	I05	<b>Interchange ID Qualifier</b> <b>Description:</b> Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified <u>Code</u> <u>Name</u> 01 Duns (Dun & Bradstreet)	M	ID	2/2	Must use
ISA08	I07	<b>Interchange Receiver ID</b> <b>Description:</b> Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them	M	AN	15/15	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA09	I08	<b>Interchange Date</b> <b>Description:</b> Date of the interchange	M	DT	6/6	Must use
ISA10	I09	<b>Interchange Time</b> <b>Description:</b> Time of the interchange	M	TM	4/4	Must use
ISA11	I65	<b>Repetition Separator</b> <b>Description:</b> Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator	M		1/1	Must use
ISA12	I11	<b>Interchange Control Version Number</b> <b>Description:</b> Code specifying the version number of the interchange control segments <b>Code Name</b> 00401 Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997	M	ID	5/5	Must use
ISA13	I12	<b>Interchange Control Number</b> <b>Description:</b> A control number assigned by the interchange sender	M	N0	9/9	Must use
ISA14	I13	<b>Acknowledgment Requested</b> <b>Description:</b> Code indicating sender's request for an interchange acknowledgment <b>Code Name</b> 1 Interchange Acknowledgment Requested (TA1)	M	ID	1/1	Must use
ISA15	I14	<b>Interchange Usage Indicator</b> <b>Description:</b> Code indicating whether data enclosed by this interchange envelope is test, production or information <b>Code Name</b> T Test Data	M	ID	1/1	Must use
ISA16	I15	<b>Component Element Separator</b> <b>Description:</b> Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator	M		1/1	Must use

# GS Functional Group Header

<b>Pos:</b>	<b>Max: 1</b>
<b>Not Defined - Mandatory</b>	
<b>Loop: N/A</b>	<b>Elements: 8</b>

**User Option (Usage):** Must use

To indicate the beginning of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	<b>Functional Identifier Code</b> <b>Description:</b> Code identifying a group of application related transaction sets	M	ID	2/2	Must use
		<b>Code Name</b> DI Dealer Information (128)				
GS02	142	<b>Application Sender's Code</b> <b>Description:</b> Code identifying party sending transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS03	124	<b>Application Receiver's Code</b> <b>Description:</b> Code identifying party receiving transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS04	373	<b>Date</b> <b>Description:</b> Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year	M	DT	8/8	Must use
GS05	337	<b>Time</b> <b>Description:</b> Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	M	TM	4/8	Must use
GS06	28	<b>Group Control Number</b> <b>Description:</b> Assigned number originated and maintained by the sender	M	N0	1/9	Must use
GS07	455	<b>Responsible Agency Code</b> <b>Description:</b> Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480	M	ID	1/2	Must use
		<b>Code Name</b> X Accredited Standards Committee X12				
GS08	480	<b>Version / Release / Industry Identifier Code</b> <b>Description:</b> Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed	M	AN	1/12	Must use
		<b>Code Name</b>				

004010 Standards Approved for Publication by ASC X12 Procedures Review Board through  
October 1997

**Semantics:**

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

**Comments:**

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

# ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the start of a transaction set and to assign a control number

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	<b>Transaction Set Identifier Code</b> <b>Description:</b> Code uniquely identifying a Transaction Set <b>Code Name</b> 810 Invoice	M	ID	3/3	Must use
ST02	329	<b>Transaction Set Control Number</b> <b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

## Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

# BIG Beginning Segment for Invoice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

**User Option (Usage):** Must use

To indicate the beginning of an invoice transaction set and transmit identifying numbers and dates

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIG01	373	<b>Date</b> <b>Description:</b> Date expressed as CCYYMMDD	M	DT	8/8	Must use
BIG02	76	<b>Invoice Number</b> <b>Description:</b>	M	AN	1/22	Must use
BIG03	373	<b>Date</b> <b>Description:</b> Date expressed as CCYYMMDD	O	DT	8/8	Used
BIG04	324	<b>Purchase Order Number</b> <b>Description:</b> Identifying number for Purchase Order assigned by the orderer/purchaser	O	AN	1/22	Used
BIG07	640	<b>Transaction Type Code</b> <b>Description:</b> Code specifying the type of transaction	O	ID	2/2	Used
		<u>Code</u> <u>Name</u>				
		DI Debit Invoice				

## Semantics:

1. BIG01 is the invoice issue date.
2. BIG03 is the date assigned by the purchaser to purchase order.
3. BIG10 indicates the consolidated invoice number. When BIG07 contains code CI, BIG10 is not used.

## Comments:

1. BIG07 is used only to further define the type of invoice when needed.

# REF Reference Identification

Pos: 050	Max: 12
Heading - Optional	
Loop: N/A	Elements: 2

**User Option (Usage):** Used

To specify identifying information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	<b>Reference Identification Qualifier</b> <b>Description:</b> Code qualifying the Reference Identification	M	ID	2/3	Must use
		<b>Code Name</b>				
		PO Purchase Order Number				
REF02	127	<b>Reference Identification</b> <b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN	1/30	Used

## Syntax:

1. R0203 - At least one of REF02,REF03 is required

## Semantics:

1. REF04 contains data relating to the value cited in REF02.



# Loop N1

Pos: 070	Repeat: 200
	Optional
Loop: N1	Elements:
	N/A

To identify a party by type of organization, name, and code

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	N1	Name	O	1		Used
080	N2	Additional Name Information	O	2		Used
090	N3	Address Information	O	2		Used
100	N4	Geographic Location	O	1		Used

# N1 Name

Pos: 070	Max: 1
Heading - Optional	
Loop: N1	Elements: 2

**User Option (Usage):** Used

To identify a party by type of organization, name, and code

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b> <b>Description:</b> Code identifying an organizational entity, a physical location, property or an individual	M	ID	2/3	Must use
		<b>Code Name</b>				
		BT Bill-to-Party				
		SE Selling Party				
		ST Ship To				
N102	93	<b>Name</b> <b>Description:</b> Free-form name	X	AN	1/60	Used

## Syntax:

1. R0203 - At least one of N102,N103 is required
2. P0304 - If either N103,N104 is present, then all are required

## Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# N2 Additional Name Information

Pos: 080	Max: 2
Heading - Optional	
Loop: N1	Elements: 1

User Option (Usage): Used

To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
Description: Free-form name						

# N3 Address Information

Pos: 090	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	<b>Address Information</b>	M	AN	1/55	Must use
		<b>Description:</b> Address information				
N302	166	<b>Address Information</b>	O	AN	1/55	Used
		<b>Description:</b> Address information				

# N4 Geographic Location

Pos: 100	Max: 1
Heading - Optional	
Loop: N1	Elements: 3

**User Option (Usage):** Used

To specify the geographic place of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	<b>City Name</b> <b>Description:</b> Free-form text for city name	O	AN	2/30	Used
N402	156	<b>State or Province Code</b> <b>Description:</b> Code (Standard State/Province) as defined by appropriate government agency	O	ID	2/2	Used
N403	116	<b>Postal Code</b> <b>Description:</b> Code defining international postal zone code excluding punctuation and blanks (zip code for United States)	O	ID	3/15	Used

## Syntax:

1. C0605 - If N406 is present, then all of N405 are required

## Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

# Loop IT1

Pos: 010	Repeat: 200000
Optional	
Loop: IT1	Elements: N/A

To specify the basic and most frequently used line item data for the invoice and related transactions

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	IT1	Baseline Item Data (Invoice)	O	1		Used
060		Loop PID	O		1000	Used
110	ITD	Terms of Sale/Deferred Terms of Sale	O	2		Used

# IT1 Baseline Item Data (Invoice)

Pos: 010	Max: 1
Detail - Optional	
Loop: IT1	Elements: 8

**User Option (Usage):** Used

To specify the basic and most frequently used line item data for the invoice and related transactions

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IT101	350	<b>Assigned Identification</b> <b>Description:</b> Alphanumeric characters assigned for differentiation within a transaction set	O	AN	1/20	Used
IT102	358	<b>Quantity Invoiced</b> <b>Description:</b> Number of units invoiced (supplier units)	X	R	1/10	Used
IT103	355	<b>Unit or Basis for Measurement Code</b> <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <b>Code Name</b> CQ Cartridge CT Carton	X	ID	2/2	Used
IT104	212	<b>Unit Price</b> <b>Description:</b> Price per unit of product, service, commodity, etc.	X	R	1/17	Used
IT106	235	<b>Product/Service ID Qualifier</b> <b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234) <b>Code Name</b> BP Buyer's Part Number	X	ID	2/2	Used
IT107	234	<b>Product/Service ID</b> <b>Description:</b> Identifying number for a product or service	X	AN	1/48	Used
IT108	235	<b>Product/Service ID Qualifier</b> <b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234) <b>Code Name</b> VP Vendor's (Seller's) Part Number	X	ID	2/2	Used
IT109	234	<b>Product/Service ID</b> <b>Description:</b> Identifying number for a product or service	X	AN	1/48	Used

## Syntax:

1. P020304 - If either IT102,IT103,IT104 is present, then all are required
2. P0607 - If either IT106,IT107 is present, then all are required
3. P0809 - If either IT108,IT109 is present, then all are required
4. P1011 - If either IT110,IT111 is present, then all are required
5. P1213 - If either IT112,IT113 is present, then all are required
6. P1415 - If either IT114,IT115 is present, then all are required
7. P1617 - If either IT116,IT117 is present, then all are required
8. P1819 - If either IT118,IT119 is present, then all are required
9. P2021 - If either IT120,IT121 is present, then all are required
10. P2223 - If either IT122,IT123 is present, then all are required
11. P2425 - If either IT124,IT125 is present, then all are required

**Semantics:**

1. IT101 is the purchase order line item identification.

**Comments:**

1. Element 235/234 combinations should be interpreted to include products and/or services. See the Data Dictionary for a complete list of IDs.
2. IT106 through IT125 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.



# Loop PID

Pos: 060	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

To describe a product or process in coded or free-form format

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	PID	Product/Item Description	O	1		Used

# PID Product/Item Description

Pos: 060	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

**User Option (Usage):** Used

To describe a product or process in coded or free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	<b>Item Description Type</b> <b>Description:</b> Code indicating the format of a description	M	ID	1/1	Must use
		<b>Code Name</b> F Free-form				
PID05	352	<b>Description</b> <b>Description:</b> A free-form description to clarify the related data elements and their content	X	AN	1/80	Used

## Syntax:

1. C0403 - If PID04 is present, then all of PID03 are required
2. R0405 - At least one of PID04,PID05 is required
3. C0703 - If PID07 is present, then all of PID03 are required
4. C0804 - If PID08 is present, then all of PID04 are required
5. C0905 - If PID09 is present, then all of PID05 are required

## Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

## Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

# ITD Terms of Sale/Deferred Terms of Sale

Pos: 110	Max: 2
Detail - Optional	
Loop: IT1	Elements: 9

User Option (Usage): Used

To specify terms of sale

## Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
ITD01	336	<b>Terms Type Code</b> <b>Description:</b> Code identifying type of payment terms <b>Code Name</b> 01 Basic	O	ID	2/2	Used
ITD02	333	<b>Terms Basis Date Code</b> <b>Description:</b> Code identifying the beginning of the terms period <b>Code Name</b> 3 Invoice Date	O	ID	1/2	Used
ITD03	338	<b>Terms Discount Percent</b> <b>Description:</b> Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date	O	R	1/6	Used
ITD04	370	<b>Terms Discount Due Date</b> <b>Description:</b> Date payment is due if discount is to be earned expressed in format CCYYMMDD	X	DT	8/8	Used
ITD05	351	<b>Terms Discount Days Due</b> <b>Description:</b> Number of days in the terms discount period by which payment is due if terms discount is earned	X	N0	1/3	Used
ITD06	446	<b>Terms Net Due Date</b> <b>Description:</b> Date when total invoice amount becomes due expressed in format CCYYMMDD	O	DT	8/8	Used
ITD07	386	<b>Terms Net Days</b> <b>Description:</b> Number of days until total invoice amount is due (discount not applicable)	O	N0	1/3	Used
ITD08	362	<b>Terms Discount Amount</b> <b>Description:</b> Total amount of terms discount	O	N2	1/10	Used
ITD12	352	<b>Description</b> <b>Description:</b> A free-form description to clarify the related data elements and their content	O	AN	1/80	Used

## Syntax:

1. L03040513 - If ITD03 is present, then at least one of ITD04,ITD05,ITD13 is required
2. L08040513 - If ITD08 is present, then at least one of ITD04,ITD05,ITD13 is required
3. L091011 - If ITD09 is present, then at least one of ITD10,ITD11 is required

## Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

## Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code

in ITD01 is "05", then ITD06 or ITD07 is required.

# TDS Total Monetary Value Summary

Pos: 010	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 1

**User Option (Usage):** Must use

To specify the total invoice discounts and amounts

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TDS01	610	<b>Amount</b>	M	N2	1/15	Must use
<b>Description:</b> Monetary amount						

## Semantics:

1. TDS01 is the total amount of invoice (including charges, less allowances) before terms discount (if discount is applicable).
2. TDS02 indicates the amount upon which the terms discount amount is calculated.
3. TDS03 is the amount of invoice due if paid by terms discount due date (total invoice or installment amount less cash discount).
4. TDS04 indicates the total amount of terms discount.

## Comments:

1. TDS02 is required if the dollar value subject to discount is not equal to the dollar value of TDS01.

# TXI Tax Information

Pos: 020	Max: 10
Summary - Optional	
Loop: N/A	Elements: 2

**User Option (Usage):** Used

To specify tax information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TXI01	963	<b>Tax Type Code</b> <b>Description:</b> Code specifying the type of tax <b>Code Name</b> LS State and Local Sales Tax	M	ID	2/2	Must use
TXI02	782	<b>Monetary Amount</b> <b>Description:</b> Monetary amount	X	R	1/18	Used

## Syntax:

1. R020306 - At least one of TXI02, TXI03, TXI06 is required
2. P0405 - If either TXI04, TXI05 is present, then all are required
3. C0803 - If TXI08 is present, then all of TXI03 are required

## Semantics:

1. TXI02 is the monetary amount of the tax.
2. TXI03 is the tax percent expressed as a decimal.
3. TXI07 is a code indicating the relationship of the price or amount to the associated segment.

# Loop SAC

Pos: 040	Repeat: 25
	Optional
Loop: SAC	Elements:
	N/A

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
040	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

# SAC Service, Promotion, Allowance, or Charge Information

Pos: 040	Max: 1
Summary - Optional	
Loop: SAC	Elements: 4

**User Option (Usage):** Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	<b>Allowance or Charge Indicator</b> <b>Description:</b> Code which indicates an allowance or charge for the service specified <u>Code</u> <u>Name</u> C Charge	M	ID	1/1	Must use
SAC02	1300	<b>Service, Promotion, Allowance, or Charge Code</b> <b>Description:</b> Code identifying the service, promotion, allowance, or charge <u>Code</u> <u>Name</u> D200 Freight Charges to Destination	X	ID	4/4	Used
SAC05	610	<b>Amount</b> <b>Description:</b> Monetary amount	O	N2	1/15	Used
SAC15	352	<b>Description</b> <b>Description:</b> A free-form description to clarify the related data elements and their content	X	AN	1/80	Used

## Syntax:

1. R0203 - At least one of SAC02,SAC03 is required
2. P0304 - If either SAC03,SAC04 is present, then all are required
3. P0607 - If either SAC06,SAC07 is present, then all are required
4. P0910 - If either SAC09,SAC10 is present, then all are required
5. C1110 - If SAC11 is present, then all of SAC10 are required
6. L130204 - If SAC13 is present, then at least one of SAC02,SAC04 is required
7. C1413 - If SAC14 is present, then all of SAC13 are required
8. C1615 - If SAC16 is present, then all of SAC15 are required

## Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

## Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction to further the code in SAC02.



2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

# Loop ISS

Pos: 060	Repeat: >1
	Optional
Loop: ISS	Elements:
	N/A

To specify summary details of total items shipped in terms of quantity, weight, and volume

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	ISS	Invoice Shipment Summary	O	1		Used

# ISS Invoice Shipment Summary

Pos: 060	Max: 1
Summary - Optional	
Loop: ISS	Elements: 2

**User Option (Usage):** Used

To specify summary details of total items shipped in terms of quantity, weight, and volume

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISS01	382	<b>Number of Units Shipped</b> <b>Description:</b> Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	X	R	1/10	Used
ISS02	355	<b>Unit or Basis for Measurement Code</b> <b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <b>Code Name</b> EA Each	X	ID	2/2	Used

## Syntax:

1. R010305 - At least one of ISS01,ISS03,ISS05 is required
2. P0102 - If either ISS01,ISS02 is present, then all are required
3. P0304 - If either ISS03,ISS04 is present, then all are required
4. P0506 - If either ISS05,ISS06 is present, then all are required

## Semantics:

1. ISS07 is the quantity of third party pallets.
2. ISS08 is the gross weight of third party pallets in pounds.

# CTT Transaction Totals

Pos: 070	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

**User Option (Usage):** Used

To transmit a hash total for a specific element in the transaction set

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	<b>Number of Line Items</b>	M	NO	1/6	Must use
		<b>Description:</b> Total number of line items in the transaction set				

## Syntax:

1. P0304 - If either CTT03,CTT04 is present, then all are required
2. P0506 - If either CTT05,CTT06 is present, then all are required

## Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

# SE Transaction Set Trailer

Pos: 080	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	<b>Number of Included Segments</b> <b>Description:</b> Total number of segments included in a transaction set including ST and SE segments	M	N0	1/10	Must use
SE02	329	<b>Transaction Set Control Number</b> <b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

## Comments:

1. SE is the last segment of each transaction set.

# GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the end of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	<b>Number of Transaction Sets Included</b> <b>Description:</b> Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	N0	1/6	Must use
GE02	28	<b>Group Control Number</b> <b>Description:</b> Assigned number originated and maintained by the sender	M	N0	1/9	Must use

## Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

## Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

# IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	<b>Number of Included Functional Groups</b> <b>Description:</b> A count of the number of functional groups included in an interchange	M	N0	1/5	Must use
IEA02	I12	<b>Interchange Control Number</b> <b>Description:</b> A control number assigned by the interchange sender	M	N0	9/9	Must use

# Table of Contents

Invoice .....	1
Interchange Control Header .....	2
Functional Group Header .....	4
Transaction Set Header .....	6
Beginning Segment for Invoice .....	7
Reference Identification .....	8
Loop N1 .....	9
Name .....	10
Additional Name Information .....	11
Address Information .....	12
Geographic Location .....	13
Loop IT1 .....	14
Baseline Item Data (Invoice) .....	15
Loop PID .....	17
Product/Item Description .....	18
Terms of Sale/Deferred Terms of Sale .....	19
Total Monetary Value Summary .....	21
Tax Information .....	22
Loop SAC .....	23
Service, Promotion, Allowance, or Charge Information .....	24
Loop ISS .....	26
Invoice Shipment Summary .....	27
Transaction Totals .....	28
Transaction Set Trailer .....	29
Functional Group Trailer .....	30
Interchange Control Trailer .....	31