

Bostwick Braun 850 Purchase Order

X12/V4010: 850 Purchase Order

Author:	SPS Commerce
Trading Partner:	
Created:	05/04/2011
Modified:	07/21/2011
Notes:	

850 Purchase Order

Functional Group=PO

This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Transaction Set (850) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the placement of purchase orders for goods and services. This transaction set should not be used to convey purchase order changes or purchase order acknowledgment information.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Used
020	BEG	Beginning Segment for Purchase Order	M	1			Used
040	CUR	Currency	O	1			Used
050	REF	Reference Identification	O	8			Used
060	PER	Administrative Communications Contact	O	1			Used
080	FOB	F.O.B. Related Instructions	O	1			Used
130	ITD	Terms of Sale/Deferred Terms of Sale	O	1			Used
150	DTM	Date/Time Reference	O	6			Used
240	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Used

<u>LOOP ID - N9</u>			<u>1</u>				
295	N9	Reference Identification	M	1			Must use
300	MSG	Message Text	O	4			Used

<u>LOOP ID - N1</u>			<u>6</u>				
310	N1	Name	M	1			Must use
330	N3	Address Information	O	1			Used
340	N4	Geographic Location	O	1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - PO1</u>			<u>100000</u>			<u>N2/010L</u>	
010	PO1	Baseline Item Data	M	1		N2/010	Must use
<u>LOOP ID - PID</u>			<u>3</u>				
050	PID	Product/Item Description	O	1			Used
100	REF	Reference Identification	O	8			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - CTT</u>			<u>1</u>			<u>N3/010L</u>	
010	CTT	Transaction Totals	M	1		N3/010	Must use
030	SE	Transaction Set Trailer	M	1			Used

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

2/010L PO102 is required.

2/010 PO102 is required.

3/010L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

3/010 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Used

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Used				
Description: Code uniquely identifying a Transaction Set										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>850</td><td>Purchase Order</td></tr></table>							<u>Code</u>	<u>Name</u>	850	Purchase Order
<u>Code</u>	<u>Name</u>									
850	Purchase Order									
ST02	329	Transaction Set Control Number	M	AN	4/9	Used				
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set										

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BEG Beginning Segment for Purchase Order

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Used

To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BEG01	353	Transaction Set Purpose Code	M	ID	2/2	Used
		Description: Code identifying purpose of transaction set				
		<u>Code</u> <u>Name</u>				
		00 Original				
BEG02	92	Purchase Order Type Code	M	ID	2/2	Used
		Description: Code specifying the type of Purchase Order				
		<u>Code</u> <u>Name</u>				
		DR Direct Ship				
		NE New Order				
BEG03	324	Purchase Order Number	M	AN	8/13	Used
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser				
		User Note 1: <i>Purchase Order Number</i>				
BEG05	373	Purchase Order Date	M	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
		User Note 1: <i>Purchase Order Date</i>				

Semantics:

1. BEG05 is the date assigned by the purchaser to purchase order.

CUR Currency

Pos: 040	Max: 1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify the currency (dollars, pounds, francs, etc.) used in a transaction

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CUR01	98	Entity Identifier Code	M	ID	2/3	Used
Description: Code identifying an organizational entity, a physical location, property or an individual						
Code Name						
BY Buying Party (Purchaser)						
CUR02	100	Currency Code	M	ID	3/3	Used
Description: Code (Standard ISO) for country in whose currency the charges are specified						
User Note 1: <i>Buyer's Currency Code</i>						

Syntax Rules:

1. C0807 - If CUR08 is present, then CUR07 is required.
2. C0907 - If CUR09 is present, then CUR07 is required.
3. C1110 - If CUR11 is present, then CUR10 is required.
4. C1210 - If CUR12 is present, then CUR10 is required.
5. C1413 - If CUR14 is present, then CUR13 is required.
6. C1513 - If CUR15 is present, then CUR13 is required.
7. C1716 - If CUR17 is present, then CUR16 is required.
8. C1816 - If CUR18 is present, then CUR16 is required.
9. C2019 - If CUR20 is present, then CUR19 is required.
10. C2119 - If CUR21 is present, then CUR19 is required.
11. L101112 - If CUR10 is present, then at least one of CUR11 or CUR12 is required.
12. L131415 - If CUR13 is present, then at least one of CUR14 or CUR15 is required.
13. L161718 - If CUR16 is present, then at least one of CUR17 or CUR18 is required.
14. L192021 - If CUR19 is present, then at least one of CUR20 or CUR21 is required.

Comments:

1. See Figures Appendix for examples detailing the use of the CUR segment.

REF Reference Identification

Pos: 050	Max: 8
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Used

Description: Code qualifying the Reference Identification

Code Name

CO	Customer Order Number
CT	Contract Number
DG	Drawing Number
IA	Internal Vendor Number
PD	Promotion/Deal Number
PR	Price Quote Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

PER Administrative Communications Contact

Pos: 060	Max: 1
Heading - Optional	
Loop: N/A	Elements: 8

User Option (Usage): Used

To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Used
Description: Code identifying the major duty or responsibility of the person or group named						
Code Name						
BD Buyer Name or Department						
PER02	93	Name	O	AN	1/60	Used
Description: Free-form name						
PER03	365	Communication Number Qualifier	X	ID	2/2	Used
Description: Code identifying the type of communication number						
Code Name						
TE Telephone						
PER04	364	Communication Number	X	AN	1/80	Used
Description: Complete communications number including country or area code when applicable						
User Note 1: Phone #						
PER05	365	Communication Number Qualifier	X	ID	2/2	Used
Description: Code identifying the type of communication number						
Code Name						
FX Facsimile						
PER06	364	Communication Number	X	AN	1/80	Used
Description: Complete communications number including country or area code when applicable						
User Note 1: Fax #						
PER07	365	Communication Number Qualifier	X	ID	2/2	Used
Description: Code identifying the type of communication number						
Code Name						
EM Electronic Mail						
PER08	364	Communication Number	X	AN	1/80	Used
Description: Complete communications number including country or area code when applicable						
User Note 1: Email						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
------------	-----------	---------------------	------------	-------------	----------------	--------------

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

FOB F.O.B. Related Instructions

Pos: 080	Max: 1
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To specify transportation instructions relating to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>																
FOB01	146	Shipment Method of Payment	M	ID	2/2	Used																
Description: Code identifying payment terms for transportation charges																						
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>CC</td><td>Collect</td></tr><tr><td>CF</td><td>Collect, Freight Credited Back to Customer</td></tr><tr><td>DF</td><td>Defined by Buyer and Seller</td></tr><tr><td>MX</td><td>Mixed</td></tr><tr><td>PC</td><td>Prepaid but Charged to Customer</td></tr><tr><td>PO</td><td>Prepaid Only</td></tr><tr><td>PP</td><td>Prepaid (by Seller)</td></tr></table>							<u>Code</u>	<u>Name</u>	CC	Collect	CF	Collect, Freight Credited Back to Customer	DF	Defined by Buyer and Seller	MX	Mixed	PC	Prepaid but Charged to Customer	PO	Prepaid Only	PP	Prepaid (by Seller)
<u>Code</u>	<u>Name</u>																					
CC	Collect																					
CF	Collect, Freight Credited Back to Customer																					
DF	Defined by Buyer and Seller																					
MX	Mixed																					
PC	Prepaid but Charged to Customer																					
PO	Prepaid Only																					
PP	Prepaid (by Seller)																					
FOB02	309	Location Qualifier	X	ID	1/2	Used																
Description: Code identifying type of location																						
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>DE</td><td>Destination (Shipping)</td></tr><tr><td>OR</td><td>Origin (Shipping Point)</td></tr></table>							<u>Code</u>	<u>Name</u>	DE	Destination (Shipping)	OR	Origin (Shipping Point)										
<u>Code</u>	<u>Name</u>																					
DE	Destination (Shipping)																					
OR	Origin (Shipping Point)																					
FOB03	352	Description	X	AN	1/80	Used																
Description: A free-form description to clarify the related data elements and their content																						

Syntax Rules:

1. C0302 - If FOB03 is present, then FOB02 is required.
2. C0405 - If FOB04 is present, then FOB05 is required.
3. C0706 - If FOB07 is present, then FOB06 is required.
4. C0809 - If FOB08 is present, then FOB09 is required.

Semantics:

1. FOB01 indicates which party will pay the carrier.
2. FOB02 is the code specifying transportation responsibility location.
3. FOB06 is the code specifying the title passage location.
4. FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 130	Max: 1
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Used

To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD01	336	Terms Type Code	O	ID	2/2	Used
		Description: Code identifying type of payment terms				
		<u>Code</u> <u>Name</u>				
		01 Basic				
		05 Discount Not Applicable				
		06 Mixed				
		08 Basic Discount Offered				
		14 Previously agreed upon				
ITD02	333	Terms Basis Date Code	O	ID	1/2	Used
		Description: Code identifying the beginning of the terms period				
		<u>Code</u> <u>Name</u>				
		3 Invoice Date				
ITD03	338	Terms Discount Percent	X	R	1/6	Used
		Description: Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date				
ITD05	351	Terms Discount Days Due	X	N0	1/3	Used
		Description: Number of days in the terms discount period by which payment is due if terms discount is earned				
ITD07	386	Terms Net Days	O	N0	1/3	Used
		Description: Number of days until total invoice amount is due (discount not applicable)				
ITD12	352	Description	O	AN	1/80	Used
		Description: A free-form description to clarify the related data elements and their content				
		User Note 1: <i>Terms Description</i>				

Syntax Rules:

1. L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.
2. L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
3. L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

DTM Date/Time Reference

Pos: 150	Max: 6
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Used

Description: Code specifying type of date or time, or both date and time

Code Name

002	Delivery Requested
010	Requested Ship
106	Required By

DTM02	373	Date	X	DT	8/8	Used
-------	-----	-------------	---	----	-----	------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. C0403 - If DTM04 is present, then DTM03 is required.
2. P0506 - If either DTM05 or DTM06 is present, then the other is required.
3. R020305 - At least one of DTM02, DTM03 or DTM05 is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 240	Max: 1
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Used

To specify the carrier and sequence of routing and provide transit time information

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
TD502	66	Identification Code Qualifier	X	ID	1/2	Used
Description: Code designating the system/method of code structure used for Identification Code (67)						
Code Name 2 Standard Carrier Alpha Code (SCAC)						
TD503	67	Identification Code	X	AN	2/80	Used
Description: Code identifying a party or other code						
User Note 1: SCAC						
TD505	387	Routing	X	AN	1/35	Used
Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity						
User Note 1: Carrier Name						
TD512	284	Service Level Code	X	ID	2/2	Used
Description: Code indicating the level of transportation service or the billing service offered by the transportation carrier						
User Note 1: Service Level for Drop Ship orders						
Code Name 3D Three Day Service CX Express Service DC Delivery Confirmation SA Same Day SE Second Day						

Syntax Rules:

1. C0203 - If TD502 is present, then TD503 is required.
2. C0708 - If TD507 is present, then TD508 is required.
3. C1011 - If TD510 is present, then TD511 is required.
4. C1312 - If TD513 is present, then TD512 is required.
5. C1413 - If TD514 is present, then TD513 is required.
6. C1512 - If TD515 is present, then TD512 is required.
7. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

N9 Reference Identification

Pos: 295	Max: 1
Heading - Mandatory	
Loop: N9	Elements: 2

User Option (Usage): Must use

To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Used

Description: Code qualifying the Reference Identification

Code Name

ZZ Mutually Defined

N903	369	Free-form Description	X	AN	1/45	Used
------	-----	-----------------------	---	----	------	------

Description: Free-form descriptive text

User Note 1: Notes

Syntax Rules:

1. C0605 - If N906 is present, then N905 is required.
2. R0203 - At least one of N902 or N903 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

MSG Message Text

Pos: 300	Max: 4
Heading - Optional	
Loop: N9	Elements: 1

User Option (Usage): Used

To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text	M	AN	1/264	Used

Description: Free-form message text

Syntax Rules:

1. C0302 - If MSG03 is present, then MSG02 is required.

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

N1 Name

Pos: 310	Max: 1
Heading - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Used
		Description: Code identifying an organizational entity, a physical location, property or an individual				
		<u>Code</u> <u>Name</u>				
		BT Bill-to-Party				
		ST Ship To				
		VN Vendor				
N102	93	Name	X	AN	1/60	Used
		Description: Free-form name				
N103	66	Identification Code Qualifier	X	ID	1/2	Used
		Description: Code designating the system/method of code structure used for Identification Code (67)				
		<u>Code</u> <u>Name</u>				
		1 D-U-N-S Number, Dun & Bradstreet				
		92 Assigned by Buyer or Buyer's Agent				
N104	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				

Syntax Rules:

1. P0304 - If either N103 or N104 is present, then the other is required.
2. R0203 - At least one of N102 or N103 is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Address Information

Pos: 330	Max: 1
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Used
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 340	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	M	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	M	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	M	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

PO1 Baseline Item Data

Pos: 010	Max: 1
Detail - Mandatory	
Loop: PO1	Elements: 11

User Option (Usage): Must use

To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification	O	AN	1/20	Used
Description: Alphanumeric characters assigned for differentiation within a transaction set						
User Note 1: Line #						
PO102	330	Quantity Ordered	X	R	1/15	Used
Description: Quantity ordered						
User Note 1: Quantity Ordered						
PO103	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
Code Name						
EA Each						
PO104	212	Unit Price	X	R	1/17	Used
Description: Price per unit of product, service, commodity, etc.						
User Note 1: Unit Price						
PO105	639	Basis of Unit Price Code	X	ID	2/2	Used
Description: Code identifying the type of unit price for an item						
Code Name						
DI Distributor						
PO106	235	Product/Service ID Qualifier	X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
Code Name						
BP Buyer's Part Number						
PO107	234	Product/Service ID	X	AN	1/48	Used
Description: Identifying number for a product or service						
User Note 1: Buyer's Part #						
PO108	235	Product/Service ID Qualifier	M	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
Code Name						

		<u>Code</u>	<u>Name</u>				
		VP	Vendor's (Seller's) Part Number				
PO109	234	Product/Service ID		M	AN	1/48	Must use
Description: Identifying number for a product or service							
User Note 1: <i>Vendor's Part #</i>							
PO110	235	Product/Service ID Qualifier		X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)							
		<u>Code</u>	<u>Name</u>				
		UP	U.P.C. Consumer Package Code (1-5-5-1)				
PO111	234	Product/Service ID		X	AN	1/48	Used
Description: Identifying number for a product or service							
User Note 1: <i>UPC</i>							

Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.
9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

PID Product/Item Description

Pos: 050	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

User Option (Usage): Used

To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
PID01	349	Item Description Type	M	ID	1/1	Used				
Description: Code indicating the format of a description										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>F</td><td>Free-form</td></tr></table>							<u>Code</u>	<u>Name</u>	F	Free-form
<u>Code</u>	<u>Name</u>									
F	Free-form									
PID05	352	Description	X	AN	1/80	Used				

Description: A free-form description to clarify the related data elements and their content

User Note 1: *Description*

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. C0703 - If PID07 is present, then PID03 is required.
3. C0804 - If PID08 is present, then PID04 is required.
4. C0905 - If PID09 is present, then PID05 is required.
5. R0405 - At least one of PID04 or PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

REF Reference Identification

Pos: 100	Max: 8
Detail - Optional	
Loop: PO1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Used

Description: Code qualifying the Reference Identification

Code Name

CO	Customer Order Number
CT	Contract Number
DG	Drawing Number
PD	Promotion/Deal Number
PR	Price Quote Number

REF02	127	Reference Identification	X	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Mandatory	
Loop: CTT	Elements: 3

User Option (Usage): Must use

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Used

Description: Total number of line items in the transaction set

CTT02	347	Hash Total	O	R	1/10	Used
-------	-----	------------	---	---	------	------

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash total prior to truncation. 855 Hash total after truncation to three-digit field.

User Note 1: Total Quantity

CTT03	81	Weight	X	R	1/10	Used
-------	----	--------	---	---	------	------

Description: Numeric value of weight

User Note 1: Total Weight

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Used

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Used
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Used
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						