



**UNIVERSITÄT PADERBORN**

*Die Universität der Informationsgesellschaft*

Faculty for Computer Science, Electrical Engineering and Mathematics

Department of Computer Science

Research Group DICE Group

## Bachelor's Thesis

Submitted to the DICE Group Research Group

in Partial Fulfilment of the Requirements for the Degree of

Bachelor of Science

# Basilisk – Continuous Benchmarking for Triplestores

by  
FABIAN RENSING

Thesis Supervisor:  
Prof. Dr. Axel-Cyrille Ngonga Ngomo

Paderborn, January 4, 2022



# Erklärung

Ich versichere, dass ich die Arbeit ohne fremde Hilfe und ohne Benutzung anderer als der angegebenen Quellen angefertigt habe und dass die Arbeit in gleicher oder ähnlicher Form noch keiner anderen Prüfungsbehörde vorgelegen hat und von dieser als Teil einer Prüfungsleistung angenommen worden ist. Alle Ausführungen, die wörtlich oder sinngemäß übernommen worden sind, sind als solche gekennzeichnet.

---

Ort, Datum

---

Unterschrift



**Abstract.** Abstract



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Related Work</b>	<b>3</b>
<b>3</b>	<b>Background</b>	<b>5</b>
3.1	Knowledge Graph . . . . .	5
3.2	Triplestore . . . . .	5
3.3	SPARQL . . . . .	6
3.4	Benchmark . . . . .	6
3.5	IGUANA . . . . .	6
<b>4</b>	<b>Approach</b>	<b>7</b>
<b>5</b>	<b>Implementation</b>	<b>9</b>
<b>6</b>	<b>Evaluation</b>	<b>11</b>
<b>7</b>	<b>Summary and Discussion</b>	<b>13</b>
	<b>Bibliography</b>	<b>14</b>





# Introduction

In the field of Semantic Web, knowledge graphs are an important structure to represent data and its relationships. To easily store and query the data in these knowledge graphs, some data structure or database is needed. The special kind of database developed to store knowledge graphs are called Triplestores.

Since knowledge graphs can contain huge amounts of data which can also be subject to many changes, Triplestores need to be able to handle many different workloads. Some scenarios need to handle huge amount of data being added, while others need to handle a lot of changes on the current data. To better test and compare Triplestores in these diverse scenarios, benchmarks are performed to allow an appropriate comparison between different Triplestores[6].

In general, Benchmarks are used to measure and compare the performance of computer programs and systems with a defined set of operations. Often they are designed to mimic and reproduce a particular type of workload to the system. In the context of Triplestores, a benchmark usually consists of creating a given knowledge graph on which multiple queries and operations are performed.

Often Triplestores are developed in long iterations and are bench-marked only in a late stage of such an development iteration. Today benchmarks and the evaluation of their results are usually done manually and bind developers time. Thus, performance regressions are found very late or never.

Several benchmarks for Triplestores have been proposed [6]. IGUANA is a benchmark-independent execution framework [3] that can measure the performance of Triplestores under several parallel query request. Currently the benchmark execution framework needs to be installed and benchmarks need to be started manually. Basilisk is a continuous benchmarking service for Triplestores which internally uses IGUANA to perform the benchmarks. The idea is that the Basilisk service will check automatically for new versions of Triplestores and start benchmarks with the IGUANA framework. Further it should be possible to start custom benchmarks on demand. If a new version is found in a provided GitHub- or DockerHub-repository, Basilisk will automatically setup a benchmark environment and starts a benchmarking suite.

This means that developers do not have to worry about performing benchmarks at different stages of development.

In this thesis we continue the development of the Basilisk platform and deploy an instance to a publicly available virtual machine.



Related Work



## Background

This chapter explains the fundamental topics required to understand this thesis.

### 3.1 Knowledge Graph

Knowledge Graphs are graphs intended to represent knowledge of the real world or smaller scenarios. The knowledge stored in Knowledge Graphs is modeled in a graph-based structure. Nodes represent entities which are connected by various types of relations, represented by labeled edges in the graph. This has the benefit to represent complex relations between different nodes and edges[5].

The simplest knowledge graph consists of three elements. The subject entity, the object entity and the labeled edge between them describing their relation. This atomic data entity is called triple.

In figure 3.1 a simple example of a knowledge graph is shown.




Figure 3.1: Simple Knowledge Graph

Since a graph structure is hard to store in a classic relational database a different type of storage is needed. The special kind of database developed to store knowledge graphs are called Triplestores.

### 3.2 Triplestore

Triplestores are a special kind of database developed to easily store and access knowledge graphs through queries. Example of Triplestores are Tentriss[2], GraphDB<sup>1</sup>, Virtuoso<sup>2</sup>, or Jena TDB<sup>3</sup>.

This thesis focuses on Triplestores that accept SPARQL queries, since the used benchmark framework IGUANA is using the SPARQL endpoint to perform benchmarks[3].

---

<sup>1</sup><https://graphdb.ontotext.com/>

<sup>2</sup><https://virtuoso.openlinksw.com/>

<sup>3</sup><https://jena.apache.org/documentation/tdb/>

### 3.3 SPARQL

SPARQL (SPARQL Protocol and RDF Query Language)[4] is a query language for manipulating and retrieving data stored in Triplestores. Queries can contain optional graph patterns, conjunctions, disjunctions, as well as aggregation functions

### 3.4 Benchmark

Benchmarks for databases consist data set and sets of operations which will be performed on the data set. These operations are designed to simulate a particular type of workload to the system. The goal of a benchmark is to measure different metrics for a better comparison between various systems. Metrics used for databases and Triplestores are e. g., number of executed queries and queries per second[1].

### 3.5 IGUANA

IGUANA is a SPARQL benchmark execution framework[3]. The framework uses the SPARQL endpoint of the Triplestore under test to load, update and query the data. It allows the measurement of the performance during loading and updating of data as well as parallel requests to the Triplestore.

4

Approach





## Implementation



# 6

## Evaluation

- Experiment setup, requirements - Performing of benchmarks - Result evaluation



## Summary and Discussion

- Summary of the work - Highlighting the key findings of the evaluation stage



# Bibliography

- [1] Metrics - Iguana 3.3 Documentation, <http://iguana-benchmark.eu/docs/3.3/usage/metrics/>.
- [2] Alexander Biggerl, Felix Conrads, Charlotte Behning, Mohamed Ahmed Sherif, Muhammad Saleem, and Axel-Cyrille Ngonga Ngomo. Tentrism – A Tensor-Based Triple Store. In Jeff Z. Pan, Valentina Tamma, Claudia d’ Amato, Krzysztof Janowicz, Bo Fu, Axel Polleres, Oshani Seneviratne, and Lalana Kagal, editors, *The Semantic Web – ISWC 2020*, volume 12506 of *Lecture Notes in Computer Science*, pages 56–73. Springer International Publishing.
- [3] Felix Conrads, Jens Lehmann, Muhammad Saleem, Mohamed Morsey, and Axel-Cyrille Ngonga Ngomo. Iguana: A Generic Framework for Benchmarking the Read-Write Performance of Triple Stores. In Claudia d’ Amato, Miriam Fernandez, Valentina Tamma, Freddy Lecue, Philippe Cudré-Mauroux, Juan Sequeda, Christoph Lange, and Jeff Heflin, editors, *The Semantic Web – ISWC 2017*, volume 10588 of *Lecture Notes in Computer Science*, pages 48–65. Springer International Publishing.
- [4] Steve Harris, Andy Seaborne, and Eric Prud’hommeaux. SPARQL 1.1 Query Language, <https://www.w3.org/TR/sparql11-query/>.
- [5] Aidan Hogan, Eva Blomqvist, Michael Cochez, Claudia D’amato, Gerard De Melo, Claudio Gutierrez, Sabrina Kirrane, José Emilio Labra Gayo, Roberto Navigli, Sebastian Neumaier, Axel-Cyrille Ngonga Ngomo, Axel Polleres, Sabbir M. Rashid, Anisa Rula, Lukas Schmelzeisen, Juan Sequeda, Steffen Staab, and Antoine Zimmermann. Knowledge Graphs. 54(4):71:1–71:37.
- [6] Muhammad Saleem, Gábor Szárnyas, Felix Conrads, Syed Ahmad Chan Bukhari, Qaiser Mehmood, and Axel-Cyrille Ngonga Ngomo. How Representative Is a SPARQL Benchmark? An Analysis of RDF Triplestore Benchmarks. In *The World Wide Web Conference*, pages 1623–1633. ACM.