

# HF41F

## SUBMINIATURE POWER RELAY



File No.: E133481



File No.: 40020043



File No.: CQC17002175724



### Features

- Slim size (width 5mm)
- 6A switching capability 4kV dielectric strength (between coil and contacts)
- Surge voltage up to 6kV (between coil and contacts)
- Meeting VDE 0700, 0631 reinforce insulation
- High sensitive: Approx.170mW
- Sockets available
- 1 Form A and 1 Form C configurations

### CONTACT DATA

Contact arrangement	1A, 1C
Contact resistance <sup>1)</sup>	No gold plated:100mΩ max. (at 1A 6VDC) Gold plated: 30mΩ max. (at 1A 6VDC)
Contact material	AgSnO <sub>2</sub> , AgNi
Contact rating (Res. load)	6A 250VAC / 30VDC
Max. switching voltage	400VAC / 300VDC
Max. switching current	6A
Max. switching power	1500VA / 180W
Mechanical endurance	1 x 10 <sup>7</sup> OPS
Electrical endurance	H type: 6 x 10 <sup>4</sup> OPS (6A 250VAC/30VDC, Resistive load, AgNi, at 85°C, 1s on 9s off) Z type: 3 x 10 <sup>4</sup> OPS (NO, 6A 250VAC/30VDC, Resistive load, AgNi, at 85°C, 1s on 9s off) 1 x 10 <sup>4</sup> OPS (NC, 6A 250VAC/30VDC, Resistive load, AgNi, at 85°C, 1s on 9s off)

Notes:1) The data shown above are initial values.

### CHARACTERISTICS

Insulation resistance		1000MΩ (at 500VDC)
Dielectric strength	Between coil & contacts	4000VAC 1 min
	Between open contacts	1000VAC 1 min
Operate time (at rated.volt.)		8ms max.
Release time (at rated.volt.)		4ms max.
Shock resistance*1)	Functional	49m/s <sup>2</sup>
	Destructive	980m/s <sup>2</sup>
Vibration resistance*1)		10Hz to 55Hz 1mm DA
Humidity		5% to 85% RH
Ambient temperature		-40°C to 85°C
Termination		PCB
Unit weight		Approx. 5g
Construction		Plastic sealed, Flux proofed

- Notes: 1) \*Index is that of relay without socket and is not in relay length direction.  
2) The data shown above are initial values.  
3) Please find coil temperature curve in the characteristic curves below.  
4) Please do not install a SPDT(1 Form C) type relay on either of the smallest sides or facing downward.  
5) UL insulation system: Class A.



HONGFA RELAY

ISO9001, ISO/TS16949, ISO14001, OHSAS18001, IECQ QC 080000 CERTIFIED

2023 Rev. 1.00

### COIL

Coil power	5VDC to 24VDC: Approx. 170mW 48VDC, 60VDC: Approx. 210mW
------------	---

### COIL DATA

at 23°C

Nominal Voltage VDC	Pick-up Voltage VDC max. <sup>2)</sup>	Drop-out Voltage VDC min. <sup>2)</sup>	Max. Voltage VDC <sup>3)</sup>	Coil Resistance Ω
5	3.75	0.25	7.5	147 x (1±10%)
6	4.50	0.30	9.0	212 x (1±10%)
9	6.75	0.45	13.5	476 x (1±10%)
12	9.00	0.60	18	848 x (1±10%)
18	13.5	0.90	27	1906 x (1±15%)
24	18.0	1.20	36	3390 x (1±15%)
48 <sup>4)</sup>	36.0	2.40	72	10600 x (1±15%)
60 <sup>4)</sup>	45.0	3.00	90	16600 x (1±15%)

- Notes: 1) When require pick-up voltage ≤ 70% nominal voltage, special order allowed.  
2) The data shown above are initial values.  
3) Maximum voltage refers to the maximum voltage which relay coil could endure in a short period of time.  
4) For products with rated voltage ≥ 48V, measures should be taken to prevent coil overvoltage in order to protect coil in test and application (eg. Connect diodes in parallel).

### SAFETY APPROVAL RATINGS

UL/CUL	6A 30VDC at 85°C 6A 277VAC at 85°C R300 B300
VDE	6A 30VDC at 85°C 6A 250VAC at 85°C

- Notes: 1) All values unspecified are at room temperature.  
2) Only typical loads are listed above. Other load specifications can be available upon request.

## ORDERING INFORMATION

Type	HF41F /	12	-H	8	S	T	G (XXX)
Coil voltage	5, 6, 9, 12, 18, 24, 48, 60VDC						
Contact arrangement	H: 1 Form A		Z: 1 Form C				
Version <sup>1)</sup>	8: Flat pack version		Nil: Vertical version				
Construction <sup>2)3)</sup>	S: Plastic sealed		Nil: Flux proofed				
Contact material	T: AgSnO <sub>2</sub>		Nil: AgNi				
Contact plating <sup>4)</sup>	G: Gold plated		Nil: No gold plated				
Special code <sup>5)</sup>	XXX: Customer special requirement			Nil: Standard			

Notes:1) We recommend flux proofed types for the flat pack version.

2) We recommend flux proofed types for a clean environment (free from contaminations like H<sub>2</sub>S, SO<sub>2</sub>, NO<sub>2</sub>, dust, etc.).

We suggest to choose plastic sealed types and validate it in real application for an unclean environment (with contaminations like H<sub>2</sub>S, SO<sub>2</sub>, NO<sub>2</sub>, dust, etc.).

3) Contact is recommended for suitable condition and specifications if water cleaning or surface process is involved in assembling relays on PCB.

4) For gold plated type, the min. switching current and min. switching voltage is 10mA 5VDC.

5) The customer special requirement express as special code after evaluating by Hongfa. e.g. (210) stands for pick-up voltage less than 70% of nominal voltage. e.g. (414) stands for wide coil pin type.

6) Standard tube packing length is 550mm. Any special requirement needed, please contact us for more details.


7) For products that should meet the explosion-proof requirements of "IEC 60079 series", please note [Ex] after the specification while placing orders. Not all products have explosion-proof certification, so please contact us if necessary, in order to select the suitable products.

## OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT


Unit: mm

### Outline Dimensions



1 Form A  
Vertical version



1 Form C





Flat pack version






## Unit: mm

1 Form A  
Special code: (414)




1 Form A

Vertical version




Technical drawing of a mechanical part with dimensions:

- Overall width:  $28$
- Overall height:  $4 \times 0.85 \pm 0.1$
- Top horizontal dimensions:  $2 \times 1.1 \pm 0.1$  and  $2 \times 1.3^{+0.1}_0$
- Left vertical dimensions:  $0.95 \pm 0.1$  and  $3.78 \pm 0.1$
- Right vertical dimension:  $5.04 \pm 0.1$
- Bottom horizontal dimension:  $16.38 \pm 0.1$
- Feature (12) is indicated on the left side.




1 Form A




107

## CHARACTERISTIC CURVES

MAXIMUM SWITCHING POWER




ENDURANCE CURVE



**Test conditions:**

NO, AgNi, Resistive load, 250VAC,  
Flux proofed, Room temp., the typical  
value of test 1s on 9s off.


COIL TEMPERATURE RISE



**Test conditions:**


6A 85°C  
(Typical curve of 24VDC standard type)

LOAD SWITCHING CAPACITY CURVE



**Test conditions:** NO, Room temp.


BREAKING CAPACITY TRIP CURVE



**Test conditions:**

Room temp., Plastic sealed, 1s on 9s off.


AC INDUCTIVE LOAD ENDURANCE CURVE



**Test conditions:**

NO, AgNi, Plastic sealed, Room temp.,  
250VAC

DC INDUCTIVE LOAD ENDURANCE CURVE



**Test conditions:**

NO, AgNi, Plastic sealed, Room temp.,  
24VDC

**Notes:** Characteristic data is not guaranteed value but measured values of samples from production line.

### Disclaimer

The specification is for reference only. See to "Terminology and Guidelines" for more information. Specifications subject to change without notice. We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.