


# Zig-zag Scanning

锯齿形扫描



# JPEG Encoder





Fig. 9.1: Block diagram for JPEG encoder.

Source: Ze-Nian Li, Mark S. Drew, Jiangchuan Liu, Fundamental of Multimedia, Springer 2021


# JPEG Decoder



# Hierarchical Search

分层搜索：阶层式搜寻

- A three-level hierarchical search, the original image is at Level 0.
- Images at Levels 1 and 2 are obtained by **down-sampling** from the previous levels by a factor of 2, and the initial search is conducted at Level 2.



三级分层搜索，原始图像处于0级。

1级和2级的图像是通过对前两级进行2倍的降采样获得的，初始搜索在2级进行。

A Three-level Hierarchical Search


# MPEG-1: I-Frame Encoding

I帧编码




# MPEG-1: P-Frame Encoding Flowchart

p帧编码流程图



# MPEG-1: B-Frame Encoding Flowchart



# Type of Scalabilities




FIGURE 4: Spatial scalability. 图4:空间可扩展性。

可以传大的基础层




FIGURE 5: Quality scalability. 图5:质量可伸缩性。

基础层传垃圾





FIGURE 6: Temporal scalability. 图6:时间可伸缩性。

可以多传一倍的照片



### 3.2.5.3.1.信噪比可扩展


步长要小得多，因为你希望它覆盖更多细节




# MPEG-2: Spatial Scalability

2:13:41

MPEG-2: 空间可扩展性



# MPEG-2: Temporal Scalability




(a) Block Diagram

# H.261: I-frame Coding


宏块包含4Y, 1Cb和1Cr的8 x 8像素块，用于4:2:0色度子采样

- A macroblock contains 4Y, 1Cb, and 1Cr of 8 x 8 pixel blocks for 4:2:0 chroma subsampling.
- Macroblocks are of size 16 x 16 pixels for the Y frame, and 8 x 8 for Cb and Cr frames. 对于Y帧，macroblock的大小为16 x 16像素，对于Cb和Cr为8 x 8像素。
- For each 8 x 8 block, a DCT transform is applied, the DCT coefficients then go through quantization, zigzag scanning, and entropy coding.

对于每个8 x 8块，应用DCT变换，DCT系数然后经过量化，之字形扫描和熵编码。




# H.261: P-frame Coding



H.261 P-frame Coding Based on Motion Compensation

# H.264: Encoder



# ResNet

消失梯度问题

继续向普通 CNN 添加许多不同的层，实际上性能在提高一段时间后就会开始下降

如果你将梯度堆叠在许多不同的层上，是的，你的早期层无法有效更新

残差块

$x$

$F(x)$

weight layer

relu

weight layer


$x$  identity

$F(x) + x$

relu

高速公路或跳过连接

高速公路连接来更有效地反向传播这个梯度仍然可以有效地反向传播






# Scaled Dot-Product Attention

- Step 1: compute the correlation (dot product) between the query (q) and key (k) vectors.
- Step 2: correlation values from Step 1 are scaled and normalized using Softmax function.
- Step 3: multiplied output from Step 2 by corresponding value (v) vectors and sum them up.

步骤1: 计算查询(q)和键(k)向量之间的相关性(点积)。  
步骤2: 使用Softmax函数对步骤1的相关值进行缩放和归一化。  
步骤3: 将步骤2的输出与相应的值向量(v)相乘并求和。




$$A(Q, K, V) = softmax\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$

Diagram illustrating the matrix operations:  $Q$  (purple 2x3) multiplied by  $K^T$  (orange 3x2) to produce a 2x2 matrix, which is then divided by  $\sqrt{d_k}$  and passed through a softmax function to produce a 2x2 weight matrix. This weight matrix is multiplied by  $V$  (blue 2x3) to produce the final output  $Z$  (pink 2x3).



# Transformer Architecture (1) 变压器结构



Source: Ria Kulshrestha, Transformers. <https://towardsdatascience.com/transformers-89034557de14>