


22-S1-Q1

(1) Q: $h(x, y) = ?$ 2 spatial properties?

Solution

① $g(x, y) = f(x, y) * h(x, y)$

②



③ $h(x, y) = 4\delta(x, y)$

$$- \delta(x-1, y) - \delta(x+1, y) - \delta(x, y-1) - \delta(x, y+1)$$

$$h(x, y) = \begin{cases} 4 & (x, y) = (0, 0) \\ -1 & (x, y) = (\pm 1, 0) \text{ or } (0, \pm 1) \\ 0 & \text{otherwise} \end{cases}$$

④ spatial properties

1. High-Pass filtering: The filter emphasizes regions with high spatial frequency content (edges) by computing the difference between a pixel and its neighbors

2. Spatial Localization: The filter is localized affecting only a pixel and its immediate neighbors due to the non-zero coefficients being limited to the central pixel and its four direct neighbors

$$(b) H(u, v) = \frac{1}{mn} \sum_{x=0}^{m-1} \sum_{y=0}^{n-1} h(x, y) e^{-j2\pi(\frac{ux}{m} + \frac{vy}{n})}$$

$$= \frac{1}{3 \times 3} \sum_{x=-1}^1 \sum_{y=-1}^1 h(x, y) e^{-j\frac{2\pi}{3}(ux + vy)}$$

$$= \frac{1}{9} \left[h(0,0) e^0 + h(1,0) e^{-j\frac{2\pi}{3}u} + h(-1,0) e^{j\frac{2\pi}{3}u} + h(0,1) e^{j\frac{2\pi}{3}v} + h(0,-1) e^{-j\frac{2\pi}{3}v} \right]$$

$$= \frac{1}{9} \left[4 - e^{-j\frac{2\pi}{3}u} - e^{j\frac{2\pi}{3}u} - e^{-j\frac{2\pi}{3}v} - e^{j\frac{2\pi}{3}v} \right]$$

$$= \frac{1}{9} \left[4 - (e^{-j\frac{2\pi}{3}u} + e^{j\frac{2\pi}{3}u}) - (e^{-j\frac{2\pi}{3}v} + e^{j\frac{2\pi}{3}v}) \right]$$

$$= \frac{1}{9} \left[4 - 2\cos\frac{2\pi}{3}u - 2\cos\frac{2\pi}{3}v \right]$$

(c)

| | | | | | | | | |
|---|----------------|----------------|----------------|----------------|----------------|----------------|----------------|---|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 0 | 0 | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | 0 | 0 |
| 0 | \ominus^{-1} | \ominus^{-2} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-2} | \ominus^{-1} | 0 |
| 0 | \ominus^{-1} | \ominus^{-1} | \ominus^0 | \ominus^0 | \ominus^0 | \ominus^{-1} | \ominus^{-1} | 0 |
| 0 | \ominus^{-1} | \ominus^{-1} | \ominus^0 | \ominus^0 | \ominus^0 | \ominus^{-1} | \ominus^{-1} | 0 |
| 0 | \ominus^{-1} | \ominus^{-1} | \ominus^0 | \ominus^0 | \ominus^0 | \ominus^{-1} | \ominus^{-1} | 0 |
| 0 | \ominus^{-1} | \ominus^{-2} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-2} | \ominus^{-1} | 0 |
| 0 | 0 | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | \ominus^{-1} | 0 | 0 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

(d)

edge detection: as it suppresses uniform region and enhances areas with significant intensity changes.