

SHOUT TS

- Supports SBD data
- AES 256-bit encryption
- 50-Channel GPS receiver

metOcean
telematics

iridium®




TELEMATICS

The Iridium Shout TS is the same as the Iridium Shout Nano but with a touchscreen allowing quick access to menus and ease of entering text via on-screen keyboards. Similar to the Nano, the TS is designed with ultra-low power consumption electronics drawing less than 35µA during sleep.

With an internal 1.95 A-Hr rechargeable Li-Ion battery, it can send a position report every hour for up to two months (about 1,500 reports). The device can periodically wake up from sleep to send its position report to a command centre. A guarded 911 button is used for immediate emergency/alert notifications. Data are packaged in either standard or 256-bit AES encrypted 10-byte, 30-byte or PECOS format.

TECHNICAL SPECIFICATIONS

Dimensions:	104 mm x 58 mm x 23 mm (4.1" x 2.3" x 0.9")
Weight:	204 g (7.2 oz)
Battery:	Rechargeable Li-Ion, 1.95 A-Hr Single Cell, 3.6V to 4.2V
I/O Interface:	Standard USB
Software Interface:	AT Commands through USB
Operating Temp:	-40°C to +85°C (-40°F to +185°F)
Operating Humidity:	< 75% RH
Operating Frequency:	1616 to 1626.5 MHz
GPS Frequency:	1575.42 MHz (L1 carrier)



CANADA

MetOcean Telematics
21 Thornhill Drive
Dartmouth, Nova Scotia
Canada B3B 1R9
sales@metocean.com

+1 902 468 2505

UNITED STATES

MetOcean Telematics
1750 Tysons Blvd
Suite 1500, Office 1547
McLean, VA 22102
sales@metocean.com

+1 844 728 2868

UNITED KINGDOM

MetOcean Telematics
Fusion 2, 1100 Parkway
Whiteley, Hampshire
United Kingdom PO15 7AB
sales@metocean.com

+44 1489 888 555

AUSTRALIA

MetOcean Telematics
1/13A Elite Way
Carrum Downs, Victoria
Australia 3196
sales@metocean.com

+61 3 9708 2884

metocean.com