

# Pointers and dynamic objects

---

**Syed Nouman Ali Shah**  
**CSD-GCU**

# Topics

## ✉ Pointers


- Memory addresses
- Declaration
- Dereferencing a pointer
- Pointers to pointer

## ✉ Static vs. dynamic objects

- `new` and `delete`


# Computer Memory

- ✉ Each variable is assigned a memory slot (the size depends on the data type) and the variable's data is stored there



# Pointers

- ✉ A pointer is a variable used to store the address of a memory cell.
- ✉ We can use the pointer to reference this memory cell



# Pointer Types

## ✉ Pointer

- C++ has pointer types for each type of object
  - 📁 Pointers to `int` objects
  - 📁 Pointers to `char` objects
  - 📁 Pointers to user-defined objects  
(e.g., `RationalNumber`)
- Even pointers to pointers
  - 📁 Pointers to pointers to `int` objects

# Pointer Variable

## ✉ Declaration of Pointer variables

```
type* pointer_name;
```

```
//or
```

```
type *pointer_name;
```

where *type* is the type of data pointed to (e.g. int, char, double)

## Examples:

```
int *n;
```

```
RationalNumber *r;
```


```
int **p;      // pointer to pointer
```

# Address Operator &

✉ *The "address of" operator (&) gives the memory address of the variable*

■ **Usage:** `&variable_name`


Memory address: 1020                      1024



a

```
int a = 100;
//get the value,
cout << a;    //prints 100
//get the memory address
cout << &a;   //prints 1024
```

# Address Operator &



```
#include <iostream>

using namespace std;

void main(){

    int a, b;

    a = 88;

    b = 100;

    cout << "The address of a is: " << &a << endl;


    cout << "The address of b is: " << &b << endl;

}
```

- Result is:  
The address of a is: 1020  
The address of b is: 1024



# Pointer Variables



```
int a = 100;  
int *p = &a;  
cout << a << " " << &a << endl;  
cout << p << " " << &p << endl;
```

● Result is:

```
100 1024  
1024 1032
```


- ✉ The value of pointer `p` is the address of variable `a`
- ✉ A pointer is also a variable, so it has its own memory address

# Pointer to Pointer




What is the output?

58 58 58



# Dereferencing Operator \*

- ✉ We can access to the value stored in the variable pointed to by using the dereferencing operator (\*),



```
int a = 100;
int *p = &a;
cout << a << endl;
cout << &a << endl;
cout << p << " " << *p << endl;
cout << &p << endl;
```

● Result is:

```
100
1024
1024 100
1032
```

# Don't get confused

- ✉ Declaring a pointer means only that it is a pointer:  
`int *p;`
- ✉ Don't be confused with the dereferencing operator, which is also written with an asterisk (\*). They are simply two different tasks represented with the same sign

```
int a = 100, b = 88, c = 8;
int *p1 = &a, *p2, *p3 = &c;
p2 = &b;      // p2 points to b
p2 = p1;      // p2 points to a
b = *p3;      //assign c to b
*p2 = *p3;    //assign c to a
cout << a << b << c;
```

● Result is:  
**888**

# A Pointer Example

## The code

```
void doubleIt(int x,
              int * p)
{
    *p = 2 * x;
}


int main(int argc, const
char * argv[])
{
    int a = 16;
    doubleIt(9, &a);
    return 0;
}
```

a gets 18

## Box diagram



## Memory Layout



# Another Pointer Example

```
#include <iostream>
using namespace std;
int main (){
    int value1 = 5, value2 = 15;
    int *p1, *p2;
    p1 = &value1; // p1 = address of value1
    p2 = &value2; // p2 = address of value2
    *p1 = 10;      // value pointed to by p1=10
    *p2 = *p1;      // value pointed to by p2= value
                  // pointed to by p1
    p1 = p2;        // p1 = p2 (pointer value copied)
    *p1 = 20;        // value pointed to by p1 = 20
    cout << "value1==" << value1 << "/ value2==" <<
    value2;
    return 0;
}
```

- Let's figure out:  
value1==? / value2==?  
Also, p1=? p2=?

# Another Pointer Example

```
int a = 3;  
char s = 'z';  
double d = 1.03;  
int *pa = &a;  
char *ps = &s;  
double *pd = &d;
```


% sizeof returns the # of bytes...

```
cout << sizeof(pa) << sizeof(*pa)  
      << sizeof(&pa) << endl;  
cout << sizeof(ps) << sizeof(*ps)  
      << sizeof(&ps) << endl;  
cout << sizeof(pd) << sizeof(*pd)  
      << sizeof(&pd) << endl;
```

# Reference Variables

*A reference is an additional name to an existing memory location*

**Pointer:**



```
int x=9;  
int *ref;  
ref = &x;
```

**Reference:**



```
int x = 9;  
int &ref = x;
```



# Reference Variables

- ✉ A **reference variable** serves as an alternative name for an object

```
int m = 10;
int &j = m;    // j is a reference variable
cout << "value of m = " << m << endl;
               //print 10

j = 18;
cout << "value of m = " << m << endl;
    // print 18
```

# Reference Variables

- ✉ A **reference variable** always refers to the same object. Assigning a reference variable with a new value actually changes the value of the referred object.
- ✉ **Reference** variables are commonly used for parameter passing to a function

# Traditional Pointer Usage


```
void IndirectSwap(char *Ptr1, char *Ptr2){  
    char temp = *Ptr1;  
    *Ptr1 = *Ptr2;  
    *Ptr2 = temp;  
}  
  
int main() {  
    char a = 'y';  
    char b = 'n';  
    IndirectSwap(&a, &b);  
    cout << a << b << endl;  
    return 0;  
}
```

# Pass by Reference

```
void IndirectSwap(char& y, char& z) {  
    char temp = y;  
    y = z;  
    z = temp;  
}  
  
int main() {  
    char a = 'y';  
    char b = 'n';  
    IndirectSwap(a, b);  
    cout << a << b << endl;  
    return 0;  
}
```

# Pointers and Arrays

- ✉ The name of an array points only to the first element not the whole array.



# Array Name is a pointer constant


```
#include <iostream>
using namespace std;

void main () {
    int a[5];
    cout << "Address of a[0]: " << &a[0] << endl
         << "Name as pointer: " << a << endl;
}
```

## Result:

```
Address of a[0]: 0x0065FDE4
Name as pointer: 0x0065FDE4
```


# Dereferencing An Array Name



# Array Names as Pointers

- ☒ To access an array, any pointer to the first element can be used instead of the name of the array.

We could replace `*p` by `*a`




```
#include <iostream>
using namespace std;
void main(){
    int a[5] = {2,4,6,8,22};
    int *p = a;
    cout << a[0] << " "
         << *p;
}
```





# Multiple Array Pointers


✉ Both `a` and `p` are pointers to the same array.




```
#include <iostream>
using namespace std;
void main(){
    int a[5] = {2,4,6,8,22};
    int *p = &a[1];
    cout << a[0] << " "
         << p[-1];
    cout << a[1] << " "
         << p[0];
}
```

# Pointer Arithmetic

- ✉ Given a pointer  $p$ ,  $p+n$  refers to the element that is offset from  $p$  by  $n$  positions.




# Dereferencing Array Pointers



**$*(a+n)$  is identical to  $a[n]$**


- Note: flexible pointer syntax

# Array of Pointers & Pointers to Array



An array of Pointers

```
int a = 1, b = 2, c = 3;
int *p[5];
p[0] = &a;
p[1] = &b;
p[2] = &c;
```



A pointer to an array

```
int list[5] = {9, 8, 7, 6, 5};
int *p;
P = list; //points to 1st entry
P = &list[0]; //points to 1st entry
P = &list[1]; //points to 2nd entry
P = list + 1; //points to 2nd entry
```

# NULL pointer

- ✉ NULL is a special value that indicates an empty pointer
- ✉ If you try to access a NULL pointer, you will get an error


```
int *p;  
p = 0;  
cout << p << endl; //prints 0  
cout << &p << endl; //prints address of p  
cout << *p << endl; //Error!
```

# Storing 2D Array in 1D Array

```
int twod[3][4] = {{0,1,2,3}, {4,5,6,7},  
                  {8,9,10,11}};
```

```
int oned[12];  
for(int i=0; i<3; i++){  
    for(int j=0; j<4 ; j++)  
        oned[i*4+j] = twod[i][j];  
}
```

# Pointer to 2-Dimensional Arrays



`table[i] =`  
`&table[i][0]`  
 refers to  
 the *address*  
 of the *ith*  
 row

```
int table[3][4] = {{1,2,3,4},
                  {5,6,7,8},{9,10,11,12}};
```

```
for(int i=0; i<3; i++){
    for(int j=0; j<4; j++)
        cout << (*(table+i)+j);
    cout << endl;
}
```

`*(table[i]+j)`  
`= table[i][j]`

What is  
`**table`  
 ?

# Dynamic Objects

---



# Memory Management

## ✉ Static Memory Allocation

- Memory is allocated at compilation time

## ✉ Dynamic Memory

- Memory is allocated at running time

# Static vs. Dynamic Objects

## ✉ Static object


(variables as declared in function calls)

- Memory is acquired automatically
- Memory is returned automatically when object goes out of scope

## ✉ Dynamic object

- Memory is acquired by program with an allocation request  
📁 `new operation`
- Dynamic objects can exist beyond the function in which they were allocated
- Object memory is returned by a deallocation request  
📁 `delete operation`

# Memory Allocation



new  
delete

```
{
    int a[200];
    ...
}
```

```
int* ptr;
ptr = new int[200];
...
delete [] ptr;
```

# Object (variable) creation: New


## Syntax

```
ptr = new SomeType;
```

where `ptr` is a pointer of type `SomeType`

## Example

```
int* p = new int;
```



# Object (variable) destruction: Delete


## Syntax

```
delete p;
```

storage pointed to by p is returned to free store and p is now undefined

## Example

```
int* p = new int;  
*p = 10;  
delete p;
```



# Array of New :

## dynamic arrays

### ✉ Syntax

```
P = new SomeType[Expression];
```

#### ■ Where

✉ P is a pointer of type SomeType

✉ Expression is the number of objects to be constructed  
-- we are making an array

✉ Because of the flexible pointer syntax, P can be considered to be an array

# Example

## Dynamic Memory Allocation

- Request for “unnamed” memory from the Operating System

```
■ int *p, n=10;  
  p = new int;
```



```
p = new int[100];
```



```
p = new int[n];
```



# Memory Allocation Example


Want an array of unknown size

```
#include <iostream>
using namespace std;
void main()
{
    int n;
    cout << "How many students? ";
    cin >> n;
    int *grades = new int[n];
    for(int i=0; i < n; i++){
        int mark;
        cout << "Input Grade for Student" << (i+1) << " ? :";
        cin >> mark;
        grades[i] = mark;
    }
    . . .
    printMean( grades, n ); // call a function with dynamic array
    . . .
}
```




# Freeing (or deleting) Memory

BEFORE




`delete ptr;`

AFTER




BEFORE



`delete[ ] ptr ;`

AFTER



# A Simple Dynamic List Example

```
cout << "Enter list size: ";
int n;
cin >> n;
int *A = new int[n];
if(n<=0){
    cout << "bad size" << endl;
    return 0;
}
initialize(A, n, 0); // initialize the array A with value 0
print(A, n);
A = addElement(A,n,5); //add an element of value 5 at the end of A
print(A, n);
A = deleteFirst(A,n); // delete the first element from A
print(A, n);
selectionSort(A, n); // sort the array (not shown)
print(A, n);
delete [] A;
```

# Initialize

```
void initialize(int list[], int size, int value){  
    for(int i=0; i<size; i++)  
        list[i] = value;  
  
}
```

# print()

```
void print(int list[], int size) {  
    cout << "[ ";  
    for(int i=0; i<size; i++)  
        cout << list[i] << " ";  
    cout << "]" << endl;  
}
```

- Remember in C++, array parameters are always passed by reference. That is, `void print(int list[], int size) {...}` is the same as `void print(int * list , int size) {...}`

Note: no & used here, so, the pointer itself is passed by value

# Adding Elements

```
// for adding a new element to end of array
int* addElement(int list[], int& size, int value){
    int* newList = new int [size+1]; // make new array
    if(newList==0){
        cout << "Memory allocation error for addElement!" << endl;
        exit(-1);
    }
    for(int i=0; i<size; i++)
        newList[i] = list[i];
    if(size) delete [] list;
    newList[size] = value;
    size++;
    return newList;
}
```

# Delete the first element

```
// for deleting the first element of the array
int* deleteFirst(int list[], int& size){
    if(size <= 1){
        if( size) delete list;
        size = 0;
        return NULL;
    }
    int* newList = new int [size-1]; // make new array
    if(newList==0){
        cout << "Memory allocation error for deleteFirst!" << endl;
        exit(-1);
    }
    for(int i=0; i<size-1; i++)        // copy and delete old array
        newList[i] = list[i+1];
    delete [] list;
    size--;
    return newList;
}
```

# Adding Element (version 2)

```
// for adding a new element to end of array
// here "list" is a reference to a pointer variable: if the value of
// the pointer is changed in function, the change is global.
void addElement( int * & list, int & size, const int value ){

    int * newList = new int [size + 1];

    if( newList == NULL ){
        cout << "Memory allocation error for addElement!" << endl;
        exit(-1);
    }

    for( int i = 0; i < size; i++ )
        newList[ i ] = list[ i ];

    if( size ) delete [] list;

    newList[ size ] = value;
    size++;
    list = newList;
    return;
}
```

# Deleting Element (version 2)

```
void deleteFirst( int * & list, int & size ){  
  
    if( size <= 1 ){  
        if( size )  
            delete list;  
        list = NULL;  
        size = 0;  
        return;  
    }  
  
    delete list; // delete the first element  
    list++;  
    size--;  
    return;  
}
```




# Another Main program

```
int main(){  
  
    int * A = NULL;  
    int size = 0;  
    int i;  
  
    for( i = 0; i < 10; i++ )  
        addElement( A, size, i );  
  
    for( i = 0; i < 10; i++ )  
        cout << A[i] << " ";  
    cout << endl;  
  
    for( i = 0; i < 4; i++ )  
        deleteFirst( A, size );  
  
    for( i = 0; i < 6; i++ )  
        cout << A[i] << " ";  
    cout << endl;  
  
    return 0;  
}
```

0	1	2	3	4	5	6	7	8	9
4	5	6	7	8	9				

# Dangling Pointer Problem

```
int *A = new int[5];  
for(int i=0; i<5; i++)  
    A[i] = i;  
int *B = A;
```



```
delete [] A;  
B[0] = 1; // illegal!
```



Locations do not belong to program

# Memory Leak Problem

```
int *A = new int [5];  
for(int i=0; i<5; i++)  
    A[i] = i;
```



```
A = new int [5];
```


These locations cannot be  
accessed by program



# A Dynamic 2D Array

- ⊠ A dynamic array is an array of pointers to save space when not all rows of the array are full.

⊠ `int **table;`



```
table = new int*[6];  
...  
table[0] = new int[4];  
table[1] = new int[7];  
table[2] = new int[1];  
table[3] = new int[3];  
table[4] = new int[2];  
table[5] = NULL;
```

# Memory Allocation

```
int **table;
```

```
table = new int*[6];
```

```
table[0]= new int[3];
```

```
table[1]= new int[1];
```

```
table[2]= new int[5];
```

```
table[3]= new int[10];
```

```
table[4]= new int[2];
```

```
table[5]= new int[6];
```

```
table[0][0] = 1; table[0][1] = 2; table[0][2] = 3;
```

```
table[1][0] = 4;
```

```
table[2][0] = 5; table[2][1] = 6; table[2][2] = 7;
```

```
table[2][3] = 8; table[2][4] = 9;
```

```
table[4][0] = 10; table[4][1] = 11;
```

```
cout << table[2][5] << endl;
```

# Memory Deallocation

- ✉ Memory leak is a serious bug!
- ✉ Each row must be deleted individually
- ✉ Be careful to delete each row before deleting the table pointer.

```
■ for(int i=0; i<6; i++)  
    delete [ ] table[i];  
delete [ ] table;
```

## Create a matrix of any dimensions, m by n:

```
int m, n;
cin >> m >> n >> endl;

int** mat;

mat = new int*[m];

for (int i=0;i<m;i++)
    mat[i] = new int[n];
```

### Put it into a function:

```
int m, n;
cin >> m >> n >> endl;
int** mat;
mat = imatrix(m,n);
...

int** imatrix(nr, nc) {
    int** m;
    m = new int*[nr];
    for (int i=0;i<nr;i++)
        m[i] = new int[nc];
    return m;
}
```