ckb-next

beta-v0.2.7 at branch testing

Generated by Doxygen 1.8.6

Tue May 16 2017 20:47:58

Contents

1 ckb-next: RGB Driver for Linux and OS X **1**

2 Building ckb **9**

3 cbk Improvements Roadmap **11**

4 DAEMON **13**

5 Todo List **21**

6 Deprecated List **23**

7 Namespace Index **25**

7.1 Namespace List 25

8 Hierarchical Index **27**

8.1 Class Hierarchy 27

9 Data Structure Index **31**

9.1 Data Structures 31

10 File Index **35**

10.1 File List 35

11 Namespace Documentation **39**

11.1 Ui Namespace Reference 39

12 Data Structure Documentation **41**

12.1 AnimAddDialog Class Reference 41

12.1.1 Detailed Description 42

12.1.2 Constructor & Destructor Documentation 42

12.1.2.1 AnimAddDialog 43

12.1.2.2 ∼AnimAddDialog 43

12.1.3 Member Function Documentation 43

12.1.3.1 chosenPreset 43

12.1.3.2 chosenScript 44

12.1.3.3 on_animBox_activated . . . 44
12.1.3.4 on_presetBox_activated . . . 45
12.1.3.5 on_previewBox_clicked . . . 46
12.1.4 Field Documentation . . . 46
12.1.4.1 _keys . . . 46
12.1.4.2 _light . . . 46
12.1.4.3 scripts . . . 46
12.1.4.4 showPreview . . . 47
12.1.4.5 ui . . . 47
12.2 Ui::AnimAddDialog Class Reference . . . 47
12.2.1 Detailed Description . . . 48
12.2.2 Member Function Documentation . . . 48
12.2.2.1 retranslateUi . . . 48
12.2.2.2 setupUi . . . 49
12.2.3 Field Documentation . . . 50
12.2.3.1 animBox . . . 50
12.2.3.2 buttonBox . . . 51
12.2.3.3 gridLayout . . . 51
12.2.3.4 horizontalLayout . . . 51
12.2.3.5 horizontalSpacer . . . 51
12.2.3.6 horizontalSpacer_2 . . . 51
12.2.3.7 label . . . 51
12.2.3.8 label_2 . . . 51
12.2.3.9 presetBox . . . 51
12.2.3.10 previewBox . . . 51
12.2.3.11 verticalSpacer_2 . . . 52
12.2.3.12 verticalSpacer_3 . . . 52
12.3 AnimScript Class Reference . . . 52
12.3.1 Detailed Description . . . 56
12.3.2 Data Structure Documentation . . . 56
12.3.2.1 struct AnimScript::Param . . . 56
12.3.3 Member Typedef Documentation . . . 57
12.3.3.1 PresetValue . . . 57
12.3.4 Constructor & Destructor Documentation . . . 57
12.3.4.1 ~AnimScript . . . 57
12.3.4.2 AnimScript . . . 57
12.3.4.3 AnimScript . . . 58
12.3.5 Member Function Documentation . . . 58
12.3.5.1 advance . . . 58
12.3.5.2 author . . . 58

12.3.5.3 begin . . . 59
12.3.5.4 colors . . . 60
12.3.5.5 copy . . . 60
12.3.5.6 copyright . . . 61
12.3.5.7 count . . . 61
12.3.5.8 description . . . 62
12.3.5.9 end . . . 62
12.3.5.10 frame . . . 63
12.3.5.11 guid . . . 64
12.3.5.12 hasFrame . . . 64
12.3.5.13 hasKeypress . . . 65
12.3.5.14 hasParam . . . 65
12.3.5.15 init . . . 66
12.3.5.16 keypress . . . 67
12.3.5.17 license . . . 68
12.3.5.18 list . . . 68
12.3.5.19 load . . . 69
12.3.5.20 name . . . 72
12.3.5.21 param . . . 72
12.3.5.22 parameters . . . 73
12.3.5.23 paramIterator . . . 74
12.3.5.24 path . . . 74
12.3.5.25 preset . . . 75
12.3.5.26 presets . . . 75
12.3.5.27 printParams . . . 75
12.3.5.28 readProcess . . . 76
12.3.5.29 retrigger . . . 77
12.3.5.30 scan . . . 78
12.3.5.31 setDuration . . . 79
12.3.5.32 stop . . . 79
12.3.5.33 version . . . 80
12.3.5.34 year . . . 80
12.3.6 Field Documentation . . . 81
12.3.6.1 _colorBuffer . . . 81
12.3.6.2 _colors . . . 81
12.3.6.3 _info . . . 81
12.3.6.4 _keys . . . 81
12.3.6.5 _map . . . 81
12.3.6.6 _paramValues . . . 81
12.3.6.7 _path . . . 81

12.3.6.8 _presets . . . 82
12.3.6.9 _presetValues . . . 82
12.3.6.10 durationMsec . . . 82
12.3.6.11 firstFrame . . . 82
12.3.6.12 inFrame . . . 82
12.3.6.13 initialized . . . 82
12.3.6.14 KP_NAME . . . 82
12.3.6.15 KP_NONE . . . 82
12.3.6.16 KP_POSITION . . . 82
12.3.6.17 lastFrame . . . 83
12.3.6.18 minX . . . 83
12.3.6.19 minY . . . 83
12.3.6.20 process . . . 83
12.3.6.21 readAnyFrame . . . 83
12.3.6.22 readFrame . . . 83
12.3.6.23 repeatMsec . . . 83
12.3.6.24 scripts . . . 83
12.3.6.25 stopped . . . 83
12.4 Ui::AnimSettingDialog Class Reference . . . 84
12.4.1 Detailed Description . . . 86
12.4.2 Member Function Documentation . . . 86
12.4.2.1 retranslateUi . . . 86
12.4.2.2 setupUi . . . 87
12.4.3 Field Documentation . . . 91
12.4.3.1 animName . . . 91
12.4.3.2 buttonBox . . . 91
12.4.3.3 delayBox . . . 91
12.4.3.4 gridLayout . . . 92
12.4.3.5 gridLayout_2 . . . 92
12.4.3.6 horizontalSpacer . . . 92
12.4.3.7 horizontalSpacer_2 . . . 92
12.4.3.8 horizontalSpacer_3 . . . 92
12.4.3.9 horizontalSpacer_4 . . . 92
12.4.3.10 horizontalSpacer_5 . . . 92
12.4.3.11 horizontalSpacer_6 . . . 92
12.4.3.12 infoTab . . . 92
12.4.3.13 kpDelayBox . . . 93
12.4.3.14 kpModeStopBox . . . 93
12.4.3.15 kpReleaseBox . . . 93
12.4.3.16 kpRepeatBox . . . 93

12.4.3.17 kpRepeatLabel . . . 93
12.4.3.18 kpRepeatLabel_2 . . . 93
12.4.3.19 label . . . 93
12.4.3.20 label_10 . . . 93
12.4.3.21 label_11 . . . 93
12.4.3.22 label_12 . . . 94
12.4.3.23 label_13 . . . 94
12.4.3.24 label_2 . . . 94
12.4.3.25 label_3 . . . 94
12.4.3.26 label_4 . . . 94
12.4.3.27 label_5 . . . 94
12.4.3.28 label_6 . . . 94
12.4.3.29 label_7 . . . 94
12.4.3.30 label_8 . . . 94
12.4.3.31 label_9 . . . 95
12.4.3.32 line . . . 95
12.4.3.33 line_2 . . . 95
12.4.3.34 repeatBox . . . 95
12.4.3.35 repeatLabel . . . 95
12.4.3.36 repeatLabel_2 . . . 95
12.4.3.37 sAuthorLabel . . . 95
12.4.3.38 sDescLabel . . . 95
12.4.3.39 settingsGrid . . . 95
12.4.3.40 settingTab . . . 96
12.4.3.41 sLicenseLabel . . . 96
12.4.3.42 sNameLabel . . . 96
12.4.3.43 sVerLabel . . . 96
12.4.3.44 sYearLabel . . . 96
12.4.3.45 tabWidget . . . 96
12.4.3.46 timeGrid . . . 96
12.4.3.47 timeTab . . . 96
12.4.3.48 verticalSpacer . . . 96
12.4.3.49 verticalSpacer_2 . . . 97
12.4.3.50 verticalSpacer_3 . . . 97
12.5 AnimSettingDialog Class Reference . . . 97
12.5.1 Detailed Description . . . 100
12.5.2 Constructor & Destructor Documentation . . . 100
12.5.2.1 AnimSettingDialog . . . 100
12.5.2.2 ~AnimSettingDialog . . . 105
12.5.3 Member Function Documentation . . . 105

12.5.3.1 angleDialChanged . . . 106
12.5.3.2 angleSpinnerChanged . . . 106
12.5.3.3 hLine . . . 107
12.5.3.4 name . . . 108
12.5.3.5 newDuration . . . 108
12.5.3.6 on_delayBox_valueChanged . . . 109
12.5.3.7 on_kpDelayBox_valueChanged . . . 110
12.5.3.8 on_kpReleaseBox_stateChanged . . . 110
12.5.3.9 on_kpRepeatBox_valueChanged . . . 111
12.5.3.10 on_repeatBox_valueChanged . . . 112
12.5.3.11 updateParam . . . 112
12.5.3.12 updateStops . . . 115
12.5.4 Field Documentation . . . 116
12.5.4.1 _anim . . . 116
12.5.4.2 angleDialMapper . . . 116
12.5.4.3 angleSpinnerMapper . . . 116
12.5.4.4 angleSpinners . . . 117
12.5.4.5 hasRepeat . . . 117
12.5.4.6 kpStopCheck . . . 117
12.5.4.7 lastDuration . . . 117
12.5.4.8 settingWidgets . . . 117
12.5.4.9 stopCheck . . . 117
12.5.4.10 ui . . . 117
12.5.4.11 updateMapper . . . 117
12.6 AutoRun Class Reference . . . 118
12.6.1 Detailed Description . . . 118
12.6.2 Member Function Documentation . . . 118
12.6.2.1 available . . . 118
12.6.2.2 disable . . . 119
12.6.2.3 enable . . . 119
12.6.2.4 isEnabled . . . 120
12.6.2.5 once . . . 121
12.7 CkbSettings Class Reference . . . 122
12.7.1 Detailed Description . . . 124
12.7.2 Constructor & Destructor Documentation . . . 124
12.7.2.1 CkbSettings . . . 124
12.7.2.2 CkbSettings . . . 124
12.7.2.3 CkbSettings . . . 125
12.7.2.4 ~CkbSettings . . . 125
12.7.3 Member Function Documentation . . . 125

12.7.3.1 beginGroup . . . 125
12.7.3.2 childGroups . . . 125
12.7.3.3 childKeys . . . 126
12.7.3.4 cleanUp . . . 127
12.7.3.5 contains . . . 128
12.7.3.6 containsGroup . . . 128
12.7.3.7 endGroup . . . 129
12.7.3.8 get . . . 129
12.7.3.9 isBusy . . . 130
12.7.3.10 pwd . . . 131
12.7.3.11 pwd . . . 132
12.7.3.12 remove . . . 133
12.7.3.13 set . . . 133
12.7.3.14 setValue . . . 135
12.7.3.15 value . . . 135
12.7.4 Field Documentation . . . 136
12.7.4.1 backing . . . 136
12.7.4.2 groups . . . 136
12.7.4.3 removeCache . . . 137
12.7.4.4 writeCache . . . 137
12.8 CkbSettingsWriter Class Reference . . . 137
12.8.1 Detailed Description . . . 138
12.8.2 Constructor & Destructor Documentation . . . 138
12.8.2.1 CkbSettingsWriter . . . 138
12.8.2.2 ~CkbSettingsWriter . . . 139
12.8.3 Member Function Documentation . . . 139
12.8.3.1 run . . . 139
12.8.4 Field Documentation . . . 139
12.8.4.1 _backing . . . 139
12.8.4.2 _removals . . . 139
12.8.4.3 _updates . . . 139
12.9 ColorButton Class Reference . . . 139
12.9.1 Detailed Description . . . 142
12.9.2 Constructor & Destructor Documentation . . . 142
12.9.2.1 ColorButton . . . 142
12.9.3 Member Function Documentation . . . 142
12.9.3.1 allowAlpha . . . 142
12.9.3.2 allowAlpha . . . 143
12.9.3.3 bigIcons . . . 143
12.9.3.4 bigIcons . . . 144

12.9.3.5 color . . . 144
12.9.3.6 color . . . 145
12.9.3.7 colorChanged . . . 146
12.9.3.8 pickColor . . . 146
12.9.3.9 setLabel . . . 147
12.9.3.10 setLabel . . . 147
12.9.3.11 updateImage . . . 147
12.9.4 Field Documentation . . . 148
12.9.4.1 _alpha . . . 148
12.9.4.2 _bigIcons . . . 148
12.9.4.3 _color . . . 148
12.9.4.4 _setLabel . . . 148
12.10 ColorMap Class Reference . . . 149
12.10.1 Detailed Description . . . 150
12.10.2 Constructor & Destructor Documentation . . . 150
12.10.2.1 ColorMap . . . 150
12.10.2.2 ~ColorMap . . . 150
12.10.2.3 ColorMap . . . 150
12.10.3 Member Function Documentation . . . 151
12.10.3.1 alloc . . . 151
12.10.3.2 clear . . . 151
12.10.3.3 colorForName . . . 152
12.10.3.4 colorForName . . . 153
12.10.3.5 colors . . . 153
12.10.3.6 colors . . . 154
12.10.3.7 count . . . 154
12.10.3.8 deAlloc . . . 154
12.10.3.9 init . . . 155
12.10.3.10 keyNames . . . 156
12.10.3.11 operator= . . . 156
12.10.4 Field Documentation . . . 157
12.10.4.1 _colors . . . 157
12.10.4.2 _count . . . 157
12.10.4.3 _keyNames . . . 157
12.10.4.4 _mapCount . . . 157
12.11 Ui::ExtraSettingsWidget Class Reference . . . 157
12.11.1 Detailed Description . . . 159
12.11.2 Member Function Documentation . . . 160
12.11.2.1 retranslateUi . . . 160
12.11.2.2 setupUi . . . 161

12.11.3 Field Documentation . . . 165
12.11.3.1 animCountLabel . . . 165
12.11.3.2 animPathLabel . . . 165
12.11.3.3 animScanButton . . . 165
12.11.3.4 brightnessBox . . . 165
12.11.3.5 buttonBox . . . 165
12.11.3.6 delayBox . . . 165
12.11.3.7 ditherBox . . . 165
12.11.3.8 fpsBox . . . 165
12.11.3.9 fpsWarnLabel . . . 166
12.11.3.10 gridLayout . . . 166
12.11.3.11 horizontalLayout . . . 166
12.11.3.12 horizontalLayout_2 . . . 166
12.11.3.13 horizontalSpacer . . . 166
12.11.3.14 horizontalSpacer_2 . . . 166
12.11.3.15 horizontalSpacer_3 . . . 166
12.11.3.16 label . . . 166
12.11.3.17 label_10 . . . 166
12.11.3.18 label_11 . . . 167
12.11.3.19 label_2 . . . 167
12.11.3.20 label_3 . . . 167
12.11.3.21 label_5 . . . 167
12.11.3.22 label_6 . . . 167
12.11.3.23 line . . . 167
12.11.3.24 line_2 . . . 167
12.11.3.25 line_3 . . . 167
12.11.3.26 mAccelBox . . . 167
12.11.3.27 osxLabel . . . 168
12.11.3.28 osxLine . . . 168
12.11.3.29 sAccelBox . . . 168
12.11.3.30 sSpeedBox . . . 168
12.11.3.31 sSpeedWidget . . . 168
12.11.3.32 trayBox . . . 168
12.11.3.33 verticalSpacer . . . 168
12.11.3.34 verticalSpacer_10 . . . 168
12.11.3.35 verticalSpacer_11 . . . 168
12.11.3.36 verticalSpacer_2 . . . 169
12.11.3.37 verticalSpacer_3 . . . 169
12.11.3.38 verticalSpacer_4 . . . 169
12.11.3.39 verticalSpacer_5 . . . 169

12.11.3.40 verticalSpacer_6 . . . 169
12.11.3.41 verticalSpacer_7 . . . 169
12.11.3.42 verticalSpacer_8 . . . 169
12.11.3.43 verticalSpacer_9 . . . 169
12.12 ExtraSettingsWidget Class Reference . . . 170
12.12.1 Detailed Description . . . 171
12.12.2 Constructor & Destructor Documentation . . . 172
12.12.2.1 ExtraSettingsWidget . . . 172
12.12.2.2 ~ExtraSettingsWidget . . . 173
12.12.3 Member Function Documentation . . . 173
12.12.3.1 on_animScanButton_clicked . . . 173
12.12.3.2 on_brightnessBox_clicked . . . 174
12.12.3.3 on_delayBox_clicked . . . 174
12.12.3.4 on_ditherBox_clicked . . . 175
12.12.3.5 on_fpsBox_valueChanged . . . 175
12.12.3.6 on_mAccelBox_clicked . . . 175
12.12.3.7 on_sAccelBox_clicked . . . 176
12.12.3.8 on_sSpeedBox_valueChanged . . . 176
12.12.3.9 on_trayBox_clicked . . . 177
12.12.3.10 pollUpdates . . . 177
12.12.4 Field Documentation . . . 178
12.12.4.1 ui . . . 178
12.13 KbFirmware::FW Struct Reference . . . 178
12.13.1 Detailed Description . . . 179
12.13.2 Constructor & Destructor Documentation . . . 179
12.13.2.1 FW . . . 179
12.13.3 Field Documentation . . . 179
12.13.3.1 ckbVersion . . . 179
12.13.3.2 fileName . . . 179
12.13.3.3 fwVersion . . . 179
12.13.3.4 hash . . . 179
12.13.3.5 url . . . 179
12.14 FwUpgradeDialog Class Reference . . . 179
12.14.1 Detailed Description . . . 181
12.14.2 Constructor & Destructor Documentation . . . 181
12.14.2.1 FwUpgradeDialog . . . 181
12.14.2.2 ~FwUpgradeDialog . . . 182
12.14.3 Member Function Documentation . . . 182
12.14.3.1 cleanBlob . . . 182
12.14.3.2 closeEvent . . . 183

12.14.3.3 exec . . . 183
12.14.3.4 fwUpdateFinished . . . 184
12.14.3.5 fwUpdateProgress . . . 185
12.14.3.6 on_actionButton_clicked . . . 185
12.14.3.7 on_cancelButton_clicked . . . 186
12.14.3.8 removeDev . . . 186
12.14.3.9 saveBlob . . . 187
12.14.4 Field Documentation . . . 187
12.14.4.1 blob . . . 187
12.14.4.2 evLoop . . . 187
12.14.4.3 exitSuccess . . . 187
12.14.4.4 kb . . . 187
12.14.4.5 savePath . . . 188
12.14.4.6 ui . . . 188
12.15 Ui::FwUpgradeDialog Class Reference . . . 188
12.15.1 Detailed Description . . . 189
12.15.2 Member Function Documentation . . . 190
12.15.2.1 retranslateUi . . . 190
12.15.2.2 setupUi . . . 190
12.15.3 Field Documentation . . . 192
12.15.3.1 actionButton . . . 192
12.15.3.2 cancelButton . . . 192
12.15.3.3 curLabel . . . 192
12.15.3.4 devLabel . . . 192
12.15.3.5 gridLayout . . . 193
12.15.3.6 gridLayout_2 . . . 193
12.15.3.7 horizontalSpacer . . . 193
12.15.3.8 horizontalSpacer_2 . . . 193
12.15.3.9 horizontalSpacer_3 . . . 193
12.15.3.10 horizontalSpacer_4 . . . 193
12.15.3.11 label_2 . . . 193
12.15.3.12 label_4 . . . 193
12.15.3.13 newLabel . . . 193
12.15.3.14 progressBar . . . 194
12.15.3.15 statusLabel . . . 194
12.16 GradientButton Class Reference . . . 194
12.16.1 Detailed Description . . . 195
12.16.2 Constructor & Destructor Documentation . . . 196
12.16.2.1 GradientButton . . . 196
12.16.3 Member Function Documentation . . . 196

12.16.3.1 fromString . . . 196
12.16.3.2 gradientChanged . . . 197
12.16.3.3 pickGradient . . . 197
12.16.3.4 toString . . . 198
12.16.3.5 updateImage . . . 199
12.16.4 Field Documentation . . . 200
12.16.4.1 _alpha . . . 200
12.16.4.2 _stops . . . 200
12.17 Ui::GradientDialog Class Reference . . . 200
12.17.1 Detailed Description . . . 202
12.17.2 Member Function Documentation . . . 202
12.17.2.1 retranslateUi . . . 202
12.17.2.2 setupUi . . . 203
12.17.3 Field Documentation . . . 205
12.17.3.1 buttonBox . . . 205
12.17.3.2 gridLayout . . . 205
12.17.3.3 gridLayout_2 . . . 205
12.17.3.4 gridLayout_3 . . . 206
12.17.3.5 groupBox_2 . . . 206
12.17.3.6 horizontalLayout . . . 206
12.17.3.7 horizontalLayout_2 . . . 206
12.17.3.8 horizontalSpacer . . . 206
12.17.3.9 horizontalSpacer_2 . . . 206
12.17.3.10 horizontalSpacer_3 . . . 206
12.17.3.11 label . . . 206
12.17.3.12 label_2 . . . 206
12.17.3.13 presetDelete . . . 207
12.17.3.14 presetList . . . 207
12.17.3.15 presetName . . . 207
12.17.3.16 presetSave . . . 207
12.17.3.17 stopBox . . . 207
12.17.3.18 stopColor . . . 207
12.17.3.19 stopOpacity . . . 207
12.17.3.20 stopPos . . . 207
12.17.3.21 verticalSpacer . . . 208
12.17.3.22 verticalSpacer_2 . . . 208
12.17.3.23 widget . . . 208
12.18 GradientDialog Class Reference . . . 208
12.18.1 Detailed Description . . . 211
12.18.2 Constructor & Destructor Documentation . . . 211

12.18.2.1 GradientDialog . . . 211
12.18.2.2 ~GradientDialog . . . 212
12.18.3 Member Function Documentation . . . 212
12.18.3.1 addPreset . . . 212
12.18.3.2 colorChanged . . . 213
12.18.3.3 currentChanged . . . 213
12.18.3.4 getGradient . . . 214
12.18.3.5 makeIcon . . . 215
12.18.3.6 on_presetDelete_clicked . . . 216
12.18.3.7 on_presetList_currentItemChanged . . . 216
12.18.3.8 on_presetName_textEdited . . . 217
12.18.3.9 on_presetSave_clicked . . . 217
12.18.3.10 on_stopOpacity_valueChanged . . . 218
12.18.3.11 on_stopPos_valueChanged . . . 218
12.18.3.12 setPreset . . . 219
12.18.3.13 updatePresets . . . 220
12.18.4 Field Documentation . . . 220
12.18.4.1 currentPreset . . . 220
12.18.4.2 presets . . . 221
12.18.4.3 ui . . . 221
12.19 GradientDialogWidget Class Reference . . . 221
12.19.1 Detailed Description . . . 224
12.19.2 Constructor & Destructor Documentation . . . 224
12.19.2.1 GradientDialogWidget . . . 224
12.19.3 Member Function Documentation . . . 224
12.19.3.1 colorAt . . . 224
12.19.3.2 current . . . 225
12.19.3.3 currentChanged . . . 225
12.19.3.4 fillRect . . . 225
12.19.3.5 makeStops . . . 226
12.19.3.6 mouseMoveEvent . . . 227
12.19.3.7 mousePressEvent . . . 228
12.19.3.8 mouseReleaseEvent . . . 229
12.19.3.9 moveCurrent . . . 229
12.19.3.10 paintEvent . . . 230
12.19.3.11 selectedStop . . . 231
12.19.3.12 selectionColors . . . 232
12.19.3.13 setCurrentColor . . . 233
12.19.3.14 setStops . . . 233
12.19.3.15 stopCount . . . 234

12.19.3.16 stopRect . . . 235
12.19.3.17 stops . . . 235
12.19.4 Field Documentation . . . 236
12.19.4.1 _colors . . . 236
12.19.4.2 _current . . . 236
12.19.4.3 _stops . . . 236
12.19.4.4 selected . . . 236
12.19.4.5 selectedOffset . . . 236
12.19.4.6 selectedPos . . . 236
12.20 JlCompress Class Reference . . . 237
12.20.1 Detailed Description . . . 238
12.20.2 Member Function Documentation . . . 238
12.20.2.1 compressDir . . . 238
12.20.2.2 compressFile . . . 239
12.20.2.3 compressFile . . . 240
12.20.2.4 compressFiles . . . 242
12.20.2.5 compressSubDir . . . 244
12.20.2.6 extractDir . . . 246
12.20.2.7 extractFile . . . 248
12.20.2.8 extractFile . . . 250
12.20.2.9 extractFiles . . . 251
12.20.2.10 getFileList . . . 252
12.20.2.11 removeFile . . . 254
12.21 Kb Class Reference . . . 255
12.21.1 Detailed Description . . . 260
12.21.2 Constructor & Destructor Documentation . . . 260
12.21.2.1 ~Kb . . . 260
12.21.2.2 Kb . . . 261
12.21.3 Member Function Documentation . . . 263
12.21.3.1 appendProfile . . . 263
12.21.3.2 autoSave . . . 263
12.21.3.3 currentBind . . . 263
12.21.3.4 currentLight . . . 264
12.21.3.5 currentMode . . . 265
12.21.3.6 currentPerf . . . 265
12.21.3.7 currentProfile . . . 266
12.21.3.8 deleteHw . . . 266
12.21.3.9 deletePrevious . . . 267
12.21.3.10 dither . . . 267
12.21.3.11 dither . . . 268

12.21.3.12find . . . 268
12.21.3.13frameRate . . . 269
12.21.3.14frameRate . . . 269
12.21.3.15frameUpdate . . . 270
12.21.3.16fwUpdate . . . 271
12.21.3.17fwUpdateFinished . . . 272
12.21.3.18fwUpdateProgress . . . 272
12.21.3.19getKeyMap . . . 273
12.21.3.20getMacroNumber . . . 273
12.21.3.21getMacroPath . . . 274
12.21.3.22hwProfile . . . 274
12.21.3.23hwProfile . . . 274
12.21.3.24hwSave . . . 275
12.21.3.25indexOf . . . 276
12.21.3.26infoUpdated . . . 277
12.21.3.27isKeyboard . . . 277
12.21.3.28isMouse . . . 278
12.21.3.29isOpen . . . 279
12.21.3.30layout . . . 279
12.21.3.31layout . . . 280
12.21.3.32load . . . 280
12.21.3.33macroDelay . . . 281
12.21.3.34macroDelay . . . 281
12.21.3.35matches . . . 282
12.21.3.36modeChanged . . . 282
12.21.3.37model . . . 283
12.21.3.38modeRenamed . . . 283
12.21.3.39mouseAccel . . . 283
12.21.3.40mouseAccel . . . 284
12.21.3.41needsSave . . . 284
12.21.3.42newMode . . . 284
12.21.3.43newMode . . . 285
12.21.3.44newProfile . . . 286
12.21.3.45newProfile . . . 286
12.21.3.46profileAdded . . . 287
12.21.3.47profileChanged . . . 287
12.21.3.48profileRenamed . . . 288
12.21.3.49profiles . . . 288
12.21.3.50profiles . . . 289
12.21.3.51readNotify . . . 289

12.21.3.52 run . . . 293
12.21.3.53 save . . . 294
12.21.3.54 scrollSpeed . . . 295
12.21.3.55 scrollSpeed . . . 295
12.21.3.56 setCurrentMode . . . 296
12.21.3.57 setCurrentMode . . . 296
12.21.3.58 setCurrentMode . . . 297
12.21.3.59 setCurrentProfile . . . 298
12.21.3.60 updateLayout . . . 299
12.21.3.61 writeProfileHeader . . . 300
12.21.4 Friends And Related Function Documentation . . . 301
12.21.4.1 KbManager . . . 301
12.21.5 Field Documentation . . . 301
12.21.5.1 _currentMode . . . 301
12.21.5.2 _currentProfile . . . 301
12.21.5.3 _delay . . . 301
12.21.5.4 _dither . . . 301
12.21.5.5 _frameRate . . . 301
12.21.5.6 _hwProfile . . . 302
12.21.5.7 _layout . . . 302
12.21.5.8 _model . . . 302
12.21.5.9 _mouseAccel . . . 302
12.21.5.10 _needsSave . . . 302
12.21.5.11 _profiles . . . 302
12.21.5.12 _scrollSpeed . . . 302
12.21.5.13 cmd . . . 302
12.21.5.14 cmdpath . . . 302
12.21.5.15 devpath . . . 303
12.21.5.16 features . . . 303
12.21.5.17 firmware . . . 303
12.21.5.18 fwUpdPath . . . 303
12.21.5.19 hwLoading . . . 303
12.21.5.20 HWMODE_MAX . . . 303
12.21.5.21 hwModeCount . . . 303
12.21.5.22 iState . . . 303
12.21.5.23 lastAutoSave . . . 303
12.21.5.24 macroNumber . . . 304
12.21.5.25 macroPath . . . 304
12.21.5.26 monochrome . . . 304
12.21.5.27 notifyNumber . . . 304

12.21.5.28 notifyPath . . . 304
12.21.5.29 pollrate . . . 304
12.21.5.30 prefsPath . . . 304
12.21.5.31 prevMode . . . 304
12.21.5.32 prevProfile . . . 304
12.21.5.33 usbModel . . . 305
12.21.5.34 usbSerial . . . 305
12.22 KbAnim Class Reference . . . 305
12.22.1 Detailed Description . . . 308
12.22.2 Member Enumeration Documentation . . . 308
12.22.2.1 Mode . . . 308
12.22.3 Constructor & Destructor Documentation . . . 309
12.22.3.1 KbAnim . . . 309
12.22.3.2 KbAnim . . . 310
12.22.3.3 KbAnim . . . 311
12.22.4 Member Function Documentation . . . 311
12.22.4.1 blend . . . 311
12.22.4.2 catchUp . . . 313
12.22.4.3 commitParams . . . 314
12.22.4.4 effectiveParams . . . 315
12.22.4.5 guid . . . 315
12.22.4.6 hasParameter . . . 316
12.22.4.7 isActive . . . 316
12.22.4.8 isRunning . . . 316
12.22.4.9 keypress . . . 317
12.22.4.10 keys . . . 318
12.22.4.11 keys . . . 319
12.22.4.12 map . . . 319
12.22.4.13 map . . . 320
12.22.4.14 mode . . . 320
12.22.4.15 mode . . . 320
12.22.4.16 name . . . 321
12.22.4.17 name . . . 321
12.22.4.18 needsSave . . . 321
12.22.4.19 newId . . . 322
12.22.4.20 opacity . . . 322
12.22.4.21 opacity . . . 322
12.22.4.22 parameter . . . 323
12.22.4.23 parameter . . . 323
12.22.4.24 reInit . . . 324

12.22.4.25 resetParams . . . 324
12.22.4.26 save . . . 325
12.22.4.27 script . . . 326
12.22.4.28 scriptName . . . 326
12.22.4.29 stop . . . 327
12.22.4.30 trigger . . . 328
12.22.4.31 updateParams . . . 329
12.22.5 Field Documentation . . . 330
12.22.5.1 _guid . . . 330
12.22.5.2 _isActive . . . 330
12.22.5.3 _isActiveKp . . . 330
12.22.5.4 _keys . . . 330
12.22.5.5 _map . . . 330
12.22.5.6 _mode . . . 330
12.22.5.7 _name . . . 330
12.22.5.8 _needsSave . . . 331
12.22.5.9 _opacity . . . 331
12.22.5.10 _parameters . . . 331
12.22.5.11 _script . . . 331
12.22.5.12 _scriptGuid . . . 331
12.22.5.13 _scriptName . . . 331
12.22.5.14 _tempParameters . . . 331
12.22.5.15 kpRepeatMsec . . . 331
12.22.5.16 kpRepeatTime . . . 331
12.22.5.17 kpStopTime . . . 332
12.22.5.18 repeatKey . . . 332
12.22.5.19 repeatMsec . . . 332
12.22.5.20 repeatTime . . . 332
12.22.5.21 stopTime . . . 332
12.23 Ui::KbAnimWidget Class Reference . . . 332
12.23.1 Detailed Description . . . 334
12.23.2 Member Function Documentation . . . 334
12.23.2.1 retranslateUi . . . 334
12.23.2.2 setupUi . . . 335
12.23.3 Field Documentation . . . 338
12.23.3.1 aCopyLabel . . . 338
12.23.3.2 aMissingLabel . . . 338
12.23.3.3 aMissingPage . . . 338
12.23.3.4 aNameLabel . . . 338
12.23.3.5 animList . . . 338

12.23.3.6 animPage . . . 339
12.23.3.7 aVerLabel . . . 339
12.23.3.8 blendBox . . . 339
12.23.3.9 deleteButton . . . 339
12.23.3.10 gridLayout . . . 339
12.23.3.11 gridLayout_2 . . . 339
12.23.3.12 gridLayout_3 . . . 339
12.23.3.13 gridLayout_4 . . . 339
12.23.3.14 horizontalLayout . . . 339
12.23.3.15 horizontalSpacer . . . 340
12.23.3.16 horizontalSpacer_2 . . . 340
12.23.3.17 horizontalSpacer_3 . . . 340
12.23.3.18 horizontalSpacer_4 . . . 340
12.23.3.19 horizontalSpacer_5 . . . 340
12.23.3.20 keyButton . . . 340
12.23.3.21 label_5 . . . 340
12.23.3.22 label_6 . . . 340
12.23.3.23 label_7 . . . 340
12.23.3.24 nameBox . . . 341
12.23.3.25 noAnimLabel . . . 341
12.23.3.26 noSelPage . . . 341
12.23.3.27 opacityBox . . . 341
12.23.3.28 propertyButton . . . 341
12.23.3.29 selectionStack . . . 341
12.23.3.30 verticalLayout . . . 341
12.23.3.31 verticalSpacer . . . 341
12.23.3.32 verticalSpacer_2 . . . 341
12.23.3.33 verticalSpacer_3 . . . 342
12.24 KbAnimWidget Class Reference . . . 342
12.24.1 Detailed Description . . . 344
12.24.2 Constructor & Destructor Documentation . . . 344
12.24.2.1 KbAnimWidget . . . 344
12.24.2.2 ~KbAnimWidget . . . 345
12.24.3 Member Function Documentation . . . 345
12.24.3.1 addAnim . . . 345
12.24.3.2 animChanged . . . 346
12.24.3.3 clearSelection . . . 347
12.24.3.4 didUpdateSelection . . . 347
12.24.3.5 duplicateAnim . . . 348
12.24.3.6 on_animList_currentItemChanged . . . 349

12.24.3.7 on_animList_customContextMenuRequested . . . 349
12.24.3.8 on_animList_itemChanged . . . 350
12.24.3.9 on_blendBox_activated . . . 350
12.24.3.10 on_deleteButton_clicked . . . 351
12.24.3.11 on_keyButton_clicked . . . 352
12.24.3.12 on_nameBox_textEdited . . . 352
12.24.3.13 on_opacityBox_valueChanged . . . 353
12.24.3.14 on_propertyButton_clicked . . . 353
12.24.3.15 refreshList . . . 354
12.24.3.16 reorderAnims . . . 355
12.24.3.17 setCurrent . . . 356
12.24.3.18 setLight . . . 357
12.24.3.19 setSelectedKeys . . . 358
12.24.4 Field Documentation . . . 359
12.24.4.1 animations . . . 359
12.24.4.2 current . . . 359
12.24.4.3 light . . . 359
12.24.4.4 noReorder . . . 359
12.24.4.5 selectedKeys . . . 359
12.24.4.6 ui . . . 359
12.25 KbBind Class Reference . . . 360
12.25.1 Detailed Description . . . 363
12.25.2 Constructor & Destructor Documentation . . . 363
12.25.2.1 KbBind . . . 363
12.25.2.2 KbBind . . . 363
12.25.3 Member Function Documentation . . . 364
12.25.3.1 action . . . 364
12.25.3.2 bindAction . . . 365
12.25.3.3 defaultAction . . . 365
12.25.3.4 devParent . . . 366
12.25.3.5 didLoad . . . 366
12.25.3.6 friendlyActionName . . . 367
12.25.3.7 friendlyName . . . 367
12.25.3.8 getMacroNumber . . . 368
12.25.3.9 getMacroPath . . . 369
12.25.3.10 globalRemap . . . 369
12.25.3.11 handleNotificationChannel . . . 370
12.25.3.12 isISO . . . 371
12.25.3.13 isKeyboard . . . 371
12.25.3.14 isMouse . . . 371

12.25.3.15 keyEvent . . . 372
12.25.3.16 layoutChanged . . . 373
12.25.3.17 light . . . 374
12.25.3.18 load . . . 374
12.25.3.19 loadGlobalRemap . . . 375
12.25.3.20 map . . . 376
12.25.3.21 map . . . 377
12.25.3.22 modeParent . . . 377
12.25.3.23 needsSave . . . 378
12.25.3.24 noAction . . . 378
12.25.3.25 noAction . . . 378
12.25.3.26 perf . . . 379
12.25.3.27 resetAction . . . 380
12.25.3.28 resetAction . . . 380
12.25.3.29 save . . . 381
12.25.3.30 saveGlobalRemap . . . 382
12.25.3.31 setAction . . . 383
12.25.3.32 setAction . . . 384
12.25.3.33 setGlobalRemap . . . 384
12.25.3.34 setNeedsUpdate . . . 385
12.25.3.35 update . . . 385
12.25.3.36 updated . . . 387
12.25.3.37 winLock . . . 387
12.25.3.38 winLock . . . 388
12.25.4 Friends And Related Function Documentation . . . 388
12.25.4.1 KeyAction . . . 388
12.25.5 Field Documentation . . . 388
12.25.5.1 _bind . . . 388
12.25.5.2 _devParent . . . 388
12.25.5.3 _globalRemap . . . 388
12.25.5.4 _map . . . 388
12.25.5.5 _needsSave . . . 388
12.25.5.6 _needsUpdate . . . 388
12.25.5.7 _winLock . . . 389
12.25.5.8 globalRemapTime . . . 389
12.25.5.9 lastCmd . . . 389
12.25.5.10 lastGlobalRemapTime . . . 389
12.26 Ui::KbBindWidget Class Reference . . . 389
12.26.1 Detailed Description . . . 391
12.26.2 Member Function Documentation . . . 391

12.26.2.1 retranslateUi . . . 391
12.26.2.2 setupUi . . . 392
12.26.3 Field Documentation . . . 394
12.26.3.1 copyButton . . . 394
12.26.3.2 gridLayout . . . 394
12.26.3.3 gridLayout_2 . . . 394
12.26.3.4 horizontalLayout_2 . . . 394
12.26.3.5 horizontalSpacer . . . 394
12.26.3.6 horizontalSpacer_2 . . . 395
12.26.3.7 keyWidget . . . 395
12.26.3.8 label . . . 395
12.26.3.9 label_2 . . . 395
12.26.3.10 line . . . 395
12.26.3.11 line_2 . . . 395
12.26.3.12 rbWidget . . . 395
12.26.3.13 resetButton . . . 395
12.26.3.14 selectLabel . . . 395
12.26.3.15 verticalLayout . . . 396
12.26.3.16 verticalSpacer . . . 396
12.26.3.17 widget . . . 396
12.27 KbBindWidget Class Reference . . . 396
12.27.1 Detailed Description . . . 398
12.27.2 Constructor & Destructor Documentation . . . 399
12.27.2.1 KbBindWidget . . . 399
12.27.2.2 ~KbBindWidget . . . 399
12.27.3 Member Function Documentation . . . 400
12.27.3.1 newLayout . . . 400
12.27.3.2 newSelection . . . 401
12.27.3.3 on_copyButton_clicked . . . 402
12.27.3.4 on_resetButton_clicked . . . 403
12.27.3.5 setBind . . . 403
12.27.3.6 updateBind . . . 405
12.27.3.7 updateSelDisplay . . . 406
12.27.4 Field Documentation . . . 407
12.27.4.1 bind . . . 407
12.27.4.2 currentSelection . . . 407
12.27.4.3 profile . . . 407
12.27.4.4 ui . . . 407
12.28 KbFirmware Class Reference . . . 407
12.28.1 Detailed Description . . . 409

12.28.2 Member Enumeration Documentation . . . 410
12.28.2.1 anonymous enum . . . 410
12.28.3 Constructor & Destructor Documentation . . . 410
12.28.3.1 KbFirmware . . . 410
12.28.3.2 ~KbFirmware . . . 410
12.28.4 Member Function Documentation . . . 410
12.28.4.1 _checkUpdates . . . 410
12.28.4.2 _fileForBoard . . . 411
12.28.4.3 _latestForBoard . . . 412
12.28.4.4 checkUpdates . . . 413
12.28.4.5 dataForBoard . . . 413
12.28.4.6 downloaded . . . 414
12.28.4.7 downloadFinished . . . 414
12.28.4.8 hasDownloaded . . . 415
12.28.4.9 initManager . . . 415
12.28.4.10 processDownload . . . 416
12.28.4.11 versionForBoard . . . 417
12.28.5 Field Documentation . . . 418
12.28.5.1 fwTable . . . 418
12.28.5.2 fwTableHash . . . 418
12.28.5.3 hasGPG . . . 418
12.28.5.4 instance . . . 418
12.28.5.5 lastCheck . . . 418
12.28.5.6 lastFinished . . . 418
12.28.5.7 networkManager . . . 419
12.28.5.8 tableDownload . . . 419
12.29 KbLight Class Reference . . . 419
12.29.1 Detailed Description . . . 422
12.29.2 Member Typedef Documentation . . . 423
12.29.2.1 AnimList . . . 423
12.29.3 Constructor & Destructor Documentation . . . 423
12.29.3.1 KbLight . . . 423
12.29.3.2 KbLight . . . 423
12.29.3.3 ~KbLight . . . 424
12.29.4 Member Function Documentation . . . 424
12.29.4.1 addAnim . . . 424
12.29.4.2 animKeypress . . . 425
12.29.4.3 animList . . . 425
12.29.4.4 animList . . . 426
12.29.4.5 base . . . 426

12.29.4.6 close . . . 427
12.29.4.7 color . . . 428
12.29.4.8 color . . . 429
12.29.4.9 colorMap . . . 429
12.29.4.10 didLoad . . . 430
12.29.4.11 dimming . . . 430
12.29.4.12 dimming . . . 430
12.29.4.13 duplicateAnim . . . 431
12.29.4.14 findAnim . . . 432
12.29.4.15 findAnimIdx . . . 432
12.29.4.16 frameDisplayed . . . 433
12.29.4.17 frameUpdate . . . 433
12.29.4.18 isStarted . . . 435
12.29.4.19 load . . . 435
12.29.4.20 map . . . 437
12.29.4.21 map . . . 437
12.29.4.22 needsSave . . . 438
12.29.4.23 open . . . 439
12.29.4.24 previewAnim . . . 439
12.29.4.25 printRGB . . . 440
12.29.4.26 rebuildBaseMap . . . 441
12.29.4.27 resetIndicators . . . 442
12.29.4.28 restartAnimation . . . 442
12.29.4.29 save . . . 443
12.29.4.30 setIndicator . . . 444
12.29.4.31 shareDimming . . . 445
12.29.4.32 shareDimming . . . 445
12.29.4.33 stopPreview . . . 445
12.29.4.34 updated . . . 446
12.29.5 Field Documentation . . . 446
12.29.5.1 _animList . . . 446
12.29.5.2 _animMap . . . 447
12.29.5.3 _colorMap . . . 447
12.29.5.4 _dimming . . . 447
12.29.5.5 _indicatorList . . . 447
12.29.5.6 _indicatorMap . . . 447
12.29.5.7 _map . . . 447
12.29.5.8 _needsMapRefresh . . . 447
12.29.5.9 _needsSave . . . 447
12.29.5.10 _previewAnim . . . 447

12.29.5.11 _qColorMap . . . 448
12.29.5.12 _start . . . 448
12.29.5.13 lastFrameSignal . . . 448
12.29.5.14 MAX_DIM . . . 448
12.30 Ui::KbLightWidget Class Reference . . . 448
12.30.1 Detailed Description . . . 450
12.30.2 Member Function Documentation . . . 450
12.30.2.1 retranslateUi . . . 450
12.30.2.2 setupUi . . . 451
12.30.3 Field Documentation . . . 454
12.30.3.1 animButton . . . 454
12.30.3.2 animWidget . . . 454
12.30.3.3 bgButton . . . 454
12.30.3.4 brightnessBox . . . 454
12.30.3.5 gridLayout . . . 454
12.30.3.6 gridLayout_2 . . . 454
12.30.3.7 gridLayout_4 . . . 454
12.30.3.8 horizontalLayout . . . 455
12.30.3.9 horizontalLayout_2 . . . 455
12.30.3.10 horizontalLayout_3 . . . 455
12.30.3.11 horizontalSpacer_3 . . . 455
12.30.3.12 horizontalSpacer_4 . . . 455
12.30.3.13 horizontalSpacer_5 . . . 455
12.30.3.14 horizontalSpacer_6 . . . 455
12.30.3.15 keyWidget . . . 455
12.30.3.16 label . . . 456
12.30.3.17 label_2 . . . 456
12.30.3.18 label_3 . . . 456
12.30.3.19 line . . . 456
12.30.3.20 line_2 . . . 456
12.30.3.21 selLabel . . . 456
12.30.3.22 showAnimBox . . . 456
12.30.3.23 verticalLayout . . . 456
12.30.3.24 verticalSpacer_2 . . . 456
12.30.3.25 verticalSpacer_3 . . . 457
12.30.3.26 widget . . . 457
12.31 KbLightWidget Class Reference . . . 457
12.31.1 Detailed Description . . . 459
12.31.2 Constructor & Destructor Documentation . . . 459
12.31.2.1 KbLightWidget . . . 459

12.31.2.2 ~KbLightWidget . . . 460
12.31.3 Member Function Documentation . . . 460
12.31.3.1 changeAnim . . . 460
12.31.3.2 changeAnimKeys . . . 460
12.31.3.3 changeColor . . . 461
12.31.3.4 newSelection . . . 462
12.31.3.5 on_animButton_clicked . . . 463
12.31.3.6 on_bgButton_clicked . . . 464
12.31.3.7 on_brightnessBox_activated . . . 464
12.31.3.8 on_showAnimBox_clicked . . . 465
12.31.3.9 setLight . . . 465
12.31.3.10 setMonochrome . . . 467
12.31.3.11 toggleSidelight . . . 467
12.31.3.12 updateLight . . . 468
12.31.4 Field Documentation . . . 469
12.31.4.1 currentSelection . . . 469
12.31.4.2 light . . . 469
12.31.4.3 ui . . . 469
12.32 KbManager Class Reference . . . 470
12.32.1 Detailed Description . . . 472
12.32.2 Constructor & Destructor Documentation . . . 472
12.32.2.1 KbManager . . . 472
12.32.3 Member Function Documentation . . . 473
12.32.3.1 ckbDaemonVersion . . . 473
12.32.3.2 ckbDaemonVersionF . . . 473
12.32.3.3 ckbGuiVersion . . . 474
12.32.3.4 ckbGuiVersionF . . . 474
12.32.3.5 devices . . . 475
12.32.3.6 eventTimer . . . 475
12.32.3.7 fps . . . 475
12.32.3.8 init . . . 476
12.32.3.9 kbConnected . . . 477
12.32.3.10 kbDisconnected . . . 477
12.32.3.11 kbManager . . . 477
12.32.3.12 parseVersionString . . . 478
12.32.3.13 scanKeyboards . . . 478
12.32.3.14 scanTimer . . . 480
12.32.3.15 stop . . . 480
12.32.3.16 versionUpdated . . . 481
12.32.4 Field Documentation . . . 481

12.32.4.1 _daemonVersion . . . 481
12.32.4.2 _devices . . . 481
12.32.4.3 _eventTimer . . . 481
12.32.4.4 _guiVersion . . . 482
12.32.4.5 _kbManager . . . 482
12.32.4.6 _scanTimer . . . 482
12.33 KbMode Class Reference . . . 482
12.33.1 Detailed Description . . . 485
12.33.2 Constructor & Destructor Documentation . . . 485
12.33.2.1 KbMode . . . 485
12.33.2.2 KbMode . . . 486
12.33.2.3 KbMode . . . 486
12.33.2.4 ∼KbMode . . . 487
12.33.3 Member Function Documentation . . . 487
12.33.3.1 bind . . . 487
12.33.3.2 doUpdate . . . 488
12.33.3.3 id . . . 488
12.33.3.4 id . . . 488
12.33.3.5 keyMap . . . 489
12.33.3.6 light . . . 490
12.33.3.7 name . . . 490
12.33.3.8 name . . . 490
12.33.3.9 needsSave . . . 491
12.33.3.10 newId . . . 491
12.33.3.11 perf . . . 492
12.33.3.12 save . . . 493
12.33.3.13 setNeedsSave . . . 493
12.33.3.14 setNeedsUpdate . . . 494
12.33.3.15 updated . . . 494
12.33.4 Field Documentation . . . 495
12.33.4.1 _bind . . . 495
12.33.4.2 _id . . . 495
12.33.4.3 _light . . . 495
12.33.4.4 _name . . . 495
12.33.4.5 _needsSave . . . 495
12.33.4.6 _perf . . . 495
12.34 KbPerf Class Reference . . . 496
12.34.1 Detailed Description . . . 499
12.34.2 Member Enumeration Documentation . . . 499
12.34.2.1 height . . . 499

12.34.2.2 i_hw . . . 500
12.34.2.3 indicator . . . 500
12.34.3 Constructor & Destructor Documentation . . . 500
12.34.3.1 KbPerf . . . 500
12.34.3.2 KbPerf . . . 501
12.34.4 Member Function Documentation . . . 502
12.34.4.1 _curDpi . . . 502
12.34.4.2 angleSnap . . . 502
12.34.4.3 angleSnap . . . 503
12.34.4.4 applyIndicators . . . 503
12.34.4.5 bind . . . 504
12.34.4.6 curDpi . . . 505
12.34.4.7 curDpi . . . 505
12.34.4.8 curDpi . . . 506
12.34.4.9 curDpiIdx . . . 507
12.34.4.10 curDpiIdx . . . 507
12.34.4.11 didLoad . . . 507
12.34.4.12 dpi . . . 508
12.34.4.13 dpi . . . 508
12.34.4.14 dpi . . . 509
12.34.4.15 dpiColor . . . 509
12.34.4.16 dpiColor . . . 510
12.34.4.17 dpiDown . . . 510
12.34.4.18 dpiEnabled . . . 511
12.34.4.19 dpiEnabled . . . 511
12.34.4.20 dpiIndicator . . . 511
12.34.4.21 dpiIndicator . . . 512
12.34.4.22 dpiUp . . . 512
12.34.4.23 getIndicator . . . 513
12.34.4.24 lOpacity . . . 513
12.34.4.25 lOpacity . . . 514
12.34.4.26 liftHeight . . . 514
12.34.4.27 liftHeight . . . 514
12.34.4.28 light . . . 514
12.34.4.29 lightIndicator . . . 515
12.34.4.30 load . . . 516
12.34.4.31 modeParent . . . 518
12.34.4.32 needsSave . . . 518
12.34.4.33 operator= . . . 518
12.34.4.34 popDpi . . . 519

12.34.4.35 pushDpi . . . 520
12.34.4.36 pushDpi . . . 520
12.34.4.37 pushSniper . . . 521
12.34.4.38 save . . . 522
12.34.4.39 setIndicator . . . 523
12.34.4.40 setNeedsUpdate . . . 523
12.34.4.41 settingsUpdated . . . 524
12.34.4.42 sniperDpi . . . 524
12.34.4.43 sniperDpi . . . 525
12.34.4.44 sniperDpi . . . 525
12.34.4.45 update . . . 526
12.34.5 Field Documentation . . . 527
12.34.5.1 _angleSnap . . . 527
12.34.5.2 _dpiIndicator . . . 527
12.34.5.3 _iOpacity . . . 527
12.34.5.4 _liftHeight . . . 527
12.34.5.5 _needsSave . . . 527
12.34.5.6 _needsUpdate . . . 528
12.34.5.7 DPI_COUNT . . . 528
12.34.5.8 DPI_MAX . . . 528
12.34.5.9 DPI_MIN . . . 528
12.34.5.10 dpiClr . . . 528
12.34.5.11 dpiCurIdx . . . 528
12.34.5.12 dpiCurX . . . 528
12.34.5.13 dpiCurY . . . 528
12.34.5.14 dpiLastIdx . . . 528
12.34.5.15 dpiOn . . . 529
12.34.5.16 dpiX . . . 529
12.34.5.17 dpiY . . . 529
12.34.5.18 HW_I_COUNT . . . 529
12.34.5.19 hwlType . . . 529
12.34.5.20 I_COUNT . . . 529
12.34.5.21 iColor . . . 529
12.34.5.22 iEnable . . . 529
12.34.5.23 light100Color . . . 529
12.34.5.24 muteNAColor . . . 530
12.34.5.25 OTHER . . . 530
12.34.5.26 pushedDpis . . . 530
12.34.5.27 runningPushIdx . . . 530
12.34.5.28 SNIPER . . . 530

12.35 KbProfile Class Reference . . . 530
12.35.1 Detailed Description . . . 533
12.35.2 Member Typedef Documentation . . . 533
12.35.2.1 ModeList . . . 533
12.35.3 Constructor & Destructor Documentation . . . 533
12.35.3.1 KbProfile . . . 533
12.35.3.2 KbProfile . . . 534
12.35.3.3 KbProfile . . . 534
12.35.4 Member Function Documentation . . . 535
12.35.4.1 append . . . 535
12.35.4.2 currentMode . . . 535
12.35.4.3 currentMode . . . 536
12.35.4.4 find . . . 536
12.35.4.5 id . . . 537
12.35.4.6 id . . . 537
12.35.4.7 indexOf . . . 538
12.35.4.8 insert . . . 538
12.35.4.9 keyMap . . . 539
12.35.4.10 keyMap . . . 539
12.35.4.11 modeCount . . . 540
12.35.4.12 modes . . . 540
12.35.4.13 modes . . . 541
12.35.4.14 move . . . 541
12.35.4.15 name . . . 542
12.35.4.16 name . . . 542
12.35.4.17 needsSave . . . 543
12.35.4.18 newId . . . 543
12.35.4.19 removeAll . . . 544
12.35.4.20 save . . . 545
12.35.4.21 setNeedsSave . . . 546
12.35.4.22 setNeedsUpdate . . . 546
12.35.5 Field Documentation . . . 547
12.35.5.1 _currentMode . . . 547
12.35.5.2 _id . . . 547
12.35.5.3 _keyMap . . . 547
12.35.5.4 _modes . . . 547
12.35.5.5 _name . . . 547
12.35.5.6 _needsSave . . . 547
12.36 KbProfileDialog Class Reference . . . 548
12.36.1 Detailed Description . . . 549

12.36.2 Constructor & Destructor Documentation . . . 550
12.36.2.1 KbProfileDialog . . . 550
12.36.2.2 ~KbProfileDialog . . . 550
12.36.3 Member Function Documentation . . . 550
12.36.3.1 addNewProfileItem . . . 550
12.36.3.2 on_profileList_currentItemChanged . . . 551
12.36.3.3 on_profileList_customContextMenuRequested . . . 551
12.36.3.4 on_profileList_itemChanged . . . 553
12.36.3.5 on_profileList_itemClicked . . . 554
12.36.3.6 profileList_reordered . . . 555
12.36.3.7 repopulate . . . 555
12.36.4 Field Documentation . . . 556
12.36.4.1 device . . . 556
12.36.4.2 GUID . . . 557
12.36.4.3 NEW_FLAG . . . 557
12.36.4.4 ui . . . 557
12.37 Ui::KbProfileDialog Class Reference . . . 557
12.37.1 Detailed Description . . . 559
12.37.2 Member Function Documentation . . . 559
12.37.2.1 retranslateUi . . . 559
12.37.2.2 setupUi . . . 560
12.37.3 Field Documentation . . . 561
12.37.3.1 buttonBox . . . 561
12.37.3.2 gridLayout . . . 561
12.37.3.3 horizontalSpacer . . . 561
12.37.3.4 horizontalSpacer_2 . . . 561
12.37.3.5 profileList . . . 561
12.38 KbWidget Class Reference . . . 562
12.38.1 Detailed Description . . . 564
12.38.2 Constructor & Destructor Documentation . . . 564
12.38.2.1 KbWidget . . . 564
12.38.2.2 ~KbWidget . . . 566
12.38.3 Member Function Documentation . . . 566
12.38.3.1 addNewModeItem . . . 566
12.38.3.2 devUpdate . . . 567
12.38.3.3 modeChanged . . . 567
12.38.3.4 modeIcon . . . 569
12.38.3.5 modesList_reordered . . . 570
12.38.3.6 modeUpdate . . . 571
12.38.3.7 name . . . 571

12.38.3.8 on_fwUpdButton_clicked . . . 572
12.38.3.9 on_hwSaveButton_clicked . . . 573
12.38.3.10 on_modesList_currentItemChanged . . . 574
12.38.3.11 on_modesList_customContextMenuRequested . . . 575
12.38.3.12 on_modesList_itemChanged . . . 577
12.38.3.13 on_modesList_itemClicked . . . 577
12.38.3.14 on_profileBox_activated . . . 578
12.38.3.15 on_tabWidget_currentChanged . . . 578
12.38.3.16 profileChanged . . . 579
12.38.3.17 showFirstTab . . . 580
12.38.3.18 showFwUpdate . . . 580
12.38.3.19 showLastTab . . . 581
12.38.3.20 updateFwButton . . . 581
12.38.3.21 updateProfileList . . . 582
12.38.4 Field Documentation . . . 583
12.38.4.1 currentMode . . . 583
12.38.4.2 device . . . 583
12.38.4.3 GUID . . . 584
12.38.4.4 hasShownNewFW . . . 584
12.38.4.5 lastAutoSave . . . 584
12.38.4.6 NEW_FLAG . . . 584
12.38.4.7 ui . . . 584
12.39 Ui::KbWidget Class Reference . . . 584
12.39.1 Detailed Description . . . 586
12.39.2 Member Function Documentation . . . 586
12.39.2.1 retranslateUi . . . 586
12.39.2.2 setupUi . . . 587
12.39.3 Field Documentation . . . 590
12.39.3.1 bindTab . . . 590
12.39.3.2 bindWidget . . . 590
12.39.3.3 devTab . . . 590
12.39.3.4 fwLabel . . . 590
12.39.3.5 fwUpdButton . . . 591
12.39.3.6 fwUpdLabel . . . 591
12.39.3.7 fwUpdLayout . . . 591
12.39.3.8 gridLayout . . . 591
12.39.3.9 gridLayout_2 . . . 591
12.39.3.10 gridLayout_3 . . . 591
12.39.3.11 gridLayout_4 . . . 591
12.39.3.12 gridLayout_5 . . . 591

12.39.3.13 gridLayout_7 . . . 591
12.39.3.14 horizontalSpacer_2 . . . 592
12.39.3.15 horizontalSpacer_3 . . . 592
12.39.3.16 hwSaveButton . . . 592
12.39.3.17 kPerfTab . . . 592
12.39.3.18 kPerfWidget . . . 592
12.39.3.19 label_3 . . . 592
12.39.3.20 label_4 . . . 592
12.39.3.21 label_9 . . . 592
12.39.3.22 lightTab . . . 592
12.39.3.23 lightWidget . . . 593
12.39.3.24 modesList . . . 593
12.39.3.25 mPerfTab . . . 593
12.39.3.26 mPerfWidget . . . 593
12.39.3.27 pollLabel . . . 593
12.39.3.28 pollLabel2 . . . 593
12.39.3.29 profileBox . . . 593
12.39.3.30 serialLabel . . . 593
12.39.3.31 tabWidget . . . 593
12.39.3.32 verticalSpacer . . . 594
12.40 Key Struct Reference . . . 594
12.40.1 Detailed Description . . . 595
12.40.2 Member Function Documentation . . . 595
12.40.2.1 friendlyName . . . 595
12.40.2.2 operator bool . . . 595
12.40.2.3 operator! . . . 596
12.40.2.4 storageName . . . 596
12.40.3 Field Documentation . . . 596
12.40.3.1 _friendlyName . . . 596
12.40.3.2 _storageName . . . 596
12.40.3.3 hasLed . . . 596
12.40.3.4 hasScan . . . 596
12.40.3.5 height . . . 597
12.40.3.6 name . . . 597
12.40.3.7 width . . . 597
12.40.3.8 x . . . 597
12.40.3.9 y . . . 597
12.41 KeyAction Class Reference . . . 597
12.41.1 Detailed Description . . . 601
12.41.2 Member Enumeration Documentation . . . 601

12.41.2.1 Type . . . 601
12.41.3 Constructor & Destructor Documentation . . . 602
12.41.3.1 KeyAction . . . 602
12.41.3.2 KeyAction . . . 602
12.41.3.3 ~KeyAction . . . 602
12.41.3.4 KeyAction . . . 602
12.41.4 Member Function Documentation . . . 602
12.41.4.1 adjustDisplay . . . 602
12.41.4.2 animAction . . . 603
12.41.4.3 animInfo . . . 604
12.41.4.4 defaultAction . . . 604
12.41.4.5 dpiAction . . . 605
12.41.4.6 dpiInfo . . . 605
12.41.4.7 driverName . . . 606
12.41.4.8 friendlyName . . . 607
12.41.4.9 isAnim . . . 608
12.41.4.10 isDPI . . . 608
12.41.4.11 isMacro . . . 609
12.41.4.12 isMedia . . . 609
12.41.4.13 isMouse . . . 609
12.41.4.14 isNormal . . . 610
12.41.4.15 isProgram . . . 611
12.41.4.16 isSpecial . . . 611
12.41.4.17 isUnbound . . . 612
12.41.4.18 isValidMacro . . . 612
12.41.4.19 keyEvent . . . 613
12.41.4.20 keyRelease . . . 616
12.41.4.21 lightAction . . . 616
12.41.4.22 lockAction . . . 617
12.41.4.23 macroAction . . . 617
12.41.4.24 macroContent . . . 618
12.41.4.25 macroDisplay . . . 618
12.41.4.26 macroFullLine . . . 619
12.41.4.27 macroLine . . . 620
12.41.4.28 modeAction . . . 621
12.41.4.29 noAction . . . 621
12.41.4.30 operator QString . . . 621
12.41.4.31 operator= . . . 621
12.41.4.32 programAction . . . 622
12.41.4.33 programInfo . . . 622

12.41.4.34specialInfo . . . 623
12.41.4.35type . . . 623
12.41.4.36value . . . 624
12.41.5 Field Documentation . . . 624
12.41.5.1 _value . . . 624
12.41.5.2 DPI_CUSTOM . . . 624
12.41.5.3 DPI_DOWN . . . 624
12.41.5.4 DPI_SNIPER . . . 625
12.41.5.5 DPI_UP . . . 625
12.41.5.6 LIGHT_DOWN . . . 625
12.41.5.7 LIGHT_DOWN_WRAP . . . 625
12.41.5.8 LIGHT_UP . . . 625
12.41.5.9 LIGHT_UP_WRAP . . . 625
12.41.5.10LOCK_OFF . . . 625
12.41.5.11LOCK_ON . . . 625
12.41.5.12LOCK_TOGGLE . . . 625
12.41.5.13MODE_NEXT . . . 626
12.41.5.14MODE_NEXT_WRAP . . . 626
12.41.5.15MODE_PREV . . . 626
12.41.5.16MODE_PREV_WRAP . . . 626
12.41.5.17preProgram . . . 626
12.41.5.18PROGRAM_PR_INDEF . . . 626
12.41.5.19PROGRAM_PR_KPSTOP . . . 626
12.41.5.20PROGRAM_PR_KRSTOP . . . 626
12.41.5.21PROGRAM_PR_MULTI . . . 626
12.41.5.22PROGRAM_RE_INDEF . . . 627
12.41.5.23PROGRAM_RE_KPSTOP . . . 627
12.41.5.24PROGRAM_RE_MULTI . . . 627
12.41.5.25relProgram . . . 627
12.41.5.26sniperValue . . . 627
12.42KeyMap Class Reference . . . 627
12.42.1 Detailed Description . . . 630
12.42.2 Member Enumeration Documentation . . . 630
12.42.2.1 Layout . . . 630
12.42.2.2 Model . . . 630
12.42.3 Constructor & Destructor Documentation . . . 631
12.42.3.1 KeyMap . . . 631
12.42.3.2 KeyMap . . . 631
12.42.4 Member Function Documentation . . . 632
12.42.4.1 byPosition . . . 632

12.42.4.2 contains . . . 632
12.42.4.3 count . . . 633
12.42.4.4 friendlyName . . . 633
12.42.4.5 fromName . . . 635
12.42.4.6 fromStorage . . . 635
12.42.4.7 getLayout . . . 636
12.42.4.8 getLayout . . . 637
12.42.4.9 getModel . . . 637
12.42.4.10 getModel . . . 638
12.42.4.11 height . . . 638
12.42.4.12 isISO . . . 638
12.42.4.13 isISO . . . 639
12.42.4.14 isKeyboard . . . 639
12.42.4.15 isKeyboard . . . 640
12.42.4.16 isMouse . . . 641
12.42.4.17 isMouse . . . 641
12.42.4.18 key . . . 642
12.42.4.19 keys . . . 642
12.42.4.20 layout . . . 643
12.42.4.21 layoutNames . . . 643
12.42.4.22 locale . . . 644
12.42.4.23 map . . . 645
12.42.4.24 model . . . 645
12.42.4.25 modelHeight . . . 646
12.42.4.26 modelWidth . . . 646
12.42.4.27 name . . . 646
12.42.4.28 operator const QHash< QString, Key > & . . . 647
12.42.4.29 operator[] . . . 647
12.42.4.30 positions . . . 647
12.42.4.31 strLayout . . . 648
12.42.4.32 strModel . . . 648
12.42.4.33 toStorage . . . 649
12.42.4.34 width . . . 649
12.42.5 Field Documentation . . . 650
12.42.5.1 _keys . . . 650
12.42.5.2 keyHeight . . . 650
12.42.5.3 keyLayout . . . 650
12.42.5.4 keyModel . . . 650
12.42.5.5 keyWidth . . . 650
12.43 KeyWidget Class Reference . . . 650

12.43.1 Detailed Description . . . 653
12.43.2 Member Typedef Documentation . . . 653
12.43.2.1 BindMap . . . 653
12.43.3 Member Enumeration Documentation . . . 654
12.43.3.1 anonymous enum . . . 654
12.43.4 Constructor & Destructor Documentation . . . 654
12.43.4.1 KeyWidget . . . 654
12.43.5 Member Function Documentation . . . 654
12.43.5.1 bindMap . . . 654
12.43.5.2 bindMap . . . 655
12.43.5.3 clearAnimation . . . 655
12.43.5.4 clearSelection . . . 655
12.43.5.5 colorMap . . . 656
12.43.5.6 colorMap . . . 656
12.43.5.7 displayColorMap . . . 656
12.43.5.8 drawInfo . . . 657
12.43.5.9 map . . . 657
12.43.5.10 map . . . 658
12.43.5.11 monochrome . . . 658
12.43.5.12 monochrome . . . 659
12.43.5.13 mouseMoveEvent . . . 659
12.43.5.14 mousePressEvent . . . 660
12.43.5.15 mouseReleaseEvent . . . 661
12.43.5.16 paintEvent . . . 662
12.43.5.17 rgbMode . . . 667
12.43.5.18 rgbMode . . . 668
12.43.5.19 selectAll . . . 668
12.43.5.20 selectionChanged . . . 669
12.43.5.21 setAnimation . . . 669
12.43.5.22 setAnimationToSelection . . . 670
12.43.5.23 setSelection . . . 670
12.43.5.24 sidelightToggled . . . 671
12.43.6 Field Documentation . . . 671
12.43.6.1 _bindMap . . . 671
12.43.6.2 _colorMap . . . 672
12.43.6.3 _displayColorMap . . . 672
12.43.6.4 _indicators . . . 672
12.43.6.5 _monochrome . . . 672
12.43.6.6 _rgbMode . . . 672
12.43.6.7 animation . . . 672

12.43.6.8 keyMap . . . 672
12.43.6.9 mouseCurrentX . . . 672
12.43.6.10 mouseCurrentY . . . 672
12.43.6.11 mouseDownMode . . . 673
12.43.6.12 mouseDownX . . . 673
12.43.6.13 mouseDownY . . . 673
12.43.6.14 newSelection . . . 673
12.43.6.15 selection . . . 673
12.44 Ui::KPerfWidget Class Reference . . . 673
12.44.1 Detailed Description . . . 677
12.44.2 Member Function Documentation . . . 677
12.44.2.1 retranslateUi . . . 677
12.44.2.2 setupUi . . . 678
12.44.3 Field Documentation . . . 685
12.44.3.1 capsBox . . . 685
12.44.3.2 capsColorOff . . . 685
12.44.3.3 capsColorOn . . . 685
12.44.3.4 copyButton . . . 685
12.44.3.5 gridLayout . . . 685
12.44.3.6 horizontalLayout . . . 685
12.44.3.7 horizontalLayout_2 . . . 685
12.44.3.8 horizontalSpacer . . . 686
12.44.3.9 horizontalSpacer_2 . . . 686
12.44.3.10 horizontalSpacer_3 . . . 686
12.44.3.11 horizontalSpacer_4 . . . 686
12.44.3.12 horizontalSpacer_5 . . . 686
12.44.3.13 horizontalSpacer_6 . . . 686
12.44.3.14 horizontalSpacer_7 . . . 686
12.44.3.15 horizontalSpacer_8 . . . 686
12.44.3.16 intensityBox . . . 686
12.44.3.17 k95Label1 . . . 687
12.44.3.18 k95Label2 . . . 687
12.44.3.19 k95Label3 . . . 687
12.44.3.20 k95Label4 . . . 687
12.44.3.21 k95Label5 . . . 687
12.44.3.22 k95Label6 . . . 687
12.44.3.23 k95Line . . . 687
12.44.3.24 k95Spacer . . . 687
12.44.3.25 label . . . 687
12.44.3.26 label_10 . . . 688

12.44.3.27 label_11 . . . 688
12.44.3.28 label_12 . . . 688
12.44.3.29 label_14 . . . 688
12.44.3.30 label_15 . . . 688
12.44.3.31 label_16 . . . 688
12.44.3.32 label_17 . . . 688
12.44.3.33 label_18 . . . 688
12.44.3.34 label_19 . . . 688
12.44.3.35 label_2 . . . 689
12.44.3.36 label_20 . . . 689
12.44.3.37 label_21 . . . 689
12.44.3.38 label_22 . . . 689
12.44.3.39 label_23 . . . 689
12.44.3.40 label_24 . . . 689
12.44.3.41 label_3 . . . 689
12.44.3.42 label_4 . . . 689
12.44.3.43 label_5 . . . 689
12.44.3.44 label_6 . . . 690
12.44.3.45 label_7 . . . 690
12.44.3.46 label_8 . . . 690
12.44.3.47 lightBox . . . 690
12.44.3.48 lightColor1 . . . 690
12.44.3.49 lightColor2 . . . 690
12.44.3.50 lightColor3 . . . 690
12.44.3.51 line . . . 690
12.44.3.52 line_2 . . . 690
12.44.3.53 line_3 . . . 691
12.44.3.54 lockBox . . . 691
12.44.3.55 lockColorOff . . . 691
12.44.3.56 lockColorOn . . . 691
12.44.3.57 macroBox . . . 691
12.44.3.58 macroColorOff . . . 691
12.44.3.59 macroColorOn . . . 691
12.44.3.60 modeBox . . . 691
12.44.3.61 modeColorOff . . . 691
12.44.3.62 modeColorOn . . . 692
12.44.3.63 muteBox . . . 692
12.44.3.64 muteColorNA . . . 692
12.44.3.65 muteColorOff . . . 692
12.44.3.66 muteColorOn . . . 692

12.44.3.67 numBox . . . 692
12.44.3.68 numColorOff . . . 692
12.44.3.69 numColorOn . . . 692
12.44.3.70 scrollBox . . . 692
12.44.3.71 scrollColorOff . . . 693
12.44.3.72 scrollColorOn . . . 693
12.44.3.73 verticalSpacer . . . 693
12.44.3.74 verticalSpacer_2 . . . 693
12.44.3.75 verticalSpacer_3 . . . 693
12.44.3.76 verticalSpacer_4 . . . 693
12.45 KPerfWidget Class Reference . . . 693
12.45.1 Detailed Description . . . 696
12.45.2 Data Structure Documentation . . . 696
12.45.2.1 struct KPerfWidget::IndicatorUi . . . 696
12.45.3 Member Typedef Documentation . . . 697
12.45.3.1 i_hw . . . 698
12.45.3.2 indicator . . . 698
12.45.4 Member Enumeration Documentation . . . 698
12.45.4.1 HwMode . . . 698
12.45.5 Constructor & Destructor Documentation . . . 698
12.45.5.1 KPerfWidget . . . 698
12.45.5.2 ~KPerfWidget . . . 700
12.45.6 Member Function Documentation . . . 700
12.45.6.1 mode2Raw . . . 700
12.45.6.2 on_copyButton_clicked . . . 701
12.45.6.3 on_intensityBox_valueChanged . . . 701
12.45.6.4 raw2Mode . . . 702
12.45.6.5 setPerf . . . 702
12.45.6.6 uiUpdated . . . 704
12.45.7 Field Documentation . . . 705
12.45.7.1 HW_I_COUNT . . . 705
12.45.7.2 I_COUNT . . . 705
12.45.7.3 indicators . . . 706
12.45.7.4 k95Widgets . . . 706
12.45.7.5 perf . . . 706
12.45.7.6 profile . . . 706
12.45.7.7 ui . . . 706
12.45.7.8 updateMapper . . . 706
12.46 Ui::LayoutDialog Class Reference . . . 706
12.46.1 Detailed Description . . . 708

12.46.2 Member Function Documentation . . . 708
12.46.2.1 retranslateUi . . . 708
12.46.2.2 setupUi . . . 709
12.46.3 Field Documentation . . . 710
12.46.3.1 buttonBox . . . 710
12.46.3.2 comboBox . . . 710
12.46.3.3 gridLayout . . . 710
12.46.3.4 horizontalSpacer . . . 710
12.46.3.5 horizontalSpacer_2 . . . 710
12.46.3.6 label . . . 711
12.46.3.7 label_2 . . . 711
12.46.3.8 verticalSpacer . . . 711
12.46.3.9 verticalSpacer_2 . . . 711
12.46.3.10 verticalSpacer_3 . . . 711
12.46.3.11 verticalSpacer_4 . . . 711
12.47 LayoutDialog Class Reference . . . 711
12.47.1 Detailed Description . . . 713
12.47.2 Constructor & Destructor Documentation . . . 713
12.47.2.1 LayoutDialog . . . 713
12.47.2.2 ~LayoutDialog . . . 713
12.47.3 Member Function Documentation . . . 714
12.47.3.1 selected . . . 714
12.47.4 Field Documentation . . . 714
12.47.4.1 ui . . . 714
12.48 MacroReader Class Reference . . . 714
12.48.1 Detailed Description . . . 716
12.48.2 Constructor & Destructor Documentation . . . 717
12.48.2.1 MacroReader . . . 717
12.48.2.2 MacroReader . . . 717
12.48.2.3 ~MacroReader . . . 717
12.48.3 Member Function Documentation . . . 717
12.48.3.1 startWorkInAThread . . . 717
12.48.4 Field Documentation . . . 718
12.48.4.1 macroReaderThread . . . 718
12.49 MacroReaderThread Class Reference . . . 718
12.49.1 Detailed Description . . . 720
12.49.2 Constructor & Destructor Documentation . . . 720
12.49.2.1 MacroReaderThread . . . 720
12.49.3 Member Function Documentation . . . 721
12.49.3.1 readMacro . . . 721

12.49.3.2 run . . . 721
12.49.4 Field Documentation . . . 721
12.49.4.1 macroBox . . . 722
12.49.4.2 macroNumber . . . 722
12.49.4.3 macroPath . . . 722
12.49.4.4 macroText . . . 722
12.50 Ui::MainWindow Class Reference . . . 722
12.50.1 Detailed Description . . . 724
12.50.2 Member Function Documentation . . . 724
12.50.2.1 retranslateUi . . . 724
12.50.2.2 setupUi . . . 724
12.50.3 Field Documentation . . . 725
12.50.3.1 actionAbout . . . 725
12.50.3.2 actionExit . . . 725
12.50.3.3 centralWidget . . . 726
12.50.3.4 gridLayout . . . 726
12.50.3.5 tabWidget . . . 726
12.51 MainWindow Class Reference . . . 726
12.51.1 Detailed Description . . . 729
12.51.2 Constructor & Destructor Documentation . . . 729
12.51.2.1 MainWindow . . . 729
12.51.2.2 ~MainWindow . . . 730
12.51.3 Member Function Documentation . . . 731
12.51.3.1 addDevice . . . 731
12.51.3.2 checkFwUpdates . . . 732
12.51.3.3 cleanup . . . 732
12.51.3.4 closeEvent . . . 733
12.51.3.5 iconClicked . . . 734
12.51.3.6 quitApp . . . 734
12.51.3.7 removeDevice . . . 735
12.51.3.8 showFwUpdateNotification . . . 735
12.51.3.9 showWindow . . . 736
12.51.3.10 stateChange . . . 737
12.51.3.11 timerTick . . . 737
12.51.3.12 toggleTrayIcon . . . 738
12.51.3.13 updateVersion . . . 739
12.51.4 Field Documentation . . . 740
12.51.4.1 closeAction . . . 740
12.51.4.2 kbWidgets . . . 740
12.51.4.3 mainWindow . . . 740

12.51.4.4 restoreAction . . . 740
12.51.4.5 settingsWidget . . . 740
12.51.4.6 trayIcon . . . 740
12.51.4.7 trayIconMenu . . . 740
12.51.4.8 ui . . . 741
12.52 Ui::ModeSelectDialog Class Reference . . . 741
12.52.1 Detailed Description . . . 742
12.52.2 Member Function Documentation . . . 742
12.52.2.1 retranslateUi . . . 742
12.52.2.2 setupUi . . . 743
12.52.3 Field Documentation . . . 744
12.52.3.1 buttonBox . . . 744
12.52.3.2 gridLayout . . . 744
12.52.3.3 label . . . 744
12.52.3.4 modeList . . . 744
12.52.3.5 selAllButton . . . 744
12.52.3.6 selNoneButton . . . 745
12.53 ModeSelectDialog Class Reference . . . 745
12.53.1 Detailed Description . . . 746
12.53.2 Constructor & Destructor Documentation . . . 747
12.53.2.1 ModeSelectDialog . . . 747
12.53.2.2 ~ModeSelectDialog . . . 747
12.53.3 Member Function Documentation . . . 747
12.53.3.1 on_selAllButton_clicked . . . 747
12.53.3.2 on_selNoneButton_clicked . . . 748
12.53.3.3 selection . . . 748
12.53.4 Field Documentation . . . 748
12.53.4.1 _modeList . . . 748
12.53.4.2 ui . . . 748
12.54 Ui::MPerfWidget Class Reference . . . 749
12.54.1 Detailed Description . . . 751
12.54.2 Member Function Documentation . . . 752
12.54.2.1 retranslateUi . . . 752
12.54.2.2 setupUi . . . 753
12.54.3 Field Documentation . . . 760
12.54.3.1 aSnapBox . . . 760
12.54.3.2 copyButton . . . 760
12.54.3.3 eBox1 . . . 760
12.54.3.4 eBox2 . . . 761
12.54.3.5 eBox3 . . . 761

12.54.3.6 eBox4 . . . 761
12.54.3.7 eBox5 . . . 761
12.54.3.8 gridLayout . . . 761
12.54.3.9 horizontalLayout . . . 761
12.54.3.10 horizontalLayout_2 . . . 761
12.54.3.11 horizontalLayout_4 . . . 761
12.54.3.12 horizontalSpacer . . . 761
12.54.3.13 horizontalSpacer_2 . . . 762
12.54.3.14 horizontalSpacer_3 . . . 762
12.54.3.15 horizontalSpacer_4 . . . 762
12.54.3.16 horizontalSpacer_5 . . . 762
12.54.3.17 horizontalSpacer_6 . . . 762
12.54.3.18 horizontalSpacer_7 . . . 762
12.54.3.19 iButton0 . . . 762
12.54.3.20 iButton1 . . . 762
12.54.3.21 iButton2 . . . 762
12.54.3.22 iButton3 . . . 763
12.54.3.23 iButton4 . . . 763
12.54.3.24 iButton5 . . . 763
12.54.3.25 iButtonO . . . 763
12.54.3.26 indicBox . . . 763
12.54.3.27 label . . . 763
12.54.3.28 label_11 . . . 763
12.54.3.29 label_12 . . . 763
12.54.3.30 label_13 . . . 763
12.54.3.31 label_14 . . . 764
12.54.3.32 label_15 . . . 764
12.54.3.33 label_2 . . . 764
12.54.3.34 label_25 . . . 764
12.54.3.35 label_3 . . . 764
12.54.3.36 label_4 . . . 764
12.54.3.37 label_5 . . . 764
12.54.3.38 label_6 . . . 764
12.54.3.39 label_7 . . . 764
12.54.3.40 label_8 . . . 765
12.54.3.41 llHeightBox . . . 765
12.54.3.42 line . . . 765
12.54.3.43 line_2 . . . 765
12.54.3.44 line_3 . . . 765
12.54.3.45 spinBox . . . 765

12.54.3.46 verticalLayout . . . 765
12.54.3.47 verticalSpacer . . . 765
12.54.3.48 verticalSpacer_2 . . . 765
12.54.3.49 verticalSpacer_3 . . . 766
12.54.3.50 xBox0 . . . 766
12.54.3.51 xBox1 . . . 766
12.54.3.52 xBox2 . . . 766
12.54.3.53 xBox3 . . . 766
12.54.3.54 xBox4 . . . 766
12.54.3.55 xBox5 . . . 766
12.54.3.56 xSlider0 . . . 766
12.54.3.57 xSlider1 . . . 766
12.54.3.58 xSlider2 . . . 767
12.54.3.59 xSlider3 . . . 767
12.54.3.60 xSlider4 . . . 767
12.54.3.61 xSlider5 . . . 767
12.54.3.62 xyBox . . . 767
12.54.3.63 yBox0 . . . 767
12.54.3.64 yBox1 . . . 767
12.54.3.65 yBox2 . . . 767
12.54.3.66 yBox3 . . . 767
12.54.3.67 yBox4 . . . 768
12.54.3.68 yBox5 . . . 768
12.54.3.69 ySlider0 . . . 768
12.54.3.70 ySlider1 . . . 768
12.54.3.71 ySlider2 . . . 768
12.54.3.72 ySlider3 . . . 768
12.54.3.73 ySlider4 . . . 768
12.54.3.74 ySlider5 . . . 768
12.55 MPerfWidget Class Reference . . . 768
12.55.1 Detailed Description . . . 771
12.55.2 Data Structure Documentation . . . 771
12.55.2.1 struct MPerfWidget::DpiUi . . . 771
12.55.3 Constructor & Destructor Documentation . . . 772
12.55.3.1 MPerfWidget . . . 772
12.55.3.2 ~MPerfWidget . . . 774
12.55.4 Member Function Documentation . . . 774
12.55.4.1 boxXChanged . . . 774
12.55.4.2 boxYChanged . . . 775
12.55.4.3 colorChanged . . . 776

12.55.4.4 colorClicked . . . 777
12.55.4.5 enableChanged . . . 777
12.55.4.6 on_aSnapBox_clicked . . . 778
12.55.4.7 on_copyButton_clicked . . . 778
12.55.4.8 on_indicBox_clicked . . . 779
12.55.4.9 on_lHeightBox_activated . . . 779
12.55.4.10 on_spinBox_valueChanged . . . 780
12.55.4.11 on_xyBox_clicked . . . 780
12.55.4.12 setPerf . . . 781
12.55.4.13 sliderXMoved . . . 782
12.55.4.14 sliderYMoved . . . 783
12.55.5 Field Documentation . . . 784
12.55.5.1 _xyLink . . . 784
12.55.5.2 boxXMapper . . . 784
12.55.5.3 boxYMapper . . . 784
12.55.5.4 buttonMapper1 . . . 784
12.55.5.5 buttonMapper2 . . . 785
12.55.5.6 colorLink . . . 785
12.55.5.7 DPI_COUNT . . . 785
12.55.5.8 DPI_MAX . . . 785
12.55.5.9 DPI_MIN . . . 785
12.55.5.10 enableMapper . . . 785
12.55.5.11 isSetting . . . 785
12.55.5.12 perf . . . 785
12.55.5.13 profile . . . 785
12.55.5.14 sliderXMapper . . . 785
12.55.5.15 sliderYMapper . . . 786
12.55.5.16 stages . . . 786
12.55.5.17 ui . . . 786
12.56 GradientDialog::Preset Struct Reference . . . 786
12.56.1 Detailed Description . . . 787
12.56.2 Constructor & Destructor Documentation . . . 787
12.56.2.1 Preset . . . 787
12.56.2.2 Preset . . . 787
12.56.2.3 Preset . . . 787
12.56.3 Field Documentation . . . 787
12.56.3.1 builtIn . . . 787
12.56.3.2 gradient . . . 787
12.56.3.3 name . . . 788
12.57 QDialog Class Reference . . . 788

12.58 QIODevice Class Reference . . . 789
12.59 QIODevice_descriptor Struct Reference . . . 790
12.59.1 Detailed Description . . . 790
12.59.2 Constructor & Destructor Documentation . . . 790
12.59.2.1 QIODevice_descriptor . . . 790
12.59.3 Field Documentation . . . 790
12.59.3.1 pos . . . 790
12.60 QListWidget Class Reference . . . 791
12.61 QMainWindow Class Reference . . . 792
12.62 QObject Class Reference . . . 793
12.63 QPushButton Class Reference . . . 794
12.64 QThread Class Reference . . . 795
12.65 QuaAdler32 Class Reference . . . 796
12.65.1 Detailed Description . . . 797
12.65.2 Constructor & Destructor Documentation . . . 798
12.65.2.1 QuaAdler32 . . . 798
12.65.3 Member Function Documentation . . . 798
12.65.3.1 calculate . . . 798
12.65.3.2 reset . . . 798
12.65.3.3 update . . . 799
12.65.3.4 value . . . 799
12.65.4 Field Documentation . . . 799
12.65.4.1 checksum . . . 799
12.66 QuaChecksum32 Class Reference . . . 799
12.66.1 Detailed Description . . . 801
12.66.2 Member Function Documentation . . . 801
12.66.2.1 calculate . . . 801
12.66.2.2 reset . . . 801
12.66.2.3 update . . . 801
12.66.2.4 value . . . 801
12.67 QuaCrc32 Class Reference . . . 802
12.67.1 Detailed Description . . . 803
12.67.2 Constructor & Destructor Documentation . . . 804
12.67.2.1 QuaCrc32 . . . 804
12.67.3 Member Function Documentation . . . 804
12.67.3.1 calculate . . . 804
12.67.3.2 reset . . . 804
12.67.3.3 update . . . 805
12.67.3.4 value . . . 805
12.67.4 Field Documentation . . . 805

12.67.4.1 checksum . . . 805
12.68 QuaGzipFile Class Reference . . . 805
12.68.1 Detailed Description . . . 808
12.68.2 Constructor & Destructor Documentation . . . 808
12.68.2.1 QuaGzipFile . . . 808
12.68.2.2 QuaGzipFile . . . 808
12.68.2.3 QuaGzipFile . . . 809
12.68.2.4 ~QuaGzipFile . . . 809
12.68.2.5 QuaGzipFile . . . 809
12.68.3 Member Function Documentation . . . 809
12.68.3.1 close . . . 809
12.68.3.2 flush . . . 810
12.68.3.3 getFileName . . . 810
12.68.3.4 isSequential . . . 810
12.68.3.5 open . . . 810
12.68.3.6 open . . . 811
12.68.3.7 operator= . . . 811
12.68.3.8 readData . . . 811
12.68.3.9 setFileName . . . 811
12.68.3.10 writeData . . . 812
12.68.4 Field Documentation . . . 812
12.68.4.1 d . . . 812
12.69 QuaZIODevice Class Reference . . . 812
12.69.1 Detailed Description . . . 815
12.69.2 Constructor & Destructor Documentation . . . 815
12.69.2.1 QuaZIODevice . . . 815
12.69.2.2 ~QuaZIODevice . . . 815
12.69.3 Member Function Documentation . . . 815
12.69.3.1 close . . . 815
12.69.3.2 flush . . . 816
12.69.3.3 getIoDevice . . . 817
12.69.3.4 isSequential . . . 817
12.69.3.5 open . . . 817
12.69.3.6 readData . . . 818
12.69.3.7 writeData . . . 819
12.69.4 Field Documentation . . . 819
12.69.4.1 d . . . 819
12.70 QuaZip Class Reference . . . 820
12.70.1 Detailed Description . . . 822
12.70.2 Member Enumeration Documentation . . . 823

12.70.2.1 CaseSensitivity . . . 823
12.70.2.2 Constants . . . 823
12.70.2.3 Mode . . . 823
12.70.3 Constructor & Destructor Documentation . . . 824
12.70.3.1 QuaZip . . . 824
12.70.3.2 QuaZip . . . 824
12.70.3.3 QuaZip . . . 824
12.70.3.4 QuaZip . . . 824
12.70.3.5 ~QuaZip . . . 824
12.70.4 Member Function Documentation . . . 825
12.70.4.1 close . . . 825
12.70.4.2 convertCaseSensitivity . . . 826
12.70.4.3 getComment . . . 827
12.70.4.4 getCommentCodec . . . 827
12.70.4.5 getCurrentFileInfo . . . 828
12.70.4.6 getCurrentFileInfo . . . 829
12.70.4.7 getCurrentFileName . . . 830
12.70.4.8 getEntriesCount . . . 831
12.70.4.9 getFileInfoList . . . 832
12.70.4.10 getFileInfoList64 . . . 833
12.70.4.11 getFileNameCodec . . . 833
12.70.4.12 getFileNameList . . . 834
12.70.4.13 getIoDevice . . . 834
12.70.4.14 getMode . . . 834
12.70.4.15 getUnzFile . . . 835
12.70.4.16 getZipError . . . 836
12.70.4.17 getZipFile . . . 837
12.70.4.18 getZipName . . . 837
12.70.4.19 goToFirstFile . . . 838
12.70.4.20 goToNextFile . . . 839
12.70.4.21 hasCurrentFile . . . 840
12.70.4.22 isAutoClose . . . 840
12.70.4.23 isDataDescriptorWritingEnabled . . . 840
12.70.4.24 isOpen . . . 841
12.70.4.25 isZip64Enabled . . . 841
12.70.4.26 open . . . 842
12.70.4.27 operator= . . . 845
12.70.4.28 setAutoClose . . . 845
12.70.4.29 setComment . . . 846
12.70.4.30 setCommentCodec . . . 846

12.70.4.31 setCommentCodec . . . 846
12.70.4.32 setCurrentFile . . . 847
12.70.4.33 setDataDescriptorWritingEnabled . . . 848
12.70.4.34 setDefaultFileNameCodec . . . 849
12.70.4.35 setDefaultFileNameCodec . . . 850
12.70.4.36 setFileNameCodec . . . 850
12.70.4.37 setFileNameCodec . . . 850
12.70.4.38 setIoDevice . . . 850
12.70.4.39 setZip64Enabled . . . 851
12.70.4.40 setZipName . . . 851
12.70.5 Friends And Related Function Documentation . . . 852
12.70.5.1 QuaZipPrivate . . . 852
12.70.6 Field Documentation . . . 852
12.70.6.1 p . . . 852
12.71 QuaZipDir Class Reference . . . 852
12.71.1 Detailed Description . . . 855
12.71.2 Constructor & Destructor Documentation . . . 855
12.71.2.1 QuaZipDir . . . 855
12.71.2.2 QuaZipDir . . . 855
12.71.2.3 ~QuaZipDir . . . 856
12.71.3 Member Function Documentation . . . 856
12.71.3.1 caseSensitivity . . . 856
12.71.3.2 cd . . . 856
12.71.3.3 cdUp . . . 858
12.71.3.4 count . . . 858
12.71.3.5 dirName . . . 859
12.71.3.6 entryInfoList . . . 859
12.71.3.7 entryInfoList . . . 860
12.71.3.8 entryInfoList64 . . . 860
12.71.3.9 entryInfoList64 . . . 861
12.71.3.10 entryList . . . 861
12.71.3.11 entryList . . . 862
12.71.3.12 exists . . . 862
12.71.3.13 exists . . . 863
12.71.3.14 filePath . . . 864
12.71.3.15 filter . . . 865
12.71.3.16 isRoot . . . 865
12.71.3.17 nameFilters . . . 865
12.71.3.18 operator!= . . . 866
12.71.3.19 operator= . . . 866

12.71.3.20 operator== . . . 866
12.71.3.21 operator[] . . . 866
12.71.3.22 path . . . 867
12.71.3.23 relativeFilePath . . . 867
12.71.3.24 setCaseSensitivity . . . 867
12.71.3.25 setFilter . . . 868
12.71.3.26 setNameFilters . . . 868
12.71.3.27 setPath . . . 868
12.71.3.28 setSorting . . . 869
12.71.3.29 sorting . . . 869
12.71.4 Field Documentation . . . 869
12.71.4.1 d . . . 869
12.72 QuaZipFile Class Reference . . . 870
12.72.1 Detailed Description . . . 872
12.72.2 Sequential or random-access? . . . 873
12.72.3 Constructor & Destructor Documentation . . . 873
12.72.3.1 QuaZipFile . . . 873
12.72.3.2 QuaZipFile . . . 873
12.72.3.3 QuaZipFile . . . 873
12.72.3.4 QuaZipFile . . . 873
12.72.3.5 QuaZipFile . . . 874
12.72.3.6 QuaZipFile . . . 874
12.72.3.7 ~QuaZipFile . . . 875
12.72.4 Member Function Documentation . . . 875
12.72.4.1 atEnd . . . 875
12.72.4.2 bytesAvailable . . . 876
12.72.4.3 close . . . 876
12.72.4.4 csize . . . 877
12.72.4.5 getActualFileName . . . 878
12.72.4.6 getCaseSensitivity . . . 879
12.72.4.7 getFileInfo . . . 879
12.72.4.8 getFileInfo . . . 880
12.72.4.9 getFileName . . . 881
12.72.4.10 getZip . . . 881
12.72.4.11 getZipError . . . 881
12.72.4.12 getZipName . . . 882
12.72.4.13 isRaw . . . 882
12.72.4.14 isSequential . . . 883
12.72.4.15 open . . . 883
12.72.4.16 open . . . 884

12.72.4.17 open . . . 884
12.72.4.18 open . . . 885
12.72.4.19 operator= . . . 887
12.72.4.20 pos . . . 887
12.72.4.21 readData . . . 888
12.72.4.22 setFileName . . . 889
12.72.4.23 setZip . . . 889
12.72.4.24 setZipName . . . 890
12.72.4.25 size . . . 890
12.72.4.26 usize . . . 891
12.72.4.27 writeData . . . 892
12.72.5 Friends And Related Function Documentation . . . 892
12.72.5.1 QuaZipFilePrivate . . . 893
12.72.6 Field Documentation . . . 893
12.72.6.1 p . . . 893
12.73 QuaZipFileInfo Struct Reference . . . 893
12.73.1 Detailed Description . . . 894
12.73.2 Member Function Documentation . . . 894
12.73.2.1 getPermissions . . . 894
12.73.3 Field Documentation . . . 895
12.73.3.1 comment . . . 895
12.73.3.2 compressedSize . . . 895
12.73.3.3 crc . . . 895
12.73.3.4 dateTime . . . 895
12.73.3.5 diskNumberStart . . . 895
12.73.3.6 externalAttr . . . 895
12.73.3.7 extra . . . 895
12.73.3.8 flags . . . 896
12.73.3.9 internalAttr . . . 896
12.73.3.10 method . . . 896
12.73.3.11 name . . . 896
12.73.3.12 uncompressedSize . . . 896
12.73.3.13 versionCreated . . . 896
12.73.3.14 versionNeeded . . . 896
12.74 QuaZipFileInfo64 Struct Reference . . . 896
12.74.1 Detailed Description . . . 898
12.74.2 Member Function Documentation . . . 898
12.74.2.1 getNTFSaTime . . . 898
12.74.2.2 getNTFScTime . . . 899
12.74.2.3 getNTFSmTime . . . 899

12.74.2.4 getPermissions . . . 900
12.74.2.5 isEncrypted . . . 901
12.74.2.6 toQuaZipFileInfo . . . 901
12.74.3 Field Documentation . . . 902
12.74.3.1 comment . . . 902
12.74.3.2 compressedSize . . . 902
12.74.3.3 crc . . . 902
12.74.3.4 dateTime . . . 902
12.74.3.5 diskNumberStart . . . 902
12.74.3.6 externalAttr . . . 903
12.74.3.7 extra . . . 903
12.74.3.8 flags . . . 903
12.74.3.9 internalAttr . . . 903
12.74.3.10 method . . . 903
12.74.3.11 name . . . 903
12.74.3.12 uncompressedSize . . . 903
12.74.3.13 versionCreated . . . 903
12.74.3.14 versionNeeded . . . 903
12.75 QuaZipFilePrivate Class Reference . . . 904
12.75.1 Detailed Description . . . 905
12.75.2 Constructor & Destructor Documentation . . . 905
12.75.2.1 QuaZipFilePrivate . . . 905
12.75.2.2 QuaZipFilePrivate . . . 905
12.75.2.3 QuaZipFilePrivate . . . 905
12.75.2.4 QuaZipFilePrivate . . . 906
12.75.2.5 ~QuaZipFilePrivate . . . 906
12.75.3 Member Function Documentation . . . 906
12.75.3.1 resetZipError . . . 906
12.75.3.2 setZipError . . . 906
12.75.4 Friends And Related Function Documentation . . . 907
12.75.4.1 QuaZipFile . . . 907
12.75.5 Field Documentation . . . 907
12.75.5.1 caseSensitivity . . . 907
12.75.5.2 crc . . . 907
12.75.5.3 fileName . . . 907
12.75.5.4 internal . . . 908
12.75.5.5 q . . . 908
12.75.5.6 raw . . . 908
12.75.5.7 uncompressedSize . . . 908
12.75.5.8 writePos . . . 908

12.75.5.9 zip . . . 908
12.75.5.10 zipError . . . 908
12.76 QuaZipNewInfo Struct Reference . . . 909
12.76.1 Detailed Description . . . 910
12.76.2 Constructor & Destructor Documentation . . . 910
12.76.2.1 QuaZipNewInfo . . . 910
12.76.2.2 QuaZipNewInfo . . . 910
12.76.2.3 QuaZipNewInfo . . . 911
12.76.2.4 QuaZipNewInfo . . . 912
12.76.3 Member Function Documentation . . . 912
12.76.3.1 setFileDateTime . . . 912
12.76.3.2 setFileNTFSaTime . . . 912
12.76.3.3 setFileNTFScTime . . . 913
12.76.3.4 setFileNTFSmTime . . . 914
12.76.3.5 setFileNTFSTimes . . . 915
12.76.3.6 setFilePermissions . . . 915
12.76.3.7 setPermissions . . . 916
12.76.4 Field Documentation . . . 916
12.76.4.1 comment . . . 916
12.76.4.2 dateTime . . . 916
12.76.4.3 externalAttr . . . 917
12.76.4.4 extraGlobal . . . 917
12.76.4.5 extraLocal . . . 917
12.76.4.6 internalAttr . . . 917
12.76.4.7 name . . . 917
12.76.4.8 uncompressedSize . . . 917
12.77 QuaZipPrivate Class Reference . . . 917
12.77.1 Detailed Description . . . 919
12.77.2 Constructor & Destructor Documentation . . . 919
12.77.2.1 QuaZipPrivate . . . 919
12.77.2.2 QuaZipPrivate . . . 920
12.77.2.3 QuaZipPrivate . . . 920
12.77.3 Member Function Documentation . . . 920
12.77.3.1 addCurrentFileToDirectoryMap . . . 920
12.77.3.2 clearDirectoryMap . . . 921
12.77.3.3 getDefaultFileNameCodec . . . 922
12.77.3.4 getFileInfoList . . . 922
12.77.3.5 goToFirstUnmappedFile . . . 923
12.77.4 Friends And Related Function Documentation . . . 924
12.77.4.1 QuaZip . . . 924

12.77.5 Field Documentation . . . 924
12.77.5.1 "@4 . . . 924
12.77.5.2 autoClose . . . 924
12.77.5.3 comment . . . 924
12.77.5.4 commentCodec . . . 924
12.77.5.5 dataDescriptorWritingEnabled . . . 925
12.77.5.6 defaultFileNameCodec . . . 925
12.77.5.7 directoryCaseInsensitive . . . 925
12.77.5.8 directoryCaseSensitive . . . 925
12.77.5.9 fileNameCodec . . . 925
12.77.5.10 hasCurrentFile_f . . . 925
12.77.5.11 ioDevice . . . 925
12.77.5.12 lastMappedDirectoryEntry . . . 925
12.77.5.13 mode . . . 925
12.77.5.14 q . . . 926
12.77.5.15 zip64 . . . 926
12.77.5.16 zipError . . . 926
12.77.5.17 zipName . . . 926
12.78 QWidget Class Reference . . . 926
12.79 Ui::RebindWidget Class Reference . . . 927
12.79.1 Detailed Description . . . 930
12.79.2 Member Function Documentation . . . 930
12.79.2.1 retranslateUi . . . 930
12.79.2.2 setupUi . . . 933
12.79.3 Field Documentation . . . 942
12.79.3.1 actionTab . . . 942
12.79.3.2 animBox . . . 942
12.79.3.3 animButton . . . 942
12.79.3.4 animKrBox . . . 942
12.79.3.5 animOnceBox . . . 943
12.79.3.6 animTab . . . 943
12.79.3.7 applyButton . . . 943
12.79.3.8 btnClearMacro . . . 943
12.79.3.9 btnStartMacro . . . 943
12.79.3.10 btnStopMacro . . . 943
12.79.3.11 cancelButton . . . 943
12.79.3.12 dpiBox . . . 943
12.79.3.13 dpiButton . . . 944
12.79.3.14 dpiCustLabel . . . 944
12.79.3.15 dpiCustXBox . . . 944

12.79.3.16 dpiCustYBox . . . 944
12.79.3.17 dpiWarning . . . 944
12.79.3.18 fnBox . . . 944
12.79.3.19 fnButton . . . 944
12.79.3.20 gridLayout . . . 944
12.79.3.21 gridLayout_10 . . . 945
12.79.3.22 gridLayout_2 . . . 945
12.79.3.23 gridLayout_3 . . . 945
12.79.3.24 gridLayout_4 . . . 945
12.79.3.25 gridLayout_5 . . . 945
12.79.3.26 gridLayout_8 . . . 945
12.79.3.27 groupBox . . . 945
12.79.3.28 groupBox_2 . . . 945
12.79.3.29 groupBox_3 . . . 945
12.79.3.30 groupBox_4 . . . 946
12.79.3.31 horizontalLayout . . . 946
12.79.3.32 horizontalLayout_2 . . . 946
12.79.3.33 horizontalLayout_3 . . . 946
12.79.3.34 horizontalSpacer . . . 946
12.79.3.35 horizontalSpacer_10 . . . 946
12.79.3.36 horizontalSpacer_11 . . . 946
12.79.3.37 horizontalSpacer_12 . . . 946
12.79.3.38 horizontalSpacer_13 . . . 946
12.79.3.39 horizontalSpacer_14 . . . 947
12.79.3.40 horizontalSpacer_15 . . . 947
12.79.3.41 horizontalSpacer_16 . . . 947
12.79.3.42 horizontalSpacer_17 . . . 947
12.79.3.43 horizontalSpacer_18 . . . 947
12.79.3.44 horizontalSpacer_19 . . . 947
12.79.3.45 horizontalSpacer_2 . . . 947
12.79.3.46 horizontalSpacer_20 . . . 947
12.79.3.47 horizontalSpacer_21 . . . 947
12.79.3.48 horizontalSpacer_22 . . . 948
12.79.3.49 horizontalSpacer_23 . . . 948
12.79.3.50 horizontalSpacer_24 . . . 948
12.79.3.51 horizontalSpacer_25 . . . 948
12.79.3.52 horizontalSpacer_26 . . . 948
12.79.3.53 horizontalSpacer_3 . . . 948
12.79.3.54 horizontalSpacer_4 . . . 948
12.79.3.55 horizontalSpacer_5 . . . 948

12.79.3.56 horizontalSpacer_6 . . . 948
12.79.3.57 horizontalSpacer_7 . . . 949
12.79.3.58 horizontalSpacer_8 . . . 949
12.79.3.59 horizontalSpacer_9 . . . 949
12.79.3.60 keyTab . . . 949
12.79.3.61 layoutWidget . . . 949
12.79.3.62 layoutWidget1 . . . 949
12.79.3.63 layoutWidget_2 . . . 949
12.79.3.64 lbl_macro . . . 949
12.79.3.65 lightBox . . . 949
12.79.3.66 lightButton . . . 950
12.79.3.67 lightWrapBox . . . 950
12.79.3.68 lockBox . . . 950
12.79.3.69 lockButton . . . 950
12.79.3.70 macroTab . . . 950
12.79.3.71 mb2Box . . . 950
12.79.3.72 mb2Button . . . 950
12.79.3.73 mbBox . . . 950
12.79.3.74 mbButton . . . 951
12.79.3.75 mediaBox . . . 951
12.79.3.76 mediaButton . . . 951
12.79.3.77 modBox . . . 951
12.79.3.78 modButton . . . 951
12.79.3.79 modeBox . . . 951
12.79.3.80 modeButton . . . 951
12.79.3.81 modeWrapBox . . . 952
12.79.3.82 mouseTab . . . 952
12.79.3.83 numBox . . . 952
12.79.3.84 numButton . . . 952
12.79.3.85 programKpBox . . . 952
12.79.3.86 programKpButton . . . 952
12.79.3.87 programKpExtra . . . 952
12.79.3.88 programKpModeBox . . . 952
12.79.3.89 programKpSIBox . . . 953
12.79.3.90 programKrBox . . . 953
12.79.3.91 programKrButton . . . 953
12.79.3.92 programKrExtra . . . 953
12.79.3.93 programKrModeBox . . . 953
12.79.3.94 programKrSIBox . . . 953
12.79.3.95 programTab . . . 953

12.79.3.96 progTipLabel . . . 953
12.79.3.97 pteMacroBox . . . 954
12.79.3.98 pteMacroComment . . . 954
12.79.3.99 pteMacroText . . . 954
12.79.3.100 resetButton . . . 954
12.79.3.101 tabWidget . . . 954
12.79.3.102 typingBox . . . 954
12.79.3.103 typingButton . . . 954
12.79.3.104 unbindButton . . . 954
12.79.3.105 verticalLayout . . . 955
12.79.3.106 verticalLayout_2 . . . 955
12.79.3.107 verticalSpacer . . . 955
12.79.3.108 verticalSpacer_10 . . . 955
12.79.3.109 verticalSpacer_11 . . . 955
12.79.3.110 verticalSpacer_2 . . . 955
12.79.3.111 verticalSpacer_3 . . . 955
12.79.3.112 verticalSpacer_4 . . . 955
12.79.3.113 verticalSpacer_5 . . . 955
12.79.3.114 verticalSpacer_6 . . . 956
12.79.3.115 verticalSpacer_7 . . . 956
12.79.3.116 verticalSpacer_8 . . . 956
12.79.3.117 wheelBox . . . 956
12.79.3.118 wheelButton . . . 956
12.80 RebindWidget Class Reference . . . 956
12.80.1 Detailed Description . . . 960
12.80.2 Constructor & Destructor Documentation . . . 960
12.80.2.1 RebindWidget . . . 960
12.80.2.2 ~RebindWidget . . . 961
12.80.3 Member Function Documentation . . . 961
12.80.3.1 applyChanges . . . 961
12.80.3.2 convertMacroBox . . . 963
12.80.3.3 helpStatus . . . 964
12.80.3.4 on_animBox_currentIndexChanged . . . 964
12.80.3.5 on_animButton_clicked . . . 965
12.80.3.6 on_applyButton_clicked . . . 965
12.80.3.7 on_btnClearMacro_clicked . . . 966
12.80.3.8 on_btnStartMacro_clicked . . . 966
12.80.3.9 on_btnStopMacro_clicked . . . 967
12.80.3.10 on_cancelButton_clicked . . . 967
12.80.3.11 on_dpiBox_currentIndexChanged . . . 968

12.80.3.12 on_dpiButton_clicked . . . 969
12.80.3.13 on_fnBox_currentIndexChanged . . . 969
12.80.3.14 on_fnButton_clicked . . . 969
12.80.3.15 on_lightBox_currentIndexChanged . . . 970
12.80.3.16 on_lightButton_clicked . . . 970
12.80.3.17 on_lockBox_currentIndexChanged . . . 970
12.80.3.18 on_lockButton_clicked . . . 971
12.80.3.19 on_mb2Box_currentIndexChanged . . . 971
12.80.3.20 on_mb2Button_clicked . . . 971
12.80.3.21 on_mbBox_currentIndexChanged . . . 971
12.80.3.22 on_mbButton_clicked . . . 972
12.80.3.23 on_mediaBox_currentIndexChanged . . . 972
12.80.3.24 on_mediaButton_clicked . . . 972
12.80.3.25 on_modBox_currentIndexChanged . . . 973
12.80.3.26 on_modButton_clicked . . . 973
12.80.3.27 on_modeBox_currentIndexChanged . . . 973
12.80.3.28 on_modeButton_clicked . . . 974
12.80.3.29 on_numBox_currentIndexChanged . . . 974
12.80.3.30 on_numButton_clicked . . . 974
12.80.3.31 on_programKpBox_textChanged . . . 974
12.80.3.32 on_programKpButton_clicked . . . 975
12.80.3.33 on_programKpSIBox_clicked . . . 975
12.80.3.34 on_programKrBox_textChanged . . . 975
12.80.3.35 on_programKrButton_clicked . . . 976
12.80.3.36 on_programKrSIBox_clicked . . . 976
12.80.3.37 on_pteMacroBox_textChanged . . . 976
12.80.3.38 on_resetButton_clicked . . . 977
12.80.3.39 on_typingBox_currentIndexChanged . . . 977
12.80.3.40 on_typingButton_clicked . . . 978
12.80.3.41 on_unbindButton_clicked . . . 978
12.80.3.42 on_wheelBox_currentIndexChanged . . . 978
12.80.3.43 on_wheelButton_clicked . . . 979
12.80.3.44 setBind . . . 979
12.80.3.45 setBox . . . 981
12.80.3.46 setSelection . . . 982
12.80.4 Field Documentation . . . 986
12.80.4.1 bind . . . 986
12.80.4.2 fnKeys . . . 986
12.80.4.3 macReader . . . 987
12.80.4.4 mediaKeys . . . 987

12.80.4.5 modKeys . . . 987
12.80.4.6 mouseExtKeys . . . 987
12.80.4.7 mouseKeys . . . 987
12.80.4.8 numKeys . . . 987
12.80.4.9 profile . . . 987
12.80.4.10 selection . . . 987
12.80.4.11 TAB_ANIM . . . 987
12.80.4.12 TAB_KB . . . 988
12.80.4.13 TAB_MACRO . . . 988
12.80.4.14 TAB_MOUSE . . . 988
12.80.4.15 TAB_PROGRAM . . . 988
12.80.4.16 TAB_SPECIAL . . . 988
12.80.4.17 typingKeys . . . 988
12.80.4.18 ui . . . 988
12.80.4.19 wheelKeys . . . 988
12.81 RListWidget Class Reference . . . 989
12.81.1 Detailed Description . . . 990
12.81.2 Constructor & Destructor Documentation . . . 991
12.81.2.1 RListWidget . . . 991
12.81.3 Member Function Documentation . . . 991
12.81.3.1 change . . . 991
12.81.3.2 enter . . . 992
12.81.3.3 orderChanged . . . 992
12.81.3.4 rescanItems . . . 993
12.81.3.5 timerTick . . . 993
12.81.4 Field Documentation . . . 994
12.81.4.1 currentData . . . 994
12.81.4.2 DATA_ROLE . . . 994
12.81.4.3 dragged . . . 994
12.81.4.4 previousItems . . . 994
12.81.4.5 reorderTimer . . . 994
12.82 SettingsWidget Class Reference . . . 994
12.82.1 Detailed Description . . . 997
12.82.2 Constructor & Destructor Documentation . . . 997
12.82.2.1 SettingsWidget . . . 997
12.82.2.2 ~SettingsWidget . . . 998
12.82.3 Member Function Documentation . . . 998
12.82.3.1 on_altBox_activated . . . 999
12.82.3.2 on_autoFWBox_clicked . . . 999
12.82.3.3 on_capsBox_activated . . . 999

12.82.3.4 on_ctrlBox_activated . . . 1000
12.82.3.5 on_extraButton_clicked . . . 1000
12.82.3.6 on_layoutBox_activated . . . 1000
12.82.3.7 on_loginItemBox_clicked . . . 1001
12.82.3.8 on_pushButton_clicked . . . 1001
12.82.3.9 on_shiftBox_activated . . . 1001
12.82.3.10 on_winBox_activated . . . 1002
12.82.3.11 pollUpdates . . . 1002
12.82.3.12 setStatus . . . 1002
12.82.3.13 setVersion . . . 1003
12.82.3.14 showLayoutDialog . . . 1003
12.82.3.15 updateModifiers . . . 1004
12.82.4 Friends And Related Function Documentation . . . 1005
12.82.4.1 MainWindow . . . 1005
12.82.5 Field Documentation . . . 1005
12.82.5.1 extra . . . 1005
12.82.5.2 ui . . . 1005
12.83 Ui::SettingsWidget Class Reference . . . 1006
12.83.1 Detailed Description . . . 1008
12.83.2 Member Function Documentation . . . 1008
12.83.2.1 retranslateUi . . . 1008
12.83.2.2 setupUi . . . 1009
12.83.3 Field Documentation . . . 1013
12.83.3.1 altBox . . . 1013
12.83.3.2 altLabel . . . 1013
12.83.3.3 autoFWBox . . . 1013
12.83.3.4 capsBox . . . 1013
12.83.3.5 capsLabel . . . 1014
12.83.3.6 ctrlBox . . . 1014
12.83.3.7 ctrlLabel . . . 1014
12.83.3.8 devicesLabel . . . 1014
12.83.3.9 extraButton . . . 1014
12.83.3.10 gridLayout . . . 1014
12.83.3.11 gridLayout_3 . . . 1014
12.83.3.12 gridLayout_5 . . . 1014
12.83.3.13 horizontalLayout . . . 1014
12.83.3.14 horizontalLayout_2 . . . 1015
12.83.3.15 horizontalSpacer . . . 1015
12.83.3.16 horizontalSpacer_10 . . . 1015
12.83.3.17 horizontalSpacer_2 . . . 1015

12.83.3.18 horizontalSpacer_7 . . . 1015
12.83.3.19 horizontalSpacer_9 . . . 1015
12.83.3.20 label . . . 1015
12.83.3.21 label_2 . . . 1015
12.83.3.22 label_3 . . . 1015
12.83.3.23 label_5 . . . 1016
12.83.3.24 label_6 . . . 1016
12.83.3.25 label_8 . . . 1016
12.83.3.26 layoutBox . . . 1016
12.83.3.27 line . . . 1016
12.83.3.28 line_2 . . . 1016
12.83.3.29 line_3 . . . 1016
12.83.3.30 loginItemBox . . . 1016
12.83.3.31 pushButton . . . 1016
12.83.3.32 shiftBox . . . 1017
12.83.3.33 shiftLabel . . . 1017
12.83.3.34 versionLabel . . . 1017
12.83.3.35 verticalSpacer . . . 1017
12.83.3.36 verticalSpacer_10 . . . 1017
12.83.3.37 verticalSpacer_2 . . . 1017
12.83.3.38 verticalSpacer_3 . . . 1017
12.83.3.39 verticalSpacer_4 . . . 1017
12.83.3.40 verticalSpacer_5 . . . 1017
12.83.3.41 verticalSpacer_6 . . . 1018
12.83.3.42 verticalSpacer_7 . . . 1018
12.83.3.43 verticalSpacer_8 . . . 1018
12.83.3.44 winBox . . . 1018
12.83.3.45 winLabel . . . 1018
12.84 SGroup Class Reference . . . 1018
12.84.1 Detailed Description . . . 1020
12.84.2 Constructor & Destructor Documentation . . . 1020
12.84.2.1 SGroup . . . 1020
12.84.2.2 ~SGroup . . . 1020
12.84.3 Field Documentation . . . 1020
12.84.3.1 _settings . . . 1020
12.85 Ui_AnimAddDialog Class Reference . . . 1021
12.85.1 Detailed Description . . . 1022
12.85.2 Member Function Documentation . . . 1022
12.85.2.1 retranslateUi . . . 1022
12.85.2.2 setupUi . . . 1022

12.85.3 Field Documentation . . . 1024
12.85.3.1 animBox . . . 1024
12.85.3.2 buttonBox . . . 1024
12.85.3.3 gridLayout . . . 1024
12.85.3.4 horizontalLayout . . . 1024
12.85.3.5 horizontalSpacer . . . 1024
12.85.3.6 horizontalSpacer_2 . . . 1025
12.85.3.7 label . . . 1025
12.85.3.8 label_2 . . . 1025
12.85.3.9 presetBox . . . 1025
12.85.3.10 previewBox . . . 1025
12.85.3.11 verticalSpacer_2 . . . 1025
12.85.3.12 verticalSpacer_3 . . . 1025
12.86 Ui_AnimSettingDialog Class Reference . . . 1025
12.86.1 Detailed Description . . . 1028
12.86.2 Member Function Documentation . . . 1028
12.86.2.1 retranslateUi . . . 1028
12.86.2.2 setupUi . . . 1029
12.86.3 Field Documentation . . . 1032
12.86.3.1 animName . . . 1032
12.86.3.2 buttonBox . . . 1032
12.86.3.3 delayBox . . . 1033
12.86.3.4 gridLayout . . . 1033
12.86.3.5 gridLayout_2 . . . 1033
12.86.3.6 horizontalSpacer . . . 1033
12.86.3.7 horizontalSpacer_2 . . . 1033
12.86.3.8 horizontalSpacer_3 . . . 1033
12.86.3.9 horizontalSpacer_4 . . . 1033
12.86.3.10 horizontalSpacer_5 . . . 1033
12.86.3.11 horizontalSpacer_6 . . . 1033
12.86.3.12 infoTab . . . 1034
12.86.3.13 kpDelayBox . . . 1034
12.86.3.14 kpModeStopBox . . . 1034
12.86.3.15 kpReleaseBox . . . 1034
12.86.3.16 kpRepeatBox . . . 1034
12.86.3.17 kpRepeatLabel . . . 1034
12.86.3.18 kpRepeatLabel_2 . . . 1034
12.86.3.19 label . . . 1034
12.86.3.20 label_10 . . . 1034
12.86.3.21 label_11 . . . 1035

12.86.3.22 label_12 . . . 1035
12.86.3.23 label_13 . . . 1035
12.86.3.24 label_2 . . . 1035
12.86.3.25 label_3 . . . 1035
12.86.3.26 label_4 . . . 1035
12.86.3.27 label_5 . . . 1035
12.86.3.28 label_6 . . . 1035
12.86.3.29 label_7 . . . 1035
12.86.3.30 label_8 . . . 1036
12.86.3.31 label_9 . . . 1036
12.86.3.32 line . . . 1036
12.86.3.33 line_2 . . . 1036
12.86.3.34 repeatBox . . . 1036
12.86.3.35 repeatLabel . . . 1036
12.86.3.36 repeatLabel_2 . . . 1036
12.86.3.37 sAuthorLabel . . . 1036
12.86.3.38 sDescLabel . . . 1036
12.86.3.39 settingsGrid . . . 1037
12.86.3.40 settingTab . . . 1037
12.86.3.41 sLicenseLabel . . . 1037
12.86.3.42 sNameLabel . . . 1037
12.86.3.43 sVerLabel . . . 1037
12.86.3.44 sYearLabel . . . 1037
12.86.3.45 tabWidget . . . 1037
12.86.3.46 timeGrid . . . 1037
12.86.3.47 timeTab . . . 1037
12.86.3.48 verticalSpacer . . . 1038
12.86.3.49 verticalSpacer_2 . . . 1038
12.86.3.50 verticalSpacer_3 . . . 1038
12.87 Ui_ExtraSettingsWidget Class Reference . . . 1038
12.87.1 Detailed Description . . . 1040
12.87.2 Member Function Documentation . . . 1041
12.87.2.1 retranslateUi . . . 1041
12.87.2.2 setupUi . . . 1042
12.87.3 Field Documentation . . . 1045
12.87.3.1 animCountLabel . . . 1045
12.87.3.2 animPathLabel . . . 1046
12.87.3.3 animScanButton . . . 1046
12.87.3.4 brightnessBox . . . 1046
12.87.3.5 buttonBox . . . 1046

12.87.3.6 delayBox . . . 1046
12.87.3.7 ditherBox . . . 1046
12.87.3.8 fpsBox . . . 1046
12.87.3.9 fpsWarnLabel . . . 1046
12.87.3.10 gridLayout . . . 1046
12.87.3.11 horizontalLayout . . . 1047
12.87.3.12 horizontalLayout_2 . . . 1047
12.87.3.13 horizontalSpacer . . . 1047
12.87.3.14 horizontalSpacer_2 . . . 1047
12.87.3.15 horizontalSpacer_3 . . . 1047
12.87.3.16 label . . . 1047
12.87.3.17 label_10 . . . 1047
12.87.3.18 label_11 . . . 1047
12.87.3.19 label_2 . . . 1047
12.87.3.20 label_3 . . . 1048
12.87.3.21 label_5 . . . 1048
12.87.3.22 label_6 . . . 1048
12.87.3.23 line . . . 1048
12.87.3.24 line_2 . . . 1048
12.87.3.25 line_3 . . . 1048
12.87.3.26 mAccelBox . . . 1048
12.87.3.27 osxLabel . . . 1048
12.87.3.28 osxLine . . . 1048
12.87.3.29 sAccelBox . . . 1049
12.87.3.30 sSpeedBox . . . 1049
12.87.3.31 sSpeedWidget . . . 1049
12.87.3.32 trayBox . . . 1049
12.87.3.33 verticalSpacer . . . 1049
12.87.3.34 verticalSpacer_10 . . . 1049
12.87.3.35 verticalSpacer_11 . . . 1049
12.87.3.36 verticalSpacer_2 . . . 1049
12.87.3.37 verticalSpacer_3 . . . 1049
12.87.3.38 verticalSpacer_4 . . . 1050
12.87.3.39 verticalSpacer_5 . . . 1050
12.87.3.40 verticalSpacer_6 . . . 1050
12.87.3.41 verticalSpacer_7 . . . 1050
12.87.3.42 verticalSpacer_8 . . . 1050
12.87.3.43 verticalSpacer_9 . . . 1050
12.88 Ui_FwUpgradeDialog Class Reference . . . 1050
12.88.1 Detailed Description . . . 1052

12.88.2 Member Function Documentation . . . 1052
12.88.2.1 retranslateUi . . . 1052
12.88.2.2 setupUi . . . 1053
12.88.3 Field Documentation . . . 1054
12.88.3.1 actionButton . . . 1054
12.88.3.2 cancelButton . . . 1055
12.88.3.3 curLabel . . . 1055
12.88.3.4 devLabel . . . 1055
12.88.3.5 gridLayout . . . 1055
12.88.3.6 gridLayout_2 . . . 1055
12.88.3.7 horizontalSpacer . . . 1055
12.88.3.8 horizontalSpacer_2 . . . 1055
12.88.3.9 horizontalSpacer_3 . . . 1055
12.88.3.10 horizontalSpacer_4 . . . 1055
12.88.3.11 label_2 . . . 1056
12.88.3.12 label_4 . . . 1056
12.88.3.13 newLabel . . . 1056
12.88.3.14 progressBar . . . 1056
12.88.3.15 statusLabel . . . 1056
12.89 Ui_GradientDialog Class Reference . . . 1056
12.89.1 Detailed Description . . . 1058
12.89.2 Member Function Documentation . . . 1058
12.89.2.1 retranslateUi . . . 1058
12.89.2.2 setupUi . . . 1059
12.89.3 Field Documentation . . . 1061
12.89.3.1 buttonBox . . . 1061
12.89.3.2 gridLayout . . . 1061
12.89.3.3 gridLayout_2 . . . 1061
12.89.3.4 gridLayout_3 . . . 1061
12.89.3.5 groupBox_2 . . . 1062
12.89.3.6 horizontalLayout . . . 1062
12.89.3.7 horizontalLayout_2 . . . 1062
12.89.3.8 horizontalSpacer . . . 1062
12.89.3.9 horizontalSpacer_2 . . . 1062
12.89.3.10 horizontalSpacer_3 . . . 1062
12.89.3.11 label . . . 1062
12.89.3.12 label_2 . . . 1062
12.89.3.13 presetDelete . . . 1062
12.89.3.14 presetList . . . 1063
12.89.3.15 presetName . . . 1063

12.89.3.16 presetSave . . . 1063
12.89.3.17 stopBox . . . 1063
12.89.3.18 stopColor . . . 1063
12.89.3.19 stopOpacity . . . 1063
12.89.3.20 stopPos . . . 1063
12.89.3.21 verticalSpacer . . . 1063
12.89.3.22 verticalSpacer_2 . . . 1063
12.89.3.23 widget . . . 1064
12.90 Ui_KbAnimWidget Class Reference . . . 1064
12.90.1 Detailed Description . . . 1066
12.90.2 Member Function Documentation . . . 1066
12.90.2.1 retranslateUi . . . 1066
12.90.2.2 setupUi . . . 1066
12.90.3 Field Documentation . . . 1069
12.90.3.1 aCopyLabel . . . 1069
12.90.3.2 aMissingLabel . . . 1069
12.90.3.3 aMissingPage . . . 1069
12.90.3.4 aNameLabel . . . 1069
12.90.3.5 animList . . . 1069
12.90.3.6 animPage . . . 1070
12.90.3.7 aVerLabel . . . 1070
12.90.3.8 blendBox . . . 1070
12.90.3.9 deleteButton . . . 1070
12.90.3.10 gridLayout . . . 1070
12.90.3.11 gridLayout_2 . . . 1070
12.90.3.12 gridLayout_3 . . . 1070
12.90.3.13 gridLayout_4 . . . 1070
12.90.3.14 horizontalLayout . . . 1071
12.90.3.15 horizontalSpacer . . . 1071
12.90.3.16 horizontalSpacer_2 . . . 1071
12.90.3.17 horizontalSpacer_3 . . . 1071
12.90.3.18 horizontalSpacer_4 . . . 1071
12.90.3.19 horizontalSpacer_5 . . . 1071
12.90.3.20 keyButton . . . 1071
12.90.3.21 label_5 . . . 1071
12.90.3.22 label_6 . . . 1071
12.90.3.23 label_7 . . . 1072
12.90.3.24 nameBox . . . 1072
12.90.3.25 noAnimLabel . . . 1072
12.90.3.26 noSelPage . . . 1072

12.90.3.27 opacityBox . . . 1072
12.90.3.28 propertyButton . . . 1072
12.90.3.29 selectionStack . . . 1072
12.90.3.30 verticalLayout . . . 1072
12.90.3.31 verticalSpacer . . . 1072
12.90.3.32 verticalSpacer_2 . . . 1073
12.90.3.33 verticalSpacer_3 . . . 1073
12.91 Ui_KbBindWidget Class Reference . . . 1073
12.91.1 Detailed Description . . . 1074
12.91.2 Member Function Documentation . . . 1075
12.91.2.1 retranslateUi . . . 1075
12.91.2.2 setupUi . . . 1075
12.91.3 Field Documentation . . . 1077
12.91.3.1 copyButton . . . 1077
12.91.3.2 gridLayout . . . 1077
12.91.3.3 gridLayout_2 . . . 1077
12.91.3.4 horizontalLayout_2 . . . 1078
12.91.3.5 horizontalSpacer . . . 1078
12.91.3.6 horizontalSpacer_2 . . . 1078
12.91.3.7 keyWidget . . . 1078
12.91.3.8 label . . . 1078
12.91.3.9 label_2 . . . 1078
12.91.3.10 line . . . 1078
12.91.3.11 line_2 . . . 1078
12.91.3.12 rbWidget . . . 1078
12.91.3.13 resetButton . . . 1079
12.91.3.14 selectLabel . . . 1079
12.91.3.15 verticalLayout . . . 1079
12.91.3.16 verticalSpacer . . . 1079
12.91.3.17 widget . . . 1079
12.92 Ui_KbLightWidget Class Reference . . . 1079
12.92.1 Detailed Description . . . 1081
12.92.2 Member Function Documentation . . . 1081
12.92.2.1 retranslateUi . . . 1081
12.92.2.2 setupUi . . . 1082
12.92.3 Field Documentation . . . 1084
12.92.3.1 animButton . . . 1084
12.92.3.2 animWidget . . . 1085
12.92.3.3 bgButton . . . 1085
12.92.3.4 brightnessBox . . . 1085

12.92.3.5 gridLayout . . . 1085
12.92.3.6 gridLayout_2 . . . 1085
12.92.3.7 gridLayout_4 . . . 1085
12.92.3.8 horizontalLayout . . . 1085
12.92.3.9 horizontalLayout_2 . . . 1085
12.92.3.10 horizontalLayout_3 . . . 1085
12.92.3.11 horizontalSpacer_3 . . . 1086
12.92.3.12 horizontalSpacer_4 . . . 1086
12.92.3.13 horizontalSpacer_5 . . . 1086
12.92.3.14 horizontalSpacer_6 . . . 1086
12.92.3.15 keyWidget . . . 1086
12.92.3.16 label . . . 1086
12.92.3.17 label_2 . . . 1086
12.92.3.18 label_3 . . . 1086
12.92.3.19 line . . . 1086
12.92.3.20 line_2 . . . 1087
12.92.3.21 selLabel . . . 1087
12.92.3.22 showAnimBox . . . 1087
12.92.3.23 verticalLayout . . . 1087
12.92.3.24 verticalSpacer_2 . . . 1087
12.92.3.25 verticalSpacer_3 . . . 1087
12.92.3.26 widget . . . 1087
12.93 Ui_KbProfileDialog Class Reference . . . 1087
12.93.1 Detailed Description . . . 1089
12.93.2 Member Function Documentation . . . 1089
12.93.2.1 retranslateUi . . . 1089
12.93.2.2 setupUi . . . 1089
12.93.3 Field Documentation . . . 1090
12.93.3.1 buttonBox . . . 1090
12.93.3.2 gridLayout . . . 1090
12.93.3.3 horizontalSpacer . . . 1091
12.93.3.4 horizontalSpacer_2 . . . 1091
12.93.3.5 profileList . . . 1091
12.94 Ui_KbWidget Class Reference . . . 1091
12.94.1 Detailed Description . . . 1093
12.94.2 Member Function Documentation . . . 1093
12.94.2.1 retranslateUi . . . 1093
12.94.2.2 setupUi . . . 1094
12.94.3 Field Documentation . . . 1097
12.94.3.1 bindTab . . . 1097

12.94.3.2 bindWidget . . . 1097
12.94.3.3 devTab . . . 1097
12.94.3.4 fwLabel . . . 1097
12.94.3.5 fwUpdButton . . . 1097
12.94.3.6 fwUpdLabel . . . 1098
12.94.3.7 fwUpdLayout . . . 1098
12.94.3.8 gridLayout . . . 1098
12.94.3.9 gridLayout_2 . . . 1098
12.94.3.10 gridLayout_3 . . . 1098
12.94.3.11 gridLayout_4 . . . 1098
12.94.3.12 gridLayout_5 . . . 1098
12.94.3.13 gridLayout_7 . . . 1098
12.94.3.14 horizontalSpacer_2 . . . 1098
12.94.3.15 horizontalSpacer_3 . . . 1099
12.94.3.16 hwSaveButton . . . 1099
12.94.3.17 kPerfTab . . . 1099
12.94.3.18 kPerfWidget . . . 1099
12.94.3.19 label_3 . . . 1099
12.94.3.20 label_4 . . . 1099
12.94.3.21 label_9 . . . 1099
12.94.3.22 lightTab . . . 1099
12.94.3.23 lightWidget . . . 1099
12.94.3.24 modesList . . . 1100
12.94.3.25 mPerfTab . . . 1100
12.94.3.26 mPerfWidget . . . 1100
12.94.3.27 pollLabel . . . 1100
12.94.3.28 pollLabel2 . . . 1100
12.94.3.29 profileBox . . . 1100
12.94.3.30 serialLabel . . . 1100
12.94.3.31 tabWidget . . . 1100
12.94.3.32 verticalSpacer . . . 1100
12.95 Ui_KPerfWidget Class Reference . . . 1101
12.95.1 Detailed Description . . . 1104
12.95.2 Member Function Documentation . . . 1104
12.95.2.1 retranslateUi . . . 1104
12.95.2.2 setupUi . . . 1105
12.95.3 Field Documentation . . . 1111
12.95.3.1 capsBox . . . 1111
12.95.3.2 capsColorOff . . . 1112
12.95.3.3 capsColorOn . . . 1112

12.95.3.4 copyButton . . . 1112
12.95.3.5 gridLayout . . . 1112
12.95.3.6 horizontalLayout . . . 1112
12.95.3.7 horizontalLayout_2 . . . 1112
12.95.3.8 horizontalSpacer . . . 1112
12.95.3.9 horizontalSpacer_2 . . . 1112
12.95.3.10 horizontalSpacer_3 . . . 1112
12.95.3.11 horizontalSpacer_4 . . . 1113
12.95.3.12 horizontalSpacer_5 . . . 1113
12.95.3.13 horizontalSpacer_6 . . . 1113
12.95.3.14 horizontalSpacer_7 . . . 1113
12.95.3.15 horizontalSpacer_8 . . . 1113
12.95.3.16 intensityBox . . . 1113
12.95.3.17 k95Label1 . . . 1113
12.95.3.18 k95Label2 . . . 1113
12.95.3.19 k95Label3 . . . 1113
12.95.3.20 k95Label4 . . . 1114
12.95.3.21 k95Label5 . . . 1114
12.95.3.22 k95Label6 . . . 1114
12.95.3.23 k95Line . . . 1114
12.95.3.24 k95Spacer . . . 1114
12.95.3.25 label . . . 1114
12.95.3.26 label_10 . . . 1114
12.95.3.27 label_11 . . . 1114
12.95.3.28 label_12 . . . 1114
12.95.3.29 label_14 . . . 1115
12.95.3.30 label_15 . . . 1115
12.95.3.31 label_16 . . . 1115
12.95.3.32 label_17 . . . 1115
12.95.3.33 label_18 . . . 1115
12.95.3.34 label_19 . . . 1115
12.95.3.35 label_2 . . . 1115
12.95.3.36 label_20 . . . 1115
12.95.3.37 label_21 . . . 1115
12.95.3.38 label_22 . . . 1116
12.95.3.39 label_23 . . . 1116
12.95.3.40 label_24 . . . 1116
12.95.3.41 label_3 . . . 1116
12.95.3.42 label_4 . . . 1116
12.95.3.43 label_5 . . . 1116

12.95.3.44 label_6 . . . 1116
12.95.3.45 label_7 . . . 1116
12.95.3.46 label_8 . . . 1116
12.95.3.47 lightBox . . . 1117
12.95.3.48 lightColor1 . . . 1117
12.95.3.49 lightColor2 . . . 1117
12.95.3.50 lightColor3 . . . 1117
12.95.3.51 line . . . 1117
12.95.3.52 line_2 . . . 1117
12.95.3.53 line_3 . . . 1117
12.95.3.54 lockBox . . . 1117
12.95.3.55 lockColorOff . . . 1117
12.95.3.56 lockColorOn . . . 1118
12.95.3.57 macroBox . . . 1118
12.95.3.58 macroColorOff . . . 1118
12.95.3.59 macroColorOn . . . 1118
12.95.3.60 modeBox . . . 1118
12.95.3.61 modeColorOff . . . 1118
12.95.3.62 modeColorOn . . . 1118
12.95.3.63 muteBox . . . 1118
12.95.3.64 muteColorNA . . . 1118
12.95.3.65 muteColorOff . . . 1119
12.95.3.66 muteColorOn . . . 1119
12.95.3.67 numBox . . . 1119
12.95.3.68 numColorOff . . . 1119
12.95.3.69 numColorOn . . . 1119
12.95.3.70 scrollBox . . . 1119
12.95.3.71 scrollColorOff . . . 1119
12.95.3.72 scrollColorOn . . . 1119
12.95.3.73 verticalSpacer . . . 1119
12.95.3.74 verticalSpacer_2 . . . 1120
12.95.3.75 verticalSpacer_3 . . . 1120
12.95.3.76 verticalSpacer_4 . . . 1120
12.96 Ui_LayoutDialog Class Reference . . . 1120
12.96.1 Detailed Description . . . 1122
12.96.2 Member Function Documentation . . . 1122
12.96.2.1 retranslateUi . . . 1122
12.96.2.2 setupUi . . . 1122
12.96.3 Field Documentation . . . 1124
12.96.3.1 buttonBox . . . 1124

12.96.3.2 comboBox . . . 1124
12.96.3.3 gridLayout . . . 1124
12.96.3.4 horizontalSpacer . . . 1124
12.96.3.5 horizontalSpacer_2 . . . 1124
12.96.3.6 label . . . 1125
12.96.3.7 label_2 . . . 1125
12.96.3.8 verticalSpacer . . . 1125
12.96.3.9 verticalSpacer_2 . . . 1125
12.96.3.10 verticalSpacer_3 . . . 1125
12.96.3.11 verticalSpacer_4 . . . 1125
12.97 Ui_MainWindow Class Reference . . . 1125
12.97.1 Detailed Description . . . 1127
12.97.2 Member Function Documentation . . . 1127
12.97.2.1 retranslateUi . . . 1127
12.97.2.2 setupUi . . . 1127
12.97.3 Field Documentation . . . 1128
12.97.3.1 actionAbout . . . 1128
12.97.3.2 actionExit . . . 1128
12.97.3.3 centralWidget . . . 1128
12.97.3.4 gridLayout . . . 1129
12.97.3.5 tabWidget . . . 1129
12.98 Ui_ModeSelectDialog Class Reference . . . 1129
12.98.1 Detailed Description . . . 1130
12.98.2 Member Function Documentation . . . 1130
12.98.2.1 retranslateUi . . . 1130
12.98.2.2 setupUi . . . 1131
12.98.3 Field Documentation . . . 1132
12.98.3.1 buttonBox . . . 1132
12.98.3.2 gridLayout . . . 1132
12.98.3.3 label . . . 1132
12.98.3.4 modeList . . . 1132
12.98.3.5 selAllButton . . . 1132
12.98.3.6 selNoneButton . . . 1133
12.99 Ui_MPerfWidget Class Reference . . . 1133
12.99.1 Detailed Description . . . 1135
12.99.2 Member Function Documentation . . . 1136
12.99.2.1 retranslateUi . . . 1136
12.99.2.2 setupUi . . . 1137
12.99.3 Field Documentation . . . 1144
12.99.3.1 aSnapBox . . . 1144

12.99.3.2 copyButton . . . 1144
12.99.3.3 eBox1 . . . 1144
12.99.3.4 eBox2 . . . 1144
12.99.3.5 eBox3 . . . 1144
12.99.3.6 eBox4 . . . 1145
12.99.3.7 eBox5 . . . 1145
12.99.3.8 gridLayout . . . 1145
12.99.3.9 horizontalLayout . . . 1145
12.99.3.10 horizontalLayout_2 . . . 1145
12.99.3.11 horizontalLayout_4 . . . 1145
12.99.3.12 horizontalSpacer . . . 1145
12.99.3.13 horizontalSpacer_2 . . . 1145
12.99.3.14 horizontalSpacer_3 . . . 1145
12.99.3.15 horizontalSpacer_4 . . . 1146
12.99.3.16 horizontalSpacer_5 . . . 1146
12.99.3.17 horizontalSpacer_6 . . . 1146
12.99.3.18 horizontalSpacer_7 . . . 1146
12.99.3.19 iButton0 . . . 1146
12.99.3.20 iButton1 . . . 1146
12.99.3.21 iButton2 . . . 1146
12.99.3.22 iButton3 . . . 1146
12.99.3.23 iButton4 . . . 1146
12.99.3.24 iButton5 . . . 1147
12.99.3.25 iButtonO . . . 1147
12.99.3.26 indicBox . . . 1147
12.99.3.27 label . . . 1147
12.99.3.28 label_11 . . . 1147
12.99.3.29 label_12 . . . 1147
12.99.3.30 label_13 . . . 1147
12.99.3.31 label_14 . . . 1147
12.99.3.32 label_15 . . . 1147
12.99.3.33 label_2 . . . 1148
12.99.3.34 label_25 . . . 1148
12.99.3.35 label_3 . . . 1148
12.99.3.36 label_4 . . . 1148
12.99.3.37 label_5 . . . 1148
12.99.3.38 label_6 . . . 1148
12.99.3.39 label_7 . . . 1148
12.99.3.40 label_8 . . . 1148
12.99.3.41 lHeightBox . . . 1148

12.99.3.42line . . . 1149
12.99.3.43line_2 . . . 1149
12.99.3.44line_3 . . . 1149
12.99.3.45spinBox . . . 1149
12.99.3.46verticalLayout . . . 1149
12.99.3.47verticalSpacer . . . 1149
12.99.3.48verticalSpacer_2 . . . 1149
12.99.3.49verticalSpacer_3 . . . 1149
12.99.3.50xBox0 . . . 1149
12.99.3.51xBox1 . . . 1150
12.99.3.52xBox2 . . . 1150
12.99.3.53xBox3 . . . 1150
12.99.3.54xBox4 . . . 1150
12.99.3.55xBox5 . . . 1150
12.99.3.56xSlider0 . . . 1150
12.99.3.57xSlider1 . . . 1150
12.99.3.58xSlider2 . . . 1150
12.99.3.59xSlider3 . . . 1150
12.99.3.60xSlider4 . . . 1151
12.99.3.61xSlider5 . . . 1151
12.99.3.62xyBox . . . 1151
12.99.3.63yBox0 . . . 1151
12.99.3.64yBox1 . . . 1151
12.99.3.65yBox2 . . . 1151
12.99.3.66yBox3 . . . 1151
12.99.3.67yBox4 . . . 1151
12.99.3.68yBox5 . . . 1151
12.99.3.69ySlider0 . . . 1152
12.99.3.70ySlider1 . . . 1152
12.99.3.71ySlider2 . . . 1152
12.99.3.72ySlider3 . . . 1152
12.99.3.73ySlider4 . . . 1152
12.99.3.74ySlider5 . . . 1152
12.100Ui_RebindWidget Class Reference . . . 1152
12.100.1Detailed Description . . . 1156
12.100.2Member Function Documentation . . . 1156
12.100.2.1retranslateUi . . . 1156
12.100.2.2setupUi . . . 1158
12.100.3Field Documentation . . . 1167
12.100.3.1actionTab . . . 1167

12.100.3.2 animBox . . . 1167
12.100.3.3 animButton . . . 1167
12.100.3.4 animKrBox . . . 1167
12.100.3.5 animOnceBox . . . 1168
12.100.3.6 animTab . . . 1168
12.100.3.7 applyButton . . . 1168
12.100.3.8 btnClearMacro . . . 1168
12.100.3.9 btnStartMacro . . . 1168
12.100.3.10 btnStopMacro . . . 1168
12.100.3.11 cancelButton . . . 1168
12.100.3.12 cpiBox . . . 1168
12.100.3.13 cpiButton . . . 1168
12.100.3.14 cpiCustLabel . . . 1169
12.100.3.15 cpiCustXBox . . . 1169
12.100.3.16 cpiCustYBox . . . 1169
12.100.3.17 cpiWarning . . . 1169
12.100.3.18 dBox . . . 1169
12.100.3.19 dButton . . . 1169
12.100.3.20 gridLayout . . . 1169
12.100.3.21 gridLayout_10 . . . 1169
12.100.3.22 gridLayout_2 . . . 1170
12.100.3.23 gridLayout_3 . . . 1170
12.100.3.24 gridLayout_4 . . . 1170
12.100.3.25 gridLayout_5 . . . 1170
12.100.3.26 gridLayout_8 . . . 1170
12.100.3.27 groupBox . . . 1170
12.100.3.28 groupBox_2 . . . 1170
12.100.3.29 groupBox_3 . . . 1170
12.100.3.30 groupBox_4 . . . 1170
12.100.3.31 horizontalLayout . . . 1171
12.100.3.32 horizontalLayout_2 . . . 1171
12.100.3.33 horizontalLayout_3 . . . 1171
12.100.3.34 horizontalSpacer . . . 1171
12.100.3.35 horizontalSpacer_10 . . . 1171
12.100.3.36 horizontalSpacer_11 . . . 1171
12.100.3.37 horizontalSpacer_12 . . . 1171
12.100.3.38 horizontalSpacer_13 . . . 1171
12.100.3.39 horizontalSpacer_14 . . . 1171
12.100.3.40 horizontalSpacer_15 . . . 1172
12.100.3.41 horizontalSpacer_16 . . . 1172

12.100.3.42 horizontalSpacer_17 . . . 1172
12.100.3.43 horizontalSpacer_18 . . . 1172
12.100.3.44 horizontalSpacer_19 . . . 1172
12.100.3.45 horizontalSpacer_2 . . . 1172
12.100.3.46 horizontalSpacer_20 . . . 1172
12.100.3.47 horizontalSpacer_21 . . . 1172
12.100.3.48 horizontalSpacer_22 . . . 1172
12.100.3.49 horizontalSpacer_23 . . . 1173
12.100.3.50 horizontalSpacer_24 . . . 1173
12.100.3.51 horizontalSpacer_25 . . . 1173
12.100.3.52 horizontalSpacer_26 . . . 1173
12.100.3.53 horizontalSpacer_3 . . . 1173
12.100.3.54 horizontalSpacer_4 . . . 1173
12.100.3.55 horizontalSpacer_5 . . . 1173
12.100.3.56 horizontalSpacer_6 . . . 1173
12.100.3.57 horizontalSpacer_7 . . . 1173
12.100.3.58 horizontalSpacer_8 . . . 1174
12.100.3.59 horizontalSpacer_9 . . . 1174
12.100.3.60 keyTab . . . 1174
12.100.3.61 layoutWidget . . . 1174
12.100.3.62 layoutWidget1 . . . 1174
12.100.3.63 layoutWidget_2 . . . 1174
12.100.3.64 lil_macro . . . 1174
12.100.3.65 lightBox . . . 1174
12.100.3.66 lightButton . . . 1174
12.100.3.67 lightWrapBox . . . 1175
12.100.3.68 lockBox . . . 1175
12.100.3.69 lockButton . . . 1175
12.100.3.70 macroTab . . . 1175
12.100.3.71 mb2Box . . . 1175
12.100.3.72 mb2Button . . . 1175
12.100.3.73 mbBox . . . 1175
12.100.3.74 mbButton . . . 1175
12.100.3.75 mediaBox . . . 1176
12.100.3.76 mediaButton . . . 1176
12.100.3.77 modBox . . . 1176
12.100.3.78 modButton . . . 1176
12.100.3.79 modeBox . . . 1176
12.100.3.80 modeButton . . . 1176
12.100.3.81 modeWrapBox . . . 1176

12.100.3.82 mouseTab . . . 1176
12.100.3.83 numBox . . . 1177
12.100.3.84 numButton . . . 1177
12.100.3.85 programKpBox . . . 1177
12.100.3.86 programKpButton . . . 1177
12.100.3.87 programKpExtra . . . 1177
12.100.3.88 programKpModeBox . . . 1177
12.100.3.89 programKpSIBox . . . 1177
12.100.3.90 programKrBox . . . 1177
12.100.3.91 programKrButton . . . 1178
12.100.3.92 programKrExtra . . . 1178
12.100.3.93 programKrModeBox . . . 1178
12.100.3.94 programKrSIBox . . . 1178
12.100.3.95 programTab . . . 1178
12.100.3.96 progTipLabel . . . 1178
12.100.3.97 rateMacroBox . . . 1178
12.100.3.98 rateMacroComment . . . 1178
12.100.3.99 rateMacroText . . . 1178
12.100.3.100 resetButton . . . 1179
12.100.3.101 tabWidget . . . 1179
12.100.3.102 typingBox . . . 1179
12.100.3.103 typingButton . . . 1179
12.100.3.104 unbindButton . . . 1179
12.100.3.105 verticalLayout . . . 1179
12.100.3.106 verticalLayout_2 . . . 1179
12.100.3.107 verticalSpacer . . . 1179
12.100.3.108 verticalSpacer_10 . . . 1180
12.100.3.109 verticalSpacer_11 . . . 1180
12.100.3.110 verticalSpacer_2 . . . 1180
12.100.3.111 verticalSpacer_3 . . . 1180
12.100.3.112 verticalSpacer_4 . . . 1180
12.100.3.113 verticalSpacer_5 . . . 1180
12.100.3.114 verticalSpacer_6 . . . 1180
12.100.3.115 verticalSpacer_7 . . . 1180
12.100.3.116 verticalSpacer_8 . . . 1180
12.100.3.117 wheelBox . . . 1181
12.100.3.118 wheelButton . . . 1181
12.101 Ui_SettingsWidget Class Reference . . . 1181
12.101.1 Detailed Description . . . 1183
12.101.2 Member Function Documentation . . . 1183

12.101.2.1 retranslateUi . . . 1183
12.101.2.2 setupUi . . . 1184
12.101.3 Field Documentation . . . 1188
12.101.3.1 altBox . . . 1188
12.101.3.2 altLabel . . . 1188
12.101.3.3 autoFWBox . . . 1188
12.101.3.4 capsBox . . . 1188
12.101.3.5 capsLabel . . . 1188
12.101.3.6 ctrlBox . . . 1188
12.101.3.7 ctrlLabel . . . 1188
12.101.3.8 devicesLabel . . . 1189
12.101.3.9 extraButton . . . 1189
12.101.3.10 gridLayout . . . 1189
12.101.3.11 gridLayout_3 . . . 1189
12.101.3.12 gridLayout_5 . . . 1189
12.101.3.13 horizontalLayout . . . 1189
12.101.3.14 horizontalLayout_2 . . . 1189
12.101.3.15 horizontalSpacer . . . 1189
12.101.3.16 horizontalSpacer_10 . . . 1189
12.101.3.17 horizontalSpacer_2 . . . 1190
12.101.3.18 horizontalSpacer_7 . . . 1190
12.101.3.19 horizontalSpacer_9 . . . 1190
12.101.3.20 label . . . 1190
12.101.3.21 label_2 . . . 1190
12.101.3.22 label_3 . . . 1190
12.101.3.23 label_5 . . . 1190
12.101.3.24 label_6 . . . 1190
12.101.3.25 label_8 . . . 1190
12.101.3.26 layoutBox . . . 1191
12.101.3.27 line . . . 1191
12.101.3.28 line_2 . . . 1191
12.101.3.29 line_3 . . . 1191
12.101.3.30 loginItemBox . . . 1191
12.101.3.31 pushButton . . . 1191
12.101.3.32 shiftBox . . . 1191
12.101.3.33 shiftLabel . . . 1191
12.101.3.34 versionLabel . . . 1191
12.101.3.35 verticalSpacer . . . 1192
12.101.3.36 verticalSpacer_10 . . . 1192
12.101.3.37 verticalSpacer_2 . . . 1192

12.101.3.38 verticalSpacer_3 . . . 1192
12.101.3.39 verticalSpacer_4 . . . 1192
12.101.3.40 verticalSpacer_5 . . . 1192
12.101.3.41 verticalSpacer_6 . . . 1192
12.101.3.42 verticalSpacer_7 . . . 1192
12.101.3.43 verticalSpacer_8 . . . 1192
12.101.3.44 winBox . . . 1193
12.101.3.45 winLabel . . . 1193
12.102 UsbId Struct Reference . . . 1193
12.102.1 Detailed Description . . . 1194
12.102.2 Constructor & Destructor Documentation . . . 1194
12.102.2.1 UsbId . . . 1194
12.102.2.2 UsbId . . . 1194
12.102.2.3 UsbId . . . 1194
12.102.3 Member Function Documentation . . . 1194
12.102.3.1 guidString . . . 1194
12.102.3.2 guidString . . . 1195
12.102.3.3 hwModifiedString . . . 1195
12.102.3.4 hwModifiedString . . . 1195
12.102.3.5 modifiedString . . . 1196
12.102.3.6 modifiedString . . . 1196
12.102.3.7 newGuid . . . 1196
12.102.3.8 newModified . . . 1197
12.102.4 Field Documentation . . . 1197
12.102.4.1 guid . . . 1197
12.102.4.2 hwModified . . . 1197
12.102.4.3 modified . . . 1197

13 File Documentation **1199**
13.1 BUILD.md File Reference . . . 1199
13.2 DAEMON.md File Reference . . . 1199
13.3 README.md File Reference . . . 1199
13.4 ROADMAP.md File Reference . . . 1199
13.5 src/ckb/animadddialog.cpp File Reference . . . 1199
13.6 src/ckb/animadddialog.h File Reference . . . 1199
13.7 src/ckb/animscript.cpp File Reference . . . 1200
13.7.1 Function Documentation . . . 1201
13.7.1.1 urlParam . . . 1201
13.7.2 Variable Documentation . . . 1201
13.7.2.1 ONE_DAY . . . 1201

13.8 src/ckb/animscript.h File Reference . . . 1202
13.8.1 Data Structure Documentation . . . 1202
13.8.1.1 struct AnimScript::Param . . . 1202
13.9 src/ckb/animsettingdialog.cpp File Reference . . . 1203
13.9.1 Function Documentation . . . 1204
13.9.1.1 angleFlip . . . 1204
13.10 src/ckb/animsettingdialog.h File Reference . . . 1205
13.11 src/ckb/autorun.cpp File Reference . . . 1205
13.11.1 Variable Documentation . . . 1206
13.11.1.1 settingPath . . . 1206
13.12 src/ckb/autorun.h File Reference . . . 1206
13.13 src/ckb/ckb-anim.h File Reference . . . 1207
13.13.1 Data Structure Documentation . . . 1209
13.13.1.1 struct ckb_key . . . 1209
13.13.1.2 struct ckb_runctx . . . 1210
13.13.1.3 struct ckb_gradient . . . 1211
13.13.2 Macro Definition Documentation . . . 1212
13.13.2.1 CKB_CONTAINER . . . 1212
13.13.2.2 CKB_COPYRIGHT . . . 1212
13.13.2.3 CKB_DESCRIPTION . . . 1212
13.13.2.4 CKB_DOWN . . . 1212
13.13.2.5 CKB_GRAD_MAX . . . 1213
13.13.2.6 CKB_GUID . . . 1213
13.13.2.7 CKB_KEYCLEAR . . . 1213
13.13.2.8 CKB_KEYNAME_MAX . . . 1213
13.13.2.9 CKB_KP_NAME . . . 1213
13.13.2.10 CKB_KP_NONE . . . 1213
13.13.2.11 CKB_KP_POSITION . . . 1213
13.13.2.12 CKB_KPMODE . . . 1213
13.13.2.13 CKB_LICENSE . . . 1213
13.13.2.14 CKB_LIVEPARAMS . . . 1213
13.13.2.15 CKB_MAX_WORD . . . 1213
13.13.2.16 CKB_NAME . . . 1214
13.13.2.17 CKB_PARAM . . . 1214
13.13.2.18 CKB_PARAM_AGRADIENT . . . 1214
13.13.2.19 CKB_PARAM_ANGLE . . . 1214
13.13.2.20 CKB_PARAM_ARGB . . . 1214
13.13.2.21 CKB_PARAM_BOOL . . . 1214
13.13.2.22 CKB_PARAM_DOUBLE . . . 1214
13.13.2.23 CKB_PARAM_GRADIENT . . . 1214

13.13.2.24 CKB_PARAM_LABEL . . . 1214
13.13.2.25 CKB_PARAM_LONG . . . 1214
13.13.2.26 CKB_PARAM_RGB . . . 1215
13.13.2.27 CKB_PARAM_STRING . . . 1215
13.13.2.28 CKB_PARSE_AGRADIENT . . . 1215
13.13.2.29 CKB_PARSE_ANGLE . . . 1215
13.13.2.30 CKB_PARSE_ARGB . . . 1215
13.13.2.31 CKB_PARSE_BOOL . . . 1215
13.13.2.32 CKB_PARSE_DOUBLE . . . 1215
13.13.2.33 CKB_PARSE_GRADIENT . . . 1215
13.13.2.34 CKB_PARSE_LONG . . . 1215
13.13.2.35 CKB_PARSE_RGB . . . 1215
13.13.2.36 CKB_PARSE_STRING . . . 1216
13.13.2.37 CKB_PREEMPT . . . 1216
13.13.2.38 CKB_PRESET_END . . . 1216
13.13.2.39 CKB_PRESET_PARAM . . . 1216
13.13.2.40 CKB_PRESET_START . . . 1216
13.13.2.41 CKB_REAL_ANGLE . . . 1216
13.13.2.42 CKB_REPEAT . . . 1216
13.13.2.43 CKB_TIME_ABSOLUTE . . . 1216
13.13.2.44 CKB_TIME_DURATION . . . 1216
13.13.2.45 CKB_TIMEMODE . . . 1216
13.13.2.46 CKB_UP . . . 1216
13.13.2.47 CKB_VERSION . . . 1216
13.13.2.48 FALSE . . . 1217
13.13.2.49 M_PI . . . 1217
13.13.2.50 TRUE . . . 1217
13.13.3 Function Documentation . . . 1217
13.13.3.1 ckb_alpha_blend . . . 1217
13.13.3.2 ckb_frame . . . 1217
13.13.3.3 ckb_getline . . . 1217
13.13.3.4 ckb_grad_color . . . 1218
13.13.3.5 ckb_info . . . 1219
13.13.3.6 ckb_init . . . 1219
13.13.3.7 ckb_keypress . . . 1219
13.13.3.8 ckb_parameter . . . 1220
13.13.3.9 ckb_read_params . . . 1220
13.13.3.10 ckb_scan_grad . . . 1221
13.13.3.11 ckb_start . . . 1221
13.13.3.12 ckb_time . . . 1222

13.13.3.13 main . . . 1222
13.13.3.14 printurl . . . 1224
13.13.3.15 urldecode . . . 1225
13.14 src/ckb/ckbsettings.cpp File Reference . . . 1226
13.14.1 Macro Definition Documentation . . . 1226
13.14.1.1 lockMutex . . . 1226
13.14.1.2 lockMutexCache . . . 1227
13.14.1.3 lockMutexStatic . . . 1227
13.14.1.4 lockMutexStatic2 . . . 1227
13.14.2 Function Documentation . . . 1227
13.14.2.1 cacheWritesInProgress . . . 1227
13.14.2.2 globalSettings . . . 1227
13.14.2.3 settingsCacheMutex . . . 1228
13.14.2.4 settingsMutex . . . 1228
13.14.3 Variable Documentation . . . 1228
13.14.3.1 _globalSettings . . . 1228
13.14.3.2 globalCache . . . 1228
13.14.3.3 globalThread . . . 1228
13.15 src/ckb/ckbsettings.h File Reference . . . 1228
13.16 src/ckb/ckbsettingswriter.cpp File Reference . . . 1229
13.16.1 Macro Definition Documentation . . . 1230
13.16.1.1 lockMutex . . . 1230
13.16.1.2 lockMutexCache . . . 1230
13.16.1.3 lockMutexStatic . . . 1230
13.16.1.4 lockMutexStatic2 . . . 1230
13.16.2 Variable Documentation . . . 1231
13.16.2.1 cacheWritesInProgress . . . 1231
13.16.2.2 settingsCacheMutex . . . 1231
13.16.2.3 settingsMutex . . . 1231
13.17 src/ckb/ckbsettingswriter.h File Reference . . . 1231
13.18 src/ckb/colorbutton.cpp File Reference . . . 1231
13.19 src/ckb/colorbutton.h File Reference . . . 1232
13.20 src/ckb/colormap.cpp File Reference . . . 1233
13.20.1 Function Documentation . . . 1233
13.20.1.1 qs_strcmp . . . 1233
13.21 src/ckb/colormap.h File Reference . . . 1234
13.21.1 Typedef Documentation . . . 1235
13.21.1.1 QColorMap . . . 1235
13.21.1.2 QColorMapIterator . . . 1235
13.21.1.3 QMutableColorMapIterator . . . 1235

13.22 src/ckb/extrasettingswidget.cpp File Reference . . . 1235
13.22.1 Variable Documentation . . . 1235
13.22.1.1 lastSharedDimming . . . 1235
13.23 src/ckb/extrasettingswidget.h File Reference . . . 1236
13.24 src/ckb/fwupgradedialog.cpp File Reference . . . 1236
13.24.1 Data Structure Documentation . . . 1237
13.24.1.1 struct KbId . . . 1237
13.24.2 Function Documentation . . . 1238
13.24.2.1 DIALOG_HEIGHT_MAX . . . 1238
13.24.2.2 verifyFw . . . 1238
13.24.3 Variable Documentation . . . 1239
13.24.3.1 DIALOG_HEIGHT_MIN . . . 1239
13.24.3.2 DIALOG_WIDTH . . . 1239
13.24.3.3 ids . . . 1239
13.25 src/ckb/fwupgradedialog.h File Reference . . . 1239
13.26 src/ckb/gradientbutton.cpp File Reference . . . 1240
13.27 src/ckb/gradientbutton.h File Reference . . . 1241
13.28 src/ckb/gradientdialog.cpp File Reference . . . 1242
13.28.1 Variable Documentation . . . 1242
13.28.1.1 prefsPath . . . 1242
13.29 src/ckb/gradientdialog.h File Reference . . . 1242
13.30 src/ckb/gradientdialogwidget.cpp File Reference . . . 1243
13.31 src/ckb/gradientdialogwidget.h File Reference . . . 1243
13.32 src/ckb/kb.cpp File Reference . . . 1244
13.32.1 Variable Documentation . . . 1245
13.32.1.1 activeDevices . . . 1245
13.32.1.2 notifyPathMutex . . . 1245
13.32.1.3 notifyPaths . . . 1245
13.33 src/ckb/kb.h File Reference . . . 1245
13.34 src/ckb/kbanim.cpp File Reference . . . 1246
13.34.1 Typedef Documentation . . . 1247
13.34.1.1 blendFunc . . . 1247
13.34.2 Function Documentation . . . 1247
13.34.2.1 blendAdd . . . 1247
13.34.2.2 blendDivide . . . 1247
13.34.2.3 blendMultiply . . . 1247
13.34.2.4 blendNormal . . . 1248
13.34.2.5 blendSubtract . . . 1248
13.34.3 Variable Documentation . . . 1248
13.34.3.1 functions . . . 1248

13.35 src/ckb/kbanim.h File Reference . . . 1248
13.36 src/ckb/kbanimwidget.cpp File Reference . . . 1249
13.37 src/ckb/kbanimwidget.h File Reference . . . 1249
13.38 src/ckb/kbbind.cpp File Reference . . . 1250
13.39 src/ckb/kbbind.h File Reference . . . 1251
13.40 src/ckb/kbbindwidget.cpp File Reference . . . 1252
13.41 src/ckb/kbbindwidget.h File Reference . . . 1252
13.42 src/ckb/kbfirmware.cpp File Reference . . . 1253
13.42.1 Function Documentation . . . 1254
13.42.1.1 tableName . . . 1254
13.42.2 Variable Documentation . . . 1254
13.42.2.1 AUTO_CHECK_TIME . . . 1254
13.43 src/ckb/kbfirmware.h File Reference . . . 1254
13.44 src/ckb/kblight.cpp File Reference . . . 1255
13.44.1 Function Documentation . . . 1256
13.44.1.1 lToS . . . 1256
13.44.1.2 monoRgb . . . 1257
13.44.1.3 sToL . . . 1257
13.44.2 Variable Documentation . . . 1258
13.44.2.1 _shareDimming . . . 1258
13.44.2.2 activeLights . . . 1258
13.45 src/ckb/kblight.h File Reference . . . 1258
13.46 src/ckb/kblightwidget.cpp File Reference . . . 1259
13.47 src/ckb/kblightwidget.h File Reference . . . 1259
13.48 src/ckb/kbmanager.cpp File Reference . . . 1260
13.48.1 Variable Documentation . . . 1261
13.48.1.1 devpath . . . 1261
13.49 src/ckb/kbmanager.h File Reference . . . 1261
13.49.1 Macro Definition Documentation . . . 1262
13.49.1.1 DAEMON_UNAVAILABLE_STR . . . 1262
13.50 src/ckb/kbmode.cpp File Reference . . . 1262
13.51 src/ckb/kbmode.h File Reference . . . 1262
13.52 src/ckb/kbperf.cpp File Reference . . . 1263
13.52.1 Macro Definition Documentation . . . 1263
13.52.1.1 map_last . . . 1263
13.53 src/ckb/kbperf.h File Reference . . . 1263
13.54 src/ckb/kbprofile.cpp File Reference . . . 1264
13.55 src/ckb/kbprofile.h File Reference . . . 1265
13.56 src/ckb/kbprofiledialog.cpp File Reference . . . 1265
13.57 src/ckb/kbprofiledialog.h File Reference . . . 1266

13.58 src/ckb/kbwidget.cpp File Reference . . . 1267
13.59 src/ckb/kbwidget.h File Reference . . . 1267
13.60 src/ckb/keyaction.cpp File Reference . . . 1268
13.60.1 Variable Documentation . . . 1269
13.60.1.1 ANIM_KRSTOP . . . 1269
13.60.1.2 ANIM_ONCE . . . 1269
13.61 src/ckb/keyaction.h File Reference . . . 1269
13.62 src/ckb/keymap.cpp File Reference . . . 1270
13.62.1 Data Structure Documentation . . . 1271
13.62.1.1 struct KeyPatch . . . 1271
13.62.2 Macro Definition Documentation . . . 1272
13.62.2.1 ANSI_ENTER_H . . . 1272
13.62.2.2 ANSI_ENTER_W . . . 1272
13.62.2.3 ANSI_ENTER_X . . . 1272
13.62.2.4 ANSI_ENTER_Y . . . 1272
13.62.2.5 ANSI_LSHIFT_W . . . 1273
13.62.2.6 ANSI_LSHIFT_X . . . 1273
13.62.2.7 K65_HEIGHT . . . 1273
13.62.2.8 K65_TOP_COUNT . . . 1273
13.62.2.9 K65_WIDTH . . . 1273
13.62.2.10 K70_HEIGHT . . . 1273
13.62.2.11 K70_WIDTH . . . 1273
13.62.2.12 K70_X_START . . . 1273
13.62.2.13 K95_HEIGHT . . . 1273
13.62.2.14 K95_WIDTH . . . 1273
13.62.2.15 KEYCOUNT_K95 . . . 1274
13.62.2.16 KEYCOUNT_M65 . . . 1274
13.62.2.17 KEYCOUNT_SABRE . . . 1274
13.62.2.18 KEYCOUNT_SCIM . . . 1274
13.62.2.19 KSTRAFE_HEIGHT . . . 1274
13.62.2.20 KSTRAFE_WIDTH . . . 1274
13.62.2.21 KSTRAFE_X_START . . . 1274
13.62.2.22 M65_HEIGHT . . . 1274
13.62.2.23 M65_WIDTH . . . 1274
13.62.2.24 N_LAYOUTS . . . 1275
13.62.2.25 N_MODELS . . . 1275
13.62.2.26 NS . . . 1275
13.62.2.27 patch . . . 1275
13.62.2.28 PATCH_COUNT . . . 1275
13.62.2.29 SABRE_HEIGHT . . . 1275

13.62.2.30 SABRE_WIDTH . . . 1275
13.62.2.31 SCIM_HEIGHT . . . 1275
13.62.2.32 SCIM_WIDTH . . . 1275
13.62.3 Function Documentation . . . 1275
13.62.3.1 _patch . . . 1275
13.62.3.2 getMap . . . 1276
13.62.3.3 patchANSI . . . 1278
13.62.3.4 patchISO . . . 1279
13.62.4 Variable Documentation . . . 1279
13.62.4.1 K65TopRow . . . 1279
13.62.4.2 K95BaseMap . . . 1279
13.62.4.3 K95Keys . . . 1280
13.62.4.4 KStrafeKeys . . . 1280
13.62.4.5 M65Keys . . . 1281
13.62.4.6 patchDE . . . 1281
13.62.4.7 patchDK . . . 1281
13.62.4.8 patchDvorak . . . 1281
13.62.4.9 patchES . . . 1282
13.62.4.10 patchEU . . . 1282
13.62.4.11 patchFR . . . 1282
13.62.4.12 patchIT . . . 1282
13.62.4.13 patchMX . . . 1282
13.62.4.14 patchNO . . . 1283
13.62.4.15 patchSE . . . 1283
13.62.4.16 SabreKeys . . . 1283
13.62.4.17 ScimKeys . . . 1283
13.62.4.18 standardMaps . . . 1284
13.63 src/ckb/keymap.h File Reference . . . 1284
13.64 src/ckb/keywidget.cpp File Reference . . . 1284
13.64.1 Function Documentation . . . 1285
13.64.1.1 monoRgb . . . 1285
13.64.2 Variable Documentation . . . 1286
13.64.2.1 KEY_SIZE . . . 1286
13.64.2.2 m65Overlay . . . 1286
13.64.2.3 sabOverlay . . . 1286
13.64.2.4 scimOverlay . . . 1286
13.65 src/ckb/keywidget.h File Reference . . . 1286
13.66 src/ckb/kperfwidget.cpp File Reference . . . 1287
13.67 src/ckb/kperfwidget.h File Reference . . . 1288
13.67.1 Data Structure Documentation . . . 1288

13.67.1.1 struct KPerfWidget::IndicatorUi . . . 1289
13.68 src/ckb/layoutdialog.cpp File Reference . . . 1290
13.69 src/ckb/layoutdialog.h File Reference . . . 1290
13.70 src/ckb/macroreader.cpp File Reference . . . 1291
13.71 src/ckb/macroreader.h File Reference . . . 1291
13.72 src/ckb/main.cpp File Reference . . . 1292
13.72.1 Macro Definition Documentation . . . 1293
13.72.1.1 SHMEM_SIZE . . . 1293
13.72.1.2 SHMEM_SIZE_V015 . . . 1293
13.72.2 Enumeration Type Documentation . . . 1294
13.72.2.1 CommandLineParseResults . . . 1294
13.72.3 Function Documentation . . . 1294
13.72.3.1 appShare . . . 1294
13.72.3.2 isRunning . . . 1294
13.72.3.3 main . . . 1295
13.72.3.4 parseCommandLine . . . 1297
13.72.3.5 pidActive . . . 1298
13.73 src/ckb/mainwindow.cpp File Reference . . . 1299
13.73.1 Variable Documentation . . . 1299
13.73.1.1 appShare . . . 1299
13.73.1.2 configLabel . . . 1299
13.74 src/ckb/mainwindow.h File Reference . . . 1299
13.75 src/ckb/media.h File Reference . . . 1300
13.75.1 Macro Definition Documentation . . . 1301
13.75.1.1 ENUM_C . . . 1301
13.75.1.2 ENUM_END_C . . . 1301
13.75.1.3 EXTERN_C . . . 1301
13.75.2 Enumeration Type Documentation . . . 1301
13.75.2.1 muteState . . . 1301
13.75.3 Function Documentation . . . 1301
13.75.3.1 getMuteState . . . 1301
13.76 src/ckb/media_linux.cpp File Reference . . . 1302
13.76.1 Function Documentation . . . 1303
13.76.1.1 getMuteState . . . 1303
13.76.2 Variable Documentation . . . 1303
13.76.2.1 muteProcess . . . 1303
13.77 src/ckb/media_mac.m File Reference . . . 1303
13.77.1 Function Documentation . . . 1304
13.77.1.1 disableAppNap . . . 1304
13.77.1.2 getMuteState . . . 1304

13.78 src/ckb/modeselectdialog.cpp File Reference . . . 1305
13.79 src/ckb/modeselectdialog.h File Reference . . . 1305
13.80 src/ckb/mperfwidget.cpp File Reference . . . 1306
13.80.1 Macro Definition Documentation . . . 1307
13.80.1.1 SET_END . . . 1307
13.80.1.2 SET_START . . . 1307
13.80.2 Function Documentation . . . 1307
13.80.2.1 dpiExp . . . 1307
13.80.2.2 dpiLog . . . 1308
13.80.2.3 dpiRound . . . 1308
13.80.3 Variable Documentation . . . 1308
13.80.3.1 DPI_BASE . . . 1308
13.80.3.2 xyLinkPath . . . 1309
13.81 src/ckb/mperfwidget.h File Reference . . . 1309
13.81.1 Data Structure Documentation . . . 1310
13.81.1.1 struct MPerfWidget::DpiUi . . . 1310
13.82 src/ckb/quazip/crypt.h File Reference . . . 1311
13.82.1 Macro Definition Documentation . . . 1312
13.82.1.1 CRC32 . . . 1312
13.82.1.2 zdecode . . . 1312
13.82.1.3 zencode . . . 1312
13.82.2 Function Documentation . . . 1312
13.82.2.1 decrypt_byte . . . 1312
13.82.2.2 init_keys . . . 1312
13.82.2.3 update_keys . . . 1313
13.83 src/ckb/quazip/ioapi.h File Reference . . . 1314
13.83.1 Data Structure Documentation . . . 1316
13.83.1.1 struct zlib_filefunc_def_s . . . 1316
13.83.1.2 struct zlib_filefunc64_def_s . . . 1316
13.83.1.3 struct zlib_filefunc64_32_def_s . . . 1317
13.83.2 Macro Definition Documentation . . . 1317
13.83.2.1 __USE_FILE_OFFSET64 . . . 1317
13.83.2.2 __USE_LARGEFILE64 . . . 1317
13.83.2.3 _FILE_OFFSET_BIT . . . 1318
13.83.2.4 _LARGEFILE64_SOURCE . . . 1318
13.83.2.5 OF . . . 1318
13.83.2.6 ZCALLBACK . . . 1318
13.83.2.7 ZCLOSE64 . . . 1318
13.83.2.8 ZERROR64 . . . 1318
13.83.2.9 ZFAKECLOSE64 . . . 1318

13.83.2.10 ZLIB_FILEFUNC_MODE_CREATE . . . 1318
13.83.2.11 ZLIB_FILEFUNC_MODE_EXISTING . . . 1318
13.83.2.12 ZLIB_FILEFUNC_MODE_READ . . . 1318
13.83.2.13 ZLIB_FILEFUNC_MODE_READWRITEFILTER . . . 1319
13.83.2.14 ZLIB_FILEFUNC_MODE_WRITE . . . 1319
13.83.2.15 ZLIB_FILEFUNC_SEEK_CUR . . . 1319
13.83.2.16 ZLIB_FILEFUNC_SEEK_END . . . 1319
13.83.2.17 ZLIB_FILEFUNC_SEEK_SET . . . 1319
13.83.2.18 ZOPEN64 . . . 1319
13.83.2.19 ZREAD64 . . . 1319
13.83.2.20 ZSEEK64 . . . 1319
13.83.2.21 ZTELL64 . . . 1320
13.83.2.22 ZWRITE64 . . . 1320
13.83.3 Typedef Documentation . . . 1320
13.83.3.1 _Z_OF . . . 1320
13.83.3.2 zlib_filefunc64_32_def . . . 1320
13.83.3.3 zlib_filefunc64_def . . . 1320
13.83.3.4 zlib_filefunc_def . . . 1320
13.83.3.5 ZPOS64_T . . . 1320
13.83.4 Function Documentation . . . 1320
13.83.4.1 _Z_OF . . . 1320
13.83.4.2 _Z_OF . . . 1320
13.83.4.3 _Z_OF . . . 1320
13.83.4.4 _Z_OF . . . 1320
13.83.4.5 _Z_OF . . . 1320
13.83.4.6 fill_zlib_filefunc64_32_def_from_filefunc32 . . . 1321
13.84 src/ckb/quazip/JlCompress.cpp File Reference . . . 1321
13.84.1 Function Documentation . . . 1322
13.84.1.1 copyData . . . 1322
13.85 src/ckb/quazip/JlCompress.h File Reference . . . 1323
13.86 src/ckb/quazip/qioapi.cpp File Reference . . . 1323
13.86.1 Macro Definition Documentation . . . 1325
13.86.1.1 SEEK_CUR . . . 1325
13.86.1.2 SEEK_END . . . 1325
13.86.1.3 SEEK_SET . . . 1325
13.86.2 Function Documentation . . . 1325
13.86.2.1 call_zopen64 . . . 1325
13.86.2.2 call_zseek64 . . . 1325
13.86.2.3 call_ztell64 . . . 1325
13.86.2.4 fill_qiodevice64_filefunc . . . 1326

13.86.2.5 fill_qiodevice_filefunc . . . 1327
13.86.2.6 fill_zlib_filefunc64_32_def_from_filefunc32 . . . 1328
13.86.2.7 qiodevice64_seek_file_func . . . 1329
13.86.2.8 qiodevice64_tell_file_func . . . 1330
13.86.2.9 qiodevice_close_file_func . . . 1330
13.86.2.10 qiodevice_error_file_func . . . 1331
13.86.2.11 qiodevice_fakeclose_file_func . . . 1331
13.86.2.12 qiodevice_open_file_func . . . 1332
13.86.2.13 qiodevice_read_file_func . . . 1333
13.86.2.14 qiodevice_seek_file_func . . . 1333
13.86.2.15 qiodevice_tell_file_func . . . 1334
13.86.2.16 qiodevice_write_file_func . . . 1335
13.87 src/ckb/quazip/quaadler32.cpp File Reference . . . 1335
13.88 src/ckb/quazip/quaadler32.h File Reference . . . 1336
13.89 src/ckb/quazip/quachecksum32.h File Reference . . . 1337
13.90 src/ckb/quazip/quacrc32.cpp File Reference . . . 1338
13.91 src/ckb/quazip/quacrc32.h File Reference . . . 1339
13.92 src/ckb/quazip/quagzipfile.cpp File Reference . . . 1340
13.93 src/ckb/quazip/quagzipfile.h File Reference . . . 1341
13.94 src/ckb/quazip/quaziodevice.cpp File Reference . . . 1342
13.94.1 Macro Definition Documentation . . . 1343
13.94.1.1 QUAZIO_INBUFSIZE . . . 1343
13.94.1.2 QUAZIO_OUTBUFSIZE . . . 1343
13.95 src/ckb/quazip/quaziodevice.h File Reference . . . 1343
13.96 src/ckb/quazip/quazip.cpp File Reference . . . 1344
13.96.1 Function Documentation . . . 1345
13.96.1.1 QuaZip_getFileInfo . . . 1345
13.96.1.2 QuaZip_getFileInfo . . . 1345
13.96.1.3 QuaZip_getFileInfo . . . 1346
13.96.1.4 QuaZip_getFileInfo . . . 1346
13.97 src/ckb/quazip/quazip.h File Reference . . . 1346
13.97.1 Macro Definition Documentation . . . 1347
13.97.1.1 UNZ_OPENERROR . . . 1347
13.98 src/ckb/quazip/quazip_global.h File Reference . . . 1347
13.98.1 Macro Definition Documentation . . . 1348
13.98.1.1 QUAZIP_EXPORT . . . 1348
13.98.1.2 QUAZIP_EXTRA_NTFS_MAGIC . . . 1348
13.98.1.3 QUAZIP_EXTRA_NTFS_TIME_MAGIC . . . 1348
13.98.1.4 UNUSED . . . 1349
13.99 src/ckb/quazip/quazipdir.cpp File Reference . . . 1349

13.99.1 Function Documentation . . . 1349
13.99.1.1 QuaZipDir_convertInfoList . . . 1349
13.99.1.2 QuaZipDir_convertInfoList . . . 1349
13.99.1.3 QuaZipDir_convertInfoList . . . 1350
13.99.1.4 QuaZipDir_getFileInfo . . . 1350
13.100 src/ckb/quazip/quazipdir.h File Reference . . . 1351
13.101 src/ckb/quazip/quazipfile.cpp File Reference . . . 1351
13.102 src/ckb/quazip/quazipfile.h File Reference . . . 1352
13.103 src/ckb/quazip/quazipfileinfo.cpp File Reference . . . 1353
13.103.1 Function Documentation . . . 1353
13.103.1.1 getNTFSTime . . . 1354
13.103.1.2 permissionsFromExternalAttr . . . 1355
13.104 src/ckb/quazip/quazipfileinfo.h File Reference . . . 1355
13.105 src/ckb/quazip/quazipnewinfo.cpp File Reference . . . 1356
13.105.1 Function Documentation . . . 1357
13.105.1.1 QuaZipNewInfo_init . . . 1357
13.105.1.2 QuaZipNewInfo_setPermissions . . . 1358
13.105.1.3 setNTFSTime . . . 1358
13.106 src/ckb/quazip/quazipnewinfo.h File Reference . . . 1360
13.107 src/ckb/quazip/unzip.c File Reference . . . 1361
13.107.1 Data Structure Documentation . . . 1364
13.107.1.1 struct unz_file_info64_internal_s . . . 1364
13.107.1.2 struct file_in_zip64_read_info_s . . . 1365
13.107.1.3 struct unz64_s . . . 1365
13.107.2 Macro Definition Documentation . . . 1366
13.107.2.1 ALLOC . . . 1366
13.107.2.2 BUFREADCOMMENT . . . 1367
13.107.2.3 CASESENSITIVITYDEFAULT_NO . . . 1367
13.107.2.4 CASESENSITIVITYDEFAULTVALUE . . . 1367
13.107.2.5 local . . . 1367
13.107.2.6 SIZECENTRALDIRITEM . . . 1367
13.107.2.7 SIZEZIPLOCALHEADER . . . 1367
13.107.2.8 STRCMPCASENOSENTIVEFUNCTION . . . 1367
13.107.2.9 TRYFREE . . . 1367
13.107.2.10 UNZ_BUFSIZE . . . 1367
13.107.2.11 UNZ_MAXFILENAMEINZIP . . . 1368
13.107.3 Typedef Documentation . . . 1368
13.107.3.1 unz_file_info64_internal . . . 1368
13.107.3.2 z_crc_t . . . 1368
13.107.4 Function Documentation . . . 1368

13.107.4.1 _Z_OF . . . 1368
13.107.4.2 _Z_OF . . . 1368
13.107.4.3 _Z_OF . . . 1368
13.107.4.4 _Z_OF . . . 1368
13.107.4.5 _Z_OF . . . 1368
13.107.4.6 strcmpcasenosensitive_internal . . . 1368
13.107.4.7 unz64local_CheckCurrentFileCoherencyHeader . . . 1368
13.107.4.8 unz64local_DosDateToTmuDate . . . 1370
13.107.4.9 unz64local_getByte . . . 1371
13.107.4.10 unz64local_GetCurrentFileInfoInternal . . . 1372
13.107.4.11 unz64local_getLong . . . 1375
13.107.4.12 unz64local_getLong64 . . . 1376
13.107.4.13 unz64local_getShort . . . 1378
13.107.4.14 unz64local_SearchCentralDir . . . 1379
13.107.4.15 unz64local_SearchCentralDir64 . . . 1380
13.107.4.16 unzClearFlags . . . 1381
13.107.4.17 unzClose . . . 1382
13.107.4.18 unzCloseCurrentFile . . . 1383
13.107.4.19 unzeof . . . 1384
13.107.4.20 unzGetCurrentFileInfo . . . 1384
13.107.4.21 unzGetCurrentFileInfo64 . . . 1385
13.107.4.22 unzGetCurrentFileZStreamPos64 . . . 1386
13.107.4.23 unzGetFilePos . . . 1386
13.107.4.24 unzGetFilePos64 . . . 1387
13.107.4.25 unzGetGlobalComment . . . 1387
13.107.4.26 unzGetGlobalInfo . . . 1388
13.107.4.27 unzGetGlobalInfo64 . . . 1388
13.107.4.28 unzGetLocalExtrafield . . . 1389
13.107.4.29 unzGetOffset . . . 1390
13.107.4.30 unzGetOffset64 . . . 1390
13.107.4.31 unzGoToFilePos . . . 1391
13.107.4.32 unzGoToFilePos64 . . . 1391
13.107.4.33 unzGoToFirstFile . . . 1392
13.107.4.34 unzGoToNextFile . . . 1393
13.107.4.35 unzLocateFile . . . 1394
13.107.4.36 unzOpen . . . 1395
13.107.4.37 unzOpen2 . . . 1395
13.107.4.38 unzOpen2_64 . . . 1396
13.107.4.39 unzOpen64 . . . 1397
13.107.4.40 unzOpenCurrentFile . . . 1398

13.107.4.41 unzOpenCurrentFile2 . . . 1398
13.107.4.42 unzOpenCurrentFile3 . . . 1398
13.107.4.43 unzOpenCurrentFilePassword . . . 1401
13.107.4.44 unzOpenInternal . . . 1402
13.107.4.45 unzReadCurrentFile . . . 1405
13.107.4.46 unzSetFlags . . . 1408
13.107.4.47 unzSetOffset . . . 1409
13.107.4.48 unzSetOffset64 . . . 1409
13.107.4.49 unzStringFileNameCompare . . . 1410
13.107.4.50 unztell . . . 1410
13.107.4.51 unztell64 . . . 1411
13.107.5 Variable Documentation . . . 1411
13.107.5.1 unz_copyright . . . 1411
13.108 src/ckb/quazip/unzip.h File Reference . . . 1412
13.108.1 Data Structure Documentation . . . 1414
13.108.1.1 struct tm_unz_s . . . 1414
13.108.1.2 struct unz_global_info64_s . . . 1414
13.108.1.3 struct unz_global_info_s . . . 1415
13.108.1.4 struct unz_file_info64_s . . . 1416
13.108.1.5 struct unz_file_info_s . . . 1417
13.108.1.6 struct unz_file_pos_s . . . 1419
13.108.1.7 struct unz64_file_pos_s . . . 1420
13.108.2 Macro Definition Documentation . . . 1420
13.108.2.1 UNZ_AUTO_CLOSE . . . 1420
13.108.2.2 UNZ_BADZIPFILE . . . 1420
13.108.2.3 UNZ_CRCERROR . . . 1420
13.108.2.4 UNZ_DEFAULT_FLAGS . . . 1421
13.108.2.5 UNZ_END_OF_LIST_OF_FILE . . . 1421
13.108.2.6 UNZ_EOF . . . 1421
13.108.2.7 UNZ_ERRNO . . . 1421
13.108.2.8 UNZ_INTERNALERROR . . . 1421
13.108.2.9 UNZ_OK . . . 1421
13.108.2.10 UNZ_PARAMERROR . . . 1421
13.108.2.11 Z_BZIP2ED . . . 1422
13.108.3 Typedef Documentation . . . 1422
13.108.3.1 tm_unz . . . 1422
13.108.3.2 unz64_file_pos . . . 1422
13.108.3.3 unz_file_info . . . 1422
13.108.3.4 unz_file_info64 . . . 1422
13.108.3.5 unz_file_pos . . . 1422

13.108.3.6 unz_global_info . . . 1422
13.108.3.7 unz_global_info64 . . . 1422
13.108.3.8 unzFile . . . 1422
13.108.4 Function Documentation . . . 1422
13.108.4.1 _Z_OF . . . 1422
13.108.4.2 _Z_OF . . . 1422
13.108.4.3 _Z_OF . . . 1422
13.108.4.4 _Z_OF . . . 1422
13.108.4.5 _Z_OF . . . 1422
13.108.4.6 _Z_OF . . . 1422
13.108.4.7 _Z_OF . . . 1422
13.108.4.8 _Z_OF . . . 1422
13.108.4.9 _Z_OF . . . 1422
13.108.4.10 _Z_OF . . . 1422
13.108.4.11 _Z_OF . . . 1423
13.108.4.12 _Z_OF . . . 1423
13.108.4.13 _Z_OF . . . 1423
13.108.4.14 _Z_OF . . . 1423
13.108.4.15 _Z_OF . . . 1423
13.108.4.16 unzClearFlags . . . 1423
13.108.4.17 unzGetFilePos . . . 1423
13.108.4.18 unzGetFilePos64 . . . 1424
13.108.4.19 unzGetOffset . . . 1424
13.108.4.20 unzGetOffset64 . . . 1425
13.108.4.21 unzGoToFilePos . . . 1425
13.108.4.22 unzGoToFilePos64 . . . 1426
13.108.4.23 unzOpenInternal . . . 1427
13.108.4.24 unzSetFlags . . . 1430
13.108.4.25 unzSetOffset . . . 1431
13.108.4.26 unzSetOffset64 . . . 1431
13.109 src/ckb/quazip/zip.c File Reference . . . 1432
13.109.1 Data Structure Documentation . . . 1435
13.109.1.1 struct linkedlist_datablock_internal_s . . . 1435
13.109.1.2 struct linkedlist_data_s . . . 1436
13.109.1.3 struct curfile64_info . . . 1437
13.109.1.4 struct zip64_internal . . . 1438
13.109.2 Macro Definition Documentation . . . 1438
13.109.2.1 ALLOC . . . 1439
13.109.2.2 BUFREADCOMMENT . . . 1439
13.109.2.3 CENTRALHEADERMAGIC . . . 1439

13.109.2.4 CRC_LOCALHEADER_OFFSET . . . 1439
13.109.2.5 DESCRIPTORHEADERMAGIC . . . 1439
13.109.2.6 ENDHEADERMAGIC . . . 1439
13.109.2.7 FLAG_LOCALHEADER_OFFSET . . . 1439
13.109.2.8 INCLUDECRYPTINGCODE_IFCRYPTALLOWED . . . 1439
13.109.2.9 local . . . 1439
13.109.2.10 LOCALHEADERMAGIC . . . 1439
13.109.2.11 MAKEULONG64 . . . 1440
13.109.2.12 SEEK_CUR . . . 1440
13.109.2.13 SEEK_END . . . 1440
13.109.2.14 SEEK_SET . . . 1440
13.109.2.15 SIZECENTRALHEADER . . . 1440
13.109.2.16 SIZEDATA_INDATABLOCK . . . 1440
13.109.2.17 TRYFREE . . . 1440
13.109.2.18 VERSIONMADEBY . . . 1440
13.109.2.19 Z_BUFSIZE . . . 1440
13.109.2.20 Z_MAXFILENAMEINZIP . . . 1440
13.109.2.21 ZIP64ENDHEADERMAGIC . . . 1441
13.109.2.22 ZIP64ENDLOCHEADERMAGIC . . . 1441
13.109.3 Typedef Documentation . . . 1441
13.109.3.1 linkedlist_data . . . 1441
13.109.3.2 linkedlist_datablock_internal . . . 1441
13.109.3.3 z_crc_t . . . 1441
13.109.4 Function Documentation . . . 1441
13.109.4.1 _Z_OF . . . 1441
13.109.4.2 _Z_OF . . . 1441
13.109.4.3 _Z_OF . . . 1441
13.109.4.4 _Z_OF . . . 1441
13.109.4.5 _Z_OF . . . 1441
13.109.4.6 _Z_OF . . . 1441
13.109.4.7 add_data_in_datablock . . . 1441
13.109.4.8 allocate_new_datablock . . . 1443
13.109.4.9 free_datablock . . . 1443
13.109.4.10 free_linkedlist . . . 1444
13.109.4.11 init_linkedlist . . . 1444
13.109.4.12 LoadCentralDirectoryRecord . . . 1445
13.109.4.13 Write_EndOfCentralDirectoryRecord . . . 1448
13.109.4.14 Write_GlobalComment . . . 1450
13.109.4.15 Write_LocalFileHeader . . . 1450
13.109.4.16 Write_Zip64EndOfCentralDirectoryLocator . . . 1452

13.109.4.17 Write_Zip64EndOfCentralDirectoryRecord . . . 1453
13.109.4.18 zip64FlushWriteBuffer . . . 1455
13.109.4.19 zip64local_getByte . . . 1455
13.109.4.20 zip64local_getLong . . . 1456
13.109.4.21 zip64local_getLong64 . . . 1457
13.109.4.22 zip64local_getShort . . . 1458
13.109.4.23 zip64local_putValue . . . 1459
13.109.4.24 zip64local_putValue_inmemory . . . 1460
13.109.4.25 zip64local_SearchCentralDir . . . 1460
13.109.4.26 zip64local_SearchCentralDir64 . . . 1461
13.109.4.27 zip64local_TmzDateToDosDate . . . 1463
13.109.4.28 zipClearFlags . . . 1464
13.109.4.29 zipClose . . . 1464
13.109.4.30 zipCloseFileInZip . . . 1466
13.109.4.31 zipCloseFileInZipRaw . . . 1467
13.109.4.32 zipCloseFileInZipRaw64 . . . 1468
13.109.4.33 zipOpen . . . 1472
13.109.4.34 zipOpen2 . . . 1472
13.109.4.35 zipOpen2_64 . . . 1473
13.109.4.36 zipOpen3 . . . 1474
13.109.4.37 zipOpen64 . . . 1476
13.109.4.38 zipOpenNewFileInZip . . . 1477
13.109.4.39 zipOpenNewFileInZip2 . . . 1477
13.109.4.40 zipOpenNewFileInZip2_64 . . . 1478
13.109.4.41 zipOpenNewFileInZip3 . . . 1478
13.109.4.42 zipOpenNewFileInZip3_64 . . . 1479
13.109.4.43 zipOpenNewFileInZip4 . . . 1479
13.109.4.44 zipOpenNewFileInZip4_64 . . . 1480
13.109.4.45 zipOpenNewFileInZip64 . . . 1484
13.109.4.46 zipRemoveExtraInfoBlock . . . 1484
13.109.4.47 zipSetFlags . . . 1485
13.109.4.48 zipWriteInFileInZip . . . 1486
13.109.5 Variable Documentation . . . 1488
13.109.5.1 zip_copyright . . . 1488
13.110 src/ckb/quazip/zip.h File Reference . . . 1488
13.110.1 Data Structure Documentation . . . 1490
13.110.1.1 struct tm_zip_s . . . 1490
13.110.1.2 struct zip_fileinfo . . . 1491
13.110.2 Macro Definition Documentation . . . 1492
13.110.2.1 APPEND_STATUS_ADDINZIP . . . 1492

13.110.2.2 APPEND_STATUS_CREATE . . . 1492
13.110.2.3 APPEND_STATUS_CREATEAFTER . . . 1493
13.110.2.4 DEF_MEM_LEVEL . . . 1493
13.110.2.5 Z_BZIP2ED . . . 1493
13.110.2.6 ZIP_AUTO_CLOSE . . . 1493
13.110.2.7 ZIP_BADZIPFILE . . . 1493
13.110.2.8 ZIP_DEFAULT_FLAGS . . . 1493
13.110.2.9 ZIP_EOF . . . 1493
13.110.2.10 ZIP_ERRNO . . . 1493
13.110.2.11 ZIP_INTERNALERROR . . . 1493
13.110.2.12 ZIP_OK . . . 1494
13.110.2.13 ZIP_PARAMERROR . . . 1494
13.110.2.14 ZIP_SEQUENTIAL . . . 1494
13.110.2.15 ZIP_WRITE_DATA_DESCRIPTOR . . . 1494
13.110.3 Typedef Documentation . . . 1494
13.110.3.1 tm_zip . . . 1494
13.110.3.2 zipcharpc . . . 1494
13.110.3.3 zipFile . . . 1494
13.110.4 Function Documentation . . . 1494
13.110.4.1 _Z_OF . . . 1494
13.110.4.2 _Z_OF . . . 1494
13.110.4.3 _Z_OF . . . 1494
13.110.4.4 _Z_OF . . . 1495
13.110.4.5 _Z_OF . . . 1495
13.110.4.6 _Z_OF . . . 1495
13.110.4.7 _Z_OF . . . 1495
13.110.4.8 _Z_OF . . . 1495
13.110.4.9 _Z_OF . . . 1495
13.110.4.10 _Z_OF . . . 1495
13.110.4.11 _Z_OF . . . 1495
13.110.4.12 _Z_OF . . . 1495
13.110.4.13 _Z_OF . . . 1495
13.110.4.14 _Z_OF . . . 1495
13.110.4.15 _Z_OF . . . 1495
13.110.4.16 _Z_OF . . . 1495
13.110.4.17 _Z_OF . . . 1495
13.110.4.18 zipClearFlags . . . 1495
13.110.4.19 zipOpen3 . . . 1496
13.110.4.20 zipSetFlags . . . 1498
13.111 src/ckb/rebindwidget.cpp File Reference . . . 1499

13.111.1 Variable Documentation . . . 1499
13.111.1.1 DPI_CUST_IDX . . . 1499
13.111.1.2 DPI_OFFSET . . . 1499
13.112 src/ckb/rebindwidget.h File Reference . . . 1499
13.113 src/ckb/release/moc_animadddialog.cpp File Reference . . . 1500
13.113.1 Data Structure Documentation . . . 1501
13.113.1.1 struct qt_meta_stringdata_AnimAddDialog_t . . . 1501
13.113.2 Macro Definition Documentation . . . 1502
13.113.2.1 QT_MOC_LITERAL . . . 1502
13.113.3 Variable Documentation . . . 1502
13.113.3.1 qt_meta_data_AnimAddDialog . . . 1502
13.113.3.2 qt_meta_stringdata_AnimAddDialog . . . 1503
13.114 src/ckb/release/moc_animscript.cpp File Reference . . . 1503
13.114.1 Data Structure Documentation . . . 1504
13.114.1.1 struct qt_meta_stringdata_AnimScript_t . . . 1504
13.114.2 Macro Definition Documentation . . . 1505
13.114.2.1 QT_MOC_LITERAL . . . 1505
13.114.3 Variable Documentation . . . 1505
13.114.3.1 qt_meta_data_AnimScript . . . 1505
13.114.3.2 qt_meta_stringdata_AnimScript . . . 1506
13.115 src/ckb/release/moc_animsettingdialog.cpp File Reference . . . 1506
13.115.1 Data Structure Documentation . . . 1507
13.115.1.1 struct qt_meta_stringdata_AnimSettingDialog_t . . . 1507
13.115.2 Macro Definition Documentation . . . 1507
13.115.2.1 QT_MOC_LITERAL . . . 1507
13.115.3 Variable Documentation . . . 1508
13.115.3.1 qt_meta_data_AnimSettingDialog . . . 1508
13.115.3.2 qt_meta_stringdata_AnimSettingDialog . . . 1508
13.116 src/ckb/release/moc_ckbsettingswriter.cpp File Reference . . . 1509
13.116.1 Data Structure Documentation . . . 1509
13.116.1.1 struct qt_meta_stringdata_CkbSettingsWriter_t . . . 1509
13.116.2 Macro Definition Documentation . . . 1510
13.116.2.1 QT_MOC_LITERAL . . . 1510
13.116.3 Variable Documentation . . . 1510
13.116.3.1 qt_meta_data_CkbSettingsWriter . . . 1510
13.116.3.2 qt_meta_stringdata_CkbSettingsWriter . . . 1511
13.117 src/ckb/release/moc_colorbutton.cpp File Reference . . . 1511
13.117.1 Data Structure Documentation . . . 1512
13.117.1.1 struct qt_meta_stringdata_ColorButton_t . . . 1512
13.117.2 Macro Definition Documentation . . . 1512

13.117.2.1 QT_MOC_LITERAL . . . 1512
13.117.3 Variable Documentation . . . 1513
13.117.3.1 qt_meta_data_ColorButton . . . 1513
13.117.3.2 qt_meta_stringdata_ColorButton . . . 1513
13.118 src/ckb/release/moc_extrasettingswidget.cpp File Reference . . . 1513
13.118.1 Data Structure Documentation . . . 1514
13.118.1.1 struct qt_meta_stringdata_ExtraSettingsWidget_t . . . 1514
13.118.2 Macro Definition Documentation . . . 1515
13.118.2.1 QT_MOC_LITERAL . . . 1515
13.118.3 Variable Documentation . . . 1515
13.118.3.1 qt_meta_data_ExtraSettingsWidget . . . 1515
13.118.3.2 qt_meta_stringdata_ExtraSettingsWidget . . . 1515
13.119 src/ckb/release/moc_fwupgradedialog.cpp File Reference . . . 1516
13.119.1 Data Structure Documentation . . . 1517
13.119.1.1 struct qt_meta_stringdata_FwUpgradeDialog_t . . . 1517
13.119.2 Macro Definition Documentation . . . 1518
13.119.2.1 QT_MOC_LITERAL . . . 1518
13.119.3 Variable Documentation . . . 1518
13.119.3.1 qt_meta_data_FwUpgradeDialog . . . 1518
13.119.3.2 qt_meta_stringdata_FwUpgradeDialog . . . 1519
13.120 src/ckb/release/moc_gradientbutton.cpp File Reference . . . 1519
13.120.1 Data Structure Documentation . . . 1520
13.120.1.1 struct qt_meta_stringdata_GradientButton_t . . . 1520
13.120.2 Macro Definition Documentation . . . 1521
13.120.2.1 QT_MOC_LITERAL . . . 1521
13.120.3 Variable Documentation . . . 1521
13.120.3.1 qt_meta_data_GradientButton . . . 1521
13.120.3.2 qt_meta_stringdata_GradientButton . . . 1522
13.121 src/ckb/release/moc_gradientdialog.cpp File Reference . . . 1522
13.121.1 Data Structure Documentation . . . 1523
13.121.1.1 struct qt_meta_stringdata_GradientDialog_t . . . 1523
13.121.2 Macro Definition Documentation . . . 1523
13.121.2.1 QT_MOC_LITERAL . . . 1523
13.121.3 Variable Documentation . . . 1524
13.121.3.1 qt_meta_data_GradientDialog . . . 1524
13.121.3.2 qt_meta_stringdata_GradientDialog . . . 1524
13.122 src/ckb/release/moc_gradientdialogwidget.cpp File Reference . . . 1525
13.122.1 Data Structure Documentation . . . 1525
13.122.1.1 struct qt_meta_stringdata_GradientDialogWidget_t . . . 1525
13.122.2 Macro Definition Documentation . . . 1526

13.122.2.1 QT_MOC_LITERAL . . . 1526
13.122.3 Variable Documentation . . . 1526
13.122.3.1 qt_meta_data_GradientDialogWidget . . . 1526
13.122.3.2 qt_meta_stringdata_GradientDialogWidget . . . 1527
13.123 src/ckb/release/moc_kb.cpp File Reference . . . 1527
13.123.1 Data Structure Documentation . . . 1528
13.123.1.1 struct qt_meta_stringdata_Kb_t . . . 1528
13.123.2 Macro Definition Documentation . . . 1529
13.123.2.1 QT_MOC_LITERAL . . . 1529
13.123.3 Variable Documentation . . . 1529
13.123.3.1 qt_meta_data_Kb . . . 1529
13.123.3.2 qt_meta_stringdata_Kb . . . 1529
13.124 src/ckb/release/moc_kbanim.cpp File Reference . . . 1530
13.124.1 Data Structure Documentation . . . 1530
13.124.1.1 struct qt_meta_stringdata_KbAnim_t . . . 1530
13.124.2 Macro Definition Documentation . . . 1531
13.124.2.1 QT_MOC_LITERAL . . . 1531
13.124.3 Variable Documentation . . . 1531
13.124.3.1 qt_meta_data_KbAnim . . . 1531
13.124.3.2 qt_meta_stringdata_KbAnim . . . 1532
13.125 src/ckb/release/moc_kbanimwidget.cpp File Reference . . . 1532
13.125.1 Data Structure Documentation . . . 1533
13.125.1.1 struct qt_meta_stringdata_KbAnimWidget_t . . . 1533
13.125.2 Macro Definition Documentation . . . 1534
13.125.2.1 QT_MOC_LITERAL . . . 1534
13.125.3 Variable Documentation . . . 1534
13.125.3.1 qt_meta_data_KbAnimWidget . . . 1534
13.125.3.2 qt_meta_stringdata_KbAnimWidget . . . 1534
13.126 src/ckb/release/moc_kbbind.cpp File Reference . . . 1535
13.126.1 Data Structure Documentation . . . 1535
13.126.1.1 struct qt_meta_stringdata_KbBind_t . . . 1535
13.126.2 Macro Definition Documentation . . . 1536
13.126.2.1 QT_MOC_LITERAL . . . 1536
13.126.3 Variable Documentation . . . 1536
13.126.3.1 qt_meta_data_KbBind . . . 1536
13.126.3.2 qt_meta_stringdata_KbBind . . . 1536
13.127 src/ckb/release/moc_kbbindwidget.cpp File Reference . . . 1537
13.127.1 Data Structure Documentation . . . 1538
13.127.1.1 struct qt_meta_stringdata_KbBindWidget_t . . . 1538
13.127.2 Macro Definition Documentation . . . 1538

13.127.2.1 QT_MOC_LITERAL . . . 1538
13.127.3 Variable Documentation . . . 1539
13.127.3.1 qt_meta_data_KbBindWidget . . . 1539
13.127.3.2 qt_meta_stringdata_KbBindWidget . . . 1539
13.128 src/ckb/release/moc_kbfirmware.cpp File Reference . . . 1539
13.128.1 Data Structure Documentation . . . 1540
13.128.1.1 struct qt_meta_stringdata_KbFirmware_t . . . 1540
13.128.2 Macro Definition Documentation . . . 1541
13.128.2.1 QT_MOC_LITERAL . . . 1541
13.128.3 Variable Documentation . . . 1541
13.128.3.1 qt_meta_data_KbFirmware . . . 1541
13.128.3.2 qt_meta_stringdata_KbFirmware . . . 1542
13.129 src/ckb/release/moc_kblight.cpp File Reference . . . 1542
13.129.1 Data Structure Documentation . . . 1543
13.129.1.1 struct qt_meta_stringdata_KbLight_t . . . 1543
13.129.2 Macro Definition Documentation . . . 1544
13.129.2.1 QT_MOC_LITERAL . . . 1544
13.129.3 Variable Documentation . . . 1544
13.129.3.1 qt_meta_data_KbLight . . . 1544
13.129.3.2 qt_meta_stringdata_KbLight . . . 1545
13.130 src/ckb/release/moc_kblightwidget.cpp File Reference . . . 1545
13.130.1 Data Structure Documentation . . . 1546
13.130.1.1 struct qt_meta_stringdata_KbLightWidget_t . . . 1546
13.130.2 Macro Definition Documentation . . . 1547
13.130.2.1 QT_MOC_LITERAL . . . 1547
13.130.3 Variable Documentation . . . 1547
13.130.3.1 qt_meta_data_KbLightWidget . . . 1547
13.130.3.2 qt_meta_stringdata_KbLightWidget . . . 1547
13.131 src/ckb/release/moc_kbmanager.cpp File Reference . . . 1548
13.131.1 Data Structure Documentation . . . 1548
13.131.1.1 struct qt_meta_stringdata_KbManager_t . . . 1548
13.131.2 Macro Definition Documentation . . . 1549
13.131.2.1 QT_MOC_LITERAL . . . 1549
13.131.3 Variable Documentation . . . 1549
13.131.3.1 qt_meta_data_KbManager . . . 1549
13.131.3.2 qt_meta_stringdata_KbManager . . . 1549
13.132 src/ckb/release/moc_kbmode.cpp File Reference . . . 1550
13.132.1 Data Structure Documentation . . . 1551
13.132.1.1 struct qt_meta_stringdata_KbMode_t . . . 1551
13.132.2 Macro Definition Documentation . . . 1551

13.132.2.1 QT_MOC_LITERAL . . . 1551
13.132.3 Variable Documentation . . . 1552
13.132.3.1 qt_meta_data_KbMode . . . 1552
13.132.3.2 qt_meta_stringdata_KbMode . . . 1552
13.133 src/ckb/release/moc_kbperf.cpp File Reference . . . 1552
13.133.1 Data Structure Documentation . . . 1553
13.133.1.1 struct qt_meta_stringdata_KbPerf_t . . . 1553
13.133.2 Macro Definition Documentation . . . 1554
13.133.2.1 QT_MOC_LITERAL . . . 1554
13.133.3 Variable Documentation . . . 1554
13.133.3.1 qt_meta_data_KbPerf . . . 1554
13.133.3.2 qt_meta_stringdata_KbPerf . . . 1555
13.134 src/ckb/release/moc_kbprofile.cpp File Reference . . . 1555
13.134.1 Data Structure Documentation . . . 1556
13.134.1.1 struct qt_meta_stringdata_KbProfile_t . . . 1556
13.134.2 Macro Definition Documentation . . . 1556
13.134.2.1 QT_MOC_LITERAL . . . 1556
13.134.3 Variable Documentation . . . 1557
13.134.3.1 qt_meta_data_KbProfile . . . 1557
13.134.3.2 qt_meta_stringdata_KbProfile . . . 1557
13.135 src/ckb/release/moc_kbprofiledialog.cpp File Reference . . . 1557
13.135.1 Data Structure Documentation . . . 1558
13.135.1.1 struct qt_meta_stringdata_KbProfileDialog_t . . . 1558
13.135.2 Macro Definition Documentation . . . 1559
13.135.2.1 QT_MOC_LITERAL . . . 1559
13.135.3 Variable Documentation . . . 1559
13.135.3.1 qt_meta_data_KbProfileDialog . . . 1559
13.135.3.2 qt_meta_stringdata_KbProfileDialog . . . 1560
13.136 src/ckb/release/moc_kbwidget.cpp File Reference . . . 1561
13.136.1 Data Structure Documentation . . . 1561
13.136.1.1 struct qt_meta_stringdata_KbWidget_t . . . 1561
13.136.2 Macro Definition Documentation . . . 1562
13.136.2.1 QT_MOC_LITERAL . . . 1562
13.136.3 Variable Documentation . . . 1562
13.136.3.1 qt_meta_data_KbWidget . . . 1562
13.136.3.2 qt_meta_stringdata_KbWidget . . . 1562
13.137 src/ckb/release/moc_keyaction.cpp File Reference . . . 1563
13.137.1 Data Structure Documentation . . . 1563
13.137.1.1 struct qt_meta_stringdata_KeyAction_t . . . 1563
13.137.2 Macro Definition Documentation . . . 1564

13.137.2.1 QT_MOC_LITERAL . . . 1564
13.137.3 Variable Documentation . . . 1564
13.137.3.1 qt_meta_data_KeyAction . . . 1564
13.137.3.2 qt_meta_stringdata_KeyAction . . . 1565
13.138 src/ckb/release/moc_keywidget.cpp File Reference . . . 1565
13.138.1 Data Structure Documentation . . . 1566
13.138.1.1 struct qt_meta_stringdata_KeyWidget_t . . . 1566
13.138.2 Macro Definition Documentation . . . 1566
13.138.2.1 QT_MOC_LITERAL . . . 1566
13.138.3 Variable Documentation . . . 1567
13.138.3.1 qt_meta_data_KeyWidget . . . 1567
13.138.3.2 qt_meta_stringdata_KeyWidget . . . 1567
13.139 src/ckb/release/moc_kperfwidget.cpp File Reference . . . 1567
13.139.1 Data Structure Documentation . . . 1568
13.139.1.1 struct qt_meta_stringdata_KPerfWidget_t . . . 1568
13.139.2 Macro Definition Documentation . . . 1569
13.139.2.1 QT_MOC_LITERAL . . . 1569
13.139.3 Variable Documentation . . . 1569
13.139.3.1 qt_meta_data_KPerfWidget . . . 1569
13.139.3.2 qt_meta_stringdata_KPerfWidget . . . 1570
13.140 src/ckb/release/moc_layoutdialog.cpp File Reference . . . 1570
13.140.1 Data Structure Documentation . . . 1571
13.140.1.1 struct qt_meta_stringdata_LayoutDialog_t . . . 1571
13.140.2 Macro Definition Documentation . . . 1572
13.140.2.1 QT_MOC_LITERAL . . . 1572
13.140.3 Variable Documentation . . . 1572
13.140.3.1 qt_meta_data_LayoutDialog . . . 1572
13.140.3.2 qt_meta_stringdata_LayoutDialog . . . 1573
13.141 src/ckb/release/moc_macroreader.cpp File Reference . . . 1573
13.141.1 Data Structure Documentation . . . 1574
13.141.1.1 struct qt_meta_stringdata_MacroReaderThread_t . . . 1574
13.141.1.2 struct qt_meta_stringdata_MacroReader_t . . . 1574
13.141.2 Macro Definition Documentation . . . 1575
13.141.2.1 QT_MOC_LITERAL . . . 1575
13.141.2.2 QT_MOC_LITERAL . . . 1575
13.141.3 Variable Documentation . . . 1575
13.141.3.1 qt_meta_data_MacroReader . . . 1576
13.141.3.2 qt_meta_data_MacroReaderThread . . . 1576
13.141.3.3 qt_meta_stringdata_MacroReader . . . 1576
13.141.3.4 qt_meta_stringdata_MacroReaderThread . . . 1576

13.142 src/ckb/release/moc_mainwindow.cpp File Reference . . . 1577
13.142.1 Data Structure Documentation . . . 1578
13.142.1.1 struct qt_meta_stringdata_MainWindow_t . . . 1578
13.142.2 Macro Definition Documentation . . . 1578
13.142.2.1 QT_MOC_LITERAL . . . 1578
13.142.3 Variable Documentation . . . 1578
13.142.3.1 qt_meta_data_MainWindow . . . 1578
13.142.3.2 qt_meta_stringdata_MainWindow . . . 1579
13.143 src/ckb/release/moc_modeselectdialog.cpp File Reference . . . 1579
13.143.1 Data Structure Documentation . . . 1579
13.143.1.1 struct qt_meta_stringdata_ModeSelectDialog_t . . . 1579
13.143.2 Macro Definition Documentation . . . 1580
13.143.2.1 QT_MOC_LITERAL . . . 1580
13.143.3 Variable Documentation . . . 1580
13.143.3.1 qt_meta_data_ModeSelectDialog . . . 1580
13.143.3.2 qt_meta_stringdata_ModeSelectDialog . . . 1581
13.144 src/ckb/release/moc_mperfwidget.cpp File Reference . . . 1581
13.144.1 Data Structure Documentation . . . 1582
13.144.1.1 struct qt_meta_stringdata_MPerfWidget_t . . . 1582
13.144.2 Macro Definition Documentation . . . 1582
13.144.2.1 QT_MOC_LITERAL . . . 1582
13.144.3 Variable Documentation . . . 1583
13.144.3.1 qt_meta_data_MPerfWidget . . . 1583
13.144.3.2 qt_meta_stringdata_MPerfWidget . . . 1583
13.145 src/ckb/release/moc_quagzipfile.cpp File Reference . . . 1584
13.145.1 Data Structure Documentation . . . 1584
13.145.1.1 struct qt_meta_stringdata_QuaGzipFile_t . . . 1584
13.145.2 Macro Definition Documentation . . . 1585
13.145.2.1 QT_MOC_LITERAL . . . 1585
13.145.3 Variable Documentation . . . 1585
13.145.3.1 qt_meta_data_QuaGzipFile . . . 1585
13.145.3.2 qt_meta_stringdata_QuaGzipFile . . . 1586
13.146 src/ckb/release/moc_quaziodevice.cpp File Reference . . . 1586
13.146.1 Data Structure Documentation . . . 1587
13.146.1.1 struct qt_meta_stringdata_QuaZIODevice_t . . . 1587
13.146.2 Macro Definition Documentation . . . 1587
13.146.2.1 QT_MOC_LITERAL . . . 1587
13.146.3 Variable Documentation . . . 1588
13.146.3.1 qt_meta_data_QuaZIODevice . . . 1588
13.146.3.2 qt_meta_stringdata_QuaZIODevice . . . 1588

13.147 src/ckb/release/moc_quazipfile.cpp File Reference . . . 1588
13.147.1 Data Structure Documentation . . . 1589
13.147.1.1 struct qt_meta_stringdata_QuaZipFile_t . . . 1589
13.147.2 Macro Definition Documentation . . . 1589
13.147.2.1 QT_MOC_LITERAL . . . 1589
13.147.3 Variable Documentation . . . 1590
13.147.3.1 qt_meta_data_QuaZipFile . . . 1590
13.147.3.2 qt_meta_stringdata_QuaZipFile . . . 1590
13.148 src/ckb/release/moc_rebindwidget.cpp File Reference . . . 1590
13.148.1 Data Structure Documentation . . . 1591
13.148.1.1 struct qt_meta_stringdata_RebindWidget_t . . . 1591
13.148.2 Macro Definition Documentation . . . 1592
13.148.2.1 QT_MOC_LITERAL . . . 1592
13.148.3 Variable Documentation . . . 1592
13.148.3.1 qt_meta_data_RebindWidget . . . 1592
13.148.3.2 qt_meta_stringdata_RebindWidget . . . 1592
13.149 src/ckb/release/moc_rlistwidget.cpp File Reference . . . 1593
13.149.1 Data Structure Documentation . . . 1593
13.149.1.1 struct qt_meta_stringdata_RListWidget_t . . . 1593
13.149.2 Macro Definition Documentation . . . 1594
13.149.2.1 QT_MOC_LITERAL . . . 1594
13.149.3 Variable Documentation . . . 1594
13.149.3.1 qt_meta_data_RListWidget . . . 1594
13.149.3.2 qt_meta_stringdata_RListWidget . . . 1594
13.150 src/ckb/release/moc_settingswidget.cpp File Reference . . . 1595
13.150.1 Data Structure Documentation . . . 1596
13.150.1.1 struct qt_meta_stringdata_SettingsWidget_t . . . 1596
13.150.2 Macro Definition Documentation . . . 1596
13.150.2.1 QT_MOC_LITERAL . . . 1596
13.150.3 Variable Documentation . . . 1597
13.150.3.1 qt_meta_data_SettingsWidget . . . 1597
13.150.3.2 qt_meta_stringdata_SettingsWidget . . . 1597
13.151 src/ckb/release/qrc_binary.cpp File Reference . . . 1597
13.151.1 Macro Definition Documentation . . . 1598
13.151.1.1 QT_RCC_MANGLE_NAMESPACE . . . 1598
13.151.1.2 QT_RCC_PREPEND_NAMESPACE . . . 1598
13.151.2 Function Documentation . . . 1598
13.151.2.1 qCleanupResources_binary . . . 1598
13.151.2.2 qInitResources_binary . . . 1599
13.151.2.3 qRegisterResourceData . . . 1599

13.151.2.4 qUnregisterResourceData . . . 1599
13.151.3 Variable Documentation . . . 1600
13.151.3.1 qt_resource_data . . . 1600
13.151.3.2 qt_resource_name . . . 1600
13.151.3.3 qt_resource_struct . . . 1600
13.152 src/ckb/release/qrc_image.cpp File Reference . . . 1600
13.152.1 Macro Definition Documentation . . . 1601
13.152.1.1 QT_RCC_MANGLE_NAMESPACE . . . 1601
13.152.1.2 QT_RCC_PREPEND_NAMESPACE . . . 1601
13.152.2 Function Documentation . . . 1601
13.152.2.1 qCleanupResources_image . . . 1601
13.152.2.2 qInitResources_image . . . 1601
13.152.2.3 qRegisterResourceData . . . 1602
13.152.2.4 qUnregisterResourceData . . . 1602
13.152.3 Variable Documentation . . . 1602
13.152.3.1 qt_resource_data . . . 1602
13.152.3.2 qt_resource_name . . . 1602
13.152.3.3 qt_resource_struct . . . 1603
13.153 src/ckb/release/qrc_text.cpp File Reference . . . 1603
13.153.1 Macro Definition Documentation . . . 1603
13.153.1.1 QT_RCC_MANGLE_NAMESPACE . . . 1603
13.153.1.2 QT_RCC_PREPEND_NAMESPACE . . . 1603
13.153.2 Function Documentation . . . 1603
13.153.2.1 qCleanupResources_text . . . 1603
13.153.2.2 qInitResources_text . . . 1604
13.153.2.3 qRegisterResourceData . . . 1604
13.153.2.4 qUnregisterResourceData . . . 1605
13.153.3 Variable Documentation . . . 1605
13.153.3.1 qt_resource_data . . . 1605
13.153.3.2 qt_resource_name . . . 1605
13.153.3.3 qt_resource_struct . . . 1605
13.154 src/ckb/rlistwidget.cpp File Reference . . . 1606
13.155 src/ckb/rlistwidget.h File Reference . . . 1606
13.156 src/ckb/settingswidget.cpp File Reference . . . 1607
13.156.1 Function Documentation . . . 1608
13.156.1.1 right . . . 1608
13.156.2 Variable Documentation . . . 1608
13.156.2.1 devpath . . . 1608
13.156.2.2 modKeys . . . 1609
13.156.2.3 modNames . . . 1609

13.157 src/ckb/settingswidget.h File Reference 1609
13.158 src/ckb/ui_animadddialog.h File Reference 1610
13.159 src/ckb/ui_animsettingdialog.h File Reference 1611
13.160 src/ckb/ui_extrasettingswidget.h File Reference 1611
13.161 src/ckb/ui_fwupgradedialog.h File Reference 1612
13.162 src/ckb/ui_gradientdialog.h File Reference 1613
13.163 src/ckb/ui_kbanimwidget.h File Reference 1614
13.164 src/ckb/ui_kbbindwidget.h File Reference 1615
13.165 src/ckb/ui_kblightwidget.h File Reference 1616
13.166 src/ckb/ui_kbprofiledialog.h File Reference 1617
13.167 src/ckb/ui_kbwidget.h File Reference 1618
13.168 src/ckb/ui_kperfwidget.h File Reference 1619
13.169 src/ckb/ui_layoutdialog.h File Reference 1620
13.170 src/ckb/ui_mainwindow.h File Reference 1621
13.171 src/ckb/ui_modeselectdialog.h File Reference 1622
13.172 src/ckb/ui_mperfwidget.h File Reference 1623
13.173 src/ckb/ui_rebindwidget.h File Reference 1624
13.174 src/ckb/ui_settingswidget.h File Reference 1625

Index **1627**

Chapter 1

ckb-next: RGB Driver for Linux and OS X

ckb-next is an open-source driver for Corsair keyboards and mice. It aims to bring the features of their proprietary CUE software to the Linux and Mac operating systems. This project is currently a work in progress, but it already supports much of the same functionality, including full RGB animations. More features are coming soon. Testing and bug reports are appreciated!

Disclaimer: ckb-next is not an official Corsair product. It is licensed under the GNU General Public License (version 2) in the hope that it will be useful, but with NO WARRANTY of any kind.

What happened to the original `ckb`?

We don't know. The author of **ckb** `ccMSC` suddenly disappeared and hasn't showed up since July 2016. So the community around ckb decided to take the project over and continue its development. That's how **ckb-next** was created. Currently it's not rock solid and very easy to set up on newer systems but we are actively working on this. Nevertheless the project already incorporates a notable amount of fixes and patches in comparison to the original ckb.

Contents

- `Current Status`
- `Device Support`
- `Linux Installation`
- `OS X/macOS Installation`
- `Usage`
- `Troubleshooting`
- `Known Issues`
- `Contributing`

See also:

- https://github.com/mattanger/ckb-next/blob/master/DAEMON.md "Manual for the driver daemon"
- `ckb testing repository` (updated more frequently, but may be unstable)

Device Support

Keyboards:

- K65 RGB
- K70
- K70 RGB
- K70 LUX RGB
- K95∗
- K95 RGB
- Strafe
- Strafe RGB
- = hardware playback not supported. Settings will be saved to software only.

Mice:

- M65 RGB
- M65 PRO RGB
- Sabre RGB
- Scimitar RGB

Linux Installation

Pre-made packages:

ckb-next packages:

- Fedora 24/25, CentOS/RHEL 7 (maintained by):
  - `johanh/ckb` - based on `master` branch

ckb packages (deprecated):

- Arch Linux (maintained by):
  - `aur/ckb-git` - based on `master` branch (more stable)
  - `aur/ckb-git-latest` - based on `testing` branch (less stable but fresher)
- Gentoo (maintained by): `emerge -av app-misc/ckb`

If you are a package maintainer or want to discuss something with package maintainers let us know in the issues, so we can have an accountable and centralized communication about this. *If you would like to maintain a package for your favorite distro/OS, please let us know as well.*

Preparation:

ckb-next requires Qt5 (Qt 5.6 recommened for OS X), libudev, zlib, gcc, g++, and glibc.

- Ubuntu: `sudo apt-get install build-essential libudev-dev qt5-default zlib1g-dev libappindicator-dev`
- Fedora: `sudo dnf install zlib-devel qt5-qtbase-devel libgudev-devel libappindicator-de systemd-devel gcc-c++`
- Arch: `sudo pacman -S base-devel qt5-base zlib`
- Other distros: Look for `qt5` or `libqt5*-devel`

Note: If you build your own kernels, ckb-next requires the uinput flag to be enabled. It is located in `Device Drivers -> Input Device Support -> Miscellaneous devices -> User level driver support`. If you don't know what this means, you can ignore this.

Installing:

You can download ckb-next using the "Download zip" option on the right. Extract it and open the ckb-master directory. The easiest way to install ckb is to double-click the `quickinstall` script and run it in a Terminal. It will attempt to build ckb and then ask if you'd like to install/run the application. If the build doesn't succeed, or if you'd like to compile ckb manually, see https://github.com/ccMSC/ckb/blob/master/BUILD.md "'BUILD.md'" for instructions.

Upgrading:

To install a new version of ckb, or to reinstall the same version, first delete the ckb-master directory and the zip file from your previous download. Then download the source code again and re-run `quickinstall`. The script will automatically replace the previous installation. You may need to reboot afterward.

Uninstalling:

First, stop the ckb-daemon service and remove the service file.

- If you have systemd (Ubuntu versions starting with 15.04): "' sudo systemctl stop ckb-daemon sudo rm -f /usr/lib/systemd/system/ckb-daemon.service "'
- If you have Upstart (Ubuntu versions earlier than 15.04): "' sudo service ckb-daemon stop sudo rm -f /etc/init/ckb-daemon.conf "'
- If you have OpenRC: "' sudo rc-service ckb-daemon stop sudo rc-update del ckb-daemon default sudo rm -f /etc/init.d/ckb-daemon "
- `If you're not sure, re-run the`quickinstall`script and proceed to the service installation. The script will say`System service: Upstart detected`or`System service: systemd detected'. Please be aware that OpenRC is currently not detected automatically.

Afterward, remove the applications and related files: "' sudo rm -f /usr/bin/ckb /usr/bin/ckb-daemon /usr/share/applications/ckb.desktop /usr/share/icons/hicolor/512x512/apps/ckb.png sudo rm -rf /usr/lib/ckb-animations "'

Before `https://github.com/mattanger/ckb-next/commit/f347e60df211c60452f95084b6c46dc4ec5f42` animations were located elsewhere, try removing them as well: "' sudo rm -rf /usr/bin/ckb-animations "'

OS X/macOS Installation

Binary download:

The latest OS X/macOS binary can be downloaded here: `https://github.com/mattanger/ckb-next/releases/late`

Click on `ckb.pkg` under the Downloads section. This is an automated installer which will set up the driver for you. After it's finished, open ckb.app (it will be installed to your Applications directory) to get started.

Building from source:

Install the latest version of Xcode from the App Store. Open Xcode, accept the license agreement, and wait for it to install any additional components (if necessary). When you see the "Welcome to Xcode" screen, the setup is finished and you can close the app. Then install Xcode Command Line Tools package issuing `xcode-select --install` in a Terminal app. Afterwards install Qt5 from here: http://www.qt.-io/download-open-source/

The easiest way to build the driver is with the `quickinstall` script, which is present in the ckb-master folder. Double-click on `quickinstall` and it will compile the app for you, then ask if you'd like to install it system-wide. If the build fails for any reason, or if you'd like to compile manually, see https://github.com/ccMSC/ckb/blob/master/-BUILD.md "'BUILD.md'".

Upgrading (binary):

Download the latest `ckb.pkg`, run the installer, and reboot. The newly-installed driver will replace the old one.

Upgrading (source):

Remove the existing ckb-master directory and zip file. Re-download the source code and run the `quickinstall` script again. The script will automatically replace the previous installation. You may need to reboot afterward.

Uninstalling:

Drag `ckb.app` into the trash. If the system service file isn't cleaned up automatically, you can find it and remove it here: `/Library/LaunchDaemons/com.ckb.daemon.plist`.

Usage

The user interface is still a work in progress.

Major features:

- Control multiple devices independently
- United States and European keyboard layouts
- Customizable key bindings
- Per-key lighting and animation
- Reactive lighting
- Multiple profiles/modes with hardware save function
- Adjustable mouse DPI with ability to change DPI on button press

Closing ckb will actually minimize it to the system tray. Use the Quit option from the tray icon or the settings screen to exit the application.

Roadmap (roughly in order)

- **v0.3 release:**
- Ability to store profiles separately from devices, import/export them
- More functions for the Win Lock key
- Key macros
- **v0.4 release:**
- Ability to import CUE profiles

- Ability to tie profiles to which application has focus
- **v0.5 release:**
- Key combos
- Timers?
- **v1.0 release:**
- OSD? (Not sure if this can actually be done)
- Extra settings?
- ????

Troubleshooting

Linux

If you have problems connecting the device to your system (device doesn't respond, ckb-daemon doesn't recognize or can't connect it) and/or you experience long boot times when using the keyboard, try adding the following to your kernel's `cmdline`:

- K65 RGB: `usbhid.quirks=0x1B1C:0x1B17:0x20000408`
- K70: `usbhid.quirks=0x1B1C:0x1B09:0x0x20000408`
- K70 RGB: `usbhid.quirks=0x1B1C:0x1B13:0x20000408`
- K95: `usbhid.quirks=0x1B1C:0x1B08:0x20000408`
- K95 RGB: `usbhid.quirks=0x1B1C:0x1B11:0x20000408`
- Strafe: `usbhid.quirks=0x1B1C:0x1B15:0x20000408`
- Strafe RGB: `usbhid.quirks=0x1B1C:0x1B20:0x20000408`
- M65 RGB: `usbhid.quirks=0x1B1C:0x1B12:0x20000408`
- Sabre RGB Optical: `usbhid.quirks=0x1B1C:0x1B14:0x20000408`
- Sabre RGB Laser: `usbhid.quirks=0x1B1C:0x1B19:0x20000408`
- Scimitar RGB: `usbhid.quirks=0x1B1C:0x1B1E:0x20000408`

For instructions on adding `cmdline` parameters in Ubuntu, see `https://wiki.ubuntu.com/Kernel/-KernelBootParameters`

If you have multiple devices, combine them with commas, starting after the =. For instance, for K70 RGB + M65 RGB: `usbhid.quirks=0x1B1C:0x1B13:0x20000408,0x1B1C:0x1B12:0x20000408`

If it still doesn't work, try replacing `0x20000408` with `0x4`. Note that this will cause the kernel driver to ignore the device(s) completely, so you need to ensure ckb-daemon is running at boot or else you'll have no input. This will not work if you are using full-disk encryption.

If you see **GLib** critical errors like 'GLib-GObject-CRITICAL **: g_type_add_interface_static: assertion 'G_TYPE_-IS_INSTANTIATABLE (instance_type)' failed' and you are using:

- Qt 5.8 and newer, remove your Qt configuration files and restart the ckb GUI. Also watch out for different style overridings in dotfiles under ~/ generated by Qt automatically, remove them as well.
- Qt 5.7 and lower, install `qt5ct` package on Arch Linux (find a similar one for your distribution). That's all. This is a known Qt bug. It happened because Qt did not ship required GTK files.

If you're using **Unity** and the tray icon doesn't appear correctly, run `sudo apt-get install libappindicator-dev`. Then reinstall ckb.

OS X/macOS

- **"ckb.pkg" can't be opened because it is from an unidentified developer** Open `System Preferences > Security & Privacy > General` and click `Open Anyway`.
- **Modifier keys (Shift, Ctrl, etc.) are not rebound correctly** ckb does not recognize modifier keys rebound from System Preferences. You can rebind them again within the application.
- **~ key prints §± Check your keyboard layout on ckb's Settings screen. Choose the layout that matches your physical keyboard.
- **Compile problems** Can usually be resolved by rebooting your computer and/or reinstalling Qt. Make sure that Xcode works on its own. If a compile fails, delete the `ckb-master` directory as well as any automatically generated `build-ckb` folders and try again from a new download.
- **Scroll wheel does not scroll** As of #c3474d2 it's now possible to **disable scroll acceleration** from the GUI. You can access it under "OSX tweaks" in the "More settings" screen. Once disabled, the scroll wheel should behave consistently.

General

Please ensure your keyboard firmware is up to date. If you've just bought the keyboard, connect it to a Windows computer first and update the firmware from Corsair's official utility.

Before reporting an issue, connect your keyboard to a Windows computer and see if the problem still occurs. If it does, contact Corsair. Additionally, please check the Corsair user forums to see if your issue has been reported by other users. If so, try their solutions first.

Common issues:

- **Problem:** ckb says "No devices connected" or "Driver inactive"
- **Solution:** Try rebooting the computer and/or reinstalling ckb. Try removing the keyboard and plugging it back in. If the error doesn't go away, try the following:
- **Problem:** Keyboard doesn't work in BIOS, doesn't work at boot
- **Solution:** Some BIOSes have trouble communicating with the keyboard. They may prevent the keyboard from working correctly in the operating system as well. First, try booting the OS *without* the keyboard attached, and plug the keyboard in after logging in. If the keyboard works after the computer is running but does not work at boot, you may need to use the keyboard's BIOS mode option.
- BIOS mode can be activated using the poll rate switch at the back of the keyboard. Slide it all the way to the position marked "BIOS". You should see the scroll lock light blinking to indicate that it is on. (Note: Unfortunately, this has its own problems - see Known Issues. You may need to activate BIOS mode when booting the computer and deactivate it after logging in).
- **Problem:** Keyboard isn't detected when plugged in, even if driver is already running
- **Solution:** Try moving to a different USB port. Be sure to follow `Corsair's USB connection requirements`. Note that the keyboard does not work with some USB3 controllers - if you have problems with USB3 ports, try USB2 instead. If you have any USB hubs on hand, try those as well. You may also have success sliding the poll switch back and forth a few times.

Reporting issues

If you have a problem that you can't solve (and it isn't mentioned in the Known Issues section below), you can report it on `the GitHub issue tracker`. Before opening a new issue, please check to see if someone else has reported your problem already - if so, feel free to leave a comment there.

Known issues

- Using the keyboard in BIOS mode prevents the media keys (including mute and volume wheel), as well as the K95's G-keys from working. This is a hardware limitation.
- The tray icon doesn't appear in some desktop environments. This is a known Qt bug. If you can't see the icon, reopen ckb to bring the window back.
- When starting the driver manually, the Terminal window sometimes gets spammed with enter keys. You can stop it by unplugging and replugging the keyboard or by moving the poll rate switch.
- When stopping the driver manually, the keyboard sometimes stops working completely. You can reconnect it by moving the poll rate switch.

Contributing

You can contribute to the project by `opening a pull request`. It's best if you base your changes off of the `testing` branch as opposed to the `master`, because the pull request will be merged there first. If you'd like to contribute but don't know what you can do, take a look at `the issue tracker` and see if any features/problems are still unresolved. Feel free to ask if you'd like some ideas.

Chapter 2

Building ckb

Linux

You can build the project by running `./qmake-auto && make` in a Terminal inside the ckb-master directory. The binaries will be placed in a new `bin` directory assuming they compile successfully. If you get a `No suitable qmake found` error, make sure Qt5 is installed and up to date. You may have to invoke qmake manually, then run `make` on its own. If you have Qt Creator installed, you can open `ckb.pro` (when asked to configure the project, make sure "Desktop" is checked) and use `Build > Build Project "ckb" (Ctrl+B)` to build the application instead.

Running as a service:

First copy the binary and the service files to their system directories:

- Upstart (Ubuntu, prior to 15.04): `sudo cp -R bin/* /usr/bin && sudo cp service/upstart/ckb-daemon conf /etc/init`
- Systemd (Ubuntu 15.04 and later): `sudo cp -R bin/* /usr/bin && sudo cp service/systemd/ckb-daem service /usr/lib/systemd/system`
- OpenRC: `sudo cp -R bin/* /usr/bin && sudo cp service/openrc/ckb-daemon /etc/init.d/`

To launch the driver and enable it at start-up:

- Upstart: `sudo service ckb-daemon start`
- Systemd: `sudo systemctl start ckb-daemon && sudo systemctl enable ckb-daemon`
- OpenRC: `sudo rc-service ckb-daemon start && sudo rc-update add ckb-daemon default`

Open the `bin` directory and double-click on `ckb` to launch the user interface. If you want to run it at login, add `ckb --background` to your Startup Applications.

Running manually:

Open the `bin` directory in a Terminal and run `sudo ./ckb-daemon` to start the driver. To start the user interface, run `./ckb`. Running the driver manually may be useful for testing/debugging purposes, but you must leave the terminal window open and you'll have to re-run it at every reboot, so installing it as a service is the best long-term solution.

OSX

Open ckb.pro in Qt Creator. You should be prompted to configure the project (make sure the "Desktop" configuration is selected and not iOS). Once it's finished loading, press `Cmd+B` or select `Build > Build Project "ckb"` from the menu bar. When it's done, you should see a newly-created `ckb.app` in the project directory. Exit Qt Creator.

Alternatively, open a Terminal in the ckb-master directory and run `./qmake-auto && make`. It will detect Qt automatically if you installed it to one of the standard locations. You should see a newly created `ckb.app` if the build is successful.

Running as a service:

Copy `ckb.app` to your Applications folder. Copy the file `'service/launchd/com.ckb.daemon.plist'` to your computer's `/Library/LaunchDaemons` folder (you can get to it by pressing `Cmd+Shift+G` in Finder and typing the location). Then open a Terminal and run the following commands to launch the driver:

"' sudo chown root:wheel /Library/LaunchDaemons/com.ckb.daemon.plist sudo chmod 0700 /Library/Launch-Daemons/com.ckb.daemon.plist sudo launchctl load /Library/LaunchDaemons/com.ckb.daemon.plist "'

After you're done, open `ckb.app` to launch the user interface.

Running manually:

Open a Terminal in the ckb directory and run `sudo ckb.app/Contents/Resources/ckb-daemon` to start the driver. Open `ckb.app` to start the user interface. Note that you must leave the terminal window open and must re-launch the driver at every boot if you choose this; installing as a service is the better long term solution.

Chapter 3

cbk Improvements Roadmap

Short term plan

- merge existing PR submitted to original ckb repo
- Contact other developers interested in collaboration on a new and improved version of ckb
- Figure out the issues relating to MacOS Sierra and other version
- Device support:
  - Determine which will need support other than just USB id additions
- Address existing bugs. Not help requests.

Chapter 4

DAEMON

The daemon provides devices at `/dev/input/ckb*`, where `*` is the device number, starting at 1. Up to 9 devices may be connected at once and controlled independently. The daemon additionally provides `/dev/input/ckb0`, which stores driver information.

Mac note: The devices on OSX are located at `/var/run/ckb*` and not `/dev/input/ckb*`. So wherever you see `/dev/input` in this document, replace it with `/var/run`.

`/dev/input/ckb0` contains the following files:

- `connected`: A list of all connected devices, one per line. Each line contains a device path followed by the device's serial number and its description.
- `pid`: The process identifier of the daemon.
- `version`: The daemon version.

Other `ckb*` devices contain the following:

- `cmd`: Keyboard controller.
- `notify0`: Keyboard notifications.
- `features`: Device features.
- `fwversion`: Device firmware version (not present on all devices).
- `model`: Device description/model.
- `pollrate`: Poll rate in milliseconds (not present on all devices).
- `serial`: Device serial number. `model` and `serial` will match the info found in `ckb0/connected`

Commands

The `/dev/input/ckb*/cmd` nodes accept input in the form of text commands. They are normally accessible to all users on the system (see Security section). Commands should be given in the following format: `[mode <n>] command1 [paramter1] [command2] [parameter2] [command3] [parameter3] ...`

In a terminal shell, you can do this like `echo mycommand > /dev/input/ckb1/cmd`. Programmatically, you can open and write them as regular files. When programming, you must append a newline character and flush the output before your command(s) will actually be read.

The `mode` parameter is used to group settings. Most (but not all) settings are mode-specific; that is, changing mode 1 will not affect mode 2. By default, all commands affect the current mode. Use `mode <n> switch` to change the current mode.

When plugged in, all devices start in hardware-controlled mode (also known as idle mode) and will not respond to commands. Before issuing any other commands, write `active` to the command node, like `echo active > /dev/input/ckb1/cmd`. To put the device back into hardware mode, issue the `idle` command.

Features

The `features` node describes features supported by the device, which may not be present on all devices. The first two words in the `features` node are always `<vendor> <model>`, like `corsair k70`. After that, any of the following features may appear:

- `adjrate`: Device supports adjustable poll rate.
- `bind`: Device supports key rebinding.
- `fwupdate`: Device supports firmware updates.
- `fwversion`: Device has a detectable firmware version (stored in the `fwversion` node).
- `notify`: Device supports key notifications.
- `pollrate`: Device has a detectable poll rate (stored in the `pollrate` node).
- `rgb`: Device supports RGB lighting.

Keyboard layout

The driver has no concept of keyboard layouts; all keys are referred to by their English names regardless of the underlying hardware. This means that, for instance, in an AZERTY layout the `q` key in ckb-daemon corresponds to A on the physical keyboard. Note that on UK/european (ISO) layouts, the backslash key (beside left shift) is called `bslash_iso`, while `bslash` refers to the backslash on the US keyboard. The key next to Enter on the ISO keyboard is known as `hash`. See `src/ckb-daemon/keymap.c` for the full table of supported keys.

For technical reasons, the OSX driver may swap the `bslash_iso` and `grave` keys if the keyboard layout is not set correctly. To compensate for this, write `layout iso` or `layout ansi` to the command node.

Poll rate

A device's current poll rate can be read from its `pollrate` node, assuming it has one. Keyboards have a hardware switch to control poll rate and cannot be adjusted via software. However, mice have a software-controlled poll rate. You can change it by issuing `pollrate <interval>` to the command node, where `interval` is the time in milliseconds. Valid poll rates are `1`, `2`, `4`, and `8`.

Profiles and modes

Each mode has its own independent binding and lighting setup. When the daemon starts or a keyboard is plugged in, the profile will be loaded from the hardware. By default, all commands will update the currently selected mode. The `mode <n>` command may be used to change the settings for a different mode. Up to 6 modes are available. Each keyboard has one profile, which may be given a name. Mode 1 may be saved to the device hardware, or modes 1-3 in the case of the K95. Modes 4 through 6 are software-only. Profile management commands are as follows:

- `profilename <name>` sets the profile's name. The name must be written without spaces; to add a space, use `%20`.
- `name <name>` sets the current mode's name. Use `mode <n> name <name>` to set a different mode's name.

- `profileid <guid> [<modification>]` sets a profile's ID. The GUID must be written in registry format, like `{12345678-ABCD-EF01-2345-6789ABCDEF01}`. The optional modification number must be written with 8 hex digits, like `ABCDEF01`.
- `id <guid> [<modification>]` sets a mode's ID.
- `mode <n> switch` switches the keyboard to mode N. If the mode does not exist, it will be created with a blank ID, black lighting, and default bindings.
- `hwload` loads the RGB profile from the hardware. Key bindings and non-hardware RGB modes are unaffected.
- `hwsave` saves the RGB profile to the hardware.
- `erase` erases the current mode, resetting its lighting and bindings. Use `mode <n> erase` to erase a different mode.
- `eraseprofile` erases the entire profile, deleting its name, ID, and all of its modes.

Examples:

- `profilename My%20Profile mode 1 name Mode%201 mode 2 name Mode%202 mode 3 name Mode%203` will name the profile "My Profile" and name modes 1-3 "Mode 1", "Mode 2", and "Mode 3".
- `eraseprofile hwload` resets the entire profile to its hardware settings.

LED commands

The backlighting is controlled by the `rgb` commands.

- `rgb <RRGGBB>` sets the entire keyboard to the color specified by the hex constant RRGGBB.
- `rgb <key>:<RRGGBB>` sets the specified key to the specified hex color.

Examples:

- `rgb ffffff` makes the whole keyboard white.
- `rgb 000000` makes the whole keyboard black.
- `rgb esc:ff0000` sets the Esc key red but leaves the rest of the keyboard unchanged.

Multiple keys may be changed to one color when separated with commas, for instance:

- `rgb w,a,s,d:0000ff` sets the WASD keys to blue.

Additionally, multiple commands may be combined into one, for instance:

- `rgb ffffff esc:ff0000 w,a,s,d:0000ff` sets the Esc key red, the WASD keys blue, and the rest of the keyboard white (note the lack of a key name before `ffffff`, implying the whole keyboard is to be set).

By default, the controller runs at 30 FPS, meaning that attempts to animate the LEDs faster than that will be ignored. If you wish to change it, send the command `fps <n>`. The maximum frame rate is 60.

For devices running in 512-color mode, color dithering can be enabled by sending the command `dither 1`. The command `dither 0` disables dithering.

Indicators

The indicator LEDs (Num Lock, Caps Lock, Scroll Lock) are controlled with the `i` commands.

- `ioff <led>` turns an indicator off permanently. Valid LED names are `num`, `caps`, and `scroll`.
- `ion <led>` turns an indicator on permanently.
- `iauto <led>` turns an indicator off or on automatically (default behavior).

Binding keys

Keys may be rebound through use of the `bind` commands. Binding is a 1-to-1 operation that translates one keypress to a different keypress regardless of circumstance.

- `bind <key1>:<key2>` remaps key1 to key2.
- `unbind <key>` unbinds a key, causing it to lose all function.
- `rebind <key>` resets a key, returning it to its default binding.

Examples:

- `bind g1:esc` makes G1 become an alternate Esc key (the actual Esc key is not changed).
- `bind caps:tab tab:caps` switches the functions of the Tab and Caps Lock keys.
- `unbind lwin rwin` disables both Windows keys, even without using the keyboard's Windows Lock function.
- `rebind all` resets the whole keyboard to its default bindings.

Key macros

Macros are a more advanced form of key binding, controlled with the `macro` command.

- `macro <keys>:<command>` binds a key combination to a command, where the command is a series of key presses. To combine keys, separate them with `+`; for instance, `lctrl+a` binds a macro to (left) Ctrl+A. In the command field, enter `+<key>` to trigger a key down or `-<key>` to trigger a key up. To simulate a key press, use `+<key>,-<key>`.
- `macro <keys>:clear` clears commands associated with a key combination. Only one macro may be assigned per combination; assigning a second one will overwrite the first.
- `macro clear` clears all macros.

Examples:

- `macro g1:+lctrl,+a,-a,-lctrl` triggers a Ctrl+A when G1 is pressed.
- `macro g2+g3:+lalt,+f4,-f4,-lalt` triggers an Alt+F4 when G2 and G3 are pressed simultaneously.

Assigning a macro to a key will cause its binding to be ignored; for instance, `macro a:+b,-b` will cause A to generate a B character regardless of its binding. However, `macro lctrl+a:+b,-b` will cause A to generate a B only when Ctrl is also held down.

DPI and mouse settings

DPI settings are stored in a bank. They are controlled with the `dpi` command.

- `dpi <stage>:<x>,<y>` sets the DPI for a given `stage` to `x` by `y`. Valid stages are `0` through `5`. In hardware, `1` is the first (lowest) stage and `5` is the highest. Stage `0` is used for Sniper mode.
- `dpi <stage>:<xy>` sets both X and Y.
- `dpi <stage>:off` disables a DPI stage.
- `dpisel <stage>` sets the current stage selection.

In order to change the mouse's current DPI, first update one of the stages with the value you want, then select that stage. For instance:

- `dpi 1:1000 dpisel 1` sets the current DPI to 1000x1000.

Additional mouse settings:

- `lift <height>` sets the lift height, from `1` (lowest) to `5` (highest)
- `snap <on|off>` enables or disables Angle Snap.

Notifications

The keyboard can be configured to generate user-readable notifications on keypress events. These are controlled with the `notify` commands. In order to see events, read from `/dev/input/ckb*/notify0`. In a terminal, you can do this like `cat /dev/input/ckb1/notify0`. Programmatically, you can open it for reading like a regular file.

Note that the file can only reliably be read by one application: if you try to open it in two different programs, they may both fail to get data. Data will be buffered as long as no programs are reading, so you will receive all unread notifications as soon as you open the file. If you'd like to read notifications from two separate applications, send the command `notifyon <n>` to the keyboard you wish to receive notifications from, where N is a number between 1 and 9. If `/dev/input/ckb*/notify<n>` does not already exist, it will be created, and you can read notifications from there without disrupting any other program. To close a notification node, send `notifyoff <n>`.

`notify0` is always open and will not be affected by `notifyon`/`notifyoff` commands. By default, all notifications are printed to `notify0`. To print output to a different node, prefix your command with `@<node>`.

Notifications are printed with one notification per line. Commands are as follows:

- `notify <key>:on` or simply `notify <key>` enables notifications for a key. Each key will generate two notifications: `key +<key>` when the key is pressed, and `key -<key>` when it is released.
- `notify <key>:off` turns notifications off for a key.

Examples:

- `notify w a s d` sends notifications whenever W, A, S, or D is pressed.
- `notify g1 g2 g3 g4 g5 g6 g7 g8 g9 g10 g11 g12 g13 g14 g15 g16 g17 g18 mr m1 m2 m3 light lock` prints a notification whenever a non-standard key is pressed.
- `notify all:off` turns all key notifications off.
- `@5 notify esc` prints Esc key notifications to `notify5`.

Note: Key notifications are *not* affected by bindings. For instance, if you run `echo bind a:b notify a > /dev/input/ckb1/cmd` and then press the A key, the notifications will read `key +a key -a`, despite the fact that the character printed on screen will be `b`. Likewise, unbinding a key or assigning a macro to a key does not affect the notifications.

Indicator notifications

You can also choose to receive notifications for the indicator LEDs by using the `inotify` command. For instance, `inotify caps:on` or simply `inotify caps` will print notifications whenever the Caps Lock LED is toggled. The notifications will read `i +caps` when the light is turned on and `i -caps` when it is turned off. It is also possible to toggle all indicators at once using `inotify all` or `inotify all:off`.

Like key notifications, indicator notifications are not affected by bindings, nor by the `ion`, `ioff`, or `iauto` commands. The notifications will reflect the state of the LEDs as seen be the event device.

Getting parameters

Parameters can be retrieved using the `get` command. The data will be sent out as a notification. Generally, the syntax to get the data associated with a command is `get :<command>` (note the colon), and the associated data will be returned in the form of `<command> <data>`. The following data may be gotten:

- `get :mode` returns the current mode in the form of a `switch` command. (Note: Do not use this in a line containing a `mode` command or it will return the mode that you selected, rather than the keyboard's current mode.)
- `get :name` returns the current mode's name in the form of `mode <n> name <name>`. To see the name of another mode, use `mode <n> get :name`. The name is URL-encoded; spaces are written as %20. The name may be truncated, so `name <some long string> get :name` may return something shorter than what was entered.
- `get :profilename` returns the profile's name, in the form of `profilename <name>`. As above, it is URL-encoded and may be truncated.
- `get :hwname` and `get :hwprofilename` return the same thing except taken from the current hardware profile instead of the in-memory profile. The output is identical but will read `hwname` instead of `name` and `hwprofilename` instead of `profilename`.
- `get :id` returns the current mode's ID and modification number in the form of `mode <n> id <guid> <modification>`.
- `get :profileid` returns the current profile's ID and modification number in the form of `profileid <guid> <modification>`.
- `get :hwid` and `get :hwprofileid` return the same thing except from the current hardware profile/mode. As before, the ouput will be the same but with `hwid` and `hwprofileid` instead of `id` and `profileid`.
- `get :rgb` returns an `rgb` command equivalent to the current RGB state.
- `get :hwrgb` does the same thing, but retrieves the colors currently stored in the hardware profile. The output will say `hwrgb` instead of `rgb`.
- `get :dpi` returns a `dpi` command equivalent to the current DPI bank.
- `get :dpisel` returns a `dpisel` command for the currently-selected DPI stage.
- `get :lift` returns a `lift` command for the current lift height.
- `get :snap` returns the current angle snap status.
- `get :hwdpi`, `get :hwdpisel`, `get :hwlift`, and `get :hwsnap` return the same properties, but for the current hardware profile.
- `get :keys` and `get :i` return the current keypress status and indicator status, respectively. They will indicate all currently pressed keys and all currently active indicators, like `key +enter` and `i +num`.

Like `notify`, you must prefix your command with `@<node>` to get data printed to a node other than `notify0`.

Firmware updates

WARNING: Improper use of `fwupdate` may brick your device; use this command *at your own risk*. I accept no responsibility for broken keyboards.

The latest firmware versions and their URLs can be found in the `FIRMWARE` document. To update your keyboard's firmware, first extract the contents of the zip file and then issue the command `fwupdate /path/to/fw/file.bin` to the keyboard you wish to update. The path name must be absolute and must not include spaces. If it succeeded, you should see `fwupdate <path> ok` logged to the keyboard's notification node and then the device will disconnect and reconnect. If you see `fwupdate <path> invalid` it means that the firmware file was not valid for the device; more info may be available in the daemon's `stdout`. If you see `fwupdate <path> fail` it means that the file was valid but the update failed at a hardware level. The keyboard may disconnect/reconnect anyway or it may remain in operation.

When the device reconnects you should see the new firmware version in its `fwversion` node; if you see `0000` instead it means that the keyboard did not update successfully and will need another `fwupdate` command in order to function again. If the update fails repeatedly, try connecting the keyboard to a Windows PC and using the official firmware update in CUE.

Restart

Because sometimes the communication between the daemon and the keyboard is corrupted after resuming from standby or suspend, a restart function is implemented. It first calls the quit() funtion, then it calls main() again with the original parameter list.

There are two ways to restart the daemon:

- send the string "restart some-description-as-one-word" to the cmd-pipe (normally /dev/input/ckb1/cmd or /dev/input/ckb2/cmd, depending on what device gets which ID.
- send SIGUSR1 to the daemon process (as root).

Later on, there may be a user interface in the client for the first method.

Security

By default, all of the `ckb*` nodes may be accessed by any user. For most single-user systems this should not present any security issues, since only one person will have access to the computer anyway. However, if you'd like to restrict the users that can write to the `cmd` nodes or read from the `notify` nodes, you can specify the `--gid=<group>` option at start up. For instance, on most systems you could run `ckb-daemon --gid=1000` to make them accessible only by the system's primary user. `ckb-daemon` must still be run as root, regardless of which `gid` you specify. The `gid` option may be set only at startup and cannot be changed while the daemon is running.

The daemon additionally supports a `--nonotify` option to disable key notifications, to prevent unauthorized programs from logging key input. Note that this will interfere with some of `ckb`'s abilities. It is also highly unlikely to increase security unless you are using the program in a stripped down terminal environment without Xorg. For most use cases there are many other (more likely) ways that a keylogger program could compromise your system. Nevertheless, the option is provided for the sake of paranoia. If you'd like to disable key rebinding as well, launch the daemon with `--nobind`. `--nobind` implies `--nonotify`, so notifications will also be disabled. As with `--gid`, these options must be set at startup and cannot be changed while the daemon is running.

Chapter 5

Todo List

Global Kb::Kb (QObject *parent, const QString &path)

Is adding notify2 to the notifypaths neccessary?

Global Kb::~Kb ()

I don't think, that notifypaths is used somewhere. So why do we have it? If we do not need it, searching for an ununsed notify channel can easy be refactored to a private member function.

Chapter 6

Deprecated List

Class QuaZipFileInfo

Use QuaZipFileInfo64 instead. Not only it supports large files, but also more convenience methods as well.

Chapter 7

Namespace Index

7.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Ui 39

Chapter 8

Hierarchical Index

8.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AutoRun . . . 118
ckb_gradient . . . 1207
ckb_key . . . 1207
ckb_runctx . . . 1207
CkbSettings . . . 122
ColorMap . . . 149
curfile64_info . . . 1432
MPerfWidget::DpiUi . . . 768
file_in_zip64_read_info_s . . . 1361
KbFirmware::FW . . . 178
KPerfWidget::IndicatorUi . . . 693
JlCompress . . . 237
KbId . . . 1236
Key . . . 594
KeyMap . . . 627
KeyPatch . . . 1270
linkedlist_data_s . . . 1432
linkedlist_datablock_internal_s . . . 1432
AnimScript::Param . . . 52
GradientDialog::Preset . . . 786
QDialog . . . 788
- AnimAddDialog . . . 41
- AnimSettingDialog . . . 97
- ExtraSettingsWidget . . . 170
- FwUpgradeDialog . . . 179
- GradientDialog . . . 208
- KbProfileDialog . . . 548
- LayoutDialog . . . 711
- ModeSelectDialog . . . 745

QIODevice . . . 789
- QuaGzipFile . . . 805
- QuaZIODevice . . . 812
- QuaZipFile . . . 870

QIODevice_descriptor . . . 790
QListWidget . . . 791
- RListWidget . . . 989

QMainWindow . . . 792

MainWindow . . . 726
QObject . . . 793
AnimScript . . . 52
CkbSettingsWriter . . . 137
KbAnim . . . 305
KbBind . . . 360
KbFirmware . . . 407
KbLight . . . 419
KbManager . . . 470
KbMode . . . 482
KbPerf . . . 496
KbProfile . . . 530
KeyAction . . . 597
QPushButton . . . 794
ColorButton . . . 139
GradientButton . . . 194
qt_meta_stringdata_AnimAddDialog_t . . . 1500
qt_meta_stringdata_AnimScript_t . . . 1503
qt_meta_stringdata_AnimSettingDialog_t . . . 1506
qt_meta_stringdata_CkbSettingsWriter_t . . . 1509
qt_meta_stringdata_ColorButton_t . . . 1511
qt_meta_stringdata_ExtraSettingsWidget_t . . . 1513
qt_meta_stringdata_FwUpgradeDialog_t . . . 1516
qt_meta_stringdata_GradientButton_t . . . 1519
qt_meta_stringdata_GradientDialog_t . . . 1522
qt_meta_stringdata_GradientDialogWidget_t . . . 1525
qt_meta_stringdata_Kb_t . . . 1527
qt_meta_stringdata_KbAnim_t . . . 1530
qt_meta_stringdata_KbAnimWidget_t . . . 1532
qt_meta_stringdata_KbBind_t . . . 1535
qt_meta_stringdata_KbBindWidget_t . . . 1537
qt_meta_stringdata_KbFirmware_t . . . 1539
qt_meta_stringdata_KbLight_t . . . 1542
qt_meta_stringdata_KbLightWidget_t . . . 1545
qt_meta_stringdata_KbManager_t . . . 1548
qt_meta_stringdata_KbMode_t . . . 1550
qt_meta_stringdata_KbPerf_t . . . 1552
qt_meta_stringdata_KbProfile_t . . . 1555
qt_meta_stringdata_KbProfileDialog_t . . . 1557
qt_meta_stringdata_KbWidget_t . . . 1561
qt_meta_stringdata_KeyAction_t . . . 1563
qt_meta_stringdata_KeyWidget_t . . . 1565
qt_meta_stringdata_KPerfWidget_t . . . 1567
qt_meta_stringdata_LayoutDialog_t . . . 1570
qt_meta_stringdata_MacroReader_t . . . 1573
qt_meta_stringdata_MacroReaderThread_t . . . 1573
qt_meta_stringdata_MainWindow_t . . . 1577
qt_meta_stringdata_ModeSelectDialog_t . . . 1579
qt_meta_stringdata_MPerfWidget_t . . . 1581
qt_meta_stringdata_QuaGzipFile_t . . . 1584
qt_meta_stringdata_QuaZIODevice_t . . . 1586
qt_meta_stringdata_QuaZipFile_t . . . 1588
qt_meta_stringdata_RebindWidget_t . . . 1590
qt_meta_stringdata_RListWidget_t . . . 1593
qt_meta_stringdata_SettingsWidget_t . . . 1595
QThread . . . 795
Kb . . . 255

MacroReader . . . 714
MacroReaderThread . . . 718
QuaChecksum32 . . . 799
QuaAdler32 . . . 796
QuaCrc32 . . . 802
QuaZip . . . 820
QuaZipDir . . . 852
QuaZipFileInfo . . . 893
QuaZipFileInfo64 . . . 896
QuaZipFilePrivate . . . 904
QuaZipNewInfo . . . 909
QuaZipPrivate . . . 917
QWidget . . . 926
GradientDialogWidget . . . 221
KbAnimWidget . . . 342
KbBindWidget . . . 396
KbLightWidget . . . 457
KbWidget . . . 562
KeyWidget . . . 650
KPerfWidget . . . 693
MPerfWidget . . . 768
RebindWidget . . . 956
SettingsWidget . . . 994
SGroup . . . 1018
tm_unz_s . . . 1412
tm_zip_s . . . 1488
Ui_AnimAddDialog . . . 1021
Ui::AnimAddDialog . . . 47
Ui_AnimSettingDialog . . . 1025
Ui::AnimSettingDialog . . . 84
Ui_ExtraSettingsWidget . . . 1038
Ui::ExtraSettingsWidget . . . 157
Ui_FwUpgradeDialog . . . 1050
Ui::FwUpgradeDialog . . . 188
Ui_GradientDialog . . . 1056
Ui::GradientDialog . . . 200
Ui_KbAnimWidget . . . 1064
Ui::KbAnimWidget . . . 332
Ui_KbBindWidget . . . 1073
Ui::KbBindWidget . . . 389
Ui_KbLightWidget . . . 1079
Ui::KbLightWidget . . . 448
Ui_KbProfileDialog . . . 1087
Ui::KbProfileDialog . . . 557
Ui_KbWidget . . . 1091
Ui::KbWidget . . . 584
Ui_KPerfWidget . . . 1101
Ui::KPerfWidget . . . 673
Ui_LayoutDialog . . . 1120
Ui::LayoutDialog . . . 706
Ui_MainWindow . . . 1125
Ui::MainWindow . . . 722
Ui_ModeSelectDialog . . . 1129

Ui::ModeSelectDialog 741
Ui_MPerfWidget 1133
Ui::MPerfWidget 749
Ui_RebindWidget 1152
Ui::RebindWidget 927
Ui_SettingsWidget 1181
Ui::SettingsWidget 1006
unz64_file_pos_s 1412
unz64_s 1361
unz_file_info64_internal_s 1361
unz_file_info64_s 1412
unz_file_info_s 1412
unz_file_pos_s 1412
unz_global_info64_s 1412
unz_global_info_s 1412
UsbId 1193
zip64_internal 1432
zip_fileinfo 1488
zlib_filefunc64_32_def_s 1314
zlib_filefunc64_def_s 1314
zlib_filefunc_def_s 1314

Chapter 9

Data Structure Index

9.1 Data Structures

Here are the data structures with brief descriptions:

AnimAddDialog . . . 41
Ui::AnimAddDialog . . . 47
AnimScript . . . 52
Ui::AnimSettingDialog . . . 84
AnimSettingDialog . . . 97
AutoRun . . . 118
CkbSettings . . . 122
CkbSettingsWriter . . . 137
ColorButton . . . 139
ColorMap . . . 149
Ui::ExtraSettingsWidget . . . 157
ExtraSettingsWidget . . . 170
KbFirmware::FW . . . 178
FwUpgradeDialog . . . 179
Ui::FwUpgradeDialog . . . 188
GradientButton . . . 194
Ui::GradientDialog . . . 200
GradientDialog . . . 208
GradientDialogWidget . . . 221
JlCompress
Utility class for typical operations . . . 237
Kb . . . 255
KbAnim . . . 305
Ui::KbAnimWidget . . . 332
KbAnimWidget . . . 342
KbBind . . . 360
Ui::KbBindWidget . . . 389
KbBindWidget . . . 396
KbFirmware . . . 407
KbLight . . . 419
Ui::KbLightWidget . . . 448
KbLightWidget . . . 457
KbManager . . . 470
KbMode . . . 482
KbPerf . . . 496
KbProfile . . . 530
KbProfileDialog . . . 548
Ui::KbProfileDialog . . . 557

KbWidget . . . 562
Ui::KbWidget . . . 584
Key . . . 594
KeyAction . . . 597
KeyMap . . . 627
KeyWidget . . . 650
Ui::KPerfWidget . . . 673
KPerfWidget . . . 693
Ui::LayoutDialog . . . 706
LayoutDialog . . . 711
MacroReader
Creates a worker thread object. It does a connect do delayed deletion of thread local variables in the case the worker thread terminates . . . 714
MacroReaderThread
Responsible for reading Macro Key Values. It is created as a separate thread (worker thread) for reading macro commands from an fresh opened notify channel. Standard notify channel for macro definitions is number 2 . . . 718
Ui::MainWindow . . . 722
MainWindow . . . 726
Ui::ModeSelectDialog . . . 741
ModeSelectDialog . . . 745
Ui::MPerfWidget . . . 749
MPerfWidget . . . 768
GradientDialog::Preset . . . 786
QDialog . . . 788
QIODevice . . . 789
QIODevice_descriptor . . . 790
QListWidget . . . 791
QMainWindow . . . 792
QObject . . . 793
QPushButton . . . 794
QThread . . . 795
QuaAdler32
Adler32 checksum . . . 796
QuaChecksum32
Checksum interface . . . 799
QuaCrc32
CRC32 checksum . . . 802
QuaGzipFile
GZIP file . . . 805
QuaZIODevice
A class to compress/decompress QIODevice . . . 812
QuaZip
ZIP archive . . . 820
QuaZipDir
Provides ZIP archive navigation . . . 852
QuaZipFile
A file inside ZIP archive . . . 870
QuaZipFileInfo
Information about a file inside archive . . . 893
QuaZipFileInfo64
Information about a file inside archive (with zip64 support) . . . 896
QuaZipFilePrivate
The implementation class for QuaZip . . . 904
QuaZipNewInfo
Information about a file to be created . . . 909
QuaZipPrivate
All the internal stuff for the QuaZip class . . . 917

QWidget 926
Ui::RebindWidget 927
RebindWidget 956
RListWidget 989
SettingsWidget 994
Ui::SettingsWidget 1006
SGroup 1018
Ui_AnimAddDialog 1021
Ui_AnimSettingDialog 1025
Ui_ExtraSettingsWidget 1038
Ui_FwUpgradeDialog 1050
Ui_GradientDialog 1056
Ui_KbAnimWidget 1064
Ui_KbBindWidget 1073
Ui_KbLightWidget 1079
Ui_KbProfileDialog 1087
Ui_KbWidget 1091
Ui_KPerfWidget 1101
Ui_LayoutDialog 1120
Ui_MainWindow 1125
Ui_ModeSelectDialog 1129
Ui_MPerfWidget 1133
Ui_RebindWidget 1152
Ui_SettingsWidget 1181
UsbId 1193

Chapter 10

File Index

10.1 File List

Here is a list of all files with brief descriptions:

src/ckb/animadddialog.cpp . . . 1199
src/ckb/animadddialog.h . . . 1199
src/ckb/animscript.cpp . . . 1200
src/ckb/animscript.h . . . 1202
src/ckb/animsettingdialog.cpp . . . 1203
src/ckb/animsettingdialog.h . . . 1205
src/ckb/autorun.cpp . . . 1205
src/ckb/autorun.h . . . 1206
src/ckb/ckb-anim.h . . . 1207
src/ckb/ckbsettings.cpp . . . 1226
src/ckb/ckbsettings.h . . . 1228
src/ckb/ckbsettingswriter.cpp . . . 1229
src/ckb/ckbsettingswriter.h . . . 1231
src/ckb/colorbutton.cpp . . . 1231
src/ckb/colorbutton.h . . . 1232
src/ckb/colormap.cpp . . . 1233
src/ckb/colormap.h . . . 1234
src/ckb/extrasettingswidget.cpp . . . 1235
src/ckb/extrasettingswidget.h . . . 1236
src/ckb/fwupgradedialog.cpp . . . 1236
src/ckb/fwupgradedialog.h . . . 1239
src/ckb/gradientbutton.cpp . . . 1240
src/ckb/gradientbutton.h . . . 1241
src/ckb/gradientdialog.cpp . . . 1242
src/ckb/gradientdialog.h . . . 1242
src/ckb/gradientdialogwidget.cpp . . . 1243
src/ckb/gradientdialogwidget.h . . . 1243
src/ckb/kb.cpp . . . 1244
src/ckb/kb.h . . . 1245
src/ckb/kbanim.cpp . . . 1246
src/ckb/kbanim.h . . . 1248
src/ckb/kbanimwidget.cpp . . . 1249
src/ckb/kbanimwidget.h . . . 1249
src/ckb/kbbind.cpp . . . 1250
src/ckb/kbbind.h . . . 1251
src/ckb/kbbindwidget.cpp . . . 1252
src/ckb/kbbindwidget.h . . . 1252
src/ckb/kbfirmware.cpp . . . 1253

src/ckb/kbfirmware.h . . . 1254
src/ckb/kblight.cpp . . . 1255
src/ckb/kblight.h . . . 1258
src/ckb/kblightwidget.cpp . . . 1259
src/ckb/kblightwidget.h . . . 1259
src/ckb/kbmanager.cpp . . . 1260
src/ckb/kbmanager.h . . . 1261
src/ckb/kbmode.cpp . . . 1262
src/ckb/kbmode.h . . . 1262
src/ckb/kbperf.cpp . . . 1263
src/ckb/kbperf.h . . . 1263
src/ckb/kbprofile.cpp . . . 1264
src/ckb/kbprofile.h . . . 1265
src/ckb/kbprofiledialog.cpp . . . 1265
src/ckb/kbprofiledialog.h . . . 1266
src/ckb/kbwidget.cpp . . . 1267
src/ckb/kbwidget.h . . . 1267
src/ckb/keyaction.cpp . . . 1268
src/ckb/keyaction.h . . . 1269
src/ckb/keymap.cpp . . . 1270
src/ckb/keymap.h . . . 1284
src/ckb/keywidget.cpp . . . 1284
src/ckb/keywidget.h . . . 1286
src/ckb/kperfwidget.cpp . . . 1287
src/ckb/kperfwidget.h . . . 1288
src/ckb/layoutdialog.cpp . . . 1290
src/ckb/layoutdialog.h . . . 1290
src/ckb/macroreader.cpp . . . 1291
src/ckb/macroreader.h . . . 1291
src/ckb/main.cpp . . . 1292
src/ckb/mainwindow.cpp . . . 1299
src/ckb/mainwindow.h . . . 1299
src/ckb/media.h . . . 1300
src/ckb/media_linux.cpp . . . 1302
src/ckb/media_mac.m . . . 1303
src/ckb/modeselectdialog.cpp . . . 1305
src/ckb/modeselectdialog.h . . . 1305
src/ckb/mperfwidget.cpp . . . 1306
src/ckb/mperfwidget.h . . . 1309
src/ckb/rebindwidget.cpp . . . 1499
src/ckb/rebindwidget.h . . . 1499
src/ckb/rlistwidget.cpp . . . 1606
src/ckb/rlistwidget.h . . . 1606
src/ckb/settingswidget.cpp . . . 1607
src/ckb/settingswidget.h . . . 1609
src/ckb/ui_animadddialog.h . . . 1610
src/ckb/ui_animsettingdialog.h . . . 1611
src/ckb/ui_extrasettingswidget.h . . . 1611
src/ckb/ui_fwupgradedialog.h . . . 1612
src/ckb/ui_gradientdialog.h . . . 1613
src/ckb/ui_kbanimwidget.h . . . 1614
src/ckb/ui_kbbindwidget.h . . . 1615
src/ckb/ui_kblightwidget.h . . . 1616
src/ckb/ui_kbprofiledialog.h . . . 1617
src/ckb/ui_kbwidget.h . . . 1618
src/ckb/ui_kperfwidget.h . . . 1619
src/ckb/ui_layoutdialog.h . . . 1620
src/ckb/ui_mainwindow.h . . . 1621

src/ckb/ui_modeselectdialog.h . . . 1622
src/ckb/ui_mperfwidget.h . . . 1623
src/ckb/ui_rebindwidget.h . . . 1624
src/ckb/ui_settingswidget.h . . . 1625
src/ckb/quazip/crypt.h . . . 1311
src/ckb/quazip/ioapi.h . . . 1314
src/ckb/quazip/JlCompress.cpp . . . 1321
src/ckb/quazip/JlCompress.h . . . 1323
src/ckb/quazip/qioapi.cpp . . . 1323
src/ckb/quazip/quaadler32.cpp . . . 1335
src/ckb/quazip/quaadler32.h . . . 1336
src/ckb/quazip/quachecksum32.h . . . 1337
src/ckb/quazip/quacrc32.cpp . . . 1338
src/ckb/quazip/quacrc32.h . . . 1339
src/ckb/quazip/quagzipfile.cpp . . . 1340
src/ckb/quazip/quagzipfile.h . . . 1341
src/ckb/quazip/quaziodevice.cpp . . . 1342
src/ckb/quazip/quaziodevice.h . . . 1343
src/ckb/quazip/quazip.cpp . . . 1344
src/ckb/quazip/quazip.h . . . 1346
src/ckb/quazip/quazip_global.h . . . 1347
src/ckb/quazip/quazipdir.cpp . . . 1349
src/ckb/quazip/quazipdir.h . . . 1351
src/ckb/quazip/quazipfile.cpp . . . 1351
src/ckb/quazip/quazipfile.h . . . 1352
src/ckb/quazip/quazipfileinfo.cpp . . . 1353
src/ckb/quazip/quazipfileinfo.h . . . 1355
src/ckb/quazip/quazipnewinfo.cpp . . . 1356
src/ckb/quazip/quazipnewinfo.h . . . 1360
src/ckb/quazip/unzip.c . . . 1361
src/ckb/quazip/unzip.h . . . 1412
src/ckb/quazip/zip.c . . . 1432
src/ckb/quazip/zip.h . . . 1488
src/ckb/release/moc_animadddialog.cpp . . . 1500
src/ckb/release/moc_animscript.cpp . . . 1503
src/ckb/release/moc_animsettingdialog.cpp . . . 1506
src/ckb/release/moc_ckbsettingswriter.cpp . . . 1509
src/ckb/release/moc_colorbutton.cpp . . . 1511
src/ckb/release/moc_extrasettingswidget.cpp . . . 1513
src/ckb/release/moc_fwupgradedialog.cpp . . . 1516
src/ckb/release/moc_gradientbutton.cpp . . . 1519
src/ckb/release/moc_gradientdialog.cpp . . . 1522
src/ckb/release/moc_gradientdialogwidget.cpp . . . 1525
src/ckb/release/moc_kb.cpp . . . 1527
src/ckb/release/moc_kbanim.cpp . . . 1530
src/ckb/release/moc_kbanimwidget.cpp . . . 1532
src/ckb/release/moc_kbbind.cpp . . . 1535
src/ckb/release/moc_kbbindwidget.cpp . . . 1537
src/ckb/release/moc_kbfirmware.cpp . . . 1539
src/ckb/release/moc_kblight.cpp . . . 1542
src/ckb/release/moc_kblightwidget.cpp . . . 1545
src/ckb/release/moc_kbmanager.cpp . . . 1548
src/ckb/release/moc_kbmode.cpp . . . 1550
src/ckb/release/moc_kbperf.cpp . . . 1552
src/ckb/release/moc_kbprofile.cpp . . . 1555
src/ckb/release/moc_kbprofiledialog.cpp . . . 1557
src/ckb/release/moc_kbwidget.cpp . . . 1561
src/ckb/release/moc_keyaction.cpp . . . 1563

src/ckb/release/moc_keywidget.cpp 1565
src/ckb/release/moc_kperfwidget.cpp 1567
src/ckb/release/moc_layoutdialog.cpp 1570
src/ckb/release/moc_macroreader.cpp 1573
src/ckb/release/moc_mainwindow.cpp 1577
src/ckb/release/moc_modeselectdialog.cpp 1579
src/ckb/release/moc_mperfwidget.cpp 1581
src/ckb/release/moc_quagzipfile.cpp 1584
src/ckb/release/moc_quaziodevice.cpp 1586
src/ckb/release/moc_quazipfile.cpp 1588
src/ckb/release/moc_rebindwidget.cpp 1590
src/ckb/release/moc_rlistwidget.cpp 1593
src/ckb/release/moc_settingswidget.cpp 1595
src/ckb/release/qrc_binary.cpp 1597
src/ckb/release/qrc_image.cpp 1600
src/ckb/release/qrc_text.cpp 1603

Chapter 11

Namespace Documentation

11.1 Ui Namespace Reference

Data Structures

- class AnimAddDialog
- class AnimSettingDialog
- class ExtraSettingsWidget
- class FwUpgradeDialog
- class GradientDialog
- class KbAnimWidget
- class KbBindWidget
- class KbLightWidget
- class KbProfileDialog
- class KbWidget
- class KPerfWidget
- class LayoutDialog
- class MainWindow
- class ModeSelectDialog
- class MPerfWidget
- class RebindWidget
- class SettingsWidget

Chapter 12

Data Structure Documentation

12.1 AnimAddDialog Class Reference

```
#include <src/ckb/animadddialog.h>
```

Inheritance diagram for AnimAddDialog:

Collaboration diagram for AnimAddDialog:

Public Member Functions

- AnimAddDialog (QWidget ∗parent, KbLight ∗light, const QStringList &keys)
- ∼AnimAddDialog ()
- const AnimScript ∗ chosenScript ()
- int chosenPreset ()

Private Slots

- void on_animBox_activated (int index)
- void on_presetBox_activated (int index)
- void on_previewBox_clicked (bool checked)

Private Attributes

- Ui::AnimAddDialog ∗ ui
- QList< const AnimScript ∗ > scripts
- KbLight ∗ _light
- QStringList _keys
- bool showPreview

12.1.1 Detailed Description

Definition at line 12 of file animadddialog.h.

12.1.2 Constructor & Destructor Documentation

12.1.2.1 AnimAddDialog::AnimAddDialog (QWidget * *parent*, KbLight * *light*, const QStringList & *keys*) [explicit]

Definition at line 4 of file animadddialog.cpp.

References Ui_AnimAddDialog::animBox, AnimScript::list(), AnimScript::name(), on_animBox_activated(), scripts, Ui_AnimAddDialog::setupUi(), and ui.

```
4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
5     QDialog(parent),
6     ui(new Ui::AnimAddDialog), _light(light), _keys(keys),
      showPreview(true)
7 {
8     ui->setupUi(this);
9     scripts = AnimScript::list();
10     foreach(const AnimScript* script, scripts)
11         ui->animBox->addItem(script->name());
12     on_animBox_activated(0);
13 }
```

Here is the call graph for this function:

12.1.2.2 AnimAddDialog::~AnimAddDialog ( )

Definition at line 15 of file animadddialog.cpp.

References _light, KbLight::stopPreview(), and ui.

```
15                                  {
16     delete ui;
17     _light->stopPreview();
18 }
```

Here is the call graph for this function:

12.1.3 Member Function Documentation

12.1.3.1 int AnimAddDialog::chosenPreset ( )

Definition at line 24 of file animadddialog.cpp.

References Ui_AnimAddDialog::presetBox, and ui.

Referenced by KbLightWidget::on_animButton_clicked().

```
                                {
    return ui->presetBox->currentIndex();
}
```

Here is the caller graph for this function:

12.1.3.2 const AnimScript * AnimAddDialog::chosenScript ( )

Definition at line 20 of file animadddialog.cpp.

References Ui_AnimAddDialog::animBox, scripts, and ui.

Referenced by on_animBox_activated(), KbLightWidget::on_animButton_clicked(), and on_presetBox_activated().

```
                                        {
    return scripts[ui->animBox->currentIndex()];
}
```

Here is the caller graph for this function:

12.1.3.3 void AnimAddDialog::on_animBox_activated (int *index*) [private],[slot]

Definition at line 28 of file animadddialog.cpp.

References chosenScript(), on_presetBox_activated(), Ui_AnimAddDialog::presetBox, and ui.

Referenced by AnimAddDialog().

```
                                            {
    // Update preset list
    ui->presetBox->clear();
    foreach(const QString& preset, chosenScript()->presets())
        ui->presetBox->addItem(preset);
    ui->presetBox->setCurrentIndex(0);
    on_presetBox_activated(0);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.1.3.4 void AnimAddDialog::on_presetBox_activated (int *index*) [private],[slot]

Definition at line 37 of file animadddialog.cpp.

References _keys, _light, chosenScript(), KbLight::previewAnim(), and showPreview.

Referenced by on_animBox_activated(), and on_previewBox_clicked().

```
37                                                  {
38     // Update preview
39     if(showPreview)
40         _light->previewAnim(chosenScript(), _keys,
     chosenScript()->preset(index));
41 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.1.3.5 void AnimAddDialog::on_previewBox_clicked (bool *checked*) [private], [slot]

Definition at line 43 of file animadddialog.cpp.

References _light, on_presetBox_activated(), Ui_AnimAddDialog::presetBox, showPreview, KbLight::stopPreview(), and ui.

```
43                                                  {
44     showPreview = checked;
45     if(showPreview)
46         on_presetBox_activated(ui->presetBox->currentIndex());
47     else
48         _light->stopPreview();
49 }
```

Here is the call graph for this function:

12.1.4 Field Documentation

12.1.4.1 QStringList AnimAddDialog::_keys [private]

Definition at line 33 of file animadddialog.h.

Referenced by on_presetBox_activated().

12.1.4.2 KbLight* AnimAddDialog::_light [private]

Definition at line 32 of file animadddialog.h.

Referenced by on_presetBox_activated(), on_previewBox_clicked(), and ~AnimAddDialog().

12.1.4.3 QList<const AnimScript*> AnimAddDialog::scripts [private]

Definition at line 30 of file animadddialog.h.

Referenced by AnimAddDialog(), and chosenScript().

12.1.4.4 bool AnimAddDialog::showPreview [private]

Definition at line 34 of file animadddialog.h.

Referenced by on_presetBox_activated(), and on_previewBox_clicked().

12.1.4.5 Ui::AnimAddDialog* AnimAddDialog::ui [private]

Definition at line 29 of file animadddialog.h.

Referenced by AnimAddDialog(), chosenPreset(), chosenScript(), on_animBox_activated(), on_previewBox_clicked(), and ~AnimAddDialog().

The documentation for this class was generated from the following files:

- src/ckb/animadddialog.h
- src/ckb/animadddialog.cpp

12.2 Ui::AnimAddDialog Class Reference

```
#include <src/ckb/ui_animadddialog.h>
```

Inheritance diagram for Ui::AnimAddDialog:

Collaboration diagram for Ui::AnimAddDialog:

Public Member Functions

- void setupUi (QDialog ∗AnimAddDialog)
- void retranslateUi (QDialog ∗AnimAddDialog)

Data Fields

- QGridLayout ∗ gridLayout
- QHBoxLayout ∗ horizontalLayout
- QDialogButtonBox ∗ buttonBox
- QSpacerItem ∗ horizontalSpacer_2
- QComboBox ∗ animBox
- QLabel ∗ label_2
- QSpacerItem ∗ verticalSpacer_2
- QLabel ∗ label
- QSpacerItem ∗ verticalSpacer_3
- QComboBox ∗ presetBox
- QSpacerItem ∗ horizontalSpacer
- QCheckBox ∗ previewBox

12.2.1 Detailed Description

Definition at line 146 of file ui_animadddialog.h.

12.2.2 Member Function Documentation

12.2.2.1 void Ui_AnimAddDialog::retranslateUi (QDialog ∗ *AnimAddDialog*) [inline],[inherited]

Definition at line 135 of file ui_animadddialog.h.

References Ui_AnimAddDialog::label, Ui_AnimAddDialog::label_2, and Ui_AnimAddDialog::previewBox.

Referenced by Ui_AnimAddDialog::setupUi().

```
    {
        AnimAddDialog->setWindowTitle(QApplication::translate("AnimAddDialog", "Add Animation", Q_NULLPTR));
        label_2->setText(QApplication::translate("AnimAddDialog", "Preset:", Q_NULLPTR));
```

```
        label->setText(QApplication::translate("AnimAddDialog", "Animation:", Q_NULLPTR));
        previewBox->setText(QApplication::translate("AnimAddDialog", "Show preview", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.2.2.2 void Ui_AnimAddDialog::setupUi (QDialog * *AnimAddDialog*) [inline],[inherited]

Definition at line 44 of file ui_animadddialog.h.

References Ui_AnimAddDialog::animBox, Ui_AnimAddDialog::buttonBox, Ui_AnimAddDialog::gridLayout, Ui_AnimAddDialog::horizontalLayout, Ui_AnimAddDialog::horizontalSpacer, Ui_AnimAddDialog::horizontalSpacer_2, Ui_AnimAddDialog::label, Ui_AnimAddDialog::label_2, Ui_AnimAddDialog::presetBox, Ui_AnimAddDialog::previewBox, Ui_AnimAddDialog::retranslateUi(), Ui_AnimAddDialog::verticalSpacer_2, and Ui_AnimAddDialog::verticalSpacer_3.

Referenced by AnimAddDialog::AnimAddDialog().

```
    {
        if (AnimAddDialog->objectName().isEmpty())
            AnimAddDialog->setObjectName(QStringLiteral("AnimAddDialog"));
        AnimAddDialog->resize(350, 205);
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(AnimAddDialog->sizePolicy().hasHeightForWidth());
        AnimAddDialog->setSizePolicy(sizePolicy);
        gridLayout = new QGridLayout(AnimAddDialog);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        buttonBox = new QDialogButtonBox(AnimAddDialog);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
        buttonBox->setCenterButtons(false);

        horizontalLayout->addWidget(buttonBox);


        gridLayout->addLayout(horizontalLayout, 5, 0, 1, 4);

        horizontalSpacer_2 = new QSpacerItem(50, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_2, 1, 3, 1, 1);

        animBox = new QComboBox(AnimAddDialog);
        animBox->setObjectName(QStringLiteral("animBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(animBox->sizePolicy().hasHeightForWidth());
        animBox->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(animBox, 1, 2, 1, 1);

        label_2 = new QLabel(AnimAddDialog);
        label_2->setObjectName(QStringLiteral("label_2"));
        QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Preferred);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(label_2->sizePolicy().hasHeightForWidth());
        label_2->setSizePolicy(sizePolicy2);
        label_2->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout->addWidget(label_2, 2, 1, 1, 1);

```

```
        verticalSpacer_2 = new QSpacerItem(20, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer_2, 4, 2, 1, 1);

        label = new QLabel(AnimAddDialog);
        label->setObjectName(QStringLiteral("label"));
         sizePolicy2.setHeightForWidth(label->sizePolicy().hasHeightForWidth());
         label->setSizePolicy(sizePolicy2);
         label->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

         gridLayout->addWidget(label, 1, 1, 1, 1);

         verticalSpacer_3 = new QSpacerItem(20, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);

         gridLayout->addItem(verticalSpacer_3, 0, 2, 1, 1);

         presetBox = new QComboBox(AnimAddDialog);
         presetBox->setObjectName(QStringLiteral("presetBox"));
         sizePolicy1.setHeightForWidth(presetBox->sizePolicy().hasHeightForWidth());
         presetBox->setSizePolicy(sizePolicy1);

         gridLayout->addWidget(presetBox, 2, 2, 1, 1);

         horizontalSpacer = new QSpacerItem(50, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

         gridLayout->addItem(horizontalSpacer, 1, 0, 1, 1);

         previewBox = new QCheckBox(AnimAddDialog);
         previewBox->setObjectName(QStringLiteral("previewBox"));
         previewBox->setChecked(true);

         gridLayout->addWidget(previewBox, 3, 2, 1, 1);


         retranslateUi(AnimAddDialog);
         QObject::connect(buttonBox, SIGNAL(accepted()), AnimAddDialog, SLOT(accept()));
         QObject::connect(buttonBox, SIGNAL(rejected()), AnimAddDialog, SLOT(reject()));

         QMetaObject::connectSlotsByName(AnimAddDialog);
     } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.2.3 Field Documentation

12.2.3.1 QComboBox* Ui_AnimAddDialog::animBox [inherited]

Definition at line 35 of file ui_animadddialog.h.

Referenced by AnimAddDialog::AnimAddDialog(), AnimAddDialog::chosenScript(), and Ui_AnimAddDialog::setupUi().

12.2.3.2 QDialogButtonBox* Ui_AnimAddDialog::buttonBox [inherited]

Definition at line 33 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.3 QGridLayout* Ui_AnimAddDialog::gridLayout [inherited]

Definition at line 31 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.4 QHBoxLayout* Ui_AnimAddDialog::horizontalLayout [inherited]

Definition at line 32 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.5 QSpacerItem* Ui_AnimAddDialog::horizontalSpacer [inherited]

Definition at line 41 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.6 QSpacerItem* Ui_AnimAddDialog::horizontalSpacer_2 [inherited]

Definition at line 34 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.7 QLabel* Ui_AnimAddDialog::label [inherited]

Definition at line 38 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::retranslateUi(), and Ui_AnimAddDialog::setupUi().

12.2.3.8 QLabel* Ui_AnimAddDialog::label_2 [inherited]

Definition at line 36 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::retranslateUi(), and Ui_AnimAddDialog::setupUi().

12.2.3.9 QComboBox* Ui_AnimAddDialog::presetBox [inherited]

Definition at line 40 of file ui_animadddialog.h.

Referenced by AnimAddDialog::chosenPreset(), AnimAddDialog::on_animBox_activated(), AnimAddDialog::on_previewBox_clicked(), and Ui_AnimAddDialog::setupUi().

12.2.3.10 QCheckBox* Ui_AnimAddDialog::previewBox [inherited]

Definition at line 42 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::retranslateUi(), and Ui_AnimAddDialog::setupUi().

12.2.3.11 QSpacerItem* Ui_AnimAddDialog::verticalSpacer_2 [inherited]

Definition at line 37 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

12.2.3.12 QSpacerItem* Ui_AnimAddDialog::verticalSpacer_3 [inherited]

Definition at line 39 of file ui_animadddialog.h.

Referenced by Ui_AnimAddDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_animadddialog.h

12.3 AnimScript Class Reference

```
#include <src/ckb/animscript.h>
```

Inheritance diagram for AnimScript:

Collaboration diagram for AnimScript:

Data Structures

- struct Param

Public Types

- typedef QMap< QString, QVariant > PresetValue

Public Member Functions

- const QUuid & guid () const
- const QString & name () const
- const QString & version () const
- QString copyright () const
- const QString & year () const
- const QString & author () const
- const QString & license () const
- const QString & description () const
- bool hasKeypress () const
- const QStringList & presets () const
- const PresetValue & preset (int index) const
- QListIterator< Param > paramIterator () const
- Param param (const QString &name) const
- bool hasParam (const QString &name) const
- void init (const KeyMap &map, const QStringList &keys, const QMap< QString, QVariant > &paramValues)
- void parameters (const QMap< QString, QVariant > &paramValues)
- void retrigger (quint64 timestamp, bool allowPreempt=false)
- void stop (quint64 timestamp)
- void keypress (const QString &key, bool pressed, quint64 timestamp)

- void frame (quint64 timestamp)
- void end ()
- bool hasFrame () const
- const ColorMap & colors () const
- ~AnimScript ()

Static Public Member Functions

- static QString path ()
- static void scan ()
- static int count ()
- static QList< const AnimScript * > list ()
- static AnimScript * copy (QObject *parent, const QUuid &id)

Private Slots

- void readProcess ()

Private Member Functions

- bool load ()
- void setDuration ()
- void printParams ()
- void begin (quint64 timestamp)
- void advance (quint64 timestamp)
- AnimScript (QObject *parent, const QString &path)
- AnimScript (QObject *parent, const AnimScript &base)

Private Attributes

- struct {
  QUuid **guid**
  QString **name**
  QString **version**
  QString **year**
  QString **author**
  QString **license**
  QString **description**
  QList< Param > **params**
  int **kpMode**:3
  bool **absoluteTime**:1
  bool **repeat**:1
  bool **preempt**:1
  bool **liveParams**:1
  } _info

- QStringList _presets
- QList< PresetValue > _presetValues
- QString _path
- KeyMap _map
- int minX
- int minY
- QStringList _keys

- ColorMap _colors
- PresetValue _paramValues
- quint64 lastFrame
- int durationMsec
- int repeatMsec
- bool initialized:1
- bool firstFrame:1
- bool readFrame:1
- bool readAnyFrame:1
- bool stopped:1
- bool inFrame:1
- QProcess * process
- ColorMap _colorBuffer

Static Private Attributes

- static const int KP_NONE = 0
- static const int KP_NAME = 1
- static const int KP_POSITION = 2
- static QHash< QUuid, AnimScript * > scripts

12.3.1 Detailed Description

Definition at line 16 of file animscript.h.

12.3.2 Data Structure Documentation

12.3.2.1 struct AnimScript::Param

Definition at line 21 of file animscript.h.

Collaboration diagram for AnimScript::Param:

Data Fields

	Type	

Data Fields

QVariant	defaultValue	
QVariant	maximum	
QVariant	minimum	
QString	name	
QString	postfix	
QString	prefix	
Type	type	

12.3.3 Member Typedef Documentation

12.3.3.1 typedef QMap<QString, QVariant> AnimScript::PresetValue

Definition at line 58 of file animscript.h.

12.3.4 Constructor & Destructor Documentation

12.3.4.1 AnimScript::~AnimScript ( )

Definition at line 21 of file animscript.cpp.

References process.

```
21                          {
22      if(process){
23          process->kill();
24          process->waitForFinished(1000);
25          delete process;
26      }
27  }
```

12.3.4.2 AnimScript::AnimScript (QObject * *parent*, const QString & *path*) [private]

Definition at line 11 of file animscript.cpp.

Referenced by copy(), and scan().

```
11                                                          :
12      QObject(parent), _path(path), initialized(false),
       process(0)
13  {
14  }
```

Here is the caller graph for this function:

12.3.4.3 AnimScript::AnimScript (QObject * *parent*, const AnimScript & *base*) [private]

Definition at line 16 of file animscript.cpp.

```
16                                                          :
17     QObject(parent), _info(base._info), _path(base._path),
      initialized(false), process(0)
18 {
19 }
```

12.3.5 Member Function Documentation

12.3.5.1 void AnimScript::advance (quint64 *timestamp*) [private]

Definition at line 445 of file animscript.cpp.

References _info, durationMsec, lastFrame, and process.

Referenced by frame(), keypress(), retrigger(), and stop().

```
445                                          {
446     if(timestamp <= lastFrame || !process)
447         // Don't do anything if the time hasn't actually advanced.
448         return;
449     double delta = (timestamp - lastFrame) / (double)durationMsec;
450     if(!_info.absoluteTime){
451         // Skip any complete durations
452         while(delta > 1.){
453             process->write("time 1\n");
454             delta--;
455         }
456     }
457     process->write(QString("time %1\n").arg(delta).toLatin1());
458     lastFrame = timestamp;
459 }
```

Here is the caller graph for this function:

12.3.5.2 const QString& AnimScript::author ( ) const [inline]

Definition at line 64 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
64 { return _info.author; }
```

Here is the caller graph for this function:

12.3.5.3 void AnimScript::begin (quint64 *timestamp*) [private]

Definition at line 287 of file animscript.cpp.

References _keys, _map, _path, end(), firstFrame, inFrame, initialized, KeyMap::key(), lastFrame, minX, minY, printParams(), process, readAnyFrame, readFrame, readProcess(), stopped, Key::x, and Key::y.

Referenced by frame(), keypress(), retrigger(), and stop().

```
287                                         {
288     if(!initialized)
289         return;
290     end();
291     stopped = firstFrame = readFrame = readAnyFrame =
      inFrame = false;
292     // Determine the upper left corner of the given keys
293     QStringList keysCopy = _keys;
294     minX = INT_MAX;
295     minY = INT_MAX;
296     foreach(const QString& key, keysCopy){
297         const Key& pos = _map.key(key);
298         if(!pos){
299             keysCopy.removeAll(key);
300             continue;
301         }
302         if(pos.x < minX)
303             minX = pos.x;
304         if(pos.y < minY)
305             minY = pos.y;
306     }
307     if(keysCopy.isEmpty()){
308         // If the key list is empty, don't actually start the animation but pretend it's running anyway
309         firstFrame = readFrame = readAnyFrame = true;
310         return;
311     }
312     process = new QProcess(this);
313     connect(process, SIGNAL(readyRead()), this, SLOT(readProcess()));
314     process->start(_path, QStringList("--ckb-run"));
315     qDebug() << "Starting " << _path;
316     // Write the keymap to the process
317     process->write("begin keymap\n");
318     process->write(QString("keycount %1\n").arg(keysCopy.count()).toLatin1());
319     foreach(const QString& key, keysCopy){
320         const Key& pos = _map.key(key);
321         process->write(QString("key %1 %2,%3\n").arg(key).arg(pos.x -
      minX).arg(pos.y - minY).toLatin1());
322     }
323     process->write("end keymap\n");
324     // Write parameters
325     printParams();
326     // Begin animating
327     process->write("begin run\n");
328     lastFrame = timestamp;
329 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.4 const ColorMap& AnimScript::colors ( ) const [inline]

Definition at line 99 of file animscript.h.

References _colors.

Referenced by KbAnim::blend().

```
99 { return _colors; }
```

Here is the caller graph for this function:

12.3.5.5 AnimScript * AnimScript::copy (QObject * *parent*, const QUuid & *id*) [static]

Definition at line 67 of file animscript.cpp.

References AnimScript(), and scripts.

Referenced by KbAnim::KbAnim().

```
67                                                    {
68      return scripts.contains(id) ? new AnimScript(parent, *
    scripts.value(id)) : 0;
69 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.6 QString AnimScript::copyright ( ) const [inline]

Definition at line 62 of file animscript.h.

References _info.

Referenced by KbAnimWidget::setCurrent().

```
62 { return "Copyright © " + _info.year + " " + _info.author; }
```

Here is the caller graph for this function:

12.3.5.7 static int AnimScript::count ( ) [inline], [static]

Definition at line 54 of file animscript.h.

References scripts.

Referenced by KbLightWidget::KbLightWidget(), load(), KbLightWidget::on_animButton_clicked(), and ExtraSettingsWidget::on_animScanButton_clicked().

```
54 { return scripts.count(); }
```

Here is the caller graph for this function:

12.3.5.8 const QString& AnimScript::description ( ) const [inline]

Definition at line 66 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
66 { return _info.description; }
```

Here is the caller graph for this function:

12.3.5.9 void AnimScript::end ( )

Definition at line 387 of file animscript.cpp.

References _colors, ColorMap::clear(), process, and readProcess().

Referenced by begin(), KbAnim::catchUp(), init(), and KbAnim::stop().

```
387                     {
388     _colors.clear();
389     if(process){
390         process->kill();
391         connect(process, SIGNAL(finished(int)), process, SLOT(deleteLater()));
392         disconnect(process, SIGNAL(readyRead()), this, SLOT(readProcess()));
393         process = 0;
394     }
395 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.10 void AnimScript::frame (quint64 *timestamp*)

Definition at line 430 of file animscript.cpp.

References advance(), begin(), firstFrame, initialized, process, readFrame, and stopped.

Referenced by KbAnim::blend(), KbAnim::keypress(), and KbAnim::trigger().

```
430                                     {
431     if(!initialized || stopped)
432         return;
433     // Start the animation if it's not running yet
434     if(!process)
435         begin(timestamp);
436
437     advance(timestamp);
438     if((readFrame || !firstFrame) && process)
439         // Don't ask for a new frame if the animation hasn't delivered the last one yet
440         process->write("frame\n");
441     firstFrame = true;
442     readFrame = false;
443 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.11 const QUuid& AnimScript::guid ( ) const [inline]

Definition at line 59 of file animscript.h.

References _info.

Referenced by KbAnim::KbAnim(), list(), and scan().

```
59 { return _info.guid; }
```

Here is the caller graph for this function:

12.3.5.12 bool AnimScript::hasFrame ( ) const [inline]

Definition at line 96 of file animscript.h.

References initialized, and readAnyFrame.

Referenced by KbAnim::isRunning().

```
96 { return initialized && readAnyFrame; }
```

Here is the caller graph for this function:

12.3.5.13 bool AnimScript::hasKeypress ( ) const [inline]

Definition at line 67 of file animscript.h.

References _info, and KP_NONE.

Referenced by AnimSettingDialog::AnimSettingDialog(), and AnimSettingDialog::updateParam().

```
67 { return _info.kpMode != KP_NONE; }
```

Here is the caller graph for this function:

12.3.5.14 bool AnimScript::hasParam (const QString & *name*) const [inline]

Definition at line 74 of file animscript.h.

References _info, and name().

Referenced by AnimSettingDialog::AnimSettingDialog(), load(), and KbAnim::parameter().

```
74 { QListIterator<Param> i(_info.params); while(i.hasNext()){ if(i.next().name ==
      name) return true; } return false; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.15 void AnimScript::init (const KeyMap & *map,* const QStringList & *keys,* const QMap< QString, QVariant > & *paramValues*)

Definition at line 239 of file animscript.cpp.

References _colorBuffer, _colors, _keys, _map, _paramValues, _path, end(), firstFrame, ColorMap::init(), initialized, setDuration(), and stopped.

Referenced by KbAnim::reInit().

```
239
    {
240     if(_path == "")
241         return;
242     end();
243     _map = map;
244     _colors.init(map);
245     _colorBuffer.init(map);
246     _keys = keys;
247     _paramValues = paramValues;
248     setDuration();
249     stopped = firstFrame = false;
250     initialized = true;
251 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.16 void AnimScript::keypress (const QString & *key,* bool *pressed,* quint64 *timestamp*)

Definition at line 354 of file animscript.cpp.

References _info, _map, _paramValues, advance(), begin(), initialized, KeyMap::key(), KP_NAME, KP_NONE, KP_POSITION, minX, minY, process, retrigger(), stop(), Key::x, and Key::y.

Referenced by KbAnim::catchUp(), and KbAnim::keypress().

```
354                                                                                 {
355     if(!initialized)
356         return;
357     if(!process)
358         begin(timestamp);
359     int kpMode = _info.kpMode;
360     if(_paramValues.value("kpmode", 0).toInt() != 0)
361         // Disable KP mode according to user preferences
362         kpMode = KP_NONE;
363     switch(kpMode){
364     case KP_NONE:
365         // If KPs aren't allowed, call retrigger/stop instead
366         if(pressed)
367             retrigger(timestamp);
368         else if(_paramValues.value("kprelease", false).toBool())
369             stop(timestamp);
370         break;
371     case KP_NAME:
372         // Print keypress by name
373         advance(timestamp);
374         process->write(("key " + key + (pressed ? " down\n" : " up\n")).toLatin1());
375         break;
376     case KP_POSITION:
377         // Print keypress by position
378         const Key& kp = _map.key(key);
379         if(!kp)
380             return;
381         advance(timestamp);
382         process->write(("key " + QString("%1,%2").arg(kp.x - minX).arg(kp.
      y - minY) + (pressed ? " down\n" : " up\n")).toLatin1());
383         break;
384     }
385 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.17 const QString& AnimScript::license ( ) const [inline]

Definition at line 65 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
65 { return _info.license; }
```

Here is the caller graph for this function:

12.3.5.18 QList< const AnimScript * > AnimScript::list ( ) [static]

Definition at line 51 of file animscript.cpp.

References _info, guid(), name(), and scripts.

Referenced by AnimAddDialog::AnimAddDialog().

```
51                                          {
52     // Gather the animations into an alphabetically-sorted list
53     QMap<QString, const AnimScript*> result;
54     foreach(AnimScript* script, scripts.values()){
55         QString name = script->name();
56         if(result.contains(name)){
57             // If duplicate names exist, make them unique by including their GUIDs
58             AnimScript* last = (AnimScript*)result[name];
59             last->_info.name += " " + last->guid().toString().toUpper();
60             script->_info.name += " " + script->guid().toString().toUpper();
61         }
62         result[script->name()] = script;
63     }
64     return result.values();
65 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.19 bool AnimScript::load ( ) [private]

Definition at line 77 of file animscript.cpp.

References _info, _path, _presets, _presetValues, AnimScript::Param::AGRADIENT, AnimScript::Param::ANGLE, AnimScript::Param::ARGB, AnimScript::Param::BOOL, count(), AnimScript::Param::defaultValue, AnimScript::Param::DOUBLE, AnimScript::Param::GRADIENT, hasParam(), AnimScript::Param::INVALID, KP_NAME, KP_NONE, KP_POSITION, AnimScript::Param::LABEL, AnimScript::Param::LONG, name(), ONE_DAY, param(), preset(), AnimScript::Param::RGB, stop(), AnimScript::Param::STRING, and urlParam().

Referenced by scan().

```
77                      {
78      // Run the process to get script info
79      QProcess infoProcess;
80      infoProcess.start(_path, QStringList("--ckb-info"));
81      qDebug() << "Scanning " << _path;
82      infoProcess.waitForFinished(1000);
83      if(infoProcess.state() == QProcess::Running){
84          // Kill the process if it takes more than 1s
85          infoProcess.kill();
86          return false;
87      }
88      // Set defaults for performance info
89      _info.kpMode = KP_NONE;
90      _info.absoluteTime = _info.preempt = _info.liveParams = false;
91      _info.repeat = true;
92      // Read output
93      QString line;
94      while((line = infoProcess.readLine()) != ""){
95          line = line.trimmed();
96          QStringList components = line.split(" ");
97          int count = components.count();
98          if(count < 2)
99              continue;
100         QString param = components[0].trimmed();
101         if(param == "guid")
102             _info.guid = QUuid(urlParam(components[1]));
```

```
        else if(param == "name")
            _info.name = urlParam(components[1]);
        else if(param == "version")
            _info.version = urlParam(components[1]);
        else if(param == "year")
            _info.year = urlParam(components[1]);
        else if(param == "author")
            _info.author = urlParam(components[1]);
        else if(param == "license")
            _info.license = urlParam(components[1]);
        else if(param == "description")
            _info.description = urlParam(components[1]);
        else if(param == "kpmode")
            _info.kpMode = (components[1] == "position") ? KP_POSITION : (components[1] == "name") ? KP_NAME : KP_NONE;
        else if(param == "time")
            _info.absoluteTime = (components[1] == "absolute");
        else if(param == "repeat")
            _info.repeat = (components[1] == "on");
        else if(param == "preempt")
            _info.preempt = (components[1] == "on");
        else if(param == "parammode")
            _info.liveParams = (components[1] == "live");
        else if(param == "param"){
            // Read parameter
            if(count < 3)
                continue;
            while(components.count() < 8)
                components.append("");
            Param::Type type = Param::INVALID;
            QString sType = components[1].toLower();
            if(sType == "long")
                type = Param::LONG;
            else if(sType == "double")
                type = Param::DOUBLE;
            else if(sType == "bool")
                type = Param::BOOL;
            else if(sType == "rgb")
                type = Param::RGB;
            else if(sType == "argb")
                type = Param::ARGB;
            else if(sType == "gradient")
                type = Param::GRADIENT;
            else if(sType == "agradient")
                type = Param::AGRADIENT;
            else if(sType == "angle")
                type = Param::ANGLE;
            else if(sType == "string")
                type = Param::STRING;
            else if(sType == "label")
                type = Param::LABEL;
            else
                continue;
            // "param <type> <name> <prefix> <postfix> <default>"
            QString name = components[2].toLower();
            // Make sure it's not present already
            if(hasParam(name))
                continue;
            QString prefix = urlParam(components[3]), postfix = urlParam(components[4]);
            QVariant def = urlParam(components[5]), minimum = urlParam(components[6]), maximum = urlParam(components[7]);
            // Don't allow predefined params
            if(name == "trigger" || name == "kptrigger" || name == "kpmode" || name == "duration" || name == "delay" || name == "kpdelay" || name == "repeat" || name == "kprepeat" || name == "stop" || name == "kpstop" || name == "kpmodestop" || name == "kprelease")
                continue;
            Param param = { type, name, prefix, postfix, def, minimum, maximum };
            _info.params.append(param);
        } else if(param == "preset"){
            // Add preset
            QString name = urlParam(components.at(1));
            QMap<QString, QVariant> preset;
            for(int i = 2; i < count; i++){
                // Scan name/value setting pairs
                QString setting = components.at(i);
                QStringList sComponents = setting.split("=");
                if(sComponents.count() != 2)
                    continue;
                QString param = sComponents.first().trimmed();
                QString value = urlParam(sComponents.last());
                preset[param] = value;
            }
            // If the preset contains a duration, set the repeat time to the same value
            if(preset.contains("duration")){
                QVariant duration = preset.value("duration");
                preset["repeat"] = duration;
                preset["kprepeat"] = duration;
```

```
            }
            _presets.append(name);
            _presetValues.append(preset);
        }
    }
    // Make sure the required parameters are filled out
    if(_info.guid.isNull() || _info.name == "" || _info.version == "" || _info.year == "" || _info.author == "" || _info.license == "")
        return false;
    // Add timing parameters
    double defaultDuration = -1.;
    if(!_info.absoluteTime){
        defaultDuration = 1.;
        Param duration = { Param::DOUBLE, "duration", "", "", defaultDuration, 0.1, ONE_DAY };
        _info.params.append(duration);
    }
    Param trigger = { Param::BOOL, "trigger", "", "", true, 0, 0 };
    _info.params.append(trigger);
    Param kptrigger = { Param::BOOL, "kptrigger", "", "", false, 0, 0 };
    _info.params.append(kptrigger);
    if(_info.absoluteTime || !_info.repeat)
        _info.preempt = false;
    Param kpmode = { Param::LONG, "kpmode", "", "", 1, 0, 0 };
    if(_info.kpMode)
        kpmode.defaultValue = 0;
    _info.params.append(kpmode);
    Param delay = { Param::DOUBLE, "delay", "", "", 0., 0., ONE_DAY };
    Param kpdelay = { Param::DOUBLE, "kpdelay", "", "", 0., 0., ONE_DAY };
    _info.params.append(delay);
    _info.params.append(kpdelay);
    Param kpmodestop = { Param::BOOL, "kpmodestop", "", "", false, 0, 0 };
    Param kprelease = { Param::BOOL, "kprelease", "", "", false, 0, 0 };
    _info.params.append(kpmodestop);
    _info.params.append(kprelease);
    if(_info.repeat){
        Param repeat = { Param::DOUBLE, "repeat", "", "", defaultDuration, 0.1, ONE_DAY };
        Param kprepeat = { Param::DOUBLE, "kprepeat", "", "", defaultDuration, 0.1, ONE_DAY };
        // When repeats are enabled, stop and kpstop are LONG values (number of repeats)
        Param stop = { Param::LONG, "stop", "", "", -1, 0, 1000 };
        Param kpstop = { Param::LONG, "kpstop", "", "", 0, 0, 1000 };
        _info.params.append(repeat);
        _info.params.append(kprepeat);
        _info.params.append(stop);
        _info.params.append(kpstop);
    } else {
        // When repeats are disabled, stop and kpstop are DOUBLE values (seconds)
        Param stop = { Param::DOUBLE, "stop", "", "", -1., 0.1, ONE_DAY };
        Param kpstop = { Param::DOUBLE, "kpstop", "", "", -1., 0.1, ONE_DAY };
        _info.params.append(stop);
        _info.params.append(kpstop);
    }
    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.20 const QString& AnimScript::name ( ) const [inline]

Definition at line 60 of file animscript.h.

References _info.

Referenced by AnimAddDialog::AnimAddDialog(), AnimSettingDialog::AnimSettingDialog(), hasParam(), KbAnim::-KbAnim(), list(), load(), and KbAnimWidget::setCurrent().

```
60 { return _info.name; }
```

Here is the caller graph for this function:

12.3.5.21 Param AnimScript::param (const QString & *name*) const [inline]

Definition at line 73 of file animscript.h.

References _info, AnimScript::Param::INVALID, and AnimScript::Param::name.

Referenced by KbAnim::KbAnim(), load(), and AnimSettingDialog::updateParam().

```
73 { QListIterator<Param> i(_info.params); while(i.hasNext()){ Param p = i.next(); if(p.name ==
     name) return p; } return ((Param[]){ { Param::INVALID, "", "", "", 0, 0, 0 } })[0]; }
```

Here is the caller graph for this function:

12.3.5.22 void AnimScript::parameters (const QMap< QString, QVariant > & *paramValues*)

Definition at line 265 of file animscript.cpp.

References _info, _paramValues, initialized, printParams(), process, and setDuration().

Referenced by KbAnim::updateParams().

```
265                                                                    {
266     if(!initialized || !process || !_info.liveParams)
267         return;
268     _paramValues = paramValues;
269     setDuration();
270     printParams();
271 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.23 QListIterator<Param> AnimScript::paramIterator ( ) const [inline]

Definition at line 72 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog(), and KbAnim::KbAnim().

```
72 { return _info.params; }
```

Here is the caller graph for this function:

12.3.5.24 QString AnimScript::path ( ) [static]

Definition at line 29 of file animscript.cpp.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and scan().

```
29                          {
30 #ifdef __APPLE__
31     return QDir(QApplication::applicationDirPath() + "/../Resources").absoluteFilePath("ckb-animations");
32 #else
33     return QDir("/usr/lib").absoluteFilePath("ckb-animations");
34 #endif
35 }
```

Here is the caller graph for this function:

12.3.5.25 const PresetValue& AnimScript::preset (int *index*) const [inline]

Definition at line 69 of file animscript.h.

References _presetValues.

Referenced by load(), and KbLightWidget::on_animButton_clicked().

```
69 { return _presetValues[index]; }
```

Here is the caller graph for this function:

12.3.5.26 const QStringList& AnimScript::presets ( ) const [inline]

Definition at line 68 of file animscript.h.

References _presets.

Referenced by KbLightWidget::on_animButton_clicked().

```
68 { return _presets; }
```

Here is the caller graph for this function:

12.3.5.27 void AnimScript::printParams ( ) [private]

Definition at line 273 of file animscript.cpp.

References _paramValues, and process.

Referenced by begin(), and parameters().

```
273                                 {
274     process->write("begin params\n");
275     QMapIterator<QString, QVariant> i(_paramValues);
276     while(i.hasNext()){
277         i.next();
278         process->write("param ");
279         process->write(i.key().toLatin1());
280         process->write(" ");
281         process->write(QUrl::toPercentEncoding(i.value().toString()));
282         process->write("\n");
283     }
284     process->write("end params\n");
285 }
```

Here is the caller graph for this function:

12.3.5.28 void AnimScript::readProcess ( ) [private],[slot]

Definition at line 397 of file animscript.cpp.

References _colorBuffer, _colors, ColorMap::colorForName(), ColorMap::colors(), ColorMap::count(), inFrame, process, readAnyFrame, readFrame, and stopped.

Referenced by begin(), and end().

```
397                             {
398     while(process->canReadLine()){
399         QByteArray line = process->readLine().trimmed();
400         if(!inFrame){
401             // Ignore anything not between "begin frame" and "end frame", except for "end run", which
        indicates that the program is done.
402             if(line == "begin frame")
403                 inFrame = true;
404             else if(line == "end run"){
405                 stopped = true;
406                 return;
407             }
408             continue;
409         }
410         if(line.startsWith("argb ")){
411             // Add a color to the buffer
412             char keyName[31];
413             QRgb keyColor = 0;
414             if(sscanf(line, "argb %30s %x", keyName, &keyColor) != 2)
415                 continue;
416             QRgb* inMap = _colorBuffer.colorForName(keyName);
417             if(!inMap)
418                 continue;
419             *inMap = keyColor;
420         }
421         if(line == "end frame"){
422             // Frame is finished. Copy color buffer back to the atomic map
423             memcpy(_colors.colors(), _colorBuffer.
      colors(), sizeof(QRgb) * _colors.count());
424             inFrame = false;
425             readFrame = readAnyFrame = true;
426         }
427     }
428 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.29 void AnimScript::retrigger (quint64 *timestamp*, bool *allowPreempt* = `false`)

Definition at line 331 of file animscript.cpp.

References _info, advance(), begin(), initialized, process, and repeatMsec.

Referenced by KbAnim::catchUp(), keypress(), and KbAnim::trigger().

```
331                                                                 {
332     if(!initialized)
333         return;
334     if(allowPreempt && _info.preempt && repeatMsec > 0)
335         // If preemption is wanted, trigger the animation 1 duration in the past first
336         retrigger(timestamp - repeatMsec);
337     if(!process)
338         begin(timestamp);
339     advance(timestamp);
340     if(process)
341         process->write("start\n");
342 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.30 void AnimScript::scan ( ) [static]

Definition at line 37 of file animscript.cpp.

References _info, AnimScript(), guid(), load(), path(), and scripts.

Referenced by ExtraSettingsWidget::on_animScanButton_clicked().

```
37                      {
38     QDir dir(path());
39     foreach(AnimScript* script, scripts)
40         delete script;
41     scripts.clear();
42     foreach(QString file, dir.entryList(QDir::Files | QDir::Executable)){
43         AnimScript* script = new AnimScript(qApp, dir.absoluteFilePath(file));
44         if(script->load() && !scripts.contains(script->_info.
      guid))
45             scripts[script->_info.guid] = script;
46         else
47             delete script;
48     }
49 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.31 void AnimScript::setDuration ( ) [private]

Definition at line 253 of file animscript.cpp.

References _info, _paramValues, durationMsec, and repeatMsec.

Referenced by init(), and parameters().

```
253                                 {
254     if(_info.absoluteTime){
255         durationMsec = 1000;
256         repeatMsec = 0;
257     } else {
258         durationMsec = round(_paramValues.value("duration").toDouble() * 1000.);
259         if(durationMsec <= 0)
260             durationMsec = -1;
261         repeatMsec = round(_paramValues.value("repeat").toDouble() * 1000.);
262     }
263 }
```

Here is the caller graph for this function:

12.3.5.32 void AnimScript::stop (quint64 *timestamp*)

Definition at line 344 of file animscript.cpp.

References advance(), begin(), initialized, and process.

Referenced by KbAnim::keypress(), keypress(), and load().

```
344                                     {
345     if(!initialized)
346         return;
347     if(!process)
348         begin(timestamp);
349     advance(timestamp);
350     if(process)
351         process->write("stop\n");
352 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.3.5.33 const QString& AnimScript::version ( ) const [inline]

Definition at line 61 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog(), and KbAnimWidget::setCurrent().

```
61 { return _info.version; }
```

Here is the caller graph for this function:

12.3.5.34 const QString& AnimScript::year ( ) const [inline]

Definition at line 63 of file animscript.h.

References _info.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
63 { return _info.year; }
```

Here is the caller graph for this function:

12.3.6 Field Documentation

12.3.6.1 ColorMap AnimScript::_colorBuffer [private]

Definition at line 143 of file animscript.h.

Referenced by init(), and readProcess().

12.3.6.2 ColorMap AnimScript::_colors [private]

Definition at line 135 of file animscript.h.

Referenced by colors(), end(), init(), and readProcess().

12.3.6.3 struct { ... } AnimScript::_info [private]

Referenced by advance(), author(), copyright(), description(), guid(), hasKeypress(), hasParam(), keypress(), license(), list(), load(), name(), param(), parameters(), paramIterator(), retrigger(), scan(), setDuration(), version(), and year().

12.3.6.4 QStringList AnimScript::_keys [private]

Definition at line 133 of file animscript.h.

Referenced by begin(), and init().

12.3.6.5 KeyMap AnimScript::_map [private]

Definition at line 130 of file animscript.h.

Referenced by begin(), init(), and keypress().

12.3.6.6 PresetValue AnimScript::_paramValues [private]

Definition at line 136 of file animscript.h.

Referenced by init(), keypress(), parameters(), printParams(), and setDuration().

12.3.6.7 QString AnimScript::_path [private]

Definition at line 128 of file animscript.h.

Referenced by begin(), init(), and load().

12.3.6.8 QStringList AnimScript::_presets [private]

Definition at line 125 of file animscript.h.

Referenced by load(), and presets().

12.3.6.9 QList<PresetValue> AnimScript::_presetValues [private]

Definition at line 126 of file animscript.h.

Referenced by load(), and preset().

12.3.6.10 int AnimScript::durationMsec [private]

Definition at line 140 of file animscript.h.

Referenced by advance(), and setDuration().

12.3.6.11 bool AnimScript::firstFrame [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), frame(), and init().

12.3.6.12 bool AnimScript::inFrame [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), and readProcess().

12.3.6.13 bool AnimScript::initialized [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), frame(), hasFrame(), init(), keypress(), parameters(), retrigger(), and stop().

12.3.6.14 const int AnimScript::KP_NAME = 1 [static], [private]

Definition at line 124 of file animscript.h.

Referenced by keypress(), and load().

12.3.6.15 const int AnimScript::KP_NONE = 0 [static], [private]

Definition at line 124 of file animscript.h.

Referenced by hasKeypress(), keypress(), and load().

12.3.6.16 const int AnimScript::KP_POSITION = 2 [static], [private]

Definition at line 124 of file animscript.h.

Referenced by keypress(), and load().

12.3.6.17 quint64 AnimScript::lastFrame [private]

Definition at line 139 of file animscript.h.

Referenced by advance(), and begin().

12.3.6.18 int AnimScript::minX [private]

Definition at line 131 of file animscript.h.

Referenced by begin(), and keypress().

12.3.6.19 int AnimScript::minY [private]

Definition at line 131 of file animscript.h.

Referenced by begin(), and keypress().

12.3.6.20 QProcess* AnimScript::process [private]

Definition at line 142 of file animscript.h.

Referenced by advance(), begin(), end(), frame(), keypress(), parameters(), printParams(), readProcess(), retrigger(), stop(), and ~AnimScript().

12.3.6.21 bool AnimScript::readAnyFrame [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), hasFrame(), and readProcess().

12.3.6.22 bool AnimScript::readFrame [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), frame(), and readProcess().

12.3.6.23 int AnimScript::repeatMsec [private]

Definition at line 140 of file animscript.h.

Referenced by retrigger(), and setDuration().

12.3.6.24 QHash< QUuid, AnimScript * > AnimScript::scripts [static], [private]

Definition at line 152 of file animscript.h.

Referenced by copy(), count(), list(), and scan().

12.3.6.25 bool AnimScript::stopped [private]

Definition at line 141 of file animscript.h.

Referenced by begin(), frame(), init(), and readProcess().

The documentation for this class was generated from the following files:

- src/ckb/animscript.h

- src/ckb/animscript.cpp

12.4 Ui::AnimSettingDialog Class Reference

```
#include <src/ckb/ui_animsettingdialog.h>
```

Inheritance diagram for Ui::AnimSettingDialog:

Collaboration diagram for Ui::AnimSettingDialog:

Public Member Functions

- void setupUi (QDialog *AnimSettingDialog)
- void retranslateUi (QDialog *AnimSettingDialog)

Data Fields

- QGridLayout * gridLayout
- QDialogButtonBox * buttonBox
- QTabWidget * tabWidget
- QWidget * settingTab
- QGridLayout * settingsGrid
- QLabel * label_2
- QSpacerItem * horizontalSpacer_3
- QLineEdit * animName
- QWidget * timeTab
- QGridLayout * timeGrid
- QSpacerItem * horizontalSpacer_5
- QLabel * kpRepeatLabel
- QLabel * repeatLabel
- QDoubleSpinBox * repeatBox
- QLabel * repeatLabel_2
- QFrame * line
- QLabel * kpRepeatLabel_2
- QLabel * label_4
- QLabel * label_8
- QDoubleSpinBox * kpDelayBox
- QLabel * label_13
- QLabel * label_12
- QDoubleSpinBox * delayBox
- QCheckBox * kpModeStopBox
- QLabel * label_10
- QSpacerItem * verticalSpacer_3
- QSpacerItem * horizontalSpacer_4

- QCheckBox * kpReleaseBox
- QLabel * label_6
- QDoubleSpinBox * kpRepeatBox
- QSpacerItem * verticalSpacer_2
- QFrame * line_2
- QSpacerItem * horizontalSpacer_6
- QWidget * infoTab
- QGridLayout * gridLayout_2
- QLabel * sNameLabel
- QLabel * label_7
- QLabel * label_11
- QLabel * sAuthorLabel
- QLabel * label_9
- QLabel * label_5
- QLabel * sYearLabel
- QLabel * label_3
- QSpacerItem * horizontalSpacer
- QSpacerItem * horizontalSpacer_2
- QLabel * sVerLabel
- QLabel * sLicenseLabel
- QLabel * label
- QSpacerItem * verticalSpacer
- QLabel * sDescLabel

12.4.1 Detailed Description

Definition at line 385 of file ui_animsettingdialog.h.

12.4.2 Member Function Documentation

12.4.2.1 void Ui_AnimSettingDialog::retranslateUi (QDialog * *AnimSettingDialog*) [inline],[inherited]

Definition at line 349 of file ui_animsettingdialog.h.

References Ui_AnimSettingDialog::infoTab, Ui_AnimSettingDialog::kpModeStopBox, Ui_AnimSettingDialog::kpReleaseBox, Ui_AnimSettingDialog::kpRepeatLabel, Ui_AnimSettingDialog::kpRepeatLabel_2, Ui_AnimSettingDialog::label, Ui_AnimSettingDialog::label_10, Ui_AnimSettingDialog::label_11, Ui_AnimSettingDialog::label_12, Ui_AnimSettingDialog::label_13, Ui_AnimSettingDialog::label_2, Ui_AnimSettingDialog::label_3, Ui_AnimSettingDialog::label_4, Ui_AnimSettingDialog::label_5, Ui_AnimSettingDialog::label_6, Ui_AnimSettingDialog::label_7, Ui_AnimSettingDialog::label_8, Ui_AnimSettingDialog::label_9, Ui_AnimSettingDialog::repeatLabel, Ui_AnimSettingDialog::repeatLabel_2, Ui_AnimSettingDialog::sAuthorLabel, Ui_AnimSettingDialog::sDescLabel, Ui_AnimSettingDialog::settingTab, Ui_AnimSettingDialog::sLicenseLabel, Ui_AnimSettingDialog::sNameLabel, Ui_AnimSettingDialog::sVerLabel, Ui_AnimSettingDialog::sYearLabel, Ui_AnimSettingDialog::tabWidget, and Ui_AnimSettingDialog::timeTab.

Referenced by Ui_AnimSettingDialog::setupUi().

```
    {
        AnimSettingDialog->setWindowTitle(QApplication::translate("AnimSettingDialog", "Dialog", Q_NULLPTR));
        label_2->setText(QApplication::translate("AnimSettingDialog", "Name:", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(settingTab), QApplication::translate("AnimSettingDialog", "Settings", Q_NULLPTR));
        kpRepeatLabel->setText(QApplication::translate("AnimSettingDialog", "Repeat every:", Q_NULLPTR));
        repeatLabel->setText(QApplication::translate("AnimSettingDialog", "Repeat every:", Q_NULLPTR));
        repeatLabel_2->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        kpRepeatLabel_2->setText(QApplication::translate("AnimSettingDialog", "seconds",
```

```
Q_NULLPTR));
        label_4->setText(QApplication::translate("AnimSettingDialog", "<b>On mode start</b>", Q_NULLPTR));
        label_8->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        label_13->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        label_12->setText(QApplication::translate("AnimSettingDialog", "Start delay:", Q_NULLPTR));
        kpModeStopBox->setText(QApplication::translate("AnimSettingDialog", "Stop on key press", Q_NULLPTR));
        label_10->setText(QApplication::translate("AnimSettingDialog", "Start delay:", Q_NULLPTR));
        kpReleaseBox->setText(QApplication::translate("AnimSettingDialog", "Stop on key release", Q_NULLPTR));
        label_6->setText(QApplication::translate("AnimSettingDialog", "<b>On key press</b>", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(timeTab), QApplication::translate("AnimSettingDialog", "Timing", Q_NULLPTR));
        sNameLabel->setText(QApplication::translate("AnimSettingDialog", "Name", Q_NULLPTR));
        label_7->setText(QApplication::translate("AnimSettingDialog", "Year:", Q_NULLPTR));
        label_11->setText(QApplication::translate("AnimSettingDialog", "Description:", Q_NULLPTR));
        sAuthorLabel->setText(QApplication::translate("AnimSettingDialog", "Author", Q_NULLPTR));
        label_9->setText(QApplication::translate("AnimSettingDialog", "License:", Q_NULLPTR));
        label_5->setText(QApplication::translate("AnimSettingDialog", "Version:", Q_NULLPTR));
        sYearLabel->setText(QApplication::translate("AnimSettingDialog", "Year", Q_NULLPTR));
        label_3->setText(QApplication::translate("AnimSettingDialog", "Author:", Q_NULLPTR));
        sVerLabel->setText(QApplication::translate("AnimSettingDialog", "Version", Q_NULLPTR));
        sLicenseLabel->setText(QApplication::translate("AnimSettingDialog", "License", Q_NULLPTR));
        label->setText(QApplication::translate("AnimSettingDialog", "Script name:", Q_NULLPTR));
        sDescLabel->setText(QApplication::translate("AnimSettingDialog", "Description", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(infoTab), QApplication::translate("AnimSettingDialog", "About", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.4.2.2 void Ui_AnimSettingDialog::setupUi (QDialog * *AnimSettingDialog*) [inline],[inherited]

Definition at line 85 of file ui_animsettingdialog.h.

References Ui_AnimSettingDialog::animName, Ui_AnimSettingDialog::buttonBox, Ui_AnimSettingDialog::delayBox, Ui_AnimSettingDialog::gridLayout, Ui_AnimSettingDialog::gridLayout_2, Ui_AnimSettingDialog::horizontalSpacer, Ui_AnimSettingDialog::horizontalSpacer_2, Ui_AnimSettingDialog::horizontalSpacer_3, Ui_AnimSettingDialog::horizontalSpacer_4, Ui_AnimSettingDialog::horizontalSpacer_5, Ui_AnimSettingDialog::horizontalSpacer_6, Ui_AnimSettingDialog::infoTab, Ui_AnimSettingDialog::kpDelayBox, Ui_AnimSettingDialog::kpModeStopBox, Ui_AnimSettingDialog::kpReleaseBox, Ui_AnimSettingDialog::kpRepeatBox, Ui_AnimSettingDialog::kpRepeatLabel, Ui_AnimSettingDialog::kpRepeatLabel_2, Ui_AnimSettingDialog::label, Ui_AnimSettingDialog::label_10, Ui_AnimSettingDialog::label_11, Ui_AnimSettingDialog::label_12, Ui_AnimSettingDialog::label_13, Ui_AnimSettingDialog::label_2, Ui_AnimSettingDialog::label_3, Ui_AnimSettingDialog::label_4, Ui_AnimSettingDialog::label_5, Ui_AnimSettingDialog::label_6, Ui_AnimSettingDialog::label_7, Ui_AnimSettingDialog::label_8, Ui_AnimSettingDialog::label_9, Ui_AnimSettingDialog::line, Ui_AnimSettingDialog::line_2, Ui_AnimSettingDialog::repeatBox, Ui_AnimSettingDialog::repeatLabel, Ui_AnimSettingDialog::repeatLabel_2, Ui_AnimSettingDialog::retranslateUi(), Ui_AnimSettingDialog::sAuthorLabel, Ui_AnimSettingDialog::sDescLabel, Ui_AnimSettingDialog::settingsGrid, Ui_AnimSettingDialog::settingTab, Ui_AnimSettingDialog::sLicenseLabel, Ui_AnimSettingDialog::sNameLabel, Ui_AnimSettingDialog::sVerLabel, Ui_AnimSettingDialog::sYearLabel, Ui_AnimSettingDialog::tabWidget, Ui_AnimSettingDialog::timeGrid, Ui_AnimSettingDialog::timeTab, Ui_AnimSettingDialog::verticalSpacer, Ui_AnimSettingDialog::verticalSpacer_2, and Ui_AnimSettingDialog::verticalSpacer_3.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
    {
        if (AnimSettingDialog->objectName().isEmpty())
            AnimSettingDialog->setObjectName(QStringLiteral("AnimSettingDialog"));
        AnimSettingDialog->resize(480, 457);
        AnimSettingDialog->setMinimumSize(QSize(480, 0));
        AnimSettingDialog->setFocusPolicy(Qt::ClickFocus);
        gridLayout = new QGridLayout(AnimSettingDialog);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        buttonBox = new QDialogButtonBox(AnimSettingDialog);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);

        gridLayout->addWidget(buttonBox, 2, 0, 1, 1);

         tabWidget = new QTabWidget(AnimSettingDialog);
         tabWidget->setObjectName(QStringLiteral("tabWidget"));
         settingTab = new QWidget();
         settingTab->setObjectName(QStringLiteral("settingTab"));
         settingsGrid = new QGridLayout(settingTab);
         settingsGrid->setSpacing(12);
         settingsGrid->setObjectName(QStringLiteral("settingsGrid"));
         settingsGrid->setContentsMargins(12, 12, 12, 12);
         label_2 = new QLabel(settingTab);
         label_2->setObjectName(QStringLiteral("label_2"));

         settingsGrid->addWidget(label_2, 0, 1, 1, 1);

         horizontalSpacer_3 = new QSpacerItem(5, 0, QSizePolicy::Fixed,
QSizePolicy::Minimum);

         settingsGrid->addItem(horizontalSpacer_3, 0, 2, 1, 1);

         animName = new QLineEdit(settingTab);
         animName->setObjectName(QStringLiteral("animName"));

         settingsGrid->addWidget(animName, 0, 3, 1, 3);

         tabWidget->addTab(settingTab, QString());
         timeTab = new QWidget();
         timeTab->setObjectName(QStringLiteral("timeTab"));
         timeGrid = new QGridLayout(timeTab);
         timeGrid->setSpacing(12);
         timeGrid->setObjectName(QStringLiteral("timeGrid"));
         timeGrid->setContentsMargins(12, 12, 12, 12);
         horizontalSpacer_5 = new QSpacerItem(15, 0, QSizePolicy::Fixed,
QSizePolicy::Minimum);

         timeGrid->addItem(horizontalSpacer_5, 3, 2, 1, 1);

         kpRepeatLabel = new QLabel(timeTab);
         kpRepeatLabel->setObjectName(QStringLiteral("kpRepeatLabel"));

         timeGrid->addWidget(kpRepeatLabel, 11, 1, 1, 1);

         repeatLabel = new QLabel(timeTab);
         repeatLabel->setObjectName(QStringLiteral("repeatLabel"));

         timeGrid->addWidget(repeatLabel, 3, 1, 1, 1);

         repeatBox = new QDoubleSpinBox(timeTab);
         repeatBox->setObjectName(QStringLiteral("repeatBox"));
         repeatBox->setDecimals(1);
         repeatBox->setMinimum(0.1);
         repeatBox->setMaximum(86400);

         timeGrid->addWidget(repeatBox, 3, 3, 1, 1);

         repeatLabel_2 = new QLabel(timeTab);
         repeatLabel_2->setObjectName(QStringLiteral("repeatLabel_2"));

         timeGrid->addWidget(repeatLabel_2, 3, 4, 1, 1);

         line = new QFrame(timeTab);
         line->setObjectName(QStringLiteral("line"));
         line->setFrameShape(QFrame::HLine);
         line->setFrameShadow(QFrame::Sunken);

         timeGrid->addWidget(line, 1, 0, 1, 6);

         kpRepeatLabel_2 = new QLabel(timeTab);
         kpRepeatLabel_2->setObjectName(QStringLiteral("kpRepeatLabel_2"));

         timeGrid->addWidget(kpRepeatLabel_2, 11, 4, 1, 1);

         label_4 = new QLabel(timeTab);
         label_4->setObjectName(QStringLiteral("label_4"));
```

```
        timeGrid->addWidget(label_4, 0, 0, 1, 6);

        label_8 = new QLabel(timeTab);
        label_8->setObjectName(QStringLiteral("label_8"));

        timeGrid->addWidget(label_8, 2, 4, 1, 1);

        kpDelayBox = new QDoubleSpinBox(timeTab);
        kpDelayBox->setObjectName(QStringLiteral("kpDelayBox"));
        kpDelayBox->setDecimals(1);
        kpDelayBox->setMaximum(86400);

        timeGrid->addWidget(kpDelayBox, 10, 3, 1, 1);

        label_13 = new QLabel(timeTab);
        label_13->setObjectName(QStringLiteral("label_13"));

        timeGrid->addWidget(label_13, 10, 4, 1, 1);

        label_12 = new QLabel(timeTab);
        label_12->setObjectName(QStringLiteral("label_12"));

        timeGrid->addWidget(label_12, 10, 1, 1, 1);

        delayBox = new QDoubleSpinBox(timeTab);
        delayBox->setObjectName(QStringLiteral("delayBox"));
        delayBox->setDecimals(1);
        delayBox->setMaximum(86400);

        timeGrid->addWidget(delayBox, 2, 3, 1, 1);

        kpModeStopBox = new QCheckBox(timeTab);
        kpModeStopBox->setObjectName(QStringLiteral("kpModeStopBox"));

        timeGrid->addWidget(kpModeStopBox, 5, 1, 1, 3);

        label_10 = new QLabel(timeTab);
        label_10->setObjectName(QStringLiteral("label_10"));

        timeGrid->addWidget(label_10, 2, 1, 1, 1);

        verticalSpacer_3 = new QSpacerItem(0, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        timeGrid->addItem(verticalSpacer_3, 7, 1, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        timeGrid->addItem(horizontalSpacer_4, 2, 5, 1, 1);

        kpReleaseBox = new QCheckBox(timeTab);
        kpReleaseBox->setObjectName(QStringLiteral("kpReleaseBox"));

        timeGrid->addWidget(kpReleaseBox, 14, 1, 1, 3);

        label_6 = new QLabel(timeTab);
        label_6->setObjectName(QStringLiteral("label_6"));

        timeGrid->addWidget(label_6, 8, 0, 1, 6);

        kpRepeatBox = new QDoubleSpinBox(timeTab);
        kpRepeatBox->setObjectName(QStringLiteral("kpRepeatBox"));
        kpRepeatBox->setDecimals(1);
        kpRepeatBox->setMinimum(0.1);
        kpRepeatBox->setMaximum(86400);

        timeGrid->addWidget(kpRepeatBox, 11, 3, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        timeGrid->addItem(verticalSpacer_2, 15, 1, 1, 1);

        line_2 = new QFrame(timeTab);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        timeGrid->addWidget(line_2, 9, 0, 1, 6);

        horizontalSpacer_6 = new QSpacerItem(0, 0, QSizePolicy::Fixed, QSizePolicy::Minimum);

        timeGrid->addItem(horizontalSpacer_6, 12, 2, 1, 1);

```

```
        tabWidget->addTab(timeTab, QString());
        infoTab = new QWidget();
        infoTab->setObjectName(QStringLiteral("infoTab"));
        gridLayout_2 = new QGridLayout(infoTab);
        gridLayout_2->setSpacing(12);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(12, 12, 12, 12);
        sNameLabel = new QLabel(infoTab);
        sNameLabel->setObjectName(QStringLiteral("sNameLabel"));

        gridLayout_2->addWidget(sNameLabel, 0, 2, 1, 1);

        label_7 = new QLabel(infoTab);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout_2->addWidget(label_7, 3, 0, 1, 1);

        label_11 = new QLabel(infoTab);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout_2->addWidget(label_11, 5, 0, 1, 1);

        sAuthorLabel = new QLabel(infoTab);
        sAuthorLabel->setObjectName(QStringLiteral("sAuthorLabel"));

        gridLayout_2->addWidget(sAuthorLabel, 2, 2, 1, 1);

        label_9 = new QLabel(infoTab);
        label_9->setObjectName(QStringLiteral("label_9"));

        gridLayout_2->addWidget(label_9, 4, 0, 1, 1);

        label_5 = new QLabel(infoTab);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout_2->addWidget(label_5, 1, 0, 1, 1);

        sYearLabel = new QLabel(infoTab);
        sYearLabel->setObjectName(QStringLiteral("sYearLabel"));

        gridLayout_2->addWidget(sYearLabel, 3, 2, 1, 1);

        label_3 = new QLabel(infoTab);
        label_3->setObjectName(QStringLiteral("label_3"));

        gridLayout_2->addWidget(label_3, 2, 0, 1, 1);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer, 0, 3, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(20, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_2, 0, 1, 1, 1);

        sVerLabel = new QLabel(infoTab);
        sVerLabel->setObjectName(QStringLiteral("sVerLabel"));

        gridLayout_2->addWidget(sVerLabel, 1, 2, 1, 1);

        sLicenseLabel = new QLabel(infoTab);
        sLicenseLabel->setObjectName(QStringLiteral("sLicenseLabel"));

        gridLayout_2->addWidget(sLicenseLabel, 4, 2, 1, 1);

        label = new QLabel(infoTab);
        label->setObjectName(QStringLiteral("label"));

        gridLayout_2->addWidget(label, 0, 0, 1, 1);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

        gridLayout_2->addItem(verticalSpacer, 6, 0, 1, 1);

        sDescLabel = new QLabel(infoTab);
        sDescLabel->setObjectName(QStringLiteral("sDescLabel"));
        sDescLabel->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignTop);

        gridLayout_2->addWidget(sDescLabel, 5, 2, 2, 2);

        tabWidget->addTab(infoTab, QString());

        gridLayout->addWidget(tabWidget, 0, 0, 1, 1);

```

```

        retranslateUi(AnimSettingDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), AnimSettingDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), AnimSettingDialog, SLOT(reject()));

        tabWidget->setCurrentIndex(0);


        QMetaObject::connectSlotsByName(AnimSettingDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.4.3 Field Documentation

12.4.3.1 QLineEdit* Ui_AnimSettingDialog::animName [inherited]

Definition at line 41 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), AnimSettingDialog::name(), and Ui_AnimSettingDialog-::setupUi().

12.4.3.2 QDialogButtonBox* Ui_AnimSettingDialog::buttonBox [inherited]

Definition at line 35 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.3 QDoubleSpinBox* Ui_AnimSettingDialog::delayBox [inherited]

Definition at line 56 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.4 QGridLayout* Ui_AnimSettingDialog::gridLayout [inherited]

Definition at line 34 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.5 QGridLayout* Ui_AnimSettingDialog::gridLayout_2 [inherited]

Definition at line 68 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.6 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer [inherited]

Definition at line 77 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.7 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_2 [inherited]

Definition at line 78 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.8 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_3 [inherited]

Definition at line 40 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.9 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_4 [inherited]

Definition at line 60 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.10 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_5 [inherited]

Definition at line 44 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.11 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_6 [inherited]

Definition at line 66 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.12 QWidget* Ui_AnimSettingDialog::infoTab [inherited]

Definition at line 67 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.13 QDoubleSpinBox* Ui_AnimSettingDialog::kpDelayBox [inherited]

Definition at line 53 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.14 QCheckBox* Ui_AnimSettingDialog::kpModeStopBox [inherited]

Definition at line 57 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.15 QCheckBox* Ui_AnimSettingDialog::kpReleaseBox [inherited]

Definition at line 61 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.16 QDoubleSpinBox* Ui_AnimSettingDialog::kpRepeatBox [inherited]

Definition at line 63 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.17 QLabel* Ui_AnimSettingDialog::kpRepeatLabel [inherited]

Definition at line 45 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.18 QLabel* Ui_AnimSettingDialog::kpRepeatLabel_2 [inherited]

Definition at line 50 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.19 QLabel* Ui_AnimSettingDialog::label [inherited]

Definition at line 81 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.20 QLabel* Ui_AnimSettingDialog::label_10 [inherited]

Definition at line 58 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.21 QLabel* Ui_AnimSettingDialog::label_11 [inherited]

Definition at line 71 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.22 QLabel* Ui_AnimSettingDialog::label_12 [inherited]

Definition at line 55 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.23 QLabel* Ui_AnimSettingDialog::label_13 [inherited]

Definition at line 54 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.24 QLabel* Ui_AnimSettingDialog::label_2 [inherited]

Definition at line 39 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.25 QLabel* Ui_AnimSettingDialog::label_3 [inherited]

Definition at line 76 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.26 QLabel* Ui_AnimSettingDialog::label_4 [inherited]

Definition at line 51 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.27 QLabel* Ui_AnimSettingDialog::label_5 [inherited]

Definition at line 74 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.28 QLabel* Ui_AnimSettingDialog::label_6 [inherited]

Definition at line 62 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.29 QLabel* Ui_AnimSettingDialog::label_7 [inherited]

Definition at line 70 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.30 QLabel* Ui_AnimSettingDialog::label_8 [inherited]

Definition at line 52 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.31 QLabel* Ui_AnimSettingDialog::label_9 [inherited]

Definition at line 73 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.32 QFrame* Ui_AnimSettingDialog::line [inherited]

Definition at line 49 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.33 QFrame* Ui_AnimSettingDialog::line_2 [inherited]

Definition at line 65 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.34 QDoubleSpinBox* Ui_AnimSettingDialog::repeatBox [inherited]

Definition at line 47 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.35 QLabel* Ui_AnimSettingDialog::repeatLabel [inherited]

Definition at line 46 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.36 QLabel* Ui_AnimSettingDialog::repeatLabel_2 [inherited]

Definition at line 48 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.37 QLabel* Ui_AnimSettingDialog::sAuthorLabel [inherited]

Definition at line 72 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.38 QLabel* Ui_AnimSettingDialog::sDescLabel [inherited]

Definition at line 83 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.39 QGridLayout* Ui_AnimSettingDialog::settingsGrid [inherited]

Definition at line 38 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.40 QWidget* Ui_AnimSettingDialog::settingTab [inherited]

Definition at line 37 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.41 QLabel* Ui_AnimSettingDialog::sLicenseLabel [inherited]

Definition at line 80 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.42 QLabel* Ui_AnimSettingDialog::sNameLabel [inherited]

Definition at line 69 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.43 QLabel* Ui_AnimSettingDialog::sVerLabel [inherited]

Definition at line 79 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.44 QLabel* Ui_AnimSettingDialog::sYearLabel [inherited]

Definition at line 75 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.45 QTabWidget* Ui_AnimSettingDialog::tabWidget [inherited]

Definition at line 36 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.46 QGridLayout* Ui_AnimSettingDialog::timeGrid [inherited]

Definition at line 43 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and Ui_AnimSettingDialog::setupUi().

12.4.3.47 QWidget* Ui_AnimSettingDialog::timeTab [inherited]

Definition at line 42 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::retranslateUi(), and Ui_AnimSettingDialog::setupUi().

12.4.3.48 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer [inherited]

Definition at line 82 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.49 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer_2 [inherited]

Definition at line 64 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

12.4.3.50 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer_3 [inherited]

Definition at line 59 of file ui_animsettingdialog.h.

Referenced by Ui_AnimSettingDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_animsettingdialog.h

12.5 AnimSettingDialog Class Reference

```
#include <src/ckb/animsettingdialog.h>
```

Inheritance diagram for AnimSettingDialog:

Collaboration diagram for AnimSettingDialog:

Public Member Functions

- AnimSettingDialog (QWidget *parent, KbAnim *anim)
- ~AnimSettingDialog ()
- QString name () const

Private Slots

- void newDuration (double duration)
- void updateStops ()
- void angleDialChanged (QString name)
- void angleSpinnerChanged (QString name)
- void updateParam (QString name)
- void on_delayBox_valueChanged (double arg1)
- void on_repeatBox_valueChanged (double arg1)
- void on_kpDelayBox_valueChanged (double arg1)
- void on_kpRepeatBox_valueChanged (double arg1)
- void on_kpReleaseBox_stateChanged (int arg1)

Private Member Functions

- QFrame * hLine ()

Private Attributes

- Ui::AnimSettingDialog * ui
- QCheckBox * stopCheck
- QCheckBox * kpStopCheck
- bool hasRepeat
- KbAnim * _anim
- double lastDuration
- QMap< QString, QWidget * > settingWidgets

- QSignalMapper updateMapper
- QMap< QString, QSpinBox * > angleSpinners
- QSignalMapper angleDialMapper
- QSignalMapper angleSpinnerMapper

12.5.1 Detailed Description

Definition at line 15 of file animsettingdialog.h.

12.5.2 Constructor & Destructor Documentation

12.5.2.1 AnimSettingDialog::AnimSettingDialog (QWidget * *parent*, KbAnim * *anim*) [explicit]

Definition at line 19 of file animsettingdialog.cpp.

References AnimScript::Param::AGRADIENT, AnimScript::Param::ANGLE, angleDialChanged(), angleDialMapper, angleFlip(), angleSpinnerChanged(), angleSpinnerMapper, angleSpinners, Ui_AnimSettingDialog::animName, AnimScript::Param::ARGB, AnimScript::author(), AnimScript::Param::BOOL, Ui_AnimSettingDialog::delayBox, AnimScript::description(), AnimScript::Param::DOUBLE, AnimScript::Param::GRADIENT, AnimScript::hasKeypress(), AnimScript::hasParam(), KbAnim::hasParameter(), hasRepeat, hLine(), Ui_AnimSettingDialog::kpDelayBox, Ui_AnimSettingDialog::kpModeStopBox, Ui_AnimSettingDialog::kpReleaseBox, Ui_AnimSettingDialog::kpRepeatBox, Ui_AnimSettingDialog::kpRepeatLabel, Ui_AnimSettingDialog::kpRepeatLabel_2, kpStopCheck, AnimScript::Param::LABEL, lastDuration, AnimScript::license(), AnimScript::Param::LONG, AnimScript::Param::maximum, AnimScript::Param::minimum, AnimScript::Param::name, AnimScript::name(), KbAnim::name(), newDuration(), KbAnim::parameter(), AnimScript::paramIterator(), AnimScript::Param::postfix, AnimScript::Param::prefix, Ui_AnimSettingDialog::repeatBox, Ui_AnimSettingDialog::repeatLabel, Ui_AnimSettingDialog::repeatLabel_2, AnimScript::Param::RGB, Ui_AnimSettingDialog::sAuthorLabel, KbAnim::script(), KbAnim::scriptName(), Ui_AnimSettingDialog::sDescLabel, Ui_AnimSettingDialog::settingsGrid, settingWidgets, Ui_AnimSettingDialog::setupUi(), Ui_AnimSettingDialog::sLicenseLabel, Ui_AnimSettingDialog::sNameLabel, stopCheck, AnimScript::Param::STRING, Ui_AnimSettingDialog::sVerLabel, Ui_AnimSettingDialog::sYearLabel, Ui_AnimSettingDialog::timeGrid, AnimScript::Param::type, ui, updateMapper, updateParam(), updateStops(), AnimScript::version(), and AnimScript::year().

```
19                                                                  :
20     QDialog(parent),
21     ui(new Ui::AnimSettingDialog), stopCheck(0),
       kpStopCheck(0),
22     _anim(anim), lastDuration(1.0)
23 {
24     ui->setupUi(this);
25     setWindowTitle(anim->scriptName() + " Animation");
26     ui->animName->setText(anim->name());
27     const AnimScript* script = anim->script();
28
29     connect(&updateMapper, SIGNAL(mapped(QString)), this, SLOT(
       updateParam(QString)));
30     connect(&angleDialMapper, SIGNAL(mapped(QString)), this, SLOT(
       angleDialChanged(QString)));
31     connect(&angleSpinnerMapper, SIGNAL(mapped(QString)), this, SLOT(
       angleSpinnerChanged(QString)));
32
33     // Build settings UI
34     int row = 1;
35     ui->settingsGrid->addItem(new QSpacerItem(0, 10, QSizePolicy::Fixed, QSizePolicy::Fixed),
       row++, 6);
36     ui->settingsGrid->addWidget(new QLabel("<b>Animation</b>", this), row++, 0, 1, 7);
37     ui->settingsGrid->addWidget(hLine(), row++, 0, 1, 7);
38     bool rSpacePlaced = false;
39     QListIterator<AnimScript::Param> i(script->paramIterator());
40     while(i.hasNext()){
41         const AnimScript::Param& param = i.next();
42         // Skip timing/playback params
43         if(param.name == "duration"
44                 || param.name == "trigger" || param.name == "kptrigger"
45                 || param.name == "kpmode"
46                 || param.name == "delay" || param.name == "kpdelay"
47                 || param.name == "repeat" || param.name == "kprepeat"
48                 || param.name == "stop" || param.name == "kpstop"
```

```
                || param.name == "kpmodestop" || param.name == "kprelease")
            continue;
        QVariant value = anim->parameter(param.name);
        // Display prefix label on the left (except for booleans and labels)
        if(param.type != AnimScript::Param::BOOL && param.type != AnimScript::Param::LABEL)
            ui->settingsGrid->addWidget(new QLabel(param.prefix, this), row, 1);
        // Configure and display main widget
        QWidget* widget = 0;
        int colSpan = 1;
        QString postfix = param.postfix;
        switch(param.type){
        case AnimScript::Param::BOOL:
            widget = new QCheckBox(param.prefix, this);
            ((QCheckBox*)widget)->setChecked(value.toBool());
            colSpan = 4;
            connect(widget, SIGNAL(stateChanged(int)), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::LONG:
            widget = new QSpinBox(this);
            ((QSpinBox*)widget)->setMinimum(param.minimum.toInt());
            ((QSpinBox*)widget)->setMaximum(param.maximum.toInt());
            ((QSpinBox*)widget)->setValue(value.toInt());
            if(postfix.length() <= 3){
                ((QSpinBox*)widget)->setSuffix(postfix);
                postfix = "";
            }
            connect(widget, SIGNAL(valueChanged(int)), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::DOUBLE:
            widget = new QDoubleSpinBox(this);
            ((QDoubleSpinBox*)widget)->setDecimals(1);
            ((QDoubleSpinBox*)widget)->setMinimum(param.minimum.toDouble());
            ((QDoubleSpinBox*)widget)->setMaximum(param.maximum.toDouble());
            ((QDoubleSpinBox*)widget)->setValue(value.toDouble());
            if(postfix.length() <= 3){
                ((QDoubleSpinBox*)widget)->setSuffix(postfix);
                postfix = "";
            }
            connect(widget, SIGNAL(valueChanged(double)), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::RGB:
            widget = new ColorButton(this);
            ((ColorButton*)widget)->color(QColor("#" + value.toString()));
            colSpan = 3;
            connect(widget, SIGNAL(colorChanged(QColor)), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::ARGB:{
            widget = new ColorButton(this, true);
            QString val = value.toString();
            QColor color;
            if(val.length() == 8){
                color = "#" + val.right(6);
                color.setAlpha(val.left(2).toInt(0, 16));
            } else
                color = "#" + val;
            ((ColorButton*)widget)->color(color);
            colSpan = 3;
            connect(widget, SIGNAL(colorChanged(QColor)), &updateMapper, SLOT(map()));
            break;
        }
        case AnimScript::Param::GRADIENT:
            widget = new GradientButton(this);
            ((GradientButton*)widget)->fromString(value.toString());
            colSpan = 3;
            connect(widget, SIGNAL(gradientChanged()), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::AGRADIENT:
            widget = new GradientButton(this, true);
            ((GradientButton*)widget)->fromString(value.toString());
            colSpan = 3;
            connect(widget, SIGNAL(gradientChanged()), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::ANGLE:
            widget = new QDial(this);
            ((QDial*)widget)->setFixedSize(60, 60);
            ((QDial*)widget)->setMinimum(0);
            ((QDial*)widget)->setMaximum(360);
            // this is NOT a typo...     ^
            // Even though 360 shouldn't be valid, the wheel/arrow keys will lose 1 degree at the bottom unless 360 is set as max
            ((QDial*)widget)->setSingleStep(5);
            ((QDial*)widget)->setPageStep(15);
            ((QDial*)widget)->setNotchTarget(6);
            ((QDial*)widget)->setNotchesVisible(true);
            ((QDial*)widget)->setWrapping(true);
            ((QDial*)widget)->setInvertedAppearance(true);
```

```
            ((QDial*)widget)->setValue(angleFlip(value.toInt()));
            angleDialMapper.setMapping(widget, param.name);
            connect(widget, SIGNAL(valueChanged(int)), &angleDialMapper, SLOT(map()));
            break;
        case AnimScript::Param::STRING:
            widget = new QLineEdit(this);
            ((QLineEdit*)widget)->setText(value.toString());
            colSpan = 3;
            connect(widget, SIGNAL(textEdited(const QString&)), &updateMapper, SLOT(map()));
            break;
        case AnimScript::Param::LABEL:
            widget = new QLabel(this);
            ((QLabel*)widget)->setText(param.prefix);
            colSpan = 4;
            break;
        default:
            break;
        }
        if(widget)
            updateMapper.setMapping(widget, param.name);
        if(param.type == AnimScript::Param::BOOL || param.type == AnimScript::Param::LABEL){
            // Boolean values are placed on the left with no prefix or postfix
            settingWidgets[param.name] = widget;
            ui->settingsGrid->addWidget(widget, row, 3, 1, colSpan);
        } else {
            // Display the widget
            if(widget){
                settingWidgets[param.name] = widget;
                ui->settingsGrid->addWidget(widget, row, 3, 1, colSpan);
            }
            // Angles additionally have a spin box
            if(param.type == AnimScript::Param::ANGLE){
                QSpinBox* spinner = new QSpinBox(this);
                spinner->setMinimum(0);
                spinner->setMaximum(359);
                spinner->setWrapping(true);
                spinner->setSuffix("°");
                spinner->setValue(value.toInt());
                angleSpinners[param.name] = spinner;
                angleSpinnerMapper.setMapping(spinner, param.name);
                connect(spinner, SIGNAL(valueChanged(int)), &angleSpinnerMapper, SLOT(map()));
                ui->settingsGrid->addWidget(spinner, row, 4);
                colSpan = 2;
            }
            // Display postfix label on the right
            ui->settingsGrid->addWidget(new QLabel(postfix, this), row, 3 + colSpan, 1, 4 - colSpan);
            if(colSpan < 3 && !rSpacePlaced){
                // Add a spacer to compress short elements to the left
                ui->settingsGrid->addItem(new QSpacerItem(0, 0, QSizePolicy::Minimum), row, 4 + colSpan);
                rSpacePlaced = true;
            }
        }
        row++;
    }
    // Add playback info at bottom
    ui->settingsGrid->addItem(new QSpacerItem(0, 10, QSizePolicy::Fixed, QSizePolicy::Fixed), row++, 6);
    ui->settingsGrid->addWidget(new QLabel("<b>Playback</b>", this), row++, 0, 1, 7);
    ui->settingsGrid->addWidget(hLine(), row++, 0, 1, 7);
    if(script->hasParam("duration")){
        // Show duration spinner (if allowed)
        lastDuration = anim->parameter("duration").toDouble();
        ui->settingsGrid->addWidget(new QLabel("Duration:", this), row, 1);
        QDoubleSpinBox* spinner = new QDoubleSpinBox(this);
        spinner->setDecimals(1);
        spinner->setMinimum(0.1);
        spinner->setValue(lastDuration);
        connect(spinner, SIGNAL(valueChanged(double)), this, SLOT(newDuration(double)));
        settingWidgets["duration"] = spinner;
        ui->settingsGrid->addWidget(spinner, row, 3, 1, 1);
        ui->settingsGrid->addWidget(new QLabel("seconds", this), row, 4, 1, 2);
        row++;
    }
    // Show boxes for start with mode/with keypress
    QCheckBox* check = new QCheckBox("Start with mode", this);
    check->setChecked(anim->parameter("trigger").toBool());
    ui->settingsGrid->addWidget(check, row, 3, 1, 4);
    settingWidgets["trigger"] = check;
    connect(check, SIGNAL(stateChanged(int)), &updateMapper, SLOT(map()));
    updateMapper.setMapping(check, "trigger");
    row++;
    check = new QCheckBox("Start with key press", this);
```

```
    check->setChecked(anim->parameter("kptrigger").toBool());
    ui->settingsGrid->addWidget(check, row, 3, 1, 2);
    settingWidgets["kptrigger"] = check;
    connect(check, SIGNAL(stateChanged(int)), &updateMapper, SLOT(map()));
    updateMapper.setMapping(check, "kptrigger");
    // Add an option allowing the user to select keypress mode
    QComboBox* combo = new QComboBox(this);
    int selected = anim->parameter("kpmode").toInt();
    if(script->hasKeypress()){
        // If the script supports keypresses, show the option to handle them that way (default)
        combo->addItem("on pressed key");
        combo->addItem("on whole keyboard");
        combo->addItem("on keyboard (once)");
    } else {
        selected--;
        // Otherwise, just show the choice of whether to start it every time or just once
        combo->addItem("every time");
        combo->addItem("only once");
    }
    if(selected < 0 || selected > combo->count())
        selected = 0;
    combo->setCurrentIndex(selected);
    ui->settingsGrid->addWidget(combo, row, 5, 1, 2);
    settingWidgets["kpmode"] = combo;
    connect(combo, SIGNAL(activated(int)), &updateMapper, SLOT(map()));
    updateMapper.setMapping(combo, "kpmode");
    row++;

    // Add horizontal spacer to compress content to left
    ui->settingsGrid->addItem(new QSpacerItem(0, 0, QSizePolicy::Expanding), 0, 6);
    // Add vertical spacer to compress content to top
    ui->settingsGrid->addItem(new QSpacerItem(0, 0, QSizePolicy::Minimum,
QSizePolicy::Expanding), row, 0);

    // Add timing fields
    settingWidgets["delay"] = ui->delayBox;
    ui->delayBox->setValue(anim->parameter("delay").toDouble());
    settingWidgets["kpdelay"] = ui->kpDelayBox;
    ui->kpDelayBox->setValue(anim->parameter("kpdelay").toDouble());
    settingWidgets["kpmodestop"] = ui->kpModeStopBox;
    ui->kpModeStopBox->setChecked(anim->parameter("kpmodestop").toBool());
    connect(ui->kpModeStopBox, SIGNAL(clicked(bool)), &
updateMapper, SLOT(map()));
    updateMapper.setMapping(ui->kpModeStopBox, "kpmodestop");
    settingWidgets["kprelease"] = ui->kpReleaseBox;
    ui->kpReleaseBox->setChecked(anim->parameter("kprelease").toBool());
    if(anim->hasParameter("repeat")){
        hasRepeat = true;
        settingWidgets["repeat"] = ui->repeatBox;
        ui->repeatBox->setValue(anim->parameter("repeat").toDouble());
        settingWidgets["kprepeat"] = ui->kpRepeatBox;
        ui->kpRepeatBox->setValue(anim->parameter("kprepeat").toDouble());
        // If repeat is enabled, add repeat counts as integer values
        // Mode repeat
        ui->timeGrid->addWidget(new QLabel("Repeat:", this), 4, 1);
        QSpinBox* spinner = new QSpinBox(this);
        spinner->setMinimum(0);
        spinner->setMaximum(1000000);
        spinner->setValue(anim->parameter("stop").toInt());
        settingWidgets["stop"] = spinner;
        connect(spinner, SIGNAL(valueChanged(int)), &updateMapper, SLOT(map()));
        updateMapper.setMapping(spinner, "stop");
        ui->timeGrid->addWidget(spinner, 4, 3);
        ui->timeGrid->addWidget(new QLabel("times", this), 4, 4);
        // KP repeat
        ui->timeGrid->addWidget(new QLabel("Repeat:", this), 12, 1);
        spinner = new QSpinBox(this);
        spinner->setMinimum(0);
        spinner->setMaximum(1000000);
        spinner->setValue(anim->parameter("kpstop").toInt());
        settingWidgets["kpstop"] = spinner;
        connect(spinner, SIGNAL(valueChanged(int)), &updateMapper, SLOT(map()));
        updateMapper.setMapping(spinner, "kpstop");
        ui->timeGrid->addWidget(spinner, 12, 3);
        ui->timeGrid->addWidget(new QLabel("times", this), 12, 4);
        // Infinite repeat toggles
        stopCheck = new QCheckBox("Forever", this);
        stopCheck->setChecked(anim->parameter("stop").toInt() < 0);
        ui->timeGrid->addWidget(stopCheck, 4, 5);
        kpStopCheck = new QCheckBox("Forever", this);
        connect(stopCheck, SIGNAL(clicked()), this, SLOT(updateStops()));
        kpStopCheck->setChecked(anim->parameter("kpstop").toInt() < 0);
        ui->timeGrid->addWidget(kpStopCheck, 12, 5);
        connect(kpStopCheck, SIGNAL(clicked()), this, SLOT(
updateStops()));
    } else {
        hasRepeat = false;
```

```
        // If repeat is not enabled, hide repeat-related fields
        ui->repeatBox->setHidden(true);
        ui->repeatLabel->setHidden(true);
        ui->repeatLabel_2->setHidden(true);
        ui->kpRepeatBox->setHidden(true);
        ui->kpRepeatLabel->setHidden(true);
        ui->kpRepeatLabel_2->setHidden(true);
        // Add stop times as double values
        // Stop time
        QDoubleSpinBox* spinner = new QDoubleSpinBox(this);
        spinner->setDecimals(1);
        spinner->setMinimum(0.1);
        spinner->setMaximum(24. * 60. * 60.);
        double stop = anim->parameter("stop").toDouble();
        if(stop <= 0.)
            spinner->setValue(lastDuration);
        else
            spinner->setValue(stop);
        settingWidgets["stop"] = spinner;
        connect(spinner, SIGNAL(valueChanged(double)), &updateMapper, SLOT(map()));
        updateMapper.setMapping(spinner, "stop");
        ui->timeGrid->addWidget(spinner, 4, 3);
        ui->timeGrid->addWidget(new QLabel("seconds", this), 4, 4);
        // KP stop time
        spinner = new QDoubleSpinBox(this);
        spinner->setDecimals(1);
        spinner->setMinimum(0.1);
        spinner->setMaximum(24. * 60. * 60.);
        double kpstop = anim->parameter("kpstop").toDouble();
        if(kpstop <= 0.)
            spinner->setValue(lastDuration);
        else
            spinner->setValue(kpstop);
        settingWidgets["kpstop"] = spinner;
        connect(spinner, SIGNAL(valueChanged(double)), &updateMapper, SLOT(map()));
        updateMapper.setMapping(spinner, "kpstop");
        ui->timeGrid->addWidget(spinner, 12, 3);
        ui->timeGrid->addWidget(new QLabel("seconds", this), 12, 4);
        // Infinite run toggles
        stopCheck = new QCheckBox("Stop after:", this);
        stopCheck->setChecked(stop > 0.);
        ui->timeGrid->addWidget(stopCheck, 4, 1);
        connect(stopCheck, SIGNAL(clicked()), this, SLOT(updateStops()));
        kpStopCheck = new QCheckBox("Stop after:", this);
        kpStopCheck->setChecked(kpstop > 0.);
        ui->timeGrid->addWidget(kpStopCheck, 12, 1);
        connect(kpStopCheck, SIGNAL(clicked()), this, SLOT(updateStops()));
    }
    updateStops();

    // Set script info UI
    ui->sNameLabel->setText(script->name());
    ui->sVerLabel->setText(script->version());
    ui->sAuthorLabel->setText(script->author());
    ui->sYearLabel->setText(script->year());
    ui->sLicenseLabel->setText(script->license());
    ui->sDescLabel->setText(script->description());

    // Lock dialog size
    setFixedSize(minimumSize());
}
```

Here is the call graph for this function:

12.5.2.2 AnimSettingDialog::~AnimSettingDialog ( )

Definition at line 476 of file animsettingdialog.cpp.

References ui.

```
476                                     {
477     delete ui;
478 }
```

12.5.3 Member Function Documentation

12.5.3.1 void AnimSettingDialog::angleDialChanged (QString *name*) [private],[slot]

Definition at line 389 of file animsettingdialog.cpp.

References angleFlip(), angleSpinners, name(), settingWidgets, and updateParam().

Referenced by AnimSettingDialog().

```
389                                                 {
390     // Dial changed; update spinner value
391     angleSpinners[name]->setValue(angleFlip(((QDial*)
      settingWidgets[name])->value()));
392     updateParam(name);
393 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.5.3.2 void AnimSettingDialog::angleSpinnerChanged (QString *name*) [private],[slot]

Definition at line 395 of file animsettingdialog.cpp.

References angleFlip(), angleSpinners, settingWidgets, and updateParam().

Referenced by AnimSettingDialog().

```
395                                                 {
```

```
    // Spinner changed; update dial value
    ((QDial*)settingWidgets[name])->setValue(angleFlip(angleSpinners[name]->value()));
    updateParam(name);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.5.3.3 QFrame * AnimSettingDialog::hLine ( ) [private]

Definition at line 480 of file animsettingdialog.cpp.

Referenced by AnimSettingDialog().

```
{
    QFrame* frame = new QFrame(this);
    frame->setFrameShape(QFrame::HLine);
    frame->setFrameShadow(QFrame::Sunken);
    return frame;
}
```

Here is the caller graph for this function:

12.5.3.4 QString AnimSettingDialog::name ( ) const

Definition at line 472 of file animsettingdialog.cpp.

References Ui_AnimSettingDialog::animName, and ui.

Referenced by angleDialChanged(), and KbAnimWidget::on_propertyButton_clicked().

```
472                                     {
473     return ui->animName->text();
474 }
```

Here is the caller graph for this function:

12.5.3.5 void AnimSettingDialog::newDuration (double *duration*) [private],[slot]

Definition at line 361 of file animsettingdialog.cpp.

References lastDuration, settingWidgets, and updateParam().

Referenced by AnimSettingDialog().

```
361                                             {
362     // Duration changed. Automatically fix Repeat and KP Repeat to the same values, if they matched before
363     QDoubleSpinBox* rep = (QDoubleSpinBox*)settingWidgets.value("repeat");
364     QDoubleSpinBox* kpRep = (QDoubleSpinBox*)settingWidgets.value("kprepeat");
365     if(rep && rep->value() == lastDuration)
366         rep->setValue(duration);
367     if(kpRep && kpRep->value() == lastDuration)
368         kpRep->setValue(duration);
369     lastDuration = duration;
370     updateParam("duration");
371     updateParam("repeat");
372     updateParam("kprepeat");
373 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.5.3.6 void AnimSettingDialog::on_delayBox_valueChanged (double *arg1*) [private],[slot]

Definition at line 487 of file animsettingdialog.cpp.

References updateParam().

```
487                                                     {
488     updateParam("delay");
489 }
```

Here is the call graph for this function:

12.5.3.7 void AnimSettingDialog::on_kpDelayBox_valueChanged (double *arg1*) [private],[slot]

Definition at line 495 of file animsettingdialog.cpp.

References updateParam().

```
495                                                                 {
496     updateParam("kpdelay");
497 }
```

Here is the call graph for this function:

12.5.3.8 void AnimSettingDialog::on_kpReleaseBox_stateChanged (int *arg1*) [private],[slot]

Definition at line 503 of file animsettingdialog.cpp.

References updateParam().

```
503                                                     {
504     updateParam("kprelease");
505 }
```

Here is the call graph for this function:

12.5.3.9 void AnimSettingDialog::on_kpRepeatBox_valueChanged (double *arg1*) [private],[slot]

Definition at line 499 of file animsettingdialog.cpp.

References updateParam().

```
499                                                     {
500     updateParam("kprepeat");
501 }
```

Here is the call graph for this function:

12.5.3.10 void AnimSettingDialog::on_repeatBox_valueChanged (double *arg1*) [private],[slot]

Definition at line 491 of file animsettingdialog.cpp.

References updateParam().

```
491                                                     {
492     updateParam("repeat");
493 }
```

Here is the call graph for this function:

12.5.3.11 void AnimSettingDialog::updateParam (QString *name*) [private],[slot]

Definition at line 401 of file animsettingdialog.cpp.

References _anim, AnimScript::Param::AGRADIENT, AnimScript::Param::ANGLE, angleFlip(), AnimScript::Param::ARGB, AnimScript::Param::BOOL, ColorButton::color(), AnimScript::Param::DOUBLE, AnimScript::Param::GRADIENT, AnimScript::hasKeypress(), hasRepeat, kpStopCheck, AnimScript::Param::LONG, AnimScript::param(), KbAnim::parameter(), AnimScript::Param::RGB, KbAnim::script(), settingWidgets, stopCheck, AnimScript::Param::STRING, GradientButton::toString(), and AnimScript::Param::type.

Referenced by angleDialChanged(), angleSpinnerChanged(), AnimSettingDialog(), newDuration(), on_delayBox_valueChanged(), on_kpDelayBox_valueChanged(), on_kpReleaseBox_stateChanged(), on_kpRepeatBox_valueChanged(), on_repeatBox_valueChanged(), and updateStops().

```
401                                                 {
402     if(!settingWidgets.contains(name))
403         return;
404     // stop and kpstop have defeat switches
405     if((name == "stop" && stopCheck->isChecked() == hasRepeat)
406             || (name == "kpstop" && kpStopCheck->isChecked() ==
    hasRepeat)){
407         _anim->parameter(name, -1);
408         return;
409     } else if(name == "kpmode"){
410         // kpmode uses a drop-down, and selection is inverted
411         QComboBox* widget = (QComboBox*)settingWidgets[name];
412         int selected = widget->currentIndex();
413         if(!_anim->script()->hasKeypress())
414             selected++;
415         _anim->parameter(name, selected);
416         return;
417     }
418     // Read value based on type
```

```
    switch(_anim->script()->param(name).type){
    case AnimScript::Param::BOOL:{
        QCheckBox* widget = (QCheckBox*)settingWidgets[name];
        _anim->parameter(name, (int)widget->isChecked());
        break;
    }
    case AnimScript::Param::LONG:{
        QSpinBox* widget = (QSpinBox*)settingWidgets[name];
        _anim->parameter(name, widget->value());
        break;
    }
    case AnimScript::Param::DOUBLE:{
        QDoubleSpinBox* widget = (QDoubleSpinBox*)settingWidgets[name];
        _anim->parameter(name, widget->value());
        break;
    }
    case AnimScript::Param::RGB:{
        ColorButton* widget = (ColorButton*)settingWidgets[name];
        QColor color = widget->color();
        char hex[7];
        snprintf(hex, sizeof(hex), "%02x%02x%02x", color.red(), color.green(), color.blue());
        _anim->parameter(name, QString(hex));
        break;
    }
    case AnimScript::Param::ARGB:{
        ColorButton* widget = (ColorButton*)settingWidgets[name];
        QColor color = widget->color();
        char hex[9];
        snprintf(hex, sizeof(hex), "%02x%02x%02x%02x", color.alpha(), color.red(), color.green(), color.blue());
        _anim->parameter(name, QString(hex));
        break;
    }
    case AnimScript::Param::GRADIENT:
    case AnimScript::Param::AGRADIENT:{
        GradientButton* widget = (GradientButton*)settingWidgets[name];
        _anim->parameter(name, widget->toString());
        break;
    }
    case AnimScript::Param::ANGLE:{
        QDial* widget = (QDial*)settingWidgets[name];
        _anim->parameter(name, angleFlip(widget->value()));
        break;
    }
    case AnimScript::Param::STRING:{
        QLineEdit* widget = (QLineEdit*)settingWidgets[name];
        _anim->parameter(name, widget->text());
        break;
    }
    default:
        break;
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.5.3.12 void AnimSettingDialog::updateStops ( ) [private],[slot]

Definition at line 375 of file animsettingdialog.cpp.

References hasRepeat, kpStopCheck, settingWidgets, stopCheck, and updateParam().

Referenced by AnimSettingDialog().

```
375                                     {
376     if(hasRepeat){
377         // When repeat is enabled, the check box is "repeat forever", so disable stop count if checked
378         settingWidgets.value("stop")->setDisabled(stopCheck->isChecked());
379         settingWidgets.value("kpstop")->setDisabled(kpStopCheck->isChecked());
380     } else {
381         // When repeat is disabled, the check box is "stop after", so disable stop count UNLESS checked
382         settingWidgets.value("stop")->setEnabled(stopCheck->isChecked());
383         settingWidgets.value("kpstop")->setEnabled(kpStopCheck->isChecked());
384     }
385     updateParam("stop");
386     updateParam("kpstop");
387 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.5.4 Field Documentation

12.5.4.1 KbAnim* AnimSettingDialog::_anim [private]

Definition at line 32 of file animsettingdialog.h.

Referenced by updateParam().

12.5.4.2 QSignalMapper AnimSettingDialog::angleDialMapper [private]

Definition at line 38 of file animsettingdialog.h.

Referenced by AnimSettingDialog().

12.5.4.3 QSignalMapper AnimSettingDialog::angleSpinnerMapper [private]

Definition at line 38 of file animsettingdialog.h.

Referenced by AnimSettingDialog().

12.5.4.4 QMap<QString, QSpinBox*> AnimSettingDialog::angleSpinners [private]

Definition at line 37 of file animsettingdialog.h.

Referenced by angleDialChanged(), angleSpinnerChanged(), and AnimSettingDialog().

12.5.4.5 bool AnimSettingDialog::hasRepeat [private]

Definition at line 30 of file animsettingdialog.h.

Referenced by AnimSettingDialog(), updateParam(), and updateStops().

12.5.4.6 QCheckBox * AnimSettingDialog::kpStopCheck [private]

Definition at line 29 of file animsettingdialog.h.

Referenced by AnimSettingDialog(), updateParam(), and updateStops().

12.5.4.7 double AnimSettingDialog::lastDuration [private]

Definition at line 33 of file animsettingdialog.h.

Referenced by AnimSettingDialog(), and newDuration().

12.5.4.8 QMap<QString, QWidget*> AnimSettingDialog::settingWidgets [private]

Definition at line 34 of file animsettingdialog.h.

Referenced by angleDialChanged(), angleSpinnerChanged(), AnimSettingDialog(), newDuration(), updateParam(), and updateStops().

12.5.4.9 QCheckBox* AnimSettingDialog::stopCheck [private]

Definition at line 29 of file animsettingdialog.h.

Referenced by AnimSettingDialog(), updateParam(), and updateStops().

12.5.4.10 Ui::AnimSettingDialog* AnimSettingDialog::ui [private]

Definition at line 28 of file animsettingdialog.h.

Referenced by AnimSettingDialog(), name(), and ~AnimSettingDialog().

12.5.4.11 QSignalMapper AnimSettingDialog::updateMapper [private]

Definition at line 35 of file animsettingdialog.h.

Referenced by AnimSettingDialog().

The documentation for this class was generated from the following files:

- src/ckb/animsettingdialog.h
- src/ckb/animsettingdialog.cpp

12.6 AutoRun Class Reference

`#include <src/ckb/autorun.h>`

Collaboration diagram for AutoRun:

Static Public Member Functions

- static bool available ()
- static bool once ()
- static bool isEnabled ()
- static void enable ()
- static void disable ()

12.6.1 Detailed Description

Definition at line 8 of file autorun.h.

12.6.2 Member Function Documentation

12.6.2.1 bool AutoRun::available ( ) [static]

Definition at line 20 of file autorun.cpp.

Referenced by disable(), enable(), and SettingsWidget::SettingsWidget().

```
20                          {
21     // Allow autostart if the program is located in a system path
22 #ifdef Q_OS_LINUX
23     return QDir::root().absoluteFilePath(QStandardPaths::findExecutable("ckb")) == qApp->
       applicationFilePath();
24 #elif defined(Q_OS_MACX)
25     return qApp->applicationFilePath().startsWith("/Applications/ckb.app", Qt::CaseInsensitive);
26 #endif
27 }
```

Here is the caller graph for this function:

12.6.2.2 void AutoRun::disable ( ) [static]

Definition at line 53 of file autorun.cpp.

References available().

Referenced by SettingsWidget::on_loginItemBox_clicked().

```
53                      {
54      if(!available())
55          return;
56      // Remove file
57      QFile::remove(path.absoluteFilePath(file));
58  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.6.2.3 void AutoRun::enable ( ) [static]

Definition at line 42 of file autorun.cpp.

References available(), and CkbSettings::set().

Referenced by SettingsWidget::on_loginItemBox_clicked(), and SettingsWidget::SettingsWidget().

```
{
    if(!available())
        return;
    // Copy file into place
    if(!path.exists())
        QDir::home().mkpath(path.absolutePath());
    QFile::copy(internalFile, path.absoluteFilePath(file));
    // Mark once() as done
    CkbSettings::set(settingPath, true);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.6.2.4 bool AutoRun::isEnabled ( ) [static]

Definition at line 33 of file autorun.cpp.

References CkbSettings::set().

Referenced by SettingsWidget::SettingsWidget().

```
{
    // Check if the file exists. If not, autostart is disabled.
    if(!path.exists() || !path.exists(file))
        return false;
    // If autostart is enabled, set the flag from once() (in case it hasn't been done yet)
    CkbSettings::set(settingPath, true);
    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.6.2.5 bool AutoRun::once ( ) [static]

Definition at line 29 of file autorun.cpp.

References CkbSettings::get().

Referenced by SettingsWidget::SettingsWidget().

```
29                  {
30      return CkbSettings::get(settingPath).toBool();
31  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

The documentation for this class was generated from the following files:

- src/ckb/autorun.h
- src/ckb/autorun.cpp

12.7 CkbSettings Class Reference

```
#include <src/ckb/ckbsettings.h>
```

Collaboration diagram for CkbSettings:

Public Member Functions

- CkbSettings ()
- CkbSettings (const QString &basePath, bool eraseExisting=false)
- CkbSettings (QSettings &settings)
- ~CkbSettings ()
- void beginGroup (const QString &prefix)
- void endGroup ()
- QStringList childGroups () const
- QStringList childKeys () const
- bool contains (const QString &key) const
- bool containsGroup (const QString &group)
- QVariant value (const QString &key, const QVariant &defaultValue=QVariant()) const
- void setValue (const QString &key, const QVariant &value)
- void remove (const QString &key)

Static Public Member Functions

- static QVariant get (const QString &key, const QVariant &defaultValue=QVariant())

- static void set (const QString &key, const QVariant &value)
- static bool isBusy ()
- static void cleanUp ()

Private Member Functions

- QString pwd () const
- QString pwd (const QString &key) const

Private Attributes

- QSettings * backing
- QStringList groups
- QStringList removeCache
- QMap< QString, QVariant > writeCache

12.7.1 Detailed Description

Definition at line 11 of file ckbsettings.h.

12.7.2 Constructor & Destructor Documentation

12.7.2.1 CkbSettings::CkbSettings ( )

Definition at line 61 of file ckbsettings.cpp.

```
61                          :
62     backing(globalSettings()) {
63 }
```

12.7.2.2 CkbSettings::CkbSettings (const QString & *basePath*, bool *eraseExisting* = `false`)

Definition at line 65 of file ckbsettings.cpp.

References beginGroup().

```
65                                                                  :
66     backing(globalSettings()) {
67     if(basePath.isEmpty()){
68         if(eraseExisting)
69             qDebug() << "CkbSettings created with basePath = \"\" and eraseExisting = true. This is a
       mistake.";
70         return;
71     }
72     if(eraseExisting)
73         remove(basePath);
74     beginGroup(basePath);
75 }
```

Here is the call graph for this function:

12.7.2.3 CkbSettings::CkbSettings (QSettings & *settings*)

Definition at line 77 of file ckbsettings.cpp.

```
77                                                  :
78     backing(&settings) {
79 }
```

12.7.2.4 CkbSettings::~CkbSettings ( )

Definition at line 145 of file ckbsettings.cpp.

References backing, removeCache, and writeCache.

```
145                                 {
146     if(removeCache.isEmpty() && writeCache.isEmpty())
147         return;
148     // Save the settings from the settings thread.
149     // They have to be saved from that thread specifically to avoid performance issues
150     CkbSettingsWriter* writer = new CkbSettingsWriter(
      backing, removeCache, writeCache);
151     writer->moveToThread(globalThread);
152     QObject::staticMetaObject.invokeMethod(writer, "run", Qt::QueuedConnection);
153 }
```

12.7.3 Member Function Documentation

12.7.3.1 void CkbSettings::beginGroup (const QString & *prefix*)

Definition at line 81 of file ckbsettings.cpp.

References groups.

Referenced by CkbSettings(), KbAnim::save(), and SGroup::SGroup().

```
81                                                  {
82     groups.append(prefix);
83 }
```

Here is the caller graph for this function:

12.7.3.2 QStringList CkbSettings::childGroups ( ) const

Definition at line 89 of file ckbsettings.cpp.

References backing, lockMutex, and pwd().

Referenced by containsGroup(), and GradientDialog::GradientDialog().

```
89                                                  {
90     QString current = pwd();
91     lockMutex;
92     if(!current.isEmpty())
93         backing->beginGroup(current);
94     QStringList res = backing->childGroups();
95     if(!current.isEmpty())
96         backing->endGroup();
97     return res;
98 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.3 QStringList CkbSettings::childKeys ( ) const

Definition at line 100 of file ckbsettings.cpp.

References backing, lockMutex, and pwd().

Referenced by GradientDialog::GradientDialog(), KbAnim::KbAnim(), KbBind::load(), KbLight::load(), and KbBind::loadGlobalRemap().

```
100                                         {
101     QString current = pwd();
102     lockMutex;
103     if(!current.isEmpty())
104         backing->beginGroup(current);
105     QStringList res = backing->childKeys();
106     if(!current.isEmpty())
107         backing->endGroup();
108     return res;
109 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.4 void CkbSettings::cleanUp ( ) [static]

Definition at line 46 of file ckbsettings.cpp.

References _globalSettings, cacheWritesInProgress(), and globalThread.

Referenced by MainWindow::cleanup().

```
46                          {
47     if(!_globalSettings)
48         return;
49     // Wait for all writers to finish
50     while(cacheWritesInProgress.load() > 0)
51         QThread::yieldCurrentThread();
52     // Stop thread and delete objects
53     globalThread->quit();
54     globalThread->wait();
55     delete globalThread;
56     delete _globalSettings;
57     globalThread = 0;
58     _globalSettings = 0;
59 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.5 bool CkbSettings::contains (const QString & *key*) const

Definition at line 111 of file ckbsettings.cpp.

References backing, lockMutex, and pwd().

Referenced by KbMode::KbMode(), KbProfile::KbProfile(), and KbPerf::load().

```
111                                                 {
112     lockMutex;
113     return backing->contains(pwd(key));
114 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.6 bool CkbSettings::containsGroup (const QString & *group*)

Definition at line 116 of file ckbsettings.cpp.

References childGroups().

Referenced by KbPerf::load().

```
                                                {
    QStringList components = group.split("/");
    if(components.length() > 1){
        // Find sub-group
        SGroup group(*this, components[0]);
        return containsGroup(QStringList(components.mid(1)).join('/'));
    }
    return childGroups().contains(group);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.7 void CkbSettings::endGroup ( )

Definition at line 85 of file ckbsettings.cpp.

References groups.

Referenced by KbAnim::save(), and SGroup::~SGroup().

```
                        {
    groups.removeLast();
}
```

Here is the caller graph for this function:

12.7.3.8 QVariant CkbSettings::get (const QString & *key*, const QVariant & *defaultValue* = `QVariant()`) `[static]`

Definition at line 155 of file ckbsettings.cpp.

References globalCache, globalSettings(), lockMutexCache, and lockMutexStatic2.

Referenced by MainWindow::closeEvent(), KbLightWidget::KbLightWidget(), MainWindow::MainWindow(), AutoRun::once(), and MainWindow::timerTick().

```
                                                                    {
    // Store these settings in a memory cache
    lockMutexCache;
    if(globalCache.contains(key))
        return globalCache.value(key);
    // If it wasn't found in the memory cache, look for it in QSettings
    lockMutexStatic2;
    QSettings* settings = globalSettings();
    return globalCache[key] = settings->value(key, defaultValue);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.9 bool CkbSettings::isBusy ( ) [static]

Definition at line 42 of file ckbsettings.cpp.

References cacheWritesInProgress().

Referenced by Kb::autoSave(), and ExtraSettingsWidget::pollUpdates().

```
                        {
    return cacheWritesInProgress.load() > 0;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.10 QString CkbSettings::pwd ( ) const [inline], [private]

Definition at line 51 of file ckbsettings.h.

References groups.

Referenced by childGroups(), childKeys(), contains(), remove(), setValue(), and value().

```
51 { return groups.join("/"); }
```

Here is the caller graph for this function:

12.7.3.11 QString CkbSettings::pwd (const QString & *key*) const [inline], [private]

Definition at line 52 of file ckbsettings.h.

References groups, and pwd().

Referenced by pwd().

```
52 { return pwd() + (groups.isEmpty() ? "" : "/") + key; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.12 void CkbSettings::remove (const QString & *key*)

Definition at line 141 of file ckbsettings.cpp.

References pwd(), and removeCache.

Referenced by SettingsWidget::SettingsWidget().

```
141                                         {
142     removeCache.append(pwd(key));
143 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.13 void CkbSettings::set (const QString & *key*, const QVariant & *value*) [static]

Definition at line 166 of file ckbsettings.cpp.

References globalCache, globalSettings(), lockMutexCache, lockMutexStatic, and value().

Referenced by MainWindow::closeEvent(), AutoRun::enable(), AutoRun::isEnabled(), SettingsWidget::on_autoFWBox_clicked(), ExtraSettingsWidget::on_delayBox_clicked(), ExtraSettingsWidget::on_ditherBox_clicked(), SettingsWidget::on_layoutBox_activated(), ExtraSettingsWidget::on_mAccelBox_clicked(), ExtraSettingsWidget::on_sAccelBox_clicked(), KbLightWidget::on_showAnimBox_clicked(), ExtraSettingsWidget::on_sSpeedBox_valueChanged(), ExtraSettingsWidget::on_trayBox_clicked(), MPerfWidget::on_xyBox_clicked(), and ExtraSettingsWidget::pollUpdates().

```
{
    {
        lockMutexCache;
        if(globalCache.value(key) == value)
            return;
        globalCache[key] = value;
    }
    lockMutexStatic;
    globalSettings()->setValue(key, value);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.14 void CkbSettings::setValue (const QString & *key*, const QVariant & *value*)

Definition at line 131 of file ckbsettings.cpp.

References globalCache, lockMutexCache, pwd(), value(), and writeCache.

Referenced by ExtraSettingsWidget::on_fpsBox_valueChanged(), KbProfile::save(), KbPerf::save(), KbAnim::save(), KbBind::save(), KbMode::save(), KbLight::save(), Kb::save(), KbBind::saveGlobalRemap(), SettingsWidget::SettingsWidget(), and GradientDialog::~GradientDialog().

```
131                                                                 {
132     // Cache the write values, save them when the object is destroyed
133     QString realKey = pwd(key);
134     writeCache[realKey] = value;
135     // Update global cache if needed
136     lockMutexCache;
137     if(globalCache.contains(realKey))
138         globalCache[realKey] = value;
139 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.3.15 QVariant CkbSettings::value (const QString & *key*, const QVariant & *defaultValue* = `QVariant()`) const

Definition at line 126 of file ckbsettings.cpp.

References backing, lockMutex, and pwd().

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), GradientDialog::GradientDialog(), KbAnim::KbAnim(), KbMode::KbMode(), KbProfile::KbProfile(), KbPerf::load(), KbBind::load(), KbLight::load(), Kb::load(), KbBind::loadGlobalRemap(), set(), SettingsWidget::SettingsWidget(), and setValue().

```
126                                                                 {
127     lockMutex;
128     return backing->value(pwd(key), defaultValue);
129 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.7.4 Field Documentation

12.7.4.1 QSettings* CkbSettings::backing [private]

Definition at line 46 of file ckbsettings.h.

Referenced by childGroups(), childKeys(), contains(), value(), and ~CkbSettings().

12.7.4.2 QStringList CkbSettings::groups [private]

Definition at line 47 of file ckbsettings.h.

Referenced by beginGroup(), endGroup(), and pwd().

12.7.4.3 QStringList CkbSettings::removeCache [private]

Definition at line 48 of file ckbsettings.h.

Referenced by remove(), and ~CkbSettings().

12.7.4.4 QMap<QString, QVariant> CkbSettings::writeCache [private]

Definition at line 49 of file ckbsettings.h.

Referenced by setValue(), and ~CkbSettings().

The documentation for this class was generated from the following files:

- src/ckb/ckbsettings.h
- src/ckb/ckbsettings.cpp

12.8 CkbSettingsWriter Class Reference

```
#include <src/ckb/ckbsettingswriter.h>
```

Inheritance diagram for CkbSettingsWriter:

Collaboration diagram for CkbSettingsWriter:

Public Member Functions

- CkbSettingsWriter (QSettings ∗backing, const QStringList &removals, const QMap< QString, QVariant > &updates)
- ∼CkbSettingsWriter ()
- Q_SLOT void run ()

Private Attributes

- QSettings ∗ _backing
- QStringList _removals
- QMap< QString, QVariant > _updates

12.8.1 Detailed Description

Definition at line 12 of file ckbsettingswriter.h.

12.8.2 Constructor & Destructor Documentation

12.8.2.1 CkbSettingsWriter::CkbSettingsWriter (QSettings ∗ *backing*, const QStringList & *removals*, const QMap< QString, QVariant > & *updates*)

Definition at line 12 of file ckbsettingswriter.cpp.

References cacheWritesInProgress.

```
12
                    :
13     _backing(backing), _removals(removals), _updates(updates) {
14     cacheWritesInProgress.ref();
15 }
```

12.8.2.2 CkbSettingsWriter::~CkbSettingsWriter ( )

Definition at line 17 of file ckbsettingswriter.cpp.

References cacheWritesInProgress.

```
17                                  {
18     cacheWritesInProgress.deref();
19 }
```

12.8.3 Member Function Documentation

12.8.3.1 void CkbSettingsWriter::run ( )

Definition at line 21 of file ckbsettingswriter.cpp.

References _backing, _removals, _updates, and lockMutexStatic.

```
21                              {
22     lockMutexStatic;
23     // Process key removals
24     foreach(const QString& rm, _removals){
25         _backing->remove(rm);
26     }
27     // Process writes
28     QMapIterator<QString, QVariant> i(_updates);
29     while(i.hasNext()){
30         i.next();
31         _backing->setValue(i.key(), i.value());
32         // Updating the global cache was done above
33     }
34     _backing->sync();
35     deleteLater();
36 }
```

12.8.4 Field Documentation

12.8.4.1 QSettings* CkbSettingsWriter::_backing [private]

Definition at line 21 of file ckbsettingswriter.h.

Referenced by run().

12.8.4.2 QStringList CkbSettingsWriter::_removals [private]

Definition at line 22 of file ckbsettingswriter.h.

Referenced by run().

12.8.4.3 QMap<QString, QVariant> CkbSettingsWriter::_updates [private]

Definition at line 23 of file ckbsettingswriter.h.

Referenced by run().

The documentation for this class was generated from the following files:

- src/ckb/ckbsettingswriter.h
- src/ckb/ckbsettingswriter.cpp

12.9 ColorButton Class Reference

```
#include <src/ckb/colorbutton.h>
```

Inheritance diagram for ColorButton:

Collaboration diagram for ColorButton:

Signals

- void colorChanged (QColor newColor)

Public Member Functions

- ColorButton (QWidget *parent=0, bool allowAlpha=false)
- const QColor & color () const
- void color (const QColor &newColor)
- bool allowAlpha () const
- void allowAlpha (bool newAllowAlpha)
- bool setLabel () const
- void setLabel (bool newSetLabel)
- bool bigIcons () const
- void bigIcons (bool newBigIcons)

Private Slots

- void pickColor ()

Private Member Functions

- void updateImage ()

Private Attributes

- QColor _color
- bool _alpha
- bool _setLabel
- bool _bigIcons

12.9.1 Detailed Description

Definition at line 6 of file colorbutton.h.

12.9.2 Constructor & Destructor Documentation

12.9.2.1 ColorButton::ColorButton (QWidget * *parent* = 0, bool *allowAlpha* = false) [explicit]

Definition at line 5 of file colorbutton.cpp.

References pickColor(), and updateImage().

```
5                                                       :
6     QPushButton(parent), _alpha(allowAlpha),
      _setLabel(true), _bigIcons(false)
7 {
8     setAutoDefault(false);
9     setDefault(false);
10     updateImage();
11     // Pick color on click (use queued connection so that any on_*_clicked() events can be processed first)
12     connect(this, SIGNAL(clicked()), this, SLOT(pickColor()), Qt::QueuedConnection);
13 }
```

Here is the call graph for this function:

12.9.3 Member Function Documentation

12.9.3.1 bool ColorButton::allowAlpha ( ) const [inline]

Definition at line 17 of file colorbutton.h.

References _alpha.

Referenced by KPerfWidget::KPerfWidget(), and MPerfWidget::MPerfWidget().

```
17 { return _alpha; }
```

Here is the caller graph for this function:

12.9.3.2 void ColorButton::allowAlpha (bool *newAllowAlpha*)

Definition at line 22 of file colorbutton.cpp.

References _alpha, and updateImage().

```
22                                                  {
23     _alpha = newAllowAlpha;
24     updateImage();
25 }
```

Here is the call graph for this function:

12.9.3.3 bool ColorButton::bigIcons ( ) const [inline]

Definition at line 23 of file colorbutton.h.

References _bigIcons.

Referenced by KPerfWidget::KPerfWidget(), and MPerfWidget::MPerfWidget().

```
23 { return _bigIcons; }
```

Here is the caller graph for this function:

12.9.3.4 void ColorButton::bigIcons (bool *newBigIcons*)

Definition at line 27 of file colorbutton.cpp.

References _bigIcons, and updateImage().

```
27                                          {
28     _bigIcons = newBigIcons;
29     updateImage();
30 }
```

Here is the call graph for this function:

12.9.3.5 const QColor& ColorButton::color ( ) const [inline]

Definition at line 13 of file colorbutton.h.

References _color.

Referenced by MPerfWidget::colorChanged(), GradientDialog::currentChanged(), KbLightWidget::newSelection(), GradientDialog::on_stopOpacity_valueChanged(), KPerfWidget::setPerf(), MPerfWidget::setPerf(), KPerfWidget::uiUpdated(), and AnimSettingDialog::updateParam().

```
13 { return _color; }
```

Here is the caller graph for this function:

12.9.3.6 void ColorButton::color (const QColor & *newColor*)

Definition at line 15 of file colorbutton.cpp.

References _alpha, _color, and updateImage().

```
15                                          {
16     _color = newColor;
17     if(!_alpha)
18         _color.setAlpha(255);
19     updateImage();
20 }
```

Here is the call graph for this function:

12.9.3.7 void ColorButton::colorChanged (QColor *newColor*) [signal]

Definition at line 132 of file moc_colorbutton.cpp.

Referenced by pickColor().

```
{
    void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
    QMetaObject::activate(this, &staticMetaObject, 0, _a);
}
```

Here is the caller graph for this function:

12.9.3.8 void ColorButton::pickColor ( ) [private],[slot]

Definition at line 60 of file colorbutton.cpp.

References _alpha, _color, colorChanged(), and updateImage().

Referenced by ColorButton().

```
                            {
    QColor newColor = QColorDialog::getColor(_color, this, QString(),
   QColorDialog::ColorDialogOptions(_alpha ? QColorDialog::ShowAlphaChannel : 0));
    if(newColor.isValid()){
        _color = newColor;
        updateImage();
        emit colorChanged(_color);
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.9.3.9 bool ColorButton::setLabel ( ) const [inline]

Definition at line 20 of file colorbutton.h.

References _setLabel.

Referenced by KPerfWidget::KPerfWidget(), and MPerfWidget::MPerfWidget().

```
20 { return _setLabel; }
```

Here is the caller graph for this function:

12.9.3.10 void ColorButton::setLabel (bool *newSetLabel*) [inline]

Definition at line 21 of file colorbutton.h.

References _setLabel.

```
21 { _setLabel = newSetLabel; }
```

12.9.3.11 void ColorButton::updateImage ( ) [private]

Definition at line 32 of file colorbutton.cpp.

References _alpha, _bigIcons, _color, and _setLabel.

Referenced by allowAlpha(), bigIcons(), color(), ColorButton(), and pickColor().

```
32                                {
33     if(!_color.isValid()){
34         setIcon(QIcon());
35         if(_setLabel)
36             setText("Change color...");
37         return;
38     }
39     const int w = 24, h = _bigIcons ? 24 : 12;
40     QImage image(w, h, QImage::Format_RGB888);
41     QPainter painter(&image);
42     painter.setPen(Qt::NoPen);
43     painter.fillRect(0, 0, w, h, QColor(0, 0, 0));
44     if(_alpha && _color.alpha() != 255){
45         painter.fillRect(1, 1, w / 2 - 1, h / 2 - 1, QColor(255, 255, 255));
46         painter.fillRect(w / 2, 1, w / 2 - 1, h / 2 - 1, QColor(192, 192, 192));
47         painter.fillRect(1, h / 2, w / 2 - 1, h / 2 - 1, QColor(192, 192, 192));
48         painter.fillRect(w / 2, h / 2, w / 2 - 1, h / 2 - 1, QColor(255, 255, 255));
49     }
50     painter.fillRect(1, 1, w - 2, h - 2, _color);
51     setIcon(QIcon(QPixmap::fromImage(image)));
52     if(_setLabel){
53         QString text = QString(" (%1, %2, %3)").arg(_color.red()).arg(
       _color.green()).arg(_color.blue());
54         if(_alpha)
```

```
            text += QString(", %4%").arg(QString::number(_color.alphaF() * 100., 'f', 0));
        setText(text);
    }
}
```

Here is the caller graph for this function:

12.9.4 Field Documentation

12.9.4.1 bool ColorButton::_alpha [private]

Definition at line 34 of file colorbutton.h.

Referenced by allowAlpha(), color(), pickColor(), and updateImage().

12.9.4.2 bool ColorButton::_bigIcons [private]

Definition at line 34 of file colorbutton.h.

Referenced by bigIcons(), and updateImage().

12.9.4.3 QColor ColorButton::_color [private]

Definition at line 33 of file colorbutton.h.

Referenced by color(), pickColor(), and updateImage().

12.9.4.4 bool ColorButton::_setLabel [private]

Definition at line 34 of file colorbutton.h.

Referenced by setLabel(), and updateImage().

The documentation for this class was generated from the following files:

- src/ckb/colorbutton.h
- src/ckb/colorbutton.cpp
- src/ckb/release/moc_colorbutton.cpp

12.10 ColorMap Class Reference

`#include <src/ckb/colormap.h>`

Collaboration diagram for ColorMap:

Public Member Functions

- ColorMap ()
- ~ColorMap ()
- ColorMap (const ColorMap &rhs)
- const ColorMap & operator= (const ColorMap &rhs)
- void init (const KeyMap &map)
- void clear ()
- int count () const
- const char ∗const ∗ keyNames () const
- QRgb ∗ colors ()
- const QRgb ∗ colors () const
- QRgb ∗ colorForName (const char ∗name)
- const QRgb ∗ colorForName (const char ∗name) const

Private Member Functions

- void alloc (int count)
- void deAlloc ()

Private Attributes

- const char ** _keyNames
- QRgb * _colors
- int _count
- int _mapCount

12.10.1 Detailed Description

Definition at line 15 of file colormap.h.

12.10.2 Constructor & Destructor Documentation

12.10.2.1 ColorMap::ColorMap ( )

Definition at line 3 of file colormap.cpp.

```
3                    :
4     _keyNames(0), _colors(0), _count(0), _mapCount(0)
5 {
6 }
```

12.10.2.2 ColorMap::~ColorMap ( )

Definition at line 8 of file colormap.cpp.

References deAlloc().

```
8                    {
9     deAlloc();
10 }
```

Here is the call graph for this function:

12.10.2.3 ColorMap::ColorMap (const ColorMap & *rhs*)

Definition at line 12 of file colormap.cpp.

```
12                                        :
13     _keyNames(0), _colors(0), _count(0), _mapCount(0)
14 {
15     *this = rhs;
16 }
```

12.10.3 Member Function Documentation

12.10.3.1 void ColorMap::alloc (int *count*) [private]

Definition at line 27 of file colormap.cpp.

References _colors, _count, _keyNames, _mapCount, clear(), and deAlloc().

Referenced by init(), and operator=().

```
27                                  {
28     if(newCount > _mapCount){
29         // ^ map never shrinks, only expands
30         deAlloc();
31         _mapCount = newCount;
32         _keyNames = new const char*[_mapCount];
33         _colors = new QRgb[_mapCount];
34     }
35     _count = newCount;
36     clear();
37 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.10.3.2 void ColorMap::clear ( )

Definition at line 45 of file colormap.cpp.

References _colors, and _count.

Referenced by alloc(), AnimScript::end(), and KbLight::resetIndicators().

```
45                          {
46     memset(_colors, 0, _count * sizeof(QRgb));
47 }
```

Here is the caller graph for this function:

12.10.3.3 QRgb ∗ ColorMap::colorForName (const char ∗ *name*)

Definition at line 72 of file colormap.cpp.

References _colors, _count, _keyNames, and qs_strcmp().

Referenced by KbLight::base(), KbLight::color(), KeyWidget::paintEvent(), AnimScript::readProcess(), KbLight::rebuildBaseMap(), and KbLight::setIndicator().

```
72                                                  {
73     if(!_keyNames)
74         return 0;
75     const char** namePtr = (const char**)bsearch(&name, _keyNames,
      _count, sizeof(const char*), qs_strcmp);
76     if(!namePtr)
77         return 0;
78     ptrdiff_t position = namePtr - _keyNames;
79     return _colors + position;
80 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.10.3.4 const QRgb * ColorMap::colorForName (const char * *name*) const

Definition at line 82 of file colormap.cpp.

References _colors, _count, _keyNames, and qs_strcmp().

```
82                                                          {
83     if(!_keyNames)
84         return 0;
85     const char** namePtr = (const char**)bsearch(&name, _keyNames,
      _count, sizeof(const char*), qs_strcmp);
86     if(!namePtr)
87         return 0;
88     ptrdiff_t position = namePtr - _keyNames;
89     return _colors + position;
90 }
```

Here is the call graph for this function:

12.10.3.5 QRgb* ColorMap::colors ( ) [inline]

Definition at line 32 of file colormap.h.

References _colors.

Referenced by KbLight::base(), KbAnim::blend(), KbLight::color(), KbLight::frameUpdate(), KbLight::printRGB(), and AnimScript::readProcess().

```
32 { return _colors; }
```

Here is the caller graph for this function:

12.10.3.6 const QRgb∗ ColorMap::colors ( ) const [inline]

Definition at line 33 of file colormap.h.

References _colors.

```
33 { return _colors; }
```

12.10.3.7 int ColorMap::count ( ) const [inline]

Definition at line 30 of file colormap.h.

References _count.

Referenced by KbLight::base(), KbAnim::blend(), KbLight::color(), KbLight::frameUpdate(), KbLight::printRGB(), and AnimScript::readProcess().

```
30 { return _count; }
```

Here is the caller graph for this function:

12.10.3.8 void ColorMap::deAlloc ( ) [private]

Definition at line 39 of file colormap.cpp.

References _colors, _count, _keyNames, and _mapCount.

Referenced by alloc(), and ∼ColorMap().

```
                        {
    _count = _mapCount = 0;
    if(_keyNames) delete[] _keyNames;
    if(_colors) delete[] _colors;
}
```

Here is the caller graph for this function:

12.10.3.9 void ColorMap::init (const KeyMap & *map*)

Definition at line 53 of file colormap.cpp.

References _count, _keyNames, alloc(), Key::hasLed, Key::name, KeyMap::positions(), and qs_strcmp().

Referenced by AnimScript::init(), and KbLight::map().

```
                                    {
    QList<Key> newKeys = map.positions();
    // There's no point including keys that don't have LEDs, so remove them now
    QMutableListIterator<Key> i(newKeys);
    while(i.hasNext()){
        Key key = i.next();
        if(!key.hasLed)
            i.remove();
    }
    // Now that we know how many keys we'll have, check memory
    alloc(newKeys.count());
    // Copy key names
    int keyPos = 0;
    foreach(const Key& key, newKeys)
        _keyNames[keyPos++] = key.name;     // as above, it's safe to copy these since the
strings are constants
    // Sort names for quick access
    qsort(_keyNames, _count, sizeof(const char*), qs_strcmp);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.10.3.10 const char* const* ColorMap::keyNames ( ) const [inline]

Definition at line 31 of file colormap.h.

References _keyNames.

Referenced by KbLight::printRGB().

```
31 { return _keyNames; }
```

Here is the caller graph for this function:

12.10.3.11 const ColorMap & ColorMap::operator= (const ColorMap & *rhs*)

Definition at line 18 of file colormap.cpp.

References _colors, _count, _keyNames, and alloc().

```
18                                                  {
19     alloc(rhs._count);
20     // Copy key names and colors
21     // (Note: it's safe to copy the const char*'s because key names are constants and will never move or be
       deleted)
22     memcpy(_keyNames, rhs._keyNames, sizeof(const char*) *
      _count);
23     memcpy(_colors, rhs._colors, sizeof(QRgb) * _count);
24     return rhs;
25 }
```

Here is the call graph for this function:

12.10.4 Field Documentation

12.10.4.1 QRgb* ColorMap::_colors [private]

Definition at line 44 of file colormap.h.

Referenced by alloc(), clear(), colorForName(), colors(), deAlloc(), and operator=().

12.10.4.2 int ColorMap::_count [private]

Definition at line 45 of file colormap.h.

Referenced by alloc(), clear(), colorForName(), count(), deAlloc(), init(), and operator=().

12.10.4.3 const char** ColorMap::_keyNames [private]

Definition at line 43 of file colormap.h.

Referenced by alloc(), colorForName(), deAlloc(), init(), keyNames(), and operator=().

12.10.4.4 int ColorMap::_mapCount [private]

Definition at line 45 of file colormap.h.

Referenced by alloc(), and deAlloc().

The documentation for this class was generated from the following files:

- src/ckb/colormap.h
- src/ckb/colormap.cpp

12.11 Ui::ExtraSettingsWidget Class Reference

```
#include <src/ckb/ui_extrasettingswidget.h>
```

Inheritance diagram for Ui::ExtraSettingsWidget:

Collaboration diagram for Ui::ExtraSettingsWidget:

Public Member Functions

- void setupUi (QDialog ∗ExtraSettingsWidget)
- void retranslateUi (QDialog ∗ExtraSettingsWidget)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QSpacerItem * verticalSpacer_2
- QLabel * fpsWarnLabel
- QSpacerItem * horizontalSpacer_3
- QLabel * label_3
- QSpinBox * fpsBox
- QSpacerItem * verticalSpacer_4
- QSpacerItem * verticalSpacer_9
- QLabel * label_6
- QSpacerItem * verticalSpacer_6
- QSpacerItem * verticalSpacer_5
- QCheckBox * sAccelBox
- QSpacerItem * verticalSpacer_7
- QSpacerItem * verticalSpacer_8
- QSpacerItem * verticalSpacer_10
- QSpacerItem * verticalSpacer_11
- QSpacerItem * horizontalSpacer
- QFrame * line_2
- QHBoxLayout * horizontalLayout
- QLabel * animPathLabel
- QLabel * animCountLabel
- QPushButton * animScanButton
- QCheckBox * brightnessBox
- QCheckBox * trayBox
- QLabel * label
- QFrame * line
- QLabel * label_5
- QFrame * line_3
- QLabel * label_2
- QCheckBox * ditherBox
- QCheckBox * delayBox
- QLabel * osxLabel
- QFrame * osxLine
- QCheckBox * mAccelBox
- QWidget * sSpeedWidget
- QHBoxLayout * horizontalLayout_2
- QLabel * label_10
- QSpinBox * sSpeedBox
- QLabel * label_11
- QDialogButtonBox * buttonBox

12.11.1 Detailed Description

Definition at line 366 of file ui_extrasettingswidget.h.

12.11.2 Member Function Documentation

12.11.2.1 void Ui_ExtraSettingsWidget::retranslateUi (QDialog * *ExtraSettingsWidget*) [inline],[inherited]

Definition at line 322 of file ui_extrasettingswidget.h.

References Ui_ExtraSettingsWidget::animCountLabel, Ui_ExtraSettingsWidget::animPathLabel, Ui_ExtraSettingsWidget::animScanButton, Ui_ExtraSettingsWidget::brightnessBox, Ui_ExtraSettingsWidget::delayBox, Ui_ExtraSettingsWidget::ditherBox, Ui_ExtraSettingsWidget::fpsWarnLabel, Ui_ExtraSettingsWidget::label, Ui_ExtraSettingsWidget::label_10, Ui_ExtraSettingsWidget::label_11, Ui_ExtraSettingsWidget::label_2, Ui_ExtraSettingsWidget::label_3, Ui_ExtraSettingsWidget::label_5, Ui_ExtraSettingsWidget::label_6, Ui_ExtraSettingsWidget::mAccelBox, Ui_ExtraSettingsWidget::osxLabel, Ui_ExtraSettingsWidget::sAccelBox, and Ui_ExtraSettingsWidget::trayBox.

Referenced by Ui_ExtraSettingsWidget::setupUi().

```
    {
        ExtraSettingsWidget->setWindowTitle(QApplication::translate("ExtraSettingsWidget", "Application Settings", Q_NULLPTR));
        fpsWarnLabel->setText(QApplication::translate("ExtraSettingsWidget", "Warning: high frame rates may cause stability issues", Q_NULLPTR));
        label_3->setText(QApplication::translate("ExtraSettingsWidget", "Frame rate (FPS):", Q_NULLPTR));
        label_6->setText(QApplication::translate("ExtraSettingsWidget", "Location:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        sAccelBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "Try this if you're having problems with the scroll wheel.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        sAccelBox->setText(QApplication::translate("ExtraSettingsWidget", "Disable scroll acceleration", Q_NULLPTR));
        animPathLabel->setText(QApplication::translate("ExtraSettingsWidget", "/path/to/animations", Q_NULLPTR));
        animCountLabel->setText(QApplication::translate("ExtraSettingsWidget", "0 animations found", Q_NULLPTR));
        animScanButton->setText(QApplication::translate("ExtraSettingsWidget", "Re-scan", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        brightnessBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "By default, the same brightness level will be applied to all profiles and all devices. Enable this to store it with the lighting mode instead.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        brightnessBox->setText(QApplication::translate("ExtraSettingsWidget", "Set brightness per-mode", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        trayBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "The tray icon will not be displayed. The application will still run in the background; re-launch the app to see the GUI again.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        trayBox->setText(QApplication::translate("ExtraSettingsWidget", "Hide tray icon", Q_NULLPTR));
        label->setText(QApplication::translate("ExtraSettingsWidget", "Behavior", Q_NULLPTR));
        label_5->setText(QApplication::translate("ExtraSettingsWidget", "Animation scripts", Q_NULLPTR));
        label_2->setText(QApplication::translate("ExtraSettingsWidget", "Hardware", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        ditherBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "May improve appearance on some keyboards.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        ditherBox->setText(QApplication::translate("ExtraSettingsWidget", "Use spatial dithering to simulate extra color resolution", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        delayBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "When using macros with strings longer than 25 chars, some OS may lose characters (e.g. Mint 17.2). Select to prevent that bug.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        delayBox->setText(QApplication::translate("ExtraSettingsWidget", "Use delay for very long macros", Q_NULLPTR));
        osxLabel->setText(QApplication::translate("ExtraSettingsWidget", "OS X tweaks", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        mAccelBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "Try this if you're having problems with mouse movement.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        mAccelBox->setText(QApplication::translate("ExtraSettingsWidget", "Disable mouse acceleration", Q_NULLPTR));
        label_10->setText(QApplication::translate("ExtraSettingsWidget", "Scroll", Q_NULLPTR));
        label_11->setText(QApplication::translate("ExtraSettingsWidget", "line(s) at a time", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.11.2.2 void Ui_ExtraSettingsWidget::setupUi (QDialog * *ExtraSettingsWidget*) [inline],[inherited]

Definition at line 78 of file ui_extrasettingswidget.h.

References Ui_ExtraSettingsWidget::animCountLabel, Ui_ExtraSettingsWidget::animPathLabel, Ui_ExtraSettingsWidget::animScanButton, Ui_ExtraSettingsWidget::brightnessBox, Ui_ExtraSettingsWidget::buttonBox, Ui_ExtraSettingsWidget::delayBox, Ui_ExtraSettingsWidget::ditherBox, Ui_ExtraSettingsWidget::fpsBox, Ui_ExtraSettingsWidget::fpsWarnLabel, Ui_ExtraSettingsWidget::gridLayout, Ui_ExtraSettingsWidget::horizontalLayout, Ui_ExtraSettingsWidget::horizontalLayout_2, Ui_ExtraSettingsWidget::horizontalSpacer, Ui_ExtraSettingsWidget::horizontalSpacer_2, Ui_ExtraSettingsWidget::horizontalSpacer_3, Ui_ExtraSettingsWidget::label, Ui_ExtraSettingsWidget::label_10, Ui_ExtraSettingsWidget::label_11, Ui_ExtraSettingsWidget::label_2, Ui_ExtraSettingsWidget::label_3, Ui_ExtraSettingsWidget::label_5, Ui_ExtraSettingsWidget::label_6, Ui_ExtraSettingsWidget::line, Ui_ExtraSettingsWidget::line_2, Ui_ExtraSettingsWidget::line_3, Ui_ExtraSettingsWidget::mAccelBox, Ui_ExtraSettingsWidget::osxLabel, Ui_ExtraSettingsWidget::osxLine, Ui_ExtraSettingsWidget::retranslateUi(), Ui_ExtraSettingsWidget::sAccelBox, Ui_ExtraSettingsWidget::sSpeedBox, Ui_ExtraSettingsWidget::sSpeedWidget, Ui_ExtraSettingsWidget::trayBox, Ui_ExtraSettingsWidget::verticalSpacer, Ui_ExtraSettingsWidget::verticalSpacer_10, Ui_ExtraSettingsWidget::verticalSpacer_11, Ui_ExtraSettingsWidget::verticalSpacer_2, Ui_ExtraSettingsWidget::verticalSpacer_3, Ui_ExtraSettingsWidget::verticalSpacer_4, Ui_ExtraSettingsWidget::verticalSpacer_5, Ui_ExtraSettingsWidget::verticalSpacer_6, Ui_ExtraSettingsWidget::verticalSpacer_7, Ui_ExtraSettingsWidget::verticalSpacer_8, and Ui_ExtraSettingsWidget::verticalSpacer_9.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget().

```
79     {
80         if (ExtraSettingsWidget->objectName().isEmpty())
81             ExtraSettingsWidget->setObjectName(QStringLiteral("ExtraSettingsWidget"));
82         ExtraSettingsWidget->resize(650, 515);
83         gridLayout = new QGridLayout(ExtraSettingsWidget);
84         gridLayout->setObjectName(QStringLiteral("gridLayout"));
85         horizontalSpacer_2 = new QSpacerItem(30, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);
86
87         gridLayout->addItem(horizontalSpacer_2, 12, 2, 1, 1);
88
89         verticalSpacer = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);
90
91         gridLayout->addItem(verticalSpacer, 2, 0, 1, 1);
92
93         verticalSpacer_3 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed)
    ;
94
95         gridLayout->addItem(verticalSpacer_3, 3, 0, 1, 1);
96
97         verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);
98
99         gridLayout->addItem(verticalSpacer_2, 19, 5, 1, 1);
100
101         fpsWarnLabel = new QLabel(ExtraSettingsWidget);
102         fpsWarnLabel->setObjectName(QStringLiteral("fpsWarnLabel"));
103         QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
104         sizePolicy.setHorizontalStretch(0);
105         sizePolicy.setVerticalStretch(0);
106         sizePolicy.setHeightForWidth(fpsWarnLabel->sizePolicy().hasHeightForWidth());
107         fpsWarnLabel->setSizePolicy(sizePolicy);
108
109         gridLayout->addWidget(fpsWarnLabel, 12, 5, 1, 1);
110
111         horizontalSpacer_3 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
```

```
QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_3, 12, 4, 1, 1);

        label_3 = new QLabel(ExtraSettingsWidget);
        label_3->setObjectName(QStringLiteral("label_3"));

        gridLayout->addWidget(label_3, 12, 1, 1, 1);

        fpsBox = new QSpinBox(ExtraSettingsWidget);
        fpsBox->setObjectName(QStringLiteral("fpsBox"));
        fpsBox->setMinimum(5);
        fpsBox->setMaximum(60);
        fpsBox->setValue(30);

        gridLayout->addWidget(fpsBox, 12, 3, 1, 1);

        verticalSpacer_4 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_4, 7, 0, 1, 1);

        verticalSpacer_9 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_9, 12, 0, 1, 1);

        label_6 = new QLabel(ExtraSettingsWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 7, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_6, 8, 1, 1, 1);

        verticalSpacer_5 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_5, 4, 1, 1, 1);

        sAccelBox = new QCheckBox(ExtraSettingsWidget);
        sAccelBox->setObjectName(QStringLiteral("sAccelBox"));

        gridLayout->addWidget(sAccelBox, 18, 1, 1, 4);

        verticalSpacer_7 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_7, 14, 1, 1, 1);

        verticalSpacer_8 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 13, 0, 1, 1);

        verticalSpacer_10 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_10, 17, 0, 1, 1);

        verticalSpacer_11 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_11, 18, 0, 1, 1);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 12, 6, 1, 1);

        line_2 = new QFrame(ExtraSettingsWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 10, 0, 1, 7);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        animPathLabel = new QLabel(ExtraSettingsWidget);
        animPathLabel->setObjectName(QStringLiteral("animPathLabel"));

        horizontalLayout->addWidget(animPathLabel);

        animCountLabel = new QLabel(ExtraSettingsWidget);
```

```
        animCountLabel->setObjectName(QStringLiteral("animCountLabel"));
        sizePolicy.setHeightForWidth(animCountLabel->sizePolicy().hasHeightForWidth());
        animCountLabel->setSizePolicy(sizePolicy);
        animCountLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        horizontalLayout->addWidget(animCountLabel);

        animScanButton = new QPushButton(ExtraSettingsWidget);
        animScanButton->setObjectName(QStringLiteral("animScanButton"));

        horizontalLayout->addWidget(animScanButton);


        gridLayout->addLayout(horizontalLayout, 7, 3, 1, 4);

        brightnessBox = new QCheckBox(ExtraSettingsWidget);
        brightnessBox->setObjectName(QStringLiteral("brightnessBox"));

        gridLayout->addWidget(brightnessBox, 3, 1, 1, 6);

        trayBox = new QCheckBox(ExtraSettingsWidget);
        trayBox->setObjectName(QStringLiteral("trayBox"));

        gridLayout->addWidget(trayBox, 2, 1, 1, 6);

        label = new QLabel(ExtraSettingsWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        gridLayout->addWidget(label, 0, 0, 1, 7);

        line = new QFrame(ExtraSettingsWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 1, 0, 1, 7);

        label_5 = new QLabel(ExtraSettingsWidget);
        label_5->setObjectName(QStringLiteral("label_5"));
        label_5->setFont(font);

        gridLayout->addWidget(label_5, 5, 0, 1, 7);

        line_3 = new QFrame(ExtraSettingsWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 6, 0, 1, 7);

        label_2 = new QLabel(ExtraSettingsWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        gridLayout->addWidget(label_2, 9, 0, 1, 7);

        ditherBox = new QCheckBox(ExtraSettingsWidget);
        ditherBox->setObjectName(QStringLiteral("ditherBox"));

        gridLayout->addWidget(ditherBox, 13, 1, 1, 6);

        delayBox = new QCheckBox(ExtraSettingsWidget);
        delayBox->setObjectName(QStringLiteral("delayBox"));

        gridLayout->addWidget(delayBox, 14, 1, 1, 6);

        osxLabel = new QLabel(ExtraSettingsWidget);
        osxLabel->setObjectName(QStringLiteral("osxLabel"));
        osxLabel->setFont(font);

        gridLayout->addWidget(osxLabel, 15, 0, 1, 7);

        osxLine = new QFrame(ExtraSettingsWidget);
        osxLine->setObjectName(QStringLiteral("osxLine"));
        osxLine->setFrameShape(QFrame::HLine);
        osxLine->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(osxLine, 16, 0, 1, 7);

        mAccelBox = new QCheckBox(ExtraSettingsWidget);
        mAccelBox->setObjectName(QStringLiteral("mAccelBox"));

        gridLayout->addWidget(mAccelBox, 17, 1, 1, 6);
```

```

        sSpeedWidget = new QWidget(ExtraSettingsWidget);
        sSpeedWidget->setObjectName(QStringLiteral("sSpeedWidget"));
        sizePolicy.setHeightForWidth(sSpeedWidget->sizePolicy().hasHeightForWidth());
        sSpeedWidget->setSizePolicy(sizePolicy);
        horizontalLayout_2 = new QHBoxLayout(sSpeedWidget);
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        horizontalLayout_2->setContentsMargins(0, 0, 0, 0);
        label_10 = new QLabel(sSpeedWidget);
        label_10->setObjectName(QStringLiteral("label_10"));

        horizontalLayout_2->addWidget(label_10);

        sSpeedBox = new QSpinBox(sSpeedWidget);
        sSpeedBox->setObjectName(QStringLiteral("sSpeedBox"));
        sSpeedBox->setMinimum(1);
        sSpeedBox->setMaximum(10);
        sSpeedBox->setValue(3);

        horizontalLayout_2->addWidget(sSpeedBox);

        label_11 = new QLabel(sSpeedWidget);
        label_11->setObjectName(QStringLiteral("label_11"));
        sizePolicy.setHeightForWidth(label_11->sizePolicy().hasHeightForWidth());
        label_11->setSizePolicy(sizePolicy);

        horizontalLayout_2->addWidget(label_11);


        gridLayout->addWidget(sSpeedWidget, 18, 5, 1, 2);

        buttonBox = new QDialogButtonBox(ExtraSettingsWidget);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Ok);

        gridLayout->addWidget(buttonBox, 20, 0, 1, 7);


        retranslateUi(ExtraSettingsWidget);
        QObject::connect(buttonBox, SIGNAL(accepted()), ExtraSettingsWidget, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), ExtraSettingsWidget, SLOT(reject()));

        QMetaObject::connectSlotsByName(ExtraSettingsWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.11.3 Field Documentation

12.11.3.1 QLabel* Ui_ExtraSettingsWidget::animCountLabel [inherited]

Definition at line 57 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::on_animScanButton_clicked(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.2 QLabel* Ui_ExtraSettingsWidget::animPathLabel [inherited]

Definition at line 56 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.3 QPushButton* Ui_ExtraSettingsWidget::animScanButton [inherited]

Definition at line 58 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.4 QCheckBox* Ui_ExtraSettingsWidget::brightnessBox [inherited]

Definition at line 59 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.5 QDialogButtonBox* Ui_ExtraSettingsWidget::buttonBox [inherited]

Definition at line 76 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.6 QCheckBox* Ui_ExtraSettingsWidget::delayBox [inherited]

Definition at line 67 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.7 QCheckBox* Ui_ExtraSettingsWidget::ditherBox [inherited]

Definition at line 66 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.8 QSpinBox* Ui_ExtraSettingsWidget::fpsBox [inherited]

Definition at line 42 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.9 QLabel* Ui_ExtraSettingsWidget::fpsWarnLabel [inherited]

Definition at line 39 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_fpsBox_valueChanged(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.10 QGridLayout* Ui_ExtraSettingsWidget::gridLayout [inherited]

Definition at line 34 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.11 QHBoxLayout* Ui_ExtraSettingsWidget::horizontalLayout [inherited]

Definition at line 55 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.12 QHBoxLayout* Ui_ExtraSettingsWidget::horizontalLayout_2 [inherited]

Definition at line 72 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.13 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer [inherited]

Definition at line 53 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.14 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer_2 [inherited]

Definition at line 35 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.15 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer_3 [inherited]

Definition at line 40 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.16 QLabel* Ui_ExtraSettingsWidget::label [inherited]

Definition at line 61 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.17 QLabel* Ui_ExtraSettingsWidget::label_10 [inherited]

Definition at line 73 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.18 QLabel* Ui_ExtraSettingsWidget::label_11 [inherited]

Definition at line 75 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.19 QLabel* Ui_ExtraSettingsWidget::label_2 [inherited]

Definition at line 65 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.20 QLabel* Ui_ExtraSettingsWidget::label_3 [inherited]

Definition at line 41 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.21 QLabel* Ui_ExtraSettingsWidget::label_5 [inherited]

Definition at line 63 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.22 QLabel* Ui_ExtraSettingsWidget::label_6 [inherited]

Definition at line 45 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.23 QFrame* Ui_ExtraSettingsWidget::line [inherited]

Definition at line 62 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.24 QFrame* Ui_ExtraSettingsWidget::line_2 [inherited]

Definition at line 54 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.25 QFrame* Ui_ExtraSettingsWidget::line_3 [inherited]

Definition at line 64 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.26 QCheckBox* Ui_ExtraSettingsWidget::mAccelBox [inherited]

Definition at line 70 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.27 QLabel* Ui_ExtraSettingsWidget::osxLabel [inherited]

Definition at line 68 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.28 QFrame* Ui_ExtraSettingsWidget::osxLine [inherited]

Definition at line 69 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.29 QCheckBox* Ui_ExtraSettingsWidget::sAccelBox [inherited]

Definition at line 48 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sSpeedBox_valueChanged(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.30 QSpinBox* Ui_ExtraSettingsWidget::sSpeedBox [inherited]

Definition at line 74 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sAccelBox_clicked(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.31 QWidget* Ui_ExtraSettingsWidget::sSpeedWidget [inherited]

Definition at line 71 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sAccelBox_clicked(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.32 QCheckBox* Ui_ExtraSettingsWidget::trayBox [inherited]

Definition at line 60 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), Ui_ExtraSettingsWidget::retranslateUi(), and Ui_ExtraSettingsWidget::setupUi().

12.11.3.33 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer [inherited]

Definition at line 36 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.34 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_10 [inherited]

Definition at line 51 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.35 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_11 [inherited]

Definition at line 52 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.36 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_2 [inherited]

Definition at line 38 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.37 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_3 [inherited]

Definition at line 37 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.38 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_4 [inherited]

Definition at line 43 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.39 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_5 [inherited]

Definition at line 47 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.40 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_6 [inherited]

Definition at line 46 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.41 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_7 [inherited]

Definition at line 49 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.42 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_8 [inherited]

Definition at line 50 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

12.11.3.43 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_9 [inherited]

Definition at line 44 of file ui_extrasettingswidget.h.

Referenced by Ui_ExtraSettingsWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_extrasettingswidget.h

12.12 ExtraSettingsWidget Class Reference

```
#include <src/ckb/extrasettingswidget.h>
```

Inheritance diagram for ExtraSettingsWidget:

Collaboration diagram for ExtraSettingsWidget:

Public Member Functions

- ExtraSettingsWidget (QWidget *parent=0)
- ~ExtraSettingsWidget ()
- void pollUpdates ()

Private Slots

- void on_trayBox_clicked (bool checked)
- void on_brightnessBox_clicked (bool checked)
- void on_animScanButton_clicked ()
- void on_fpsBox_valueChanged (int arg1)
- void on_ditherBox_clicked (bool checked)
- void on_mAccelBox_clicked (bool checked)
- void on_sAccelBox_clicked (bool checked)
- void on_sSpeedBox_valueChanged (int arg1)
- void on_delayBox_clicked (bool checked)

Private Attributes

- Ui::ExtraSettingsWidget * ui

12.12.1 Detailed Description

Definition at line 10 of file extrasettingswidget.h.

12.12.2 Constructor & Destructor Documentation

12.12.2.1 ExtraSettingsWidget::ExtraSettingsWidget (QWidget * *parent* = 0) [explicit]

Read Macro Delay setting, update UI and Kb-internal flag

Definition at line 10 of file extrasettingswidget.cpp.

References Ui_ExtraSettingsWidget::animPathLabel, Ui_ExtraSettingsWidget::brightnessBox, Ui_ExtraSettingsWidget::delayBox, Kb::dither(), Ui_ExtraSettingsWidget::ditherBox, Ui_ExtraSettingsWidget::fpsBox, Ui_ExtraSettingsWidget::fpsWarnLabel, Kb::frameRate(), lastSharedDimming, Ui_ExtraSettingsWidget::mAccelBox, Kb::macroDelay(), KbLight::MAX_DIM, Kb::mouseAccel(), on_animScanButton_clicked(), Ui_ExtraSettingsWidget::osxLabel, Ui_ExtraSettingsWidget::osxLine, AnimScript::path(), Ui_ExtraSettingsWidget::sAccelBox, Kb::scrollSpeed(), Ui_ExtraSettingsWidget::setupUi(), KbLight::shareDimming(), Ui_ExtraSettingsWidget::sSpeedBox, Ui_ExtraSettingsWidget::sSpeedWidget, Ui_ExtraSettingsWidget::trayBox, ui, and CkbSettings::value().

```
10                                                          :
11     QDialog(parent),
12     ui(new Ui::ExtraSettingsWidget)
13 {
14     ui->setupUi(this);
15     CkbSettings settings("Program");
16
17     // Read frame rate from settings
18     int rate = settings.value("framerate").toInt();
19     if(rate <= 0 || rate > 60)
20         rate = 30;
21     ui->fpsBox->setValue(rate);
22     Kb::frameRate(rate);
23     ui->fpsWarnLabel->setVisible(rate > 30);
24
25     // Read global brightness setting (default = on, 100% brightness)
26     int dimming = settings.value("GlobalBrightness").toInt();
27     if(dimming < -1 || dimming > KbLight::MAX_DIM)
28         dimming = 0;
29     lastSharedDimming = dimming;
30     KbLight::shareDimming(dimming);
31     // Set checkbox value (-1 = don't share)
32     ui->brightnessBox->setChecked(dimming == -1);
33
34     // Read dither
35     bool dither = settings.value("Dither").toBool();
36     Kb::dither(dither);
37     ui->ditherBox->setChecked(dither);
38
39 #ifdef Q_OS_MACX
40     // Read OSX settings
41     bool noAccel = settings.value("DisableMouseAccel").toBool();
42     Kb::mouseAccel(!noAccel);
43     ui->mAccelBox->setChecked(noAccel);
44     bool noScrollAccel = settings.value("DisableScrollAccel").toBool();
45     int scrollSpeed = settings.value("ScrollSpeed", 3).toInt();
46     ui->sAccelBox->setChecked(noScrollAccel);
47     ui->sSpeedBox->setValue(scrollSpeed);
48     Kb::scrollSpeed(noScrollAccel ? scrollSpeed : 0);
49     if(!noScrollAccel)
50         ui->sSpeedWidget->hide();
51 #else
52     // Hide all OSX options on Linux
53     ui->osxLabel->hide();
54     ui->osxLine->hide();
55     ui->mAccelBox->hide();
56     ui->sAccelBox->hide();
57     ui->sSpeedWidget->hide();
58 #endif
59
60     // Read tray icon setting
61     ui->trayBox->setChecked(settings.value("SuppressTrayIcon").toBool());
62
63     // Update animation info
64     ui->animPathLabel->setText(AnimScript::path());
65     on_animScanButton_clicked();
66
68     bool macroDelay = settings.value("MacroDelay").toBool();
69     Kb::macroDelay(macroDelay);
70     ui->delayBox->setChecked(macroDelay);
71 }
```

Here is the call graph for this function:

12.12.2.2 ExtraSettingsWidget::~ExtraSettingsWidget ( )

Definition at line 73 of file extrasettingswidget.cpp.

References ui.

```
73                                          {
74     delete ui;
75 }
```

12.12.3 Member Function Documentation

12.12.3.1 void ExtraSettingsWidget::on_animScanButton_clicked ( ) [private], [slot]

Definition at line 87 of file extrasettingswidget.cpp.

References Ui_ExtraSettingsWidget::animCountLabel, AnimScript::count(), AnimScript::scan(), and ui.

Referenced by ExtraSettingsWidget().

```
87                                                  {
88     AnimScript::scan();
89     int count = AnimScript::count();
90     if(count == 0)
91         ui->animCountLabel->setText("No animations found");
92     else if(count == 1)
93         ui->animCountLabel->setText("1 animation found");
94     else
95         ui->animCountLabel->setText(QString("%1 animations found").arg(count));
96 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.12.3.2 void ExtraSettingsWidget::on_brightnessBox_clicked (bool *checked*) [private],[slot]

Definition at line 82 of file extrasettingswidget.cpp.

References pollUpdates(), and KbLight::shareDimming().

```
82                                                          {
83     KbLight::shareDimming(checked ? -1 : 0);
84     pollUpdates();
85 }
```

Here is the call graph for this function:

12.12.3.3 void ExtraSettingsWidget::on_delayBox_clicked (bool *checked*) [private],[slot]

Definition at line 143 of file extrasettingswidget.cpp.

References Kb::macroDelay(), and CkbSettings::set().

```
143                                                         {
144     CkbSettings::set("Program/MacroDelay", checked);
145     Kb::macroDelay(checked);
146 }
```

Here is the call graph for this function:

12.12.3.4 void ExtraSettingsWidget::on_ditherBox_clicked (bool *checked*) [private],[slot]

Definition at line 110 of file extrasettingswidget.cpp.

References Kb::dither(), and CkbSettings::set().

```
110                                                     {
111     CkbSettings::set("Program/Dither", checked);
112     Kb::dither(checked);
113 }
```

Here is the call graph for this function:

12.12.3.5 void ExtraSettingsWidget::on_fpsBox_valueChanged (int *arg1*) [private],[slot]

Definition at line 98 of file extrasettingswidget.cpp.

References Ui_ExtraSettingsWidget::fpsWarnLabel, Kb::frameRate(), CkbSettings::setValue(), and ui.

```
98                                                      {
99     // Set FPS
100     CkbSettings settings("Program");
101     settings.setValue("framerate", arg1);
102     Kb::frameRate(arg1);
103     // Show warning label if FPS is above 30
104     if(arg1 > 30)
105         ui->fpsWarnLabel->show();
106     else
107         ui->fpsWarnLabel->hide();
108 }
```

Here is the call graph for this function:

12.12.3.6 void ExtraSettingsWidget::on_mAccelBox_clicked (bool *checked*) [private],[slot]

Definition at line 124 of file extrasettingswidget.cpp.

References Kb::mouseAccel(), and CkbSettings::set().

```
124                                                     {
125     CkbSettings::set("Program/DisableMouseAccel", checked);
126     Kb::mouseAccel(!checked);
127 }
```

Here is the call graph for this function:

12.12.3.7 void ExtraSettingsWidget::on_sAccelBox_clicked (bool *checked*) [private],[slot]

Definition at line 129 of file extrasettingswidget.cpp.

References Kb::scrollSpeed(), CkbSettings::set(), Ui_ExtraSettingsWidget::sSpeedBox, Ui_ExtraSettingsWidget::sSpeedWidget, and ui.

```
129                                                         {
130     CkbSettings::set("Program/DisableScrollAccel", checked);
131     Kb::scrollSpeed(checked ? ui->sSpeedBox->value() : 0);
132     if(checked)
133         ui->sSpeedWidget->show();
134     else
135         ui->sSpeedWidget->hide();
136 }
```

Here is the call graph for this function:

12.12.3.8 void ExtraSettingsWidget::on_sSpeedBox_valueChanged (int *arg1*) [private],[slot]

Definition at line 138 of file extrasettingswidget.cpp.

References Ui_ExtraSettingsWidget::sAccelBox, Kb::scrollSpeed(), CkbSettings::set(), and ui.

```
138                                                         {
139     CkbSettings::set("Program/ScrollSpeed", arg1);
140     Kb::scrollSpeed(ui->sAccelBox->isChecked() ? arg1 : 0);
141 }
```

Here is the call graph for this function:

12.12.3.9 void ExtraSettingsWidget::on_trayBox_clicked (bool *checked*) [private],[slot]

Definition at line 77 of file extrasettingswidget.cpp.

References MainWindow::mainWindow, CkbSettings::set(), and MainWindow::toggleTrayIcon().

```
77                                                  {
78     CkbSettings::set("Program/SuppressTrayIcon", checked);
79     MainWindow::mainWindow->toggleTrayIcon(!checked);
80 }
```

Here is the call graph for this function:

12.12.3.10 void ExtraSettingsWidget::pollUpdates ( )

Definition at line 115 of file extrasettingswidget.cpp.

References CkbSettings::isBusy(), lastSharedDimming, CkbSettings::set(), and KbLight::shareDimming().

Referenced by on_brightnessBox_clicked(), and SettingsWidget::pollUpdates().

```
115                                     {
116     // Check for changes to shared brightness setting
117     int dimming = KbLight::shareDimming();
118     if(dimming != lastSharedDimming && !CkbSettings::isBusy()){
119         CkbSettings::set("Program/GlobalBrightness", dimming);
120         lastSharedDimming = dimming;
121     }
122 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.12.4 Field Documentation

12.12.4.1 Ui::ExtraSettingsWidget* ExtraSettingsWidget::ui [private]

Definition at line 33 of file extrasettingswidget.h.

Referenced by ExtraSettingsWidget(), on_animScanButton_clicked(), on_fpsBox_valueChanged(), on_sAccelBox_clicked(), on_sSpeedBox_valueChanged(), and ~ExtraSettingsWidget().

The documentation for this class was generated from the following files:

- src/ckb/extrasettingswidget.h
- src/ckb/extrasettingswidget.cpp

12.13 KbFirmware::FW Struct Reference

Collaboration diagram for KbFirmware::FW:

Public Member Functions

- FW ()

Data Fields

- QString url
- QString fileName
- QByteArray hash
- float fwVersion
- float ckbVersion

12.13.1 Detailed Description

Definition at line 34 of file kbfirmware.h.

12.13.2 Constructor & Destructor Documentation

12.13.2.1 KbFirmware::FW::FW ( )

Definition at line 12 of file kbfirmware.cpp.

```
12 : fwVersion(0.f), ckbVersion(0.f) {}
```

12.13.3 Field Documentation

12.13.3.1 float KbFirmware::FW::ckbVersion

Definition at line 37 of file kbfirmware.h.

Referenced by KbFirmware::_latestForBoard(), and KbFirmware::processDownload().

12.13.3.2 QString KbFirmware::FW::fileName

Definition at line 35 of file kbfirmware.h.

Referenced by KbFirmware::_fileForBoard(), and KbFirmware::processDownload().

12.13.3.3 float KbFirmware::FW::fwVersion

Definition at line 37 of file kbfirmware.h.

Referenced by KbFirmware::_latestForBoard(), and KbFirmware::processDownload().

12.13.3.4 QByteArray KbFirmware::FW::hash

Definition at line 36 of file kbfirmware.h.

Referenced by KbFirmware::_fileForBoard(), KbFirmware::_latestForBoard(), and KbFirmware::processDownload().

12.13.3.5 QString KbFirmware::FW::url

Definition at line 35 of file kbfirmware.h.

Referenced by KbFirmware::_fileForBoard(), and KbFirmware::processDownload().

The documentation for this struct was generated from the following files:

- src/ckb/kbfirmware.h
- src/ckb/kbfirmware.cpp

12.14 FwUpgradeDialog Class Reference

```
#include <src/ckb/fwupgradedialog.h>
```

Inheritance diagram for FwUpgradeDialog:

Collaboration diagram for FwUpgradeDialog:

Public Member Functions

- FwUpgradeDialog (QWidget *parent, float newV, const QByteArray &fwBlob, Kb *device)
- ~FwUpgradeDialog ()
- int exec ()

Private Slots

- void fwUpdateProgress (int current, int total)
- void fwUpdateFinished (bool succeeded)
- void removeDev ()
- void on_cancelButton_clicked ()
- void on_actionButton_clicked ()

Private Member Functions

- void closeEvent (QCloseEvent *event)
- const QString & saveBlob ()
- void cleanBlob ()

Private Attributes

- Ui::FwUpgradeDialog * ui
- QString savePath
- QByteArray blob
- Kb * kb
- QEventLoop * evLoop
- bool exitSuccess

12.14.1 Detailed Description

Definition at line 13 of file fwupgradedialog.h.

12.14.2 Constructor & Destructor Documentation

12.14.2.1 FwUpgradeDialog::FwUpgradeDialog (QWidget * *parent*, float *newV*, const QByteArray & *fwBlob*, Kb * *device*)

Definition at line 31 of file fwupgradedialog.cpp.

References Ui_FwUpgradeDialog::curLabel, Ui_FwUpgradeDialog::devLabel, DIALOG_HEIGHT_MIN, DIALOG_WIDTH, Kb::firmware, fwUpdateFinished(), fwUpdateProgress(), kb, Ui_FwUpgradeDialog::newLabel, removeDev(), Ui_FwUpgradeDialog::setupUi(), ui, and Kb::usbModel.

```
31                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                :
32     QDialog(parent),
33     ui(new Ui::FwUpgradeDialog),
34     blob(fwBlob), kb(device), evLoop(0), exitSuccess(true)
35 {
36     ui->setupUi(this);
37     ui->curLabel->setText(kb->firmware);
38     ui->newLabel->setText(QString::number(newV, 'f', 2));
39     ui->devLabel->setText(kb->usbModel);
40
41     connect(device, SIGNAL(destroyed()), this, SLOT(removeDev()));
42     connect(device, SIGNAL(fwUpdateProgress(int,int)), this, SLOT(
       fwUpdateProgress(int,int)));
43     connect(device, SIGNAL(fwUpdateFinished(bool)), this, SLOT(
       fwUpdateFinished(bool)));
44
45     setFixedSize(DIALOG_WIDTH, DIALOG_HEIGHT_MIN);
46 }
```

Here is the call graph for this function:

12.14.2.2 FwUpgradeDialog::~FwUpgradeDialog ( )

Definition at line 48 of file fwupgradedialog.cpp.

References cleanBlob(), and ui.

```
48                                  {
49     cleanBlob();
50     delete ui;
51 }
```

Here is the call graph for this function:

12.14.3 Member Function Documentation

12.14.3.1 void FwUpgradeDialog::cleanBlob ( ) [private]

Definition at line 77 of file fwupgradedialog.cpp.

References savePath.

Referenced by fwUpdateFinished(), and ~FwUpgradeDialog().

```
77                                  {
78     if(savePath.isEmpty())
79         return;
80     QFile(savePath).remove();
81     savePath = "";
82 }
```

Here is the caller graph for this function:

12.14.3.2 void FwUpgradeDialog::closeEvent (QCloseEvent * *event*) [private]

Definition at line 53 of file fwupgradedialog.cpp.

```
53                                                  {
54     event->ignore();
55 }
```

12.14.3.3 int FwUpgradeDialog::exec ( )

Definition at line 107 of file fwupgradedialog.cpp.

References Ui_FwUpgradeDialog::actionButton, blob, Ui_FwUpgradeDialog::cancelButton, KbFirmware::dataForBoard(), DIALOG_HEIGHT_MAX(), DIALOG_WIDTH, evLoop, exitSuccess, Kb::features, kb, Ui_FwUpgradeDialog::newLabel, Ui_FwUpgradeDialog::progressBar, saveBlob(), Ui_FwUpgradeDialog::statusLabel, ui, and verifyFw().

Referenced by KbWidget::on_fwUpdButton_clicked().

```
107                         {
108     QString features = kb->features;
109     if(!blob.isEmpty()){
110         // If a blob was already specified, check its version and validity
111         float newV = verifyFw(blob, features);
112         if(newV == 0.f){
113             QMessageBox::warning(parentWidget(), "Error", "<center>Not a valid firmware for this
        device.</center>");
114             return QDialog::Rejected;
115         }
116         ui->newLabel->setText(QString::number(newV, 'f', 2));
117     } else {
118         // Download a new blob file
119         ui->progressBar->show();
120         ui->cancelButton->setEnabled(false);
121         ui->actionButton->setEnabled(false);
122         show();
123         // This can take a while
124         blob = KbFirmware::dataForBoard(features);
125         // Check validity
126         float newV = verifyFw(blob, features);
127         if(newV == 0.f){
128             hide();
129             QMessageBox::warning(parentWidget(), "Error", "<center>There was a problem with the downloaded
        file.<br />Please try again later.</center>");
130             return QDialog::Rejected;
131         }
132     }
133     // Save temporary file
134     if(saveBlob().isEmpty()){
135         hide();
136         QMessageBox::warning(parentWidget(), "Error", "<center>Unable to save temporary file.</center>");
137         return QDialog::Rejected;
138     }
139     // Set up UI
140     ui->progressBar->setValue(0);
141     ui->progressBar->setMaximum(1);
142     ui->progressBar->setTextVisible(false);
143     ui->statusLabel->setText("Ready to install new firmware.<br /><br /><b>Disclaimer:</b> ckb
        is not endorsed by Corsair. This is <i>unlikely</i> to brick your device, but I accept no responsibility if
        it does. If you're paranoid, update from Windows.");
144     ui->cancelButton->setEnabled(true);
145     ui->actionButton->setEnabled(true);
146     setFixedSize(DIALOG_WIDTH, DIALOG_HEIGHT_MAX);
147     show();
148     // Run modal event loop
149     evLoop = new QEventLoop(this);
150     evLoop->exec();
151     delete evLoop;
152     hide();
153     return exitSuccess ? QDialog::Accepted : QDialog::Rejected;
154 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.14.3.4 void FwUpgradeDialog::fwUpdateFinished (bool *succeeded*) [private],[slot]

Definition at line 170 of file fwupgradedialog.cpp.

References Ui_FwUpgradeDialog::actionButton, cleanBlob(), evLoop, Ui_FwUpgradeDialog::progressBar, Ui_FwUpgradeDialog::statusLabel, and ui.

Referenced by FwUpgradeDialog(), and removeDev().

```
170                                                 {
171     cleanBlob();
172     if(succeeded)
173         ui->statusLabel->setText("Update successful!");
174     else
175         ui->statusLabel->setText("Update failed.");
176     ui->actionButton->setText("OK");
177     ui->actionButton->setEnabled(true);
178     ui->progressBar->setMaximum(1);
179     ui->progressBar->setValue(1);
180     // Exit after 10s
181     if(evLoop)
182         QTimer::singleShot(10000, evLoop, SLOT(quit()));
183 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.14.3.5 void FwUpgradeDialog::fwUpdateProgress (int *current*, int *total*) [private],[slot]

Definition at line 163 of file fwupgradedialog.cpp.

References Ui_FwUpgradeDialog::progressBar, and ui.

Referenced by FwUpgradeDialog().

```
163                                                         {
164     if(current > 0 && total > 0){
165         ui->progressBar->setMaximum(total);
166         ui->progressBar->setValue(current);
167     }
168 }
```

Here is the caller graph for this function:

12.14.3.6 void FwUpgradeDialog::on_actionButton_clicked ( ) [private],[slot]

Definition at line 191 of file fwupgradedialog.cpp.

References Ui_FwUpgradeDialog::actionButton, Ui_FwUpgradeDialog::cancelButton, DIALOG_HEIGHT_MIN, DIALOG_WIDTH, evLoop, Kb::fwUpdate(), kb, Ui_FwUpgradeDialog::progressBar, savePath, Ui_FwUpgradeDialog::statusLabel, and ui.

```
191                                             {
192     if(!savePath.isEmpty() && kb){
193         // Start upgrade
194         setFixedSize(DIALOG_WIDTH, DIALOG_HEIGHT_MIN);
195         ui->progressBar->show();
196         ui->progressBar->setValue(0);
197         ui->progressBar->setMaximum(0);
198         ui->progressBar->setTextVisible(true);
199         ui->cancelButton->hide();
200         ui->actionButton->setEnabled(false);
201         ui->actionButton->setText("Please wait");
202         ui->statusLabel->setText("Installing firmware...");
203         kb->fwUpdate(savePath);
204     } else {
205         // Finished, close dialog.
206         if(evLoop)
207             evLoop->quit();
208     }
209 }
```

Here is the call graph for this function:

12.14.3.7 void FwUpgradeDialog::on_cancelButton_clicked ( ) [private],[slot]

Definition at line 185 of file fwupgradedialog.cpp.

References evLoop, and exitSuccess.

```
185                                                 {
186     exitSuccess = false;
187     if(evLoop)
188         evLoop->quit();
189 }
```

12.14.3.8 void FwUpgradeDialog::removeDev ( ) [private],[slot]

Definition at line 156 of file fwupgradedialog.cpp.

References fwUpdateFinished(), kb, and savePath.

Referenced by FwUpgradeDialog().

```
156                                 {
157     kb = 0;
158     // Assume success if upgrade in progress
159     if(!savePath.isEmpty())
160         fwUpdateFinished(true);
161 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.14.3.9 const QString & FwUpgradeDialog::saveBlob ( ) [private]

Definition at line 57 of file fwupgradedialog.cpp.

References blob, and savePath.

Referenced by exec().

```
57                                          {
58     if(!savePath.isEmpty())
59         return savePath;
60     QDir tmp = QDir::temp();
61     qint64 pid = QCoreApplication::applicationPid();
62     QString path = tmp.absoluteFilePath(QString("ckb-%1-fwblob.bin").arg(pid));
63     QFile output(path);
64     if(!output.open(QIODevice::WriteOnly)){
65         return savePath;
66     }
67     if(!output.write(blob)){
68         output.close();
69         tmp.remove(path);
70         return savePath;
71     }
72     output.close();
73     savePath = path;
74     return savePath;
75 }
```

Here is the caller graph for this function:

12.14.4 Field Documentation

12.14.4.1 QByteArray FwUpgradeDialog::blob [private]

Definition at line 41 of file fwupgradedialog.h.

Referenced by exec(), and saveBlob().

12.14.4.2 QEventLoop* FwUpgradeDialog::evLoop [private]

Definition at line 45 of file fwupgradedialog.h.

Referenced by exec(), fwUpdateFinished(), on_actionButton_clicked(), and on_cancelButton_clicked().

12.14.4.3 bool FwUpgradeDialog::exitSuccess [private]

Definition at line 46 of file fwupgradedialog.h.

Referenced by exec(), and on_cancelButton_clicked().

12.14.4.4 Kb* FwUpgradeDialog::kb [private]

Definition at line 42 of file fwupgradedialog.h.

Referenced by exec(), FwUpgradeDialog(), on_actionButton_clicked(), and removeDev().

12.14.4.5 QString FwUpgradeDialog::savePath [private]

Definition at line 37 of file fwupgradedialog.h.

Referenced by cleanBlob(), on_actionButton_clicked(), removeDev(), and saveBlob().

12.14.4.6 Ui::FwUpgradeDialog* FwUpgradeDialog::ui [private]

Definition at line 32 of file fwupgradedialog.h.

Referenced by exec(), fwUpdateFinished(), fwUpdateProgress(), FwUpgradeDialog(), on_actionButton_clicked(), and ~FwUpgradeDialog().

The documentation for this class was generated from the following files:

- src/ckb/fwupgradedialog.h
- src/ckb/fwupgradedialog.cpp

12.15 Ui::FwUpgradeDialog Class Reference

```
#include <src/ckb/ui_fwupgradedialog.h>
```

Inheritance diagram for Ui::FwUpgradeDialog:

Collaboration diagram for Ui::FwUpgradeDialog:

Public Member Functions

- void setupUi (QDialog ∗FwUpgradeDialog)
- void retranslateUi (QDialog ∗FwUpgradeDialog)

Data Fields

- QGridLayout ∗ gridLayout_2
- QSpacerItem ∗ horizontalSpacer
- QGridLayout ∗ gridLayout
- QSpacerItem ∗ horizontalSpacer_3
- QLabel ∗ label_4
- QSpacerItem ∗ horizontalSpacer_4
- QLabel ∗ label_2
- QLabel ∗ curLabel
- QLabel ∗ newLabel
- QLabel ∗ statusLabel
- QSpacerItem ∗ horizontalSpacer_2
- QLabel ∗ devLabel
- QProgressBar ∗ progressBar
- QPushButton ∗ actionButton
- QPushButton ∗ cancelButton

12.15.1 Detailed Description

Definition at line 171 of file ui_fwupgradedialog.h.

12.15.2 Member Function Documentation

12.15.2.1 void Ui_FwUpgradeDialog::retranslateUi (QDialog * *FwUpgradeDialog*) [inline],[inherited]

Definition at line 155 of file ui_fwupgradedialog.h.

References Ui_FwUpgradeDialog::actionButton, Ui_FwUpgradeDialog::cancelButton, Ui_FwUpgradeDialog::curLabel, Ui_FwUpgradeDialog::devLabel, Ui_FwUpgradeDialog::label_2, Ui_FwUpgradeDialog::label_4, Ui_FwUpgradeDialog::newLabel, and Ui_FwUpgradeDialog::statusLabel.

Referenced by Ui_FwUpgradeDialog::setupUi().

```
156     {
157         FwUpgradeDialog->setWindowTitle(QApplication::translate("FwUpgradeDialog", "Firmware update",
    Q_NULLPTR));
158         label_4->setText(QApplication::translate("FwUpgradeDialog", "New:", Q_NULLPTR));
159         label_2->setText(QApplication::translate("FwUpgradeDialog", "Current:", Q_NULLPTR));
160         curLabel->setText(QApplication::translate("FwUpgradeDialog", "0.00", Q_NULLPTR));
161         newLabel->setText(QApplication::translate("FwUpgradeDialog", "0.00", Q_NULLPTR));
162         statusLabel->setText(QApplication::translate("FwUpgradeDialog", "Downloading new
     firmware, please wait...", Q_NULLPTR));
163         devLabel->setText(QApplication::translate("FwUpgradeDialog", "Device", Q_NULLPTR));
164         actionButton->setText(QApplication::translate("FwUpgradeDialog", "Start", Q_NULLPTR));
165         cancelButton->setText(QApplication::translate("FwUpgradeDialog", "Cancel", Q_NULLPTR));
166     } // retranslateUi
```

Here is the caller graph for this function:

12.15.2.2 void Ui_FwUpgradeDialog::setupUi (QDialog * *FwUpgradeDialog*) [inline],[inherited]

Definition at line 45 of file ui_fwupgradedialog.h.

References Ui_FwUpgradeDialog::actionButton, Ui_FwUpgradeDialog::cancelButton, Ui_FwUpgradeDialog::curLabel, Ui_FwUpgradeDialog::devLabel, Ui_FwUpgradeDialog::gridLayout, Ui_FwUpgradeDialog::gridLayout_2, Ui_FwUpgradeDialog::horizontalSpacer, Ui_FwUpgradeDialog::horizontalSpacer_2, Ui_FwUpgradeDialog::horizontalSpacer_3, Ui_FwUpgradeDialog::horizontalSpacer_4, Ui_FwUpgradeDialog::label_2, Ui_FwUpgradeDialog::label_4, Ui_FwUpgradeDialog::newLabel, Ui_FwUpgradeDialog::progressBar, Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::statusLabel.

Referenced by FwUpgradeDialog::FwUpgradeDialog().

```
46     {
47         if (FwUpgradeDialog->objectName().isEmpty())
48             FwUpgradeDialog->setObjectName(QStringLiteral("FwUpgradeDialog"));
49         FwUpgradeDialog->resize(420, 240);
50         QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
51         sizePolicy.setHorizontalStretch(0);
52         sizePolicy.setVerticalStretch(0);
53         sizePolicy.setHeightForWidth(FwUpgradeDialog->sizePolicy().hasHeightForWidth());
54         FwUpgradeDialog->setSizePolicy(sizePolicy);
55         gridLayout_2 = new QGridLayout(FwUpgradeDialog);
56         gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
57         horizontalSpacer = new QSpacerItem(127, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
58
59         gridLayout_2->addItem(horizontalSpacer, 1, 0, 1, 1);
60
61         gridLayout = new QGridLayout();
62         gridLayout->setObjectName(QStringLiteral("gridLayout"));
63         horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
```

```
        gridLayout->addItem(horizontalSpacer_3, 1, 0, 1, 1);

        label_4 = new QLabel(FwUpgradeDialog);
        label_4->setObjectName(QStringLiteral("label_4"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label_4->setFont(font);

        gridLayout->addWidget(label_4, 1, 4, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_4, 1, 6, 1, 1);

        label_2 = new QLabel(FwUpgradeDialog);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        gridLayout->addWidget(label_2, 1, 1, 1, 1);

        curLabel = new QLabel(FwUpgradeDialog);
        curLabel->setObjectName(QStringLiteral("curLabel"));

        gridLayout->addWidget(curLabel, 1, 2, 1, 1);

        newLabel = new QLabel(FwUpgradeDialog);
        newLabel->setObjectName(QStringLiteral("newLabel"));

        gridLayout->addWidget(newLabel, 1, 5, 1, 1);

        statusLabel = new QLabel(FwUpgradeDialog);
        statusLabel->setObjectName(QStringLiteral("statusLabel"));
        QSizePolicy sizePolicy1(QSizePolicy::Preferred, QSizePolicy::Expanding);
        sizePolicy1.setHorizontalStretch(0);
         sizePolicy1.setVerticalStretch(0);
         sizePolicy1.setHeightForWidth(statusLabel->sizePolicy().hasHeightForWidth());
         statusLabel->setSizePolicy(sizePolicy1);
         statusLabel->setAlignment(Qt::AlignCenter);
         statusLabel->setWordWrap(true);

         gridLayout->addWidget(statusLabel, 2, 0, 1, 7);

         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

         gridLayout->addItem(horizontalSpacer_2, 1, 3, 1, 1);

         devLabel = new QLabel(FwUpgradeDialog);
         devLabel->setObjectName(QStringLiteral("devLabel"));
         QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Minimum);
         sizePolicy2.setHorizontalStretch(0);
         sizePolicy2.setVerticalStretch(0);
         sizePolicy2.setHeightForWidth(devLabel->sizePolicy().hasHeightForWidth());
         devLabel->setSizePolicy(sizePolicy2);
         devLabel->setFont(font);
         devLabel->setAlignment(Qt::AlignCenter);

         gridLayout->addWidget(devLabel, 0, 0, 1, 7);

         progressBar = new QProgressBar(FwUpgradeDialog);
         progressBar->setObjectName(QStringLiteral("progressBar"));
         progressBar->setMaximum(0);
         progressBar->setValue(0);

         gridLayout->addWidget(progressBar, 3, 0, 1, 7);


         gridLayout_2->addLayout(gridLayout, 0, 0, 1, 3);

         actionButton = new QPushButton(FwUpgradeDialog);
         actionButton->setObjectName(QStringLiteral("actionButton"));
         actionButton->setEnabled(false);

         gridLayout_2->addWidget(actionButton, 1, 2, 1, 1);

         cancelButton = new QPushButton(FwUpgradeDialog);
         cancelButton->setObjectName(QStringLiteral("cancelButton"));
         cancelButton->setEnabled(false);

         gridLayout_2->addWidget(cancelButton, 1, 1, 1, 1);


         retranslateUi(FwUpgradeDialog);

```

```
        actionButton->setDefault(true);


        QMetaObject::connectSlotsByName(FwUpgradeDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.15.3 Field Documentation

12.15.3.1 QPushButton* Ui_FwUpgradeDialog::actionButton [inherited]

Definition at line 42 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::on_action-Button_clicked(), Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.2 QPushButton* Ui_FwUpgradeDialog::cancelButton [inherited]

Definition at line 43 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::on_actionButton_clicked(), Ui_FwUpgradeDialog-::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.3 QLabel* Ui_FwUpgradeDialog::curLabel [inherited]

Definition at line 36 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgrade-Dialog::setupUi().

12.15.3.4 QLabel* Ui_FwUpgradeDialog::devLabel [inherited]

Definition at line 40 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgrade-Dialog::setupUi().

12.15.3.5 QGridLayout* Ui_FwUpgradeDialog::gridLayout [inherited]

Definition at line 31 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.6 QGridLayout* Ui_FwUpgradeDialog::gridLayout_2 [inherited]

Definition at line 29 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.7 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer [inherited]

Definition at line 30 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.8 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_2 [inherited]

Definition at line 39 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.9 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_3 [inherited]

Definition at line 32 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.10 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_4 [inherited]

Definition at line 34 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::setupUi().

12.15.3.11 QLabel* Ui_FwUpgradeDialog::label_2 [inherited]

Definition at line 35 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.12 QLabel* Ui_FwUpgradeDialog::label_4 [inherited]

Definition at line 33 of file ui_fwupgradedialog.h.

Referenced by Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.13 QLabel* Ui_FwUpgradeDialog::newLabel [inherited]

Definition at line 37 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::FwUpgradeDialog(), Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.14 QProgressBar* Ui_FwUpgradeDialog::progressBar [inherited]

Definition at line 41 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::fwUpdateProgress(), FwUpgradeDialog::on_actionButton_clicked(), and Ui_FwUpgradeDialog::setupUi().

12.15.3.15 QLabel* Ui_FwUpgradeDialog::statusLabel [inherited]

Definition at line 38 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::on_actionButton_clicked(), Ui_FwUpgradeDialog::retranslateUi(), and Ui_FwUpgradeDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_fwupgradedialog.h

12.16 GradientButton Class Reference

`#include <src/ckb/gradientbutton.h>`

Inheritance diagram for GradientButton:

Collaboration diagram for GradientButton:

Signals

- void gradientChanged ()

Public Member Functions

- GradientButton (QWidget *parent=0, bool allowAlpha=false)
- void fromString (const QString &string)
- QString toString () const

Private Slots

- void pickGradient ()

Private Member Functions

- void updateImage ()

Private Attributes

- QGradientStops _stops
- bool _alpha

12.16.1 Detailed Description

Definition at line 6 of file gradientbutton.h.

12.16.2 Constructor & Destructor Documentation

12.16.2.1 GradientButton::GradientButton (QWidget * *parent* = 0, bool *allowAlpha* = false) [explicit]

Definition at line 7 of file gradientbutton.cpp.

References fromString(), and pickGradient().

```
7                                                                   :
8     QPushButton(parent), _alpha(allowAlpha)
9 {
10     connect(this, SIGNAL(clicked()), this, SLOT(pickGradient()));
11     setAutoDefault(false);
12     setDefault(false);
13     fromString("");
14     setText("");
15 }
```

Here is the call graph for this function:

12.16.3 Member Function Documentation

12.16.3.1 void GradientButton::fromString (const QString & *string*)

Definition at line 38 of file gradientbutton.cpp.

References _alpha, _stops, and updateImage().

Referenced by GradientButton().

```
38                                                          {
39     // Clear existing stops
40     _stops.clear();
41     // Parse string with sscanf
42     QByteArray cString = string.toLatin1();
43     const char* data = cString.data();
44     char pos = -1;
45     uchar a, r, g, b;
46     while(1){
47         int scanned = 0;
48         char newpos;
49         if(sscanf(data, "%hhd:%2hhx%2hhx%2hhx%2hhx%n", &newpos, &a, &r, &g, &b, &scanned) != 5)
50             break;
51         data += scanned;
52         // Don't allow stops out-of-order or past 100
53         if(newpos <= pos || newpos > 100)
54             break;
55         pos = newpos;
56         if(!_alpha)
57             a = 255;
58         _stops.append(QGradientStop(pos / 100., QColor(r, g, b, a)));
59     }
60     if(_stops.count() == 0){
61         // If nothing was read, try a single ARGB constant.
62         if(sscanf(data, "%2hhx%2hhx%2hhx%2hhx", &a, &r, &g, &b) == 4){
63             _stops.append(QGradientStop(0., QColor(r, g, b, a)));
64             _stops.append(QGradientStop(1., QColor(r, g, b, 0.)));
65         }
66     }
67     // If that still didn't work, fill with white
68     if(_stops.count() == 0){
69         _stops.append(QGradientStop(0., QColor(255, 255, 255)));
70         _stops.append(QGradientStop(1., QColor(255, 255, 255)));
71     }
72     // Make sure there are stops at 0 and at 100
73     if(_stops[0].first != 0.)
74         _stops.prepend(QGradientStop(0., _stops[0].second));
```

```
    if(_stops.last().first != 1.)
        _stops.prepend(QGradientStop(1., _stops.last().second));
    updateImage();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.16.3.2 void GradientButton::gradientChanged ( ) [signal]

Definition at line 132 of file moc_gradientbutton.cpp.

Referenced by pickGradient().

```
{
    QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
}
```

Here is the caller graph for this function:

12.16.3.3 void GradientButton::pickGradient ( ) [private],[slot]

Definition at line 90 of file gradientbutton.cpp.

References _stops, GradientDialog::getGradient(), gradientChanged(), and updateImage().

Referenced by GradientButton().

```
                                {
    GradientDialog dialog(this);
    _stops = dialog.getGradient(_stops);
    updateImage();
    emit gradientChanged();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.16.3.4 QString GradientButton::toString ( ) const

Definition at line 80 of file gradientbutton.cpp.

References _stops.

Referenced by AnimSettingDialog::updateParam().

```
                                    {
    QStringList result;
    foreach(const QGradientStop& stop, _stops){
        QString string;
        const QColor& color = stop.second;
        result << string.sprintf("%d:%02x%02x%02x%02x", (int)round(stop.first * 100.f), color.alpha(),
    color.red(), color.green(), color.blue());
    }
    return result.join(" ");
}
```

Here is the caller graph for this function:

12.16.3.5 void GradientButton::updateImage ( ) [private]

Definition at line 17 of file gradientbutton.cpp.

References _alpha, and _stops.

Referenced by fromString(), and pickGradient().

```
17                                  {
18      const int w = 130, h = 16;
19      QImage image(w, h, QImage::Format_RGB888);
20      QPainter painter(&image);
21      painter.setPen(Qt::NoPen);
22      painter.fillRect(0, 0, w, h, QColor(0, 0, 0));
23      if(_alpha){
24          for(int x = 1; x < w - 1; x += h){
25              painter.fillRect(x, 1, h / 2, h / 2 - 1, QColor(255, 255, 255));
26              painter.fillRect(x + h / 2, 1, h / 2, h / 2 - 1, QColor(192, 192, 192));
27              painter.fillRect(x, h / 2, h / 2, h / 2 - 1, QColor(192, 192, 192));
28              painter.fillRect(x + h / 2, h / 2, h / 2, h / 2 - 1, QColor(255, 255, 255));
29          }
30      }
31      QLinearGradient gradient(1., 0., w - 1, 0.);
32      gradient.setStops(_stops);
33      painter.fillRect(1, 1, w - 2, h - 2, QBrush(gradient));
34      setIconSize(QSize(w, h));
35      setIcon(QIcon(QPixmap::fromImage(image)));
36  }
```

Here is the caller graph for this function:

12.16.4 Field Documentation

12.16.4.1 bool GradientButton::_alpha [private]

Definition at line 23 of file gradientbutton.h.

Referenced by fromString(), and updateImage().

12.16.4.2 QGradientStops GradientButton::_stops [private]

Definition at line 22 of file gradientbutton.h.

Referenced by fromString(), pickGradient(), toString(), and updateImage().

The documentation for this class was generated from the following files:

- src/ckb/gradientbutton.h
- src/ckb/gradientbutton.cpp
- src/ckb/release/moc_gradientbutton.cpp

12.17 Ui::GradientDialog Class Reference

```
#include <src/ckb/ui_gradientdialog.h>
```

Inheritance diagram for Ui::GradientDialog:

Collaboration diagram for Ui::GradientDialog:

Public Member Functions

- void setupUi (QDialog *GradientDialog)
- void retranslateUi (QDialog *GradientDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_2
- GradientDialogWidget * widget
- QDialogButtonBox * buttonBox
- QGroupBox * stopBox
- QGridLayout * gridLayout_2
- QHBoxLayout * horizontalLayout_2
- ColorButton * stopColor
- QSpinBox * stopOpacity
- QSpacerItem * horizontalSpacer_2
- QLabel * label
- QHBoxLayout * horizontalLayout
- QSpinBox * stopPos
- QSpacerItem * horizontalSpacer
- QLabel * label_2
- QSpacerItem * horizontalSpacer_3
- QGroupBox * groupBox_2
- QGridLayout * gridLayout_3
- QListWidget * presetList
- QLineEdit * presetName
- QPushButton * presetSave
- QPushButton * presetDelete

12.17.1 Detailed Description

Definition at line 225 of file ui_gradientdialog.h.

12.17.2 Member Function Documentation

12.17.2.1 void Ui_GradientDialog::retranslateUi (QDialog * *GradientDialog*) [inline],[inherited]

Definition at line 207 of file ui_gradientdialog.h.

References Ui_GradientDialog::groupBox_2, Ui_GradientDialog::label, Ui_GradientDialog::label_2, Ui_GradientDialog::presetDelete, Ui_GradientDialog::presetName, Ui_GradientDialog::presetSave, Ui_GradientDialog::stopBox, Ui_GradientDialog::stopColor, Ui_GradientDialog::stopOpacity, and Ui_GradientDialog::stopPos.

Referenced by Ui_GradientDialog::setupUi().

```
    {
        GradientDialog->setWindowTitle(QApplication::translate("GradientDialog", "Pick Gradient", Q_NULLPTR));
        stopBox->setTitle(QApplication::translate("GradientDialog", "Point X of Y", Q_NULLPTR));
        stopColor->setText(QApplication::translate("GradientDialog", "Pick Color...", Q_NULLPTR));
        stopOpacity->setSuffix(QApplication::translate("GradientDialog", "%", Q_NULLPTR));
        label->setText(QApplication::translate("GradientDialog", "Position:", Q_NULLPTR));
        stopPos->setSuffix(QApplication::translate("GradientDialog", "%", Q_NULLPTR));
        label_2->setText(QApplication::translate("GradientDialog", "Color:", Q_NULLPTR));
        groupBox_2->setTitle(QApplication::translate("GradientDialog", "Presets", Q_NULLPTR));
        presetName->setPlaceholderText(QApplication::translate("GradientDialog", "Name", Q_NULLPTR));
        presetSave->setText(QApplication::translate("GradientDialog", "Save", Q_NULLPTR));
        presetDelete->setText(QApplication::translate("GradientDialog", "Delete", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.17.2.2 void Ui_GradientDialog::setupUi (QDialog * *GradientDialog*) [inline],[inherited]

Definition at line 60 of file ui_gradientdialog.h.

References Ui_GradientDialog::buttonBox, Ui_GradientDialog::gridLayout, Ui_GradientDialog::gridLayout_2, Ui_GradientDialog::gridLayout_3, Ui_GradientDialog::groupBox_2, Ui_GradientDialog::horizontalLayout, Ui_GradientDialog::horizontalLayout_2, Ui_GradientDialog::horizontalSpacer, Ui_GradientDialog::horizontalSpacer_2, Ui_GradientDialog::horizontalSpacer_3, Ui_GradientDialog::label, Ui_GradientDialog::label_2, Ui_GradientDialog::presetDelete, Ui_GradientDialog::presetList, Ui_GradientDialog::presetName, Ui_GradientDialog::presetSave, Ui_GradientDialog::retranslateUi(), Ui_GradientDialog::stopBox, Ui_GradientDialog::stopColor, Ui_GradientDialog::stopOpacity, Ui_GradientDialog::stopPos, Ui_GradientDialog::verticalSpacer, Ui_GradientDialog::verticalSpacer_2, and Ui_GradientDialog::widget.

Referenced by GradientDialog::GradientDialog().

```
61     {
62         if (GradientDialog->objectName().isEmpty())
63             GradientDialog->setObjectName(QStringLiteral("GradientDialog"));
64         GradientDialog->resize(400, 440);
65         GradientDialog->setMinimumSize(QSize(400, 440));
66         GradientDialog->setMaximumSize(QSize(400, 440));
67         GradientDialog->setFocusPolicy(Qt::ClickFocus);
68         gridLayout = new QGridLayout(GradientDialog);
69         gridLayout->setObjectName(QStringLiteral("gridLayout"));
70         verticalSpacer = new QSpacerItem(0, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);
71
72         gridLayout->addItem(verticalSpacer, 1, 0, 1, 1);
73
74         verticalSpacer_2 = new QSpacerItem(0, 15, QSizePolicy::Minimum, QSizePolicy::Fixed)
    ;
75
76         gridLayout->addItem(verticalSpacer_2, 3, 0, 1, 1);
77
78         widget = new GradientDialogWidget(GradientDialog);
79         widget->setObjectName(QStringLiteral("widget"));
80         QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Fixed);
81         sizePolicy.setHorizontalStretch(0);
82         sizePolicy.setVerticalStretch(0);
83         sizePolicy.setHeightForWidth(widget->sizePolicy().hasHeightForWidth());
84         widget->setSizePolicy(sizePolicy);
85         widget->setMinimumSize(QSize(0, 74));
86         widget->setMaximumSize(QSize(16777215, 74));
87
88         gridLayout->addWidget(widget, 2, 0, 1, 1);
89
90         buttonBox = new QDialogButtonBox(GradientDialog);
91         buttonBox->setObjectName(QStringLiteral("buttonBox"));
92         buttonBox->setOrientation(Qt::Horizontal);
93         buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
94
95         gridLayout->addWidget(buttonBox, 5, 0, 1, 1);
96
97         stopBox = new QGroupBox(GradientDialog);
98         stopBox->setObjectName(QStringLiteral("stopBox"));
99         sizePolicy.setHeightForWidth(stopBox->sizePolicy().hasHeightForWidth());
100         stopBox->setSizePolicy(sizePolicy);
101         gridLayout_2 = new QGridLayout(stopBox);
102         gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
103         horizontalLayout_2 = new QHBoxLayout();
104         horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
105         stopColor = new ColorButton(stopBox);
106         stopColor->setObjectName(QStringLiteral("stopColor"));
107
```

```
        horizontalLayout_2->addWidget(stopColor);

        stopOpacity = new QSpinBox(stopBox);
        stopOpacity->setObjectName(QStringLiteral("stopOpacity"));
        stopOpacity->setMaximum(100);

        horizontalLayout_2->addWidget(stopOpacity);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_2);


        gridLayout_2->addLayout(horizontalLayout_2, 1, 2, 1, 1);

        label = new QLabel(stopBox);
        label->setObjectName(QStringLiteral("label"));

        gridLayout_2->addWidget(label, 0, 0, 1, 1);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        stopPos = new QSpinBox(stopBox);
        stopPos->setObjectName(QStringLiteral("stopPos"));
        stopPos->setMaximum(100);

        horizontalLayout->addWidget(stopPos);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer);


        gridLayout_2->addLayout(horizontalLayout, 0, 2, 1, 1);

        label_2 = new QLabel(stopBox);
        label_2->setObjectName(QStringLiteral("label_2"));

        gridLayout_2->addWidget(label_2, 1, 0, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(10, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 0, 1, 1, 1);


        gridLayout->addWidget(stopBox, 4, 0, 1, 1);

        groupBox_2 = new QGroupBox(GradientDialog);
        groupBox_2->setObjectName(QStringLiteral("groupBox_2"));
        sizePolicy.setHeightForWidth(groupBox_2->sizePolicy().hasHeightForWidth());
        groupBox_2->setSizePolicy(sizePolicy);
        gridLayout_3 = new QGridLayout(groupBox_2);
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        presetList = new QListWidget(groupBox_2);
        presetList->setObjectName(QStringLiteral("presetList"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(presetList->sizePolicy().hasHeightForWidth());
        presetList->setSizePolicy(sizePolicy1);
        presetList->setFrameShadow(QFrame::Plain);
        presetList->setHorizontalScrollBarPolicy(Qt::ScrollBarAlwaysOn);
        presetList->setIconSize(QSize(64, 64));
        presetList->setHorizontalScrollMode(QAbstractItemView::ScrollPerPixel);
        presetList->setFlow(QListView::TopToBottom);
        presetList->setViewMode(QListView::IconMode);
        presetList->setUniformItemSizes(true);

        gridLayout_3->addWidget(presetList, 0, 0, 3, 1);

        presetName = new QLineEdit(groupBox_2);
        presetName->setObjectName(QStringLiteral("presetName"));
        presetName->setMaxLength(30);

        gridLayout_3->addWidget(presetName, 0, 1, 1, 1);

        presetSave = new QPushButton(groupBox_2);
        presetSave->setObjectName(QStringLiteral("presetSave"));
        presetSave->setAutoDefault(false);

        gridLayout_3->addWidget(presetSave, 1, 1, 1, 1);

        presetDelete = new QPushButton(groupBox_2);
        presetDelete->setObjectName(QStringLiteral("presetDelete"));
```

```
        presetDelete->setAutoDefault(false);

        gridLayout_3->addWidget(presetDelete, 2, 1, 1, 1);


        gridLayout->addWidget(groupBox_2, 0, 0, 1, 1);


        retranslateUi(GradientDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), GradientDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), GradientDialog, SLOT(reject()));

        QMetaObject::connectSlotsByName(GradientDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.17.3 Field Documentation

12.17.3.1 QDialogButtonBox* Ui_GradientDialog::buttonBox [inherited]

Definition at line 40 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.2 QGridLayout* Ui_GradientDialog::gridLayout [inherited]

Definition at line 36 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.3 QGridLayout* Ui_GradientDialog::gridLayout_2 [inherited]

Definition at line 42 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.4 QGridLayout* Ui_GradientDialog::gridLayout_3 [inherited]

Definition at line 54 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.5 QGroupBox* Ui_GradientDialog::groupBox_2 [inherited]

Definition at line 53 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.6 QHBoxLayout* Ui_GradientDialog::horizontalLayout [inherited]

Definition at line 48 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.7 QHBoxLayout* Ui_GradientDialog::horizontalLayout_2 [inherited]

Definition at line 43 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.8 QSpacerItem* Ui_GradientDialog::horizontalSpacer [inherited]

Definition at line 50 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.9 QSpacerItem* Ui_GradientDialog::horizontalSpacer_2 [inherited]

Definition at line 46 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.10 QSpacerItem* Ui_GradientDialog::horizontalSpacer_3 [inherited]

Definition at line 52 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.11 QLabel* Ui_GradientDialog::label [inherited]

Definition at line 47 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.12 QLabel* Ui_GradientDialog::label_2 [inherited]

Definition at line 51 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.13 QPushButton* Ui_GradientDialog::presetDelete [inherited]

Definition at line 58 of file ui_gradientdialog.h.

Referenced by GradientDialog::getGradient(), GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), Ui_GradientDialog::retranslateUi(), GradientDialog::setPreset(), and Ui_GradientDialog::setupUi().

12.17.3.14 QListWidget* Ui_GradientDialog::presetList [inherited]

Definition at line 55 of file ui_gradientdialog.h.

Referenced by GradientDialog::setPreset(), Ui_GradientDialog::setupUi(), and GradientDialog::updatePresets().

12.17.3.15 QLineEdit* Ui_GradientDialog::presetName [inherited]

Definition at line 56 of file ui_gradientdialog.h.

Referenced by GradientDialog::on_presetSave_clicked(), Ui_GradientDialog::retranslateUi(), GradientDialog::setPreset(), and Ui_GradientDialog::setupUi().

12.17.3.16 QPushButton* Ui_GradientDialog::presetSave [inherited]

Definition at line 57 of file ui_gradientdialog.h.

Referenced by GradientDialog::getGradient(), GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), Ui_GradientDialog::retranslateUi(), GradientDialog::setPreset(), and Ui_GradientDialog::setupUi().

12.17.3.17 QGroupBox* Ui_GradientDialog::stopBox [inherited]

Definition at line 41 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.18 ColorButton* Ui_GradientDialog::stopColor [inherited]

Definition at line 44 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), GradientDialog::GradientDialog(), GradientDialog::on_stopOpacity_valueChanged(), Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.19 QSpinBox* Ui_GradientDialog::stopOpacity [inherited]

Definition at line 45 of file ui_gradientdialog.h.

Referenced by GradientDialog::colorChanged(), GradientDialog::currentChanged(), Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.20 QSpinBox* Ui_GradientDialog::stopPos [inherited]

Definition at line 49 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), GradientDialog::on_stopPos_valueChanged(), Ui_GradientDialog::retranslateUi(), and Ui_GradientDialog::setupUi().

12.17.3.21 QSpacerItem* Ui_GradientDialog::verticalSpacer [inherited]

Definition at line 37 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.22 QSpacerItem* Ui_GradientDialog::verticalSpacer_2 [inherited]

Definition at line 38 of file ui_gradientdialog.h.

Referenced by Ui_GradientDialog::setupUi().

12.17.3.23 GradientDialogWidget* Ui_GradientDialog::widget [inherited]

Definition at line 39 of file ui_gradientdialog.h.

Referenced by GradientDialog::colorChanged(), GradientDialog::currentChanged(), GradientDialog::getGradient(), GradientDialog::GradientDialog(), GradientDialog::on_presetSave_clicked(), GradientDialog::on_stopPos_valueChanged(), GradientDialog::setPreset(), and Ui_GradientDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_gradientdialog.h

12.18 GradientDialog Class Reference

```
#include <src/ckb/gradientdialog.h>
```

Inheritance diagram for GradientDialog:

Collaboration diagram for GradientDialog:

Data Structures

- struct Preset

Public Member Functions

- GradientDialog (QWidget ∗parent=0)
- ∼GradientDialog ()
- QGradientStops getGradient (const QGradientStops &prevGradient)

Private Slots

- void currentChanged (QColor color, bool spontaneous, int position)
- void colorChanged (QColor color)
- void on_presetList_currentItemChanged (QListWidgetItem ∗current, QListWidgetItem ∗previous)
- void on_presetName_textEdited (const QString &arg1)
- void on_presetSave_clicked ()
- void on_presetDelete_clicked ()
- void on_stopPos_valueChanged (int arg1)
- void on_stopOpacity_valueChanged (int arg1)

Private Member Functions

- void addPreset (const Preset &preset)
- QIcon makeIcon (const Preset &preset)
- void updatePresets ()
- void setPreset (const QString &newPreset)

Private Attributes

- QMap< QString, Preset > presets
- QString currentPreset
- Ui::GradientDialog * ui

12.18.1 Detailed Description

Definition at line 12 of file gradientdialog.h.

12.18.2 Constructor & Destructor Documentation

12.18.2.1 GradientDialog::GradientDialog (QWidget * *parent* = 0) [explicit]

Definition at line 11 of file gradientdialog.cpp.

References addPreset(), CkbSettings::childGroups(), CkbSettings::childKeys(), colorChanged(), currentChanged(), GradientDialog::Preset::gradient, prefsPath, presets, Ui_GradientDialog::setupUi(), Ui_GradientDialog::stopColor, ui, updatePresets(), CkbSettings::value(), and Ui_GradientDialog::widget.

```
11                                                  :
12     QDialog(parent),
13     ui(new Ui::GradientDialog)
14 {
15     ui->setupUi(this);
16     connect(ui->widget, SIGNAL(currentChanged(QColor,bool,int)), this, SLOT(
       currentChanged(QColor,bool,int)));
17     connect(ui->stopColor, SIGNAL(colorChanged(QColor)), this, SLOT(
       colorChanged(QColor)));
18
19     // Add built-in presets
20     Preset blackAndWhite("B & W", true);
21     blackAndWhite.gradient.append(QGradientStop(0., QColor(0, 0, 0)));
22     blackAndWhite.gradient.append(QGradientStop(1., QColor(255, 255, 255)));
23     Preset fade("Fade", true);
24     fade.gradient.append(QGradientStop(0., QColor(255, 255, 255)));
25     fade.gradient.append(QGradientStop(1., QColor(255, 255, 255, 0)));
26     Preset rainbow("Rainbow", true);
27     rainbow.gradient.append(QGradientStop(0.00, QColor(255, 0, 0)));
28     rainbow.gradient.append(QGradientStop(0.17, QColor(255, 255, 0)));
29     rainbow.gradient.append(QGradientStop(0.33, QColor(0, 255, 0)));
30     rainbow.gradient.append(QGradientStop(0.50, QColor(0, 255, 255)));
31     rainbow.gradient.append(QGradientStop(0.67, QColor(0, 0, 255)));
32     rainbow.gradient.append(QGradientStop(0.83, QColor(255, 0, 255)));
33     rainbow.gradient.append(QGradientStop(1.00, QColor(255, 0, 0)));
34     addPreset(blackAndWhite);
35     addPreset(fade);
36     addPreset(rainbow);
37
38     // Load stored presets
39     CkbSettings settings(prefsPath);
40     foreach(const QString& name, settings.childGroups()){
41         QString pName = name.toLower();
42         if(presets.contains(pName))
43             continue;
44         SGroup group(settings, name);
45         // Create keys in a map to ensure correct order and no duplicates
46         QMap<int, QColor> colors;
47         foreach(const QString& position, settings.childKeys()){
48             int pos = position.toInt();
49             if(pos < 0 || pos > 100)
50                 continue;
51             colors[pos] = settings.value(position).value<QColor>();
52         }
53         if(colors.count() < 2)
54             continue;
55         Preset preset(name);
56         QMapIterator<int, QColor> i(colors);
57         while(i.hasNext()){
58             i.next();
59             preset.gradient.append(QGradientStop(i.key() / 100., i.value()));
60         }
61         presets[pName] = preset;
62     }
63
```

```
    updatePresets();
}
```

Here is the call graph for this function:

12.18.2.2 GradientDialog::~GradientDialog ( )

Definition at line 77 of file gradientdialog.cpp.

References GradientDialog::Preset::builtIn, GradientDialog::Preset::gradient, GradientDialog::Preset::name, prefsPath, presets, CkbSettings::setValue(), and ui.

```
                                {
    // Save presets
    CkbSettings settings(prefsPath, true);
    QMapIterator<QString, Preset> i(presets);
    while(i.hasNext()){
        Preset preset = i.next().value();
        if(!preset.builtIn){
            SGroup group(settings, preset.name);
            foreach(const QGradientStop& stop, preset.gradient)
                settings.setValue(QString::number((int)(stop.first * 100.)), stop.second);
        }
    }
    delete ui;
}
```

Here is the call graph for this function:

12.18.3 Member Function Documentation

12.18.3.1 void GradientDialog::addPreset (const Preset & *preset*) [inline],[private]

Definition at line 34 of file gradientdialog.h.

References GradientDialog::Preset::name, and presets.

Referenced by GradientDialog().

```
34 { presets[preset.name.toLower()] = preset; }
```

Here is the caller graph for this function:

12.18.3.2 void GradientDialog::colorChanged (QColor *color*) [private],[slot]

Definition at line 234 of file gradientdialog.cpp.

References GradientDialogWidget::setCurrentColor(), setPreset(), Ui_GradientDialog::stopOpacity, ui, and Ui_GradientDialog::widget.

Referenced by GradientDialog(), and on_stopOpacity_valueChanged().

```
234                                                 {
235     color.setAlphaF(ui->stopOpacity->value() / 100.f);
236     ui->widget->setCurrentColor(color);
237     setPreset("");
238 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.18.3.3 void GradientDialog::currentChanged (QColor *color,* bool *spontaneous,* int *position*) [private],[slot]

Definition at line 128 of file gradientdialog.cpp.

References ColorButton::color(), setPreset(), Ui_GradientDialog::stopBox, Ui_GradientDialog::stopColor, GradientDialogWidget::stopCount(), Ui_GradientDialog::stopOpacity, Ui_GradientDialog::stopPos, ui, and Ui_GradientDialog::widget.

Referenced by GradientDialog().

```
128                                                                                 {
129     int pCount = ui->widget->stopCount();
130     if(pCount == 1)
131         ui->stopBox->setTitle("1 point");
132     else
133         ui->stopBox->setTitle(QString("%1 points").arg(pCount));
134     if(!color.isValid()){
135         ui->stopBox->setEnabled(false);
136         ui->stopPos->setValue(0);
137         ui->stopColor->color(QColor(0, 0, 0));
138         ui->stopOpacity->setValue(0);
139     } else {
140         ui->stopBox->setEnabled(true);
141         ui->stopPos->setValue(position);
142         ui->stopColor->color(color);
143         ui->stopOpacity->setValue(round(color.alphaF() * 100.f));
144     }
145     // Un-set current preset
146     if(spontaneous)
147         setPreset("");
148     setFocus();
149 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.18.3.4 QGradientStops GradientDialog::getGradient (const QGradientStops & *prevGradient*)

Definition at line 67 of file gradientdialog.cpp.

References Ui_GradientDialog::presetDelete, Ui_GradientDialog::presetSave, GradientDialogWidget::setStops(), GradientDialogWidget::stops(), ui, and Ui_GradientDialog::widget.

Referenced by GradientButton::pickGradient().

```
67                                                                                  {
68     ui->presetDelete->setEnabled(false);
69     ui->presetSave->setEnabled(true);
70     ui->widget->setStops(prevGradient);
```

```
    exec();
    if(result() != QDialog::Accepted)
        return prevGradient;
    return ui->widget->stops();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.18.3.5 QIcon GradientDialog::makeIcon (const Preset & *preset*) [private]

Definition at line 92 of file gradientdialog.cpp.

References GradientDialog::Preset::gradient.

Referenced by updatePresets().

```
92                                                  {
93     // Paint gradient into a square
94     int w = 60, h = 60;
95     QImage image(w, h, QImage::Format_RGB888);
96     QPainter painter(&image);
97     // Draw background
98     for(int x = 0; x < w; x += 30){
99         for(int y = 0; y < h; y += 30){
100            painter.fillRect(x, y, 15, 15, QColor(255, 255, 255));
101            painter.fillRect(x + 15, y, 15, 15, QColor(192, 192, 192));
102            painter.fillRect(x, y + 15, 15, 15, QColor(192, 192, 192));
103            painter.fillRect(x + 15, y + 15, 15, 15, QColor(255, 255, 255));
104        }
105    }
106    // Draw gradient
107    painter.setPen(QColor(0, 0, 0));
108    QLinearGradient gradient(1., 1., w - 1., h - 1.);
109    gradient.setStops(preset.gradient);
110    painter.setBrush(gradient);
111    painter.drawRect(0, 0, w - 1, h - 1);
112    return QPixmap::fromImage(image);
113 }
```

Here is the caller graph for this function:

12.18.3.6 void GradientDialog::on_presetDelete_clicked ( ) [private],[slot]

Definition at line 211 of file gradientdialog.cpp.

References GradientDialog::Preset::builtIn, currentPreset, GradientDialog::Preset::name, Ui_GradientDialog::presetDelete, presets, Ui_GradientDialog::presetSave, ui, and updatePresets().

```
211                                                 {
212     Preset current = presets.value(currentPreset);
213     if(current.name == "" || current.builtIn)
214         return;
215     if(QMessageBox::warning(this, "Warning", QString("Delete preset \"%1\"?").arg(current.name),
      QMessageBox::StandardButtons(QMessageBox::Yes | QMessageBox::No)) != QMessageBox::Yes){
216         setFocus();
217         return;
218     }
219     presets.remove(currentPreset);
220     currentPreset = "";
221     ui->presetDelete->setEnabled(false);
222     ui->presetSave->setEnabled(true);
223     updatePresets();
224     setFocus();
225 }
```

Here is the call graph for this function:

12.18.3.7 void GradientDialog::on_presetList_currentItemChanged (QListWidgetItem * *current*, QListWidgetItem * *previous*) [private],[slot]

Definition at line 174 of file gradientdialog.cpp.

References setPreset().

```
174                                                                                                 {
175     setPreset(current ? current->text().toLower() : "");
176 }
```

Here is the call graph for this function:

12.18.3.8 void GradientDialog::on_presetName_textEdited (const QString & *arg1*) [private],[slot]

Definition at line 178 of file gradientdialog.cpp.

References currentPreset, presets, and setPreset().

```
178                                                                 {
179     if(currentPreset != "" && arg1.trimmed() != presets[
      currentPreset].name)
180         setPreset("");
181 }
```

Here is the call graph for this function:

12.18.3.9 void GradientDialog::on_presetSave_clicked ( ) [private],[slot]

Definition at line 183 of file gradientdialog.cpp.

References GradientDialog::Preset::builtIn, currentPreset, GradientDialog::Preset::name, Ui_GradientDialog-::presetDelete, Ui_GradientDialog::presetName, presets, Ui_GradientDialog::presetSave, GradientDialogWidget-::stops(), ui, updatePresets(), and Ui_GradientDialog::widget.

```
183                                                 {
184     if(currentPreset != "")
185         return;
186     QString name = ui->presetName->text().trimmed();
187     if(name == "")
188         ui->presetName->setText(name = "Custom");
189     QString pName = name.toLower();
190     // Make sure not to overwrite a built-in preset
191     Preset previous = presets[pName];
192     if(previous.builtIn){
193         QMessageBox::warning(this, "Error", "Can't overwrite a built-in preset. Please choose a different
      name.");
194         setFocus();
195         return;
196     } else if(previous.name != ""){
197         // Warn when overwriting an existing preset
198         if(QMessageBox::warning(this, "Warning", QString("Preset \"%1\" already exists. Replace?").arg(name
      ), QMessageBox::StandardButtons(QMessageBox::Save | QMessageBox::Cancel)) != QMessageBox::Save){
199             setFocus();
200             return;
201         }
202     }
203     presets[pName] = Preset(name, ui->widget->stops());
204     currentPreset = pName;
205     ui->presetDelete->setEnabled(true);
206     ui->presetSave->setEnabled(false);
207     updatePresets();
208     setFocus();
209 }
```

Here is the call graph for this function:

12.18.3.10 void GradientDialog::on_stopOpacity_valueChanged (int *arg1*) [private],[slot]

Definition at line 240 of file gradientdialog.cpp.

References ColorButton::color(), colorChanged(), setPreset(), Ui_GradientDialog::stopColor, and ui.

```
240                                                     {
241     colorChanged(ui->stopColor->color());
242     setPreset("");
243 }
```

Here is the call graph for this function:

12.18.3.11 void GradientDialog::on_stopPos_valueChanged (int *arg1*) [private],[slot]

Definition at line 227 of file gradientdialog.cpp.

References GradientDialogWidget::moveCurrent(), setPreset(), Ui_GradientDialog::stopPos, ui, and Ui_GradientDialog::widget.

```
227                                                     {
228     int res = ui->widget->moveCurrent(arg1);
229     if(res != arg1)
230         ui->stopPos->setValue(res);
231     setPreset("");
232 }
```

Here is the call graph for this function:

12.18.3.12 void GradientDialog::setPreset (const QString & *newPreset*) [private]

Definition at line 151 of file gradientdialog.cpp.

References GradientDialog::Preset::builtIn, currentPreset, GradientDialog::Preset::gradient, GradientDialog::-Preset::name, Ui_GradientDialog::presetDelete, Ui_GradientDialog::presetList, Ui_GradientDialog::presetName, presets, Ui_GradientDialog::presetSave, GradientDialogWidget::setStops(), ui, and Ui_GradientDialog::widget.

Referenced by colorChanged(), currentChanged(), on_presetList_currentItemChanged(), on_presetName_text-Edited(), on_stopOpacity_valueChanged(), and on_stopPos_valueChanged().

```
151                                                     {
152     if(currentPreset == newPreset)
153         return;
154     if(newPreset == ""){
155         ui->presetList->clearSelection();
156         ui->presetList->setCurrentItem(0);
157         Preset current = presets.value(currentPreset);
158         QString curName = ui->presetName->text().trimmed();
159         if(curName == "" || (curName == current.name && current.builtIn))
160             ui->presetName->setText("Custom");
161         ui->presetDelete->setEnabled(false);
162         ui->presetSave->setEnabled(true);
163     } else {
164         Preset current = presets.value(newPreset);
165         ui->presetName->setText(current.name);
166         ui->presetDelete->setEnabled(!current.builtIn);
167         ui->presetSave->setEnabled(false);
168         ui->widget->setStops(current.gradient);
169     }
170     currentPreset = newPreset;
171     setFocus();
172 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.18.3.13 void GradientDialog::updatePresets ( ) [private]

Definition at line 115 of file gradientdialog.cpp.

References currentPreset, makeIcon(), GradientDialog::Preset::name, Ui_GradientDialog::presetList, presets, and ui.

Referenced by GradientDialog(), on_presetDelete_clicked(), and on_presetSave_clicked().

```
115                                 {
116     ui->presetList->clear();
117     QMapIterator<QString, Preset> i(presets);
118     while(i.hasNext()){
119         i.next();
120         const Preset& preset = i.value();
121         QListWidgetItem* item = new QListWidgetItem(makeIcon(preset), preset.name,
      ui->presetList);
122         if(currentPreset == i.key())
123             item->setSelected(true);
124         ui->presetList->addItem(item);
125     }
126 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.18.4 Field Documentation

12.18.4.1 QString GradientDialog::currentPreset [private]

Definition at line 32 of file gradientdialog.h.

Referenced by on_presetDelete_clicked(), on_presetName_textEdited(), on_presetSave_clicked(), setPreset(), and updatePresets().

12.18.4.2 QMap<QString, Preset> GradientDialog::presets [private]

Definition at line 31 of file gradientdialog.h.

Referenced by addPreset(), GradientDialog(), on_presetDelete_clicked(), on_presetName_textEdited(), on_presetSave_clicked(), setPreset(), updatePresets(), and ~GradientDialog().

12.18.4.3 Ui::GradientDialog* GradientDialog::ui [private]

Definition at line 39 of file gradientdialog.h.

Referenced by colorChanged(), currentChanged(), getGradient(), GradientDialog(), on_presetDelete_clicked(), on_presetSave_clicked(), on_stopOpacity_valueChanged(), on_stopPos_valueChanged(), setPreset(), updatePresets(), and ~GradientDialog().

The documentation for this class was generated from the following files:

- src/ckb/gradientdialog.h
- src/ckb/gradientdialog.cpp

12.19 GradientDialogWidget Class Reference

```
#include <src/ckb/gradientdialogwidget.h>
```

Inheritance diagram for GradientDialogWidget:

Collaboration diagram for GradientDialogWidget:

Signals

- void currentChanged (QColor color, bool spontaneous, int position)

Public Member Functions

- GradientDialogWidget (QWidget ∗parent=0)
- void setStops (const QGradientStops &stops)
- QGradientStops stops ()
- int stopCount ()
- QColor colorAt (int position)
- int current ()
- int moveCurrent (int to)
- void setCurrentColor (const QColor &color)

Private Member Functions

- QRect fillRect ()
- QRect stopRect (int pos)
- int selectedStop ()
- QMap< int, QColor > selectionColors ()
- void makeStops ()
- void paintEvent (QPaintEvent ∗)
- void mousePressEvent (QMouseEvent ∗event)
- void mouseMoveEvent (QMouseEvent ∗event)
- void mouseReleaseEvent (QMouseEvent ∗event)

Private Attributes

- QColor selected
- int selectedPos
- int selectedOffset
- int _current
- QMap< int, QColor > _colors
- QGradientStops _stops

12.19.1 Detailed Description

Definition at line 8 of file gradientdialogwidget.h.

12.19.2 Constructor & Destructor Documentation

12.19.2.1 GradientDialogWidget::GradientDialogWidget (QWidget * *parent* = 0) [explicit]

Definition at line 6 of file gradientdialogwidget.cpp.

```
6                                                       :
7     QWidget(parent), selectedPos(-1), _current(-1)
8 {
9     setMouseTracking(true);
10 }
```

12.19.3 Member Function Documentation

12.19.3.1 QColor GradientDialogWidget::colorAt (int *position*)

Definition at line 65 of file gradientdialogwidget.cpp.

References _stops.

Referenced by mousePressEvent().

```
65                                              {
66     // Find which stops the position is between
67     qreal pos = position / 100.;
68     QVectorIterator<QGradientStop> i(_stops);
69     QGradientStop previous = i.next();
70     while(i.hasNext()){
71         QGradientStop next = i.next();
72         if(next.first >= pos){
73             // Get color by linear interpolation. Premultiply the alpha value so that it returns the
       expected color
74             // (i.e. stops with zero opacity won't contribute to color)
75             QColor c1 = next.second, c2 = previous.second;
76             qreal distance = next.first - previous.first;
77             qreal dx = (pos - previous.first) / distance;
78             qreal a1 = c1.alphaF(), a2 = c2.alphaF();
79             qreal a3 = a1 * dx + a2 * (1.f - dx);
80             if(a3 == 0.){
81                 c2.setAlpha(0);
82                 return c2;
83             }
84             qreal r = (c1.redF() * a1 * dx + c2.redF() * a2 * (1.f - dx)) / a3;
85             qreal g = (c1.greenF() * a1 * dx + c2.greenF() * a2 * (1.f - dx)) / a3;
86             qreal b = (c1.blueF() * a1 * dx + c2.blueF() * a2 * (1.f - dx)) / a3;
87             return QColor::fromRgbF(r, g, b, a3);
88         }
89         previous = next;
90     }
91     return QColor();
92 }
```

Here is the caller graph for this function:

12.19.3.2 int GradientDialogWidget::current ( ) [inline]

Definition at line 20 of file gradientdialogwidget.h.

References _current.

```
20 { return _current; }
```

12.19.3.3 void GradientDialogWidget::currentChanged (QColor *color*, bool *spontaneous*, int *position*) [signal]

Definition at line 126 of file moc_gradientdialogwidget.cpp.

Referenced by mouseReleaseEvent(), and setStops().

```
127 {
128     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)), const_cast<void*>(
      reinterpret_cast<const void*>(&_t2)), const_cast<void*>(reinterpret_cast<const void*>(&_t3)) };
129     QMetaObject::activate(this, &staticMetaObject, 0, _a);
130 }
```

Here is the caller graph for this function:

12.19.3.4 QRect GradientDialogWidget::fillRect ( ) [private]

Definition at line 138 of file gradientdialogwidget.cpp.

Referenced by mouseMoveEvent(), mousePressEvent(), paintEvent(), selectedStop(), and stopRect().

```
{
    int x = 8, y = 1;
    int w = (width() - x * 2) / 16 * 16, h = (height() - 24) / 16 * 16;
    return QRect(x, y, w, h);
}
```

Here is the caller graph for this function:

12.19.3.5 void GradientDialogWidget::makeStops ( ) [private]

Definition at line 30 of file gradientdialogwidget.cpp.

References _stops, and selectionColors().

Referenced by mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), moveCurrent(), and setCurrentColor().

```
{
    _stops.clear();
    QMap<int, QColor> colors = selectionColors();
    // If there's only a single color, put it at the beginning and end
    if(colors.count() == 1){
#if QT_VERSION >= QT_VERSION_CHECK(5, 2, 0)
        QColor color = colors.first();
#else
        QColor color = colors.value(colors.keys().first());
#endif
        _stops.append(QGradientStop(0., color));
        _stops.append(QGradientStop(1., color));
        update();
        return;
    }
    // Add colors at 0 and 100 if needed
#if QT_VERSION >= QT_VERSION_CHECK(5, 2, 0)
    if(!colors.contains(0))
        colors[0] = colors.first();
    if(!colors.contains(100))
        colors[100] = colors.last();
#else
    if(!colors.contains(0))
        colors[0] = colors.value(colors.keys().first());
    if(!colors.contains(100))
        colors[100] = colors.value(colors.keys().last());
#endif
    QMapIterator<int, QColor> i(colors);
    while(i.hasNext()){
        i.next();
        _stops.append(QGradientStop(i.key() / 100., i.value()));
    }
    update();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.6 void GradientDialogWidget::mouseMoveEvent (QMouseEvent * *event*) [private]

Definition at line 255 of file gradientdialogwidget.cpp.

References _colors, fillRect(), makeStops(), right(), selected, selectedOffset, and selectedPos.

```
255                                                                 {
256     if(!selected.isValid()){
257         if(event->y() >= height() - 24)
258             setCursor(QCursor(Qt::PointingHandCursor));
259         else
260             setCursor(QCursor(Qt::ArrowCursor));
261         return;
262     }
263     // Move selected point (if any)
264     setCursor(QCursor(Qt::ClosedHandCursor));
265     selectedPos = event->x() + selectedOffset;
266     // Allow the point to be deleted as long as there is at least 1 other point
267     bool last = (_colors.count() == 0);
268     // Hug the left/right edges
269     QRect rect = fillRect();
270     int left = rect.left(), right = rect.right();
271     if(selectedPos < left && (last || selectedPos >= left - 30))
272         selectedPos = left;
273     else if(selectedPos > right && (last || selectedPos <=
    right + 30))
274         selectedPos = right;
275     // Remove point if it's too far above/below the widget
276     int top = -30, bottom = height() + 30;
277     if(!last && (event->y() < top || event->y() > bottom))
278         selectedPos = -1;
279     makeStops();
280 }
```

Here is the call graph for this function:

12.19.3.7 void GradientDialogWidget::mousePressEvent (QMouseEvent * *event*) [private]

Definition at line 222 of file gradientdialogwidget.cpp.

References _colors, colorAt(), fillRect(), makeStops(), mouseReleaseEvent(), selected, selectedOffset, selectedPos, selectedStop(), and stopRect().

```
222                                                                 {
223     int x = event->x(), y = event->y();
224     if(y < height() - 24)
225         return;
226     QMapIterator<int, QColor> i(_colors);
227     while(i.hasNext()){
228         i.next();
229         // If a point was selected, remove it from the color map and set it as the selected point
230         QRect stop = stopRect(i.key());
231         if(x >= stop.left() - 1 && x <= stop.right() + 1){
232             selected = i.value();
233             selectedPos = stop.x() + stop.width() / 2;
234             selectedOffset = selectedPos - x;
235             _colors.remove(i.key());
236             // On right click, delete the point
237             if(event->button() == Qt::RightButton && _colors.count() > 1){
238                 selectedPos = -1;
239                 mouseReleaseEvent(event);
240             } else
241                 update();
242             return;
243         }
244     }
245     // If nothing was selected, create a new point
246     QRect fill = fillRect();
247     if(x > fill.left() && x < fill.right() && event->button() != Qt::RightButton){
248         selectedPos = x;
249         selectedOffset = 0;
250         selected = colorAt(selectedStop());
251         makeStops();
252     }
253 }
```

Here is the call graph for this function:

12.19.3.8 void GradientDialogWidget::mouseReleaseEvent (QMouseEvent * *event*) [private]

Definition at line 282 of file gradientdialogwidget.cpp.

References _colors, _current, currentChanged(), makeStops(), selected, selectedPos, selectedStop(), and selectionColors().

Referenced by mousePressEvent().

```
282                                                                 {
283     if(selected.isValid()){
284         // Rejoin selection with gradient
285         _current = selectedStop();
286         _colors = selectionColors();
287         emit currentChanged(_colors.value(_current), true,
      _current);
288         selectedPos = -1;
289         selected = QColor();
290         makeStops();
291     }
292     if(event->y() >= height() - 24)
293         setCursor(QCursor(Qt::PointingHandCursor));
294     else
295         setCursor(QCursor(Qt::ArrowCursor));
296 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.9 int GradientDialogWidget::moveCurrent (int *to*)

Definition at line 94 of file gradientdialogwidget.cpp.

References _colors, _current, makeStops(), and selected.

Referenced by GradientDialog::on_stopPos_valueChanged().

```
94                                          {
95     if(_current < 0 || to == _current || selected.isValid())
96         return _current;
97     // If there's a point in the way, skip past it by continuing in the current direction
98     if(_current < to){
99         while(_colors.contains(to)){
100             to++;
101             if(to > 100)
```

```
                return _current;
        }
    } else {
        while(_colors.contains(to)){
            to--;
            if(to < 0)
                return _current;
        }
    }
    _colors[to] = _colors.take(_current);
    _current = to;
    makeStops();
    return to;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.10 void GradientDialogWidget::paintEvent (QPaintEvent *) [private]

Definition at line 172 of file gradientdialogwidget.cpp.

References _colors, _current, _stops, fillRect(), selected, selectedPos, and stopRect().

```
172                                                 {
173     QPainter painter(this);
174     QRect fill = fillRect();
175     int x = fill.x(), y = fill.y(), w = fill.width(), h = fill.height();
176
177     // Draw border around gradient
178     painter.setPen(palette().color(QPalette::Dark));
179     painter.drawLine(x - 1, y - 1, x + w, y - 1);
180     painter.drawLine(x - 1, y - 1, x - 1, y + h);
181     painter.setPen(palette().color(QPalette::Light));
182     painter.drawLine(x - 1, y + h, x + w, y + h);
183     painter.drawLine(x + w, y - 1, x + w, y + h);
184     // Draw background grid
185     for(int i = 0; i < w; i += 16){
186         for(int iy = 0; iy < h; iy += 16){
187             if(i % 32 != iy % 32)
188                 painter.fillRect(x + i, y + iy, 16, 16, QColor(192, 192, 192));
189             else
190                 painter.fillRect(x + i, y + iy, 16, 16, QColor(255, 255, 255));
191         }
192     }
193     // Draw gradient
194     painter.setRenderHint(QPainter::Antialiasing);
195     QLinearGradient gradient(x, 0, x + w, 0);
196     gradient.setStops(_stops);
197     painter.fillRect(fill, QBrush(gradient));
198
199     // Draw stops
```

```
    QMapIterator<int, QColor> i(_colors);
    painter.setPen(palette().color(QPalette::Shadow));
    while(i.hasNext()){
        i.next();
        painter.setBrush(QBrush(i.value()));
        int index = i.key();
        if(index == _current){
            // Highlight currently-edited stop
            painter.setPen(QPen(palette().color(QPalette::Highlight), 2));
            painter.drawRoundedRect(stopRect(index), 4, 4);
            painter.setPen(palette().color(QPalette::Shadow));
        } else
            painter.drawRoundedRect(stopRect(index), 4, 4);
    }
    // Draw selection (if any)
    if(selected.isValid() && selectedPos >= x && selectedPos <= x + w){
        painter.setPen(QPen(palette().color(QPalette::Highlight), 2.5));
        painter.setBrush(selected);
        painter.drawRoundedRect(selectedPos - 6, height() - 18 - 2, 12, 18, 4, 4);
    }
}
```

Here is the call graph for this function:

12.19.3.11 int GradientDialogWidget::selectedStop ( ) [private]

Definition at line 152 of file gradientdialogwidget.cpp.

References fillRect(), and selectedPos.

Referenced by mousePressEvent(), mouseReleaseEvent(), and selectionColors().

```
                                        {
    QRect rect = fillRect();
    int res = round((selectedPos - rect.x()) * 100. / rect.width());
    if(res < 0 || res > 100)
        return -1;
    return res;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.12 QMap< int, QColor > GradientDialogWidget::selectionColors ( ) [private]

Definition at line 160 of file gradientdialogwidget.cpp.

References _colors, selected, and selectedStop().

Referenced by makeStops(), and mouseReleaseEvent().

```
160                                                     {
161     if(!selected.isValid())
162         return _colors;
163     // Determine selected stop position
164     int selPos = selectedStop();
165     // Re-add if in range
166     QMap<int, QColor> res = _colors;
167     if(selPos >= 0 && selPos <= 100)
168         res[selPos] = selected;
169     return res;
170 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.13 void GradientDialogWidget::setCurrentColor (const QColor & *color*)

Definition at line 117 of file gradientdialogwidget.cpp.

References _colors, _current, makeStops(), and selected.

Referenced by GradientDialog::colorChanged().

```
117                                                                 {
118     if(_current < 0 || selected.isValid())
119         return;
120     QRgb rgb = _colors.value(_current).rgb();
121     _colors[_current] = color;
122     // If any points follow with the same color but different opacity, change them to match
123     QMutableMapIterator<int, QColor> i(_colors);
124     while(i.hasNext()){
125         i.next();
126         if(i.key() <= _current)
127             continue;
128         QColor& value = i.value();
129         if(value.rgb() != rgb)
130             break;
131         int alpha = value.alpha();
132         value = color;
133         value.setAlpha(alpha);
134     }
135     makeStops();
136 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.14 void GradientDialogWidget::setStops (const QGradientStops & *stops*)

Definition at line 12 of file gradientdialogwidget.cpp.

References _colors, _current, _stops, currentChanged(), and stops().

Referenced by GradientDialog::getGradient(), and GradientDialog::setPreset().

```
12                                                                  {
13     _stops = stops;
14     _colors.clear();
15     foreach(const QGradientStop& stop, stops){
16         double pos = stop.first;
17         if(pos < 0. || pos > 1.)
18             continue;
19         _colors[round(pos * 100.)] = stop.second;
20     }
21     _current = 0;
```

```
#if QT_VERSION >= QT_VERSION_CHECK(5, 2, 0)
    emit currentChanged(_colors.first(), false, 0);
#else
    emit currentChanged(_colors.value(_colors.keys().first()), false, 0);
#endif
    update();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.15 int GradientDialogWidget::stopCount ( ) [inline]

Definition at line 16 of file gradientdialogwidget.h.

References _stops.

Referenced by GradientDialog::currentChanged().

```
16 { return _stops.count(); }
```

Here is the caller graph for this function:

12.19.3.16 QRect GradientDialogWidget::stopRect (int *pos*) [private]

Definition at line 144 of file gradientdialogwidget.cpp.

References fillRect().

Referenced by mousePressEvent(), and paintEvent().

```
144                                                 {
145     QRect fill = fillRect();
146     int sx = round(pos / 100. * fill.width()) + fill.x() - 6;
147     int sw = 12, sh = 18;
148     int sy = height() - sh - 2;
149     return QRect(sx, sy, sw, sh);
150 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.19.3.17 QGradientStops GradientDialogWidget::stops ( ) [inline]

Definition at line 15 of file gradientdialogwidget.h.

References _stops.

Referenced by GradientDialog::getGradient(), GradientDialog::on_presetSave_clicked(), and setStops().

```
15 { return _stops; }
```

Here is the caller graph for this function:

12.19.4 Field Documentation

12.19.4.1 QMap<int, QColor> GradientDialogWidget::_colors [private]

Definition at line 31 of file gradientdialogwidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), moveCurrent(), paintEvent(), selectionColors(), setCurrentColor(), and setStops().

12.19.4.2 int GradientDialogWidget::_current [private]

Definition at line 30 of file gradientdialogwidget.h.

Referenced by current(), mouseReleaseEvent(), moveCurrent(), paintEvent(), setCurrentColor(), and setStops().

12.19.4.3 QGradientStops GradientDialogWidget::_stops [private]

Definition at line 32 of file gradientdialogwidget.h.

Referenced by colorAt(), makeStops(), paintEvent(), setStops(), stopCount(), and stops().

12.19.4.4 QColor GradientDialogWidget::selected [private]

Definition at line 28 of file gradientdialogwidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), moveCurrent(), paintEvent(), selectionColors(), and setCurrentColor().

12.19.4.5 int GradientDialogWidget::selectedOffset [private]

Definition at line 29 of file gradientdialogwidget.h.

Referenced by mouseMoveEvent(), and mousePressEvent().

12.19.4.6 int GradientDialogWidget::selectedPos [private]

Definition at line 29 of file gradientdialogwidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), paintEvent(), and selectedStop().

The documentation for this class was generated from the following files:

- src/ckb/gradientdialogwidget.h
- src/ckb/gradientdialogwidget.cpp
- src/ckb/release/moc_gradientdialogwidget.cpp

12.20 JlCompress Class Reference

Utility class for typical operations.

`#include <src/ckb/quazip/JlCompress.h>`

Collaboration diagram for JlCompress:

Static Public Member Functions

- static bool compressFile (QString fileCompressed, QString file)

  Compress a single file.
- static bool compressFiles (QString fileCompressed, QStringList files)

  Compress a list of files.
- static bool compressDir (QString fileCompressed, QString dir=QString(), bool recursive=true)

  Compress a whole directory.
- static QString extractFile (QString fileCompressed, QString fileName, QString fileDest=QString())

  Extract a single file.
- static QStringList extractFiles (QString fileCompressed, QStringList files, QString dir=QString())

  Extract a list of files.
- static QStringList extractDir (QString fileCompressed, QString dir=QString())

  Extract a whole archive.
- static QStringList getFileList (QString fileCompressed)

  Get the file list.

Static Private Member Functions

- static bool compressFile (QuaZip *zip, QString fileName, QString fileDest)

  Compress a single file.
- static bool compressSubDir (QuaZip *parentZip, QString dir, QString parentDir, bool recursive=true)

  Compress a subdirectory.
- static bool extractFile (QuaZip *zip, QString fileName, QString fileDest)

  Extract a single file.
- static bool removeFile (QStringList listFile)

  Remove some files.

12.20.1 Detailed Description

This class contains a number of useful static functions to perform simple operations, such as mass ZIP packing or extraction.

Definition at line 42 of file JlCompress.h.

12.20.2 Member Function Documentation

12.20.2.1 bool JlCompress::compressDir (QString *fileCompressed*, QString *dir* = `QString()`, bool *recursive* = `true`) `[static]`

OK Comprime la cartella dir nel file fileCompressed, se recursive e true allora comprime anche le sotto cartelle.

Parameters

fileCompressed	The name of the archive.
dir	The directory to compress.
recursive	Whether to pack the subdirectories as well, or just regular files.

Returns

true if success, false otherwise.

Se la funzione fallisce restituisce false e cancella il file che si e tentato di creare.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- la compressione di un file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 338 of file JlCompress.cpp.

References QuaZip::close(), compressSubDir(), QuaZip::getZipError(), QuaZip::mdCreate, and QuaZip::open().

```
338                                                                                 {
339     // Creo lo zip
340     QuaZip zip(fileCompressed);
341     QDir().mkpath(QFileInfo(fileCompressed).absolutePath());
342     if(!zip.open(QuaZip::mdCreate)) {
343         QFile::remove(fileCompressed);
344         return false;
345     }
346
347     // Aggiungo i file e le sotto cartelle
348     if (!compressSubDir(&zip,dir,dir,recursive)) {
349         QFile::remove(fileCompressed);
350         return false;
```

```
    }

    // Chiudo il file zip
    zip.close();
    if(zip.getZipError()!=0) {
        QFile::remove(fileCompressed);
        return false;
    }

    return true;
}
```

Here is the call graph for this function:

12.20.2.2 bool JICompress::compressFile (QuaZip * *zip*, QString *fileName*, QString *fileDest*) [static], [private]

OK Comprime il file fileName, nell'oggetto zip, con il nome fileDest.

Parameters

zip	Opened zip to compress the file to.
fileName	The full path to the source file.
fileDest	The full name of the file inside the archive.

Returns

true if success, false otherwise.

La funzione fallisce se:

- zip==NULL;
- l'oggetto zip e stato aperto in una modalita non compatibile con l'aggiunta di file;
- non e possibile aprire il file d'origine;
- non e possibile creare il file all'interno dell'oggetto zip;
- si e rilevato un errore nella copia dei dati;
- non e stato possibile chiudere il file all'interno dell'oggetto zip;

Definition at line 53 of file JICompress.cpp.

References QuaZipFile::close(), copyData(), QuaZip::getMode(), QuaZipFile::getZipError(), QuaZip::mdAdd, QuaZip::mdAppend, QuaZip::mdCreate, QuaZipFile::open(), and UNZ_OK.

Referenced by compressFile(), compressFiles(), and compressSubDir().

```
                                                                    {
    // zip: oggetto dove aggiungere il file
    // fileName: nome del file reale
    // fileDest: nome del file all'interno del file compresso

    // Controllo l'apertura dello zip
    if (!zip) return false;
    if (zip->getMode()!=QuaZip::mdCreate &&
        zip->getMode()!=QuaZip::mdAppend &&
        zip->getMode()!=QuaZip::mdAdd) return false;

    // Apro il file originale
    QFile inFile;
    inFile.setFileName(fileName);
    if(!inFile.open(QIODevice::ReadOnly)) return false;

    // Apro il file risulato
    QuaZipFile outFile(zip);
    if(!outFile.open(QIODevice::WriteOnly, QuaZipNewInfo(fileDest, inFile.fileName()))) return
    false;

    // Copio i dati
    if (!copyData(inFile, outFile) || outFile.getZipError()!=UNZ_OK) {
        return false;
    }

    // Chiudo i file
    outFile.close();
    if (outFile.getZipError()!=UNZ_OK) return false;
    inFile.close();

    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.20.2.3 bool JICompress::compressFile (QString *fileCompressed*, QString *file*) [static]

OK Comprime il file fileName nel file fileCompressed.

Parameters

fileCompressed	The name of the archive.
file	The file to compress.

Returns

true if success, false otherwise.

Se la funzione fallisce restituisce false e cancella il file che si e tentato di creare.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- la compressione del file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 263 of file JICompress.cpp.

References QuaZip::close(), compressFile(), QuaZip::getZipError(), QuaZip::mdCreate, and QuaZip::open().

```
263                                                                 {
264     // Creo lo zip
265     QuaZip zip(fileCompressed);
266     QDir().mkpath(QFileInfo(fileCompressed).absolutePath());
267     if(!zip.open(QuaZip::mdCreate)) {
268         QFile::remove(fileCompressed);
269         return false;
270     }
271
272     // Aggiungo il file
273     if (!compressFile(&zip,file,QFileInfo(file).fileName())) {
274         QFile::remove(fileCompressed);
275         return false;
276     }
277
278     // Chiudo il file zip
279     zip.close();
280     if(zip.getZipError()!=0) {
281         QFile::remove(fileCompressed);
282         return false;
283     }
284
285     return true;
286 }
```

Here is the call graph for this function:

12.20.2.4 bool JlCompress::compressFiles (QString *fileCompressed*, QStringList *files*) [static]

OK Comprime i file specificati in files nel file fileCompressed.

Parameters

fileCompressed	The name of the archive.
files	The file list to compress.

Returns

true if success, false otherwise.

Se la funzione fallisce restituisce false e cancella il file che si e tentato di creare.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- la compressione di un file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 298 of file JICompress.cpp.

References QuaZip::close(), compressFile(), QuaZip::getZipError(), QuaZip::mdCreate, and QuaZip::open().

```
298                                                                                 {
299     // Creo lo zip
300     QuaZip zip(fileCompressed);
301     QDir().mkpath(QFileInfo(fileCompressed).absolutePath());
302     if(!zip.open(QuaZip::mdCreate)) {
303         QFile::remove(fileCompressed);
304         return false;
305     }
306
307     // Comprimo i file
308     QFileInfo info;
309     Q_FOREACH (QString file, files) {
310         info.setFile(file);
311         if (!info.exists() || !compressFile(&zip,file,info.fileName())) {
312             QFile::remove(fileCompressed);
313             return false;
314         }
315     }
316
317     // Chiudo il file zip
318     zip.close();
319     if(zip.getZipError()!=0) {
320         QFile::remove(fileCompressed);
321         return false;
322     }
323
324     return true;
325 }
```

Here is the call graph for this function:

12.20.2.5 bool JlCompress::compressSubDir (QuaZip * *zip,* QString *dir,* QString *origDir,* bool *recursive* = `true`) [static],[private]

OK Comprime la cartella dir nel file fileCompressed, se recursive e true allora comprime anche le sotto cartelle.

Parameters

parentZip	Opened zip containing the parent directory.
dir	The full path to the directory to pack.
parentDir	The full path to the directory corresponding to the root of the ZIP.
recursive	Whether to pack sub-directories as well or only files.

Returns

true if success, false otherwise.

I nomi dei file preceduti dal path creato togliendo il pat della cartella origDir al path della cartella dir. Se la funzione fallisce restituisce false e cancella il file che si e tentato di creare.

La funzione fallisce se:

- zip==NULL;
- l'oggetto zip e stato aperto in una modalita non compatibile con l'aggiunta di file;
- la cartella dir non esiste;
- la compressione di una sotto cartella fallisce (1);
- la compressione di un file fallisce; (1) La funzione si richiama in maniera ricorsiva per comprimere le sotto cartelle dunque gli errori di compressione di una sotto cartella sono gli stessi di questa funzione.

Definition at line 103 of file JICompress.cpp.

References QuaZipFile::close(), compressFile(), QuaZip::getMode(), QuaZip::getZipName(), QuaZip::mdAdd, QuaZip::mdAppend, QuaZip::mdCreate, and QuaZipFile::open().

Referenced by compressDir().

```
103                                                                                                    {
104     // zip: oggetto dove aggiungere il file
105     // dir: cartella reale corrente
106     // origDir: cartella reale originale
107     // (path(dir)-path(origDir)) = path interno all'oggetto zip
108
109     // Controllo l'apertura dello zip
110     if (!zip) return false;
111     if (zip->getMode()!=QuaZip::mdCreate &&
112         zip->getMode()!=QuaZip::mdAppend &&
113         zip->getMode()!=QuaZip::mdAdd) return false;
114
115     // Controllo la cartella
116     QDir directory(dir);
117     if (!directory.exists()) return false;
118
119     QDir origDirectory(origDir);
120     if (dir != origDir) {
121         QuaZipFile dirZipFile(zip);
122         if (!dirZipFile.open(QIODevice::WriteOnly,
123             QuaZipNewInfo(origDirectory.relativeFilePath(dir) + "/", dir), 0, 0, 0)) {
124                 return false;
125         }
126         dirZipFile.close();
127     }
128
129
130     // Se comprimo anche le sotto cartelle
131     if (recursive) {
132         // Per ogni sotto cartella
133         QFileInfoList files = directory.entryInfoList(QDir::AllDirs|QDir::NoDotAndDotDot);
134         Q_FOREACH (QFileInfo file, files) {
135             // Comprimo la sotto cartella
136             if(!compressSubDir(zip,file.absoluteFilePath(),origDir,recursive)) return false;
137         }
138     }
139
140     // Per ogni file nella cartella
141     QFileInfoList files = directory.entryInfoList(QDir::Files);
142     Q_FOREACH (QFileInfo file, files) {
143         // Se non e un file o e il file compresso che sto creando
```

```
        if(!file.isFile()||file.absoluteFilePath()==zip->getZipName()) continue;

        // Creo il nome relativo da usare all'interno del file compresso
        QString filename = origDirectory.relativeFilePath(file.absoluteFilePath());

        // Comprimo il file
        if (!compressFile(zip,file.absoluteFilePath(),filename)) return false;
    }

    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.20.2.6 QStringList JICompress::extractDir (QString *fileCompressed*, QString *dir* = `QString()`) [static]

OK Estrae il file fileCompressed nella cartella dir.

Parameters

fileCompressed	The name of the archive.
dir	The directory to extract to, the current directory if left empty.

Returns

The list of the full paths of the files extracted, empty on failure.

Se dir = "" allora il file viene estratto nella cartella corrente. Se la funzione fallisce cancella i file che si e tentato di estrarre. Restituisce i nomi assoluti dei file estratti.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- la compressione di un file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 451 of file JICompress.cpp.

References QuaZip::close(), extractFile(), QuaZip::getCurrentFileName(), QuaZip::getZipError(), QuaZip::goToFirstFile(), QuaZip::goToNextFile(), QuaZip::mdUnzip, QuaZip::open(), and removeFile().

```
451                                                                 {
452     // Apro lo zip
453     QuaZip zip(fileCompressed);
454     if(!zip.open(QuaZip::mdUnzip)) {
455         return QStringList();
456     }
457
458     QDir directory(dir);
459     QStringList extracted;
460     if (!zip.goToFirstFile()) {
461         return QStringList();
462     }
463     do {
464         QString name = zip.getCurrentFileName();
465         QString absFilePath = directory.absoluteFilePath(name);
466         if (!extractFile(&zip, "", absFilePath)) {
467             removeFile(extracted);
468             return QStringList();
469         }
470         extracted.append(absFilePath);
471     } while (zip.goToNextFile());
472
473     // Chiudo il file zip
474     zip.close();
475     if(zip.getZipError()!=0) {
476         removeFile(extracted);
477         return QStringList();
478     }
479
480     return extracted;
481 }
```

Here is the call graph for this function:

12.20.2.7 bool JlCompress::extractFile (QuaZip * *zip*, QString *fileName*, QString *fileDest*) [static],[private]

OK Estrae il file fileName, contenuto nell'oggetto zip, con il nome fileDest.

Parameters

zip	The opened zip archive to extract from.
fileName	The full name of the file to extract.
fileDest	The full path to the destination file.

Returns

true if success, false otherwise.

Se la funzione fallisce restituisce false e cancella il file che si e tentato di estrarre.

La funzione fallisce se:

- zip==NULL;
- l'oggetto zip e stato aperto in una modalita non compatibile con l'estrazione di file;
- non e possibile aprire il file all'interno dell'oggetto zip;
- non e possibile creare il file estratto;
- si e rilevato un errore nella copia dei dati (1);
- non e stato possibile chiudere il file all'interno dell'oggetto zip (1);

(1): prima di uscire dalla funzione cancella il file estratto.

Definition at line 170 of file JlCompress.cpp.

References QuaZipFile::close(), copyData(), QuaZip::getCurrentFileInfo(), QuaZip::getMode(), QuaZipFileInfo64::getPermissions(), QuaZipFile::getZipError(), QuaZip::mdUnzip, QuaZipFile::open(), removeFile(), QuaZip::setCurrentFile(), and UNZ_OK.

Referenced by extractDir(), extractFile(), and extractFiles().

```
170                                                                                 {
171     // zip: oggetto dove aggiungere il file
172     // filename: nome del file reale
173     // fileincompress: nome del file all'interno del file compresso
174
175     // Controllo l'apertura dello zip
176     if (!zip) return false;
177     if (zip->getMode()!=QuaZip::mdUnzip) return false;
178
179     // Apro il file compresso
180     if (!fileName.isEmpty())
181         zip->setCurrentFile(fileName);
182     QuaZipFile inFile(zip);
183     if(!inFile.open(QIODevice::ReadOnly) || inFile.getZipError()!=UNZ_OK) return false;
184
185     // Controllo esistenza cartella file risultato
186     QDir curDir;
187     if (fileDest.endsWith('/')) {
188         if (!curDir.mkpath(fileDest)) {
189             return false;
190         }
191     } else {
192         if (!curDir.mkpath(QFileInfo(fileDest).absolutePath())) {
193             return false;
194         }
195     }
196
197     QuaZipFileInfo64 info;
198     if (!zip->getCurrentFileInfo(&info))
199         return false;
200
201     QFile::Permissions srcPerm = info.getPermissions();
202     if (fileDest.endsWith('/') && QFileInfo(fileDest).isDir()) {
203         if (srcPerm != 0) {
```

```
            QFile(fileDest).setPermissions(srcPerm);
        }
        return true;
    }

    // Apro il file risultato
    QFile outFile;
    outFile.setFileName(fileDest);
    if(!outFile.open(QIODevice::WriteOnly)) return false;

    // Copio i dati
    if (!copyData(inFile, outFile) || inFile.getZipError()!=UNZ_OK) {
        outFile.close();
        removeFile(QStringList(fileDest));
        return false;
    }
    outFile.close();

    // Chiudo i file
    inFile.close();
    if (inFile.getZipError()!=UNZ_OK) {
        removeFile(QStringList(fileDest));
        return false;
    }

    if (srcPerm != 0) {
        outFile.setPermissions(srcPerm);
    }
    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.20.2.8 QString JlCompress::extractFile (QString *fileCompressed*, QString *fileName*, QString *fileDest* = `QString()`) `[static]`

OK Estrae il file fileName, contenuto nel file fileCompressed, con il nome fileDest.

Parameters

fileCompressed	The name of the archive.
fileName	The file to extract.
fileDest	The destination file, assumed to be identical to *file* if left empty.

Returns

The list of the full paths of the files extracted, empty on failure.

Se fileDest = "" allora il file viene estratto con lo stesso nome con cui e stato compresso. Se la funzione fallisce cancella il file che si e tentato di estrarre. Restituisce il nome assoluto del file estratto.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- l'estrazione del file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 377 of file JlCompress.cpp.

References QuaZip::close(), extractFile(), QuaZip::getZipError(), QuaZip::mdUnzip, QuaZip::open(), and removeFile().

```
377                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
378     // Apro lo zip
379     QuaZip zip(fileCompressed);
380     if(!zip.open(QuaZip::mdUnzip)) {
381         return QString();
382     }
383
384     // Estraggo il file
385     if (fileDest.isEmpty())
386         fileDest = fileName;
387     if (!extractFile(&zip,fileName,fileDest)) {
388         return QString();
389     }
390
391     // Chiudo il file zip
392     zip.close();
393     if(zip.getZipError()!=0) {
394         removeFile(QStringList(fileDest));
395         return QString();
396     }
397     return QFileInfo(fileDest).absoluteFilePath();
398 }
```

Here is the call graph for this function:

12.20.2.9 QStringList JICompress::extractFiles (QString *fileCompressed,* QStringList *files,* QString *dir* = `QString()`) `[static]`

OK Estrae i file specificati in files, contenuti nel file fileCompressed, nella cartella dir.

Parameters

fileCompressed	The name of the archive.
files	The file list to extract.
dir	The directory to put the files to, the current directory if left empty.

Returns

The list of the full paths of the files extracted, empty on failure.

La struttura a cartelle del file compresso viene rispettata. Se dir = "" allora il file viene estratto nella cartella corrente. Se la funzione fallisce cancella i file che si e tentato di estrarre. Restituisce i nomi assoluti dei file estratti.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- l'estrazione di un file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 412 of file JICompress.cpp.

References QuaZip::close(), extractFile(), QuaZip::getZipError(), QuaZip::mdUnzip, QuaZip::open(), and removeFile().

```
                                                                                                                    {
    // Creo lo zip
    QuaZip zip(fileCompressed);
    if(!zip.open(QuaZip::mdUnzip)) {
        return QStringList();
    }

    // Estraggo i file
    QStringList extracted;
    for (int i=0; i<files.count(); i++) {
        QString absPath = QDir(dir).absoluteFilePath(files.at(i));
        if (!extractFile(&zip, files.at(i), absPath)) {
            removeFile(extracted);
            return QStringList();
        }
        extracted.append(absPath);
    }

    // Chiudo il file zip
    zip.close();
    if(zip.getZipError()!=0) {
        removeFile(extracted);
        return QStringList();
    }

    return extracted;
}
```

Here is the call graph for this function:

12.20.2.10 QStringList JlCompress::getFileList (QString *fileCompressed*) [static]

OK Restituisce la lista dei file resenti nel file compresso fileCompressed.

Returns

The list of the files in the archive, or, more precisely, the list of the entries, including both files and directories if they are present separately.

Se la funzione fallisce, restituisce un elenco vuoto.

La funzione fallisce se:

- non si riesce ad aprire l'oggetto zip;
- la richiesta di informazioni di un file fallisce;
- non si riesce a chiudere l'oggetto zip;

Definition at line 492 of file JICompress.cpp.

References QuaZip::close(), QuaZip::getCurrentFileInfo(), QuaZip::getZipError(), QuaZip::goToFirstFile(), QuaZip::goToNextFile(), QuaZip::mdUnzip, QuaZipFileInfo64::name, and QuaZip::open().

```
492                                                         {
493     // Apro lo zip
494     QuaZip* zip = new QuaZip(QFileInfo(fileCompressed).absoluteFilePath());
495     if(!zip->open(QuaZip::mdUnzip)) {
496         delete zip;
497         return QStringList();
498     }
499
500     // Estraggo i nomi dei file
501     QStringList lst;
502     QuaZipFileInfo64 info;
503     for(bool more=zip->goToFirstFile(); more; more=zip->
      goToNextFile()) {
504       if(!zip->getCurrentFileInfo(&info)) {
505           delete zip;
506           return QStringList();
507       }
508       lst << info.name;
509       //info.name.toLocal8Bit().constData()
510     }
511
512     // Chiudo il file zip
513     zip->close();
514     if(zip->getZipError()!=0) {
515         delete zip;
516         return QStringList();
517     }
518     delete zip;
519
520     return lst;
521 }
```

Here is the call graph for this function:

12.20.2.11 bool JlCompress::removeFile (QStringList *listFile*) [static],[private]

Rimuove i file il cui nome e specificato all'interno di listFile.

Parameters

listFile	The list of files to remove.

Returns

true if success, false otherwise.

Restituisce true se tutti i file sono stati cancellati correttamente, attenzione perche puo restituire false anche se alcuni file non esistevano e si e tentato di cancellarli.

Definition at line 241 of file JlCompress.cpp.

Referenced by extractDir(), extractFile(), and extractFiles().

```
241                                                 {
242     bool ret = true;
243     // Per ogni file
244     for (int i=0; i<listFile.count(); i++) {
245         // Lo elimino
246         ret = ret && QFile::remove(listFile.at(i));
247     }
248     return ret;
249 }
```

Here is the caller graph for this function:

The documentation for this class was generated from the following files:

- src/ckb/quazip/JlCompress.h
- src/ckb/quazip/JlCompress.cpp

12.21 Kb Class Reference

```
#include <src/ckb/kb.h>
```

Inheritance diagram for Kb:

Collaboration diagram for Kb:

Public Slots

- void frameUpdate ()
- void autoSave ()

Signals

- void infoUpdated ()
- void profileAdded ()
- void profileRenamed ()
- void modeRenamed ()
- void profileChanged ()
- void modeChanged (bool spontaneous)
- void fwUpdateProgress (int current, int total)
- void fwUpdateFinished (bool succeeded)

Public Member Functions

- KeyMap::Model model () const
- bool isKeyboard () const
- bool isMouse () const
- KbProfile ∗ hwProfile ()
- void hwProfile (KbProfile ∗newHwProfile)
- void fwUpdate (const QString &path)
- KbProfile ∗ currentProfile ()
- const QList< KbProfile ∗ > & profiles () const
- void profiles (const QList< KbProfile ∗ > &newProfiles)
- void appendProfile (KbProfile ∗newProfile)
- int indexOf (KbProfile ∗profile)
- KbProfile ∗ find (const QUuid &id)
- KbMode ∗ currentMode ()

- KbLight * currentLight ()
- KbBind * currentBind ()
- KbPerf * currentPerf ()
- void setCurrentProfile (KbProfile *profile, bool spontaneous=true)
- void setCurrentMode (KbProfile *profile, KbMode *mode, bool spontaneous=true)
- void setCurrentMode (KbProfile *profile, int index, bool spontaneous=true)
- void setCurrentMode (KbMode *mode, bool spontaneous=true)
- KbProfile * newProfile ()
- KbProfile * newProfile (KbProfile *other)
- KbMode * newMode ()
- KbMode * newMode (KbMode *other)
- void load ()
- void save ()
- bool needsSave () const
- void hwSave ()
- int getMacroNumber ()

  For usage with macro definions, these two params must only be readable. So there are no setters.
- QString getMacroPath ()

  getMacroPath returns the macroPath (e.g. /dev/input/ckb1/notify), which we have saved in the constructor. For usage with macro definions, this param must only be readable. So there is no setter.
- ~Kb ()

Static Public Member Functions

- static int frameRate ()
- static void frameRate (int newFrameRate)
- static KeyMap::Layout layout ()
- static void layout (KeyMap::Layout newLayout)
- static bool dither ()
- static void dither (bool newDither)
- static bool macroDelay ()
- static void macroDelay (bool flag)

  Kb::macroDelay handles the UI-Element macroBox. Sends a command to the keyboard to switch on or off the delay function on very large macros.
- static bool mouseAccel ()
- static void mouseAccel (bool newAccel)
- static int scrollSpeed ()
- static void scrollSpeed (int newSpeed)

Data Fields

- QString usbModel
- QString usbSerial
- QString features
- QString firmware
- QString pollrate
- bool monochrome
- int hwModeCount

Static Public Attributes

- static const int HWMODE_MAX = 3

Private Slots

- void readNotify (QString line)
- void deleteHw ()
- void deletePrevious ()

Private Member Functions

- Kb (QObject *parent, const QString &path)
- bool isOpen () const
- bool matches (const QString &path, const QString &serial)
- void updateLayout ()
- void writeProfileHeader ()
- KeyMap getKeyMap ()
- void run ()

Private Attributes

- QString devpath

  pathVars devpath is the device root path (e.g. /dev/device/ckb1), cmdpath leads to the daemon input pipe for daemon commands, notifyPath is the standard input monitor for general purpose, macroPath added for a second thread to read macro input.
- QString cmdpath
- QString notifyPath
- QString macroPath
- KbProfile * _currentProfile
- QList< KbProfile * > _profiles
- KbMode * _currentMode
- KeyMap::Model _model
- bool iState [KbPerf::HW_I_COUNT]
- QString prefsPath
- quint64 lastAutoSave
- QString fwUpdPath
- KbProfile * _hwProfile
- KbProfile * prevProfile
- KbMode * prevMode
- QFile cmd
- int notifyNumber

  notifyNumber is the trailing number in the device path.
- int macroNumber
- bool _needsSave
- bool hwLoading [HWMODE_MAX+1]

Static Private Attributes

- static KeyMap::Layout _layout = KeyMap::NO_LAYOUT
- static int _frameRate = 30
- static int _scrollSpeed = 0
- static bool _dither = false
- static bool _mouseAccel = true
- static bool _delay = false

Friends

- class KbManager

12.21.1 Detailed Description

Definition at line 11 of file kb.h.

12.21.2 Constructor & Destructor Documentation

12.21.2.1 Kb::~Kb ( )

<

Todo I don't think, that notifypaths is used somewhere. So why do we have it? If we do not need it, searching for an ununsed notify channel can easy be refactored to a private member function.

Definition at line 141 of file kb.cpp.

References activeDevices, cmd, isOpen(), macroPath, notifyNumber, notifyPaths, and save().

```
141         {
142     // Save settings first
143     save();
144
145     // remove the notify channel from the list of notifyPaths.
148     notifyPaths.remove(macroPath);
149
150     // Kill notification thread and remove node
151     activeDevices.remove(this);
152     if(!isOpen()){
153         terminate();
154         wait(1000);
155         return;
156     }
157     if(notifyNumber > 0)
158         cmd.write(QString("idle\nnotifyoff %1\n").arg(notifyNumber).toLatin1());
159     cmd.flush();
160     terminate();
161     wait(1000);
162     cmd.close();
163 }
```

Here is the call graph for this function:

12.21.2.2 Kb::Kb (QObject * *parent*, const QString & *path*) [private]

<

Todo Is adding notify2 to the notifypaths neccessary?

Definition at line 19 of file kb.cpp.

References _delay, _dither, _frameRate, _layout, _model, _mouseAccel, _scrollSpeed, activeDevices, cmd, cmdpath, features, firmware, KeyMap::getModel(), hwLoading, hwModeCount, infoUpdated(), KeyMap::isISO(), iState, KeyMap::K95, macroNumber, macroPath, monochrome, KeyMap::NO_MODEL, notifyNumber, notifyPath, notifyPathMutex, notifyPaths, pollrate, prefsPath, usbModel, and usbSerial.

```
19                                                  :
20     QThread(parent), features("N/A"), firmware("N/A"),
       pollrate("N/A"), monochrome(false),
21     devpath(path), cmdpath(path + "/cmd"), notifyPath(path + "/notify1"),
       macroPath(path + "/notify2"),
22     _currentProfile(0), _currentMode(0), _model(
       KeyMap::NO_MODEL),
23     lastAutoSave(QDateTime::currentMSecsSinceEpoch()),
24     _hwProfile(0), prevProfile(0), prevMode(0),
25     cmd(cmdpath), notifyNumber(1), macroNumber(2),
       _needsSave(false)
26 {
27     memset(iState, 0, sizeof(iState));
28     memset(hwLoading, 0, sizeof(hwLoading));
29
30     // Get the features, model, serial number, FW version (if available), and poll rate (if available) from
       /dev nodes
31     QFile ftpath(path + "/features"), mpath(path + "/model"), spath(path + "/serial"), fwpath(path + "
       /fwversion"), ppath(path + "/pollrate");
32     if(ftpath.open(QIODevice::ReadOnly)){
33         features = ftpath.read(1000);
34         features = features.trimmed();
35         ftpath.close();
36         // Read model from features (first word: vendor, second word: product)
37         QStringList list = features.split(" ");
38         if(list.length() < 2)
39             return;
40         _model = KeyMap::getModel(list[1]);
41         if(_model == KeyMap::NO_MODEL)
42             return;
43     } else
44         // Bail if features aren't readable
45         return;
46     if(features.contains("monochrome"))
47         monochrome = true;
48     if(mpath.open(QIODevice::ReadOnly)){
49         usbModel = mpath.read(100);
50         usbModel = usbModel.remove("Corsair").remove("Gaming").remove("Keyboard").remove("
       Mouse").remove("Bootloader").trimmed();
51         mpath.close();
52     }
53     if(usbModel == "")
54         usbModel = "Keyboard";
55     if(spath.open(QIODevice::ReadOnly)){
56         usbSerial = spath.read(100);
57         usbSerial = usbSerial.trimmed().toUpper();
58         spath.close();
59     }
60     if(usbSerial == "")
61         usbSerial = "Unknown-" + usbModel;
62     if(features.contains("fwversion") && fwpath.open(QIODevice::ReadOnly)){
63         firmware = fwpath.read(100);
64         firmware = QString::number(firmware.trimmed().toInt() / 100., 'f', 2);
65         fwpath.close();
66     }
67     if(features.contains("pollrate") && ppath.open(QIODevice::ReadOnly)){
68         pollrate = ppath.read(100);
69         pollrate = pollrate.trimmed();
70         ppath.close();
71     }
72
73     prefsPath = "Devices/" + usbSerial;
74
75     hwModeCount = (_model == KeyMap::K95) ? 3 : 1;
76     // Open cmd in non-blocking mode so that it doesn't lock up if nothing is reading
77     // (e.g. if the daemon crashed and didn't clean up the node)
78     int fd = open(cmdpath.toLatin1().constData(), O_WRONLY | O_NONBLOCK);
79     if(!cmd.open(fd, QIODevice::WriteOnly, QFileDevice::AutoCloseHandle))
80         return;
```

```

    // Find an available notification node (if none is found, take notify1)
    {
        QMutexLocker locker(&notifyPathMutex);
        for(int i = 1; i < 10; i++){
            QString notify = QString(path + "/notify%1").arg(i);
            if(!QFile::exists(notify) && !notifyPaths.contains(notify)){
                notifyNumber = i;
                notifyPath = notify;
                break;
            }
        }
        notifyPaths.insert(notifyPath);
    }
    cmd.write(QString("notifyon %1\n").arg(notifyNumber).toLatin1());
    cmd.flush();

    // Again, find an available notification node for macro definition
    // (if none is found, take notify2)
    {
        QMutexLocker locker(&notifyPathMutex);
        for(int i = 1; i < 10; i++){
            QString notify = QString(path + "/notify%1").arg(i);
            if(!QFile::exists(notify) && !notifyPaths.contains(notify)){
                macroNumber = i;
                macroPath = notify;
                break;
            }
        }
        notifyPaths.insert(notifyPath);
    }
    // Activate device, apply settings, and ask for hardware profile
    cmd.write(QString("fps %1\n").arg(_frameRate).toLatin1());
    cmd.write(QString("dither %1\n").arg(static_cast<int>(_dither)).toLatin1());
    cmd.write(QString("\ndelay %1\n").arg(_delay? "on" : "off").toLatin1());
#ifdef Q_OS_MACX
    // Write ANSI/ISO flag to daemon (OSX only)
    cmd.write("layout ");
    cmd.write(KeyMap::isISO(_layout) ? "iso" : "ansi");
    // Also OSX only: scroll speed and mouse acceleration
    cmd.write(QString("accel %1\n").arg(QString(_mouseAccel ? "on" : "off")).toLatin1());
    cmd.write(QString("scrollspeed %1\n").arg(_scrollSpeed).toLatin1());
#endif
    cmd.write(QString("\nactive\n@%1 get :hwprofileid").arg(notifyNumber).toLatin1());
    hwLoading[0] = true;
    for(int i = 0; i < hwModeCount; i++){
        cmd.write(QString(" mode %1 get :hwid").arg(i + 1).toLatin1());
        hwLoading[i + 1] = true;
    }
    // Ask for current indicator and key state
    cmd.write(" get :i :keys\n");
    cmd.flush();

    emit infoUpdated();
    activeDevices.insert(this);

    // Start a separate thread to read from the notification node
    start();
}
```

Here is the call graph for this function:

12.21.3 Member Function Documentation

12.21.3.1 void Kb::appendProfile (KbProfile * *newProfile*) [inline]

Definition at line 60 of file kb.h.

References _needsSave, and _profiles.

Referenced by KbProfileDialog::on_profileList_itemClicked().

```
60 { _needsSave = true; _profiles.append(newProfile); }
```

Here is the caller graph for this function:

12.21.3.2 void Kb::autoSave ( ) [slot]

Definition at line 289 of file kb.cpp.

References CkbSettings::isBusy(), lastAutoSave, needsSave(), and save().

```
289                 {
290     quint64 now = QDateTime::currentMSecsSinceEpoch();
291     if(needsSave() && now >= lastAutoSave + 15 * 1000 && !
      CkbSettings::isBusy()){
292         save();
293         lastAutoSave = now;
294     }
295 }
```

Here is the call graph for this function:

12.21.3.3 KbBind* Kb::currentBind ( ) [inline]

Definition at line 67 of file kb.h.

References _currentMode, and KbMode::bind().

Referenced by KbWidget::modeChanged().

```
67 { return !_currentMode ? 0 : _currentMode->bind(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.4 KbLight* Kb::currentLight ( ) [inline]

Definition at line 66 of file kb.h.

References _currentMode, and KbMode::light().

Referenced by KbWidget::modeChanged().

```
66 { return !_currentMode ? 0 : _currentMode->light(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.5 KbMode* Kb::currentMode ( ) [inline]

Definition at line 65 of file kb.h.

References _currentMode.

Referenced by KbWidget::modeChanged().

```
65 { return _currentMode; }
```

Here is the caller graph for this function:

12.21.3.6 KbPerf* Kb::currentPerf ( ) [inline]

Definition at line 68 of file kb.h.

References _currentMode, and KbMode::perf().

Referenced by KbWidget::modeChanged().

```
68 { return !_currentMode ? 0 : _currentMode->perf(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.7 KbProfile* Kb::currentProfile ( ) [inline]

Definition at line 56 of file kb.h.

References _currentProfile.

Referenced by KeyAction::keyEvent(), KbWidget::modeChanged(), KbWidget::modeIcon(), KbWidget::modesList_reordered(), KbWidget::on_modesList_currentItemChanged(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemClicked(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemChanged(), KbWidget::profileChanged(), KbProfileDialog::repopulate(), and KbWidget::updateProfileList().

```
56 { return _currentProfile; }
```

Here is the caller graph for this function:

12.21.3.8 void Kb::deleteHw ( ) [private],[slot]

Definition at line 441 of file kb.cpp.

References _hwProfile.

Referenced by hwProfile().

```
441                 {
442     disconnect(_hwProfile, SIGNAL(destroyed()), this, SLOT(deleteHw()));
443     _hwProfile = 0;
444 }
```

Here is the caller graph for this function:

12.21.3.9 void Kb::deletePrevious ( ) [private],[slot]

Definition at line 426 of file kb.cpp.

References prevMode.

Referenced by frameUpdate(), and hwSave().

```
426                         {
427     disconnect(prevMode, SIGNAL(destroyed()), this, SLOT(deletePrevious()));
428     prevMode = 0;
429 }
```

Here is the caller graph for this function:

12.21.3.10 static bool Kb::dither ( ) [inline],[static]

Definition at line 33 of file kb.h.

References _dither.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and ExtraSettingsWidget::on_ditherBox_clicked().

```
33 { return _dither; }
```

Here is the caller graph for this function:

12.21.3.11 void Kb::dither (bool *newDither*) [static]

Definition at line 204 of file kb.cpp.

References _dither, activeDevices, and cmd.

```
204                                 {
205     if(newDither == _dither)
206         return;
207     _dither = newDither;
208     // Update all devices
209     foreach(Kb* kb, activeDevices){
210         kb->cmd.write(QString("dither %1\n").arg(static_cast<int>(newDither)).toLatin1());
211         kb->cmd.flush();
212     }
213 }
```

12.21.3.12 KbProfile* Kb::find (const QUuid & *id*) [inline]

Definition at line 62 of file kb.h.

References _profiles, UsbId::guid, and KbProfile::id().

Referenced by KbProfileDialog::on_profileList_currentItemChanged(), KbProfileDialog::on_profileList_customContextMenuRequested(), and KbProfileDialog::profileList_reordered().

```
62 { foreach(KbProfile* profile, _profiles) { if(profile->id().
      guid == id) return profile; } return 0; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.13 static int Kb::frameRate ( ) [inline], [static]

Definition at line 27 of file kb.h.

References _frameRate.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and ExtraSettingsWidget::on_fpsBox_valueChanged().

```
27 { return _frameRate; }
```

Here is the caller graph for this function:

12.21.3.14 void Kb::frameRate (int *newFrameRate*) [static]

Definition at line 165 of file kb.cpp.

References _frameRate, activeDevices, cmd, and KbManager::fps().

```
165                                 {
166     KbManager::fps(newFrameRate);
167     // If the rate has changed, send to all devices
168     if(newFrameRate == _frameRate)
169         return;
170     _frameRate = newFrameRate;
171     foreach(Kb* kb, activeDevices){
172         kb->cmd.write(QString("fps %1\n").arg(newFrameRate).toLatin1());
173         kb->cmd.flush();
174     }
175 }
```

Here is the call graph for this function:

12.21.3.15 void Kb::frameUpdate ( ) [slot]

Definition at line 375 of file kb.cpp.

References _currentMode, _currentProfile, KbPerf::applyIndicators(), KbMode::bind(), KbLight::close(), cmd, deletePrevious(), KbLight::frameUpdate(), KbProfile::indexOf(), KbLight::isStarted(), iState, KbMode::light(), monochrome, notifyNumber, KbLight::open(), KbMode::perf(), prevMode, prevProfile, KbBind::update(), KbPerf::update(), and writeProfileHeader().

```
375                     {
376     // Advance animation frame
377     if(!_currentMode)
378         return;
379     KbLight* light = _currentMode->light();
380     KbBind* bind = _currentMode->bind();
381     KbPerf* perf = _currentMode->perf();
382     if(!light->isStarted()){
383         // Don't do anything until the animations are started
384         light->open();
385         return;
386     }
387
388     // Stop animations on the previously active mode (if any)
389     bool changed = false;
390     if(prevMode != _currentMode){
391         if(prevMode){
392             prevMode->light()->close();
393             disconnect(prevMode, SIGNAL(destroyed()), this, SLOT(
      deletePrevious()));
394         }
395         prevMode = _currentMode;
396         connect(prevMode, SIGNAL(destroyed()), this, SLOT(deletePrevious()));
397         changed = true;
398     }
399
400     // If the profile has changed, update it
401     if(prevProfile != _currentProfile){
402         writeProfileHeader();
403         cmd.write(" ");
404         prevProfile = _currentProfile;
405     }
406
407     // Update current mode
408     int index = _currentProfile->indexOf(_currentMode);
409     // ckb-daemon only has 6 modes: 3 hardware, 3 non-hardware. Beyond mode six, switch back to four.
410     // e.g. 1, 2, 3, 4, 5, 6, 4, 5, 6, 4, 5, 6 ...
411     if(index >= 6)
412         index = 3 + index % 3;
413
414     // Send lighting/binding to driver
415     cmd.write(QString("mode %1 switch ").arg(index + 1).toLatin1());
416     perf->applyIndicators(index, iState);
417     light->frameUpdate(cmd, monochrome);
418     cmd.write(QString("\n@%1 ").arg(notifyNumber).toLatin1());
419     bind->update(cmd, changed);
420     cmd.write(" ");
421     perf->update(cmd, changed);
422     cmd.write("\n");
423     cmd.flush();
424 }
```

Here is the call graph for this function:

12.21.3.16 void Kb::fwUpdate (const QString & *path*)

Definition at line 365 of file kb.cpp.

References cmd, fwUpdPath, and notifyNumber.

Referenced by FwUpgradeDialog::on_actionButton_clicked().

```
365                                     {
366     fwUpdPath = path;
367     // Write the active command to ensure it's not ignored
368     cmd.write("active");
369     cmd.write(QString(" @%1 ").arg(notifyNumber).toLatin1());
370     cmd.write("fwupdate ");
371     cmd.write(path.toLatin1());
372     cmd.write("\n");
373 }
```

Here is the caller graph for this function:

12.21.3.17 void Kb::fwUpdateFinished (bool *succeeded*) [signal]

Definition at line 277 of file moc_kb.cpp.

Referenced by readNotify().

```
278 {
279     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
280     QMetaObject::activate(this, &staticMetaObject, 7, _a);
281 }
```

Here is the caller graph for this function:

12.21.3.18 void Kb::fwUpdateProgress (int *current*, int *total*) [signal]

Definition at line 270 of file moc_kb.cpp.

Referenced by readNotify().

```
271 {
272     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)), const_cast<void*>(
      reinterpret_cast<const void*>(&_t2)) };
273     QMetaObject::activate(this, &staticMetaObject, 6, _a);
274 }
```

Here is the caller graph for this function:

12.21.3.19 KeyMap Kb::getKeyMap ( ) [private]

Definition at line 756 of file kb.cpp.

References _layout, and _model.

Referenced by hwSave(), load(), newMode(), newProfile(), readNotify(), setCurrentProfile(), and updateLayout().

```
756                     {
757     return KeyMap(_model, _layout);
758 }
```

Here is the caller graph for this function:

12.21.3.20 int Kb::getMacroNumber ( ) [inline]

getMacroNumber returns the macroNumber, which we have saved in the constructor. For usage with macro definions, this param must only be readable. So there is no setter.

Returns

The Number is returned as int.

Definition at line 97 of file kb.h.

References macroNumber.

Referenced by KbBind::getMacroNumber().

```
97 { return macroNumber; }
```

Here is the caller graph for this function:

12.21.3.21 QString Kb::getMacroPath ( ) [inline]

Returns

The absolute path as String

Definition at line 106 of file kb.h.

References macroPath.

Referenced by KbBind::getMacroPath().

```
106 { return macroPath; }
```

Here is the caller graph for this function:

12.21.3.22 KbProfile* Kb::hwProfile ( ) [inline]

Definition at line 46 of file kb.h.

References _hwProfile.

Referenced by hwSave(), KbWidget::modeIcon(), KbProfileDialog::on_profileList_customContextMenuRequested(), readNotify(), KbProfileDialog::repopulate(), and KbWidget::updateProfileList().

```
46 { return _hwProfile; }
```

Here is the caller graph for this function:

12.21.3.23 void Kb::hwProfile (KbProfile * *newHwProfile*)

Definition at line 431 of file kb.cpp.

References _hwProfile, and deleteHw().

```
{
    if(_hwProfile == newHwProfile)
        return;
    if(_hwProfile)
        disconnect(_hwProfile, SIGNAL(destroyed()), this, SLOT(deleteHw()));
    _hwProfile = newHwProfile;
    if(_hwProfile)
        connect(_hwProfile, SIGNAL(destroyed()), this, SLOT(deleteHw()));
}
```

Here is the call graph for this function:

12.21.3.24 void Kb::hwSave ( )

Definition at line 297 of file kb.cpp.

References _currentMode, _currentProfile, _hwProfile, KbProfile::append(), KbLight::base(), KbLight::close(), cmd, deletePrevious(), getKeyMap(), UsbId::guidString(), hwModeCount, UsbId::hwModified, hwProfile(), KbProfile::id(), KbMode::id(), KbMode::light(), KbProfile::modeCount(), KbProfile::modes(), UsbId::modified, UsbId::modifiedString(), monochrome, KbMode::name(), KbMode::perf(), prevMode, KbProfile::setNeedsSave(), KbMode::setNeedsSave(), KbPerf::update(), and writeProfileHeader().

Referenced by KbWidget::on_hwSaveButton_clicked(), and KbProfileDialog::on_profileList_customContextMenuRequested().

```
{
    if(!_currentProfile)
        return;
    // Close active lighting (if any)
    if(prevMode){
        prevMode->light()->close();
        deletePrevious();
    }
    hwProfile(_currentProfile);
    _hwProfile->id().hwModified = _hwProfile->id().modified;
    _hwProfile->setNeedsSave();
    // Re-send the current profile from scratch to ensure consistency
    writeProfileHeader();
    // Make sure there are enough modes
    while(_currentProfile->modeCount() < hwModeCount)
        _currentProfile->append(new KbMode(this, getKeyMap()));
    // Write only the base colors of each mode, no animations
    for(int i = 0; i < hwModeCount; i++){
        KbMode* mode = _currentProfile->modes()[i];
        cmd.write(QString("\nmode %1").arg(i + 1).toLatin1());
        KbLight* light = mode->light();
        KbPerf* perf = mode->perf();
        if(mode == _currentMode)
            cmd.write(" switch");
        // Write the mode name and ID
        cmd.write(" name ");
        cmd.write(QUrl::toPercentEncoding(mode->name()));
        cmd.write(" id ");
        cmd.write(mode->id().guidString().toLatin1());
        cmd.write(" ");
        cmd.write(mode->id().modifiedString().toLatin1());
        cmd.write(" ");
        // Write lighting and performance
        light->base(cmd, true, monochrome);
```

```
        cmd.write(" ");
        perf->update(cmd, true, false);
        // Update mode ID
        mode->id().hwModified = mode->id().modified;
        mode->setNeedsSave();
    }
    cmd.write("\n");

    // Save the profile to memory
    cmd.write("hwsave\n");
    cmd.flush();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.25 int Kb::indexOf (KbProfile * *profile*) [inline]

Definition at line 61 of file kb.h.

References _profiles.

Referenced by KbProfileDialog::on_profileList_customContextMenuRequested().

```
61 { return _profiles.indexOf(profile); }
```

Here is the caller graph for this function:

12.21.3.26 void Kb::infoUpdated ( ) [signal]

Definition at line 233 of file moc_kb.cpp.

Referenced by Kb(), load(), and updateLayout().

```
234 {
235     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
236 }
```

Here is the caller graph for this function:

12.21.3.27 bool Kb::isKeyboard ( ) const [inline]

Definition at line 23 of file kb.h.

References _model, and KeyMap::isKeyboard().

Referenced by KbWidget::KbWidget().

```
23 { return KeyMap::isKeyboard(_model); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.28 bool Kb::isMouse ( ) const [inline]

Definition at line 24 of file kb.h.

References _model, and KeyMap::isMouse().

Referenced by KbWidget::KbWidget(), and readNotify().

```
24 { return KeyMap::isMouse(_model); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.29 bool Kb::isOpen ( ) const [inline], [private]

Definition at line 147 of file kb.h.

References cmd.

Referenced by KbManager::scanKeyboards(), and ~Kb().

```
147 { return cmd.isOpen(); }
```

Here is the caller graph for this function:

12.21.3.30 static KeyMap::Layout Kb::layout ( ) [inline], [static]

Definition at line 30 of file kb.h.

References _layout.

Referenced by LayoutDialog::LayoutDialog(), SettingsWidget::on_layoutBox_activated(), and SettingsWidget::-SettingsWidget().

```
30 { return _layout; }
```

Here is the caller graph for this function:

12.21.3.31 void Kb::layout (KeyMap::Layout *newLayout*) [static]

Definition at line 177 of file kb.cpp.

References _layout, activeDevices, KeyMap::NO_LAYOUT, and updateLayout().

```
177                                     {
178     if(newLayout == KeyMap::NO_LAYOUT || newLayout == _layout)
179         return;
180     _layout = newLayout;
181     // Update all devices
182     foreach(Kb* kb, activeDevices)
183         kb->updateLayout();
184 }
```

Here is the call graph for this function:

12.21.3.32 void Kb::load ( )

Definition at line 241 of file kb.cpp.

References _needsSave, _profiles, getKeyMap(), infoUpdated(), prefsPath, profileAdded(), setCurrentProfile(), and CkbSettings::value().

Referenced by KbManager::scanKeyboards().

```
241             {
242     if(prefsPath.isEmpty())
243         return;
244     _needsSave = false;
245     CkbSettings settings(prefsPath);
246     // Read profiles
247     KbProfile* newCurrentProfile = 0;
248     QString current = settings.value("CurrentProfile").toString().trimmed().toUpper();
249     foreach(QString guid, settings.value("Profiles").toString().split(" ")){
250         guid = guid.trimmed().toUpper();
251         if(guid != ""){
252             KbProfile* profile = new KbProfile(this, getKeyMap(), settings, guid
    );
253             _profiles.append(profile);
254             if(guid == current || !newCurrentProfile)
255                 newCurrentProfile = profile;
256         }
257     }
258     if(newCurrentProfile)
259         setCurrentProfile(newCurrentProfile);
260     else {
261         // If nothing was loaded, load the demo profile
262         QSettings demoSettings(":/txt/demoprofile.conf", QSettings::IniFormat, this);
263         CkbSettings cSettings(demoSettings);
264         KbProfile* demo = new KbProfile(this, getKeyMap(), cSettings, "
    {BA7FC152-2D51-4C26-A7A6-A036CC93D924}");
265         _profiles.append(demo);
266         setCurrentProfile(demo);
267     }
268
269     emit infoUpdated();
270     emit profileAdded();
271 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.33 static bool Kb::macroDelay ( ) [inline], [static]

Definition at line 36 of file kb.h.

References _delay.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and ExtraSettingsWidget::on_delayBox_clicked().

```
36 { return _delay; }
```

Here is the caller graph for this function:

12.21.3.34 void Kb::macroDelay (bool *flag*) [static]

Parameters

flag	true: Switch on delay function, else switch off

Definition at line 787 of file kb.cpp.

References _delay, activeDevices, and cmd.

```
787                                 {
788     _delay = flag;
789
790     foreach(Kb* kb, activeDevices){
791         kb->cmd.write(QString("\ndelay %1\n").arg(flag? "on" : "off").toLatin1());
792     }
793 }
```

12.21.3.35 bool Kb::matches (const QString & *path,* const QString & *serial*) [inline],[private]

Definition at line 157 of file kb.h.

References devpath, and usbSerial.

Referenced by KbManager::scanKeyboards().

```
157 { return path.trimmed() == devpath.trimmed() && usbSerial == serial.trimmed().toUpper(); }
```

Here is the caller graph for this function:

12.21.3.36 void Kb::modeChanged (bool *spontaneous*) [signal]

Definition at line 263 of file moc_kb.cpp.

Referenced by setCurrentMode().

```
264 {
265     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
266     QMetaObject::activate(this, &staticMetaObject, 5, _a);
267 }
```

Here is the caller graph for this function:

12.21.3.37 KeyMap::Model Kb::model ( ) const [inline]

Definition at line 22 of file kb.h.

References _model.

```
22 { return _model; }
```

12.21.3.38 void Kb::modeRenamed ( ) [signal]

Definition at line 251 of file moc_kb.cpp.

Referenced by readNotify().

```
252 {
253     QMetaObject::activate(this, &staticMetaObject, 3, Q_NULLPTR);
254 }
```

Here is the caller graph for this function:

12.21.3.39 static bool Kb::mouseAccel ( ) [inline],[static]

Definition at line 39 of file kb.h.

References _mouseAccel.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and ExtraSettingsWidget::on_mAccelBox_clicked().

```
39 { return _mouseAccel; }
```

Here is the caller graph for this function:

12.21.3.40 void Kb::mouseAccel (bool *newAccel*) [static]

Definition at line 215 of file kb.cpp.

References _mouseAccel, activeDevices, and cmd.

```
215                                 {
216     if(newAccel == _mouseAccel)
217         return;
218     _mouseAccel = newAccel;
219 #ifdef Q_OS_MACX
220     // Update all devices
221     foreach(Kb* kb, activeDevices){
222         kb->cmd.write(QString("accel %1\n").arg(QString(newAccel ? "on" : "off")).toLatin1());
223         kb->cmd.flush();
224     }
225 #endif
226 }
```

12.21.3.41 bool Kb::needsSave ( ) const

Definition at line 344 of file kb.cpp.

References _needsSave, _profiles, and KbProfile::needsSave().

Referenced by autoSave().

```
344                         {
345     if(_needsSave)
346         return true;
347     foreach(const KbProfile* profile, _profiles){
348         if(profile->needsSave())
349             return true;
350     }
351     return false;
352 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.42 KbMode* Kb::newMode ( ) [inline]

Definition at line 79 of file kb.h.

References getKeyMap().

Referenced by KbWidget::on_modesList_customContextMenuRequested(), and KbWidget::on_modesList_itemClicked().

```
79 { return new KbMode(this, getKeyMap()); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.43 KbMode* Kb::newMode (KbMode * *other*) [inline]

Definition at line 80 of file kb.h.

References getKeyMap().

```
80 { return new KbMode(this, getKeyMap(), *other); }
```

Here is the call graph for this function:

12.21.3.44 KbProfile* Kb::newProfile ( ) [inline]

Definition at line 77 of file kb.h.

References getKeyMap().

Referenced by KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_-itemClicked(), and readNotify().

```
77 { return new KbProfile(this, getKeyMap()); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.45 KbProfile* Kb::newProfile (KbProfile * *other*) [inline]

Definition at line 78 of file kb.h.

References getKeyMap().

```
78 { return new KbProfile(this, getKeyMap(), *other); }
```

Here is the call graph for this function:

12.21.3.46 void Kb::profileAdded ( ) [signal]

Definition at line 239 of file moc_kb.cpp.

Referenced by load(), and readNotify().

```
240 {
241     QMetaObject::activate(this, &staticMetaObject, 1, Q_NULLPTR);
242 }
```

Here is the caller graph for this function:

12.21.3.47 void Kb::profileChanged ( ) [signal]

Definition at line 257 of file moc_kb.cpp.

Referenced by readNotify(), and setCurrentMode().

```
258 {
259     QMetaObject::activate(this, &staticMetaObject, 4, Q_NULLPTR);
260 }
```

Here is the caller graph for this function:

12.21.3.48 void Kb::profileRenamed ( ) [signal]

Definition at line 245 of file moc_kb.cpp.

Referenced by readNotify().

```
246 {
247     QMetaObject::activate(this, &staticMetaObject, 2, Q_NULLPTR);
248 }
```

Here is the caller graph for this function:

12.21.3.49 const QList<KbProfile*>& Kb::profiles ( ) const [inline]

Definition at line 58 of file kb.h.

References _profiles.

Referenced by KbWidget::on_profileBox_activated(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::profileList_reordered(), KbProfileDialog::repopulate(), and KbWidget::updateProfileList().

```
58 { return _profiles; }
```

Here is the caller graph for this function:

12.21.3.50 void Kb::profiles (const QList< KbProfile * > & *newProfiles*) [inline]

Definition at line 59 of file kb.h.

References _needsSave, and _profiles.

```
59 { _needsSave = true; _profiles = newProfiles; }
```

12.21.3.51 void Kb::readNotify (QString *line*) [private], [slot]

Definition at line 471 of file kb.cpp.

References _currentMode, _currentProfile, _hwProfile, _needsSave, _profiles, KbPerf::angleSnap(), KbLight::animKeypress(), KbProfile::append(), KbMode::bind(), cmd, KbLight::color(), KbPerf::curDpiIdx(), KbPerf::dpi(), KbPerf::DPI_COUNT, KbPerf::dpiColor(), KbPerf::dpiEnabled(), fwUpdateFinished(), fwUpdateProgress(), fwUpdPath, getKeyMap(), UsbId::guid, hwLoading, HWMODE_MAX, hwModeCount, UsbId::hwModifiedString(), hwProfile(), KbProfile::id(), KbMode::id(), KbProfile::indexOf(), isMouse(), iState, KbBind::keyEvent(), KbPerf::liftHeight(), KbMode::light(), KbProfile::modeCount(), modeRenamed(), KbProfile::modes(), UsbId::modifiedString(), KbProfile::move(), KbProfile::name(), KbMode::name(), newProfile(), notifyNumber, KbMode::perf(), profileAdded(), profileChanged(), profileRenamed(), setCurrentProfile(), KbProfile::setNeedsSave(), and KbMode::setNeedsSave().

```
471                                 {
472     QStringList components = line.trimmed().split(" ");
473     if(components.count() < 2)
474         return;
475     if(components[0] == "key"){
476         // Key event
477         QString key = components[1];
478         if(key.length() < 2)
479             return;
480         QString keyName = key.mid(1);
481         bool keyPressed = (key[0] == '+');
482         KbMode* mode = _currentMode;
483         if(mode){
484             mode->light()->animKeypress(keyName, keyPressed);
485             mode->bind()->keyEvent(keyName, keyPressed);
486         }
487     } else if(components[0] == "i"){
488         // Indicator event
489         QString i = components[1];
490         if(i.length() < 2)
491             return;
492         QString iName = i.mid(1);
493         bool on = (i[0] == '+');
494         if(iName == "num")
495             iState[0] = on;
496         else if(iName == "caps")
497             iState[1] = on;
498         else if(iName == "scroll")
499             iState[2] = on;
500     } else if(components[0] == "hwprofileid"){
501         // Hardware profile ID
502         if(components.count() < 3)
503             return;
504         // Find the hardware profile in the list of profiles
505         QString guid = components[1];
506         QString modified = components[2];
507         KbProfile* newProfile = 0;
508         foreach(KbProfile* profile, _profiles){
509             if(profile->id().guid == guid){
510                 newProfile = profile;
511                 break;
512             }
513         }
514         // If it wasn't found, create it
515         if(!newProfile){
516             newProfile = new KbProfile(this, getKeyMap(), guid, modified);
517             hwLoading[0] = true;
518             cmd.write(QString("@%1 get :hwprofilename\n").arg(notifyNumber).toLatin1());
519             cmd.flush();
520         } else {
521             // If it's been updated, fetch its name
522             if(newProfile->id().hwModifiedString() != modified){
523                 newProfile->id().modifiedString(modified);
524                 newProfile->id().hwModifiedString(modified);
525                 newProfile->setNeedsSave();
```

```
                if(hwLoading[0]){
                    cmd.write(QString("@%1 get :hwprofilename\n").arg(notifyNumber).toLatin1());
                    cmd.flush();
                }
            } else {
                hwLoading[0] = false;
            }
        }
        hwProfile(newProfile);
        emit profileAdded();
        if(_hwProfile == _currentProfile)
            emit profileChanged();
    } else if(components[0] == "hwprofilename"){
        // Hardware profile name
        QString name = QUrl::fromPercentEncoding(components[1].toUtf8());
        if(!_hwProfile || !hwLoading[0])
            return;
        QString oldName = _hwProfile->name();
        if(!(oldName.length() >= name.length() && oldName.left(name.length()) == name)){
            // Don't change the name if it's a truncated version of what we already have
            _hwProfile->name(name);
            emit profileRenamed();
        }
    } else if(components[0] == "mode"){
        // Mode-specific data
        if(components.count() < 4)
            return;
        int mode = components[1].toInt() - 1;
        if(components[2] == "hwid"){
            if(components.count() < 5 || mode >= HWMODE_MAX || !_hwProfile)
                return;
            // Hardware mode ID
            QString guid = components[3];
            QString modified = components[4];
            // Look for this mode in the hardware profile
            KbMode* hwMode = 0;
            bool isUpdated = false;
            foreach(KbMode* kbMode, _hwProfile->modes()){
                if(kbMode->id().guid == guid){
                    hwMode = kbMode;
                    if(kbMode->id().hwModifiedString() != modified){
                        // Update modification time
                        hwMode->id().modifiedString(modified);
                        hwMode->id().hwModifiedString(modified);
                        hwMode->setNeedsSave();
                        isUpdated = true;
                    } else {
                        hwLoading[mode + 1] = false;
                    }
                    break;
                }
            }
            // If it wasn't found, add it
            if(!hwMode){
                isUpdated = true;
                hwMode = new KbMode(this, getKeyMap(), guid, modified);
                _hwProfile->append(hwMode);
                // If the hardware profile now contains enough modes to be added to the list, do so
                if(!_profiles.contains(_hwProfile) && _hwProfile->modeCount() >= hwModeCount){
                    _profiles.append(_hwProfile);
                    _needsSave = true;
                    emit profileAdded();
                    if(!_currentProfile)
                        setCurrentProfile(_hwProfile);
                }
            }
            if(hwLoading[mode + 1] && isUpdated){
                // If the mode isn't in the right place, move it
                int index = _hwProfile->indexOf(hwMode);
                if(mode < _hwProfile->modeCount() && index != mode)
                    _hwProfile->move(index, mode);
                // Fetch the updated data
                cmd.write(QString("@%1 mode %2 get :hwname :hwrgb").arg(notifyNumber).arg(mode + 1).toLatin1());
                if(isMouse())
                    cmd.write(" :hwdpi :hwdpisel :hwlift :hwsnap");
                cmd.write("\n");
                cmd.flush();
            }
        } else if(components[2] == "hwname"){
            // Mode name - update list
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
```

```
            KbMode* hwMode = _hwProfile->modes()[mode];
            QString name = QUrl::fromPercentEncoding(components[3].toUtf8());
            QString oldName = hwMode->name();
            if(!(oldName.length() >= name.length() && oldName.left(name.length()) == name)){
                // Don't change the name if it's a truncated version of what we already have
                hwMode->name(name);
                if(_hwProfile == _currentProfile)
                    emit modeRenamed();
            }
        } else if(components[2] == "hwrgb"){
            // RGB - set mode lighting
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
            KbMode* kbmode = _hwProfile->modes()[mode];
            KbLight* light = kbmode->light();
            // Scan the input for colors
            QColor lightColor = QColor();
            for(int i = 3; i < components.count(); i++){
                QString comp = components[i];
                if(comp.indexOf(":") < 0){
                    // No ":" - single hex constant
                    bool ok;
                    int rgb = comp.toInt(&ok, 16);
                    if(ok)
                        light->color(QColor::fromRgb((QRgb)rgb));
                } else {
                    // List of keys ("a,b:xxxxxx"). Parse color first
                    QStringList set = comp.split(":");
                    bool ok;
                    int rgb = set[1].toInt(&ok, 16);
                    if(ok){
                        QColor color = QColor::fromRgb((QRgb)rgb);
                        // Parse keys
                        QStringList keys = set[0].split(",");
                        foreach(QString key, keys){
                            if(key == "light")
                                // Extrapolate the Light key to the M-keys and Lock key, since those will be set to black on hwsave
                                lightColor = color;
                            if(key.startsWith("dpi") && key.length() > 3){
                                // DPI levels go to the KbPerf object instead of KbLight
                                bool ok = false;
                                int index = key.mid(3).toInt(&ok);
                                if(ok)
                                    kbmode->perf()->dpiColor(index, color);
                                continue;
                            }
                            light->color(key, color);
                        }
                    }
                }
            }
            if(lightColor.isValid()){
                light->color("mr", lightColor);
                light->color("m1", lightColor);
                light->color("m2", lightColor);
                light->color("m3", lightColor);
                light->color("lock", lightColor);
            }
        } else if(components[2] == "hwdpi"){
            // DPI settings
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
            KbPerf* perf = _hwProfile->modes()[mode]->perf();
            // Read the rest of the line as stage:x,y
            foreach(QString comp, components.mid(3)){
                QStringList dpi = comp.split(':');
                if(dpi.length() != 2)
                    continue;
                QStringList xy = dpi[1].split(',');
                int x, y;
                bool off = false;
                if(xy.length() < 2){
                    // If the right side only has one parameter, set both X and Y
                    if(xy[0] == "off")
                        off = true;
                    else
                        x = y = xy[0].toInt();
                } else {
                    x = xy[0].toInt();
                    y = xy[1].toInt();
                }
                // Set DPI for this stage
                int index = dpi[0].toInt();
                if(off){
```

```
                    perf->dpiEnabled(index, false);
                    // If all DPIs have been disabled, turn them back on
                    bool allOff = true;
                    for(int i = 1; i < KbPerf::DPI_COUNT; i++){
                        if(perf->dpiEnabled(i)){
                            allOff = false;
                            break;
                        }
                    }
                    if(allOff){
                        for(int i = 1; i < KbPerf::DPI_COUNT; i++)
                            perf->dpiEnabled(i, true);
                    }
                } else {
                    perf->dpiEnabled(index, true);
                    perf->dpi(index, QPoint(x, y));
                }
            }
        } else if(components[2] == "hwdpisel"){
            // Hardware DPI selection (0...5)
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
            KbPerf* perf = _hwProfile->modes()[mode]->perf();
            int idx = components[3].toInt();
            if(idx < 1)
                idx = 1;
            if(idx >= KbPerf::DPI_COUNT)
                idx = KbPerf::DPI_COUNT - 1;
            perf->curDpiIdx(idx);
        } else if(components[2] == "hwlift"){
            // Mouse lift height (1...5)
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
            KbPerf* perf = _hwProfile->modes()[mode]->perf();
            perf->liftHeight((KbPerf::height)components[3].toInt());
        } else if(components[3] == "hwsnap"){
            // Mouse angle snapping ("on" or "off")
            if(!_hwProfile || _hwProfile->modeCount() <= mode || mode >= HWMODE_MAX || !hwLoading[mode + 1])
                return;
            KbPerf* perf = _hwProfile->modes()[mode]->perf();
            perf->angleSnap(components[3] == "on");
        }
    } else if(components[0] == "fwupdate"){
        // Firmware update progress
        if(components.count() < 3)
            return;
        // Make sure path is the same
        if(components[1] != fwUpdPath)
            return;
        QString res = components[2];
        if(res == "invalid" || res == "fail")
            emit fwUpdateFinished(false);
        else if(res == "ok")
            emit fwUpdateFinished(true);
        else {
            // "xx/yy" indicates progress
            if(!res.contains("/"))
                return;
            QStringList numbers = res.split("/");
            emit fwUpdateProgress(numbers[0].toInt(), numbers[1].toInt());
        }
    }
}
```

Here is the call graph for this function:

12.21.3.52 void Kb::run ( ) [private]

Definition at line 446 of file kb.cpp.

References notifyPath, notifyPathMutex, and notifyPaths.

```
446             {
447     QFile notify(notifyPath);
448     // Wait a small amount of time for the node to open (100ms)
```

```
    QThread::usleep(100000);
    if(!notify.open(QIODevice::ReadOnly)){
        // If it's still not open, try again before giving up (1s at a time, 10s total)
        QThread::usleep(900000);
        for(int i = 1; i < 10; i++){
            if(notify.open(QIODevice::ReadOnly))
                break;
            QThread::sleep(1);
        }
        if(!notify.isOpen())
            return;
    }
    // Read data from notification node
    QByteArray line;
    while(notify.isOpen() && (line = notify.readLine()).length() > 0){
        QString text = QString::fromUtf8(line);
        metaObject()->invokeMethod(this, "readNotify", Qt::QueuedConnection, Q_ARG(QString, text));
    }
    QMutexLocker locker(&notifyPathMutex);
    notifyPaths.remove(notifyPath);
}
```

12.21.3.53 void Kb::save ( )

Definition at line 273 of file kb.cpp.

References _currentProfile, _needsSave, _profiles, UsbId::guidString(), KbProfile::id(), prefsPath, KbProfile::save(), and CkbSettings::setValue().

Referenced by autoSave(), KbWidget::on_hwSaveButton_clicked(), KbManager::scanKeyboards(), and ~Kb().

```
            {
    if(prefsPath.isEmpty())
        return;
    _needsSave = false;
    CkbSettings settings(prefsPath, true);
    QString guids, currentGuid;
    foreach(KbProfile* profile, _profiles){
        guids.append(" " + profile->id().guidString());
        if(profile == _currentProfile)
            currentGuid = profile->id().guidString();
        profile->save(settings);
    }
    settings.setValue("CurrentProfile", currentGuid);
    settings.setValue("Profiles", guids.trimmed());
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.54 static int Kb::scrollSpeed ( ) [inline],[static]

Definition at line 42 of file kb.h.

References _scrollSpeed.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sAccelBox_clicked(), and ExtraSettingsWidget::on_sSpeedBox_valueChanged().

```
42 { return _scrollSpeed; }
```

Here is the caller graph for this function:

12.21.3.55 void Kb::scrollSpeed (int *newSpeed*) [static]

Definition at line 228 of file kb.cpp.

References _scrollSpeed, activeDevices, and cmd.

```
228                                 {
229     if(newSpeed == _scrollSpeed)
230         return;
231     _scrollSpeed = newSpeed;
232 #ifdef Q_OS_MACX
233     // Update all devices
234     foreach(Kb* kb, activeDevices){
235         kb->cmd.write(QString("scrollspeed %1\n").arg(newSpeed).toLatin1());
```

```
        kb->cmd.flush();
    }
#endif
}
```

12.21.3.56 void Kb::setCurrentMode (KbProfile * *profile*, KbMode * *mode*, bool *spontaneous* = `true`)

Definition at line 769 of file kb.cpp.

References _currentMode, _currentProfile, _needsSave, KbProfile::currentMode(), modeChanged(), and profileChanged().

Referenced by KeyAction::keyEvent(), KbWidget::on_modesList_currentItemChanged(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemClicked(), and setCurrentProfile().

```
769                                                                 {
770     if(_currentProfile != profile){
771         _currentProfile = profile;
772         _needsSave = true;
773         emit profileChanged();
774     }
775     if(_currentMode != mode || _currentProfile->
      currentMode() != mode){
776         _currentProfile->currentMode(_currentMode = mode);
777         _needsSave = true;
778         emit modeChanged(spontaneous);
779     }
780 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.57 void Kb::setCurrentMode (KbProfile * *profile*, int *index*, bool *spontaneous* = `true`) `[inline]`

Definition at line 73 of file kb.h.

References KbProfile::modes(), and setCurrentMode().

Referenced by setCurrentMode().

```
73 { setCurrentMode(profile, profile->modes()[index], spontaneous); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.58 void Kb::setCurrentMode (KbMode * *mode*, bool *spontaneous* = `true`) [inline]

Definition at line 74 of file kb.h.

References _currentProfile, and setCurrentMode().

Referenced by setCurrentMode().

```
74 { setCurrentMode(_currentProfile, mode, spontaneous); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.59 void Kb::setCurrentProfile (KbProfile * *profile*, bool *spontaneous* = `true`)

Definition at line 760 of file kb.cpp.

References KbProfile::append(), KbProfile::currentMode(), getKeyMap(), hwModeCount, KbProfile::modeCount(), KbProfile::modes(), and setCurrentMode().

Referenced by load(), KbWidget::on_profileBox_activated(), KbProfileDialog::on_profileList_currentItemChanged(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemClicked(), and readNotify().

```
760                                                                 {
761     while(profile->modeCount() < hwModeCount)
762         profile->append(new KbMode(this, getKeyMap()));
763     KbMode* mode = profile->currentMode();
764     if(!mode)
765         profile->currentMode(mode = profile->modes().first());
766     setCurrentMode(profile, mode, spontaneous);
767 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.60 void Kb::updateLayout ( ) [private]

Definition at line 186 of file kb.cpp.

References _currentProfile, _hwProfile, _layout, _profiles, KbLight::close(), cmd, getKeyMap(), infoUpdated(), KeyMap::isISO(), KbProfile::keyMap(), KbMode::light(), and KbProfile::modes().

Referenced by layout().

```
186                     {
187 #ifdef Q_OS_MACX
188     // Write ANSI/ISO flag to daemon (OSX only)
189     cmd.write("layout ");
190     cmd.write(KeyMap::isISO(_layout) ? "iso" : "ansi");
191     cmd.write("\n");
192     cmd.flush();
193 #endif
194     foreach(KbProfile* profile, _profiles)
195         profile->keyMap(getKeyMap());
196     if(_hwProfile && !_profiles.contains(_hwProfile))
197         _hwProfile->keyMap(getKeyMap());
198     // Stop all animations as they'll need to be restarted
199     foreach(KbMode* mode, _currentProfile->modes())
200         mode->light()->close();
201     emit infoUpdated();
202 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.3.61 void Kb::writeProfileHeader ( ) [private]

Definition at line 354 of file kb.cpp.

References _currentProfile, cmd, UsbId::guidString(), KbProfile::id(), UsbId::modifiedString(), and KbProfile::name().

Referenced by frameUpdate(), and hwSave().

```
354                             {
355     cmd.write("eraseprofile");
356     // Write the profile name and ID
357     cmd.write(" profilename ");
358     cmd.write(QUrl::toPercentEncoding(_currentProfile->name()));
359     cmd.write(" profileid ");
360     cmd.write(_currentProfile->id().guidString().toLatin1());
361     cmd.write(" ");
362     cmd.write(_currentProfile->id().modifiedString().toLatin1());
363 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.21.4 Friends And Related Function Documentation

12.21.4.1 friend class KbManager [friend]

Definition at line 142 of file kb.h.

12.21.5 Field Documentation

12.21.5.1 KbMode* Kb::_currentMode [private]

Definition at line 169 of file kb.h.

Referenced by currentBind(), currentLight(), currentMode(), currentPerf(), frameUpdate(), hwSave(), readNotify(), and setCurrentMode().

12.21.5.2 KbProfile* Kb::_currentProfile [private]

Definition at line 167 of file kb.h.

Referenced by currentProfile(), frameUpdate(), hwSave(), readNotify(), save(), setCurrentMode(), updateLayout(), and writeProfileHeader().

12.21.5.3 bool Kb::_delay = false [static], [private]

Definition at line 198 of file kb.h.

Referenced by Kb(), and macroDelay().

12.21.5.4 bool Kb::_dither = false [static], [private]

Definition at line 165 of file kb.h.

Referenced by dither(), and Kb().

12.21.5.5 int Kb::_frameRate = 30 [static], [private]

Definition at line 164 of file kb.h.

Referenced by frameRate(), and Kb().

12.21.5.6 KbProfile* Kb::_hwProfile [private]

Definition at line 183 of file kb.h.

Referenced by deleteHw(), hwProfile(), hwSave(), readNotify(), and updateLayout().

12.21.5.7 KeyMap::Layout Kb::_layout = KeyMap::NO_LAYOUT [static], [private]

Definition at line 161 of file kb.h.

Referenced by getKeyMap(), Kb(), layout(), and updateLayout().

12.21.5.8 KeyMap::Model Kb::_model [private]

Definition at line 171 of file kb.h.

Referenced by getKeyMap(), isKeyboard(), isMouse(), Kb(), and model().

12.21.5.9 bool Kb::_mouseAccel = true [static], [private]

Definition at line 165 of file kb.h.

Referenced by Kb(), and mouseAccel().

12.21.5.10 bool Kb::_needsSave [private]

Definition at line 201 of file kb.h.

Referenced by appendProfile(), load(), needsSave(), profiles(), readNotify(), save(), and setCurrentMode().

12.21.5.11 QList<KbProfile*> Kb::_profiles [private]

Definition at line 168 of file kb.h.

Referenced by appendProfile(), find(), indexOf(), load(), needsSave(), profiles(), readNotify(), save(), and updateLayout().

12.21.5.12 int Kb::_scrollSpeed = 0 [static], [private]

Definition at line 164 of file kb.h.

Referenced by Kb(), and scrollSpeed().

12.21.5.13 QFile Kb::cmd [private]

Definition at line 191 of file kb.h.

Referenced by dither(), frameRate(), frameUpdate(), fwUpdate(), hwSave(), isOpen(), Kb(), macroDelay(), mouseAccel(), readNotify(), scrollSpeed(), updateLayout(), writeProfileHeader(), and ~Kb().

12.21.5.14 QString Kb::cmdpath [private]

Definition at line 155 of file kb.h.

Referenced by Kb().

12.21.5.15 QString Kb::devpath [private]

Definition at line 155 of file kb.h.

Referenced by matches().

12.21.5.16 QString Kb::features

Definition at line 18 of file kb.h.

Referenced by MainWindow::checkFwUpdates(), FwUpgradeDialog::exec(), Kb(), KbWidget::KbWidget(), KbWidget::on_fwUpdButton_clicked(), and KbWidget::updateFwButton().

12.21.5.17 QString Kb::firmware

Definition at line 18 of file kb.h.

Referenced by MainWindow::checkFwUpdates(), KbWidget::devUpdate(), FwUpgradeDialog::FwUpgradeDialog(), Kb(), KbWidget::on_fwUpdButton_clicked(), and KbWidget::updateFwButton().

12.21.5.18 QString Kb::fwUpdPath [private]

Definition at line 181 of file kb.h.

Referenced by fwUpdate(), and readNotify().

12.21.5.19 bool Kb::hwLoading[HWMODE_MAX+1] [private]

Definition at line 205 of file kb.h.

Referenced by Kb(), and readNotify().

12.21.5.20 const int Kb::HWMODE_MAX = 3 [static]

Definition at line 50 of file kb.h.

Referenced by KbPerf::applyIndicators(), and readNotify().

12.21.5.21 int Kb::hwModeCount

Definition at line 49 of file kb.h.

Referenced by hwSave(), Kb(), KbWidget::modeIcon(), KbWidget::on_modesList_customContextMenuRequested(), readNotify(), and setCurrentProfile().

12.21.5.22 bool Kb::iState[KbPerf::HW_I_COUNT] [private]

Definition at line 174 of file kb.h.

Referenced by frameUpdate(), Kb(), and readNotify().

12.21.5.23 quint64 Kb::lastAutoSave [private]

Definition at line 178 of file kb.h.

Referenced by autoSave().

12.21.5.24 int Kb::macroNumber [private]

Definition at line 196 of file kb.h.

Referenced by getMacroNumber(), and Kb().

12.21.5.25 QString Kb::macroPath [private]

Definition at line 155 of file kb.h.

Referenced by getMacroPath(), Kb(), and ~Kb().

12.21.5.26 bool Kb::monochrome

Definition at line 19 of file kb.h.

Referenced by frameUpdate(), hwSave(), Kb(), and KbWidget::KbWidget().

12.21.5.27 int Kb::notifyNumber [private]

Definition at line 194 of file kb.h.

Referenced by frameUpdate(), fwUpdate(), Kb(), readNotify(), and ~Kb().

12.21.5.28 QString Kb::notifyPath [private]

Definition at line 155 of file kb.h.

Referenced by Kb(), and run().

12.21.5.29 QString Kb::pollrate

Definition at line 18 of file kb.h.

Referenced by KbWidget::devUpdate(), and Kb().

12.21.5.30 QString Kb::prefsPath [private]

Definition at line 177 of file kb.h.

Referenced by Kb(), load(), and save().

12.21.5.31 KbMode* Kb::prevMode [private]

Definition at line 186 of file kb.h.

Referenced by deletePrevious(), frameUpdate(), and hwSave().

12.21.5.32 KbProfile* Kb::prevProfile [private]

Definition at line 185 of file kb.h.

Referenced by frameUpdate().

12.21.5.33 QString Kb::usbModel

Definition at line 16 of file kb.h.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), Kb(), KbWidget::name(), and MainWindow::showFwUpdateNotification().

12.21.5.34 QString Kb::usbSerial

Definition at line 16 of file kb.h.

Referenced by KbWidget::devUpdate(), Kb(), and matches().

The documentation for this class was generated from the following files:

- src/ckb/kb.h
- src/ckb/kb.cpp
- src/ckb/release/moc_kb.cpp

12.22 KbAnim Class Reference

```
#include <src/ckb/kbanim.h>
```

Inheritance diagram for KbAnim:

Collaboration diagram for KbAnim:

Public Types

- enum Mode {
  Normal, Add, Subtract, Multiply,
  Divide }

Public Member Functions

- KbAnim (QObject ∗parent, const KeyMap &map, const QUuid id, CkbSettings &settings)
- void save (CkbSettings &settings)
- bool needsSave () const
- KbAnim (QObject ∗parent, const KeyMap &map, const QString &name, const QStringList &keys, const AnimScript ∗script)
- KbAnim (QObject ∗parent, const KeyMap &map, const KbAnim &other)
- const KeyMap & map ()
- void map (const KeyMap &newMap)
- const QStringList & keys ()
- void keys (const QStringList &newKeys)
- bool hasParameter (const QString &name) const
- QVariant parameter (const QString &name) const
- void parameter (const QString &name, const QVariant &value)
- void commitParams ()
- void resetParams ()
- void reInit ()
- void trigger (quint64 timestamp, bool ignoreParameter=false)
- void keypress (const QString &key, bool pressed, quint64 timestamp)
- void stop ()
- bool isActive () const
- bool isRunning () const
- void blend (ColorMap &animMap, quint64 timestamp)
- const QUuid & guid () const

- void newId ()
- const QString & name () const
- void name (const QString &newName)
- float opacity () const
- void opacity (float newOpacity)
- Mode mode () const
- void mode (Mode newMode)
- const AnimScript * script () const
- const QString & scriptName () const

Private Member Functions

- QMap< QString, QVariant > effectiveParams ()
- void updateParams ()
- void catchUp (quint64 timestamp)

Private Attributes

- AnimScript * _script
- QUuid _scriptGuid
- QString _scriptName
- KeyMap _map
- QStringList _keys
- QMap< QString, QVariant > _parameters
- QMap< QString, QVariant > _tempParameters
- QString repeatKey
- quint64 repeatTime
- quint64 kpRepeatTime
- quint64 stopTime
- quint64 kpStopTime
- int repeatMsec
- int kpRepeatMsec
- QUuid _guid
- QString _name
- float _opacity
- Mode _mode
- bool _isActive
- bool _isActiveKp
- bool _needsSave

12.22.1 Detailed Description

Definition at line 11 of file kbanim.h.

12.22.2 Member Enumeration Documentation

12.22.2.1 enum KbAnim::Mode

Enumerator

Normal

Add

Subtract

Multiply

Divide

Definition at line 17 of file kbanim.h.

```
17              {
18          Normal,
19          Add,
20          Subtract,
21          Multiply,
22          Divide
23      };
```

12.22.3 Constructor & Destructor Documentation

12.22.3.1 KbAnim::KbAnim (QObject * *parent,* const KeyMap & *map,* const QUuid *id,* CkbSettings & *settings*)

Definition at line 8 of file kbanim.cpp.

References _guid, _keys, _map, _mode, _name, _opacity, _parameters, _script, _scriptGuid, _scriptName, CkbSettings::childKeys(), AnimScript::copy(), AnimScript::Param::defaultValue, KeyMap::fromStorage(), AnimScript::Param::INVALID, AnimScript::Param::LABEL, AnimScript::Param::name, AnimScript::name(), name(), Normal, AnimScript::param(), AnimScript::paramIterator(), reInit(), AnimScript::Param::type, and CkbSettings::value().

```
8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                :
9       QObject(parent), _script(0), _map(map),
10       repeatTime(0), kpRepeatTime(0), stopTime(0),
        kpStopTime(0), repeatMsec(0), kpRepeatMsec(0),
11       _guid(id), _isActive(false), _isActiveKp(false),
        _needsSave(false)
12  {
13       SGroup group(settings, _guid.toString().toUpper());
14       _keys = settings.value("Keys").toStringList();
15       // Convert key list from storage names if needed
16       if(!settings.value("UseRealNames").toBool()){
17           QMutableListIterator<QString> i(_keys);
18           while(i.hasNext()){
19               i.next();
20               QString& key = i.value();
21               key = _map.fromStorage(key);
22           }
23       }
24       _name = settings.value("Name").toString().trimmed();
25       _opacity = settings.value("Opacity").toString().toDouble();
26       if(_opacity < 0.)
27           _opacity = 0.;
28       else if(_opacity > 1.)
29           _opacity = 1.;
30       bool modeOk = false;
31       _mode = (Mode)metaObject()->enumerator(metaObject()->indexOfEnumerator("Mode")).keysToValue(
        settings.value("BlendMode").toString().toLatin1(), &modeOk);
32       if(!modeOk)
33           _mode = Normal;
34       _scriptName = settings.value("ScriptName").toString().trimmed();
35       _scriptGuid = settings.value("ScriptGuid").toString();
36       {
37           SGroup group(settings, "Parameters");
38           foreach(const QString& param, settings.childKeys())
39               _parameters[param.toLower()] = settings.value(param);
40       }
41
42       if(!_scriptGuid.isNull()){
43           _script = AnimScript::copy(this, _scriptGuid);
44           if(_script){
45               // Remove nonexistant parameters
46               foreach(const QString& name, _parameters.keys()){
47                   AnimScript::Param param = _script->param(name);
48                   if(param.type == AnimScript::Param::INVALID || param.
        type == AnimScript::Param::LABEL)
49                       _parameters.remove(name);
50               }
51               // Add defaults for unset parameters
52               QListIterator<AnimScript::Param> i = _script->paramIterator();
53               while(i.hasNext()){
54                   AnimScript::Param param = i.next();
55                   if(!_parameters.contains(param.name) && param.
        type != AnimScript::Param::LABEL)
```

```
                    _parameters[param.name] = param.defaultValue;
            }
            _scriptName = _script->name();
            reInit();
        }
    }
}
```

Here is the call graph for this function:

12.22.3.2 KbAnim::KbAnim (QObject * *parent,* const KeyMap & *map,* const QString & *name,* const QStringList & *keys,* const AnimScript * *script*)

Definition at line 84 of file kbanim.cpp.

References _parameters, _script, _scriptGuid, _scriptName, AnimScript::Param::defaultValue, AnimScript::guid(), AnimScript::Param::LABEL, AnimScript::Param::name, AnimScript::name(), AnimScript::paramIterator(), reInit(), and AnimScript::Param::type.

```
                :
    QObject(parent),
    _script(AnimScript::copy(this, script->guid())),
   _map(map), _keys(keys),
    repeatTime(0), kpRepeatTime(0), stopTime(0),
   kpStopTime(0), repeatMsec(0), kpRepeatMsec(0),
    _guid(QUuid::createUuid()), _name(name), _opacity(1.),
   _mode(Normal), _isActive(false), _isActiveKp(false),
   _needsSave(true)
{
    if(_script){
        // Set default parameters
        QListIterator<AnimScript::Param> i = _script->paramIterator();
        while(i.hasNext()){
            AnimScript::Param param = i.next();
            if(param.type != AnimScript::Param::LABEL)
                _parameters[param.name] = param.defaultValue;
        }
        _scriptGuid = script->guid();
        _scriptName = script->name();
         reInit();
     }
}
```

Here is the call graph for this function:

12.22.3.3 KbAnim::KbAnim (QObject * *parent,* const KeyMap & *map,* const KbAnim & *other*)

Definition at line 104 of file kbanim.cpp.

References reInit().

```
104                                                                                    :
105     QObject(parent),
106     _script(AnimScript::copy(this, other.script()->
      guid())), _scriptGuid(_script->guid()), _scriptName(
      _script->name()),
107     _map(map), _keys(other._keys), _parameters(other.
      _parameters),
108     repeatTime(0), kpRepeatTime(0), stopTime(0),
      kpStopTime(0), repeatMsec(0), kpRepeatMsec(0),
109     _guid(other._guid), _name(other._name), _opacity(other.
      _opacity), _mode(other._mode), _isActive(false),
      _isActiveKp(false), _needsSave(true)
110 {
111     reInit();
112 }
```

Here is the call graph for this function:

12.22.4 Member Function Documentation

12.22.4.1 void KbAnim::blend (ColorMap & *animMap,* quint64 *timestamp*)

Definition at line 365 of file kbanim.cpp.

References _mode, _opacity, _script, catchUp(), ColorMap::colors(), AnimScript::colors(), ColorMap::count(), AnimScript::frame(), and functions.

Referenced by KbLight::frameUpdate().

```
365                                                    {
366     if(!_script)
367         return;
368
369     // Fetch the next frame from the script
370     catchUp(timestamp);
```

```
    _script->frame(timestamp);

    // Blend the script's map with the current map
    int blendMode = (int)_mode;
    blendFunc blend = functions[blendMode];
    float fOpacity = _opacity / 255.f;  // save some math by pre-dividing the 255 for qAlpha

    const ColorMap& scriptMap = _script->colors();
    int count = animMap.count();
    if(scriptMap.count() != count){
        qDebug() << "Script map didn't match base map (" << count << " vs " << scriptMap.count() << "). This should never happen.";
        return;
    }
    QRgb* background = animMap.colors();
    const QRgb* foreground = scriptMap.colors();
    for(int i = 0; i < count; i++){
        // Mix the colors in with the color map according to blend mode and alpha
        QRgb& bg = background[i];
        QRgb fg = foreground[i];
        int alpha = qAlpha(fg);
        if(alpha == 0)
            continue;
        if(blendMode == 0){
            // Blend: normal
            // This is the most common use case and it requires much less arithmetic
            if(alpha == 255){
                bg = fg;
            } else {
                float r = qRed(bg), g = qGreen(bg), b = qBlue(bg);
                float a = alpha * fOpacity;
                r = r * (1.f - a) + qRed(fg) * a;
                g = g * (1.f - a) + qGreen(fg) * a;
                b = b * (1.f - a) + qBlue(fg) * a;
                bg = qRgb(round(r), round(g), round(b));
            }
        } else {
            // Use blend function
            float r = qRed(bg) / 255.f, g = qGreen(bg) / 255.f, b = qBlue(bg) / 255.f;
            float a = alpha * fOpacity;
            r = r * (1.f - a) + blend(r, qRed(fg) / 255.f) * a;
            g = g * (1.f - a) + blend(g, qGreen(fg) / 255.f) * a;
            b = b * (1.f - a) + blend(b, qBlue(fg) / 255.f) * a;
            bg = qRgb(round(r * 255.f), round(g * 255.f), round(b * 255.f));
        }
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.2 void KbAnim::catchUp (quint64 *timestamp*) [private]

Definition at line 166 of file kbanim.cpp.

References _isActive, _isActiveKp, _script, effectiveParams(), AnimScript::end(), AnimScript::keypress(), kpRepeatMsec, kpRepeatTime, kpStopTime, repeatKey, repeatMsec, repeatTime, AnimScript::retrigger(), and stopTime.

Referenced by blend(), keypress(), and trigger().

```
166                                     {
167     QMap<QString, QVariant> parameters = effectiveParams();
168     // Stop the animation if its time has run out
169     if(stopTime != 0 && timestamp >= stopTime){
170         repeatMsec = repeatTime = 0;
171         if(!parameters.contains("repeat")){
172             // If repeats aren't allowed, stop the animation entirely
173             _script->end();
174             _isActive = false;
175             return;
176         } else
177             // Otherwise, simply stop repeating
178             stopTime = 0;
179     }
180     if(kpStopTime != 0 && timestamp >= kpStopTime){
181         kpRepeatMsec = kpRepeatTime = 0;
182         if(!parameters.contains("kprepeat")){
183             _script->end();
184             _isActiveKp = false;
185             return;
186         } else
187             kpStopTime = 0;
188     }
189
190     // Restart (or start, if there was a delay) the animation if its repeat time is up
191     while(repeatTime > 0 && timestamp >= repeatTime){
192         _script->retrigger(repeatTime);
193         if(repeatMsec <= 0){
194             repeatTime = 0;
195             break;
196         }
197         repeatTime += repeatMsec;
198     }
199     while(kpRepeatTime > 0 && timestamp >= kpRepeatTime){
200         _script->keypress(repeatKey, 1, kpRepeatTime);
201         if(kpRepeatMsec <= 0){
202             kpRepeatTime = 0;
203             break;
204         }
205         kpRepeatTime += kpRepeatMsec;
206     }
207 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.3 void KbAnim::commitParams ( )

Definition at line 121 of file kbanim.cpp.

References _needsSave, _parameters, _tempParameters, and effectiveParams().

Referenced by KbLight::addAnim(), KbAnimWidget::on_propertyButton_clicked(), and KbLight::previewAnim().

```
121                         {
122     _needsSave = true;
123     _parameters = effectiveParams();
124     _tempParameters.clear();
125 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.4 QMap< QString, QVariant > KbAnim::effectiveParams ( ) [private]

Definition at line 138 of file kbanim.cpp.

References _parameters, and _tempParameters.

Referenced by catchUp(), commitParams(), keypress(), reInit(), trigger(), and updateParams().

```
138                                                 {
139     QMap<QString, QVariant> res = _parameters;
140     // Apply all uncommited parameters
141     QMapIterator<QString, QVariant> i(_tempParameters);
142     while(i.hasNext()){
143         i.next();
144         res[i.key()] = i .value();
145     }
146     return res;
147 }
```

Here is the caller graph for this function:

12.22.4.5 const QUuid& KbAnim::guid ( ) const [inline]

Definition at line 71 of file kbanim.h.

References _guid.

Referenced by KbAnimWidget::addAnim(), RebindWidget::applyChanges(), KbLight::findAnim(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::refreshList(), and KbLight::save().

```
71 { return _guid; }
```

Here is the caller graph for this function:

12.22.4.6 bool KbAnim::hasParameter (const QString & *name*) const [inline]

Definition at line 44 of file kbanim.h.

References _parameters.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
44 { return _parameters.contains(name); }
```

Here is the caller graph for this function:

12.22.4.7 bool KbAnim::isActive ( ) const [inline]

Definition at line 63 of file kbanim.h.

References _isActive, and _isActiveKp.

Referenced by KeyAction::keyEvent(), and keypress().

```
63 { return _isActive || _isActiveKp; }
```

Here is the caller graph for this function:

12.22.4.8 bool KbAnim::isRunning ( ) const

Definition at line 325 of file kbanim.cpp.

References _script, and AnimScript::hasFrame().

Referenced by KbLight::isStarted().

```
325                                 {
326     if(!_script)
327         return true;    // If the script wasn't loaded, pretend it's running anyway so it won't lock up
328     return _script->hasFrame();
329 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.9 void KbAnim::keypress (const QString & *key*, bool *pressed*, quint64 *timestamp*)

Definition at line 250 of file kbanim.cpp.

References _isActive, _isActiveKp, _script, catchUp(), effectiveParams(), AnimScript::frame(), isActive(), AnimScript::keypress(), kpRepeatMsec, kpRepeatTime, kpStopTime, repeatKey, repeatMsec, repeatTime, stop(), AnimScript::stop(), and stopTime.

Referenced by KbLight::animKeypress().

```
250                                                                                 {
251     if(!_script)
252         return;
253     QMap<QString, QVariant> parameters = effectiveParams();
254     if(pressed && parameters.value("kpmodestop").toBool()){
255         // If stop on key press is enabled, stop mode-wide animation
256         catchUp(timestamp);
257         _script->stop(timestamp);
258         stopTime = repeatTime = repeatMsec = 0;
259         _isActive = false;
260     } else {
261         if(!parameters.value("kptrigger").toBool())
262             return;
263         catchUp(timestamp);
264     }
265
266     if(pressed){
267         // Key pressed
268         _isActiveKp = true;
269         if(parameters.value("kpmode", 0).toInt() == 2 && isActive())
270             // If mode is start once and a key has already been pressed, do nothing
271             return;
272         int delay = round(parameters.value("kpdelay").toDouble() * 1000.);
273         if(delay > 0){
274             // If delay is enabled, wait to trigger the event
275             timestamp += delay;
276             kpRepeatTime = timestamp;
277         } else
278             _script->keypress(key, pressed, timestamp);
279
280         int repeat = round(parameters.value("kprepeat").toDouble() * 1000.);
281         if(repeat <= 0){
282             // If no repeat allowed, calculate stop time in seconds
283             kpRepeatMsec = -1;
284             double stop = parameters.value("kpstop").toDouble();
285             if(stop <= 0.)
```

```
                kpStopTime = 0;
            else
                kpStopTime = timestamp + round(stop * 1000.);
        } else {
            // If repeat is allowed, calculate stop time in repetitions
            kpRepeatMsec = repeat;
            if(delay <= 0)
                kpRepeatTime = timestamp + repeat;
            int stop = parameters.value("kpstop").toInt();
            if(stop < 0)
                kpStopTime = 0;
            else
                kpStopTime = timestamp + repeat * (1 + stop);
        }
        repeatKey = key;
    } else {
        // Key released
        _isActiveKp = false;
        _script->keypress(key, pressed, timestamp);
        if(parameters.value("kprelease").toBool())
            // Stop repeating keypress if "Stop on key release" is enabled
            kpStopTime = timestamp;
    }
    _script->frame(timestamp);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.10 const QStringList& KbAnim::keys ( ) [inline]

Definition at line 40 of file kbanim.h.

References _keys.

Referenced by KbLight::animKeypress(), KbLightWidget::changeAnim(), KbAnimWidget::on_keyButton_clicked(), and KbAnimWidget::setCurrent().

```
40 { return _keys; }
```

Here is the caller graph for this function:

12.22.4.11 void KbAnim::keys (const QStringList & *newKeys*)

Definition at line 161 of file kbanim.cpp.

References _keys, and reInit().

```
161                                         {
162     _keys = newKeys;
163     reInit();
164 }
```

Here is the call graph for this function:

12.22.4.12 const KeyMap& KbAnim::map ( ) [inline]

Definition at line 37 of file kbanim.h.

References _map.

Referenced by KbLight::map().

```
37 { return _map; }
```

Here is the caller graph for this function:

12.22.4.13 void KbAnim::map (const KeyMap & *newMap*)

Definition at line 156 of file kbanim.cpp.

References _map, and reInit().

```
156                                     {
157     _map = newMap;
158     reInit();
159 }
```

Here is the call graph for this function:

12.22.4.14 Mode KbAnim::mode ( ) const [inline]

Definition at line 77 of file kbanim.h.

References _mode.

Referenced by KbAnimWidget::on_blendBox_activated(), and KbAnimWidget::setCurrent().

```
77 { return _mode; }
```

Here is the caller graph for this function:

12.22.4.15 void KbAnim::mode (Mode *newMode*) [inline]

Definition at line 78 of file kbanim.h.

References _mode, and _needsSave.

```
78 { _needsSave = true; _mode = newMode; }
```

12.22.4.16 const QString& KbAnim::name ( ) const [inline]

Definition at line 73 of file kbanim.h.

References _name.

Referenced by KbAnimWidget::addAnim(), AnimSettingDialog::AnimSettingDialog(), KbAnim(), KbAnimWidget::on_animList_itemChanged(), KbAnimWidget::on_nameBox_textEdited(), parameter(), KbAnimWidget::refreshList(), KbAnimWidget::setCurrent(), and RebindWidget::setSelection().

```
73 { return _name; }
```

Here is the caller graph for this function:

12.22.4.17 void KbAnim::name (const QString & *newName*) [inline]

Definition at line 74 of file kbanim.h.

References _name, and _needsSave.

```
74 { _needsSave = true; _name = newName; }
```

12.22.4.18 bool KbAnim::needsSave ( ) const [inline]

Definition at line 29 of file kbanim.h.

References _needsSave.

Referenced by KbLight::needsSave().

```
29 { return _needsSave; }
```

Here is the caller graph for this function:

12.22.4.19 void KbAnim::newId ( ) [inline]

Definition at line 72 of file kbanim.h.

References _guid, and _needsSave.

Referenced by KbLight::duplicateAnim(), and KbMode::newId().

```
72 { _needsSave = true; _guid = QUuid::createUuid(); }
```

Here is the caller graph for this function:

12.22.4.20 float KbAnim::opacity ( ) const [inline]

Definition at line 75 of file kbanim.h.

References _opacity.

Referenced by KbAnimWidget::on_opacityBox_valueChanged(), and KbAnimWidget::setCurrent().

```
75 { return _opacity; }
```

Here is the caller graph for this function:

12.22.4.21 void KbAnim::opacity (float *newOpacity*) [inline]

Definition at line 76 of file kbanim.h.

References _needsSave, and _opacity.

```
76 { _needsSave = true; _opacity = newOpacity; }
```

12.22.4.22 QVariant KbAnim::parameter (const QString & *name*) const [inline]

Definition at line 45 of file kbanim.h.

References _parameters.

Referenced by KbLight::addAnim(), AnimSettingDialog::AnimSettingDialog(), KbLight::previewAnim(), and AnimSettingDialog::updateParam().

```
45 { return _parameters.value(name); }
```

Here is the caller graph for this function:

12.22.4.23 void KbAnim::parameter (const QString & *name,* const QVariant & *value*)

Definition at line 114 of file kbanim.cpp.

References _script, _tempParameters, AnimScript::hasParam(), name(), and updateParams().

```
114                                                                 {
115     if(!_script->hasParam(name))
116         return;
117     _tempParameters[name] = value;
118     updateParams();
119 }
```

Here is the call graph for this function:

12.22.4.24 void KbAnim::relnit ( )

Definition at line 149 of file kbanim.cpp.

References _isActive, _isActiveKp, _keys, _map, _script, effectiveParams(), AnimScript::init(), and repeatKey.

Referenced by KbAnim(), keys(), map(), KbAnimWidget::on_propertyButton_clicked(), and KbLight::previewAnim().

```
149                     {
150     if(_script)
151         _script->init(_map, _keys, effectiveParams());
152     repeatKey = "";
153     _isActive = _isActiveKp = false;
154 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.25 void KbAnim::resetParams ( )

Definition at line 127 of file kbanim.cpp.

References _tempParameters, and updateParams().

Referenced by KbAnimWidget::on_propertyButton_clicked().

```
127                     {
128     _tempParameters.clear();
129     updateParams();
130 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.26 void KbAnim::save (CkbSettings & *settings*)

Definition at line 64 of file kbanim.cpp.

References _guid, _keys, _mode, _name, _needsSave, _opacity, _parameters, _scriptGuid, _scriptName, CkbSettings::beginGroup(), CkbSettings::endGroup(), and CkbSettings::setValue().

Referenced by KbLight::save().

```
64                                      {
65     _needsSave = false;
66     settings.beginGroup(_guid.toString().toUpper());
67     settings.setValue("UseRealNames", true);
68     settings.setValue("Keys", _keys);
69     settings.setValue("Name", _name);
70     settings.setValue("Opacity", QString::number(_opacity));
71     settings.setValue("BlendMode", metaObject()->enumerator(metaObject()->indexOfEnumerator("Mode")
      ).valueToKey(_mode));
72     settings.setValue("ScriptName", _scriptName);
73     settings.setValue("ScriptGuid", _scriptGuid.toString().toUpper());
74     settings.beginGroup("Parameters");
75     QMapIterator<QString, QVariant> i(_parameters);
76     while(i.hasNext()){
77         i.next();
78         settings.setValue(i.key(), i.value());
79     }
80     settings.endGroup();
81     settings.endGroup();
82 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.27 const AnimScript* KbAnim::script ( ) const [inline]

Definition at line 81 of file kbanim.h.

References _script.

Referenced by AnimSettingDialog::AnimSettingDialog(), KbAnimWidget::setCurrent(), and AnimSettingDialog::updateParam().

```
81 { return _script; }
```

Here is the caller graph for this function:

12.22.4.28 const QString& KbAnim::scriptName ( ) const [inline]

Definition at line 82 of file kbanim.h.

References _scriptName.

Referenced by AnimSettingDialog::AnimSettingDialog(), and KbAnimWidget::setCurrent().

```
82 { return _scriptName; }
```

Here is the caller graph for this function:

12.22.4.29 void KbAnim::stop ( )

Definition at line 312 of file kbanim.cpp.

References _isActive, _isActiveKp, _script, AnimScript::end(), kpRepeatMsec, kpRepeatTime, kpStopTime, repeatKey, repeatMsec, repeatTime, and stopTime.

Referenced by KbLight::addAnim(), KbLight::close(), KbLight::duplicateAnim(), KeyAction::keyEvent(), keypress(), KbLight::restartAnimation(), and trigger().

```
312                 {
313     if(_script)
314         _script->end();
315     repeatTime = 0;
316     kpRepeatTime = 0;
317     repeatMsec = 0;
318     kpRepeatMsec = 0;
319     stopTime = 0;
320     kpStopTime = 0;
321     repeatKey = "";
322     _isActive = _isActiveKp = false;
323 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.30 void KbAnim::trigger (quint64 *timestamp*, bool *ignoreParameter* = `false`)

Definition at line 209 of file kbanim.cpp.

References _isActive, _script, catchUp(), effectiveParams(), AnimScript::frame(), repeatMsec, repeatTime, AnimScript::retrigger(), stop(), and stopTime.

Referenced by KbLight::addAnim(), KbLight::duplicateAnim(), KeyAction::keyEvent(), KbLight::open(), KbLight::previewAnim(), and KbLight::restartAnimation().

```
209                                                                    {
210     if(!_script)
211         return;
212     QMap<QString, QVariant> parameters = effectiveParams();
213
214     catchUp(timestamp);
215     if(parameters.value("trigger").toBool() || ignoreParameter){
216         _isActive = true;
217         int delay = round(parameters.value("delay").toDouble() * 1000.);
218         if(delay > 0){
219             // If delay is enabled, wait to trigger the event
220             timestamp += delay;
221             repeatTime = timestamp;
222         } else
223             _script->retrigger(timestamp, true);
224
225         int repeat = round(parameters.value("repeat").toDouble() * 1000.);
226         if(repeat <= 0){
227             // If no repeat allowed, calculate stop time in seconds
228             repeatMsec = -1;
229             double stop = parameters.value("stop").toDouble();
230             if(stop <= 0)
231                 stopTime = 0;
232             else
233                 stopTime = timestamp + round(stop * 1000.);
234         } else {
235             // If repeat is allowed, calculate stop time in repetitions
236             repeatMsec = repeat;
237             if(delay <= 0)
238                 repeatTime = timestamp + repeat;
239             int stop = parameters.value("stop").toInt();
240             if(stop < 0)
241                 stopTime = 0;
242             else
243                 stopTime = timestamp + repeat * (1 + stop);
244         }
245     }
246     // Ask the script for a frame even if we didn't do anything here. This way ckb knows the script is
        responding.
247     _script->frame(timestamp);
```

```
248 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.4.31 void KbAnim::updateParams ( ) [private]

Definition at line 132 of file kbanim.cpp.

References _script, effectiveParams(), AnimScript::parameters(), and repeatKey.

Referenced by parameter(), and resetParams().

```
132                                 {
133     if(_script)
134         _script->parameters(effectiveParams());
135     repeatKey = "";
136 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.22.5 Field Documentation

12.22.5.1 QUuid KbAnim::_guid [private]

Definition at line 110 of file kbanim.h.

Referenced by guid(), KbAnim(), newId(), and save().

12.22.5.2 bool KbAnim::_isActive [private]

Definition at line 114 of file kbanim.h.

Referenced by catchUp(), isActive(), keypress(), reInit(), stop(), and trigger().

12.22.5.3 bool KbAnim::_isActiveKp [private]

Definition at line 114 of file kbanim.h.

Referenced by catchUp(), isActive(), keypress(), reInit(), and stop().

12.22.5.4 QStringList KbAnim::_keys [private]

Definition at line 92 of file kbanim.h.

Referenced by KbAnim(), keys(), reInit(), and save().

12.22.5.5 KeyMap KbAnim::_map [private]

Definition at line 91 of file kbanim.h.

Referenced by KbAnim(), map(), and reInit().

12.22.5.6 Mode KbAnim::_mode [private]

Definition at line 113 of file kbanim.h.

Referenced by blend(), KbAnim(), mode(), and save().

12.22.5.7 QString KbAnim::_name [private]

Definition at line 111 of file kbanim.h.

Referenced by KbAnim(), name(), and save().

12.22.5.8 bool KbAnim::_needsSave [private]

Definition at line 115 of file kbanim.h.

Referenced by commitParams(), mode(), name(), needsSave(), newId(), opacity(), and save().

12.22.5.9 float KbAnim::_opacity [private]

Definition at line 112 of file kbanim.h.

Referenced by blend(), KbAnim(), opacity(), and save().

12.22.5.10 QMap<QString, QVariant> KbAnim::_parameters [private]

Definition at line 94 of file kbanim.h.

Referenced by commitParams(), effectiveParams(), hasParameter(), KbAnim(), parameter(), and save().

12.22.5.11 AnimScript* KbAnim::_script [private]

Definition at line 86 of file kbanim.h.

Referenced by blend(), catchUp(), isRunning(), KbAnim(), keypress(), parameter(), reInit(), script(), stop(), trigger(), and updateParams().

12.22.5.12 QUuid KbAnim::_scriptGuid [private]

Definition at line 88 of file kbanim.h.

Referenced by KbAnim(), and save().

12.22.5.13 QString KbAnim::_scriptName [private]

Definition at line 89 of file kbanim.h.

Referenced by KbAnim(), save(), and scriptName().

12.22.5.14 QMap<QString, QVariant> KbAnim::_tempParameters [private]

Definition at line 96 of file kbanim.h.

Referenced by commitParams(), effectiveParams(), parameter(), and resetParams().

12.22.5.15 int KbAnim::kpRepeatMsec [private]

Definition at line 106 of file kbanim.h.

Referenced by catchUp(), keypress(), and stop().

12.22.5.16 quint64 KbAnim::kpRepeatTime [private]

Definition at line 105 of file kbanim.h.

Referenced by catchUp(), keypress(), and stop().

12.22.5.17 quint64 KbAnim::kpStopTime [private]

Definition at line 105 of file kbanim.h.

Referenced by catchUp(), keypress(), and stop().

12.22.5.18 QString KbAnim::repeatKey [private]

Definition at line 104 of file kbanim.h.

Referenced by catchUp(), keypress(), reInit(), stop(), and updateParams().

12.22.5.19 int KbAnim::repeatMsec [private]

Definition at line 106 of file kbanim.h.

Referenced by catchUp(), keypress(), stop(), and trigger().

12.22.5.20 quint64 KbAnim::repeatTime [private]

Definition at line 105 of file kbanim.h.

Referenced by catchUp(), keypress(), stop(), and trigger().

12.22.5.21 quint64 KbAnim::stopTime [private]

Definition at line 105 of file kbanim.h.

Referenced by catchUp(), keypress(), stop(), and trigger().

The documentation for this class was generated from the following files:

- src/ckb/kbanim.h
- src/ckb/kbanim.cpp

12.23 Ui::KbAnimWidget Class Reference

```
#include <src/ckb/ui_kbanimwidget.h>
```

Inheritance diagram for Ui::KbAnimWidget:

Collaboration diagram for Ui::KbAnimWidget:

Public Member Functions

- void setupUi (QWidget ∗KbAnimWidget)
- void retranslateUi (QWidget ∗KbAnimWidget)

Data Fields

- QGridLayout * gridLayout
- QStackedWidget * selectionStack
- QWidget * noSelPage
- QGridLayout * gridLayout_2
- QLabel * noAnimLabel
- QSpacerItem * verticalSpacer
- QWidget * animPage
- QVBoxLayout * verticalLayout
- QHBoxLayout * horizontalLayout
- QLabel * aNameLabel
- QLabel * aVerLabel
- QSpacerItem * horizontalSpacer
- QLabel * aCopyLabel
- QSpacerItem * verticalSpacer_3
- QGridLayout * gridLayout_3
- QLineEdit * nameBox
- QDoubleSpinBox * opacityBox
- QComboBox * blendBox
- QLabel * label_6
- QSpacerItem * horizontalSpacer_4
- QSpacerItem * horizontalSpacer_2
- QLabel * label_5
- QSpacerItem * horizontalSpacer_3
- QLabel * label_7
- QPushButton * keyButton
- QPushButton * deleteButton
- QPushButton * propertyButton
- QSpacerItem * horizontalSpacer_5
- QSpacerItem * verticalSpacer_2
- QWidget * aMissingPage
- QGridLayout * gridLayout_4
- QLabel * aMissingLabel
- RListWidget * animList

12.23.1 Detailed Description

Definition at line 269 of file ui_kbanimwidget.h.

12.23.2 Member Function Documentation

12.23.2.1 void Ui_KbAnimWidget::retranslateUi (QWidget * *KbAnimWidget*) [inline],[inherited]

Definition at line 241 of file ui_kbanimwidget.h.

References Ui_KbAnimWidget::aCopyLabel, Ui_KbAnimWidget::aMissingLabel, Ui_KbAnimWidget::aNameLabel, Ui_KbAnimWidget::aVerLabel, Ui_KbAnimWidget::blendBox, Ui_KbAnimWidget::deleteButton, Ui_KbAnimWidget::keyButton, Ui_KbAnimWidget::label_5, Ui_KbAnimWidget::label_6, Ui_KbAnimWidget::label_7, Ui_KbAnimWidget::noAnimLabel, Ui_KbAnimWidget::opacityBox, and Ui_KbAnimWidget::propertyButton.

Referenced by Ui_KbAnimWidget::setupUi().

```
    {
        KbAnimWidget->setWindowTitle(QApplication::translate("KbAnimWidget", "Form", Q_NULLPTR));
        noAnimLabel->setText(QApplication::translate("KbAnimWidget", "No animations in this mode", Q_NULLPTR));
        aNameLabel->setText(QApplication::translate("KbAnimWidget", "Animation name", Q_NULLPTR);
        aVerLabel->setText(QApplication::translate("KbAnimWidget", "v0.0", Q_NULLPTR));
        aCopyLabel->setText(QApplication::translate("KbAnimWidget", "Copyright \302\251", Q_NULLPTR));
        opacityBox->setSuffix(QApplication::translate("KbAnimWidget", "%", Q_NULLPTR));
        blendBox->clear();
        blendBox->insertItems(0, QStringList()
         << QApplication::translate("KbAnimWidget", "Normal", Q_NULLPTR)
         << QApplication::translate("KbAnimWidget", "Add", Q_NULLPTR)
         << QApplication::translate("KbAnimWidget", "Subtract", Q_NULLPTR)
         << QApplication::translate("KbAnimWidget", "Multiply", Q_NULLPTR)
         << QApplication::translate("KbAnimWidget", "Divide", Q_NULLPTR)
        );
        label_6->setText(QApplication::translate("KbAnimWidget", "Blend mode:", Q_NULLPTR));
        label_5->setText(QApplication::translate("KbAnimWidget", "Opacity:", Q_NULLPTR));
        label_7->setText(QApplication::translate("KbAnimWidget", "Name:", Q_NULLPTR));
        keyButton->setText(QApplication::translate("KbAnimWidget", "Set keys", Q_NULLPTR));
        deleteButton->setText(QApplication::translate("KbAnimWidget", "Delete animation", Q_NULLPTR));
        propertyButton->setText(QApplication::translate("KbAnimWidget", "Edit properties", Q_NULLPTR));
        aMissingLabel->setText(QApplication::translate("KbAnimWidget", "Mising animation", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.23.2.2 void Ui_KbAnimWidget::setupUi (QWidget * *KbAnimWidget*) [inline],[inherited]

Definition at line 69 of file ui_kbanimwidget.h.

References Ui_KbAnimWidget::aCopyLabel, Ui_KbAnimWidget::aMissingLabel, Ui_KbAnimWidget::aMissingPage, Ui_KbAnimWidget::aNameLabel, Ui_KbAnimWidget::animList, Ui_KbAnimWidget::animPage, Ui_KbAnimWidget::aVerLabel, Ui_KbAnimWidget::blendBox, Ui_KbAnimWidget::deleteButton, Ui_KbAnimWidget::gridLayout, Ui_KbAnimWidget::gridLayout_2, Ui_KbAnimWidget::gridLayout_3, Ui_KbAnimWidget::gridLayout_4, Ui_KbAnimWidget::horizontalLayout, Ui_KbAnimWidget::horizontalSpacer, Ui_KbAnimWidget::horizontalSpacer_2, Ui_KbAnimWidget::horizontalSpacer_3, Ui_KbAnimWidget::horizontalSpacer_4, Ui_KbAnimWidget::horizontalSpacer_5, Ui_KbAnimWidget::keyButton, Ui_KbAnimWidget::label_5, Ui_KbAnimWidget::label_6, Ui_KbAnimWidget::label_7, Ui_KbAnimWidget::nameBox, Ui_KbAnimWidget::noAnimLabel, Ui_KbAnimWidget::noSelPage, Ui_KbAnimWidget::opacityBox, Ui_KbAnimWidget::propertyButton, Ui_KbAnimWidget::retranslateUi(), Ui_KbAnimWidget::selectionStack, Ui_KbAnimWidget::verticalLayout, Ui_KbAnimWidget::verticalSpacer, Ui_KbAnimWidget::verticalSpacer_2, and Ui_KbAnimWidget::verticalSpacer_3.

Referenced by KbAnimWidget::KbAnimWidget().

```
    {
        if (KbAnimWidget->objectName().isEmpty())
            KbAnimWidget->setObjectName(QStringLiteral("KbAnimWidget"));
        KbAnimWidget->resize(613, 300);
        gridLayout = new QGridLayout(KbAnimWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        gridLayout->setContentsMargins(0, 0, 0, 0);
        selectionStack = new QStackedWidget(KbAnimWidget);
        selectionStack->setObjectName(QStringLiteral("selectionStack"));
        noSelPage = new QWidget();
        noSelPage->setObjectName(QStringLiteral("noSelPage"));
        gridLayout_2 = new QGridLayout(noSelPage);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(6, 6, 6, 6);
        noAnimLabel = new QLabel(noSelPage);
```

```
        noAnimLabel->setObjectName(QStringLiteral("noAnimLabel"));

        gridLayout_2->addWidget(noAnimLabel, 0, 0, 1, 1);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout_2->addItem(verticalSpacer, 1, 0, 1, 1);

        selectionStack->addWidget(noSelPage);
        animPage = new QWidget();
        animPage->setObjectName(QStringLiteral("animPage"));
        verticalLayout = new QVBoxLayout(animPage);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        verticalLayout->setContentsMargins(6, 0, 0, 0);
        horizontalLayout = new QHBoxLayout();
         horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
         aNameLabel = new QLabel(animPage);
         aNameLabel->setObjectName(QStringLiteral("aNameLabel"));
         QFont font;
         font.setBold(true);
         font.setWeight(75);
         aNameLabel->setFont(font);

         horizontalLayout->addWidget(aNameLabel);

         aVerLabel = new QLabel(animPage);
         aVerLabel->setObjectName(QStringLiteral("aVerLabel"));

         horizontalLayout->addWidget(aVerLabel);

         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

         horizontalLayout->addItem(horizontalSpacer);

         aCopyLabel = new QLabel(animPage);
         aCopyLabel->setObjectName(QStringLiteral("aCopyLabel"));

         horizontalLayout->addWidget(aCopyLabel);


         verticalLayout->addLayout(horizontalLayout);

         verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

         verticalLayout->addItem(verticalSpacer_3);

         gridLayout_3 = new QGridLayout();
         gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
         nameBox = new QLineEdit(animPage);
         nameBox->setObjectName(QStringLiteral("nameBox"));
         QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
         sizePolicy.setHorizontalStretch(0);
         sizePolicy.setVerticalStretch(0);
         sizePolicy.setHeightForWidth(nameBox->sizePolicy().hasHeightForWidth());
         nameBox->setSizePolicy(sizePolicy);
         nameBox->setMinimumSize(QSize(150, 0));
         nameBox->setMaximumSize(QSize(150, 16777215));

         gridLayout_3->addWidget(nameBox, 0, 3, 1, 2);

         opacityBox = new QDoubleSpinBox(animPage);
         opacityBox->setObjectName(QStringLiteral("opacityBox"));
         opacityBox->setDecimals(1);
         opacityBox->setValue(100);

         gridLayout_3->addWidget(opacityBox, 1, 3, 1, 1);

         blendBox = new QComboBox(animPage);
         blendBox->setObjectName(QStringLiteral("blendBox"));

         gridLayout_3->addWidget(blendBox, 2, 3, 1, 2);

         label_6 = new QLabel(animPage);
         label_6->setObjectName(QStringLiteral("label_6"));

         gridLayout_3->addWidget(label_6, 2, 1, 1, 1);

         horizontalSpacer_4 = new QSpacerItem(0, 0, QSizePolicy::Fixed, QSizePolicy::Minimum);

         gridLayout_3->addItem(horizontalSpacer_4, 0, 0, 1, 1);

         horizontalSpacer_2 = new QSpacerItem(30, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);
```

```

        gridLayout_3->addItem(horizontalSpacer_2, 0, 2, 1, 1);

        label_5 = new QLabel(animPage);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout_3->addWidget(label_5, 1, 1, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_3, 0, 5, 1, 1);

        label_7 = new QLabel(animPage);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout_3->addWidget(label_7, 0, 1, 1, 1);

        keyButton = new QPushButton(animPage);
        keyButton->setObjectName(QStringLiteral("keyButton"));

        gridLayout_3->addWidget(keyButton, 1, 6, 1, 1);

        deleteButton = new QPushButton(animPage);
        deleteButton->setObjectName(QStringLiteral("deleteButton"));

        gridLayout_3->addWidget(deleteButton, 2, 6, 1, 1);

        propertyButton = new QPushButton(animPage);
        propertyButton->setObjectName(QStringLiteral("propertyButton"));

        gridLayout_3->addWidget(propertyButton, 0, 6, 1, 1);

        horizontalSpacer_5 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_5, 1, 4, 1, 1);


        verticalLayout->addLayout(gridLayout_3);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        selectionStack->addWidget(animPage);
        aMissingPage = new QWidget();
        aMissingPage->setObjectName(QStringLiteral("aMissingPage"));
        gridLayout_4 = new QGridLayout(aMissingPage);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        aMissingLabel = new QLabel(aMissingPage);
        aMissingLabel->setObjectName(QStringLiteral("aMissingLabel"));
        aMissingLabel->setFont(font);

        gridLayout_4->addWidget(aMissingLabel, 0, 0, 1, 1);

        selectionStack->addWidget(aMissingPage);

        gridLayout->addWidget(selectionStack, 0, 2, 2, 1);

        animList = new RListWidget(KbAnimWidget);
        animList->setObjectName(QStringLiteral("animList"));
        animList->setMaximumSize(QSize(130, 16777215));
        animList->setContextMenuPolicy(Qt::CustomContextMenu);
        animList->setFrameShadow(QFrame::Plain);
        animList->setDragDropMode(QAbstractItemView::InternalMove);
        animList->setMovement(QListView::Snap);

        gridLayout->addWidget(animList, 0, 0, 2, 1);


        retranslateUi(KbAnimWidget);

        QMetaObject::connectSlotsByName(KbAnimWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.23.3 Field Documentation

12.23.3.1 QLabel* Ui_KbAnimWidget::aCopyLabel [inherited]

Definition at line 47 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.2 QLabel* Ui_KbAnimWidget::aMissingLabel [inherited]

Definition at line 66 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.3 QWidget* Ui_KbAnimWidget::aMissingPage [inherited]

Definition at line 64 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.4 QLabel* Ui_KbAnimWidget::aNameLabel [inherited]

Definition at line 44 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.5 RListWidget* Ui_KbAnimWidget::animList [inherited]

Definition at line 67 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::addAnim(), KbAnimWidget::clearSelection(), KbAnimWidget::duplicateAnim(), KbAnimWidget::KbAnimWidget(), KbAnimWidget::on_animList_customContextMenuRequested(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::on_nameBox_textEdited(), KbAnimWidget::refreshList(), KbAnimWidget::reorderAnims(), and Ui_KbAnimWidget::setupUi().

12.23.3.6 QWidget* Ui_KbAnimWidget::animPage [inherited]

Definition at line 41 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.7 QLabel* Ui_KbAnimWidget::aVerLabel [inherited]

Definition at line 45 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.8 QComboBox* Ui_KbAnimWidget::blendBox [inherited]

Definition at line 52 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.9 QPushButton* Ui_KbAnimWidget::deleteButton [inherited]

Definition at line 60 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.10 QGridLayout* Ui_KbAnimWidget::gridLayout [inherited]

Definition at line 35 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.11 QGridLayout* Ui_KbAnimWidget::gridLayout_2 [inherited]

Definition at line 38 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.12 QGridLayout* Ui_KbAnimWidget::gridLayout_3 [inherited]

Definition at line 49 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.13 QGridLayout* Ui_KbAnimWidget::gridLayout_4 [inherited]

Definition at line 65 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.14 QHBoxLayout* Ui_KbAnimWidget::horizontalLayout [inherited]

Definition at line 43 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.15 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer [inherited]

Definition at line 46 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.16 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_2 [inherited]

Definition at line 55 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.17 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_3 [inherited]

Definition at line 57 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.18 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_4 [inherited]

Definition at line 54 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.19 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_5 [inherited]

Definition at line 62 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.20 QPushButton* Ui_KbAnimWidget::keyButton [inherited]

Definition at line 59 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setSelectedKeys(), and Ui_KbAnimWidget::setupUi().

12.23.3.21 QLabel* Ui_KbAnimWidget::label_5 [inherited]

Definition at line 56 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.22 QLabel* Ui_KbAnimWidget::label_6 [inherited]

Definition at line 53 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.23 QLabel* Ui_KbAnimWidget::label_7 [inherited]

Definition at line 58 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.24 QLineEdit* Ui_KbAnimWidget::nameBox [inherited]

Definition at line 50 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::on_animList_itemChanged(), KbAnimWidget::on_propertyButton_clicked(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.25 QLabel* Ui_KbAnimWidget::noAnimLabel [inherited]

Definition at line 39 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::addAnim(), KbAnimWidget::duplicateAnim(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::refreshList(), Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.26 QWidget* Ui_KbAnimWidget::noSelPage [inherited]

Definition at line 37 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.27 QDoubleSpinBox* Ui_KbAnimWidget::opacityBox [inherited]

Definition at line 51 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.28 QPushButton* Ui_KbAnimWidget::propertyButton [inherited]

Definition at line 61 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::retranslateUi(), and Ui_KbAnimWidget::setupUi().

12.23.3.29 QStackedWidget* Ui_KbAnimWidget::selectionStack [inherited]

Definition at line 36 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::setCurrent(), and Ui_KbAnimWidget::setupUi().

12.23.3.30 QVBoxLayout* Ui_KbAnimWidget::verticalLayout [inherited]

Definition at line 42 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.31 QSpacerItem* Ui_KbAnimWidget::verticalSpacer [inherited]

Definition at line 40 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.32 QSpacerItem* Ui_KbAnimWidget::verticalSpacer_2 [inherited]

Definition at line 63 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

12.23.3.33 QSpacerItem* Ui_KbAnimWidget::verticalSpacer_3 [inherited]

Definition at line 48 of file ui_kbanimwidget.h.

Referenced by Ui_KbAnimWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbanimwidget.h

12.24 KbAnimWidget Class Reference

```
#include <src/ckb/kbanimwidget.h>
```

Inheritance diagram for KbAnimWidget:

Collaboration diagram for KbAnimWidget:

Signals

- void animChanged (KbAnim ∗selection)
- void didUpdateSelection (QStringList keys)

Public Member Functions

- KbAnimWidget (QWidget ∗parent=0)
- ∼KbAnimWidget ()
- void setLight (KbLight ∗newLight)
- void addAnim (const AnimScript ∗base, const QStringList &keyList, const QString &name, const QMap< QString, QVariant > &preset)
- void duplicateAnim (KbAnim ∗old)
- void clearSelection ()
- void setSelectedKeys (const QStringList &keys)

Private Slots

- void on_animList_currentItemChanged (QListWidgetItem ∗current, QListWidgetItem ∗previous)
- void on_animList_itemChanged (QListWidgetItem ∗item)
- void on_animList_customContextMenuRequested (const QPoint &pos)
- void on_nameBox_textEdited (const QString &arg1)
- void on_opacityBox_valueChanged (double arg1)
- void on_blendBox_activated (int index)
- void on_keyButton_clicked ()
- void on_deleteButton_clicked ()
- void refreshList ()
- void reorderAnims ()
- void on_propertyButton_clicked ()

Private Member Functions

- void setCurrent (KbAnim *newCurrent)

Private Attributes

- KbLight * light
- QHash< QUuid, KbAnim * > animations
- KbAnim * current
- QStringList selectedKeys
- bool noReorder
- Ui::KbAnimWidget * ui

12.24.1 Detailed Description

Definition at line 15 of file kbanimwidget.h.

12.24.2 Constructor & Destructor Documentation

12.24.2.1 KbAnimWidget::KbAnimWidget (QWidget * *parent* = 0) [explicit]

Definition at line 7 of file kbanimwidget.cpp.

References Ui_KbAnimWidget::animList, reorderAnims(), setCurrent(), Ui_KbAnimWidget::setupUi(), and ui.

```
7                                          :
8     QWidget(parent), light(0), current(0), noReorder(false),
9     ui(new Ui::KbAnimWidget)
10 {
11     ui->setupUi(this);
12     ui->animList->setVisible(false);
13     setCurrent(0);
14     connect(ui->animList, SIGNAL(orderChanged()), this, SLOT(
      reorderAnims()));
15 }
```

Here is the call graph for this function:

12.24.2.2 KbAnimWidget::~KbAnimWidget ( )

Definition at line 17 of file kbanimwidget.cpp.

References ui.

```
17                                  {
18     delete ui;
19 }
```

12.24.3 Member Function Documentation

12.24.3.1 void KbAnimWidget::addAnim (const AnimScript * *base*, const QStringList & *keyList*, const QString & *name*, const QMap< QString, QVariant > & *preset*)

Definition at line 82 of file kbanimwidget.cpp.

References KbLight::addAnim(), animations, Ui_KbAnimWidget::animList, KbAnim::guid(), light, KbAnim::name(), Ui_KbAnimWidget::noAnimLabel, noReorder, on_propertyButton_clicked(), setCurrent(), and ui.

Referenced by KbLightWidget::on_animButton_clicked().

```
82
                                        {
83     if(!light)
84         return;
85     noReorder = true;
86     KbAnim* animation = light->addAnim(base, keyList, name, preset);
87     QListWidgetItem* item = new QListWidgetItem(animation->name(), ui->
       animList);
88     item->setData(Qt::UserRole, animation->guid());
89     item->setFlags(item->flags() | Qt::ItemIsEditable);
90     animations[animation->guid()] = animation;
91     ui->animList->addItem(item);
92     ui->animList->setCurrentItem(item);
```

```
    ui->animList->setVisible(true);
    ui->noAnimLabel->setVisible(false);

    setCurrent(animation);
    noReorder = false;

    // Activate settings dialog
     on_propertyButton_clicked();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.2 void KbAnimWidget::animChanged (KbAnim * *selection*) [signal]

Definition at line 213 of file moc_kbanimwidget.cpp.

Referenced by setCurrent().

```
{
    void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
    QMetaObject::activate(this, &staticMetaObject, 0, _a);
}
```

Here is the caller graph for this function:

12.24.3.3 void KbAnimWidget::clearSelection ( )

Definition at line 77 of file kbanimwidget.cpp.

References Ui_KbAnimWidget::animList, setCurrent(), and ui.

Referenced by KbLightWidget::setLight().

```
77                                  {
78      ui->animList->setCurrentItem(0);
79      setCurrent(0);
80  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.4 void KbAnimWidget::didUpdateSelection (QStringList *keys*) [signal]

Definition at line 220 of file moc_kbanimwidget.cpp.

Referenced by on_keyButton_clicked().

```
221 {
222     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
223     QMetaObject::activate(this, &staticMetaObject, 1, _a);
224 }
```

Here is the caller graph for this function:

12.24.3.5 void KbAnimWidget::duplicateAnim (KbAnim * *old*)

Definition at line 103 of file kbanimwidget.cpp.

References KbLight::animList(), Ui_KbAnimWidget::animList, KbLight::duplicateAnim(), light, Ui_KbAnimWidget::noAnimLabel, noReorder, refreshList(), setCurrent(), and ui.

Referenced by on_animList_customContextMenuRequested().

```
103                                                 {
104     if(!light)
105         return;
106     noReorder = true;
107     KbAnim* animation = light->duplicateAnim(old);
108     // Refresh the list. insertItem doesn't seem to place the item in the correct position on its own...
109     refreshList();
110     ui->animList->setCurrentRow(light->animList().indexOf(animation));
111     ui->animList->setVisible(true);
112     ui->noAnimLabel->setVisible(false);
113
114     setCurrent(animation);
115     noReorder = false;
116 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.6 void KbAnimWidget::on_animList_currentItemChanged (QListWidgetItem * *current*, QListWidgetItem * *previous*) [private], [slot]

Definition at line 151 of file kbanimwidget.cpp.

References animations, and setCurrent().

```
151                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
{
    if(!current)
        setCurrent(0);
    else
        setCurrent(animations[current->data(Qt::UserRole).toUuid()]);
156 }
```

Here is the call graph for this function:

12.24.3.7 void KbAnimWidget::on_animList_customContextMenuRequested (const QPoint & *pos*) [private], [slot]

Definition at line 169 of file kbanimwidget.cpp.

References animations, Ui_KbAnimWidget::animList, current, duplicateAnim(), on_deleteButton_clicked(), setCurrent(), and ui.

```
169                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
{
    QListWidgetItem* item = ui->animList->itemAt(pos);
    if(!item)
        return;
    setCurrent(animations[item->data(Qt::UserRole).toUuid()]);

    QMenu menu(this);
    QAction* rename = new QAction("Rename...", this);
    QAction* duplicate = new QAction("Duplicate", this);
    QAction* del = new QAction("Delete", this);
    menu.addAction(rename);
    menu.addAction(duplicate);
    menu.addAction(del);
    QAction* result = menu.exec(QCursor::pos());
    if(result == rename)
        ui->animList->editItem(item);
```

```
    else if(result == duplicate)
        duplicateAnim(current);
    else if(result == del)
        on_deleteButton_clicked();
}
```

Here is the call graph for this function:

12.24.3.8 void KbAnimWidget::on_animList_itemChanged (QListWidgetItem * *item*) [private],[slot]

Definition at line 158 of file kbanimwidget.cpp.

References animations, current, KbAnim::name(), Ui_KbAnimWidget::nameBox, noReorder, and ui.

```
158                                                                 {
159     if(item){
160         KbAnim* anim = animations[item->data(Qt::UserRole).toUuid()];
161         if(anim){
162             anim->name(item->text().trimmed());
163             if(anim == current && !noReorder)
164                 ui->nameBox->setText(anim->name());
165         }
166     }
167 }
```

Here is the call graph for this function:

12.24.3.9 void KbAnimWidget::on_blendBox_activated (int *index*) [private],[slot]

Definition at line 205 of file kbanimwidget.cpp.

References current, and KbAnim::mode().

```
205                                                 {
206     if(current)
207         current->mode((KbAnim::Mode)index);
208 }
```

Here is the call graph for this function:

12.24.3.10 void KbAnimWidget::on_deleteButton_clicked ( ) [private],[slot]

Definition at line 226 of file kbanimwidget.cpp.

References animations, KbLight::animList(), Ui_KbAnimWidget::animList, current, KbAnim::guid(), light, Ui_KbAnimWidget::noAnimLabel, KbLight::restartAnimation(), setCurrent(), and ui.

Referenced by on_animList_customContextMenuRequested().

```
226                                                 {
227     if(current){
228         animations.remove(current->guid());
229         QList<KbAnim*> animList = light->animList();
230         animList.removeAll(current);
231         light->animList(animList);
232         current->deleteLater();
233         setCurrent(0);
234         delete ui->animList->currentItem();
235         if(animations.count() == 0){
236             ui->animList->setVisible(false);
237             ui->noAnimLabel->setVisible(true);
238         }
239     }
240     light->restartAnimation();
241 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.11 void KbAnimWidget::on_keyButton_clicked ( ) [private],[slot]

Definition at line 210 of file kbanimwidget.cpp.

References KeyMap::contains(), current, didUpdateSelection(), KbAnim::keys(), light, KbLight::map(), KbLight::restartAnimation(), and selectedKeys.

```
210                                         {
211     if(current){
212         QStringList keys = selectedKeys;
213         // If any keys were selected previously that aren't in the keymap now, leave them in
214         // This is important for layout compatibility - e.g. being able to select both bslash_iso and
        bslash, because no single layout contains both
215         const KeyMap& map = light->map();
216         foreach(const QString& key, current->keys()){
217             if(!map.contains(key))
218                 keys << key;
219         }
220         current->keys(keys);
221         emit didUpdateSelection(selectedKeys);
222     }
223     light->restartAnimation();
224 }
```

Here is the call graph for this function:

12.24.3.12 void KbAnimWidget::on_nameBox_textEdited (const QString & *arg1*) [private],[slot]

Definition at line 191 of file kbanimwidget.cpp.

References Ui_KbAnimWidget::animList, current, KbAnim::name(), noReorder, and ui.

Referenced by on_propertyButton_clicked().

```
191                                                     {
192     if(current){
193         noReorder = true;
194         current->name(arg1.trimmed());
195         ui->animList->currentItem()->setText(current->name());
196         noReorder = false;
197     }
198 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.13 void KbAnimWidget::on_opacityBox_valueChanged (double *arg1*) [private],[slot]

Definition at line 200 of file kbanimwidget.cpp.

References current, and KbAnim::opacity().

```
200                                                         {
201     if(current)
202         current->opacity(arg1 / 100.);
203 }
```

Here is the call graph for this function:

12.24.3.14 void KbAnimWidget::on_propertyButton_clicked ( ) [private],[slot]

Definition at line 243 of file kbanimwidget.cpp.

References KbAnim::commitParams(), current, light, AnimSettingDialog::name(), Ui_KbAnimWidget::nameBox, on_nameBox_textEdited(), KbAnim::reInit(), KbAnim::resetParams(), KbLight::restartAnimation(), and ui.

Referenced by addAnim().

```
243                                             {
244     if(!current)
245         return;
246     // Present animation property popup
247     AnimSettingDialog dialog(this, current);
248     dialog.exec();
249     if(dialog.result() != QDialog::Accepted){
250         current->resetParams();
251         return;
252     }
253     // Apply settings and restart all animations
254     current->commitParams();
255     current->reInit();
256     light->restartAnimation();
257     // Update name
258     ui->nameBox->setText(dialog.name());
259     on_nameBox_textEdited(dialog.name());
260 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.15 void KbAnimWidget::refreshList ( ) [private],[slot]

Definition at line 32 of file kbanimwidget.cpp.

References animations, KbLight::animList(), Ui_KbAnimWidget::animList, KbAnim::guid(), light, KbAnim::name(), Ui_KbAnimWidget::noAnimLabel, noReorder, setCurrent(), and ui.

Referenced by duplicateAnim(), and setLight().

```
32                                  {
33     noReorder = true;
34     setCurrent(0);
35     ui->animList->clear();
36     animations.clear();
37     // Add the animations from the new lighting mode
38     if(!light){
39         ui->animList->setVisible(false);
40         ui->noAnimLabel->setVisible(true);
41         return;
42     }
43     QList<KbAnim*> newAnimations = light->animList();
44     if(newAnimations.count() == 0){
45         ui->animList->setVisible(false);
46         ui->noAnimLabel->setVisible(true);
47         return;
48     }
49     ui->animList->setVisible(true);
50     foreach(KbAnim* anim, newAnimations){
51         QListWidgetItem* item = new QListWidgetItem(anim->name(), ui->
       animList);
52         item->setData(Qt::UserRole, anim->guid());
53         item->setFlags(item->flags() | Qt::ItemIsEditable);
54         animations[anim->guid()] = anim;
55         ui->animList->addItem(item);
56     }
57     ui->noAnimLabel->setVisible(false);
58     noReorder = false;
59 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.16 void KbAnimWidget::reorderAnims ( ) [private],[slot]

Definition at line 61 of file kbanimwidget.cpp.

References animations, KbLight::animList(), Ui_KbAnimWidget::animList, light, noReorder, and ui.

Referenced by KbAnimWidget().

```
61                                  {
62      if(light && !noReorder){
63          // Clear and rebuild the list of animations in case the animation moved
64          int count = ui->animList->count();
65          QList<KbAnim*> animList;
66          for(int i = 0; i < count; i++){
67              QListWidgetItem* item = ui->animList->item(i);
68              KbAnim* anim = animations[item->data(Qt::UserRole).toUuid()];
69              if(anim && !animList.contains(anim))
70                  animList.append(anim);
71              item->setFlags(item->flags() | Qt::ItemIsEditable);
72          }
73          light->animList(animList);
74      }
75  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.17 void KbAnimWidget::setCurrent (KbAnim * *newCurrent*) [private]

Definition at line 118 of file kbanimwidget.cpp.

References Ui_KbAnimWidget::aCopyLabel, Ui_KbAnimWidget::aMissingLabel, Ui_KbAnimWidget::aNameLabel, animChanged(), Ui_KbAnimWidget::aVerLabel, Ui_KbAnimWidget::blendBox, AnimScript::copyright(), current, KbAnim::keys(), KbAnim::mode(), AnimScript::name(), KbAnim::name(), Ui_KbAnimWidget::nameBox, KbAnim::opacity(), Ui_KbAnimWidget::opacityBox, KbAnim::script(), KbAnim::scriptName(), selectedKeys, Ui_KbAnimWidget::selectionStack, ui, and AnimScript::version().

Referenced by addAnim(), clearSelection(), duplicateAnim(), KbAnimWidget(), on_animList_currentItemChanged(), on_animList_customContextMenuRequested(), on_deleteButton_clicked(), and refreshList().

```
118                                                 {
119     if(newCurrent != current)
120         emit animChanged(current = newCurrent);
121     if(!current){
122         selectedKeys.clear();
123         ui->selectionStack->setCurrentIndex(0);
124         return;
125     }
126     selectedKeys = current->keys();
127     const AnimScript* script = current->script();
128     if(!script){
129         ui->selectionStack->setCurrentIndex(2);
130         ui->aMissingLabel->setText("The \"" + current->
        scriptName() + "\" script could not be loaded. Please check your animation directory.");
131         return;
132     }
133     ui->selectionStack->setCurrentIndex(1);
134     ui->aNameLabel->setText(script->name());
135     ui->aVerLabel->setText("v" + script->version());
136     ui->aCopyLabel->setText(script->copyright());
137
138     ui->nameBox->setText(current->name());
139     ui->opacityBox->setValue(current->opacity() * 100.);
140     ui->blendBox->setCurrentIndex((int)current->mode());
141 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.18 void KbAnimWidget::setLight (KbLight * *newLight*)

Definition at line 21 of file kbanimwidget.cpp.

References light, and refreshList().

Referenced by KbLightWidget::setLight().

```
{
    if(light != newLight){
        if(light)
            disconnect(light, SIGNAL(didLoad()), this, SLOT(refreshList()));
        if(newLight)
            connect(newLight, SIGNAL(didLoad()), this, SLOT(refreshList()));
        light = newLight;
    }
    refreshList();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.24.3.19 void KbAnimWidget::setSelectedKeys (const QStringList & *keys*)

Definition at line 143 of file kbanimwidget.cpp.

References Ui_KbAnimWidget::keyButton, selectedKeys, and ui.

Referenced by KbLightWidget::newSelection().

```
{
    selectedKeys = keys;
    if(keys.count() == 0)
        ui->keyButton->setVisible(false);
    else
        ui->keyButton->setVisible(true);
}
```

Here is the caller graph for this function:

12.24.4 Field Documentation

12.24.4.1 QHash<QUuid, KbAnim*> KbAnimWidget::animations [private]

Definition at line 53 of file kbanimwidget.h.

Referenced by addAnim(), on_animList_currentItemChanged(), on_animList_customContextMenuRequested(), on_animList_itemChanged(), on_deleteButton_clicked(), refreshList(), and reorderAnims().

12.24.4.2 KbAnim* KbAnimWidget::current [private]

Definition at line 55 of file kbanimwidget.h.

Referenced by on_animList_customContextMenuRequested(), on_animList_itemChanged(), on_blendBox_activated(), on_deleteButton_clicked(), on_keyButton_clicked(), on_nameBox_textEdited(), on_opacityBox_valueChanged(), on_propertyButton_clicked(), and setCurrent().

12.24.4.3 KbLight* KbAnimWidget::light [private]

Definition at line 52 of file kbanimwidget.h.

Referenced by addAnim(), duplicateAnim(), on_deleteButton_clicked(), on_keyButton_clicked(), on_propertyButton_clicked(), refreshList(), reorderAnims(), and setLight().

12.24.4.4 bool KbAnimWidget::noReorder [private]

Definition at line 58 of file kbanimwidget.h.

Referenced by addAnim(), duplicateAnim(), on_animList_itemChanged(), on_nameBox_textEdited(), refreshList(), and reorderAnims().

12.24.4.5 QStringList KbAnimWidget::selectedKeys [private]

Definition at line 57 of file kbanimwidget.h.

Referenced by on_keyButton_clicked(), setCurrent(), and setSelectedKeys().

12.24.4.6 Ui::KbAnimWidget* KbAnimWidget::ui [private]

Definition at line 60 of file kbanimwidget.h.

Referenced by addAnim(), clearSelection(), duplicateAnim(), KbAnimWidget(), on_animList_customContextMenuRequested(), on_animList_itemChanged(), on_deleteButton_clicked(), on_nameBox_textEdited(), on_propertyButton_clicked(), refreshList(), reorderAnims(), setCurrent(), setSelectedKeys(), and ~KbAnimWidget().

The documentation for this class was generated from the following files:

- src/ckb/kbanimwidget.h

- src/ckb/kbanimwidget.cpp
- src/ckb/release/moc_kbanimwidget.cpp

12.25 KbBind Class Reference

`#include <src/ckb/kbbind.h>`

Inheritance diagram for KbBind:

Collaboration diagram for KbBind:

Public Slots

- void keyEvent (const QString &key, bool down)

Signals

- void didLoad ()
- void layoutChanged ()
- void updated ()

Public Member Functions

- KbBind (KbMode ∗modeParent, Kb ∗devParent, const KeyMap &keyMap)
- KbBind (KbMode ∗modeParent, Kb ∗devParent, const KeyMap &keyMap, const KbBind &other)

  KbBind.
- void load (CkbSettings &settings)
- void save (CkbSettings &settings)
- bool needsSave () const
- const KeyMap & map ()
- void map (const KeyMap &map)
- bool isISO () const
- bool isKeyboard () const
- bool isMouse () const
- KbPerf ∗ perf ()
- KbLight ∗ light ()
- QString action (const QString &key)
- QString friendlyName (const QString &key)

- QString friendlyActionName (const QString &key)
- void setAction (const QString &key, const QString &action)
- void setAction (const QStringList &keys, const QString &action)
- void resetAction (const QString &key)
- void resetAction (const QStringList &keys)
- void noAction (const QString &key)
- void noAction (const QStringList &keys)
- bool winLock ()
- void winLock (bool newWinLock)
- void update (QFile &cmd, bool force=false)
- void setNeedsUpdate ()
- int getMacroNumber ()

  KbBind::getMacroNumber.
- QString getMacroPath ()

  KbBind::getMacroPath.
- void handleNotificationChannel (bool start)

  handleNotificationChannel sends commands to ckb-daemon for (de-) activating the notify channel. Send a notify cmd to the keyboard to set or clear notification for reading macro definition. The file handle for the cmd pipe is stored in lastCmd.

Static Public Member Functions

- static QString globalRemap (const QString &key)
- static void setGlobalRemap (const QHash< QString, QString > keyToActual)
- static void loadGlobalRemap ()
- static void saveGlobalRemap ()
- static QString defaultAction (const QString &key)

Private Member Functions

- Kb * devParent () const
- KbMode * modeParent () const
- KeyAction * bindAction (const QString &key)

Private Attributes

- Kb * _devParent
- quint64 lastGlobalRemapTime
- QFile * lastCmd

  lastCmd is a cache-hack. Because the QFile ist opened in Kb, and we need it in the macro processing functions, we cache the value her in lastCmd.
- KeyMap _map
- QHash< QString, KeyAction * > _bind
- bool _winLock
- bool _needsUpdate
- bool _needsSave

Static Private Attributes

- static QHash< QString, QString > _globalRemap
- static quint64 globalRemapTime = 0

Friends

- class KeyAction

12.25.1 Detailed Description

Definition at line 20 of file kbbind.h.

12.25.2 Constructor & Destructor Documentation

12.25.2.1 KbBind::KbBind (KbMode * *modeParent*, Kb * *devParent*, const KeyMap & *keyMap*) [explicit]

Definition at line 12 of file kbbind.cpp.

```
12                                                                  :
13     QObject(modeParent), _devParent(parentBoard),
      lastGlobalRemapTime(globalRemapTime), _map(keyMap),
14     _winLock(false), _needsUpdate(true), _needsSave(true) {
15 }
```

12.25.2.2 KbBind::KbBind (KbMode * *modeParent*, Kb * *parentBoard*, const KeyMap & *keyMap*, const KbBind & *other*)

KbBind::KbBind // copy all existing Key bindings.

Parameters

modeParent	
devParent	
keyMap	
other	This is the KbBind object to copy from Use this constructor to copy an existing Binding
modeParent	
parentBoard	
keyMap	
other	

Create a new Hash table and copy all entries

clear the destination list (there are the original KeyActions as references, so do not delete them)

and move the KeyActions we just created

Definition at line 24 of file kbbind.cpp.

References _bind, KeyAction, map(), and KeyAction::value().

```
24                                                                                                  :
25     QObject(modeParent), _devParent(parentBoard),
      lastGlobalRemapTime(globalRemapTime), _bind(other.
      _bind),
26     _winLock(false), _needsUpdate(true), _needsSave(true) {
27     map(keyMap);
28
30     QHash<QString, KeyAction*> newBind;
31     foreach(QString key, _bind.keys()) {
32         KeyAction* act = _bind.value(key);
33         if(act) {
34             newBind[key] = new KeyAction(act->value(), this);
35         }
36     }
37
39     _bind.clear();
40     foreach(QString key, newBind.keys()) {
41         KeyAction* act = newBind.value(key);
42         if(act) {
44             _bind[key] = new KeyAction(act->value(), this);
45         }
46     }
```

```
    newBind.clear();      // here we *must not* delete the KeyActions, because they are referenced by _bind
    now
}
```

Here is the call graph for this function:

12.25.3 Member Function Documentation

12.25.3.1 QString KbBind::action (const QString & *key*)

Definition at line 140 of file kbbind.cpp.

References bindAction(), globalRemap(), and KeyAction::value().

Referenced by friendlyActionName(), KbBindWidget::on_copyButton_clicked(), resetAction(), RebindWidget::setSelection(), and KbBindWidget::updateBind().

```
                                        {
    QString rKey = globalRemap(key);
    return bindAction(rKey)->value();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.2 KeyAction* KbBind::bindAction (const QString & *key*) [inline], [private]

Definition at line 117 of file kbbind.h.

References _bind, KeyAction::defaultAction(), and KeyAction.

Referenced by action(), keyEvent(), and update().

```
117 { if(!_bind.contains(key)) return _bind[key] = new KeyAction(
      KeyAction::defaultAction(key), this); return _bind[key]; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.3 QString KbBind::defaultAction (const QString & *key*) [static]

Definition at line 145 of file kbbind.cpp.

References KeyAction::defaultAction(), and globalRemap().

Referenced by KeyWidget::paintEvent(), and RebindWidget::setBind().

```
145                                                 {
146     QString rKey = globalRemap(key);
147     return KeyAction::defaultAction(rKey);
148 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.4 Kb* KbBind::devParent ( ) const [inline], [private]

Definition at line 114 of file kbbind.h.

References _devParent.

Referenced by getMacroNumber(), getMacroPath(), and KeyAction::keyEvent().

```
114 { return _devParent; }
```

Here is the caller graph for this function:

12.25.3.5 void KbBind::didLoad ( ) [signal]

Definition at line 155 of file moc_kbbind.cpp.

Referenced by load().

```
156 {
157     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
158 }
```

Here is the caller graph for this function:

12.25.3.6 QString KbBind::friendlyActionName (const QString & *key*)

Definition at line 157 of file kbbind.cpp.

References _map, action(), and KeyAction.

Referenced by KbBindWidget::updateSelDisplay().

```
157                                                 {
158     QString act = action(key);
159     return KeyAction(act).friendlyName(_map);
160 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.7 QString KbBind::friendlyName (const QString & *key*)

Definition at line 150 of file kbbind.cpp.

References _map, Key::friendlyName(), and globalRemap().

```
150                                             {
151     const Key& pos = _map[globalRemap(key)];
152     if(!pos)
153         return "(Unknown)";
154     return pos.friendlyName();
155 }
```

Here is the call graph for this function:

12.25.3.8 int KbBind::getMacroNumber ( )

Returns

number of notification channel. Use it in combination with notifyon/off-Statement

Definition at line 257 of file kbbind.cpp.

References devParent(), and Kb::getMacroNumber().

Referenced by handleNotificationChannel(), and RebindWidget::on_btnStartMacro_clicked().

```
257                                 {
258     return devParent()->getMacroNumber();
259 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.9 QString KbBind::getMacroPath ( )

Returns

Filepath of macro notification pipe. If not set, returns initial value ""

Definition at line 265 of file kbbind.cpp.

References devParent(), and Kb::getMacroPath().

Referenced by RebindWidget::on_btnStartMacro_clicked().

```
265                                 {
266     return devParent()->getMacroPath();
267 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.10 QString KbBind::globalRemap (const QString & *key*) [static]

Definition at line 98 of file kbbind.cpp.

References _globalRemap.

Referenced by action(), defaultAction(), friendlyName(), keyEvent(), noAction(), KeyWidget::paintEvent(), resetAction(), setAction(), and SettingsWidget::SettingsWidget().

```
98                                          {
99     if(!_globalRemap.contains(key))
100         return key;
101     return _globalRemap.value(key);
102 }
```

Here is the caller graph for this function:

12.25.3.11 void KbBind::handleNotificationChannel (bool *start*)

Parameters

start	is boolean. If true, notification channel is opened for all keys, otherwise channel ist closed.
start	If true, notification channel is opened for all keys, otherwise channel ist closed.

Definition at line 275 of file kbbind.cpp.

References getMacroNumber(), and lastCmd.

Referenced by RebindWidget::on_btnStartMacro_clicked(), and RebindWidget::on_btnStopMacro_clicked().

```
                                                {
    if (getMacroNumber() > 0 && lastCmd) {
        if (start) {
            lastCmd->write (QString("\nnotifyon %1\n@%1 notify all:on\n").arg(getMacroNumber()).toLatin1());
        } else {
            lastCmd->write (QString("\n@%1 notify all:off\nnotifyoff %1\n").arg(getMacroNumber()).toLatin1());
        }
        lastCmd->flush();
    } else qDebug() << QString("No cmd or valid handle for notification found, macroNumber = %1, lastCmd = %2")
                        .arg(getMacroNumber()).arg(lastCmd? "set" : "unset");
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.12 bool KbBind::isISO ( ) const [inline]

Definition at line 43 of file kbbind.h.

References _map, and KeyMap::isISO().

```
43 { return _map.isISO(); }
```

Here is the call graph for this function:

12.25.3.13 bool KbBind::isKeyboard ( ) const [inline]

Definition at line 44 of file kbbind.h.

References _map, and KeyMap::isKeyboard().

```
44 { return _map.isKeyboard(); }
```

Here is the call graph for this function:

12.25.3.14 bool KbBind::isMouse ( ) const [inline]

Definition at line 45 of file kbbind.h.

References _map, and KeyMap::isMouse().

Referenced by KbBindWidget::on_copyButton_clicked(), KbBindWidget::on_resetButton_clicked(), RebindWidget::setBind(), and KbBindWidget::updateSelDisplay().

```
45 { return _map.isMouse(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.15 void KbBind::keyEvent (const QString & *key*, bool *down*) [slot]

Definition at line 287 of file kbbind.cpp.

References bindAction(), globalRemap(), and KeyAction::keyEvent().

Referenced by Kb::readNotify().

```
287                                                 {
288     QString rKey = globalRemap(key);
289     KeyAction* act = bindAction(rKey);
290     if(act)
291         act->keyEvent(this, down);
292 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.16 void KbBind::layoutChanged ( ) [signal]

Definition at line 161 of file moc_kbbind.cpp.

Referenced by map().

```
162 {
163     QMetaObject::activate(this, &staticMetaObject, 1, Q_NULLPTR);
164 }
```

Here is the caller graph for this function:

12.25.3.17 KbLight * KbBind::light ( )

Definition at line 54 of file kbbind.cpp.

References KbMode::light(), and modeParent().

Referenced by RebindWidget::applyChanges(), KeyAction::keyEvent(), and RebindWidget::setSelection().

```
54                          {
55      return modeParent()->light();
56  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.18 void KbBind::load (CkbSettings & *settings*)

Definition at line 58 of file kbbind.cpp.

References _bind, _map, _needsSave, _winLock, CkbSettings::childKeys(), didLoad(), KeyMap::fromName(), KeyMap::fromStorage(), KeyAction, map(), and CkbSettings::value().

Referenced by KbMode::KbMode().

```
                                        {
    _needsSave = false;
    SGroup group(settings, "Binding");
    KeyMap currentMap = _map;
    _map = KeyMap::fromName(settings.value("KeyMap").toString());
    // Load key settings
    bool useReal = settings.value("UseRealNames").toBool();
    _bind.clear();
    {
        SGroup group(settings, "Keys");
        foreach(QString key, settings.childKeys()){
            QString name = key.toLower();
            if(!useReal)
                name = _map.fromStorage(name);
            QString bind = settings.value(key).toString();
            _bind[name] = new KeyAction(bind, this);
        }
    }
    _winLock = settings.value("WinLock").toBool();
    emit didLoad();
    map(currentMap);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.19 void KbBind::loadGlobalRemap ( ) [static]

Definition at line 116 of file kbbind.cpp.

References _globalRemap, CkbSettings::childKeys(), globalRemapTime, and CkbSettings::value().

Referenced by SettingsWidget::SettingsWidget().

```
                                {
    _globalRemap.clear();
    CkbSettings settings("Program/GlobalRemap");
    foreach(const QString& key, settings.childKeys())
        _globalRemap[key] = settings.value(key).toString();
    globalRemapTime = QDateTime::currentMSecsSinceEpoch();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.20 const KeyMap& KbBind::map ( ) [inline]

Definition at line 41 of file kbbind.h.

References _map.

Referenced by KbBind(), KbMode::keyMap(), load(), map(), KbBindWidget::newLayout(), KbBindWidget::on_copyButton_clicked(), KbBindWidget::on_resetButton_clicked(), RebindWidget::setBind(), KbBindWidget::updateBind(), and KbBindWidget::updateSelDisplay().

```
41 { return _map; }
```

Here is the caller graph for this function:

12.25.3.21 void KbBind::map (const KeyMap & *map*)

Definition at line 133 of file kbbind.cpp.

References _map, _needsSave, _needsUpdate, layoutChanged(), and map().

```
133                                 {
134     _map = map;
135     _needsUpdate = true;
136     _needsSave = true;
137     emit layoutChanged();
138 }
```

Here is the call graph for this function:

12.25.3.22 KbMode* KbBind::modeParent ( ) const [inline], [private]

Definition at line 115 of file kbbind.h.

Referenced by light(), and perf().

```
115 { return (KbMode*)parent(); }
```

Here is the caller graph for this function:

12.25.3.23 bool KbBind::needsSave ( ) const [inline]

Definition at line 38 of file kbbind.h.

References _needsSave.

Referenced by KbMode::needsSave().

```
38 { return _needsSave; }
```

Here is the caller graph for this function:

12.25.3.24 void KbBind::noAction (const QString & *key*)

Definition at line 172 of file kbbind.cpp.

References _bind, _map, globalRemap(), KeyMap::key(), KeyAction, and resetAction().

Referenced by RebindWidget::applyChanges(), and RebindWidget::on_unbindButton_clicked().

```
172                                         {
173     resetAction(key);
174     QString rKey = globalRemap(key);
175     if(!_map.key(rKey))
176         return;
177     _bind[rKey] = new KeyAction(this);
178 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.25 void KbBind::noAction (const QStringList & *keys*) [inline]

Definition at line 75 of file kbbind.h.

References noAction().

Referenced by noAction().

```
75 { foreach(const QString& key, keys) noAction(key); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.26 KbPerf * KbBind::perf ( )

Definition at line 50 of file kbbind.cpp.

References modeParent(), and KbMode::perf().

Referenced by KeyAction::keyEvent(), and RebindWidget::setBind().

```
50                      {
51     return modeParent()->perf();
52 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.27 void KbBind::resetAction (const QString & *key*)

Definition at line 162 of file kbbind.cpp.

References _bind, _needsSave, _needsUpdate, action(), and globalRemap().

Referenced by noAction(), KbBindWidget::on_resetButton_clicked(), RebindWidget::on_resetButton_clicked(), and setAction().

```
162                                         {
163     QString rKey = globalRemap(key);
164     // Clean up existing action (if any)
165     KeyAction* action = _bind.value(rKey);
166     delete action;
167     _bind.remove(rKey);
168     _needsUpdate = true;
169     _needsSave = true;
170 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.28 void KbBind::resetAction (const QStringList & *keys*) [inline]

Definition at line 72 of file kbbind.h.

References resetAction().

Referenced by resetAction().

```
72 { foreach(const QString& key, keys) resetAction(key); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.29 void KbBind::save (CkbSettings & *settings*)

Definition at line 81 of file kbbind.cpp.

References _bind, _map, _needsSave, _winLock, KeyAction::defaultAction(), KeyMap::name(), CkbSettings::setValue(), and KeyAction::value().

Referenced by KbMode::save().

```
81                                      {
82     _needsSave = false;
83     SGroup group(settings, "Binding");
84     settings.setValue("KeyMap", _map.name());
85     // Save key settings
86     settings.setValue("UseRealNames", true);
87     {
88         SGroup group(settings, "Keys");
89         foreach(QString key, _bind.keys()){
90             KeyAction* act = _bind.value(key);
91             if(act && act->value() != KeyAction::defaultAction(key))
92                 settings.setValue(key, act->value());
93         }
94     }
95     settings.setValue("WinLock", _winLock);
96 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.30 void KbBind::saveGlobalRemap ( ) [static]

Definition at line 124 of file kbbind.cpp.

References _globalRemap, and CkbSettings::setValue().

Referenced by SettingsWidget::updateModifiers().

```
124                                 {
125     CkbSettings settings("Program/GlobalRemap", true);
126     QHashIterator<QString, QString> i(_globalRemap);
127     while(i.hasNext()){
128         i.next();
129         settings.setValue(i.key(), i.value());
130     }
131 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.31 void KbBind::setAction (const QString & *key*, const QString & *action*)

Definition at line 180 of file kbbind.cpp.

References _bind, _map, globalRemap(), KeyMap::key(), KeyAction, and resetAction().

Referenced by RebindWidget::applyChanges(), and KbBindWidget::on_copyButton_clicked().

```
180                                                                 {
181     resetAction(key);
182     QString rKey = globalRemap(key);
183     if(!_map.key(rKey))
184         return;
185     _bind[rKey] = new KeyAction(action, this);
186 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.32 void KbBind::setAction (const QStringList & *keys*, const QString & *action*) [inline]

Definition at line 69 of file kbbind.h.

References setAction().

Referenced by setAction().

```
69 { foreach(const QString& key, keys) setAction(key, action); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.33 void KbBind::setGlobalRemap (const QHash< QString, QString > *keyToActual*) [static]

Definition at line 104 of file kbbind.cpp.

References _globalRemap, and globalRemapTime.

Referenced by SettingsWidget::updateModifiers().

```
104                                                                 {
105     _globalRemap.clear();
106     // Ignore any keys with the standard binding
107     QHashIterator<QString, QString> i(keyToActual);
108     while(i.hasNext()){
109         i.next();
110         if(i.key() != i.value())
111             _globalRemap[i.key()] = i.value();
112     }
113     globalRemapTime = QDateTime::currentMSecsSinceEpoch();
114 }
```

Here is the caller graph for this function:

12.25.3.34 void KbBind::setNeedsUpdate ( ) [inline]

Definition at line 84 of file kbbind.h.

References _needsUpdate.

Referenced by KbMode::setNeedsUpdate().

```
84 { _needsUpdate = true; }
```

Here is the caller graph for this function:

12.25.3.35 void KbBind::update (QFile & *cmd*, bool *force* = false)

Definition at line 188 of file kbbind.cpp.

References _bind, _globalRemap, _needsUpdate, _winLock, bindAction(), KeyAction::driverName(), globalRemapTime, KeyAction::isValidMacro(), lastCmd, lastGlobalRemapTime, KeyAction::macroContent(), updated(), and KeyAction::value().

Referenced by Kb::frameUpdate().

```
188                                         {
189     if(!force && !_needsUpdate && lastGlobalRemapTime ==
      globalRemapTime)
190         return;
```

```
    lastGlobalRemapTime = globalRemapTime;
    emit updated();
    _needsUpdate = false;
    // Reset all keys and enable notifications for all
    cmd.write("rebind all notify all");
    // Make sure modifier keys are included as they may be remapped globally
    QHash<QString, KeyAction*> bind(_bind);
    if(!_bind.contains("caps")) bind["caps"] = 0;
    if(!_bind.contains("lshift")) bind["lshift"] = 0;
    if(!_bind.contains("rshift")) bind["rshift"] = 0;
    if(!_bind.contains("lctrl")) bind["lctrl"] = 0;
    if(!_bind.contains("rctrl")) bind["rctrl"] = 0;
    if(!_bind.contains("lwin")) bind["lwin"] = 0;
    if(!_bind.contains("rwin")) bind["rwin"] = 0;
    if(!_bind.contains("lalt")) bind["lalt"] = 0;
    if(!_bind.contains("ralt")) bind["ralt"] = 0;
    if(!_bind.contains("fn")) bind["fn"] = 0;
    QHashIterator<QString, KeyAction*> i(bind);

    // Initialize String buffer for macro Key definitions (G-keys)
    // "macro clear" is neccessary, if an older definition is unbound.
    QString macros = "\nmacro clear\n";

    // Write out rebound keys and collect infos for macro definitions
    while(i.hasNext()){
        i.next();
        QString key = i.key();
        KeyAction* act = i.value();
        if(_globalRemap.contains(key))
            act = bindAction(_globalRemap.value(key));
        if(!act)
            continue;
        QString value = act->driverName();
        if(value.isEmpty()){
            // If the key is unbound or is a special action, unbind it
            cmd.write(" unbind ");
            cmd.write(key.toLatin1());
            // if a macro definiton for the key is given,
            // add the converted string to key-buffer "macro"
            if (act->isValidMacro()) {
                if (act->macroContent().length() > 0) {
                    macros.append("macro " + key.toLatin1() + ":" + act->macroContent().toLatin1() + "\n");
                }
            }
        } else {
            // Otherwise, write the binding
            cmd.write(" bind ");
            cmd.write(key.toLatin1());
            cmd.write(":");
            cmd.write(value.toLatin1());
        }
    }
    // If win lock is enabled, unbind windows keys
    if(_winLock)
        cmd.write(" unbind lwin rwin");

    // At last, send Macro definitions if avalilable.
    // If no definitions are made, clear macro will be sent only to reset all macros,
    cmd.write(macros.toLatin1());
    lastCmd = &cmd;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.25.3.36 void KbBind::updated ( ) [signal]

Definition at line 167 of file moc_kbbind.cpp.

Referenced by update().

```
168 {
169     QMetaObject::activate(this, &staticMetaObject, 2, Q_NULLPTR);
170 }
```

Here is the caller graph for this function:

12.25.3.37 bool KbBind::winLock ( ) [inline]

Definition at line 78 of file kbbind.h.

References _winLock.

Referenced by KeyAction::keyEvent().

```
78 { return _winLock; }
```

Here is the caller graph for this function:

12.25.3.38 void KbBind::winLock (bool *newWinLock*) [inline]

Definition at line 79 of file kbbind.h.

References _needsUpdate, and _winLock.

```
79 { _winLock = newWinLock; _needsUpdate = true; }
```

12.25.4 Friends And Related Function Documentation

12.25.4.1 friend class KeyAction [friend]

Definition at line 136 of file kbbind.h.

Referenced by bindAction(), friendlyActionName(), KbBind(), load(), noAction(), and setAction().

12.25.5 Field Documentation

12.25.5.1 QHash<QString, KeyAction*> KbBind::_bind [private]

Definition at line 131 of file kbbind.h.

Referenced by bindAction(), KbBind(), load(), noAction(), resetAction(), save(), setAction(), and update().

12.25.5.2 Kb* KbBind::_devParent [private]

Definition at line 113 of file kbbind.h.

Referenced by devParent().

12.25.5.3 QHash< QString, QString > KbBind::_globalRemap [static], [private]

Definition at line 119 of file kbbind.h.

Referenced by globalRemap(), loadGlobalRemap(), saveGlobalRemap(), setGlobalRemap(), and update().

12.25.5.4 KeyMap KbBind::_map [private]

Definition at line 129 of file kbbind.h.

Referenced by friendlyActionName(), friendlyName(), isISO(), isKeyboard(), isMouse(), load(), map(), noAction(), save(), and setAction().

12.25.5.5 bool KbBind::_needsSave [private]

Definition at line 135 of file kbbind.h.

Referenced by load(), map(), needsSave(), resetAction(), and save().

12.25.5.6 bool KbBind::_needsUpdate [private]

Definition at line 134 of file kbbind.h.

Referenced by map(), resetAction(), setNeedsUpdate(), update(), and winLock().

12.25.5.7 bool KbBind::_winLock [private]

Definition at line 133 of file kbbind.h.

Referenced by load(), save(), update(), and winLock().

12.25.5.8 quint64 KbBind::globalRemapTime = 0 [static], [private]

Definition at line 120 of file kbbind.h.

Referenced by loadGlobalRemap(), setGlobalRemap(), and update().

12.25.5.9 QFile* KbBind::lastCmd [private]

Definition at line 127 of file kbbind.h.

Referenced by handleNotificationChannel(), and update().

12.25.5.10 quint64 KbBind::lastGlobalRemapTime [private]

Definition at line 121 of file kbbind.h.

Referenced by update().

The documentation for this class was generated from the following files:

- src/ckb/kbbind.h
- src/ckb/kbbind.cpp
- src/ckb/release/moc_kbbind.cpp

12.26 Ui::KbBindWidget Class Reference

```
#include <src/ckb/ui_kbbindwidget.h>
```

Inheritance diagram for Ui::KbBindWidget:

Collaboration diagram for Ui::KbBindWidget:

Public Member Functions

- void setupUi (QWidget *KbBindWidget)
- void retranslateUi (QWidget *KbBindWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QLabel * label
- QFrame * line
- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer_2
- KeyWidget * keyWidget
- QSpacerItem * horizontalSpacer
- QHBoxLayout * horizontalLayout_2
- QPushButton * copyButton
- QLabel * selectLabel
- QPushButton * resetButton
- QSpacerItem * verticalSpacer
- QLabel * label_2
- QFrame * line_2
- QWidget * widget
- QGridLayout * gridLayout_2
- RebindWidget * rbWidget

12.26.1 Detailed Description

Definition at line 206 of file ui_kbbindwidget.h.

12.26.2 Member Function Documentation

12.26.2.1 void Ui_KbBindWidget::retranslateUi (QWidget * *KbBindWidget*) [inline],[inherited]

Definition at line 193 of file ui_kbbindwidget.h.

References Ui_KbBindWidget::copyButton, Ui_KbBindWidget::label, Ui_KbBindWidget::label_2, Ui_KbBindWidget::resetButton, and Ui_KbBindWidget::selectLabel.

Referenced by Ui_KbBindWidget::setupUi().

```
    {
        KbBindWidget->setWindowTitle(QApplication::translate("KbBindWidget", "Form", Q_NULLPTR));
        label->setText(QApplication::translate("KbBindWidget", "Keys", Q_NULLPTR));
        copyButton->setText(QApplication::translate("KbBindWidget", "Copy to mode...", Q_NULLPTR));
        selectLabel->setText(QApplication::translate("KbBindWidget", "Click to select keys", Q_NULLPTR));
        resetButton->setText(QApplication::translate("KbBindWidget", "Reset", Q_NULLPTR));
        label_2->setText(QApplication::translate("KbBindWidget", "Binding", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.26.2.2 void Ui_KbBindWidget::setupUi (QWidget * *KbBindWidget*) [inline],[inherited]

Definition at line 51 of file ui_kbbindwidget.h.

References Ui_KbBindWidget::copyButton, Ui_KbBindWidget::gridLayout, Ui_KbBindWidget::gridLayout_2, Ui_KbBindWidget::horizontalLayout_2, Ui_KbBindWidget::horizontalSpacer, Ui_KbBindWidget::horizontalSpacer_2, Ui_KbBindWidget::keyWidget, Ui_KbBindWidget::label, Ui_KbBindWidget::label_2, Ui_KbBindWidget::line, Ui_KbBindWidget::line_2, Ui_KbBindWidget::rbWidget, Ui_KbBindWidget::resetButton, Ui_KbBindWidget::retranslateUi(), Ui_KbBindWidget::selectLabel, Ui_KbBindWidget::verticalLayout, Ui_KbBindWidget::verticalSpacer, and Ui_KbBindWidget::widget.

Referenced by KbBindWidget::KbBindWidget().

```
52     {
53         if (KbBindWidget->objectName().isEmpty())
54             KbBindWidget->setObjectName(QStringLiteral("KbBindWidget"));
55         KbBindWidget->resize(581, 473);
56         verticalLayout = new QVBoxLayout(KbBindWidget);
57         verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
58         verticalLayout->setContentsMargins(0, 0, 0, -1);
59         label = new QLabel(KbBindWidget);
60         label->setObjectName(QStringLiteral("label"));
61         QFont font;
62         font.setBold(true);
63         font.setWeight(75);
64         label->setFont(font);
65
66         verticalLayout->addWidget(label);
67
68         line = new QFrame(KbBindWidget);
69         line->setObjectName(QStringLiteral("line"));
70         line->setFrameShape(QFrame::HLine);
71         line->setFrameShadow(QFrame::Sunken);
72
73         verticalLayout->addWidget(line);
74
75         gridLayout = new QGridLayout();
76         gridLayout->setObjectName(QStringLiteral("gridLayout"));
77         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
78
79         gridLayout->addItem(horizontalSpacer_2, 0, 4, 1, 1);
80
81         keyWidget = new KeyWidget(KbBindWidget);
82         keyWidget->setObjectName(QStringLiteral("keyWidget"));
83         QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Preferred);
84         sizePolicy.setHorizontalStretch(0);
85         sizePolicy.setVerticalStretch(0);
86         sizePolicy.setHeightForWidth(keyWidget->sizePolicy().hasHeightForWidth());
87         keyWidget->setSizePolicy(sizePolicy);
88
89         gridLayout->addWidget(keyWidget, 0, 1, 1, 3);
90
91         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
92
93         gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);
94
95         horizontalLayout_2 = new QHBoxLayout();
96         horizontalLayout_2->setSpacing(0);
97         horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
98         copyButton = new QPushButton(KbBindWidget);
99         copyButton->setObjectName(QStringLiteral("copyButton"));
100         QSizePolicy sizePolicy1(QSizePolicy::Fixed, QSizePolicy::Fixed);
101         sizePolicy1.setHorizontalStretch(0);
102         sizePolicy1.setVerticalStretch(0);
103         sizePolicy1.setHeightForWidth(copyButton->sizePolicy().hasHeightForWidth());
104         copyButton->setSizePolicy(sizePolicy1);
105         copyButton->setMinimumSize(QSize(140, 0));
106         copyButton->setMaximumSize(QSize(140, 16777215));
107
108         horizontalLayout_2->addWidget(copyButton);
109
110         selectLabel = new QLabel(KbBindWidget);
111         selectLabel->setObjectName(QStringLiteral("selectLabel"));
112         QSizePolicy sizePolicy2(QSizePolicy::Expanding, QSizePolicy::Preferred);
113         sizePolicy2.setHorizontalStretch(0);
114         sizePolicy2.setVerticalStretch(0);
115         sizePolicy2.setHeightForWidth(selectLabel->sizePolicy().hasHeightForWidth());
116         selectLabel->setSizePolicy(sizePolicy2);
117         selectLabel->setAlignment(Qt::AlignCenter);
118
119         horizontalLayout_2->addWidget(selectLabel);
```

```

        resetButton = new QPushButton(KbBindWidget);
        resetButton->setObjectName(QStringLiteral("resetButton"));
        QSizePolicy sizePolicy3(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy3.setHorizontalStretch(0);
        sizePolicy3.setVerticalStretch(0);
        sizePolicy3.setHeightForWidth(resetButton->sizePolicy().hasHeightForWidth());
        resetButton->setSizePolicy(sizePolicy3);
        resetButton->setMinimumSize(QSize(140, 0));
        resetButton->setMaximumSize(QSize(140, 16777215));

        horizontalLayout_2->addWidget(resetButton);


        gridLayout->addLayout(horizontalLayout_2, 1, 1, 1, 3);


        verticalLayout->addLayout(gridLayout);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

        verticalLayout->addItem(verticalSpacer);

        label_2 = new QLabel(KbBindWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        verticalLayout->addWidget(label_2);

        line_2 = new QFrame(KbBindWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line_2);

        widget = new QWidget(KbBindWidget);
        widget->setObjectName(QStringLiteral("widget"));
        QSizePolicy sizePolicy4(QSizePolicy::Preferred, QSizePolicy::Fixed);
        sizePolicy4.setHorizontalStretch(0);
        sizePolicy4.setVerticalStretch(0);
        sizePolicy4.setHeightForWidth(widget->sizePolicy().hasHeightForWidth());
        widget->setSizePolicy(sizePolicy4);
        widget->setMinimumSize(QSize(0, 280));
        widget->setMaximumSize(QSize(16777215, 280));
        gridLayout_2 = new QGridLayout(widget);
        gridLayout_2->setSpacing(0);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(0, 0, 0, 0);
        rbWidget = new RebindWidget(widget);
        rbWidget->setObjectName(QStringLiteral("rbWidget"));
        QSizePolicy sizePolicy5(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy5.setHorizontalStretch(0);
        sizePolicy5.setVerticalStretch(0);
        sizePolicy5.setHeightForWidth(rbWidget->sizePolicy().hasHeightForWidth());
        rbWidget->setSizePolicy(sizePolicy5);

        gridLayout_2->addWidget(rbWidget, 0, 0, 1, 1);


        verticalLayout->addWidget(widget);

        label->raise();
        line->raise();
        label_2->raise();
        line_2->raise();
        widget->raise();

        retranslateUi(KbBindWidget);

        QMetaObject::connectSlotsByName(KbBindWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.26.3 Field Documentation

12.26.3.1 QPushButton* Ui_KbBindWidget::copyButton [inherited]

Definition at line 41 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::retranslateUi(), and Ui_KbBindWidget::setupUi().

12.26.3.2 QGridLayout* Ui_KbBindWidget::gridLayout [inherited]

Definition at line 36 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.3 QGridLayout* Ui_KbBindWidget::gridLayout_2 [inherited]

Definition at line 48 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.4 QHBoxLayout* Ui_KbBindWidget::horizontalLayout_2 [inherited]

Definition at line 40 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.5 QSpacerItem* Ui_KbBindWidget::horizontalSpacer [inherited]

Definition at line 39 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.6 QSpacerItem* Ui_KbBindWidget::horizontalSpacer_2 [inherited]

Definition at line 37 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.7 KeyWidget* Ui_KbBindWidget::keyWidget [inherited]

Definition at line 38 of file ui_kbbindwidget.h.

Referenced by KbBindWidget::KbBindWidget(), KbBindWidget::newLayout(), KbBindWidget::setBind(), Ui_KbBindWidget::setupUi(), and KbBindWidget::updateBind().

12.26.3.8 QLabel* Ui_KbBindWidget::label [inherited]

Definition at line 34 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::retranslateUi(), and Ui_KbBindWidget::setupUi().

12.26.3.9 QLabel* Ui_KbBindWidget::label_2 [inherited]

Definition at line 45 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::retranslateUi(), and Ui_KbBindWidget::setupUi().

12.26.3.10 QFrame* Ui_KbBindWidget::line [inherited]

Definition at line 35 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.11 QFrame* Ui_KbBindWidget::line_2 [inherited]

Definition at line 46 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.12 RebindWidget* Ui_KbBindWidget::rbWidget [inherited]

Definition at line 49 of file ui_kbbindwidget.h.

Referenced by KbBindWidget::newLayout(), KbBindWidget::newSelection(), KbBindWidget::setBind(), Ui_KbBindWidget::setupUi(), and KbBindWidget::updateBind().

12.26.3.13 QPushButton* Ui_KbBindWidget::resetButton [inherited]

Definition at line 43 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::retranslateUi(), and Ui_KbBindWidget::setupUi().

12.26.3.14 QLabel* Ui_KbBindWidget::selectLabel [inherited]

Definition at line 42 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::retranslateUi(), Ui_KbBindWidget::setupUi(), and KbBindWidget::updateSelDisplay().

12.26.3.15 QVBoxLayout* Ui_KbBindWidget::verticalLayout [inherited]

Definition at line 33 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.16 QSpacerItem* Ui_KbBindWidget::verticalSpacer [inherited]

Definition at line 44 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

12.26.3.17 QWidget* Ui_KbBindWidget::widget [inherited]

Definition at line 47 of file ui_kbbindwidget.h.

Referenced by Ui_KbBindWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbbindwidget.h

12.27 KbBindWidget Class Reference

```
#include <src/ckb/kbbindwidget.h>
```

Inheritance diagram for KbBindWidget:

Collaboration diagram for KbBindWidget:

Public Member Functions

- KbBindWidget (QWidget ∗parent=0)
- ∼KbBindWidget ()
- void setBind (KbBind ∗newBind, KbProfile ∗newProfile)

Private Slots

- void updateBind ()
- void newLayout ()
- void newSelection (QStringList selection)
- void updateSelDisplay ()
- void on_resetButton_clicked ()
- void on_copyButton_clicked ()

Private Attributes

- Ui::KbBindWidget ∗ ui
- KbBind ∗ bind
- KbProfile ∗ profile
- QStringList currentSelection

12.27.1 Detailed Description

Definition at line 12 of file kbbindwidget.h.

12.27.2 Constructor & Destructor Documentation

12.27.2.1 KbBindWidget::KbBindWidget (QWidget * *parent* = 0) [explicit]

Definition at line 7 of file kbbindwidget.cpp.

References Ui_KbBindWidget::keyWidget, newSelection(), KeyWidget::rgbMode(), Ui_KbBindWidget::setupUi(), and ui.

```
7                                           :
8     QWidget(parent),
9     ui(new Ui::KbBindWidget), bind(0), profile(0)
10 {
11     ui->setupUi(this);
12     ui->keyWidget->rgbMode(false);
13     connect(ui->keyWidget, SIGNAL(selectionChanged(QStringList)), this, SLOT(
      newSelection(QStringList)));
14 }
```

Here is the call graph for this function:

12.27.2.2 KbBindWidget::~KbBindWidget ( )

Definition at line 16 of file kbbindwidget.cpp.

References ui.

```
16                                  {
17     delete ui;
18 }
```

12.27.3 Member Function Documentation

12.27.3.1 void KbBindWidget::newLayout ( ) [private],[slot]

Definition at line 50 of file kbbindwidget.cpp.

References bind, Ui_KbBindWidget::keyWidget, KeyWidget::map(), KbBind::map(), profile, Ui_KbBindWidget::rbWidget, RebindWidget::setBind(), ui, and updateSelDisplay().

Referenced by setBind().

```
50                                {
51     ui->keyWidget->map(bind->map());
52     ui->rbWidget->setBind(bind, profile);
53     updateSelDisplay();
54 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.27.3.2 void KbBindWidget::newSelection (QStringList *selection*) [private], [slot]

Definition at line 56 of file kbbindwidget.cpp.

References currentSelection, Ui_KbBindWidget::rbWidget, RebindWidget::setSelection(), ui, and updateSelDisplay().

Referenced by KbBindWidget(), and setBind().

```
56                                                  {
57     currentSelection = selection;
58     ui->rbWidget->setSelection(selection, true);
59     updateSelDisplay();
60 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.27.3.3 void KbBindWidget::on_copyButton_clicked ( ) [private],[slot]

Definition at line 103 of file kbbindwidget.cpp.

References KbBind::action(), bind, KbMode::bind(), KeyMap::count(), KbProfile::currentMode(), currentSelection, KbBind::isMouse(), KeyMap::keys(), KbBind::map(), KbProfile::modes(), profile, ModeSelectDialog::selection(), KbBind::setAction(), and KeyAction::type().

```
103                                         {
104     QStringList selection = currentSelection;
105     const KeyMap& map = bind->map();
106     int count = selection.count();
107     QString type = bind->isMouse() ? "button" : "key";
108     QString text = tr("%1 %2").arg(count).arg(type) + (count == 1 ? "" : "s");
109     if(count == 0){
110         // Copy all keys if none selected
111         selection = map.keys();
112         text = tr("all %1s").arg(type);
113     }
114     text = "Copy binding for " + text + " to:";
115     // Display popup
116     ModeSelectDialog dialog(this, profile->currentMode(),
      profile->modes(), text);
117     if(dialog.exec() != QDialog::Accepted)
118         return;
119     // Copy selected keys to selected modes
120     QList<KbMode*> selectedModes = dialog.selection();
121     foreach(KbMode* mode, selectedModes){
122         KbBind* modeBind = mode->bind();
123         foreach(const QString& key, selection){
124             modeBind->setAction(key, bind->action(key));
125         }
126     }
127 }
```

Here is the call graph for this function:

12.27.3.4 void KbBindWidget::on_resetButton_clicked ( ) [private],[slot]

Definition at line 82 of file kbbindwidget.cpp.

References bind, KeyMap::count(), currentSelection, KbBind::isMouse(), KeyMap::keys(), KbBind::map(), KbBind::resetAction(), KeyAction::type(), and updateBind().

```
82                                          {
83     QStringList selection = currentSelection;
84     const KeyMap& map = bind->map();
85     if(selection.isEmpty())
86         // Reset all keys if none selected
87         selection = map.keys();
88     uint count = selection.count();
89     QString type = bind->isMouse() ? "button" : "key";
90     QString text;
91     if(count == map.count())
92         text = "<center>Reset all %1s to default?</center>";
93     else if(count == 1)
94         text = "<center>Reset this %1 to default?</center>";
95     else
96         text = tr("<center>Reset %1 %2s to default?</center>").arg(count);
97     if(QMessageBox(QMessageBox::NoIcon, "Confirm action", text.arg(type), QMessageBox::Yes |
       QMessageBox::No, this).exec() != QMessageBox::Yes)
98         return;
99     bind->resetAction(selection);
100     updateBind();
101 }
```

Here is the call graph for this function:

12.27.3.5 void KbBindWidget::setBind (KbBind * *newBind*, KbProfile * *newProfile*)

Definition at line 20 of file kbbindwidget.cpp.

References bind, KeyWidget::clearSelection(), Ui_KbBindWidget::keyWidget, newLayout(), newSelection(), profile, Ui_KbBindWidget::rbWidget, RebindWidget::setBind(), ui, and updateBind().

Referenced by KbWidget::modeChanged().

```
                                                        {
    ui->keyWidget->clearSelection();
    ui->rbWidget->setBind(newBind, newProfile);
    newSelection(QStringList());
    if(bind == newBind)
        return;
    if(bind){
        disconnect(bind, SIGNAL(layoutChanged()), this, SLOT(newLayout()));
        disconnect(bind, SIGNAL(updated()), this, SLOT(updateBind()));
    }
    connect(newBind, SIGNAL(layoutChanged()), this, SLOT(newLayout()));
    connect(newBind, SIGNAL(updated()), this, SLOT(updateBind()));
    bind = newBind;
    profile = newProfile;
    newLayout();
    ui->rbWidget->setBind(bind, profile);
    updateBind();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.27.3.6 void KbBindWidget::updateBind ( ) [private],[slot]

Definition at line 39 of file kbbindwidget.cpp.

References KbBind::action(), bind, KeyWidget::bindMap(), currentSelection, KeyMap::keys(), Ui_KbBindWidget::keyWidget, KbBind::map(), Ui_KbBindWidget::rbWidget, RebindWidget::setSelection(), ui, and updateSelDisplay().

Referenced by on_resetButton_clicked(), and setBind().

```
39                                {
40     const KeyMap& map = bind->map();
41     // Build the action list based on the keymap
42     QHash<QString, QString> actions;
43     foreach(const QString& key, map.keys())
44         actions[key] = bind->action(key);
45     ui->keyWidget->bindMap(actions);
46     ui->rbWidget->setSelection(currentSelection);
47     updateSelDisplay();
48 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.27.3.7 void KbBindWidget::updateSelDisplay ( ) [private],[slot]

Definition at line 62 of file kbbindwidget.cpp.

References bind, currentSelection, KbBind::friendlyActionName(), Key::friendlyName(), KbBind::isMouse(), KbBind::map(), Ui_KbBindWidget::selectLabel, and ui.

Referenced by newLayout(), newSelection(), and updateBind().

```
62                                  {
63     int count = currentSelection.count();
64     if(count == 0){
65         // No keys selected
66         ui->selectLabel->setText("Click to select");
67         return;
68     }
69     if(count == 1){
70         // Single key selected: show key name and binding
71         QString key = currentSelection[0];
72         const Key& pos = bind->map()[key];
73         if(!pos)
74             ui->selectLabel->setText("(Unknown)");
75         else
76             ui->selectLabel->setText(pos.friendlyName(false).split("\n")[0] + " →
      " + bind->friendlyActionName(key).split("\n")[0]);
77         return;
78     }
79     ui->selectLabel->setText(QString("%1 %2 selected").arg(count).arg(
      bind->isMouse() ? "buttons" : "keys"));
80 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.27.4 Field Documentation

12.27.4.1 KbBind* KbBindWidget::bind [private]

Definition at line 34 of file kbbindwidget.h.

Referenced by newLayout(), on_copyButton_clicked(), on_resetButton_clicked(), setBind(), updateBind(), and updateSelDisplay().

12.27.4.2 QStringList KbBindWidget::currentSelection [private]

Definition at line 36 of file kbbindwidget.h.

Referenced by newSelection(), on_copyButton_clicked(), on_resetButton_clicked(), updateBind(), and updateSelDisplay().

12.27.4.3 KbProfile* KbBindWidget::profile [private]

Definition at line 35 of file kbbindwidget.h.

Referenced by newLayout(), on_copyButton_clicked(), and setBind().

12.27.4.4 Ui::KbBindWidget* KbBindWidget::ui [private]

Definition at line 32 of file kbbindwidget.h.

Referenced by KbBindWidget(), newLayout(), newSelection(), setBind(), updateBind(), updateSelDisplay(), and ~KbBindWidget().

The documentation for this class was generated from the following files:

- src/ckb/kbbindwidget.h
- src/ckb/kbbindwidget.cpp

12.28 KbFirmware Class Reference

```
#include <src/ckb/kbfirmware.h>
```

Inheritance diagram for KbFirmware:

Collaboration diagram for KbFirmware:

Data Structures

- struct FW

Signals

- void downloaded ()

Static Public Member Functions

- static bool checkUpdates ()
- static bool hasDownloaded ()
- static float versionForBoard (const QString &features, bool waitForComplete=false)
- static QByteArray dataForBoard (const QString &features)

Private Types

- enum { UNKNOWN = -1, NO, YES }

Private Slots

- void processDownload (QNetworkReply ∗reply)
- void downloadFinished ()

Private Member Functions

- KbFirmware ()
- ∼KbFirmware ()
- void initManager ()
- bool _checkUpdates ()
- float _latestForBoard (const QString &features, bool waitForComplete)
- QByteArray _fileForBoard (const QString &features)

Private Attributes

- quint64 lastCheck
- quint64 lastFinished
- QMap< QString, FW > fwTable
- QByteArray fwTableHash
- QNetworkAccessManager ∗ networkManager
- QNetworkReply ∗ tableDownload
- enum KbFirmware:: { ... } hasGPG

Static Private Attributes

- static KbFirmware instance

12.28.1 Detailed Description

Definition at line 10 of file kbfirmware.h.

12.28.2 Member Enumeration Documentation

12.28.2.1 anonymous enum [private]

Enumerator

UNKNOWN

NO

YES

Definition at line 53 of file kbfirmware.h.

```
53 { UNKNOWN = -1, NO, YES } hasGPG :2;
```

12.28.3 Constructor & Destructor Documentation

12.28.3.1 KbFirmware::KbFirmware ( ) [private]

Definition at line 14 of file kbfirmware.cpp.

```
14                          :
15     lastCheck(0), lastFinished(0), networkManager(0),
       tableDownload(0), hasGPG(UNKNOWN)
16 {
17 }
```

12.28.3.2 KbFirmware::~KbFirmware ( ) [private]

Definition at line 19 of file kbfirmware.cpp.

```
19                          {
20     //delete networkManager;
21     // ^ This can cause a crash (QT bug?)
22 }
```

12.28.4 Member Function Documentation

12.28.4.1 bool KbFirmware::_checkUpdates ( ) [private]

Definition at line 30 of file kbfirmware.cpp.

References AUTO_CHECK_TIME, downloadFinished(), initManager(), lastCheck, networkManager, and tableDownload.

Referenced by checkUpdates().

```
30                                  {
31     initManager();
32     quint64 now = QDateTime::currentMSecsSinceEpoch();
33     if(now < lastCheck + AUTO_CHECK_TIME)
34         return false;
35     // First location is for debugging only.
36     // tableDownload =
       networkManager->get(QNetworkRequest(QUrl("https://raw.githubusercontent.com/frickler24/ckb-next/issues-26-Firmware-Inc
37     // This one is the production one.
38     tableDownload = networkManager->get(QNetworkRequest(QUrl("
       https://raw.githubusercontent.com/mattanger/ckb-next/master/FIRMWARE")));
39     connect(tableDownload, SIGNAL(finished()), this, SLOT(
       downloadFinished()));
40     lastCheck = now;
41     return true;
42 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.2 QByteArray KbFirmware::_fileForBoard (const QString & *features*) [private]

Definition at line 183 of file kbfirmware.cpp.

References QuaZip::csInsensitive, KbFirmware::FW::fileName, fwTable, KbFirmware::FW::hash, QuaZip::mdUnzip, networkManager, QuaZip::open(), QuaZipFile::open(), QuaZip::setCurrentFile(), tableName(), and KbFirmware::FW::url.

Referenced by dataForBoard().

```
183                                                         {
184     QString name = tableName(features);
185     FW info = fwTable.value(name);
186     if(info.hash.isEmpty())
187         return "";
188     // Download zip from URL. Wait for it to finish.
189     QNetworkReply* reply = networkManager->get(QNetworkRequest(QUrl(info.url)));
190     QEventLoop loop(this);
191     connect(reply, SIGNAL(finished()), &loop, SLOT(quit()));
192     loop.exec();
193     // Download finished, process data
194     if(reply->error() != QNetworkReply::NoError)
195         return "";
196     QByteArray zipData = reply->readAll();
197     QBuffer buffer(&zipData);
198     // Open zip archive
199     QuaZip zip(&buffer);
200     if(!zip.open(QuaZip::mdUnzip))
201         return "";
202     // Find the desired file
203     if(!zip.setCurrentFile(info.fileName, QuaZip::csInsensitive))
204         return "";
205     QuaZipFile binFile(&zip);
206     if(!binFile.open(QIODevice::ReadOnly))
207         return "";
208     QByteArray binary = binFile.readAll();
209     // Check the hash
210     if(QCryptographicHash::hash(binary, QCryptographicHash::Sha256) != info.hash)
211         return "";
212     return binary;
213 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.3 float KbFirmware::_latestForBoard (const QString & *features*, bool *waitForComplete*) [private]

Definition at line 165 of file kbfirmware.cpp.

References checkUpdates(), KbManager::ckbDaemonVersionF(), KbManager::ckbGuiVersionF(), KbFirmware::FW::ckbVersion, downloaded(), fwTable, KbFirmware::FW::fwVersion, KbFirmware::FW::hash, tableDownload, and tableName().

Referenced by versionForBoard().

```
165                                                                                 {
166     if((tableDownload || checkUpdates()) && waitForComplete){
167         // If waiting is desired, enter an event loop and stay here until the download is finished
168         QEventLoop loop(this);
169         connect(this, SIGNAL(downloaded()), &loop, SLOT(quit()));
170         loop.exec();
171     }
172     // Find this board
173     QString name = tableName(features);
174     FW info = fwTable.value(name);
175     if(info.hash.isEmpty())
176         return 0.f;
177     // Don't return the new version if the current ckb doesn't support it
178     if(info.ckbVersion > KbManager::ckbGuiVersionF() || info.ckbVersion >
    KbManager::ckbDaemonVersionF())
179         return -1.f;
180     return info.fwVersion;
181 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.4 static bool KbFirmware::checkUpdates ( ) [inline], [static]

Definition at line 15 of file kbfirmware.h.

References _checkUpdates(), and instance.

Referenced by _latestForBoard(), and MainWindow::timerTick().

```
15 { return instance._checkUpdates(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.5 static QByteArray KbFirmware::dataForBoard (const QString & *features*) [inline], [static]

Definition at line 25 of file kbfirmware.h.

References _fileForBoard(), and instance.

Referenced by FwUpgradeDialog::exec().

```
25 { return instance._fileForBoard(features); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.6 void KbFirmware::downloaded ( ) [signal]

Definition at line 148 of file moc_kbfirmware.cpp.

Referenced by _latestForBoard(), and downloadFinished().

```
149 {
150     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
151 }
```

Here is the caller graph for this function:

12.28.4.7 void KbFirmware::downloadFinished ( ) [private],[slot]

Definition at line 144 of file kbfirmware.cpp.

References downloaded(), processDownload(), and tableDownload.

Referenced by _checkUpdates().

```
                                {
    if(!tableDownload)
        return;
    processDownload(tableDownload);
    tableDownload->deleteLater();
    tableDownload = 0;
    emit downloaded();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.8 static bool KbFirmware::hasDownloaded ( ) [inline],[static]

Definition at line 18 of file kbfirmware.h.

References instance, and lastFinished.

Referenced by KbWidget::on_fwUpdButton_clicked(), and KbWidget::updateFwButton().

```
18 { return instance.lastFinished != 0; }
```

Here is the caller graph for this function:

12.28.4.9 void KbFirmware::initManager ( ) [private]

Definition at line 24 of file kbfirmware.cpp.

References networkManager.

Referenced by _checkUpdates().

```
                                {
    if(networkManager)
        return;
    networkManager = new QNetworkAccessManager();
}
```

Here is the caller graph for this function:

12.28.4.10 void KbFirmware::processDownload (QNetworkReply * *reply*) [private],[slot]

Definition at line 44 of file kbfirmware.cpp.

References KbFirmware::FW::ckbVersion, KbFirmware::FW::fileName, fwTable, fwTableHash, KbFirmware::FW::fwVersion, hasGPG, KbFirmware::FW::hash, lastCheck, lastFinished, NO, KbManager::parseVersionString(), UNKNOWN, KbFirmware::FW::url, and YES.

Referenced by downloadFinished().

```
44                                                  {
45     if(reply->error() != QNetworkReply::NoError)
46         return;
47     // Update last check
48     lastCheck = lastFinished = QDateTime::currentMSecsSinceEpoch();
49     QByteArray data = reply->readAll();
50     // Don't do anything if this is the same as the last version downloaded
51     QByteArray hash = QCryptographicHash::hash(data, QCryptographicHash::Sha256);
52     if(hash == fwTableHash)
53         return;
54     fwTableHash = hash;
55     if(hasGPG == UNKNOWN){
56         // Check for a GPG installation
57         QProcess gpg;
58         gpg.start("gpg", QStringList("--version"));
59         gpg.waitForFinished();
60         if(gpg.error() == QProcess::FailedToStart)
61             // No GPG install
62             hasGPG = NO;
63         else {
64             QString output = QString::fromUtf8(gpg.readAll());
65             // Must support RSA keys and SHA256
66             if(output.contains("RSA", Qt::CaseInsensitive) && output.contains("SHA256", Qt::CaseInsensitive
    ))
67                 hasGPG = YES;
68             else
69                 hasGPG = NO;
70         }
71         if(!hasGPG)
72             qDebug() << "No GPG detected, signature verification disabled";
73     }
74     if(hasGPG){
75         // If GPG is available, check the signature on the file before proceeding.
76         QDir tmp = QDir::temp();
77         // Save file to a temporary path. Include PID to avoid conflicts
78         qint64 pid = QCoreApplication::applicationPid();
79         QString fwPath = tmp.absoluteFilePath(QString("ckb-%1-firmware").arg(pid));
80         QFile firmware(fwPath);
81         if(!firmware.open(QIODevice::WriteOnly)
82                 || firmware.write(data) != data.length()){
83             qDebug() << "Failed to write firmware file to temporary location, aborting firmware check";
84             return;
85         }
86         firmware.close();
87         // Write GPG key
88         QString keyPath = tmp.absoluteFilePath(QString("ckb-%1-key.gpg").arg(pid));
89         if(!QFile::copy(":/bin/ckb-next-key.gpg", keyPath)){
90             firmware.remove();
91             qDebug() << "Failed to write GPG key to temporary location, aborting firmware check";
92             return;
93         }
94         // Check signature
95         QProcess gpg;
96         gpg.start("gpg", QStringList("--no-default-keyring") << "--keyring" << keyPath << "--verify" <<
    fwPath);
97         gpg.waitForFinished();
98         // Clean up temp files
99         tmp.remove(fwPath);
100         tmp.remove(keyPath);
```

```
        if(gpg.error() != QProcess::UnknownError || gpg.exitCode() != 0){
            qDebug() << "GPG couldn't verify firmware signature:";
            qDebug() << gpg.readAllStandardOutput();
            qDebug() << gpg.readAllStandardError();
            return;
        }
        // Signature good, proceed to update database
    }
    fwTable.clear();
    QStringList lines = QString::fromUtf8(data).split("\n");
    bool scan = false;
    foreach(QString line, lines){
        // Collapse whitespace
        line.replace(QRegExp("\\s+"), " ").remove(QRegExp("^\\s")).remove(QRegExp("\\s$"));
        // Skip empty or commented-out lines
        if(line.length() == 0 || line.at(0) == '#')
            continue;
        // Don't read anything until the entries begin and don't read anything after they end
        if(!scan){
            if(line == "!BEGIN FW ENTRIES")
                scan = true;
            else
                continue;
        }
        if(line == "!END FW ENTRIES")
            break;
        QStringList components = line.split(" ");
        if(components.length() != 7)
            continue;
        // "VENDOR-PRODUCT"
        QString device = components[0].toUpper() + "-" + components[1].toUpper();
        FW fw;
        fw.fwVersion = components[2].toFloat();                          // Firmware blob version
        fw.url = QUrl::fromPercentEncoding(components[3].toLatin1());    // URL to zip file
        fw.ckbVersion = KbManager::parseVersionString(components[4]);    //
    Minimum ckb version
        fw.fileName = QUrl::fromPercentEncoding(components[5].toLatin1());  // Name of file inside zip
        fw.hash = QByteArray::fromHex(components[6].toLatin1());            // SHA256 of file inside zip
        // Update entry
        fwTable[device] = fw;
    }
    qDebug() << "Downloaded new firmware list." << fwTable.count() << "entries found.";
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.4.11 static float KbFirmware::versionForBoard (const QString & *features*, bool *waitForComplete* = `false`) [inline], [static]

Definition at line 22 of file kbfirmware.h.

References _latestForBoard(), and instance.

Referenced by MainWindow::checkFwUpdates(), KbWidget::on_fwUpdButton_clicked(), and KbWidget::updateFwButton().

```
22 { return instance._latestForBoard(features, waitForComplete); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.28.5 Field Documentation

12.28.5.1 QMap<QString, FW> KbFirmware::fwTable [private]

Definition at line 41 of file kbfirmware.h.

Referenced by _fileForBoard(), _latestForBoard(), and processDownload().

12.28.5.2 QByteArray KbFirmware::fwTableHash [private]

Definition at line 43 of file kbfirmware.h.

Referenced by processDownload().

12.28.5.3 enum { ... } KbFirmware::hasGPG [private]

Referenced by processDownload().

12.28.5.4 KbFirmware KbFirmware::instance [static], [private]

Definition at line 59 of file kbfirmware.h.

Referenced by checkUpdates(), dataForBoard(), hasDownloaded(), and versionForBoard().

12.28.5.5 quint64 KbFirmware::lastCheck [private]

Definition at line 32 of file kbfirmware.h.

Referenced by _checkUpdates(), and processDownload().

12.28.5.6 quint64 KbFirmware::lastFinished [private]

Definition at line 32 of file kbfirmware.h.

Referenced by hasDownloaded(), and processDownload().

12.28.5.7 QNetworkAccessManager* KbFirmware::networkManager [private]

Definition at line 47 of file kbfirmware.h.

Referenced by _checkUpdates(), _fileForBoard(), and initManager().

12.28.5.8 QNetworkReply* KbFirmware::tableDownload [private]

Definition at line 50 of file kbfirmware.h.

Referenced by _checkUpdates(), _latestForBoard(), and downloadFinished().

The documentation for this class was generated from the following files:

- src/ckb/kbfirmware.h
- src/ckb/kbfirmware.cpp
- src/ckb/release/moc_kbfirmware.cpp

12.29 KbLight Class Reference

```
#include <src/ckb/kblight.h>
```

Inheritance diagram for KbLight:

Collaboration diagram for KbLight:

Public Types

- typedef QList< KbAnim * > AnimList

Signals

- void didLoad ()
- void updated ()
- void frameDisplayed (const ColorMap &animatedColors, const QSet< QString > &indicatorList)

Public Member Functions

- KbLight (KbMode *parent, const KeyMap &keyMap)
- KbLight (KbMode *parent, const KeyMap &keyMap, const KbLight &other)
- ~KbLight ()
- const KeyMap & map ()
- void map (const KeyMap &map)
- const QColorMap & colorMap ()
- void color (const QString &key, const QColor &newColor)
- void color (const QColor &newColor)
- int dimming ()
- void dimming (int newDimming)
- KbAnim * addAnim (const AnimScript *base, const QStringList &keys, const QString &name, const QMap< QString, QVariant > &preset)
- KbAnim * duplicateAnim (KbAnim *oldAnim)
- const AnimList & animList ()
- void animList (const AnimList &newAnimList)
- KbAnim * findAnim (const QUuid &guid) const

- int findAnimIdx (const QUuid &guid) const
- void previewAnim (const AnimScript *base, const QStringList &keys, const QMap< QString, QVariant > &preset)
- void stopPreview ()
- void restartAnimation ()
- void animKeypress (const QString &key, bool down)
- void open ()
- bool isStarted ()
- void close ()
- void resetIndicators ()
- void setIndicator (const char *name, QRgb argb)
- void frameUpdate (QFile &cmd, bool monochrome=false)
- void base (QFile &cmd, bool ignoreDim=false, bool monochrome=false)
- void load (CkbSettings &settings)
- void save (CkbSettings &settings)
- bool needsSave () const

Static Public Member Functions

- static int shareDimming ()
- static void shareDimming (int newShareDimming)

Static Public Attributes

- static const int MAX_DIM = 3

Private Member Functions

- void rebuildBaseMap ()
- void printRGB (QFile &cmd, const ColorMap &animMap)

Private Attributes

- AnimList _animList
- KbAnim * _previewAnim
- KeyMap _map
- QColorMap _qColorMap
- ColorMap _colorMap
- ColorMap _animMap
- ColorMap _indicatorMap
- QSet< QString > _indicatorList
- quint64 lastFrameSignal
- int _dimming
- bool _start
- bool _needsSave
- bool _needsMapRefresh

12.29.1 Detailed Description

Definition at line 17 of file kblight.h.

12.29.2 Member Typedef Documentation

12.29.2.1 typedef QList<KbAnim*> KbLight::AnimList

Definition at line 46 of file kblight.h.

12.29.3 Constructor & Destructor Documentation

12.29.3.1 KbLight::KbLight (KbMode * *parent*, const KeyMap & *keyMap*)

Definition at line 10 of file kblight.cpp.

References map().

```
10                                                    :
11     QObject(parent), _previewAnim(0), lastFrameSignal(0),
      _dimming(0), _start(false), _needsSave(true),
      _needsMapRefresh(true)
12 {
13     map(keyMap);
14 }
```

Here is the call graph for this function:

12.29.3.2 KbLight::KbLight (KbMode * *parent*, const KeyMap & *keyMap*, const KbLight & *other*)

Definition at line 16 of file kblight.cpp.

References _animList, and map().

```
16                                                                                    :
17     QObject(parent), _previewAnim(0), _map(other._map),
      _qColorMap(other._qColorMap), lastFrameSignal(0),
      _dimming(other._dimming), _start(false), _needsSave(true),
      _needsMapRefresh(true)
18 {
19     map(keyMap);
20     // Duplicate animations
21     foreach(KbAnim* animation, other._animList)
22         _animList.append(new KbAnim(this, keyMap, *animation));
23 }
```

Here is the call graph for this function:

12.29.3.3 KbLight::~KbLight ( )

Definition at line 45 of file kblight.cpp.

References activeLights.

```
45                  {
46      activeLights.remove(this);
47  }
```

12.29.4 Member Function Documentation

12.29.4.1 KbAnim * KbLight::addAnim (const AnimScript * *base*, const QStringList & *keys*, const QString & *name*, const QMap< QString, QVariant > & *preset*)

Definition at line 100 of file kblight.cpp.

References _animList, _map, _needsSave, _start, KbAnim::commitParams(), KbAnim::parameter(), KbAnim::stop(), stopPreview(), and KbAnim::trigger().

Referenced by KbAnimWidget::addAnim().

```
100
                                {
101     // Stop and restart all existing animations
102     stopPreview();
103     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
104     foreach(KbAnim* anim, _animList){
105         anim->stop();
106         anim->trigger(timestamp);
107     }
108     // Load the new animation and set preset parameters
109     KbAnim* anim = new KbAnim(this, _map, name, keys, base);
110     QMapIterator<QString, QVariant> i(preset);
111     while(i.hasNext()){
112         i.next();
113         anim->parameter(i.key(), i.value());
114     }
115     anim->commitParams();
116     // Add the animation and start it
117     _animList.append(anim);
118     anim->trigger(timestamp);
119     _start = true;
120     _needsSave = true;
121     return anim;
122 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.2 void KbLight::animKeypress (const QString & *key*, bool *down*)

Definition at line 189 of file kblight.cpp.

References _animList, _previewAnim, KbAnim::keypress(), and KbAnim::keys().

Referenced by Kb::readNotify().

```
189                                                 {
190     foreach(KbAnim* anim, _animList){
191         if(anim->keys().contains(key))
192             anim->keypress(key, down, QDateTime::currentMSecsSinceEpoch());
193     }
194     if(_previewAnim){
195         if(_previewAnim->keys().contains(key))
196             _previewAnim->keypress(key, down, QDateTime::currentMSecsSinceEpoch());
197     }
198 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.3 const AnimList& KbLight::animList ( ) [inline]

Definition at line 49 of file kblight.h.

References _animList.

Referenced by RebindWidget::applyChanges(), KbAnimWidget::duplicateAnim(), KbMode::newId(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::refreshList(), KbAnimWidget::reorderAnims(), and RebindWidget::setSelection().

```
49 { return _animList; }
```

Here is the caller graph for this function:

12.29.4.4 void KbLight::animList (const AnimList & *newAnimList*) [inline]

Definition at line 50 of file kblight.h.

References _animList, and _needsSave.

```
50 { _needsSave = true; _animList = newAnimList; }
```

12.29.4.5 void KbLight::base (QFile & *cmd*, bool *ignoreDim* = false, bool *monochrome* = false)

Definition at line 371 of file kblight.cpp.

References _animMap, _colorMap, _dimming, close(), ColorMap::colorForName(), ColorMap::colors(), ColorMap::count(), MAX_DIM, monoRgb(), printRGB(), and rebuildBaseMap().

Referenced by Kb::hwSave().

```
371                                                                 {
372     close();
373     if(_dimming == MAX_DIM && !ignoreDim){
374         cmd.write(QString().sprintf("rgb 000000").toLatin1());
375         return;
376     }
377     // Set just the background color, ignoring any animation
378     rebuildBaseMap();
379     _animMap = _colorMap;
380     // If monochrome is active, create grayscale
381     if(monochrome){
382         int count = _animMap.count();
383         QRgb* colors = _animMap.colors();
384         for(int i = 0; i < count; i++){
385             QRgb& rgb = colors[i];
386             rgb = monoRgb(qRed(rgb), qGreen(rgb), qBlue(rgb));
387         }
388     }
389     // Set a few indicators to black as the hardware handles them differently
390     QRgb* mr = _animMap.colorForName("mr"), *m1 = _animMap.
      colorForName("m1"), *m2 = _animMap.colorForName("m2"), *m3 =
      _animMap.colorForName("m3"), *lock = _animMap.
      colorForName("lock");
391     if(mr) *mr = 0;
392     if(m1) *m1 = 0;
393     if(m2) *m2 = 0;
394     if(m3) *m3 = 0;
395     if(lock) *lock = 0;
396     // Send to driver
397     cmd.write("rgb");
398     printRGB(cmd, _animMap);
399 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.6 void KbLight::close ( )

Definition at line 215 of file kblight.cpp.

References _animList, _start, activeLights, KbAnim::stop(), and stopPreview().

Referenced by base(), Kb::frameUpdate(), Kb::hwSave(), and Kb::updateLayout().

```
215                 {
216     activeLights.remove(this);
217     foreach(KbAnim* anim, _animList)
218         anim->stop();
219     stopPreview();
220     _start = false;
221 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.7 void KbLight::color (const QString & *key*, const QColor & *newColor*)

Definition at line 49 of file kblight.cpp.

References _colorMap, _needsMapRefresh, _needsSave, _qColorMap, and ColorMap::colorForName().

Referenced by KbLightWidget::changeColor(), load(), printRGB(), Kb::readNotify(), rebuildBaseMap(), and KbLightWidget::toggleSidelight().

```
49                                                          {
50     QRgb newRgb = newColor.rgb();
51     _qColorMap[key] = newRgb;
52     _needsSave = true;
53     if(!_needsMapRefresh){
54         // Update flat map if we're not scheduled to rebuild it
55         QByteArray rawName = key.toLatin1();
56         QRgb* rawRgb = _colorMap.colorForName(rawName.data());
57         if(rawRgb)
58             *rawRgb = newRgb;
59     }
60 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.8 void KbLight::color (const QColor & *newColor*)

Definition at line 62 of file kblight.cpp.

References _colorMap, _needsMapRefresh, _needsSave, _qColorMap, ColorMap::colors(), and ColorMap::count().

```
62                                          {
63     QRgb newRgb = newColor.rgb();
64     QMutableColorMapIterator i(_qColorMap);
65     while(i.hasNext()){
66         i.next();
67         i.value() = newRgb;
68     }
69     _needsSave = true;
70     // Reset flat map
71     _needsMapRefresh = false;
72     int mapCount = _colorMap.count();
73     QRgb* flat = _colorMap.colors();
74     for(int i = 0; i < mapCount; i++)
75         flat[i] = mapCount;
76 }
```

Here is the call graph for this function:

12.29.4.9 const QColorMap& KbLight::colorMap ( ) [inline]

Definition at line 31 of file kblight.h.

References _qColorMap.

Referenced by KbLightWidget::changeColor(), KbLightWidget::newSelection(), KbLightWidget::toggleSidelight(), and KbLightWidget::updateLight().

```
31 { return _qColorMap; }
```

Here is the caller graph for this function:

12.29.4.10 void KbLight::didLoad ( ) [signal]

Definition at line 162 of file moc_kblight.cpp.

Referenced by load().

```
163 {
164     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
165 }
```

Here is the caller graph for this function:

12.29.4.11 int KbLight::dimming ( ) [inline]

Definition at line 39 of file kblight.h.

References _dimming.

Referenced by KeyAction::keyEvent(), KbLightWidget::on_brightnessBox_activated(), open(), shareDimming(), and KbLightWidget::updateLight().

```
39 { return _dimming; }
```

Here is the caller graph for this function:

12.29.4.12 void KbLight::dimming (int *newDimming*)

Definition at line 92 of file kblight.cpp.

References _dimming, _needsSave, _shareDimming, shareDimming(), and updated().

```
92                                  {
93     if(_shareDimming != -1)
94         shareDimming(newDimming);
95     _needsSave = true;
96     _dimming = newDimming;
97     emit updated();
98 }
```

Here is the call graph for this function:

12.29.4.13 KbAnim * KbLight::duplicateAnim (KbAnim * *oldAnim*)

Definition at line 148 of file kblight.cpp.

References _animList, _map, _needsSave, _start, KbAnim::newId(), KbAnim::stop(), and KbAnim::trigger().

Referenced by KbAnimWidget::duplicateAnim().

```
148                                                 {
149     // Stop and restart all existing animations
150     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
151     foreach(KbAnim* anim, _animList){
152         anim->stop();
153         anim->trigger(timestamp);
154     }
155     // Same as addAnim, just duplicate the existing one
156     KbAnim* anim = new KbAnim(this, _map, *oldAnim);
157     anim->newId();
158     int index = _animList.indexOf(oldAnim);
159     if(index < 0)
160         _animList.append(anim);
161     else
162         _animList.insert(index + 1, anim);
163     anim->trigger(timestamp);
164     _start = true;
165     _needsSave = true;
166     return anim;
167 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.14 KbAnim* KbLight::findAnim (const QUuid & *guid*) const [inline]

Definition at line 51 of file kblight.h.

References _animList, and KbAnim::guid().

Referenced by findAnimIdx(), and KeyAction::keyEvent().

```
51 { foreach(KbAnim* anim, _animList) { if(anim->guid() == guid) return anim; } return 0; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.15 int KbLight::findAnimIdx (const QUuid & *guid*) const [inline]

Definition at line 52 of file kblight.h.

References _animList, and findAnim().

Referenced by RebindWidget::setSelection().

```
52 { return _animList.indexOf(findAnim(guid)); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.16 void KbLight::frameDisplayed (const ColorMap & *animatedColors*, const QSet< QString > & *indicatorList*) [signal]

Definition at line 174 of file moc_kblight.cpp.

Referenced by frameUpdate().

```
175 {
176     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)), const_cast<void*>(
    reinterpret_cast<const void*>(&_t2)) };
177     QMetaObject::activate(this, &staticMetaObject, 2, _a);
178 }
```

Here is the caller graph for this function:

12.29.4.17 void KbLight::frameUpdate (QFile & *cmd*, bool *monochrome* = false)

Definition at line 296 of file kblight.cpp.

References _animList, _animMap, _colorMap, _dimming, _indicatorList, _indicatorMap, _previewAnim, KbAnim::blend(), ColorMap::colors(), ColorMap::count(), frameDisplayed(), lastFrameSignal, IToS(), monoRgb(), printRGB(), rebuildBaseMap(), and sToL().

Referenced by Kb::frameUpdate().

```
296                                                 {
297     rebuildBaseMap();
298     _animMap = _colorMap;
299     // Advance animations
300     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
301     foreach(KbAnim* anim, _animList)
302         anim->blend(_animMap, timestamp);
303     if(_previewAnim)
304         _previewAnim->blend(_animMap, timestamp);
305
306     int count = _animMap.count();
307     QRgb* colors = _animMap.colors();
308     // Apply active indicators and/or perform monochrome conversion
309     if(monochrome || !_indicatorList.isEmpty()){
310         QRgb* indicators = _indicatorMap.colors();
311         for(int i = 0; i < count; i++){
312             QRgb& rgb = colors[i];
313             float r = qRed(rgb);
314             float g = qGreen(rgb);
```

```
            float b = qBlue(rgb);
            // Apply indicators
            QRgb rgb2 = indicators[i];
            if(qAlpha(rgb2) != 0){
                float r2 = qRed(rgb2);
                float g2 = qGreen(rgb2);
                float b2 = qBlue(rgb2);
                float a2 = qAlpha(rgb2) / 255.f;
                r = round(r2 * a2 + r * (1.f - a2));
                g = round(g2 * a2 + g * (1.f - a2));
                b = round(b2 * a2 + b * (1.f - a2));
            }
            // If monochrome mode is active, average the channels to get a grayscale image
            if(monochrome)
                rgb = monoRgb(r, g, b);
            else
                rgb = qRgb(r, g, b);
        }
    }

    // Emit signals for the animation (only do this every 50ms - it can cause a lot of CPU usage)
    if(timestamp >= lastFrameSignal + 50){
        emit frameDisplayed(_animMap, _indicatorList);
        lastFrameSignal = timestamp;
    }

    // If brightness is at 0%, turn off lighting entirely
    if(_dimming == 3){
        cmd.write("rgb 000000");
        return;
    }

    float light = (3 - _dimming) / 3.f;
    // Apply global dimming
    if(light != 1.f || monochrome){
        for(int i = 0; i < count; i++){
            QRgb& rgb = colors[i];
            // Like the monochrome conversion, this should be done in a linear colorspace
            float r = sToL(qRed(rgb));
            float g = sToL(qGreen(rgb));
            float b = sToL(qBlue(rgb));
            r *= light;
            g *= light;
            b *= light;
            r = round(lToS(r));
            g = round(lToS(g));
            b = round(lToS(b));
            rgb = qRgb(r, g, b);
        }
    }

    // Apply light
    cmd.write("rgb");
    printRGB(cmd, _animMap);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.18 bool KbLight::isStarted ( )

Definition at line 169 of file kblight.cpp.

References _animList, _start, and KbAnim::isRunning().

Referenced by Kb::frameUpdate().

```
169                         {
170     if(!_start)
171         return false;
172     foreach(KbAnim* animation, _animList){
173         if(!animation->isRunning())
174             return false;
175     }
176     return true;
177 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.19 void KbLight::load (CkbSettings & *settings*)

Definition at line 401 of file kblight.cpp.

References _animList, _dimming, _map, _needsMapRefresh, _needsSave, _qColorMap, CkbSettings::childKeys(), color(), didLoad(), KeyMap::fromName(), KeyMap::fromStorage(), map(), MAX_DIM, and CkbSettings::value().

Referenced by KbMode::KbMode().

```
                                        {
    // Load light settings
    _needsSave = false;
    SGroup group(settings, "Lighting");
    KeyMap currentMap = _map;
    _map = KeyMap::fromName(settings.value("KeyMap").toString());
    _dimming = settings.value("Brightness").toUInt();
    if(_dimming > MAX_DIM)
        _dimming = MAX_DIM;
    // Load RGB settings
    bool useReal = settings.value("UseRealNames").toBool();
    {
        SGroup group(settings, "Keys");
        foreach(QString key, settings.childKeys()){
            QString name = key.toLower();
            if(!useReal)
                name = _map.fromStorage(name);
            QColor color = settings.value(key).toString();
            if(!color.isValid())
                color = QColor(255, 255, 255);
            _qColorMap[name] = color.rgb();
        }
        _needsMapRefresh = true;
    }
    // Load animations
    foreach(KbAnim* anim, _animList)
        anim->deleteLater();
    _animList.clear();
    {
        SGroup group(settings, "Animations");
        foreach(QString anim, settings.value("List").toStringList()){
            QUuid id = anim;
            _animList.append(new KbAnim(this, _map, id, settings));
        }
    }
    emit didLoad();
    map(currentMap);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.20 const KeyMap& KbLight::map ( ) [inline]

Definition at line 28 of file kblight.h.

References _map.

Referenced by KbLight(), KbMode::keyMap(), load(), map(), KbLightWidget::newSelection(), KbAnimWidget::on_keyButton_clicked(), and KbLightWidget::updateLight().

```
28 { return _map; }
```

Here is the caller graph for this function:

12.29.4.21 void KbLight::map (const KeyMap & *map*)

Definition at line 25 of file kblight.cpp.

References _animList, _animMap, _colorMap, _indicatorMap, _map, _needsMapRefresh, _needsSave, _qColorMap, ColorMap::init(), map(), KbAnim::map(), and updated().

```
25                                  {
26     // If any of the keys are missing from the color map, set them to white
27     QHashIterator<QString, Key> i(map);
28     while(i.hasNext()){
29         i.next();
30         const QString& key = i.key();
31         if(!_qColorMap.contains(key))
32             _qColorMap[key] = 0xFFFFFFFF;
33     }
34     // Set the new map
35     _map = map;
36     foreach(KbAnim* anim, _animList)
37         anim->map(map);
38     _colorMap.init(_map);
```

```
    _animMap.init(_map);
    _indicatorMap.init(_map);
    _needsSave = _needsMapRefresh = true;
    emit updated();
}
```

Here is the call graph for this function:

12.29.4.22 bool KbLight::needsSave ( ) const

Definition at line 467 of file kblight.cpp.

References _animList, _needsSave, and KbAnim::needsSave().

Referenced by KbMode::needsSave().

```
467                                 {
468     if(_needsSave)
469         return true;
470     foreach(KbAnim* anim, _animList){
471         if(anim->needsSave())
472             return true;
473     }
474     return false;
475 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.23 void KbLight::open ( )

Definition at line 200 of file kblight.cpp.

References _animList, _dimming, _previewAnim, _shareDimming, _start, activeLights, dimming(), and KbAnim::trigger().

Referenced by Kb::frameUpdate().

```
200                 {
201     // Apply shared dimming if needed
202     if(_shareDimming != -1 && _shareDimming !=
    _dimming)
203         dimming(_shareDimming);
204     activeLights.insert(this);
205     if(_start)
206         return;
207     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
208     foreach(KbAnim* anim, _animList)
209         anim->trigger(timestamp);
210     if(_previewAnim)
211         _previewAnim->trigger(timestamp);
212     _start = true;
213 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.24 void KbLight::previewAnim (const AnimScript * *base*, const QStringList & *keys*, const QMap< QString, QVariant > & *preset*)

Definition at line 124 of file kblight.cpp.

References _map, _previewAnim, _start, KbAnim::commitParams(), KbAnim::parameter(), KbAnim::reInit(), stopPreview(), and KbAnim::trigger().

Referenced by AnimAddDialog::on_presetBox_activated().

```
124
            {
125     if(_previewAnim)
126         stopPreview();
127     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
128     // Load the new animation and set preset parameters
```

```
    KbAnim* anim = new KbAnim(this, _map, "", keys, base);
    QMapIterator<QString, QVariant> i(preset);
    while(i.hasNext()){
        i.next();
        anim->parameter(i.key(), i.value());
    }
    anim->commitParams();
    anim->reInit();
    // Add the animation and start it
    _previewAnim = anim;
    anim->trigger(timestamp);
    _start = true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.25 void KbLight::printRGB (QFile & *cmd*, const ColorMap & *animMap*) [private]

Definition at line 223 of file kblight.cpp.

References color(), ColorMap::colors(), ColorMap::count(), and ColorMap::keyNames().

Referenced by base(), and frameUpdate().

```
223                                                     {
224     int count = animMap.count();
225     const char* const* names = animMap.keyNames();
226     const QRgb* colors = animMap.colors();
227     // Print each color and the corresponding RGB value
228     for(int i = 0; i < count; i++){
229         cmd.write(" ");
230         cmd.write(names[i]);
231         char output[8];
232         QRgb color = colors[i];
233         snprintf(output, sizeof(output), ":%02x%02x%02x", qRed(color), qGreen(color), qBlue(color));
234         cmd.write(output);
235     }
236 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.26 void KbLight::rebuildBaseMap ( ) [private]

Definition at line 238 of file kblight.cpp.

References _colorMap, _needsMapRefresh, _qColorMap, color(), and ColorMap::colorForName().

Referenced by base(), and frameUpdate().

```
238                                 {
239     if(!_needsMapRefresh)
240         return;
241     _needsMapRefresh = false;
242     // Copy RGB values from QColorMap to ColorMap
243     QColorMapIterator i(_qColorMap);
244     while(i.hasNext()){
245         i.next();
246         QByteArray rawName = i.key().toLatin1();
247         QRgb color = i.value();
248         QRgb* rawColor = _colorMap.colorForName(rawName.data());
249         if(rawColor)
250             *rawColor = color;
251     }
252 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.27 void KbLight::resetIndicators ( )

Definition at line 254 of file kblight.cpp.

References _indicatorList, _indicatorMap, and ColorMap::clear().

Referenced by KbPerf::applyIndicators().

```
254                                 {
255     _indicatorMap.clear();
256     _indicatorList.clear();
257 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.28 void KbLight::restartAnimation ( )

Definition at line 179 of file kblight.cpp.

References _animList, _start, KbAnim::stop(), stopPreview(), and KbAnim::trigger().

Referenced by KbLightWidget::on_animButton_clicked(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::on_keyButton_clicked(), and KbAnimWidget::on_propertyButton_clicked().

```
179                                 {
180     quint64 timestamp = QDateTime::currentMSecsSinceEpoch();
```

```
    foreach(KbAnim* anim, _animList){
        anim->stop();
        anim->trigger(timestamp);
    }
    stopPreview();
    _start = true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.29 void KbLight::save (CkbSettings & *settings*)

Definition at line 440 of file kblight.cpp.

References _animList, _dimming, _map, _needsSave, _qColorMap, KbAnim::guid(), KeyMap::name(), KbAnim::save(), and CkbSettings::setValue().

Referenced by KbMode::save().

```
440                                         {
441     _needsSave = false;
442     SGroup group(settings, "Lighting");
443     settings.setValue("KeyMap", _map.name());
444     settings.setValue("Brightness", _dimming);
445     settings.setValue("UseRealNames", true);
446     {
447         // Save RGB settings
448         SGroup group(settings, "Keys");
449         QMutableColorMapIterator i(_qColorMap);
450         while(i.hasNext()){
451             i.next();
452             settings.setValue(i.key(), QColor(i.value()).name());
453         }
454     }
455     {
456         // Save animations
457         SGroup group(settings, "Animations");
458         QStringList aList;
459         foreach(KbAnim* anim, _animList){
460             aList << anim->guid().toString().toUpper();
461             anim->save(settings);
462         }
463         settings.setValue("List", aList);
464     }
465 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.30 void KbLight::setIndicator (const char * *name*, QRgb *argb*)

Definition at line 259 of file kblight.cpp.

References _indicatorList, _indicatorMap, and ColorMap::colorForName().

Referenced by KbPerf::lightIndicator().

```
259                                                 {
260     QRgb* dest = _indicatorMap.colorForName(name);
261     if(dest){
262         *dest = argb;
263         _indicatorList.insert(name);
264     }
265 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.29.4.31 int KbLight::shareDimming ( ) [static]

Definition at line 78 of file kblight.cpp.

References _shareDimming.

Referenced by dimming(), ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_brightnessBox_clicked(), and ExtraSettingsWidget::pollUpdates().

```
78                                  {
79     return _shareDimming;
80 }
```

Here is the caller graph for this function:

12.29.4.32 void KbLight::shareDimming (int *newShareDimming*) [static]

Definition at line 82 of file kblight.cpp.

References _shareDimming, activeLights, and dimming().

```
82                                                  {
83     if(_shareDimming == newShareDimming)
84         return;
85     _shareDimming = newShareDimming;
86     if(newShareDimming != -1){
87         foreach(KbLight* light, activeLights)
88             light->dimming(newShareDimming);
89     }
90 }
```

Here is the call graph for this function:

12.29.4.33 void KbLight::stopPreview ( )

Definition at line 143 of file kblight.cpp.

References _previewAnim.

Referenced by addAnim(), close(), AnimAddDialog::on_previewBox_clicked(), previewAnim(), restartAnimation(), and AnimAddDialog::~AnimAddDialog().

```
                        {
    delete _previewAnim;
    _previewAnim = 0;
}
```

Here is the caller graph for this function:

12.29.4.34 void KbLight::updated ( ) [signal]

Definition at line 168 of file moc_kblight.cpp.

Referenced by dimming(), and map().

```
{
    QMetaObject::activate(this, &staticMetaObject, 1, Q_NULLPTR);
}
```

Here is the caller graph for this function:

12.29.5 Field Documentation

12.29.5.1 AnimList KbLight::_animList [private]

Definition at line 89 of file kblight.h.

Referenced by addAnim(), animKeypress(), animList(), close(), duplicateAnim(), findAnim(), findAnimIdx(), frameUpdate(), isStarted(), KbLight(), load(), map(), needsSave(), open(), restartAnimation(), and save().

12.29.5.2 ColorMap KbLight::_animMap [private]

Definition at line 93 of file kblight.h.

Referenced by base(), frameUpdate(), and map().

12.29.5.3 ColorMap KbLight::_colorMap [private]

Definition at line 93 of file kblight.h.

Referenced by base(), color(), frameUpdate(), map(), and rebuildBaseMap().

12.29.5.4 int KbLight::_dimming [private]

Definition at line 96 of file kblight.h.

Referenced by base(), dimming(), frameUpdate(), load(), open(), and save().

12.29.5.5 QSet<QString> KbLight::_indicatorList [private]

Definition at line 94 of file kblight.h.

Referenced by frameUpdate(), resetIndicators(), and setIndicator().

12.29.5.6 ColorMap KbLight::_indicatorMap [private]

Definition at line 93 of file kblight.h.

Referenced by frameUpdate(), map(), resetIndicators(), and setIndicator().

12.29.5.7 KeyMap KbLight::_map [private]

Definition at line 91 of file kblight.h.

Referenced by addAnim(), duplicateAnim(), load(), map(), previewAnim(), and save().

12.29.5.8 bool KbLight::_needsMapRefresh [private]

Definition at line 98 of file kblight.h.

Referenced by color(), load(), map(), and rebuildBaseMap().

12.29.5.9 bool KbLight::_needsSave [private]

Definition at line 98 of file kblight.h.

Referenced by addAnim(), animList(), color(), dimming(), duplicateAnim(), load(), map(), needsSave(), and save().

12.29.5.10 KbAnim* KbLight::_previewAnim [private]

Definition at line 90 of file kblight.h.

Referenced by animKeypress(), frameUpdate(), open(), previewAnim(), and stopPreview().

12.29.5.11 QColorMap KbLight::_qColorMap [private]

Definition at line 92 of file kblight.h.

Referenced by color(), colorMap(), load(), map(), rebuildBaseMap(), and save().

12.29.5.12 bool KbLight::_start [private]

Definition at line 97 of file kblight.h.

Referenced by addAnim(), close(), duplicateAnim(), isStarted(), open(), previewAnim(), and restartAnimation().

12.29.5.13 quint64 KbLight::lastFrameSignal [private]

Definition at line 95 of file kblight.h.

Referenced by frameUpdate().

12.29.5.14 const int KbLight::MAX_DIM = 3 [static]

Definition at line 38 of file kblight.h.

Referenced by base(), ExtraSettingsWidget::ExtraSettingsWidget(), KeyAction::keyEvent(), and load().

The documentation for this class was generated from the following files:

- src/ckb/kblight.h
- src/ckb/kblight.cpp
- src/ckb/release/moc_kblight.cpp

12.30 Ui::KbLightWidget Class Reference

```
#include <src/ckb/ui_kblightwidget.h>
```

Inheritance diagram for Ui::KbLightWidget:

Collaboration diagram for Ui::KbLightWidget:

Public Member Functions

- void setupUi (QWidget *KbLightWidget)

- void retranslateUi (QWidget *KbLightWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QHBoxLayout * horizontalLayout_3
- QLabel * label_3
- QCheckBox * showAnimBox
- QFrame * line_2
- QHBoxLayout * horizontalLayout_2
- QSpacerItem * horizontalSpacer_5
- QGridLayout * gridLayout
- KeyWidget * keyWidget
- QHBoxLayout * horizontalLayout
- ColorButton * bgButton
- QLabel * selLabel
- QPushButton * animButton
- QSpacerItem * horizontalSpacer_6
- QSpacerItem * verticalSpacer_2
- QGridLayout * gridLayout_2
- QComboBox * brightnessBox
- QLabel * label
- QSpacerItem * horizontalSpacer_3
- QSpacerItem * horizontalSpacer_4
- QSpacerItem * verticalSpacer_3
- QLabel * label_2
- QFrame * line
- QWidget * widget
- QGridLayout * gridLayout_4
- KbAnimWidget * animWidget

12.30.1 Detailed Description

Definition at line 263 of file ui_kblightwidget.h.

12.30.2 Member Function Documentation

12.30.2.1 void Ui_KbLightWidget::retranslateUi (QWidget * *KbLightWidget*) [inline],[inherited]

Definition at line 238 of file ui_kblightwidget.h.

References Ui_KbLightWidget::animButton, Ui_KbLightWidget::bgButton, Ui_KbLightWidget::brightnessBox, Ui_KbLightWidget::label, Ui_KbLightWidget::label_2, Ui_KbLightWidget::label_3, Ui_KbLightWidget::selLabel, and Ui_KbLightWidget::showAnimBox.

Referenced by Ui_KbLightWidget::setupUi().

```
    {
        KbLightWidget->setWindowTitle(QApplication::translate("KbLightWidget", "Form", Q_NULLPTR));
        label_3->setText(QApplication::translate("KbLightWidget", "Colors", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        showAnimBox->setToolTip(QApplication::translate("KbLightWidget", "If enabled, the same colors will be displayed here as on the keyboard. If disabled, the base colors will be shown.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        showAnimBox->setText(QApplication::translate("KbLightWidget", "Show animated", Q_NULLPTR));
        bgButton->setText(QApplication::translate("KbLightWidget", "Change color...", Q_NULLPTR));
        selLabel->setText(QApplication::translate("KbLightWidget", "Click to select", Q_NULLPTR));
        animButton->setText(QApplication::translate("KbLightWidget", "New animation...",
```

```
    Q_NULLPTR));
        brightnessBox->clear();
        brightnessBox->insertItems(0, QStringList()
         << QApplication::translate("KbLightWidget", "100%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "67%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "33%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "Off", Q_NULLPTR)
        );
        label->setText(QApplication::translate("KbLightWidget", "\342\230\274", Q_NULLPTR));
        label_2->setText(QApplication::translate("KbLightWidget", "Animations", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.30.2.2 void Ui_KbLightWidget::setupUi (QWidget * *KbLightWidget*) [inline],[inherited]

Definition at line 63 of file ui_kblightwidget.h.

References Ui_KbLightWidget::animButton, Ui_KbLightWidget::animWidget, Ui_KbLightWidget::bgButton, Ui_KbLightWidget::brightnessBox, Ui_KbLightWidget::gridLayout, Ui_KbLightWidget::gridLayout_2, Ui_KbLightWidget::gridLayout_4, Ui_KbLightWidget::horizontalLayout, Ui_KbLightWidget::horizontalLayout_2, Ui_KbLightWidget::horizontalLayout_3, Ui_KbLightWidget::horizontalSpacer_3, Ui_KbLightWidget::horizontalSpacer_4, Ui_KbLightWidget::horizontalSpacer_5, Ui_KbLightWidget::horizontalSpacer_6, Ui_KbLightWidget::keyWidget, Ui_KbLightWidget::label, Ui_KbLightWidget::label_2, Ui_KbLightWidget::label_3, Ui_KbLightWidget::line, Ui_KbLightWidget::line_2, Ui_KbLightWidget::retranslateUi(), Ui_KbLightWidget::selLabel, Ui_KbLightWidget::showAnimBox, Ui_KbLightWidget::verticalLayout, Ui_KbLightWidget::verticalSpacer_2, Ui_KbLightWidget::verticalSpacer_3, and Ui_KbLightWidget::widget.

Referenced by KbLightWidget::KbLightWidget().

```
    {
        if (KbLightWidget->objectName().isEmpty())
            KbLightWidget->setObjectName(QStringLiteral("KbLightWidget"));
        KbLightWidget->resize(632, 540);
        KbLightWidget->setFocusPolicy(Qt::ClickFocus);
        verticalLayout = new QVBoxLayout(KbLightWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        verticalLayout->setContentsMargins(0, 0, 0, -1);
        horizontalLayout_3 = new QHBoxLayout();
        horizontalLayout_3->setObjectName(QStringLiteral("horizontalLayout_3"));
        label_3 = new QLabel(KbLightWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(label_3->sizePolicy().hasHeightForWidth());
        label_3->setSizePolicy(sizePolicy);
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label_3->setFont(font);

        horizontalLayout_3->addWidget(label_3);

        showAnimBox = new QCheckBox(KbLightWidget);
        showAnimBox->setObjectName(QStringLiteral("showAnimBox"));
        showAnimBox->setChecked(true);

        horizontalLayout_3->addWidget(showAnimBox);


        verticalLayout->addLayout(horizontalLayout_3);

        line_2 = new QFrame(KbLightWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
```

```
        line_2->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line_2);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        horizontalSpacer_5 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_5);

        gridLayout = new QGridLayout();
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        keyWidget = new KeyWidget(KbLightWidget);
        keyWidget->setObjectName(QStringLiteral("keyWidget"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(keyWidget->sizePolicy().hasHeightForWidth());
        keyWidget->setSizePolicy(sizePolicy1);
        keyWidget->setMinimumSize(QSize(100, 100));
        keyWidget->setFocusPolicy(Qt::ClickFocus);

        gridLayout->addWidget(keyWidget, 0, 0, 1, 3);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        bgButton = new ColorButton(KbLightWidget);
        bgButton->setObjectName(QStringLiteral("bgButton"));
        QSizePolicy sizePolicy2(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(bgButton->sizePolicy().hasHeightForWidth());
        bgButton->setSizePolicy(sizePolicy2);
        bgButton->setMinimumSize(QSize(140, 0));
        bgButton->setMaximumSize(QSize(140, 16777215));

        horizontalLayout->addWidget(bgButton);

        selLabel = new QLabel(KbLightWidget);
        selLabel->setObjectName(QStringLiteral("selLabel"));
        sizePolicy.setHeightForWidth(selLabel->sizePolicy().hasHeightForWidth());
        selLabel->setSizePolicy(sizePolicy);
        selLabel->setAlignment(Qt::AlignCenter);

        horizontalLayout->addWidget(selLabel);

        animButton = new QPushButton(KbLightWidget);
        animButton->setObjectName(QStringLiteral("animButton"));
        sizePolicy2.setHeightForWidth(animButton->sizePolicy().hasHeightForWidth());
        animButton->setSizePolicy(sizePolicy2);
        animButton->setMinimumSize(QSize(140, 0));
        animButton->setMaximumSize(QSize(140, 16777215));

        horizontalLayout->addWidget(animButton);


        gridLayout->addLayout(horizontalLayout, 1, 0, 1, 3);


        horizontalLayout_2->addLayout(gridLayout);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_6);


        verticalLayout->addLayout(horizontalLayout_2);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        gridLayout_2 = new QGridLayout();
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        brightnessBox = new QComboBox(KbLightWidget);
        brightnessBox->setObjectName(QStringLiteral("brightnessBox"));
        sizePolicy2.setHeightForWidth(brightnessBox->sizePolicy().hasHeightForWidth());
        brightnessBox->setSizePolicy(sizePolicy2);

        gridLayout_2->addWidget(brightnessBox, 1, 3, 1, 1);

        label = new QLabel(KbLightWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font1;
```

```
        font1.setPointSize(20);
        label->setFont(font1);
        label->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_2->addWidget(label, 1, 2, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(0, 0, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 0, 4, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(0, 0, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_4, 0, 2, 1, 1);


        verticalLayout->addLayout(gridLayout_2);

        verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_3);

        label_2 = new QLabel(KbLightWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        verticalLayout->addWidget(label_2);

        line = new QFrame(KbLightWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line);

        widget = new QWidget(KbLightWidget);
        widget->setObjectName(QStringLiteral("widget"));
        widget->setMinimumSize(QSize(0, 170));
        gridLayout_4 = new QGridLayout(widget);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        gridLayout_4->setContentsMargins(-1, 0, -1, 0);
        animWidget = new KbAnimWidget(widget);
        animWidget->setObjectName(QStringLiteral("animWidget"));

        gridLayout_4->addWidget(animWidget, 0, 0, 1, 1);


        verticalLayout->addWidget(widget);


        retranslateUi(KbLightWidget);

        QMetaObject::connectSlotsByName(KbLightWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.30.3 Field Documentation

12.30.3.1 QPushButton* Ui_KbLightWidget::animButton [inherited]

Definition at line 48 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.2 KbAnimWidget* Ui_KbLightWidget::animWidget [inherited]

Definition at line 61 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), KbLightWidget::newSelection(), KbLightWidget::on_animButton_clicked(), KbLightWidget::setLight(), and Ui_KbLightWidget::setupUi().

12.30.3.3 ColorButton* Ui_KbLightWidget::bgButton [inherited]

Definition at line 46 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), KbLightWidget::newSelection(), Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.4 QComboBox* Ui_KbLightWidget::brightnessBox [inherited]

Definition at line 52 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::retranslateUi(), Ui_KbLightWidget::setupUi(), and KbLightWidget::updateLight().

12.30.3.5 QGridLayout* Ui_KbLightWidget::gridLayout [inherited]

Definition at line 43 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.6 QGridLayout* Ui_KbLightWidget::gridLayout_2 [inherited]

Definition at line 51 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.7 QGridLayout* Ui_KbLightWidget::gridLayout_4 [inherited]

Definition at line 60 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.8 QHBoxLayout* Ui_KbLightWidget::horizontalLayout [inherited]

Definition at line 45 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.9 QHBoxLayout* Ui_KbLightWidget::horizontalLayout_2 [inherited]

Definition at line 41 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.10 QHBoxLayout* Ui_KbLightWidget::horizontalLayout_3 [inherited]

Definition at line 37 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.11 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_3 [inherited]

Definition at line 54 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.12 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_4 [inherited]

Definition at line 55 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.13 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_5 [inherited]

Definition at line 42 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.14 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_6 [inherited]

Definition at line 49 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.15 KeyWidget* Ui_KbLightWidget::keyWidget [inherited]

Definition at line 44 of file ui_kblightwidget.h.

Referenced by KbLightWidget::changeAnim(), KbLightWidget::changeAnimKeys(), KbLightWidget::changeColor(), KbLightWidget::KbLightWidget(), KbLightWidget::on_animButton_clicked(), KbLightWidget::on_bgButton_clicked(), KbLightWidget::on_showAnimBox_clicked(), KbLightWidget::setLight(), KbLightWidget::setMonochrome(), Ui_KbLightWidget::setupUi(), KbLightWidget::toggleSidelight(), and KbLightWidget::updateLight().

12.30.3.16 QLabel* Ui_KbLightWidget::label [inherited]

Definition at line 53 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.17 QLabel* Ui_KbLightWidget::label_2 [inherited]

Definition at line 57 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.18 QLabel* Ui_KbLightWidget::label_3 [inherited]

Definition at line 38 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.19 QFrame* Ui_KbLightWidget::line [inherited]

Definition at line 58 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.20 QFrame* Ui_KbLightWidget::line_2 [inherited]

Definition at line 40 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.21 QLabel* Ui_KbLightWidget::selLabel [inherited]

Definition at line 47 of file ui_kblightwidget.h.

Referenced by KbLightWidget::newSelection(), Ui_KbLightWidget::retranslateUi(), and Ui_KbLightWidget::setupUi().

12.30.3.22 QCheckBox* Ui_KbLightWidget::showAnimBox [inherited]

Definition at line 39 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), Ui_KbLightWidget::retranslateUi(), KbLightWidget::setLight(), and Ui_KbLightWidget::setupUi().

12.30.3.23 QVBoxLayout* Ui_KbLightWidget::verticalLayout [inherited]

Definition at line 36 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.24 QSpacerItem* Ui_KbLightWidget::verticalSpacer_2 [inherited]

Definition at line 50 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.25 QSpacerItem* Ui_KbLightWidget::verticalSpacer_3 [inherited]

Definition at line 56 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

12.30.3.26 QWidget* Ui_KbLightWidget::widget [inherited]

Definition at line 59 of file ui_kblightwidget.h.

Referenced by Ui_KbLightWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kblightwidget.h

12.31 KbLightWidget Class Reference

```
#include <src/ckb/kblightwidget.h>
```

Inheritance diagram for KbLightWidget:

Collaboration diagram for KbLightWidget:

Public Member Functions

- KbLightWidget (QWidget *parent=0)
- ~KbLightWidget ()
- void setLight (KbLight *newLight)
- void setMonochrome ()

Private Slots

- void updateLight ()
- void newSelection (QStringList selection)
- void changeColor (QColor newColor)
- void changeAnim (KbAnim *newAnim)
- void changeAnimKeys (QStringList keys)
- void on_brightnessBox_activated (int index)
- void on_animButton_clicked ()
- void on_bgButton_clicked ()
- void on_showAnimBox_clicked (bool checked)
- void toggleSidelight ()

Private Attributes

- KbLight * light
- QStringList currentSelection
- Ui::KbLightWidget * ui

12.31.1 Detailed Description

Definition at line 15 of file kblightwidget.h.

12.31.2 Constructor & Destructor Documentation

12.31.2.1 KbLightWidget::KbLightWidget (QWidget * *parent* = 0) [explicit]

Definition at line 6 of file kblightwidget.cpp.

References Ui_KbLightWidget::animButton, Ui_KbLightWidget::animWidget, Ui_KbLightWidget::bgButton, changeAnim(), changeAnimKeys(), changeColor(), AnimScript::count(), CkbSettings::get(), Ui_KbLightWidget::keyWidget, newSelection(), Ui_KbLightWidget::setupUi(), Ui_KbLightWidget::showAnimBox, toggleSidelight(), and ui.

```
6                                                   :
7     QWidget(parent), light(0),
8     ui(new Ui::KbLightWidget)
9 {
10     ui->setupUi(this);
11     if(AnimScript::count() == 0)
12         ui->animButton->setVisible(false);
13
14     connect(ui->bgButton, SIGNAL(colorChanged(QColor)), this, SLOT(
      changeColor(QColor)));
15     connect(ui->keyWidget, SIGNAL(selectionChanged(QStringList)), this, SLOT(
      newSelection(QStringList)));
16     connect(ui->keyWidget, SIGNAL(sidelightToggled()), this, SLOT(
      toggleSidelight())); // click on a toggle button, like sidelight
17     connect(ui->animWidget, SIGNAL(animChanged(KbAnim*)), this, SLOT(
      changeAnim(KbAnim*)));
18     connect(ui->animWidget, SIGNAL(didUpdateSelection(QStringList)), this, SLOT(
      changeAnimKeys(QStringList)));
19
20     // Restore "show animated" setting
21     ui->showAnimBox->setChecked(!CkbSettings::get("UI/Light/ShowBaseOnly").
      toBool());
22 }
```

Here is the call graph for this function:

12.31.2.2 KbLightWidget::~KbLightWidget ( )

Definition at line 24 of file kblightwidget.cpp.

References ui.

```
24                                  {
25     delete ui;
26 }
```

12.31.3 Member Function Documentation

12.31.3.1 void KbLightWidget::changeAnim (KbAnim * *newAnim*) [private],[slot]

Definition at line 121 of file kblightwidget.cpp.

References KeyWidget::clearSelection(), KbAnim::keys(), Ui_KbLightWidget::keyWidget, KeyWidget::setAnimationToSelection(), KeyWidget::setSelection(), and ui.

Referenced by KbLightWidget().

```
121                                                 {
122     if(newAnim)
123         ui->keyWidget->setSelection(newAnim->keys());
124     else
125         ui->keyWidget->clearSelection();
126     ui->keyWidget->setAnimationToSelection();
127 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.2 void KbLightWidget::changeAnimKeys (QStringList *keys*) [private],[slot]

Definition at line 129 of file kblightwidget.cpp.

References Ui_KbLightWidget::keyWidget, KeyWidget::setAnimation(), and ui.

Referenced by KbLightWidget().

```
129                                                 {
130     ui->keyWidget->setAnimation(keys);
131 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.3 void KbLightWidget::changeColor (QColor *newColor*) [private],[slot]

Definition at line 99 of file kblightwidget.cpp.

References KbLight::color(), KeyWidget::colorMap(), KbLight::colorMap(), currentSelection, Ui_KbLightWidget::keyWidget, light, and ui.

Referenced by KbLightWidget().

```
99                                                  {
100     if(light){
101         foreach(QString key, currentSelection)
102             light->color(key, newColor);
103         ui->keyWidget->colorMap(light->colorMap());
104     }
105 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.4 void KbLightWidget::newSelection (QStringList *selection*) [private],[slot]

Definition at line 72 of file kblightwidget.cpp.

References Ui_KbLightWidget::animWidget, Ui_KbLightWidget::bgButton, ColorButton::color(), KbLight::colorMap(), currentSelection, KeyMap::isMouse(), light, KbLight::map(), Ui_KbLightWidget::selLabel, KbAnimWidget::setSelectedKeys(), and ui.

Referenced by KbLightWidget().

```
72                                                  {
73     // Determine selected color (invalid color if no selection or if they're not all the same)
74     QColor selectedColor;
75     const QColorMap& colorMap = light->colorMap();
76     foreach(const QString& key, selection){
77         QColor color = colorMap.value(key);
78         if(!selectedColor.isValid())
79             selectedColor = color;
80         else if(color != selectedColor){
81             selectedColor = QColor();
82             break;
83         }
84     }
85
86     currentSelection = selection;
87     ui->animWidget->setSelectedKeys(selection);
88     ui->bgButton->color(selectedColor);
89     int count = selection.count();
90     if(count == 0){
91         ui->selLabel->setText("Click to select");
92         return;
93     } else if(count == 1)
94         ui->selLabel->setText(tr("1 %1 selected").arg(light->map().
      isMouse() ? "zone" : "key"));
95     else
96         ui->selLabel->setText(tr("%1 %2 selected").arg(count).arg(
      light->map().isMouse() ? "zones" : "keys"));
97 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.5 void KbLightWidget::on_animButton_clicked ( ) [private],[slot]

Definition at line 143 of file kblightwidget.cpp.

References KbAnimWidget::addAnim(), Ui_KbLightWidget::animWidget, AnimAddDialog::chosenPreset(), AnimAddDialog::chosenScript(), AnimScript::count(), currentSelection, Ui_KbLightWidget::keyWidget, light, AnimScript::preset(), AnimScript::presets(), KbLight::restartAnimation(), KeyWidget::selectAll(), and ui.

```
143                                         {
144     if(AnimScript::count() == 0)
145         return;
146     if(currentSelection.isEmpty())
147         ui->keyWidget->selectAll();
148     AnimAddDialog dialog(this, light, currentSelection);
149     dialog.exec();
150     if(dialog.result() != QDialog::Accepted)
151         return;
152     const AnimScript* script = dialog.chosenScript();
153     int presetId = dialog.chosenPreset();
154     ui->animWidget->addAnim(script, currentSelection, script->
      presets()[presetId], script->preset(presetId));
155     light->restartAnimation();
156 }
```

Here is the call graph for this function:

12.31.3.6 void KbLightWidget::on_bgButton_clicked ( ) [private],[slot]

Definition at line 138 of file kblightwidget.cpp.

References currentSelection, Ui_KbLightWidget::keyWidget, KeyWidget::selectAll(), and ui.

```
138                                     {
139     if(currentSelection.isEmpty())
140         ui->keyWidget->selectAll();
141 }
```

Here is the call graph for this function:

12.31.3.7 void KbLightWidget::on_brightnessBox_activated (int *index*) [private],[slot]

Definition at line 133 of file kblightwidget.cpp.

References KbLight::dimming(), and light.

```
133                                                     {
134     if(light)
135         light->dimming(index);
136 }
```

Here is the call graph for this function:

12.31.3.8 void KbLightWidget::on_showAnimBox_clicked (bool *checked*) [private],[slot]

Definition at line 52 of file kblightwidget.cpp.

References KeyWidget::displayColorMap(), Ui_KbLightWidget::keyWidget, light, CkbSettings::set(), and ui.

Referenced by setLight().

```
52                                                  {
53     // FIXME: set globally if there's more than one KbLightWidget active
54     // Connect/disconnect animation slot
55     if(checked){
56         if(light)
57             connect(light, SIGNAL(frameDisplayed(const ColorMap&,const QSet<QString>&)),
       ui->keyWidget, SLOT(displayColorMap(const ColorMap&,const QSet<QString>&)));
58     } else {
59         if(light)
60             disconnect(light, SIGNAL(frameDisplayed(const ColorMap&,const QSet<QString>&)),
       ui->keyWidget, SLOT(displayColorMap(const ColorMap&,const QSet<QString>&)));
61         ui->keyWidget->displayColorMap(ColorMap());
62     }
63     CkbSettings::set("UI/Light/ShowBaseOnly", !checked);
64 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.9 void KbLightWidget::setLight (KbLight * *newLight*)

Definition at line 28 of file kblightwidget.cpp.

References Ui_KbLightWidget::animWidget, KeyWidget::clearAnimation(), KbAnimWidget::clearSelection(), KeyWidget::clearSelection(), Ui_KbLightWidget::keyWidget, light, on_showAnimBox_clicked(), KeyWidget::setAnimation(), KbAnimWidget::setLight(), Ui_KbLightWidget::showAnimBox, ui, and updateLight().

Referenced by KbWidget::modeChanged().

```
{
    ui->keyWidget->clearSelection();
    ui->keyWidget->clearAnimation();
    ui->animWidget->clearSelection();
    if(light == newLight)
        return;
    if(light){
        disconnect(light, SIGNAL(updated()), this, SLOT(updateLight()));
        // Disabled animated colors for previous light
        on_showAnimBox_clicked(false);
    }
    connect(newLight, SIGNAL(updated()), this, SLOT(updateLight()));
    light = newLight;
    updateLight();
    ui->keyWidget->setAnimation(QStringList());
    ui->animWidget->setLight(newLight);
    if(ui->showAnimBox->isChecked())
        on_showAnimBox_clicked(true);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.10 void KbLightWidget::setMonochrome ( )

Definition at line 48 of file kblightwidget.cpp.

References Ui_KbLightWidget::keyWidget, KeyWidget::monochrome(), and ui.

Referenced by KbWidget::KbWidget().

```
48                                  {
49      ui->keyWidget->monochrome(true);
50  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.11 void KbLightWidget::toggleSidelight ( ) [private],[slot]

Definition at line 107 of file kblightwidget.cpp.

References KbLight::color(), KeyWidget::colorMap(), KbLight::colorMap(), Ui_KbLightWidget::keyWidget, light, and ui.

Referenced by KbLightWidget().

```
107                                     {
108     if(light){
109         if (light->colorMap()["lsidel"] == 0xFF000000){
110                 light->color("lsidel",QRgb(0xFFFFFFFF));
111                 light->color("rsidel",QRgb(0xFFFFFFFF));
112         } else {
113                 light->color("lsidel", QRgb(0xFF000000));
114                 light->color("rsidel", QRgb(0xFF000000));
115         }
116         ui->keyWidget->colorMap(light->colorMap());
117     }
118 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.3.12 void KbLightWidget::updateLight ( ) [private],[slot]

Definition at line 66 of file kblightwidget.cpp.

References Ui_KbLightWidget::brightnessBox, KeyWidget::colorMap(), KbLight::colorMap(), KbLight::dimming(), Ui_KbLightWidget::keyWidget, light, KeyWidget::map(), KbLight::map(), and ui.

Referenced by setLight().

```
66                                {
67     ui->keyWidget->map(light->map());
68     ui->keyWidget->colorMap(light->colorMap());
69     ui->brightnessBox->setCurrentIndex(light->dimming());
70 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.31.4 Field Documentation

12.31.4.1 QStringList KbLightWidget::currentSelection [private]

Definition at line 44 of file kblightwidget.h.

Referenced by changeColor(), newSelection(), on_animButton_clicked(), and on_bgButton_clicked().

12.31.4.2 KbLight* KbLightWidget::light [private]

Definition at line 43 of file kblightwidget.h.

Referenced by changeColor(), newSelection(), on_animButton_clicked(), on_brightnessBox_activated(), on_showAnimBox_clicked(), setLight(), toggleSidelight(), and updateLight().

12.31.4.3 Ui::KbLightWidget* KbLightWidget::ui [private]

Definition at line 46 of file kblightwidget.h.

Referenced by changeAnim(), changeAnimKeys(), changeColor(), KbLightWidget(), newSelection(), on_animButton_clicked(), on_bgButton_clicked(), on_showAnimBox_clicked(), setLight(), setMonochrome(), toggleSidelight(), updateLight(), and ~KbLightWidget().

The documentation for this class was generated from the following files:

- src/ckb/kblightwidget.h

- src/ckb/kblightwidget.cpp

12.32 KbManager Class Reference

```
#include <src/ckb/kbmanager.h>
```

Inheritance diagram for KbManager:

Collaboration diagram for KbManager:

Signals

- void kbConnected (Kb ∗device)
- void kbDisconnected (Kb ∗device)
- void versionUpdated ()

Static Public Member Functions

- static void init (QString guiVersion)
- static void stop ()
- static KbManager ∗ kbManager ()
- static QString ckbGuiVersion ()
- static QString ckbDaemonVersion ()
- static float parseVersionString (QString version)
- static float ckbGuiVersionF ()
- static float ckbDaemonVersionF ()
- static const QSet< Kb ∗ > devices ()
- static QTimer ∗ eventTimer ()
- static void fps (int framerate)
- static QTimer ∗ scanTimer ()

Private Slots

- void scanKeyboards ()

Private Member Functions

- KbManager (QObject *parent=0)

Private Attributes

- QSet< Kb * > _devices
- QTimer * _eventTimer
- QTimer * _scanTimer

Static Private Attributes

- static KbManager * _kbManager = 0
- static QString _guiVersion
- static QString _daemonVersion = "<unavailable>"

12.32.1 Detailed Description

Definition at line 14 of file kbmanager.h.

12.32.2 Constructor & Destructor Documentation

12.32.2.1 KbManager::KbManager (QObject * *parent* = 0) [explicit],[private]

Definition at line 26 of file kbmanager.cpp.

References _eventTimer, _scanTimer, and scanKeyboards().

Referenced by init().

```
26                                  : QObject(parent){
27     // Set up the timers
28     _eventTimer = new QTimer(this);
29     _eventTimer->setTimerType(Qt::PreciseTimer);
30     _scanTimer = new QTimer(this);
31     _scanTimer->start(100);
32     connect(_scanTimer, SIGNAL(timeout()), this, SLOT(scanKeyboards()));
33 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3 Member Function Documentation

12.32.3.1 static QString KbManager::ckbDaemonVersion ( ) [inline], [static]

Definition at line 27 of file kbmanager.h.

References _daemonVersion.

Referenced by MainWindow::updateVersion().

```
27 { return _daemonVersion; }
```

Here is the caller graph for this function:

12.32.3.2 static float KbManager::ckbDaemonVersionF ( ) [inline], [static]

Definition at line 31 of file kbmanager.h.

References _daemonVersion, DAEMON_UNAVAILABLE_STR, and parseVersionString().

Referenced by KbFirmware::_latestForBoard(), and MainWindow::updateVersion().

```
31 { return _daemonVersion == DAEMON_UNAVAILABLE_STR ? INFINITY :
     parseVersionString(_daemonVersion); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3.3 static QString KbManager::ckbGuiVersion ( ) [inline],[static]

Definition at line 26 of file kbmanager.h.

References _guiVersion.

```
26 { return _guiVersion; }
```

12.32.3.4 static float KbManager::ckbGuiVersionF ( ) [inline],[static]

Definition at line 30 of file kbmanager.h.

References _guiVersion, and parseVersionString().

Referenced by KbFirmware::_latestForBoard(), and MainWindow::updateVersion().

```
30 { return parseVersionString(_guiVersion); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3.5 static const QSet<Kb*> KbManager::devices ( ) [inline], [static]

Definition at line 34 of file kbmanager.h.

References _devices, and _kbManager.

```
34 { return _kbManager ? _kbManager->_devices : QSet<Kb*>(); }
```

12.32.3.6 static QTimer* KbManager::eventTimer ( ) [inline], [static]

Definition at line 38 of file kbmanager.h.

References _eventTimer, and _kbManager.

Referenced by fps().

```
38 { return _kbManager ? _kbManager->_eventTimer : 0; }
```

Here is the caller graph for this function:

12.32.3.7 void KbManager::fps (int *framerate*) [static]

Definition at line 35 of file kbmanager.cpp.

References eventTimer().

Referenced by Kb::frameRate().

```
35                                  {
36     QTimer* timer = eventTimer();
37     if(!timer)
38         return;
39     if(timer->isActive())
40         timer->setInterval(1000 / framerate);
41     else
42         timer->start(1000 / framerate);
43 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3.8 void KbManager::init (QString *guiVersion*) [static]

Definition at line 12 of file kbmanager.cpp.

References _guiVersion, _kbManager, and KbManager().

Referenced by MainWindow::MainWindow().

```
12                                          {
13     _guiVersion = guiVersion;
14     if(_kbManager)
15         return;
16     _kbManager = new KbManager();
17 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3.9 void KbManager::kbConnected (Kb * *device*) [signal]

Definition at line 174 of file moc_kbmanager.cpp.

Referenced by scanKeyboards().

```
175 {
176     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
177     QMetaObject::activate(this, &staticMetaObject, 0, _a);
178 }
```

Here is the caller graph for this function:

12.32.3.10 void KbManager::kbDisconnected (Kb * *device*) [signal]

Definition at line 181 of file moc_kbmanager.cpp.

Referenced by scanKeyboards().

```
182 {
183     void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
184     QMetaObject::activate(this, &staticMetaObject, 1, _a);
185 }
```

Here is the caller graph for this function:

12.32.3.11 static KbManager* KbManager::kbManager ( ) [inline],[static]

Definition at line 23 of file kbmanager.h.

References _kbManager.

Referenced by MainWindow::MainWindow().

```
23 { return _kbManager; }
```

Here is the caller graph for this function:

12.32.3.12 float KbManager::parseVersionString (QString *version*) [static]

Definition at line 45 of file kbmanager.cpp.

Referenced by ckbDaemonVersionF(), ckbGuiVersionF(), and KbFirmware::processDownload().

```
45                                                  {
46     // Remove extraneous info (anything after a +, anything non-numeric)
47     QStringList dots = version.replace(QRegExp("\\+.+"), "").replace(QRegExp("[^\\d\\.]"), "").split(".");
48     float base = 1.f;
49     float res = 0.f;
50     // A number like "1.2.3" will result in 1.0203
51     // NB: will fail if a point version goes over 99 or if using more than two dots. floats can only
       reliably encode 7 decimal digits.
52     foreach(const QString& dot, dots){
53         res += dot.toFloat() * base;
54         base /= 100.f;
55     }
56     return res;
57 }
```

Here is the caller graph for this function:

12.32.3.13 void KbManager::scanKeyboards ( ) [private], [slot]

Definition at line 59 of file kbmanager.cpp.

References _daemonVersion, _devices, _eventTimer, _scanTimer, DAEMON_UNAVAILABLE_STR, devpath, Kb::isOpen(), kbConnected(), kbDisconnected(), Kb::load(), Kb::matches(), Kb::save(), and versionUpdated().

Referenced by KbManager().

```
59                                  {
60     QString rootdev = devpath.arg(0);
61     QFile connected(rootdev + "/connected");
62     if(!connected.open(QIODevice::ReadOnly)){
63         // No root controller - remove all keyboards
64         foreach(Kb* kb, _devices){
65             emit kbDisconnected(kb);
66             kb->save();
67             delete kb;
68         }
69         _devices.clear();
70         if(_daemonVersion != DAEMON_UNAVAILABLE_STR){
```

```
            _daemonVersion = DAEMON_UNAVAILABLE_STR;
            emit versionUpdated();
        }
        return;
    }
    // Check daemon version
    QFile version(rootdev + "/version");
    QString vString;
    if(version.open(QIODevice::ReadOnly)){
        vString = QString::fromUtf8(version.readLine()).trimmed();
        version.close();
    } else
        vString = DAEMON_UNAVAILABLE_STR;
    if(_daemonVersion != vString){
        _daemonVersion = vString;
        emit versionUpdated();
    }

    // Scan connected devices
    QList<QStringList> lines;
    while(1){
        QString line = connected.readLine().trimmed();
        if(line.isEmpty())
            break;
        QStringList components = line.split(" ");
        if(components.length() < 2)             // "<path> <serial> <name>" (we're only interested in the first two)
            continue;
        lines.append(components);
    }
    connected.close();

    // Remove any active devices not in the list
    QMutableSetIterator<Kb*> i(_devices);
    while(i.hasNext()){
        Kb* kb = i.next();
        bool matched = false;
        foreach(const QStringList& line, lines){
            if(kb->matches(line[0], line[1])){
                matched = true;
                break;
            }
        }
        if(matched)
            continue;
        // Device not found, remove
        i.remove();
        emit kbDisconnected(kb);
        kb->save();
        delete kb;
    }

    // Add any new devices found in the list
    foreach(const QStringList& line, lines){
        bool matched = false;
        foreach(Kb* kb, _devices){
            if(kb->matches(line[0], line[1])){
                matched = true;
                break;
            }
        }
        if(matched)
            continue;
        // Device not found, create new
        Kb* kb = new Kb(this, line[0]);
        if(!kb->isOpen()){
            delete kb;
            continue;
        }
        _devices.insert(kb);
        // Load preferences and send signal
        emit kbConnected(kb);
        kb->load();
        connect(_eventTimer, SIGNAL(timeout()), kb, SLOT(frameUpdate()));
        connect(_scanTimer, SIGNAL(timeout()), kb, SLOT(autoSave()));
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.32.3.14 static QTimer∗ KbManager::scanTimer ( ) [inline],[static]

Definition at line 43 of file kbmanager.h.

References _kbManager, and _scanTimer.

Referenced by MainWindow::MainWindow().

```
43 { return _kbManager ? _kbManager->_scanTimer : 0; }
```

Here is the caller graph for this function:

12.32.3.15 void KbManager::stop ( ) [static]

Definition at line 19 of file kbmanager.cpp.

References _kbManager.

Referenced by MainWindow::cleanup().

```
                    {
    if(!_kbManager)
        return;
    delete _kbManager;
    _kbManager = 0;
}
```

Here is the caller graph for this function:

12.32.3.16 void KbManager::versionUpdated ( ) [signal]

Definition at line 188 of file moc_kbmanager.cpp.

Referenced by scanKeyboards().

```
{
    QMetaObject::activate(this, &staticMetaObject, 2, Q_NULLPTR);
}
```

Here is the caller graph for this function:

12.32.4 Field Documentation

12.32.4.1 QString KbManager::_daemonVersion = "<unavailable>" [static], [private]

Definition at line 59 of file kbmanager.h.

Referenced by ckbDaemonVersion(), ckbDaemonVersionF(), and scanKeyboards().

12.32.4.2 QSet<Kb*> KbManager::_devices [private]

Definition at line 63 of file kbmanager.h.

Referenced by devices(), and scanKeyboards().

12.32.4.3 QTimer* KbManager::_eventTimer [private]

Definition at line 64 of file kbmanager.h.

Referenced by eventTimer(), KbManager(), and scanKeyboards().

12.32.4.4 QString KbManager::_guiVersion [static],[private]

Definition at line 59 of file kbmanager.h.

Referenced by ckbGuiVersion(), ckbGuiVersionF(), and init().

12.32.4.5 KbManager * KbManager::_kbManager = 0 [static],[private]

Definition at line 58 of file kbmanager.h.

Referenced by devices(), eventTimer(), init(), kbManager(), scanTimer(), and stop().

12.32.4.6 QTimer * KbManager::_scanTimer [private]

Definition at line 64 of file kbmanager.h.

Referenced by KbManager(), scanKeyboards(), and scanTimer().

The documentation for this class was generated from the following files:

- src/ckb/kbmanager.h
- src/ckb/kbmanager.cpp
- src/ckb/release/moc_kbmanager.cpp

12.33 KbMode Class Reference

```
#include <src/ckb/kbmode.h>
```

Inheritance diagram for KbMode:

Collaboration diagram for KbMode:

Signals

- void updated ()

Public Member Functions

- KbMode (Kb *parent, const KeyMap &keyMap, const QString &guid="", const QString &modified="")
- KbMode (Kb *parent, const KeyMap &keyMap, CkbSettings &settings)
- KbMode (Kb *parent, const KeyMap &keyMap, const KbMode &other)

  KbMode::KbMode.
- ~KbMode ()

  KbMode::~KbMode Destructor may be used for Debugging (issue #38 with SIGSEGV). Insert qDebug-statement.
- const QString & name () const
- void name (const QString &newName)
- UsbId & id ()
- void id (const UsbId &newId)
- void newId ()
- void keyMap (const KeyMap &keyMap)
- KbLight * light ()
- KbBind * bind ()
- KbPerf * perf ()

- void save (CkbSettings &settings)
- bool needsSave () const
- void setNeedsSave ()
- void setNeedsUpdate ()

Private Slots

- void doUpdate ()

Private Attributes

- QString _name
- UsbId _id
- KbLight * _light
- KbBind * _bind
- KbPerf * _perf
- bool _needsSave

12.33.1 Detailed Description

Definition at line 36 of file kbmode.h.

12.33.2 Constructor & Destructor Documentation

12.33.2.1 KbMode::KbMode (Kb * *parent*, const KeyMap & *keyMap*, const QString & *guid* = " ", const QString & *modified* = " ")

Definition at line 4 of file kbmode.cpp.

References _id, _light, doUpdate(), UsbId::guid, and updated().

```
4                                                                                                                    :
5     QObject(parent),
6     _name("Unnamed"), _id(guid, modified),
7     _light(new KbLight(this, keyMap)), _bind(new KbBind(this, parent, keyMap)),
      _perf(new KbPerf(this)),
8     _needsSave(true)
9 {
10     connect(_light, SIGNAL(updated()), this, SLOT(doUpdate()));
11     if(_id.guid.isNull())
12         _id.guid = QUuid::createUuid();
13 }
```

Here is the call graph for this function:

12.33.2.2 KbMode::KbMode (Kb * *parent*, const KeyMap & *keyMap*, CkbSettings & *settings*)

Definition at line 30 of file kbmode.cpp.

References _bind, _id, _light, _name, _perf, CkbSettings::contains(), doUpdate(), UsbId::guid, UsbId::hwModified, UsbId::hwModifiedString(), KbPerf::load(), KbBind::load(), KbLight::load(), UsbId::modified, updated(), and CkbSettings::value().

```
30                                                                  :
31     QObject(parent),
32     _name(settings.value("Name").toString().trimmed()),
33     _id(settings.value("GUID").toString().trimmed(), settings.value("Modified").toString().
     trimmed()),
34     _light(new KbLight(this, keyMap)), _bind(new KbBind(this, parent, keyMap)),
     _perf(new KbPerf(this)),
35     _needsSave(false)
36 {
37     if(settings.contains("HwModified"))
38         _id.hwModifiedString(settings.value("HwModified").toString());
39     else
40         _id.hwModified = _id.modified;
41
42     connect(_light, SIGNAL(updated()), this, SLOT(doUpdate()));
43     if(_id.guid.isNull())
44         _id.guid = QUuid::createUuid();
45     if(_name == "")
46         _name = "Unnamed";
47     _light->load(settings);
48     _bind->load(settings);
49     _perf->load(settings);
50 }
```

Here is the call graph for this function:

12.33.2.3 KbMode::KbMode (Kb * *parent*, const KeyMap & *keyMap*, const KbMode & *other*)

Parameters

parent	Kb as parent (append to the Keyboard list
keyMap	Map to copy from
other	Mode to copy from Constructor to copy an existing Keyboard-Mode KbMode &other

Definition at line 21 of file kbmode.cpp.

References _light, doUpdate(), and updated().

```
21                                                                  :
22     QObject(parent),
```

```
    _name(other._name), _id(other._id),
    _light(new KbLight(this, keyMap, *other._light)), _bind(new
   KbBind(this, parent, keyMap, *other._bind)), _perf(new KbPerf(this, *other.
   _perf)),
    _needsSave(true)
{
    connect(_light, SIGNAL(updated()), this, SLOT(doUpdate()));
}
```

Here is the call graph for this function:

12.33.2.4 KbMode::~KbMode ( )

Definition at line 89 of file kbmode.cpp.

```
89                  {
90 }
```

12.33.3 Member Function Documentation

12.33.3.1 KbBind* KbMode::bind ( ) [inline]

Definition at line 61 of file kbmode.h.

References _bind.

Referenced by KbPerf::bind(), Kb::currentBind(), Kb::frameUpdate(), KbBindWidget::on_copyButton_clicked(), and Kb::readNotify().

```
61 { return _bind; }
```

Here is the caller graph for this function:

12.33.3.2 void KbMode::doUpdate ( ) [private],[slot]

Definition at line 82 of file kbmode.cpp.

References updated().

Referenced by KbMode().

```
82                      {
83     emit updated();
84 }
```

Here is the caller graph for this function:

12.33.3.3 UsbId& KbMode::id ( ) [inline]

Definition at line 52 of file kbmode.h.

References _id.

Referenced by KbProfile::find(), Kb::hwSave(), KbProfile::KbProfile(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemChanged(), KbWidget::on_modesList_itemClicked(), KbWidget::profileChanged(), Kb::readNotify(), and KbProfile::save().

```
52 { return _id; }
```

Here is the caller graph for this function:

12.33.3.4 void KbMode::id (const UsbId & *newId*) [inline]

Definition at line 53 of file kbmode.h.

References _id, _needsSave, and newId().

```
53 { _needsSave = true; _id = newId; }
```

Here is the call graph for this function:

12.33.3.5 void KbMode::keyMap (const KeyMap & *keyMap*)

Definition at line 60 of file kbmode.cpp.

References _bind, _light, _needsSave, KbLight::map(), and KbBind::map().

Referenced by KbProfile::keyMap().

```
60                                          {
61     _needsSave = true;
62     _light->map(keyMap);
63     _bind->map(keyMap);
64 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.33.3.6 KbLight* KbMode::light ( ) [inline]

Definition at line 60 of file kbmode.h.

References _light.

Referenced by Kb::currentLight(), Kb::frameUpdate(), Kb::hwSave(), KbBind::light(), KbPerf::light(), Kb::readNotify(), and Kb::updateLayout().

```
60 { return _light; }
```

Here is the caller graph for this function:

12.33.3.7 const QString& KbMode::name ( ) const [inline]

Definition at line 50 of file kbmode.h.

References _name.

Referenced by Kb::hwSave(), ModeSelectDialog::ModeSelectDialog(), KbWidget::on_modesList_itemChanged(), KbWidget::profileChanged(), Kb::readNotify(), and RebindWidget::setBind().

```
50 { return _name; }
```

Here is the caller graph for this function:

12.33.3.8 void KbMode::name (const QString & *newName*) [inline]

Definition at line 51 of file kbmode.h.

References _name, and _needsSave.

```
51 { _needsSave = true; _name = newName.trimmed(); if(_name == "")
     _name = "Unnamed"; }
```

12.33.3.9 bool KbMode::needsSave ( ) const

Definition at line 78 of file kbmode.cpp.

References _bind, _light, _needsSave, _perf, KbPerf::needsSave(), KbBind::needsSave(), and KbLight::needsSave().

Referenced by KbProfile::needsSave().

```
78                                {
79     return _needsSave || _light->needsSave() || _bind->
     needsSave() || _perf->needsSave();
80 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.33.3.10 void KbMode::newId ( )

Definition at line 52 of file kbmode.cpp.

References _id, _light, _needsSave, KbLight::animList(), and KbAnim::newId().

Referenced by id(), KbProfile::newId(), and KbWidget::on_modesList_customContextMenuRequested().

```
52                    {
53     _needsSave = true;
54     _id = UsbId();
55     // Create new IDs for animations
56     foreach(KbAnim* anim, _light->animList())
57         anim->newId();
58 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.33.3.11 KbPerf* KbMode::perf ( ) [inline]

Definition at line 62 of file kbmode.h.

References _perf.

Referenced by Kb::currentPerf(), Kb::frameUpdate(), Kb::hwSave(), KPerfWidget::on_copyButton_clicked(), MPerfWidget::on_copyButton_clicked(), KbBind::perf(), and Kb::readNotify().

```
62 { return _perf; }
```

Here is the caller graph for this function:

12.33.3.12 void KbMode::save (CkbSettings & *settings*)

Definition at line 66 of file kbmode.cpp.

References _bind, _id, _light, _name, _needsSave, _perf, UsbId::guidString(), UsbId::hwModifiedString(), UsbId::modifiedString(), UsbId::newModified(), KbPerf::save(), KbBind::save(), KbLight::save(), and CkbSettings::setValue().

Referenced by KbProfile::save().

```
66                                          {
67     _needsSave = false;
68     _id.newModified();
69     settings.setValue("GUID", _id.guidString());
70     settings.setValue("Modified", _id.modifiedString());
71     settings.setValue("HwModified", _id.hwModifiedString());
72     settings.setValue("Name", _name);
73     _light->save(settings);
74     _bind->save(settings);
75     _perf->save(settings);
76 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.33.3.13 void KbMode::setNeedsSave ( ) [inline]

Definition at line 67 of file kbmode.h.

References _needsSave.

Referenced by Kb::hwSave(), and Kb::readNotify().

```
67 { _needsSave = true; }
```

Here is the caller graph for this function:

12.33.3.14 void KbMode::setNeedsUpdate ( ) [inline]

Definition at line 68 of file kbmode.h.

References _bind, _perf, KbBind::setNeedsUpdate(), and KbPerf::setNeedsUpdate().

Referenced by KbProfile::setNeedsUpdate().

```
68 { _bind->setNeedsUpdate(); _perf->setNeedsUpdate(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.33.3.15 void KbMode::updated ( ) [signal]

Definition at line 131 of file moc_kbmode.cpp.

Referenced by doUpdate(), and KbMode().

```
{
    QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
}
```

Here is the caller graph for this function:

12.33.4 Field Documentation

12.33.4.1 KbBind* KbMode::_bind [private]

Definition at line 78 of file kbmode.h.

Referenced by bind(), KbMode(), keyMap(), needsSave(), save(), and setNeedsUpdate().

12.33.4.2 UsbId KbMode::_id [private]

Definition at line 75 of file kbmode.h.

Referenced by id(), KbMode(), newId(), and save().

12.33.4.3 KbLight* KbMode::_light [private]

Definition at line 77 of file kbmode.h.

Referenced by KbMode(), keyMap(), light(), needsSave(), newId(), and save().

12.33.4.4 QString KbMode::_name [private]

Definition at line 74 of file kbmode.h.

Referenced by KbMode(), name(), and save().

12.33.4.5 bool KbMode::_needsSave [private]

Definition at line 81 of file kbmode.h.

Referenced by id(), keyMap(), name(), needsSave(), newId(), save(), and setNeedsSave().

12.33.4.6 KbPerf* KbMode::_perf [private]

Definition at line 79 of file kbmode.h.

Referenced by KbMode(), needsSave(), perf(), save(), and setNeedsUpdate().

The documentation for this class was generated from the following files:

- src/ckb/kbmode.h
- src/ckb/kbmode.cpp
- src/ckb/release/moc_kbmode.cpp

12.34 KbPerf Class Reference

`#include <src/ckb/kbperf.h>`

Inheritance diagram for KbPerf:

Collaboration diagram for KbPerf:

Public Types

- enum height {
  LOW = 1, LOWMED, MEDIUM, MEDHIGH,
  HIGH }
- enum indicator {
  NUM, CAPS, SCROLL, HW_IMAX = SCROLL,
  MODE, MACRO, LIGHT, LOCK,
  MUTE }
- enum i_hw { NONE = -1, NORMAL, ON, OFF }

Signals

- void didLoad ()
- void settingsUpdated ()

Public Member Functions

- KbPerf (KbMode *parent)
- KbPerf (KbMode *parent, const KbPerf &other)
- const KbPerf & operator= (const KbPerf &rhs)
- void load (CkbSettings &settings)
- void save (CkbSettings &settings)
- bool needsSave () const
- height liftHeight () const
- void liftHeight (height newHeight)
- bool angleSnap () const
- void angleSnap (bool newAngleSnap)
- QPoint dpi (int index) const
- void dpi (int index, const QPoint &newValue)
- QPoint sniperDpi () const
- void sniperDpi (const QPoint &newValue)

- void dpi (int index, int newValue)
- void sniperDpi (int newValue)
- QPoint curDpi () const
- void curDpi (const QPoint &newDpi)
- void curDpi (int newDpi)
- int curDpiIdx () const
- void curDpiIdx (int newIdx)
- void dpiUp ()
- void dpiDown ()
- bool dpiEnabled (int index) const
- void dpiEnabled (int index, bool newEnabled)
- quint64 pushDpi (const QPoint &newDpi)
- quint64 pushDpi (int newDpi)
- quint64 pushSniper ()
- void popDpi (quint64 pushIdx)
- float iOpacity () const
- void iOpacity (float newIOpacity)
- bool dpiIndicator () const
- void dpiIndicator (bool newDpiIndicator)
- QColor dpiColor (int index) const
- void dpiColor (int index, const QColor &newColor)
- void getIndicator (indicator index, QColor &color1, QColor &color2, QColor &color3, bool &software_enable, i_hw &hardware_enable)
- void setIndicator (indicator index, const QColor &color1, const QColor &color2, const QColor &color3=QColor(), bool software_enable=true, i_hw hardware_enable=NORMAL)
- void update (QFile &cmd, bool force=false, bool saveCustomDpi=true)
- void setNeedsUpdate ()
- void applyIndicators (int modeIndex, const bool indicatorState[HW_I_COUNT])

Static Public Attributes

- static const int DPI_COUNT = 6
- static const int SNIPER = 0
- static const int DPI_MIN = 100
- static const int DPI_MAX = 12000
- static const int OTHER = DPI_COUNT
- static const int I_COUNT = (int)MUTE + 1
- static const int HW_I_COUNT = (int)HW_IMAX + 1

Private Member Functions

- KbMode * modeParent () const
- KbBind * bind () const
- KbLight * light () const
- void lightIndicator (const char *name, QRgb rgba)
- void _curDpi (const QPoint &newDpi)

Private Attributes

- int dpiX [DPI_COUNT]
- int dpiY [DPI_COUNT]
- int dpiCurX
- int dpiCurY
- int dpiCurIdx
- QColor dpiClr [DPI_COUNT+1]
- bool dpiOn [DPI_COUNT]
- int dpiLastIdx
- QMap< quint64, QPoint > pushedDpis
- uint runningPushIdx
- float _iOpacity
- QColor iColor [I_COUNT][2]
- QColor light100Color
- QColor muteNAColor
- bool iEnable [I_COUNT]
- i_hw hwIType [HW_I_COUNT]
- bool _dpiIndicator
- height _liftHeight
- bool _angleSnap
- bool _needsUpdate
- bool _needsSave

12.34.1 Detailed Description

Definition at line 15 of file kbperf.h.

12.34.2 Member Enumeration Documentation

12.34.2.1 enum KbPerf::height

Enumerator

LOW

LOWMED

MEDIUM

MEDHIGH

HIGH

Definition at line 31 of file kbperf.h.

```
31                  {
32          LOW = 1,
33          LOWMED,
34          MEDIUM,
35          MEDHIGH,
36          HIGH
37      };
```

12.34.2.2 enum KbPerf::i_hw

Enumerator

NONE

NORMAL

ON

OFF

Definition at line 98 of file kbperf.h.

```
98                {
99          NONE = -1,  // For non-hardware indicators
100          NORMAL,
101          ON,
102          OFF
103      };
```

12.34.2.3 enum KbPerf::indicator

Enumerator

NUM

CAPS

SCROLL

HW_IMAX

MODE

MACRO

LIGHT

LOCK

MUTE

Definition at line 85 of file kbperf.h.

```
85                    {
86          // Hardware
87          NUM,
88          CAPS,
89          SCROLL, HW_IMAX = SCROLL,
90          // Software
91          MODE,
92          MACRO,
93          LIGHT,
94          LOCK,
95          MUTE
96      };
```

12.34.3 Constructor & Destructor Documentation

12.34.3.1 KbPerf::KbPerf (KbMode * *parent*) [explicit]

Definition at line 13 of file kbperf.cpp.

References CAPS, DPI_COUNT, dpiClr, dpiCurIdx, dpiCurX, dpiCurY, dpiLastIdx, dpiOn, dpiX, dpiY, HW_I_COUNT, hwIType, I_COUNT, iColor, iEnable, LIGHT, light100Color, LOCK, MACRO, MODE, MUTE, muteNAColor, NORMAL, NUM, and SCROLL.

```
13                                :
14     QObject(parent), runningPushIdx(1),
15     _iOpacity(1.f), _dpiIndicator(true), _liftHeight(
      MEDIUM), _angleSnap(false),
16     _needsUpdate(true), _needsSave(true) {
17     // Default DPI settings
18     dpiX[0] = dpiY[0] = 400;
19     dpiX[1] = dpiY[1] = 450;
20     dpiX[2] = dpiY[2] = 800;
21     dpiX[3] = dpiY[3] = 1500;
22     dpiX[4] = dpiY[4] = 3000;
23     dpiX[5] = dpiY[5] = 6000;
24     dpiClr[0] = QColor(255, 0, 0);
25     dpiClr[1] = QColor(255, 192, 0);
26     dpiClr[2] = QColor(255, 255, 0);
27     dpiClr[3] = QColor(0, 255, 0);
28     dpiClr[4] = QColor(0, 255, 255);
29     dpiClr[5] = QColor(255, 255, 255);
30     dpiClr[6] = QColor(192, 192, 192);
31     for(int i = 0; i < DPI_COUNT; i++)
32         dpiOn[i] = true;
33     dpiLastIdx = dpiCurIdx = 3;
34     dpiCurX = dpiX[dpiCurIdx];
35     dpiCurY = dpiY[dpiCurIdx];
36     // Default indicators
37     iColor[NUM][0] = iColor[CAPS][0] = iColor[SCROLL][0] = QColor(0, 255, 0)
      ;   // Lock lights: on = green, off = black
38     iColor[NUM][1] = iColor[CAPS][1] = iColor[SCROLL][1] = QColor(0, 0, 0);
39     iColor[MACRO][0] = QColor(255, 0, 0);                                    // Macro: on =
       red, off = black
40     iColor[LOCK][0] = QColor(255, 255, 255);                                 // Win lock: on =
       white, off = black
41     iColor[MODE][0] = iColor[MUTE][0] = QColor(255, 255, 255, 0);            //
       Mode, mute: on = transparent, off = black
42     iColor[MODE][1] = iColor[MACRO][1] = iColor[LOCK][1] =
      iColor[MUTE][1] = muteNAColor = QColor(0, 0, 0);
43     iColor[LIGHT][0] = QColor(255, 0, 0);       // Brightness: red, yellow, white
44     iColor[LIGHT][1] = QColor(255, 255, 0);
45     light100Color = QColor(255, 255, 255);
46     for(int i = 0; i < HW_I_COUNT; i++){
47         // Set all lock lights to HW mode
48         iEnable[i] = false;
49         hwIType[i] = NORMAL;
50     }
51     for(int i = HW_I_COUNT; i < I_COUNT; i++){
52         // Turn all other indicators on
53         iEnable[i] = true;
54     }
55 }
```

12.34.3.2 KbPerf::KbPerf (KbMode * *parent*, const KbPerf & *other*)

Definition at line 57 of file kbperf.cpp.

References curDpi(), DPI_COUNT, dpiClr, dpiOn, dpiX, dpiY, hwIType, I_COUNT, iColor, iEnable, and pushedDpis.

```
57                                                  :
58     QObject(parent), dpiCurX(other.dpiCurX), dpiCurY(other.
      dpiCurY), dpiCurIdx(other.dpiCurIdx), dpiLastIdx(other.
      dpiLastIdx), runningPushIdx(1),
59     _iOpacity(other._iOpacity), light100Color(other.
      light100Color), muteNAColor(other.muteNAColor),
      _dpiIndicator(other._dpiIndicator),
60     _liftHeight(other._liftHeight), _angleSnap(other.
      _angleSnap),
61     _needsUpdate(true), _needsSave(true) {
62     memcpy(dpiX, other.dpiX, sizeof(dpiX));
63     memcpy(dpiY, other.dpiY, sizeof(dpiY));
64     for(int i = 0; i < DPI_COUNT + 1; i++)
65         dpiClr[i] = other.dpiClr[i];
66     memcpy(dpiOn, other.dpiOn, sizeof(dpiOn));
67     for(int i = 0; i < I_COUNT; i++){
68         iColor[i][0] = other.iColor[i][0];
69         iColor[i][1] = other.iColor[i][1];
70     }
71     memcpy(iEnable, other.iEnable, sizeof(iEnable));
72     memcpy(hwIType, other.hwIType, sizeof(hwIType));
73     // Don't copy pushed DPI states. If the other mode has any, restore the original DPI
74     if(!other.pushedDpis.isEmpty())
75         curDpi(other.pushedDpis[0]);
76 }
```

Here is the call graph for this function:

12.34.4 Member Function Documentation

12.34.4.1 void KbPerf::_curDpi (const QPoint & *newDpi*) [private]

Definition at line 262 of file kbperf.cpp.

References _needsSave, _needsUpdate, DPI_COUNT, dpiCurIdx, dpiCurX, dpiCurY, dpiLastIdx, dpiX, and dpiY.

Referenced by curDpi(), popDpi(), and pushDpi().

```
262                                         {
263     dpiCurX = newDpi.x();
264     dpiCurY = newDpi.y();
265     // Set current/last index
266     dpiCurIdx = -1;
267     for(int i = 0; i < DPI_COUNT; i++){
268         if(dpiCurX == dpiX[i] && dpiCurY == dpiY[i]){
269             dpiCurIdx = i;
270             if(i != 0)
271                 dpiLastIdx = i;
272             break;
273         }
274     }
275     _needsUpdate = _needsSave = true;
276 }
```

Here is the caller graph for this function:

12.34.4.2 bool KbPerf::angleSnap ( ) const [inline]

Definition at line 42 of file kbperf.h.

References _angleSnap.

Referenced by MPerfWidget::on_aSnapBox_clicked(), Kb::readNotify(), and MPerfWidget::setPerf().

```
42 { return _angleSnap; }
```

Here is the caller graph for this function:

12.34.4.3 void KbPerf::angleSnap (bool *newAngleSnap*)

Definition at line 368 of file kbperf.cpp.

References _angleSnap, _needsSave, and _needsUpdate.

```
368                                         {
369     _angleSnap = newAngleSnap;
370     _needsUpdate = _needsSave = true;
371 }
```

12.34.4.4 void KbPerf::applyIndicators (int *modeIndex*, const bool *indicatorState[HW_I_COUNT]*)

Definition at line 432 of file kbperf.cpp.

References _dpiIndicator, _iOpacity, bind(), CAPS, curDpiIdx(), dpiClr, getMuteState(), Kb::HWMODE_MAX, iColor, iEnable, LIGHT, light(), light100Color, lightIndicator(), LOCK, MACRO, MODE, MUTE, MUTED, muteNAColor, NUM, OTHER, KbLight::resetIndicators(), SCROLL, and UNMUTED.

Referenced by Kb::frameUpdate().

```
432                                                                         {
433     light()->resetIndicators();
434     if(_iOpacity <= 0.f)
435         return;
436     if(_dpiIndicator){
437         // Set DPI indicator according to index
438         int index = curDpiIdx();
439         if(index == -1 || index > OTHER)
440             index = OTHER;
441         lightIndicator("dpi", dpiClr[index].rgba());
442     }
443     // KB indicators
444     if(iEnable[MODE]){
445         for(int i = 0; i < Kb::HWMODE_MAX; i++){
446             char name[4];
447             snprintf(name, sizeof(name), "m%d", i + 1);
448             if(modeIndex == i)
449                 lightIndicator(name, iColor[MODE][0].rgba());
450             else
451                 lightIndicator(name, iColor[MODE][1].rgba());
452         }
453     }
454     if(iEnable[MACRO])
455         lightIndicator("mr", iColor[MUTE][1].rgba());
456     if(iEnable[LIGHT]){
457         switch(light()->dimming()){
458         case 0: // 100%
459             lightIndicator("light", light100Color.rgba());
460             break;
461         case 1: // 67%
462             lightIndicator("light", iColor[LIGHT][1].rgba());
463             break;
464         case 2: // 33%
465         case 3: // light off
466             lightIndicator("light", iColor[LIGHT][0].rgba());
467             break;
```

```
        }
    }
    if(iEnable[LOCK]){
        if(bind()->winLock())
            lightIndicator("lock", iColor[LOCK][0].rgba());
        else
            lightIndicator("lock", iColor[LOCK][1].rgba());
    }
    if(iEnable[MUTE]){
        switch(getMuteState()){
        case MUTED:
            lightIndicator("mute", iColor[MUTE][0].rgba());
            break;
        case UNMUTED:
            lightIndicator("mute", iColor[MUTE][1].rgba());
            break;
        default:
            lightIndicator("mute", muteNAColor.rgba());
            break;
        }
    }
    // Lock lights
    if(iEnable[NUM])
        lightIndicator("numlock", indicatorState[0] ? iColor[NUM][0].rgba() :
    iColor[NUM][1].rgba());
    if(iEnable[CAPS])
        lightIndicator("caps", indicatorState[1] ? iColor[CAPS][0].rgba() :
    iColor[CAPS][1].rgba());
    if(iEnable[SCROLL])
        lightIndicator("scroll", indicatorState[2] ? iColor[SCROLL][0].rgba() :
    iColor[SCROLL][1].rgba());
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.5 KbBind * KbPerf::bind ( ) const [private]

Definition at line 100 of file kbperf.cpp.

References KbMode::bind(), and modeParent().

Referenced by applyIndicators().

```
100                                 {
101     return modeParent()->bind();
102 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.6 QPoint KbPerf::curDpi ( ) const [inline]

Definition at line 57 of file kbperf.h.

References dpiCurX, and dpiCurY.

Referenced by curDpiIdx(), KbPerf(), load(), operator=(), and pushDpi().

```
57 { return QPoint(dpiCurX, dpiCurY); }
```

Here is the caller graph for this function:

12.34.4.7 void KbPerf::curDpi (const QPoint & *newDpi*)

Definition at line 278 of file kbperf.cpp.

References _curDpi(), popDpi(), and pushedDpis.

```
                                        {
    while(pushedDpis.count() > 0)
        popDpi(pushedDpis.keys().last());
    _curDpi(newDpi);
}
```

Here is the call graph for this function:

12.34.4.8 void KbPerf::curDpi (int *newDpi*) [inline]

Definition at line 59 of file kbperf.h.

References curDpi().

Referenced by curDpi().

```
59 { curDpi(QPoint(newDpi, newDpi)); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.9 int KbPerf::curDpiIdx ( ) const [inline]

Definition at line 61 of file kbperf.h.

References dpiCurIdx.

Referenced by applyIndicators(), dpiDown(), dpiUp(), and Kb::readNotify().

```
61 { return dpiCurIdx; }
```

Here is the caller graph for this function:

12.34.4.10 void KbPerf::curDpiIdx (int *newIdx*) [inline]

Definition at line 62 of file kbperf.h.

References curDpi(), and dpi().

```
62 { curDpi(dpi(newIdx)); }
```

Here is the call graph for this function:

12.34.4.11 void KbPerf::didLoad ( ) [signal]

Definition at line 134 of file moc_kbperf.cpp.

Referenced by load().

```
135 {
136     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
137 }
```

Here is the caller graph for this function:

12.34.4.12 QPoint KbPerf::dpi (int *index*) const [inline]

Definition at line 48 of file kbperf.h.

References DPI_COUNT, dpiX, and dpiY.

Referenced by MPerfWidget::boxXChanged(), MPerfWidget::boxYChanged(), curDpiIdx(), KeyAction::keyEvent(), Kb::readNotify(), RebindWidget::setBind(), MPerfWidget::setPerf(), MPerfWidget::sliderXMoved(), MPerfWidget::sliderYMoved(), and sniperDpi().

```
48 { if(index < 0 || index >= DPI_COUNT) return QPoint(); return QPoint(
      dpiX[index], dpiY[index]); }
```

Here is the caller graph for this function:

12.34.4.13 void KbPerf::dpi (int *index,* const QPoint & *newValue*)

Definition at line 249 of file kbperf.cpp.

References _needsSave, _needsUpdate, DPI_COUNT, dpiCurIdx, dpiCurX, dpiCurY, dpiX, and dpiY.

```
249                                                 {
250     if(index < 0 || index >= DPI_COUNT)
251         return;
252     dpiX[index] = newValue.x();
253     dpiY[index] = newValue.y();
254     // Update current DPI if needed
255     if(dpiCurIdx == index){
256         dpiCurX = newValue.x();
257         dpiCurY = newValue.y();
258     }
259     _needsUpdate = _needsSave = true;
260 }
```

12.34.4.14 void KbPerf::dpi (int *index*, int *newValue*) [inline]

Definition at line 53 of file kbperf.h.

References dpi().

Referenced by dpi().

```
53 { dpi(index, QPoint(newValue, newValue)); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.15 QColor KbPerf::dpiColor (int *index*) const [inline]

Definition at line 82 of file kbperf.h.

References dpiClr.

Referenced by MPerfWidget::colorChanged(), Kb::readNotify(), MPerfWidget::setPerf(), and update().

```
82 { return dpiClr[index]; }
```

Here is the caller graph for this function:

12.34.4.16 void KbPerf::dpiColor (int *index*, const QColor & *newColor*) [inline]

Definition at line 83 of file kbperf.h.

References _needsSave, _needsUpdate, and dpiClr.

```
83 { dpiClr[index] = newColor; _needsUpdate = _needsSave = true; }
```

12.34.4.17 void KbPerf::dpiDown ( )

Definition at line 319 of file kbperf.cpp.

References curDpiIdx(), dpiOn, and SNIPER.

Referenced by KeyAction::keyEvent().

```
319                     {
320     int idx = curDpiIdx();
321     do {
322         idx--;
323         if(idx <= SNIPER)
324             return;
325     } while(!dpiOn[idx]);
326     curDpiIdx(idx);
327 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.18 bool KbPerf::dpiEnabled (int *index*) const [inline]

Definition at line 66 of file kbperf.h.

References dpiOn.

Referenced by MPerfWidget::enableChanged(), Kb::readNotify(), and MPerfWidget::setPerf().

```
66 { return dpiOn[index]; }
```

Here is the caller graph for this function:

12.34.4.19 void KbPerf::dpiEnabled (int *index*, bool *newEnabled*) [inline]

Definition at line 67 of file kbperf.h.

References _needsSave, _needsUpdate, and dpiOn.

```
67 { if(index <= 0) return; dpiOn[index] = newEnabled; _needsUpdate =
      _needsSave = true; }
```

12.34.4.20 bool KbPerf::dpiIndicator ( ) const [inline]

Definition at line 79 of file kbperf.h.

References _dpiIndicator.

Referenced by MPerfWidget::on_indicBox_clicked(), and MPerfWidget::setPerf().

```
79 { return _dpiIndicator; }
```

Here is the caller graph for this function:

12.34.4.21 void KbPerf::dpiIndicator (bool *newDpiIndicator*) [inline]

Definition at line 80 of file kbperf.h.

References _dpiIndicator, and _needsSave.

```
80 { _dpiIndicator = newDpiIndicator; _needsSave = true; }
```

12.34.4.22 void KbPerf::dpiUp ( )

Definition at line 308 of file kbperf.cpp.

References curDpiIdx(), DPI_COUNT, and dpiOn.

Referenced by KeyAction::keyEvent().

```
308                 {
309     // Scroll past disabled DPIs and choose the next one up
310     int idx = curDpiIdx();
311     do {
312         idx++;
313         if(idx >= DPI_COUNT)
314             return;
315     } while(!dpiOn[idx]);
316     curDpiIdx(idx);
317 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.23 void KbPerf::getIndicator (indicator *index*, QColor & *color1*, QColor & *color2*, QColor & *color3*, bool & *software_enable*, i_hw & *hardware_enable*)

Definition at line 329 of file kbperf.cpp.

References HW_IMAX, hwIType, I_COUNT, iColor, iEnable, LIGHT, light100Color, MUTE, muteNAColor, and NONE.

Referenced by KPerfWidget::setPerf().

```
329                                 {
330     if(index < 0 || index >= I_COUNT)
331         return;
332     color1 = iColor[index][0];
333     color2 = iColor[index][1];
334     if(index == LIGHT)
335         color3 = light100Color;
336     else if(index == MUTE)
337         color3 = muteNAColor;
338     else
339         color3 = QColor();
340     software_enable = iEnable[index];
341     hardware_enable = (index <= HW_IMAX ? hwIType[index] : NONE);
342 }
```

Here is the caller graph for this function:

12.34.4.24 float KbPerf::iOpacity ( ) const [inline]

Definition at line 76 of file kbperf.h.

References _iOpacity.

Referenced by KPerfWidget::on_intensityBox_valueChanged(), MPerfWidget::on_spinBox_valueChanged(), KPerfWidget::setPerf(), and MPerfWidget::setPerf().

```
76 { return _iOpacity; }
```

Here is the caller graph for this function:

12.34.4.25 void KbPerf::iOpacity (float *newIOpacity*) [inline]

Definition at line 77 of file kbperf.h.

References _iOpacity, and _needsSave.

```
77 { _iOpacity = newIOpacity; _needsSave = true; }
```

12.34.4.26 height KbPerf::liftHeight ( ) const [inline]

Definition at line 38 of file kbperf.h.

References _liftHeight.

Referenced by MPerfWidget::on_lHeightBox_activated(), Kb::readNotify(), and MPerfWidget::setPerf().

```
38 { return _liftHeight; }
```

Here is the caller graph for this function:

12.34.4.27 void KbPerf::liftHeight (height *newHeight*)

Definition at line 361 of file kbperf.cpp.

References _liftHeight, _needsSave, _needsUpdate, and HIGH.

```
361                                     {
362     if(newHeight < LOW || newHeight > HIGH)
363         return;
364     _liftHeight = newHeight;
365     _needsUpdate = _needsSave = true;
366 }
```

12.34.4.28 KbLight * KbPerf::light ( ) const [private]

Definition at line 104 of file kbperf.cpp.

References KbMode::light(), and modeParent().

Referenced by applyIndicators(), and lightIndicator().

```
104                             {
105     return modeParent()->light();
106 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.29 void KbPerf::lightIndicator (const char * *name*, QRgb *rgba*) [private]

Definition at line 425 of file kbperf.cpp.

References _iOpacity, light(), and KbLight::setIndicator().

Referenced by applyIndicators().

```
425                                                 {
426     int a = round(qAlpha(rgba) * _iOpacity);
427     if(a <= 0)
428         return;
429     light()->setIndicator(name, qRgba(qRed(rgba), qGreen(rgba), qBlue(rgba), a));
430 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.30 void KbPerf::load (CkbSettings & *settings*)

Definition at line 108 of file kbperf.cpp.

References _angleSnap, _dpiIndicator, _iOpacity, _liftHeight, _needsSave, CkbSettings::contains(), CkbSettings::containsGroup(), curDpi(), didLoad(), DPI_COUNT, dpiClr, dpiLastIdx, dpiOn, dpiX, dpiY, HIGH, HW_IMAX, hwIType, I_COUNT, iColor, iEnable, LIGHT, light100Color, LOCK, MACRO, MEDIUM, MODE, MUTE, muteNAColor, NORMAL, OTHER, pushedDpis, runningPushIdx, and CkbSettings::value().

Referenced by KbMode::KbMode().

```
108                                         {
109     pushedDpis.clear();
110     runningPushIdx = 1;
111     _needsSave = false;
112     bool readIndicators = true;
113     if(!settings.containsGroup("Performance/Indicators")){
114         // Read old indicator settings from the lighting group, if present
115         // (ckb <= v0.2.0)
116         SGroup group(settings, "Lighting");
117         if(settings.contains("InactiveIndicators")){
118             bool inOk = false;
119             int inactive = settings.value("InactiveIndicators").toInt(&inOk);
120             if(!inOk || inactive > 2)
121                 inactive = 2;
122             if(inactive == 1)
123                 _iOpacity = 0.75f;
124             else if(inactive == 0)
125                 _iOpacity = 0.5f;
126             else if(inactive < 0){
127                 // Indicators disabled
128                 iEnable[MODE] = iEnable[MACRO] = iEnable[
    LIGHT] = iEnable[LOCK]  = iEnable[MUTE] = false;
129             }
130             bool showMute = (settings.value("ShowMute").toInt(&inOk) != 0);
131             if(inOk && !showMute)
132                 iEnable[MUTE] = false;
133             readIndicators = false;
134         }
135     }
136     SGroup group(settings, "Performance");
137     // Read DPI settings
138     {
139         SGroup group(settings, "DPI");
140         for(int i = 0; i < DPI_COUNT; i++){
141             QString iStr = QString::number(i);
142             QPoint value = settings.value(iStr).toPoint();
143             if(value.isNull())
144                 continue;
145             dpiX[i] = value.x(); dpiY[i] = value.y();
146             QColor color = settings.value(iStr + "RGB").toString();
147             if(color.isValid())
148                 dpiClr[i] = color;
149             if(i != 0)
150                 dpiOn[i] = !settings.value(iStr + "Disabled").toBool();
151         }
152         QColor color = settings.value("6RGB").toString();
153         if(color.isValid())
154             dpiClr[OTHER] = color;
155         if(settings.contains("LastIdx")){
156             dpiLastIdx = settings.value("LastIdx").toInt();
157             if(dpiLastIdx >= DPI_COUNT || dpiLastIdx < 0)
158                 dpiLastIdx = 1;
159         }
160         QPoint value = settings.value("Current").toPoint();
161         if(!value.isNull())
```

```
            curDpi(value);
    }
    // Read misc. mouse settings
    _liftHeight = (height)settings.value("LiftHeight").toInt();
    if(_liftHeight < LOW || _liftHeight > HIGH)
        _liftHeight = MEDIUM;
    _angleSnap = settings.value("AngleSnap").toBool();
    if(settings.contains("NoIndicator")){
        // ckb <= v0.2.0
        _dpiIndicator = !settings.value("NoIndicator").toBool();
    } else {
        _dpiIndicator = settings.value("Indicators/DPI", true).toBool();
    }
    // Read indicator settings
    if(readIndicators){
        SGroup group(settings, "Indicators");
        _iOpacity = settings.value("Opacity", 100).toInt() / 100.f;
        for(int i = 0; i < I_COUNT; i++){
            SGroup group(settings, QString::number(i));
            QColor color = settings.value("RGB0").toString();
            if(color.isValid())
                iColor[i][0] = color;
            color = settings.value("RGB1").toString();
            if(color.isValid())
                iColor[i][1] = color;
            if(i == LIGHT){
                color = settings.value("RGB2").toString();
                if(color.isValid())
                    light100Color = color;
            } else if(i == MUTE){
                color = settings.value("RGB2").toString();
                if(color.isValid())
                    muteNAColor = color;
            }
            if(i <= HW_IMAX){
                iEnable[i] = settings.value("Enable", false).toBool();
                hwIType[i] = (i_hw)settings.value("Hardware", (int)
NORMAL).toInt();
            } else {
                iEnable[i] = settings.value("Enable", true).toBool();
            }
        }
    }
    emit didLoad();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.31 KbMode* KbPerf::modeParent ( ) const [inline], [private]

Definition at line 124 of file kbperf.h.

Referenced by bind(), and light().

```
124 { return (KbMode*)parent(); }
```

Here is the caller graph for this function:

12.34.4.32 bool KbPerf::needsSave ( ) const [inline]

Definition at line 28 of file kbperf.h.

References _needsSave.

Referenced by KbMode::needsSave().

```
28 { return _needsSave; }
```

Here is the caller graph for this function:

12.34.4.33 const KbPerf & KbPerf::operator= (const KbPerf & *rhs*)

Definition at line 78 of file kbperf.cpp.

References _angleSnap, _dpiIndicator, _iOpacity, _liftHeight, _needsSave, _needsUpdate, curDpi(), DPI_COUNT, dpiClr, dpiCurIdx, dpiCurX, dpiCurY, dpiLastIdx, dpiOn, dpiX, dpiY, hwIType, I_COUNT, iColor, iEnable, light100Color, muteNAColor, pushedDpis, and runningPushIdx.

```
78                                                  {
79     dpiCurX = other.dpiCurX; dpiCurY = other.dpiCurY; dpiCurIdx = other.dpiCurIdx;
      dpiLastIdx = other.dpiLastIdx; runningPushIdx = 1;
80     _iOpacity = other._iOpacity; light100Color = other.light100Color;
      muteNAColor = other.muteNAColor; _dpiIndicator = other._dpiIndicator;
81     _liftHeight = other._liftHeight; _angleSnap = other._angleSnap;
82     _needsUpdate = true; _needsSave = true;
83     memcpy(dpiX, other.dpiX, sizeof(dpiX));
84     memcpy(dpiY, other.dpiY, sizeof(dpiY));
85     for(int i = 0; i < DPI_COUNT + 1; i++)
86         dpiClr[i] = other.dpiClr[i];
87     memcpy(dpiOn, other.dpiOn, sizeof(dpiOn));
88     for(int i = 0; i < I_COUNT; i++){
89         iColor[i][0] = other.iColor[i][0];
90         iColor[i][1] = other.iColor[i][1];
91     }
92     memcpy(iEnable, other.iEnable, sizeof(iEnable));
```

```
    memcpy(hwIType, other.hwIType, sizeof(hwIType));
    // Don't copy pushed DPI states. If the other mode has any, restore the original DPI
    if(!other.pushedDpis.isEmpty())
        curDpi(other.pushedDpis[0]);
    return other;
}
```

Here is the call graph for this function:

12.34.4.34 void KbPerf::popDpi (quint64 *pushIdx*)

Definition at line 296 of file kbperf.cpp.

References _curDpi(), _needsSave, _needsUpdate, map_last, and pushedDpis.

Referenced by curDpi(), and KeyAction::keyEvent().

```
296                                 {
297     if(pushIdx == 0 || !pushedDpis.contains(pushIdx))
298         return;
299     pushedDpis.remove(pushIdx);
300     // Set the DPI to the last-pushed value still on the stack
301     _curDpi(map_last(pushedDpis));
302     // If all values have been popped, remove the original DPI
303     if(pushedDpis.count() == 1)
304         pushedDpis.clear();
305     _needsUpdate = _needsSave = true;
306 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.35 quint64 KbPerf::pushDpi (const QPoint & *newDpi*)

Definition at line 284 of file kbperf.cpp.

References _curDpi(), curDpi(), pushedDpis, and runningPushIdx.

Referenced by KeyAction::keyEvent(), and pushSniper().

```
284                                                 {
285     if(pushedDpis.isEmpty())
286         // Push original DPI
287         pushedDpis[0] = curDpi();
288     quint64 index = runningPushIdx++;
289     if(runningPushIdx == 0)
290         runningPushIdx = 1;
291     pushedDpis[index] = newDpi;
292     _curDpi(newDpi);
293     return index;
294 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.36 quint64 KbPerf::pushDpi (int *newDpi*) [inline]

Definition at line 71 of file kbperf.h.

References pushDpi().

Referenced by pushDpi().

```
71 { return pushDpi(QPoint(newDpi, newDpi)); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.37 quint64 KbPerf::pushSniper ( ) [inline]

Definition at line 72 of file kbperf.h.

References pushDpi(), and sniperDpi().

Referenced by KeyAction::keyEvent().

```
72 { return pushDpi(sniperDpi()); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.38 void KbPerf::save (CkbSettings & *settings*)

Definition at line 207 of file kbperf.cpp.

References _angleSnap, _dpiIndicator, _liftHeight, _needsSave, DPI_COUNT, dpiClr, dpiCurX, dpiCurY, dpiLastIdx, dpiOn, dpiX, dpiY, HW_IMAX, hwIType, I_COUNT, iColor, iEnable, LIGHT, light100Color, MUTE, muteNAColor, OTHER, pushedDpis, and CkbSettings::setValue().

Referenced by KbMode::save().

```
207                                     {
208     _needsSave = false;
209     SGroup group(settings, "Performance");
210     {
211         SGroup group(settings, "DPI");
212         for(int i = 0; i < DPI_COUNT; i++){
213             QString iStr = QString::number(i);
214             settings.setValue(iStr, QPoint(dpiX[i], dpiY[i]));
215             settings.setValue(iStr + "RGB", dpiClr[i].name(QColor::HexArgb));
216             if(i != 0)
217                 settings.setValue(iStr + "Disabled", !dpiOn[i]);
218         }
219         settings.setValue("6RGB", dpiClr[OTHER].name(QColor::HexArgb));
220         settings.setValue("LastIdx", dpiLastIdx);
221         int curX = dpiCurX, curY = dpiCurY;
222         // Ignore any pushed modes
223         if(pushedDpis.count() > 0){
224             curX = pushedDpis.value(0).x();
225             curY = pushedDpis.value(0).y();
226         }
227         settings.setValue("Current", QPoint(curX, curY));
228     }
229     settings.setValue("LiftHeight", _liftHeight);
230     settings.setValue("AngleSnap", _angleSnap);
231     {
232         SGroup group(settings, "Indicators");
233         settings.setValue("DPI", _dpiIndicator);
234         for(int i = 0; i < I_COUNT; i++){
235             SGroup group(settings, QString::number(i));
236             settings.setValue("RGB0", iColor[i][0].name(QColor::HexArgb));
237             settings.setValue("RGB1", iColor[i][1].name(QColor::HexArgb));
238             if(i == LIGHT)
239                 settings.setValue("RGB2", light100Color.name(QColor::HexArgb));
240             else if(i == MUTE)
241                 settings.setValue("RGB2", muteNAColor.name(QColor::HexArgb));
242             settings.setValue("Enable", iEnable[i]);
243             if(i <= HW_IMAX)
244                 settings.setValue("Hardware", (int)hwIType[i]);
245         }
246     }
247 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.39 void KbPerf::setIndicator (indicator *index*, const QColor & *color1*, const QColor & *color2*, const QColor & *color3* = `QColor()`, bool *software_enable* = `true`, i_hw *hardware_enable* = NORMAL)

Definition at line 344 of file kbperf.cpp.

References _needsSave, _needsUpdate, HW_IMAX, hwIType, I_COUNT, iColor, iEnable, LIGHT, light100Color, MUTE, muteNAColor, NONE, and NORMAL.

Referenced by KPerfWidget::uiUpdated().

```
344                                                     {
345     if(index < 0 || index >= I_COUNT)
346         return;
347     iColor[index][0] = color1;
348     iColor[index][1] = color2;
349     if(index == LIGHT)
350         light100Color = color3;
351     else if(index == MUTE)
352         muteNAColor = color3;
353     iEnable[index] = software_enable;
354     if(hardware_enable == NONE)
355         hardware_enable = NORMAL;
356     if(index <= HW_IMAX)
357         hwIType[index] = hardware_enable;
358     _needsUpdate = _needsSave = true;
359 }
```

Here is the caller graph for this function:

12.34.4.40 void KbPerf::setNeedsUpdate ( ) [inline]

Definition at line 113 of file kbperf.h.

References _needsUpdate.

Referenced by KbMode::setNeedsUpdate().

```
113 { _needsUpdate = true; }
```

Here is the caller graph for this function:

12.34.4.41 void KbPerf::settingsUpdated ( ) [signal]

Definition at line 140 of file moc_kbperf.cpp.

Referenced by update().

```
141 {
142     QMetaObject::activate(this, &staticMetaObject, 1, Q_NULLPTR);
143 }
```

Here is the caller graph for this function:

12.34.4.42 QPoint KbPerf::sniperDpi ( ) const [inline]

Definition at line 50 of file kbperf.h.

References dpi(), and SNIPER.

Referenced by pushSniper().

```
50 { return dpi(SNIPER); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.43 void KbPerf::sniperDpi (const QPoint & *newValue*) [inline]

Definition at line 51 of file kbperf.h.

References dpi(), and SNIPER.

```
51 { dpi(SNIPER, newValue); }
```

Here is the call graph for this function:

12.34.4.44 void KbPerf::sniperDpi (int *newValue*) [inline]

Definition at line 54 of file kbperf.h.

References sniperDpi().

Referenced by sniperDpi().

```
54 { sniperDpi(QPoint(newValue, newValue)); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.4.45 void KbPerf::update (QFile & *cmd*, bool *force* = `false`, bool *saveCustomDpi* = `true`)

Definition at line 373 of file kbperf.cpp.

References _angleSnap, _liftHeight, _needsUpdate, DPI_COUNT, dpiColor(), dpiCurIdx, dpiCurX, dpiCurY, dpiOn, dpiX, dpiY, HW_I_COUNT, hwIType, OFF, ON, and settingsUpdated().

Referenced by Kb::frameUpdate(), and Kb::hwSave().

```
373                                                                 {
374     if(!force && !_needsUpdate)
375         return;
376     emit settingsUpdated();
377     _needsUpdate = false;
378     // Save DPI stage 0 (sniper)
379     cmd.write(QString("dpi 0:%1,%2").arg(dpiX[0]).arg(dpiY[0]).toLatin1());
380     // If the mouse is set to a custom DPI, save it in stage 1
381     int stage = dpiCurIdx;
382     if(stage < 0 && saveCustomDpi){
383         stage = 1;
384         cmd.write(QString(" 1:%1,%2").arg(dpiCurX).arg(dpiCurY).toLatin1());
385     } else {
386         // Otherwise, save stage 1 normally
387         if(!dpiOn[1] && stage != 1)
388             cmd.write(" 1:off");
389         else
390             cmd.write(QString(" 1:%1,%2").arg(dpiX[1]).arg(dpiY[1]).toLatin1());
391     }
392     // Save stages 1 - 5
393     for(int i = 2; i < DPI_COUNT; i++){
394         if(!dpiOn[i] && stage != i)
395             cmd.write(QString(" %1:off").arg(i).toLatin1());
396         else
397         cmd.write(QString(" %1:%2,%3").arg(i).arg(dpiX[i]).arg(dpiY[i]).toLatin1());
398     }
399     // Save stage selection, lift height, and angle snap
400     cmd.write(QString(" dpisel %1 lift %2 snap %3").arg(stage).arg(_liftHeight).arg(
    _angleSnap ? "on" : "off").toLatin1());
401     // Save DPI colors
402     cmd.write(" rgb");
403     for(int i = 0; i < DPI_COUNT; i++){
404         QColor color = dpiColor(i);
405         cmd.write(" dpi");
406         char output[9];
407         snprintf(output, sizeof(output), "%1d:%02x%02x%02x", i, color.red(), color.green(), color.blue());
408         cmd.write(output);
409     }
410     // Enable indicator notifications
411     cmd.write(" inotify all");
412     // Set indicator state
413     const char* iNames[HW_I_COUNT] = { "num", "caps", "scroll" };
414     for(int i = 0; i < HW_I_COUNT; i++){
415         if(hwIType[i] == ON)
416             cmd.write(" ion ");
417         else if(hwIType[i] == OFF)
418             cmd.write(" ioff ");
419         else
420             cmd.write(" iauto ");
421         cmd.write(iNames[i]);
422     }
423 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.34.5 Field Documentation

12.34.5.1 bool KbPerf::_angleSnap [private]

Definition at line 158 of file kbperf.h.

Referenced by angleSnap(), load(), operator=(), save(), and update().

12.34.5.2 bool KbPerf::_dpiIndicator [private]

Definition at line 154 of file kbperf.h.

Referenced by applyIndicators(), dpiIndicator(), load(), operator=(), and save().

12.34.5.3 float KbPerf::_iOpacity [private]

Definition at line 149 of file kbperf.h.

Referenced by applyIndicators(), iOpacity(), lightIndicator(), load(), and operator=().

12.34.5.4 height KbPerf::_liftHeight [private]

Definition at line 157 of file kbperf.h.

Referenced by liftHeight(), load(), operator=(), save(), and update().

12.34.5.5 bool KbPerf::_needsSave [private]

Definition at line 160 of file kbperf.h.

Referenced by _curDpi(), angleSnap(), dpi(), dpiColor(), dpiEnabled(), dpiIndicator(), iOpacity(), liftHeight(), load(), needsSave(), operator=(), popDpi(), save(), and setIndicator().

12.34.5.6 bool KbPerf::_needsUpdate [private]

Definition at line 160 of file kbperf.h.

Referenced by _curDpi(), angleSnap(), dpi(), dpiColor(), dpiEnabled(), liftHeight(), operator=(), popDpi(), setIndicator(), setNeedsUpdate(), and update().

12.34.5.7 const int KbPerf::DPI_COUNT = 6 [static]

Definition at line 46 of file kbperf.h.

Referenced by _curDpi(), dpi(), dpiUp(), KbPerf(), KeyAction::keyEvent(), load(), operator=(), Kb::readNotify(), save(), RebindWidget::setBind(), and update().

12.34.5.8 const int KbPerf::DPI_MAX = 12000 [static]

Definition at line 47 of file kbperf.h.

12.34.5.9 const int KbPerf::DPI_MIN = 100 [static]

Definition at line 47 of file kbperf.h.

Referenced by dpiExp(), and dpiLog().

12.34.5.10 QColor KbPerf::dpiClr[DPI_COUNT+1] [private]

Definition at line 135 of file kbperf.h.

Referenced by applyIndicators(), dpiColor(), KbPerf(), load(), operator=(), and save().

12.34.5.11 int KbPerf::dpiCurIdx [private]

Definition at line 134 of file kbperf.h.

Referenced by _curDpi(), curDpiIdx(), dpi(), KbPerf(), operator=(), and update().

12.34.5.12 int KbPerf::dpiCurX [private]

Definition at line 134 of file kbperf.h.

Referenced by _curDpi(), curDpi(), dpi(), KbPerf(), operator=(), save(), and update().

12.34.5.13 int KbPerf::dpiCurY [private]

Definition at line 134 of file kbperf.h.

Referenced by _curDpi(), curDpi(), dpi(), KbPerf(), operator=(), save(), and update().

12.34.5.14 int KbPerf::dpiLastIdx [private]

Definition at line 138 of file kbperf.h.

Referenced by _curDpi(), KbPerf(), load(), operator=(), and save().

12.34.5.15 bool KbPerf::dpiOn[DPI_COUNT] [private]

Definition at line 136 of file kbperf.h.

Referenced by dpiDown(), dpiEnabled(), dpiUp(), KbPerf(), load(), operator=(), save(), and update().

12.34.5.16 int KbPerf::dpiX[DPI_COUNT] [private]

Definition at line 132 of file kbperf.h.

Referenced by _curDpi(), dpi(), KbPerf(), load(), operator=(), save(), and update().

12.34.5.17 int KbPerf::dpiY[DPI_COUNT] [private]

Definition at line 133 of file kbperf.h.

Referenced by _curDpi(), dpi(), KbPerf(), load(), operator=(), save(), and update().

12.34.5.18 const int KbPerf::HW_I_COUNT = (int)HW_IMAX + 1 [static]

Definition at line 104 of file kbperf.h.

Referenced by KbPerf(), and update().

12.34.5.19 i_hw KbPerf::hwlType[HW_I_COUNT] [private]

Definition at line 153 of file kbperf.h.

Referenced by getIndicator(), KbPerf(), load(), operator=(), save(), setIndicator(), and update().

12.34.5.20 const int KbPerf::I_COUNT = (int)MUTE + 1 [static]

Definition at line 104 of file kbperf.h.

Referenced by getIndicator(), KbPerf(), load(), operator=(), save(), and setIndicator().

12.34.5.21 QColor KbPerf::iColor[I_COUNT][2] [private]

Definition at line 150 of file kbperf.h.

Referenced by applyIndicators(), getIndicator(), KbPerf(), load(), operator=(), save(), and setIndicator().

12.34.5.22 bool KbPerf::iEnable[I_COUNT] [private]

Definition at line 152 of file kbperf.h.

Referenced by applyIndicators(), getIndicator(), KbPerf(), load(), operator=(), save(), and setIndicator().

12.34.5.23 QColor KbPerf::light100Color [private]

Definition at line 151 of file kbperf.h.

Referenced by applyIndicators(), getIndicator(), KbPerf(), load(), operator=(), save(), and setIndicator().

12.34.5.24 QColor KbPerf::muteNAColor [private]

Definition at line 151 of file kbperf.h.

Referenced by applyIndicators(), getIndicator(), KbPerf(), load(), operator=(), save(), and setIndicator().

12.34.5.25 const int KbPerf::OTHER = DPI_COUNT [static]

Definition at line 81 of file kbperf.h.

Referenced by applyIndicators(), MPerfWidget::colorChanged(), load(), save(), and MPerfWidget::setPerf().

12.34.5.26 QMap<quint64, QPoint> KbPerf::pushedDpis [private]

Definition at line 142 of file kbperf.h.

Referenced by curDpi(), KbPerf(), load(), operator=(), popDpi(), pushDpi(), and save().

12.34.5.27 uint KbPerf::runningPushIdx [private]

Definition at line 143 of file kbperf.h.

Referenced by load(), operator=(), and pushDpi().

12.34.5.28 const int KbPerf::SNIPER = 0 [static]

Definition at line 46 of file kbperf.h.

Referenced by dpiDown(), and sniperDpi().

The documentation for this class was generated from the following files:

- src/ckb/kbperf.h
- src/ckb/kbperf.cpp
- src/ckb/release/moc_kbperf.cpp

12.35 KbProfile Class Reference

```
#include <src/ckb/kbprofile.h>
```

Inheritance diagram for KbProfile:

Collaboration diagram for KbProfile:

Public Types

- typedef QList< KbMode * > ModeList

Public Member Functions

- KbProfile (Kb *parent, const KeyMap &keyMap, const KbProfile &other)
- KbProfile (Kb *parent, const KeyMap &keyMap, const QString &guid="", const QString &modified="")
- KbProfile (Kb *parent, const KeyMap &keyMap, CkbSettings &settings, const QString &guid)
- void save (CkbSettings &settings)
- bool needsSave () const
- void setNeedsSave ()
- QString name () const
- void name (const QString &newName)
- UsbId & id ()
- void id (const UsbId &newId)
- void newId ()
- const KeyMap & keyMap () const
- void keyMap (const KeyMap &newKeyMap)
- const ModeList & modes () const
- void modes (const QList< KbMode * > &newModes)
- void append (KbMode *newMode)
- void insert (int index, KbMode *newMode)
- void removeAll (KbMode *mode)
- void move (int from, int to)
- int modeCount () const
- int indexOf (KbMode *mode) const
- KbMode * find (const QUuid &id)
- KbMode * currentMode () const
- void currentMode (KbMode *newCurrentMode)

Private Member Functions

- void setNeedsUpdate ()

Private Attributes

- KbMode * _currentMode
- QString _name
- UsbId _id
- KeyMap _keyMap
- ModeList _modes
- bool _needsSave

12.35.1 Detailed Description

Definition at line 11 of file kbprofile.h.

12.35.2 Member Typedef Documentation

12.35.2.1 typedef QList<KbMode*> KbProfile::ModeList

Definition at line 41 of file kbprofile.h.

12.35.3 Constructor & Destructor Documentation

12.35.3.1 KbProfile::KbProfile (Kb * *parent*, const KeyMap & *keyMap*, const KbProfile & *other*) [explicit]

Definition at line 4 of file kbprofile.cpp.

References _currentMode, _modes, and modes().

```
4                                                                                    :
5     QObject(parent), _currentMode(0), _name(other._name),
      _id(other._id), _keyMap(keyMap), _needsSave(true)
6 {
7     foreach(KbMode* mode, other.modes()){
8         KbMode* newMode = new KbMode(parent, keyMap, *mode);
9         if(!_currentMode || mode == other._currentMode)
10            _currentMode = newMode;
11         _modes.append(newMode);
12     }
13 }
```

Here is the call graph for this function:

12.35.3.2 KbProfile::KbProfile (Kb * *parent*, const KeyMap & *keyMap*, const QString & *guid* = "", const QString & *modified* = "") [explicit]

Definition at line 15 of file kbprofile.cpp.

References _id, and UsbId::guid.

```
15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
16     QObject(parent), _currentMode(0), _id(guid, modified.toUInt(0, 16)),
      _keyMap(keyMap), _needsSave(true)
17 {
18     if(_id.guid.isNull())
19         _id.guid = QUuid::createUuid();
20 }
```

12.35.3.3 KbProfile::KbProfile (Kb * *parent*, const KeyMap & *keyMap*, CkbSettings & *settings*, const QString & *guid*) [explicit]

Definition at line 22 of file kbprofile.cpp.

References _currentMode, _id, _keyMap, _modes, _name, CkbSettings::contains(), UsbId::guid, UsbId::hwModified, UsbId::hwModifiedString(), KbMode::id(), UsbId::modified, UsbId::modifiedString(), and CkbSettings::value().

```
22                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                
23     QObject(parent), _currentMode(0), _id(guid, 0),
      _keyMap(keyMap), _needsSave(false)
24 {
25     // Load data from preferences
26     SGroup group(settings, guid);
27     _name = settings.value("Name").toString().trimmed();
28     if(_name == "")
29         _name = "Unnamed";
30     _id.modifiedString(settings.value("Modified").toString());
31     if(settings.contains("HwModified"))
32         _id.hwModifiedString(settings.value("HwModified").toString());
33     else
34         _id.hwModified = _id.modified;
35     QUuid current = settings.value("CurrentMode").toString().trimmed();
36     // Load modes
37     uint count = settings.value("ModeCount").toUInt();
38     for(uint i = 0; i < count; i++){
39         SGroup group(settings, QString::number(i));
40         KbMode* mode = new KbMode(parent, _keyMap, settings);
41         _modes.append(mode);
42         // Set currentMode to the mode matching the current GUID, or the first mode in case it's not found
43         if(current == mode->id().guid || !_currentMode)
44             _currentMode = mode;
45     }
46 }
```

Here is the call graph for this function:

12.35.4 Member Function Documentation

12.35.4.1 void KbProfile::append (KbMode * *newMode*) [inline]

Definition at line 44 of file kbprofile.h.

References _modes, and setNeedsUpdate().

Referenced by Kb::hwSave(), KbWidget::on_modesList_itemClicked(), KbProfileDialog::profileList_reordered(), Kb::readNotify(), and Kb::setCurrentProfile().

```
44 { setNeedsUpdate(); _modes.append(newMode); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.2 KbMode* KbProfile::currentMode ( ) const [inline]

Definition at line 54 of file kbprofile.h.

References _currentMode.

Referenced by KeyAction::keyEvent(), KbBindWidget::on_copyButton_clicked(), KPerfWidget::on_copyButton_clicked(), MPerfWidget::on_copyButton_clicked(), Kb::setCurrentMode(), and Kb::setCurrentProfile().

```
54 { return _currentMode; }
```

Here is the caller graph for this function:

12.35.4.3 void KbProfile::currentMode (KbMode * *newCurrentMode*) [inline]

Definition at line 55 of file kbprofile.h.

References _currentMode, and _needsSave.

```
55 { _needsSave = true; _currentMode = newCurrentMode; }
```

12.35.4.4 KbMode* KbProfile::find (const QUuid & *id*) [inline]

Definition at line 51 of file kbprofile.h.

References _modes, UsbId::guid, id(), and KbMode::id().

Referenced by KbWidget::modesList_reordered(), and KbWidget::on_modesList_currentItemChanged().

```
51 { foreach(KbMode* mode, _modes) { if(mode->id().guid == id) return mode; } return 0; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.5 UsbId& KbProfile::id ( ) [inline]

Definition at line 30 of file kbprofile.h.

References _id.

Referenced by find(), Kb::find(), Kb::hwSave(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemChanged(), KbProfileDialog::on_profileList_itemClicked(), Kb::readNotify(), KbProfileDialog::repopulate(), Kb::save(), and Kb::writeProfileHeader().

```
30 { return _id; }
```

Here is the caller graph for this function:

12.35.4.6 void KbProfile::id (const UsbId & *newId*) [inline]

Definition at line 31 of file kbprofile.h.

References _id, _needsSave, and newId().

```
31 { _needsSave = true; _id = newId; }
```

Here is the call graph for this function:

12.35.4.7 int KbProfile::indexOf (KbMode * *mode*) const [inline]

Definition at line 50 of file kbprofile.h.

References _modes.

Referenced by Kb::frameUpdate(), KeyAction::keyEvent(), KbWidget::modeChanged(), KbWidget::on_modesList_-customContextMenuRequested(), and Kb::readNotify().

```
50 { return _modes.indexOf(mode); }
```

Here is the caller graph for this function:

12.35.4.8 void KbProfile::insert (int *index*, KbMode * *newMode*) [inline]

Definition at line 45 of file kbprofile.h.

References _modes, and setNeedsUpdate().

Referenced by KbWidget::on_modesList_customContextMenuRequested().

```
45 { setNeedsUpdate(); _modes.insert(index, newMode); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.9 const KeyMap& KbProfile::keyMap ( ) const [inline]

Definition at line 37 of file kbprofile.h.

References _keyMap.

Referenced by KPerfWidget::setPerf(), and Kb::updateLayout().

```
37 { return _keyMap; }
```

Here is the caller graph for this function:

12.35.4.10 void KbProfile::keyMap (const KeyMap & *newKeyMap*)

Definition at line 85 of file kbprofile.cpp.

References _keyMap, _modes, KbMode::keyMap(), and setNeedsUpdate().

```
85                                                  {
86     _keyMap = newKeyMap;
87     foreach(KbMode* mode, _modes)
88         mode->keyMap(newKeyMap);
89     setNeedsUpdate();
90 }
```

Here is the call graph for this function:

12.35.4.11 int KbProfile::modeCount ( ) const [inline]

Definition at line 49 of file kbprofile.h.

References _modes.

Referenced by Kb::hwSave(), KeyAction::keyEvent(), KbWidget::on_modesList_customContextMenuRequested(), Kb::readNotify(), save(), and Kb::setCurrentProfile().

```
49 { return _modes.count(); }
```

Here is the caller graph for this function:

12.35.4.12 const ModeList& KbProfile::modes ( ) const [inline]

Definition at line 42 of file kbprofile.h.

References _modes.

Referenced by Kb::hwSave(), KbProfile(), KeyAction::keyEvent(), KbWidget::modesList_reordered(), KbBindWidget::on_copyButton_clicked(), KPerfWidget::on_copyButton_clicked(), MPerfWidget::on_copyButton_clicked(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::profileChanged(), Kb::readNotify(), RebindWidget::setBind(), Kb::setCurrentMode(), Kb::setCurrentProfile(), and Kb::updateLayout().

```
42 { return _modes; }
```

Here is the caller graph for this function:

12.35.4.13 void KbProfile::modes (const QList< KbMode * > & *newModes*) [inline]

Definition at line 43 of file kbprofile.h.

References _modes, and setNeedsUpdate().

```
43 { setNeedsUpdate(); _modes = newModes; }
```

Here is the call graph for this function:

12.35.4.14 void KbProfile::move (int *from*, int *to*) [inline]

Definition at line 47 of file kbprofile.h.

References _modes, and setNeedsUpdate().

Referenced by Kb::readNotify().

```
47 { setNeedsUpdate(); _modes.move(from, to); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.15 QString KbProfile::name ( ) const [inline]

Definition at line 28 of file kbprofile.h.

References _name.

Referenced by KbProfileDialog::on_profileList_itemChanged(), Kb::readNotify(), KbProfileDialog::repopulate(), save(), KbWidget::updateProfileList(), and Kb::writeProfileHeader().

```
28 { return _name; }
```

Here is the caller graph for this function:

12.35.4.16 void KbProfile::name (const QString & *newName*) [inline]

Definition at line 29 of file kbprofile.h.

References _name, and _needsSave.

```
29 { _needsSave = true; _name = newName.trimmed(); if(_name == "")
     _name = "Unnamed"; }
```

12.35.4.17 bool KbProfile::needsSave ( ) const

Definition at line 68 of file kbprofile.cpp.

References _modes, _needsSave, and KbMode::needsSave().

Referenced by Kb::needsSave().

```
68                                  {
69      if(_needsSave)
70          return true;
71      foreach(KbMode* mode, _modes){
72          if(mode->needsSave())
73              return true;
74      }
75      return false;
76  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.18 void KbProfile::newId ( )

Definition at line 78 of file kbprofile.cpp.

References _id, _modes, _needsSave, and KbMode::newId().

Referenced by id(), and KbProfileDialog::on_profileList_customContextMenuRequested().

```
78                          {
79      _needsSave = true;
80      _id = UsbId();
81      foreach(KbMode* mode, _modes)
82          mode->newId();
83  }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.19 void KbProfile::removeAll (KbMode * *mode*) [inline]

Definition at line 46 of file kbprofile.h.

References _modes, and setNeedsUpdate().

Referenced by KbWidget::on_modesList_customContextMenuRequested(), and KbProfileDialog::on_profileList_-customContextMenuRequested().

```
46 { setNeedsUpdate(); _modes.removeAll(mode); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.20 void KbProfile::save (CkbSettings & *settings*)

Definition at line 48 of file kbprofile.cpp.

References _currentMode, _id, _modes, _needsSave, UsbId::guidString(), UsbId::hwModifiedString(), KbMode::id(), modeCount(), UsbId::modifiedString(), name(), UsbId::newModified(), KbMode::save(), and CkbSettings::setValue().

Referenced by Kb::save().

```
48                                          {
49     _needsSave = false;
50     _id.newModified();
51     // Save data to preferences
52     SGroup group(settings, id().guidString());
53     settings.setValue("Name", name());
54     settings.setValue("Modified", _id.modifiedString());
55     settings.setValue("HwModified", _id.hwModifiedString());
56     if(_currentMode)
57         settings.setValue("CurrentMode", _currentMode->id().
      guidString());
58     // Save modes
59     uint count = modeCount();
60     settings.setValue("ModeCount", count);
61     for(uint i = 0; i < count; i++){
62         SGroup group(settings, QString::number(i));
63         KbMode* mode = _modes.at(i);
64         mode->save(settings);
65     }
66 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.4.21 void KbProfile::setNeedsSave ( ) [inline]

Definition at line 25 of file kbprofile.h.

References _needsSave.

Referenced by Kb::hwSave(), Kb::readNotify(), and setNeedsUpdate().

```
25 { _needsSave = true; }
```

Here is the caller graph for this function:

12.35.4.22 void KbProfile::setNeedsUpdate ( ) [inline],[private]

Definition at line 66 of file kbprofile.h.

References _modes, setNeedsSave(), and KbMode::setNeedsUpdate().

Referenced by append(), insert(), keyMap(), modes(), move(), and removeAll().

```
66 { setNeedsSave(); foreach(KbMode* mode, _modes){ mode->
     setNeedsUpdate(); } }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.35.5 Field Documentation

12.35.5.1 KbMode* KbProfile::_currentMode [private]

Definition at line 58 of file kbprofile.h.

Referenced by currentMode(), KbProfile(), and save().

12.35.5.2 UsbId KbProfile::_id [private]

Definition at line 60 of file kbprofile.h.

Referenced by id(), KbProfile(), newId(), and save().

12.35.5.3 KeyMap KbProfile::_keyMap [private]

Definition at line 61 of file kbprofile.h.

Referenced by KbProfile(), and keyMap().

12.35.5.4 ModeList KbProfile::_modes [private]

Definition at line 62 of file kbprofile.h.

Referenced by append(), find(), indexOf(), insert(), KbProfile(), keyMap(), modeCount(), modes(), move(), needsSave(), newId(), removeAll(), save(), and setNeedsUpdate().

12.35.5.5 QString KbProfile::_name [private]

Definition at line 59 of file kbprofile.h.

Referenced by KbProfile(), and name().

12.35.5.6 bool KbProfile::_needsSave [private]

Definition at line 63 of file kbprofile.h.

Referenced by currentMode(), id(), name(), needsSave(), newId(), save(), and setNeedsSave().

The documentation for this class was generated from the following files:

- src/ckb/kbprofile.h
- src/ckb/kbprofile.cpp

12.36 KbProfileDialog Class Reference

```
#include <src/ckb/kbprofiledialog.h>
```

Inheritance diagram for KbProfileDialog:

Collaboration diagram for KbProfileDialog:

Public Member Functions

- KbProfileDialog (KbWidget ∗parent=0)
- ∼KbProfileDialog ()

Private Slots

- void profileList_reordered ()
- void on_profileList_currentItemChanged (QListWidgetItem ∗current, QListWidgetItem ∗previous)
- void on_profileList_itemClicked (QListWidgetItem ∗item)
- void on_profileList_itemChanged (QListWidgetItem ∗item)
- void on_profileList_customContextMenuRequested (const QPoint &pos)

Private Member Functions

- void repopulate ()
- void addNewProfileItem ()

Private Attributes

- Ui::KbProfileDialog ∗ ui
- Kb ∗ device

Static Private Attributes

- static const int GUID = Qt::UserRole
- static const int NEW_FLAG = Qt::UserRole + 1

12.36.1 Detailed Description

Definition at line 11 of file kbprofiledialog.h.

12.36.2 Constructor & Destructor Documentation

12.36.2.1 KbProfileDialog::KbProfileDialog (KbWidget * *parent* = 0) [explicit]

Definition at line 5 of file kbprofiledialog.cpp.

References Ui_KbProfileDialog::profileList, profileList_reordered(), repopulate(), Ui_KbProfileDialog::setupUi(), and ui.

```
5                                                   :
6     QDialog(parent),
7     ui(new Ui::KbProfileDialog), device(parent->
      device)
8 {
9     ui->setupUi(this);
10     connect(ui->profileList, SIGNAL(orderChanged()), this, SLOT(
      profileList_reordered()));
11
12     // Populate profile list
13     repopulate();
14 }
```

Here is the call graph for this function:

12.36.2.2 KbProfileDialog::~KbProfileDialog ( )

Definition at line 16 of file kbprofiledialog.cpp.

References ui.

```
16                                      {
17     delete ui;
18 }
```

12.36.3 Member Function Documentation

12.36.3.1 void KbProfileDialog::addNewProfileItem ( ) [private]

Definition at line 66 of file kbprofiledialog.cpp.

References NEW_FLAG, Ui_KbProfileDialog::profileList, and ui.

Referenced by on_profileList_itemClicked(), and repopulate().

```
66                                          {
67     // Add an item for creating a new profile. Make it editable but not dragable.
68     QListWidgetItem* item = new QListWidgetItem("New profile...", ui->
      profileList);
69     item->setFlags((item->flags() | Qt::ItemIsEditable) & ~Qt::ItemIsDragEnabled & ~Qt::ItemIsDropEnabled);
70     item->setData(NEW_FLAG, 1);
```

```
    QFont font = item->font();
    font.setItalic(true);
    item->setFont(font);
    item->setIcon(QIcon(":/img/icon_plus.png"));
    ui->profileList->addItem(item);
}
```

Here is the caller graph for this function:

12.36.3.2 void KbProfileDialog::on_profileList_currentItemChanged (QListWidgetItem * *current*, QListWidgetItem * *previous*) [private],[slot]

Definition at line 39 of file kbprofiledialog.cpp.

References device, Kb::find(), GUID, and Kb::setCurrentProfile().

```
39                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                {
40     if(!current)
41         return;
42     KbProfile* profile = device->find(current->data(GUID).toUuid());
43     if(!profile)
44         return;
45     device->setCurrentProfile(profile);
46 }
```

Here is the call graph for this function:

12.36.3.3 void KbProfileDialog::on_profileList_customContextMenuRequested (const QPoint & *pos*) [private],[slot]

Definition at line 109 of file kbprofiledialog.cpp.

References Kb::currentProfile(), device, Kb::find(), UsbId::guid, GUID, Kb::hwProfile(), Kb::hwSave(), KbProfile::id(), Kb::indexOf(), NEW_FLAG, KbProfile::newId(), Kb::newProfile(), Ui_KbProfileDialog::profileList, Kb::profiles(), KbProfile::removeAll(), repopulate(), Kb::setCurrentProfile(), and ui.

```
109                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                {
```

```
    QListWidgetItem* item = ui->profileList->itemAt(pos);
    KbProfile* currentProfile = device->currentProfile();
    if(!item || !currentProfile || item->data(GUID).toUuid() != currentProfile->id().guid)
        return;
    int index = device->indexOf(currentProfile);
    QList<KbProfile*> profiles = device->profiles();

    QMenu menu(this);
    QAction* rename = new QAction("Rename...", this);
    QAction* duplicate = new QAction("Duplicate", this);
    QAction* del = new QAction("Delete", this);
    bool canDelete = (profiles.count() > 1);
    if(!canDelete)
        // Can't delete the last profile on the device
        del->setEnabled(false);
    QAction* hwsave = new QAction("Save to Hardware", this);
    QAction* moveup = new QAction("Move Up", this);
    if(index == 0)
        moveup->setEnabled(false);
    QAction* movedown = new QAction("Move Down", this);
    if(index >= profiles.count() - 1)
        movedown->setEnabled(false);
    menu.addAction(rename);
    menu.addAction(duplicate);
    menu.addAction(del);
    menu.addSeparator();
    menu.addAction(hwsave);
    menu.addSeparator();
    menu.addAction(moveup);
    menu.addAction(movedown);
    QAction* result = menu.exec(QCursor::pos());
    if(result == rename){
        ui->profileList->editItem(item);
    } else if(result == duplicate){
        KbProfile* newProfile = device->newProfile(currentProfile);
        newProfile->newId();
        profiles.insert(index + 1, newProfile);
        device->profiles(profiles);
        device->setCurrentProfile(newProfile);
    } else if(result == del){
        if(!canDelete)
            return;
        profiles.removeAll(currentProfile);
        device->profiles(profiles);
        currentProfile->deleteLater();
        // Select next profile
        if(index < profiles.count())
            device->setCurrentProfile(profiles.at(index));
        else
            device->setCurrentProfile(profiles.last());
    } else if(result == hwsave){
        device->hwSave();
        // Refresh item icons
        int count = ui->profileList->count();
        for(int i = 0; i < count; i++){
            QListWidgetItem* item = ui->profileList->item(i);
            if(item->data(NEW_FLAG).toUInt() == 1)
                continue;
            KbProfile* profile = device->find(item->data(GUID).toUuid());
            item->setIcon(QIcon((profile == device->hwProfile()) ? ":/img/icon_profile_hardware.png" : ":/img/icon_profile.png"));
        }
    } else if(result == moveup){
        profiles.removeAll(currentProfile);
        profiles.insert(index - 1, currentProfile);
        device->profiles(profiles);
    } else if(result == movedown){
        profiles.removeAll(currentProfile);
        profiles.insert(index + 1, currentProfile);
        device->profiles(profiles);
    }
    repopulate();
}
```

Here is the call graph for this function:

12.36.3.4 void KbProfileDialog::on_profileList_itemChanged (QListWidgetItem * *item*) [private],[slot]

Definition at line 100 of file kbprofiledialog.cpp.

References Kb::currentProfile(), device, UsbId::guid, GUID, KbProfile::id(), and KbProfile::name().

```
100                                                                 {
101     KbProfile* currentProfile = device->currentProfile();
102     if(!item || !currentProfile || item->data(GUID).toUuid() != currentProfile->
      id().guid)
103         return;
104     currentProfile->name(item->text());
105     // Set the text to the actual name (trimmed, "" replaced with "Unnamed")
106     item->setText(currentProfile->name());
107 }
```

Here is the call graph for this function:

12.36.3.5 void KbProfileDialog::on_profileList_itemClicked (QListWidgetItem * *item*) [private],[slot]

Definition at line 78 of file kbprofiledialog.cpp.

References addNewProfileItem(), Kb::appendProfile(), device, UsbId::guid, GUID, KbProfile::id(), NEW_FLAG, Kb::newProfile(), Ui_KbProfileDialog::profileList, Kb::setCurrentProfile(), and ui.

```
78                                                                  {
79     QUuid guid = item->data(GUID).toUuid();
80     if(guid.isNull() && item->data(NEW_FLAG).toInt() == 1){
81         // New profile
82         item->setText("");
83         ui->profileList->editItem(item);
84         item->setFlags(item->flags() | Qt::ItemIsEditable | Qt::ItemIsDragEnabled | Qt::ItemIsDropEnabled);
85         QFont font = item->font();
86         font.setItalic(false);
87         item->setFont(font);
88         item->setIcon(QIcon(":/img/icon_profile.png"));
89         // Add the new profile and assign it to this item
90         KbProfile* newProfile = device->newProfile();
91         device->appendProfile(newProfile);
92         item->setData(GUID, newProfile->id().guid);
93         item->setData(NEW_FLAG, 0);
94         device->setCurrentProfile(newProfile);
95         // Create another "new profile" item to replace this one
96         addNewProfileItem();
97     }
98 }
```

Here is the call graph for this function:

12.36.3.6 void KbProfileDialog::profileList_reordered ( ) [private],[slot]

Definition at line 20 of file kbprofiledialog.cpp.

References KbProfile::append(), device, Kb::find(), GUID, Ui_KbProfileDialog::profileList, Kb::profiles(), and ui.

Referenced by KbProfileDialog().

```
20                                          {
21     // Rebuild profile list from items
22     QList<KbProfile*> newProfiles;
23     int count = ui->profileList->count();
24     for(int i = 0; i < count; i++){
25         QListWidgetItem* item = ui->profileList->item(i);
26         KbProfile* profile = device->find(item->data(GUID).toUuid());
27         if(profile && !newProfiles.contains(profile))
28             newProfiles.append(profile);
29         item->setFlags(item->flags() | Qt::ItemIsEditable);
30     }
31     // Add any missing profiles at the end of the list
32     foreach(KbProfile* profile, device->profiles()){
33         if(!newProfiles.contains(profile))
34             newProfiles.append(profile);
35     }
36     device->profiles(newProfiles);
37 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.36.3.7 void KbProfileDialog::repopulate ( ) [private]

Definition at line 48 of file kbprofiledialog.cpp.

References addNewProfileItem(), Kb::currentProfile(), device, UsbId::guid, GUID, Kb::hwProfile(), KbProfile::id(), KbProfile::name(), Ui_KbProfileDialog::profileList, Kb::profiles(), and ui.

Referenced by KbProfileDialog(), and on_profileList_customContextMenuRequested().

```
48                                          {
49     ui->profileList->clear();
50     QListWidgetItem* current = 0;
51     foreach(KbProfile* profile, device->profiles()){
52         QListWidgetItem* item = new QListWidgetItem(QIcon((profile == device->
      hwProfile()) ? ":/img/icon_profile_hardware.png" : ":/img/icon_profile.png"), profile->
```

```
    name(), ui->profileList);
        item->setData(GUID, profile->id().guid);
        item->setFlags(item->flags() | Qt::ItemIsEditable);
        if(profile == device->currentProfile()){
            item->setSelected(true);
            current = item;
        }
        ui->profileList->addItem(item);
    }
    if(current)
        ui->profileList->setCurrentItem(current);
    addNewProfileItem();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.36.4 Field Documentation

12.36.4.1 Kb* KbProfileDialog::device [private]

Definition at line 29 of file kbprofiledialog.h.

Referenced by on_profileList_currentItemChanged(), on_profileList_customContextMenuRequested(), on_profileList_itemChanged(), on_profileList_itemClicked(), profileList_reordered(), and repopulate().

12.36.4.2 const int KbProfileDialog::GUID = Qt::UserRole [static], [private]

Definition at line 30 of file kbprofiledialog.h.

Referenced by on_profileList_currentItemChanged(), on_profileList_customContextMenuRequested(), on_profileList_itemChanged(), on_profileList_itemClicked(), profileList_reordered(), and repopulate().

12.36.4.3 const int KbProfileDialog::NEW_FLAG = Qt::UserRole + 1 [static], [private]

Definition at line 31 of file kbprofiledialog.h.

Referenced by addNewProfileItem(), on_profileList_customContextMenuRequested(), and on_profileList_itemClicked().

12.36.4.4 Ui::KbProfileDialog* KbProfileDialog::ui [private]

Definition at line 27 of file kbprofiledialog.h.

Referenced by addNewProfileItem(), KbProfileDialog(), on_profileList_customContextMenuRequested(), on_profileList_itemClicked(), profileList_reordered(), repopulate(), and ~KbProfileDialog().

The documentation for this class was generated from the following files:

- src/ckb/kbprofiledialog.h
- src/ckb/kbprofiledialog.cpp

12.37 Ui::KbProfileDialog Class Reference

```
#include <src/ckb/ui_kbprofiledialog.h>
```

Inheritance diagram for Ui::KbProfileDialog:

Collaboration diagram for Ui::KbProfileDialog:

Public Member Functions

- void setupUi (QDialog *KbProfileDialog)
- void retranslateUi (QDialog *KbProfileDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer
- QSpacerItem * horizontalSpacer_2
- RListWidget * profileList
- QDialogButtonBox * buttonBox

12.37.1 Detailed Description

Definition at line 81 of file ui_kbprofiledialog.h.

12.37.2 Member Function Documentation

12.37.2.1 void Ui_KbProfileDialog::retranslateUi (QDialog * *KbProfileDialog*) [inline],[inherited]

Definition at line 73 of file ui_kbprofiledialog.h.

Referenced by Ui_KbProfileDialog::setupUi().

```
74     {
75         KbProfileDialog->setWindowTitle(QApplication::translate("KbProfileDialog", "Keyboard Profiles",
       Q_NULLPTR));
76     } // retranslateUi
```

Here is the caller graph for this function:

12.37.2.2 void Ui_KbProfileDialog::setupUi (QDialog * *KbProfileDialog*) [inline],[inherited]

Definition at line 34 of file ui_kbprofiledialog.h.

References Ui_KbProfileDialog::buttonBox, Ui_KbProfileDialog::gridLayout, Ui_KbProfileDialog::horizontalSpacer, Ui_KbProfileDialog::horizontalSpacer_2, Ui_KbProfileDialog::profileList, and Ui_KbProfileDialog::retranslateUi().

Referenced by KbProfileDialog::KbProfileDialog().

```
35     {
36         if (KbProfileDialog->objectName().isEmpty())
37             KbProfileDialog->setObjectName(QStringLiteral("KbProfileDialog"));
38         KbProfileDialog->resize(400, 300);
39         KbProfileDialog->setFocusPolicy(Qt::ClickFocus);
40         gridLayout = new QGridLayout(KbProfileDialog);
41         gridLayout->setObjectName(QStringLiteral("gridLayout"));
42         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
       QSizePolicy::Minimum);
43
44         gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);
45
46         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
       QSizePolicy::Minimum);
47
48         gridLayout->addItem(horizontalSpacer_2, 0, 2, 1, 1);
49
50         profileList = new RListWidget(KbProfileDialog);
51         profileList->setObjectName(QStringLiteral("profileList"));
52         profileList->setContextMenuPolicy(Qt::CustomContextMenu);
53         profileList->setFrameShadow(QFrame::Plain);
54         profileList->setIconSize(QSize(24, 24));
55
56         gridLayout->addWidget(profileList, 0, 1, 1, 1);
57
58         buttonBox = new QDialogButtonBox(KbProfileDialog);
59         buttonBox->setObjectName(QStringLiteral("buttonBox"));
60         buttonBox->setOrientation(Qt::Horizontal);
61         buttonBox->setStandardButtons(QDialogButtonBox::Ok);
62
63         gridLayout->addWidget(buttonBox, 1, 0, 1, 3);
64
65
66         retranslateUi(KbProfileDialog);
67         QObject::connect(buttonBox, SIGNAL(accepted()), KbProfileDialog, SLOT(accept()));
68         QObject::connect(buttonBox, SIGNAL(rejected()), KbProfileDialog, SLOT(reject()));
69
70         QMetaObject::connectSlotsByName(KbProfileDialog);
71     } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.37.3 Field Documentation

12.37.3.1 QDialogButtonBox* Ui_KbProfileDialog::buttonBox [inherited]

Definition at line 32 of file ui_kbprofiledialog.h.

Referenced by Ui_KbProfileDialog::setupUi().

12.37.3.2 QGridLayout* Ui_KbProfileDialog::gridLayout [inherited]

Definition at line 28 of file ui_kbprofiledialog.h.

Referenced by Ui_KbProfileDialog::setupUi().

12.37.3.3 QSpacerItem* Ui_KbProfileDialog::horizontalSpacer [inherited]

Definition at line 29 of file ui_kbprofiledialog.h.

Referenced by Ui_KbProfileDialog::setupUi().

12.37.3.4 QSpacerItem* Ui_KbProfileDialog::horizontalSpacer_2 [inherited]

Definition at line 30 of file ui_kbprofiledialog.h.

Referenced by Ui_KbProfileDialog::setupUi().

12.37.3.5 RListWidget* Ui_KbProfileDialog::profileList [inherited]

Definition at line 31 of file ui_kbprofiledialog.h.

Referenced by KbProfileDialog::addNewProfileItem(), KbProfileDialog::KbProfileDialog(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemClicked(), KbProfileDialog::profileList_reordered(), KbProfileDialog::repopulate(), and Ui_KbProfileDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbprofiledialog.h

12.38 KbWidget Class Reference

```
#include <src/ckb/kbwidget.h>
```

Inheritance diagram for KbWidget:

Collaboration diagram for KbWidget:

Public Slots

- void showFirstTab ()
- void showLastTab ()
- void showFwUpdate ()

Public Member Functions

- KbWidget (QWidget ∗parent, Kb ∗_device)
- ∼KbWidget ()
- QString name () const
- void updateFwButton ()

Data Fields

- Kb ∗ device
- bool hasShownNewFW

Private Slots

- void updateProfileList ()
- void profileChanged ()
- void on_profileBox_activated (int index)
- QIcon modeIcon (int i)
- void addNewModeItem ()
- void modeChanged (bool spontaneous=true)
- void on_modesList_currentItemChanged (QListWidgetItem ∗current, QListWidgetItem ∗previous)
- void modesList_reordered ()
- void on_modesList_itemChanged (QListWidgetItem ∗item)
- void on_modesList_itemClicked (QListWidgetItem ∗item)
- void on_modesList_customContextMenuRequested (const QPoint &pos)

  KbWidget::on_modesList_customContextMenuRequested.
- void devUpdate ()
- void modeUpdate ()
- void on_hwSaveButton_clicked ()
- void on_tabWidget_currentChanged (int index)
- void on_fwUpdButton_clicked ()

Private Attributes

- Ui::KbWidget ∗ ui
- quint64 lastAutoSave
- KbMode ∗ currentMode

Static Private Attributes

- static const int GUID = Qt::UserRole
- static const int NEW_FLAG = Qt::UserRole + 1

12.38.1 Detailed Description

Definition at line 15 of file kbwidget.h.

12.38.2 Constructor & Destructor Documentation

12.38.2.1 KbWidget::KbWidget (QWidget ∗ *parent*, Kb ∗ *_device*) [explicit]

Definition at line 15 of file kbwidget.cpp.

References device, devUpdate(), Kb::features, Ui_KbWidget::fwUpdButton, Ui_KbWidget::fwUpdLabel, Ui_KbWidget::fwUpdLayout, Kb::isKeyboard(), Kb::isMouse(), Ui_KbWidget::kPerfTab, Ui_KbWidget::lightTab, Ui_KbWidget::lightWidget, modeChanged(), Ui_KbWidget::modesList, modesList_reordered(), Kb::monochrome, Ui_KbWidget::mPerfTab, Ui_KbWidget::pollLabel, Ui_KbWidget::pollLabel2, profileChanged(), KbLightWidget::setMonochrome(), Ui_KbWidget::setupUi(), Ui_KbWidget::tabWidget, ui, and updateProfileList().

```
15                                                  :
16     QWidget(parent),
17     device(_device), hasShownNewFW(false),
18     ui(new Ui::KbWidget),
19     currentMode(0)
20 {
21     ui->setupUi(this);
22     connect(ui->modesList, SIGNAL(orderChanged()), this, SLOT(
       modesList_reordered()));
23
```

```
    connect(device, SIGNAL(infoUpdated()), this, SLOT(devUpdate()));
    connect(device, SIGNAL(profileAdded()), this, SLOT(updateProfileList()));
    connect(device, SIGNAL(profileChanged()), this, SLOT(profileChanged()));
    connect(device, SIGNAL(profileRenamed()), this, SLOT(updateProfileList()));
    connect(device, SIGNAL(modeRenamed()), this, SLOT(profileChanged()));
    connect(device, SIGNAL(modeRenamed()), this, SLOT(modeChanged()));
    connect(device, SIGNAL(modeChanged(bool)), this, SLOT(modeChanged(bool)));

    // Remove the Lighting and Performance tabs from non-RGB keyboards
    if(!device->features.contains("rgb")){
        ui->tabWidget->removeTab(ui->tabWidget->indexOf(ui->lightTab));
        ui->tabWidget->removeTab(ui->tabWidget->indexOf(ui->kPerfTab));
        ui->tabWidget->removeTab(ui->tabWidget->indexOf(ui->mPerfTab));
    } else {
        // Remove mouse Performance tab from non-mice
        if(!device->isMouse())
            ui->tabWidget->removeTab(ui->tabWidget->indexOf(ui->mPerfTab));
        // Remove keyboard Performance tab from non-keyboards
        if(!device->isKeyboard())
            ui->tabWidget->removeTab(ui->tabWidget->indexOf(ui->kPerfTab));
    }
    // Hide poll rate and FW update as appropriate
    if(!device->features.contains("pollrate")){
        ui->pollLabel->hide();
        ui->pollLabel2->hide();
    }
    if(!device->features.contains("fwupdate")){
        ui->fwUpdButton->hide();
        ui->fwUpdLabel->hide();
        ui->fwUpdLayout->removeItem(ui->fwUpdLayout->itemAt(1));
    }
    // Set monochrome mode according to hardware
    if(device->monochrome)
        ui->lightWidget->setMonochrome();
}
```

Here is the call graph for this function:

12.38.2.2 KbWidget::~KbWidget ( )

Definition at line 60 of file kbwidget.cpp.

References ui.

```
60                  {
61      delete ui;
62  }
```

12.38.3 Member Function Documentation

12.38.3.1 void KbWidget::addNewModeItem ( ) [private],[slot]

Definition at line 136 of file kbwidget.cpp.

References Ui_KbWidget::modesList, NEW_FLAG, and ui.

Referenced by on_modesList_itemClicked(), and profileChanged().

```
                                {
    // Add an item for creating a new mode. Make it editable but not dragable.
    QListWidgetItem* item = new QListWidgetItem("New mode...", ui->modesList);
    item->setFlags((item->flags() | Qt::ItemIsEditable) & ~Qt::ItemIsDragEnabled & ~Qt::ItemIsDropEnabled);
    item->setData(NEW_FLAG, 1);
    QFont font = item->font();
    font.setItalic(true);
    item->setFont(font);
    item->setIcon(QIcon(":/img/icon_plus.png"));
    ui->modesList->addItem(item);
}
```

Here is the caller graph for this function:

12.38.3.2 void KbWidget::devUpdate ( ) [private],[slot]

Definition at line 300 of file kbwidget.cpp.

References device, Kb::firmware, Ui_KbWidget::fwLabel, Ui_KbWidget::pollLabel, Kb::pollrate, Ui_KbWidget::serialLabel, ui, and Kb::usbSerial.

Referenced by KbWidget().

```
                        {
    // Update device tab
    ui->serialLabel->setText(device->usbSerial);
    ui->fwLabel->setText(device->firmware);
    ui->pollLabel->setText(device->pollrate);
}
```

Here is the caller graph for this function:

12.38.3.3 void KbWidget::modeChanged (bool *spontaneous* = true) [private],[slot]

Definition at line 148 of file kbwidget.cpp.

References Ui_KbWidget::bindWidget, Kb::currentBind(), Kb::currentLight(), currentMode, Kb::currentMode(), Kb::currentPerf(), Kb::currentProfile(), device, KbProfile::indexOf(), Ui_KbWidget::kPerfWidget, Ui_KbWidget::lightWidget, Ui_KbWidget::modesList, modeUpdate(), Ui_KbWidget::mPerfWidget, KbBindWidget::setBind(), KbLightWidget::setLight(), KPerfWidget::setPerf(), MPerfWidget::setPerf(), and ui.

Referenced by KbWidget(), and on_modesList_customContextMenuRequested().

```
                                        {
    int index = device->currentProfile()->indexOf(device->currentMode());
    if(index < 0)
        return;
    // Update tabs
    ui->lightWidget->setLight(device->currentLight());
    ui->bindWidget->setBind(device->currentBind(), device->currentProfile());
    ui->kPerfWidget->setPerf(device->currentPerf(), device->currentProfile());
    ui->mPerfWidget->setPerf(device->currentPerf(), device->currentProfile());
    // Update selection
    if(spontaneous)
        ui->modesList->setCurrentRow(index);
    // Connect signals
    if(currentMode)
        disconnect(currentMode, SIGNAL(updated()), this, SLOT(modeUpdate()));
    currentMode = device->currentMode();
    connect(currentMode, SIGNAL(updated()), this, SLOT(modeUpdate()));
    modeUpdate();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.4 QIcon KbWidget::modeIcon (int *i*) [private],[slot]

Definition at line 127 of file kbwidget.cpp.

References Kb::currentProfile(), device, Kb::hwModeCount, and Kb::hwProfile().

Referenced by modesList_reordered(), and profileChanged().

```
127                                 {
128     KbProfile* currentProfile = device->currentProfile(), *hwProfile =
      device->hwProfile();
129     int hwModeCount = device->hwModeCount;
130     if(i >= hwModeCount)
131         return QIcon(":/img/icon_mode.png");
132     else
133         return QIcon(QString(currentProfile == hwProfile ? ":/img/icon_mode%1_hardware.png" : "
      :/img/icon_mode%1.png").arg(i + 1));
134 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.5 void KbWidget::modesList_reordered ( ) [private],[slot]

Definition at line 177 of file kbwidget.cpp.

References Kb::currentProfile(), device, KbProfile::find(), GUID, modeIcon(), KbProfile::modes(), Ui_KbWidget::modesList, NEW_FLAG, and ui.

Referenced by KbWidget().

```
177                                 {
178     KbProfile* currentProfile = device->currentProfile();
179     // Rebuild mode list from items
180     QList<KbMode*> newModes;
181     int count = ui->modesList->count();
182     for(int i = 0; i < count; i++){
183         QListWidgetItem* item = ui->modesList->item(i);
184         KbMode* mode = currentProfile->find(item->data(GUID).toUuid());
185         if(mode && !newModes.contains(mode))
186             newModes.append(mode);
187         if(item->data(NEW_FLAG).toInt() != 1)
188             item->setIcon(modeIcon(i));
189         item->setFlags(item->flags() | Qt::ItemIsEditable);
190     }
191     // Add any missing modes at the end of the list
192     foreach(KbMode* mode, currentProfile->modes()){
193         if(!newModes.contains(mode))
194             newModes.append(mode);
195     }
196     currentProfile->modes(newModes);
197 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.6 void KbWidget::modeUpdate ( ) [private],[slot]

Definition at line 307 of file kbwidget.cpp.

Referenced by modeChanged().

```
307                         {
308 }
```

Here is the caller graph for this function:

12.38.3.7 QString KbWidget::name ( ) const [inline]

Definition at line 25 of file kbwidget.h.

References device, and Kb::usbModel.

Referenced by MainWindow::addDevice().

```
25 { return device->usbModel; }
```

Here is the caller graph for this function:

12.38.3.8 void KbWidget::on_fwUpdButton_clicked ( ) [private],[slot]

Definition at line 339 of file kbwidget.cpp.

References device, FwUpgradeDialog::exec(), Kb::features, Kb::firmware, Ui_KbWidget::fwUpdButton, KbFirmware::hasDownloaded(), ui, updateFwButton(), and KbFirmware::versionForBoard().

Referenced by showFwUpdate().

```
339                                     {
340     // If alt is pressed, ignore upgrades and go straight to the manual prompt
341     if(!(qApp->keyboardModifiers() & Qt::AltModifier)){
342         // Check version numbers
343         if(!KbFirmware::hasDownloaded()){
344             ui->fwUpdButton->setText("Checking...");
345             ui->fwUpdButton->setEnabled(false);
346         }
347         float newVersion = KbFirmware::versionForBoard(
      device->features, true);
348         float oldVersion = device->firmware.toFloat();
349         ui->fwUpdButton->setEnabled(true);
350         updateFwButton();
351         if(newVersion == -1.f){
352             QMessageBox::information(this, "Firmware update", "<center>There is a new firmware available
      for this device.<br />However, it requires a newer version of ckb.<br />Please upgrade ckb and try
      again.</center>");
353             return;
354         } else if(newVersion == 0.f){
355             if(QMessageBox::question(this, "Firmware update", "<center>There was a problem getting the
      status for this device.<br />Would you like to select a file manually?</center>") != QMessageBox::Yes)
356                 return;
357             // "Yes" -> fall through to browse file
358         } else if(newVersion <= oldVersion){
359             if(QMessageBox::question(this, "Firmware update", "<center>Your firmware is already up to
      date.<br />Would you like to select a file manually?</center>") != QMessageBox::Yes)
360                 return;
361             // "Yes" -> fall through to browse file
362         } else {
363             // Automatic upgrade. Fetch file from web.
364             // FwUpgradeDialog can't be parented to KbWidget because KbWidget may be deleted before the
      dialog exits
365             FwUpgradeDialog dialog(parentWidget(), newVersion, "",
      device);
366             dialog.exec();
367             return;
368         }
369     }
370     // Browse for file
371     QString path = QFileDialog::getOpenFileName(this, "Select firmware file",
      QStandardPaths::writableLocation(QStandardPaths::DownloadLocation), "Firmware blobs (*.bin)");
372     if(path.isEmpty())
373         return;
374     QFile file(path);
375     if(!file.open(QIODevice::ReadOnly)){
376         QMessageBox::warning(parentWidget(), "Error", "<center>File could not be read.</center>");
377         return;
378     }
379     QByteArray blob = file.readAll();
380     FwUpgradeDialog dialog(parentWidget(), 0.f, blob, device);
381     dialog.exec();
382 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.9 void KbWidget::on_hwSaveButton_clicked ( ) [private],[slot]

Definition at line 310 of file kbwidget.cpp.

References device, Kb::hwSave(), profileChanged(), Kb::save(), and updateProfileList().

```
310                                         {
311     device->save();
312     device->hwSave();
313     updateProfileList();
314     profileChanged();
315 }
```

Here is the call graph for this function:

12.38.3.10 void KbWidget::on_modesList_currentItemChanged (QListWidgetItem * *current*, QListWidgetItem * *previous*) [private],[slot]

Definition at line 168 of file kbwidget.cpp.

References Kb::currentProfile(), device, KbProfile::find(), GUID, and Kb::setCurrentMode().

```
168                                                                                                                                {
169     if(!current)
170         return;
171     KbMode* mode = device->currentProfile()->find(current->data(
      GUID).toUuid());
172     if(!mode)
173         return;
174     device->setCurrentMode(mode, false);
175 }
```

Here is the call graph for this function:

12.38.3.11 void KbWidget::on_modesList_customContextMenuRequested (const QPoint & *pos*) [private], [slot]

Parameters

pos	Opens on right click in the profiles list a context sensitive menue at position pos.

When clicking on a command it is located and executed.

Definition at line 236 of file kbwidget.cpp.

References currentMode, Kb::currentProfile(), device, UsbId::guid, GUID, Kb::hwModeCount, KbMode::id(), KbProfile::indexOf(), KbProfile::insert(), modeChanged(), KbProfile::modeCount(), KbProfile::modes(), Ui_KbWidget::modesList, KbMode::newId(), Kb::newMode(), profileChanged(), KbProfile::removeAll(), Kb::setCurrentMode(), and ui.

```
236                                                                                 {
237     QListWidgetItem* item = ui->modesList->itemAt(pos);
238     if(!item || !currentMode || item->data(GUID).toUuid() !=
    currentMode->id().guid)
239         return;
240     KbProfile* currentProfile = device->currentProfile();
241     int index = currentProfile->indexOf(currentMode);
242
243     QMenu menu(this);
244     QAction* rename = new QAction("Rename...", this);
245     QAction* duplicate = new QAction("Duplicate", this);
246     QAction* del = new QAction("Delete", this);
247     bool canDelete = (device->currentProfile()->modeCount() >
    device->hwModeCount);
248     if(!canDelete)
249         // Can't delete modes if they're required by hardware
250         del->setEnabled(false);
251     QAction* moveup = new QAction("Move Up", this);
252     if(index == 0)
253         moveup->setEnabled(false);
254     QAction* movedown = new QAction("Move Down", this);
255     if(index >= currentProfile->modeCount() - 1)
256         movedown->setEnabled(false);
257     menu.addAction(rename);
258     menu.addAction(duplicate);
259     menu.addAction(del);
260     menu.addSeparator();
261     menu.addAction(moveup);
262     menu.addAction(movedown);
263     QAction* result = menu.exec(QCursor::pos());
264     if(result == rename){
265         ui->modesList->editItem(item);
266     } else if(result == duplicate){
267         KbMode* newMode = device->newMode(currentMode);
268         newMode->newId();
269         currentProfile->insert(index + 1, newMode);
270         // Update UI
271         profileChanged();
272         device->setCurrentMode(newMode);
273     } else if(result == del){
274         if(!canDelete)
275             return;
276         currentProfile->removeAll(currentMode);
277         currentMode->deleteLater();
```

```
        currentMode = 0;
        // Select next mode
        profileChanged();
        if(index < currentProfile->modeCount())
            device->setCurrentMode(currentProfile->modes()[index]);
        else
            device->setCurrentMode(currentProfile->modes().last());
    } else if(result == moveup){
        currentProfile->removeAll(currentMode);
        currentProfile->insert(index - 1, currentMode);
        // Update UI
        profileChanged();
        modeChanged(true);
    } else if(result == movedown){
        currentProfile->removeAll(currentMode);
        currentProfile->insert(index + 1, currentMode);
        // Update UI
        profileChanged();
        modeChanged(true);
    }
}
```

Here is the call graph for this function:

12.38.3.12 void KbWidget::on_modesList_itemChanged (QListWidgetItem * *item*) [private],[slot]

Definition at line 199 of file kbwidget.cpp.

References currentMode, UsbId::guid, GUID, KbMode::id(), and KbMode::name().

```
199                                                                 {
200     if(!item || !currentMode || item->data(GUID).toUuid() !=
      currentMode->id().guid)
201         return;
202     currentMode->name(item->text());
203     // Set the text to the actual name (trimmed, "" replaced with "Unnamed")
204     item->setText(currentMode->name());
205 }
```

Here is the call graph for this function:

12.38.3.13 void KbWidget::on_modesList_itemClicked (QListWidgetItem * *item*) [private],[slot]

Definition at line 207 of file kbwidget.cpp.

References addNewModeItem(), KbProfile::append(), Kb::currentProfile(), device, UsbId::guid, GUID, KbMode::id(), Ui_KbWidget::modesList, NEW_FLAG, Kb::newMode(), Kb::setCurrentMode(), and ui.

```
207                                                                 {
208     QUuid guid = item->data(GUID).toUuid();
209     if(guid.isNull() && item->data(NEW_FLAG).toInt() == 1){
210         // "New mode" item. Clear text and start editing
211         item->setText("");
212         ui->modesList->editItem(item);
213         item->setFlags(item->flags() | Qt::ItemIsEditable | Qt::ItemIsDragEnabled | Qt::ItemIsDropEnabled);
214         QFont font = item->font();
215         font.setItalic(false);
216         item->setFont(font);
217         item->setIcon(QIcon(":/img/icon_mode.png"));
218         // Add the new mode and assign it to this item
219         KbMode* newMode = device->newMode();
220         device->currentProfile()->append(newMode);
221         item->setData(GUID, newMode->id().guid);
222         item->setData(NEW_FLAG, 0);
223         device->setCurrentMode(newMode, false);
224         // Create another "new mode" item to replace this one
225         addNewModeItem();
226     }
227 }
```

Here is the call graph for this function:

12.38.3.14 void KbWidget::on_profileBox_activated (int *index*) [private],[slot]

Definition at line 113 of file kbwidget.cpp.

References device, Kb::profiles(), Kb::setCurrentProfile(), and updateProfileList().

```
113                                                 {
114     if(index < 0)
115         return;
116     if(index >= device->profiles().count()){
117         // "Manage profiles" option
118         KbProfileDialog dialog(this);
119         dialog.exec();
120         updateProfileList();
121         return;
122     }
123     device->setCurrentProfile(device->profiles()[index]);
124     // Device will emit profileChanged() and modeChanged() signals to update UI
125 }
```

Here is the call graph for this function:

12.38.3.15 void KbWidget::on_tabWidget_currentChanged (int *index*) [private],[slot]

Definition at line 317 of file kbwidget.cpp.

References device, Ui_KbWidget::tabWidget, ui, and updateFwButton().

```
317                                                 {
318     if(!device)
319         return;
320     if(index == ui->tabWidget->count() - 1){
321         // Device tab
```

```
        updateFwButton();
    }
}
```

Here is the call graph for this function:

12.38.3.16 void KbWidget::profileChanged ( ) [private],[slot]

Definition at line 91 of file kbwidget.cpp.

References addNewModeItem(), currentMode, Kb::currentProfile(), device, UsbId::guid, GUID, KbMode::id(), modeIcon(), KbProfile::modes(), Ui_KbWidget::modesList, KbMode::name(), and ui.

Referenced by KbWidget(), on_hwSaveButton_clicked(), and on_modesList_customContextMenuRequested().

```
91                              {
92     // Rebuild mode list
93     ui->modesList->clear();
94     int i = 0;
95     QListWidgetItem* current = 0;
96     foreach(KbMode* mode, device->currentProfile()->
       modes()){
97         QListWidgetItem* item = new QListWidgetItem(modeIcon(i), mode->
       name(), ui->modesList);
98         item->setData(GUID, mode->id().guid);
99         item->setFlags(item->flags() | Qt::ItemIsEditable);
100         if(mode == currentMode){
101             item->setSelected(true);
102             current = item;
103         }
104         ui->modesList->addItem(item);
105         i++;
106     }
107     if(current)
108         ui->modesList->setCurrentItem(current);
109     addNewModeItem();
110     // Wait for modeChanged() to refresh the rest of the UI
111 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.17 void KbWidget::showFirstTab ( ) [slot]

Definition at line 64 of file kbwidget.cpp.

References Ui_KbWidget::tabWidget, and ui.

```
64                              {
65     ui->tabWidget->setCurrentIndex(0);
66 }
```

12.38.3.18 void KbWidget::showFwUpdate ( ) [inline],[slot]

Definition at line 38 of file kbwidget.h.

References on_fwUpdButton_clicked().

Referenced by MainWindow::showFwUpdateNotification().

```
38 { on_fwUpdButton_clicked(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.19 void KbWidget::showLastTab ( ) [slot]

Definition at line 68 of file kbwidget.cpp.

References Ui_KbWidget::tabWidget, and ui.

Referenced by MainWindow::showFwUpdateNotification().

```
68                          {
69     ui->tabWidget->setCurrentIndex(ui->tabWidget->count() - 1);
70 }
```

Here is the caller graph for this function:

12.38.3.20 void KbWidget::updateFwButton ( )

Definition at line 326 of file kbwidget.cpp.

References device, Kb::features, Kb::firmware, Ui_KbWidget::fwUpdButton, KbFirmware::hasDownloaded(), ui, and KbFirmware::versionForBoard().

Referenced by MainWindow::checkFwUpdates(), on_fwUpdButton_clicked(), and on_tabWidget_currentChanged().

```
326                             {
327     if(!KbFirmware::hasDownloaded())
328         ui->fwUpdButton->setText("Check for updates");
329     else {
330         float newVersion = KbFirmware::versionForBoard(
      device->features);
331         float oldVersion = device->firmware.toFloat();
332         if(newVersion <= 0.f || newVersion <= oldVersion)
333             ui->fwUpdButton->setText("Up to date");
334         else
335             ui->fwUpdButton->setText(tr("Upgrade to v%1").arg(QString::number(newVersion, 'f',
       2)));
336     }
337 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.3.21 void KbWidget::updateProfileList ( ) [private],[slot]

Definition at line 73 of file kbwidget.cpp.

References Kb::currentProfile(), device, Kb::hwProfile(), KbProfile::name(), Ui_KbWidget::profileBox, Kb::profiles(), and ui.

Referenced by KbWidget(), on_hwSaveButton_clicked(), and on_profileBox_activated().

```
73                                  {
74     // Clear profile list and rebuild
75     KbProfile* hwProfile = device->hwProfile(), *currentProfile =
      device->currentProfile();
76     ui->profileBox->clear();
77     int i = 0;
78     foreach(KbProfile* profile, device->profiles()){
79         ui->profileBox->addItem((profile == hwProfile) ? QIcon(":/img/icon_profile_hardware.png
      ") : QIcon(":/img/icon_profile.png"),
80                                 profile->name());
81         if(profile == currentProfile)
82             ui->profileBox->setCurrentIndex(i);
83         i++;
84     }
85     ui->profileBox->addItem(QIcon(":/img/icon_blank.png"), "Manage profiles...");
86     QFont font = ui->profileBox->font();
87     font.setItalic(true);
88     ui->profileBox->setItemData(ui->profileBox->count() - 1, font, Qt::FontRole);
89 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.38.4 Field Documentation

12.38.4.1 KbMode* KbWidget::currentMode [private]

Definition at line 44 of file kbwidget.h.

Referenced by modeChanged(), on_modesList_customContextMenuRequested(), on_modesList_itemChanged(), and profileChanged().

12.38.4.2 Kb* KbWidget::device

Definition at line 24 of file kbwidget.h.

Referenced by MainWindow::addDevice(), MainWindow::checkFwUpdates(), devUpdate(), KbWidget(), modeChanged(), modeIcon(), modesList_reordered(), name(), on_fwUpdButton_clicked(), on_hwSaveButton_clicked(), on_modesList_currentItemChanged(), on_modesList_customContextMenuRequested(), on_modesList_item-

Clicked(), on_profileBox_activated(), on_tabWidget_currentChanged(), profileChanged(), MainWindow::removeDevice(), MainWindow::showFwUpdateNotification(), updateFwButton(), and updateProfileList().

12.38.4.3 const int KbWidget::GUID = Qt::UserRole [static], [private]

Definition at line 46 of file kbwidget.h.

Referenced by modesList_reordered(), on_modesList_currentItemChanged(), on_modesList_customContextMenuRequested(), on_modesList_itemChanged(), on_modesList_itemClicked(), and profileChanged().

12.38.4.4 bool KbWidget::hasShownNewFW

Definition at line 28 of file kbwidget.h.

Referenced by MainWindow::checkFwUpdates().

12.38.4.5 quint64 KbWidget::lastAutoSave [private]

Definition at line 42 of file kbwidget.h.

12.38.4.6 const int KbWidget::NEW_FLAG = Qt::UserRole + 1 [static], [private]

Definition at line 47 of file kbwidget.h.

Referenced by addNewModeItem(), modesList_reordered(), and on_modesList_itemClicked().

12.38.4.7 Ui::KbWidget* KbWidget::ui [private]

Definition at line 41 of file kbwidget.h.

Referenced by addNewModeItem(), devUpdate(), KbWidget(), modeChanged(), modesList_reordered(), on_fwUpdButton_clicked(), on_modesList_customContextMenuRequested(), on_modesList_itemClicked(), on_tabWidget_currentChanged(), profileChanged(), showFirstTab(), showLastTab(), updateFwButton(), updateProfileList(), and ~KbWidget().

The documentation for this class was generated from the following files:

- src/ckb/kbwidget.h
- src/ckb/kbwidget.cpp

12.39 Ui::KbWidget Class Reference

```
#include <src/ckb/ui_kbwidget.h>
```

Inheritance diagram for Ui::KbWidget:

Collaboration diagram for Ui::KbWidget:

Public Member Functions

- void setupUi (QWidget *KbWidget)
- void retranslateUi (QWidget *KbWidget)

Data Fields

- QGridLayout * gridLayout
- QComboBox * profileBox
- QTabWidget * tabWidget
- QWidget * lightTab
- QGridLayout * gridLayout_2
- KbLightWidget * lightWidget
- QLabel * label_3
- QWidget * bindTab
- QGridLayout * gridLayout_5
- KbBindWidget * bindWidget
- QWidget * kPerfTab
- QGridLayout * gridLayout_4
- KPerfWidget * kPerfWidget
- QWidget * mPerfTab
- QGridLayout * gridLayout_7
- MPerfWidget * mPerfWidget
- QWidget * devTab
- QGridLayout * gridLayout_3
- QLabel * fwUpdLabel
- QSpacerItem * verticalSpacer
- QLabel * fwLabel
- QLabel * label_4
- QSpacerItem * horizontalSpacer_2
- QLabel * label_9
- QLabel * serialLabel
- QHBoxLayout * fwUpdLayout
- QPushButton * fwUpdButton
- QSpacerItem * horizontalSpacer_3
- QLabel * pollLabel2
- QLabel * pollLabel
- RListWidget * modesList
- QPushButton * hwSaveButton

12.39.1 Detailed Description

Definition at line 291 of file ui_kbwidget.h.

12.39.2 Member Function Documentation

12.39.2.1 void Ui_KbWidget::retranslateUi (QWidget * *KbWidget*) [inline],[inherited]

Definition at line 268 of file ui_kbwidget.h.

References Ui_KbWidget::bindTab, Ui_KbWidget::devTab, Ui_KbWidget::fwLabel, Ui_KbWidget::fwUpdButton, Ui_KbWidget::fwUpdLabel, Ui_KbWidget::hwSaveButton, Ui_KbWidget::kPerfTab, Ui_KbWidget::label_3, Ui_KbWidget::label_4, Ui_KbWidget::label_9, Ui_KbWidget::lightTab, Ui_KbWidget::mPerfTab, Ui_KbWidget::pollLabel, Ui_KbWidget::pollLabel2, Ui_KbWidget::serialLabel, and Ui_KbWidget::tabWidget.

Referenced by Ui_KbWidget::setupUi().

```
    {
        KbWidget->setWindowTitle(QApplication::translate("KbWidget", "Form", Q_NULLPTR));
        label_3->setText(QApplication::translate("KbWidget", "Tip: Drag+drop items to reorder. Right-click for menu.", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(lightTab), QApplication::translate("KbWidget", "Lighting", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(bindTab), QApplication::translate("KbWidget", "Binding", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(kPerfTab), QApplication::translate("KbWidget", "Performance", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(mPerfTab), QApplication::translate("KbWidget", "Performance", Q_NULLPTR));
        fwUpdLabel->setText(QApplication::translate("KbWidget", "Status:", Q_NULLPTR));
        fwLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        label_4->setText(QApplication::translate("KbWidget", "USB device ID:", Q_NULLPTR));
        label_9->setText(QApplication::translate("KbWidget", "Firmware version:", Q_NULLPTR));
        serialLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        fwUpdButton->setText(QApplication::translate("KbWidget", "Check for updates", Q_NULLPTR));
        pollLabel2->setText(QApplication::translate("KbWidget", "Poll rate:", Q_NULLPTR));
        pollLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(devTab), QApplication::translate("KbWidget", "Device", Q_NULLPTR));
        hwSaveButton->setText(QApplication::translate("KbWidget", "Save to hardware", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.39.2.2 void Ui_KbWidget::setupUi (QWidget * *KbWidget*) [inline], [inherited]

Definition at line 69 of file ui_kbwidget.h.

References Ui_KbWidget::bindTab, Ui_KbWidget::bindWidget, Ui_KbWidget::devTab, Ui_KbWidget::fwLabel, Ui_KbWidget::fwUpdButton, Ui_KbWidget::fwUpdLabel, Ui_KbWidget::fwUpdLayout, Ui_KbWidget::gridLayout, Ui_KbWidget::gridLayout_2, Ui_KbWidget::gridLayout_3, Ui_KbWidget::gridLayout_4, Ui_KbWidget::gridLayout_5, Ui_KbWidget::gridLayout_7, Ui_KbWidget::horizontalSpacer_2, Ui_KbWidget::horizontalSpacer_3, Ui_KbWidget::hwSaveButton, Ui_KbWidget::kPerfTab, Ui_KbWidget::kPerfWidget, Ui_KbWidget::label_3, Ui_KbWidget::label_4, Ui_KbWidget::label_9, Ui_KbWidget::lightTab, Ui_KbWidget::lightWidget, Ui_KbWidget::modesList, Ui_KbWidget::mPerfTab, Ui_KbWidget::mPerfWidget, Ui_KbWidget::pollLabel, Ui_KbWidget::pollLabel2, Ui_KbWidget::profileBox, Ui_KbWidget::retranslateUi(), Ui_KbWidget::serialLabel, Ui_KbWidget::tabWidget, and Ui_KbWidget::verticalSpacer.

Referenced by KbWidget::KbWidget().

```
    {
        if (KbWidget->objectName().isEmpty())
            KbWidget->setObjectName(QStringLiteral("KbWidget"));
        KbWidget->resize(773, 539);
        gridLayout = new QGridLayout(KbWidget);
        gridLayout->setSpacing(9);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        gridLayout->setContentsMargins(9, -1, 9, 9);
        profileBox = new QComboBox(KbWidget);
        profileBox->setObjectName(QStringLiteral("profileBox"));
        QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(18);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(profileBox->sizePolicy().hasHeightForWidth());
        profileBox->setSizePolicy(sizePolicy);
        profileBox->setIconSize(QSize(24, 24));

        gridLayout->addWidget(profileBox, 0, 0, 1, 1);

```

```
        tabWidget = new QTabWidget(KbWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy1.setHorizontalStretch(82);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(tabWidget->sizePolicy().hasHeightForWidth());
        tabWidget->setSizePolicy(sizePolicy1);
        lightTab = new QWidget();
        lightTab->setObjectName(QStringLiteral("lightTab"));
        gridLayout_2 = new QGridLayout(lightTab);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
         gridLayout_2->setHorizontalSpacing(0);
         gridLayout_2->setVerticalSpacing(6);
         gridLayout_2->setContentsMargins(6, 6, 6, 6);
         lightWidget = new KbLightWidget(lightTab);
         lightWidget->setObjectName(QStringLiteral("lightWidget"));
         QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Expanding);
         sizePolicy2.setHorizontalStretch(0);
         sizePolicy2.setVerticalStretch(0);
         sizePolicy2.setHeightForWidth(lightWidget->sizePolicy().hasHeightForWidth());
         lightWidget->setSizePolicy(sizePolicy2);

         gridLayout_2->addWidget(lightWidget, 0, 0, 1, 1);

         label_3 = new QLabel(lightTab);
         label_3->setObjectName(QStringLiteral("label_3"));
         QSizePolicy sizePolicy3(QSizePolicy::Preferred, QSizePolicy::Minimum);
         sizePolicy3.setHorizontalStretch(0);
         sizePolicy3.setVerticalStretch(0);
         sizePolicy3.setHeightForWidth(label_3->sizePolicy().hasHeightForWidth());
         label_3->setSizePolicy(sizePolicy3);

         gridLayout_2->addWidget(label_3, 1, 0, 1, 1);

         tabWidget->addTab(lightTab, QString());
         bindTab = new QWidget();
         bindTab->setObjectName(QStringLiteral("bindTab"));
         gridLayout_5 = new QGridLayout(bindTab);
         gridLayout_5->setSpacing(0);
         gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
         gridLayout_5->setContentsMargins(6, 6, 6, 6);
         bindWidget = new KbBindWidget(bindTab);
         bindWidget->setObjectName(QStringLiteral("bindWidget"));
         sizePolicy2.setHeightForWidth(bindWidget->sizePolicy().hasHeightForWidth());
         bindWidget->setSizePolicy(sizePolicy2);

         gridLayout_5->addWidget(bindWidget, 0, 0, 1, 1);

         tabWidget->addTab(bindTab, QString());
         kPerfTab = new QWidget();
         kPerfTab->setObjectName(QStringLiteral("kPerfTab"));
         gridLayout_4 = new QGridLayout(kPerfTab);
         gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
         gridLayout_4->setContentsMargins(6, 6, 6, 6);
         kPerfWidget = new KPerfWidget(kPerfTab);
         kPerfWidget->setObjectName(QStringLiteral("kPerfWidget"));

         gridLayout_4->addWidget(kPerfWidget, 0, 0, 1, 1);

         tabWidget->addTab(kPerfTab, QString());
         mPerfTab = new QWidget();
         mPerfTab->setObjectName(QStringLiteral("mPerfTab"));
         gridLayout_7 = new QGridLayout(mPerfTab);
         gridLayout_7->setObjectName(QStringLiteral("gridLayout_7"));
         gridLayout_7->setContentsMargins(6, 6, 6, 6);
         mPerfWidget = new MPerfWidget(mPerfTab);
         mPerfWidget->setObjectName(QStringLiteral("mPerfWidget"));

         gridLayout_7->addWidget(mPerfWidget, 0, 0, 1, 1);

         tabWidget->addTab(mPerfTab, QString());
         devTab = new QWidget();
         devTab->setObjectName(QStringLiteral("devTab"));
         gridLayout_3 = new QGridLayout(devTab);
         gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
         gridLayout_3->setContentsMargins(6, 6, 6, 6);
         fwUpdLabel = new QLabel(devTab);
         fwUpdLabel->setObjectName(QStringLiteral("fwUpdLabel"));
         fwUpdLabel->setMinimumSize(QSize(0, 34));

         gridLayout_3->addWidget(fwUpdLabel, 4, 0, 1, 1);

         verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

         gridLayout_3->addItem(verticalSpacer, 6, 2, 1, 1);

```

```
        fwLabel = new QLabel(devTab);
        fwLabel->setObjectName(QStringLiteral("fwLabel"));
        fwLabel->setCursor(QCursor(Qt::IBeamCursor));
        fwLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|Qt::TextSelectableByMouse);

        gridLayout_3->addWidget(fwLabel, 2, 2, 1, 1);

        label_4 = new QLabel(devTab);
        label_4->setObjectName(QStringLiteral("label_4"));
        label_4->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(label_4, 0, 0, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(40, 1, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_2, 2, 1, 1, 1);

        label_9 = new QLabel(devTab);
        label_9->setObjectName(QStringLiteral("label_9"));
        label_9->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(label_9, 2, 0, 1, 1);

        serialLabel = new QLabel(devTab);
        serialLabel->setObjectName(QStringLiteral("serialLabel"));
        serialLabel->setCursor(QCursor(Qt::IBeamCursor));
        serialLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|
Qt::TextSelectableByMouse);

        gridLayout_3->addWidget(serialLabel, 0, 2, 1, 1);

        fwUpdLayout = new QHBoxLayout();
        fwUpdLayout->setObjectName(QStringLiteral("fwUpdLayout"));
        fwUpdButton = new QPushButton(devTab);
        fwUpdButton->setObjectName(QStringLiteral("fwUpdButton"));

        fwUpdLayout->addWidget(fwUpdButton);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        fwUpdLayout->addItem(horizontalSpacer_3);


        gridLayout_3->addLayout(fwUpdLayout, 4, 2, 1, 1);

        pollLabel2 = new QLabel(devTab);
        pollLabel2->setObjectName(QStringLiteral("pollLabel2"));
        pollLabel2->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(pollLabel2, 1, 0, 1, 1);

        pollLabel = new QLabel(devTab);
        pollLabel->setObjectName(QStringLiteral("pollLabel"));

        gridLayout_3->addWidget(pollLabel, 1, 2, 1, 1);

        tabWidget->addTab(devTab, QString());

        gridLayout->addWidget(tabWidget, 0, 1, 3, 1);

        modesList = new RListWidget(KbWidget);
        modesList->setObjectName(QStringLiteral("modesList"));
        QSizePolicy sizePolicy4(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy4.setHorizontalStretch(18);
        sizePolicy4.setVerticalStretch(0);
        sizePolicy4.setHeightForWidth(modesList->sizePolicy().hasHeightForWidth());
        modesList->setSizePolicy(sizePolicy4);
        modesList->setContextMenuPolicy(Qt::CustomContextMenu);
        modesList->setFrameShadow(QFrame::Plain);
        modesList->setDragDropMode(QAbstractItemView::InternalMove);
        modesList->setIconSize(QSize(24, 24));
        modesList->setMovement(QListView::Snap);

        gridLayout->addWidget(modesList, 1, 0, 1, 1);

        hwSaveButton = new QPushButton(KbWidget);
        hwSaveButton->setObjectName(QStringLiteral("hwSaveButton"));
        QSizePolicy sizePolicy5(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy5.setHorizontalStretch(18);
        sizePolicy5.setVerticalStretch(0);
        sizePolicy5.setHeightForWidth(hwSaveButton->sizePolicy().hasHeightForWidth());
        hwSaveButton->setSizePolicy(sizePolicy5);

        gridLayout->addWidget(hwSaveButton, 2, 0, 1, 1);

```

```
        retranslateUi(KbWidget);

        tabWidget->setCurrentIndex(0);


        QMetaObject::connectSlotsByName(KbWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.39.3 Field Documentation

12.39.3.1 QWidget* Ui_KbWidget::bindTab [inherited]

Definition at line 43 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.2 KbBindWidget* Ui_KbWidget::bindWidget [inherited]

Definition at line 45 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and Ui_KbWidget::setupUi().

12.39.3.3 QWidget* Ui_KbWidget::devTab [inherited]

Definition at line 52 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.4 QLabel* Ui_KbWidget::fwLabel [inherited]

Definition at line 56 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.5 QPushButton* Ui_KbWidget::fwUpdButton [inherited]

Definition at line 62 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::on_fwUpdButton_clicked(), Ui_KbWidget::retranslateUi(), Ui_KbWidget::setupUi(), and KbWidget::updateFwButton().

12.39.3.6 QLabel* Ui_KbWidget::fwUpdLabel [inherited]

Definition at line 54 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.7 QHBoxLayout* Ui_KbWidget::fwUpdLayout [inherited]

Definition at line 61 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), and Ui_KbWidget::setupUi().

12.39.3.8 QGridLayout* Ui_KbWidget::gridLayout [inherited]

Definition at line 36 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.9 QGridLayout* Ui_KbWidget::gridLayout_2 [inherited]

Definition at line 40 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.10 QGridLayout* Ui_KbWidget::gridLayout_3 [inherited]

Definition at line 53 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.11 QGridLayout* Ui_KbWidget::gridLayout_4 [inherited]

Definition at line 47 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.12 QGridLayout* Ui_KbWidget::gridLayout_5 [inherited]

Definition at line 44 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.13 QGridLayout* Ui_KbWidget::gridLayout_7 [inherited]

Definition at line 50 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.14 QSpacerItem* Ui_KbWidget::horizontalSpacer_2 [inherited]

Definition at line 58 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.15 QSpacerItem* Ui_KbWidget::horizontalSpacer_3 [inherited]

Definition at line 63 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

12.39.3.16 QPushButton* Ui_KbWidget::hwSaveButton [inherited]

Definition at line 67 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.17 QWidget* Ui_KbWidget::kPerfTab [inherited]

Definition at line 46 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.18 KPerfWidget* Ui_KbWidget::kPerfWidget [inherited]

Definition at line 48 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and Ui_KbWidget::setupUi().

12.39.3.19 QLabel* Ui_KbWidget::label_3 [inherited]

Definition at line 42 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.20 QLabel* Ui_KbWidget::label_4 [inherited]

Definition at line 57 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.21 QLabel* Ui_KbWidget::label_9 [inherited]

Definition at line 59 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.22 QWidget* Ui_KbWidget::lightTab [inherited]

Definition at line 39 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.23 KbLightWidget* Ui_KbWidget::lightWidget [inherited]

Definition at line 41 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::modeChanged(), and Ui_KbWidget::setupUi().

12.39.3.24 RListWidget* Ui_KbWidget::modesList [inherited]

Definition at line 66 of file ui_kbwidget.h.

Referenced by KbWidget::addNewModeItem(), KbWidget::KbWidget(), KbWidget::modeChanged(), KbWidget::modesList_reordered(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemClicked(), KbWidget::profileChanged(), and Ui_KbWidget::setupUi().

12.39.3.25 QWidget* Ui_KbWidget::mPerfTab [inherited]

Definition at line 49 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.26 MPerfWidget* Ui_KbWidget::mPerfWidget [inherited]

Definition at line 51 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and Ui_KbWidget::setupUi().

12.39.3.27 QLabel* Ui_KbWidget::pollLabel [inherited]

Definition at line 65 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.28 QLabel* Ui_KbWidget::pollLabel2 [inherited]

Definition at line 64 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.29 QComboBox* Ui_KbWidget::profileBox [inherited]

Definition at line 37 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi(), and KbWidget::updateProfileList().

12.39.3.30 QLabel* Ui_KbWidget::serialLabel [inherited]

Definition at line 60 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), Ui_KbWidget::retranslateUi(), and Ui_KbWidget::setupUi().

12.39.3.31 QTabWidget* Ui_KbWidget::tabWidget [inherited]

Definition at line 38 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::on_tabWidget_currentChanged(), Ui_KbWidget::retranslateUi(), Ui_KbWidget::setupUi(), KbWidget::showFirstTab(), and KbWidget::showLastTab().

12.39.3.32 QSpacerItem* Ui_KbWidget::verticalSpacer [inherited]

Definition at line 55 of file ui_kbwidget.h.

Referenced by Ui_KbWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbwidget.h

12.40 Key Struct Reference

`#include <src/ckb/keymap.h>`

Collaboration diagram for Key:

Public Member Functions

- const char * storageName () const
- QString friendlyName (bool os=true) const
- operator bool () const
- bool operator! () const

Data Fields

- const char * _storageName
- const char * _friendlyName
- const char * name

- short x
- short y
- short width
- short height
- bool hasLed
- bool hasScan

12.40.1 Detailed Description

Definition at line 8 of file keymap.h.

12.40.2 Member Function Documentation

12.40.2.1 QString Key::friendlyName (bool *os* = `true`) const [inline]

Definition at line 23 of file keymap.h.

References _friendlyName, and name.

Referenced by KbBind::friendlyName(), KeyWidget::mouseMoveEvent(), KeyWidget::paintEvent(), RebindWidget::setBind(), and KbBindWidget::updateSelDisplay().

```
23                                                      {
24          if(os){
25  #ifdef Q_OS_MACX
26              if(!strcmp(name, "lwin")) return "Left Cmd";
27              if(!strcmp(name, "rwin")) return "Right Cmd";
28              if(!strcmp(name, "lalt")) return "Left Option";
29              if(!strcmp(name, "ralt")) return "Right Option";
30              if(!strcmp(name, "prtscn")) return "F13";
31              if(!strcmp(name, "scroll")) return "F14";
32              if(!strcmp(name, "pause")) return "F15";
33              if(!strcmp(name, "ins")) return "Help";
34              if(!strcmp(name, "numlock")) return "Clear";
35  #elif defined(Q_OS_LINUX)
36              if(!strcmp(name, "lwin")) return "Left Super";
37              if(!strcmp(name, "rwin")) return "Right Super";
38  #endif
39          }
40          return _friendlyName ? _friendlyName : QString(
        name).toUpper();
41      }
```

Here is the caller graph for this function:

12.40.2.2 Key::operator bool ( ) const [inline]

Definition at line 44 of file keymap.h.

References name.

```
44 { return name != 0; }
```

12.40.2.3 bool Key::operator! ( ) const [inline]

Definition at line 45 of file keymap.h.

```
45 { return !(bool)*this; }
```

12.40.2.4 const char* Key::storageName ( ) const [inline]

Definition at line 11 of file keymap.h.

References _storageName, and name.

Referenced by KeyMap::toStorage().

```
11 { return _storageName ? _storageName : name; }
```

Here is the caller graph for this function:

12.40.3 Field Documentation

12.40.3.1 const char* Key::_friendlyName

Definition at line 13 of file keymap.h.

Referenced by _patch(), and friendlyName().

12.40.3.2 const char* Key::_storageName

Definition at line 10 of file keymap.h.

Referenced by _patch(), and storageName().

12.40.3.3 bool Key::hasLed

Definition at line 19 of file keymap.h.

Referenced by ColorMap::init(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and KeyWidget::selectAll().

12.40.3.4 bool Key::hasScan

Definition at line 20 of file keymap.h.

Referenced by KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and KeyWidget::selectAll().

12.40.3.5 short Key::height

Definition at line 17 of file keymap.h.

Referenced by getMap(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and patchANSI().

12.40.3.6 const char* Key::name

Definition at line 14 of file keymap.h.

Referenced by friendlyName(), ColorMap::init(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), operator bool(), KeyWidget::paintEvent(), KeyWidget::selectAll(), and storageName().

12.40.3.7 short Key::width

Definition at line 17 of file keymap.h.

Referenced by getMap(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and patchANSI().

12.40.3.8 short Key::x

Definition at line 16 of file keymap.h.

Referenced by AnimScript::begin(), KeyMap::byPosition(), getMap(), AnimScript::keypress(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and patchANSI().

12.40.3.9 short Key::y

Definition at line 16 of file keymap.h.

Referenced by AnimScript::begin(), KeyMap::byPosition(), getMap(), AnimScript::keypress(), KeyWidget::mouseMoveEvent(), KeyWidget::mousePressEvent(), KeyWidget::paintEvent(), and patchANSI().

The documentation for this struct was generated from the following file:

- src/ckb/keymap.h

12.41 KeyAction Class Reference

```
#include <src/ckb/keyaction.h>
```

Inheritance diagram for KeyAction:

Collaboration diagram for KeyAction:

Public Types

- enum Type { UNBOUND, NORMAL, SPECIAL }

Public Member Functions

- KeyAction (const QString &action, QObject *parent=0)
- QString value () const
- operator QString () const
- KeyAction (QObject *parent=0)
- QString friendlyName (const KeyMap &map) const
- QString driverName () const

- QString macroFullLine () const

  macroFullLine If a macro command and a macro definition exists for the given key, returns the complete string except the leading "$" (the $ may confuse some caller).
- bool isValidMacro () const

  isValidMacro checks whether a keyAction contains a valid macro. This is done easily: If the macro action starts with $macro: and has four elements, delimited by ":", we may assume, that is a structural correct macro action.
- QStringList macroLine () const

  macroLine returns all interresting content for a macro definition.
- QString macroContent () const

  macroContent returns the macro key definition only (the second part of the macro action).
- void macroDisplay ()

  Debug output for invalid macro Definitions.
- Type type () const
- bool isUnbound () const
- bool isNormal () const
- bool isSpecial () const
- bool isMedia () const
- bool isProgram () const
- bool isAnim () const
- bool isMacro () const
- bool isDPI () const
- bool isMouse () const
- QString specialInfo (int &parameter) const
- int programInfo (QString &onPress, QString &onRelease) const
- int dpiInfo (QPoint &custom) const
- QUuid animInfo (bool &onlyOnce, bool &stopOnRelease) const
- void keyEvent (KbBind *bind, bool down)
- void keyRelease (KbBind *bind)
- void adjustDisplay ()
- ~KeyAction ()

Static Public Member Functions

- static QString noAction ()
- static QString defaultAction (const QString &key)
- static QString modeAction (int mode)
- static QString dpiAction (int level, int customX=0, int customY=0)
- static QString lightAction (int type=LIGHT_UP_WRAP)
- static QString lockAction (int type=LOCK_TOGGLE)
- static QString programAction (const QString &onPress, const QString &onRelease, int stop)
- static QString animAction (const QUuid &guid, bool onlyOnce, bool stopOnRelease)
- static QString macroAction (QString macroDef)

  well documented in cpp file

Static Public Attributes

- static const int MODE_PREV = -2
- static const int MODE_NEXT = -1
- static const int MODE_PREV_WRAP = -4
- static const int MODE_NEXT_WRAP = -3
- static const int DPI_UP = -2
- static const int DPI_DOWN = -1
- static const int DPI_SNIPER = 0

- static const int DPI_CUSTOM = 6
- static const int LIGHT_UP = 0
- static const int LIGHT_DOWN = 1
- static const int LIGHT_UP_WRAP = 2
- static const int LIGHT_DOWN_WRAP = 3
- static const int LOCK_TOGGLE = 0
- static const int LOCK_ON = 1
- static const int LOCK_OFF = 2
- static const int PROGRAM_PR_MULTI = 0x04
- static const int PROGRAM_PR_INDEF = 0x00
- static const int PROGRAM_PR_KRSTOP = 0x01
- static const int PROGRAM_PR_KPSTOP = 0x02
- static const int PROGRAM_RE_MULTI = 0x40
- static const int PROGRAM_RE_INDEF = 0x00
- static const int PROGRAM_RE_KPSTOP = 0x20

Private Member Functions

- void operator= (const KeyAction &rhs)

  ccMSC: Don't copy key actions (the old one needs to be deleted first) frickler24: statement left as described, but copying is done in KbBind copy constructor
- KeyAction (const KeyAction &rhs)

Private Attributes

- QString _value
- QProcess * preProgram
- QProcess * relProgram
- quint64 sniperValue

12.41.1 Detailed Description

Definition at line 13 of file keyaction.h.

12.41.2 Member Enumeration Documentation

12.41.2.1 enum KeyAction::Type

Enumerator

UNBOUND

NORMAL

SPECIAL

Definition at line 125 of file keyaction.h.

```
125             {
126         UNBOUND,
127         NORMAL,
128         SPECIAL,
129     };
```

12.41.3 Constructor & Destructor Documentation

12.41.3.1 KeyAction::KeyAction (const QString & *action*, QObject * *parent* = 0)

Definition at line 22 of file keyaction.cpp.

```
23     : QObject(parent), _value(action), preProgram(0),
      relProgram(0), sniperValue(0)
24 {
25 }
```

12.41.3.2 KeyAction::KeyAction (QObject * *parent* = 0) [explicit]

Definition at line 27 of file keyaction.cpp.

```
28     : QObject(parent), _value(""), preProgram(0),
      relProgram(0), sniperValue(0)
29 {
30 }
```

12.41.3.3 KeyAction::~KeyAction ( )

Definition at line 32 of file keyaction.cpp.

References preProgram, and relProgram.

```
32                     {
33     // Clean up processes
34     if(preProgram){
35         preProgram->kill();
36         delete preProgram;
37     }
38     if(relProgram){
39         relProgram->kill();
40         delete relProgram;
41     }
42 }
```

12.41.3.4 KeyAction::KeyAction (const KeyAction & *rhs*) [inline],[private]

Definition at line 166 of file keyaction.h.

```
166 : QObject() {}
```

12.41.4 Member Function Documentation

12.41.4.1 void KeyAction::adjustDisplay ( )

Definition at line 445 of file keyaction.cpp.

Referenced by keyEvent().

```
445                             {
446 #ifdef USE_LIBX11
447     // Try to get the current display from the X server
448     char* display_name = XDisplayName(NULL);
449     if(!display_name)
450         return;
451     Display* display = XOpenDisplay(display_name);
452     if(!display)
453         return;
454     char* display_string = DisplayString(display);
455     if(!display_string || strlen(display_string) == 0){
```

```
        XCloseDisplay(display);
        return;
    }
    size_t envstr_size = strlen(display_string) + 4;
    char* envstr = new char[envstr_size];
    strncpy(envstr, display_string, envstr_size);
    envstr[envstr_size - 1] = 0;

    Window root_window = XRootWindow(display, DefaultScreen(display));
    Window root_window_ret, child_window_ret, window;
    XWindowAttributes attr;
    int root_x, root_y, win_x, win_y;
    unsigned int mask_ret;

    // Find the screen which currently has the mouse
    XQueryPointer(display, root_window, &root_window_ret, &child_window_ret, &root_x, &root_y, &win_x, &
win_y, &mask_ret);
    if(child_window_ret == (Window)NULL)
        window = root_window_ret;
    else
        window = child_window_ret;
    XGetWindowAttributes(display, window,  &attr);

    char* ptr = strchr(envstr, ':');
    if(ptr){
        ptr = strchr(ptr, '.');
        if(ptr)
            *ptr = '\0';
        char buf[16];
        snprintf(buf, sizeof(buf), ".%i", XScreenNumberOfScreen(attr.screen));
        strncat(envstr, buf, envstr_size - 1 - strlen(envstr));

        // Update environment variable
        setenv("DISPLAY", envstr, 1);
    }

    delete[] envstr;
    XCloseDisplay(display);
#endif
}
```

Here is the caller graph for this function:

12.41.4.2 QString KeyAction::animAction (const QUuid & *guid*, bool *onlyOnce*, bool *stopOnRelease*) [static]

Definition at line 175 of file keyaction.cpp.

References ANIM_KRSTOP, and ANIM_ONCE.

Referenced by RebindWidget::applyChanges().

```
175                                                                                                    {
176     int flags = (onlyOnce ? ANIM_ONCE : 0) | (stopOnRelease ?
    ANIM_KRSTOP : 0);
177     return "$anim:" + guid.toString() + QString("+%1").arg(flags);
178 }
```

Here is the caller graph for this function:

12.41.4.3 QUuid KeyAction::animInfo (bool & *onlyOnce*, bool & *stopOnRelease*) const

Definition at line 216 of file keyaction.cpp.

References _value, ANIM_KRSTOP, ANIM_ONCE, and isAnim().

Referenced by keyEvent(), and RebindWidget::setSelection().

```
216                                                                 {
217     if(!isAnim())
218         return QUuid();
219     QString param = _value.mid(6);
220     QStringList split = param.split("+");
221     if(split.length() < 2)
222         return QUuid();
223     QUuid id = split[0];
224     int flags = split[1].toInt();
225     onlyOnce = !!(flags & ANIM_ONCE);
226     stopOnRelease = !!(flags & ANIM_KRSTOP);
227     return id;
228 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.4 QString KeyAction::defaultAction (const QString & *key*) [static]

Definition at line 44 of file keyaction.cpp.

Referenced by KbBind::bindAction(), KbBind::defaultAction(), and KbBind::save().

```
44                                                  {
45     // G1-G18 are unbound by default
46     if(key.length() >= 2 && key[0] == 'g'
47         && ((key.length() == 2 && key[1] >= '0' && key[1] <= '9')
48         || (key.length() == 3 && key[1] == '1' && key[2] >= '0' && key[2] <= '8')))
49         return "";
50     // So are thumbgrid buttons
51     if(key.startsWith("thumb"))
52         return "";
53     // TODO: default action for MR
54     if(key == "mr")
55         return "";
56     // M1-M3 switch modes
```

```
    if(key == "m1")
        return "$mode:0";
    if(key == "m2")
        return "$mode:1";
    if(key == "m3")
        return "$mode:2";
    // Brightness and Win Lock are their own functions
    if(key == "light")
        return "$light:2";
    if(key == "lock")
        return "$lock:0";
    // DPI buttons
    if(key == "dpiup")
        return "$dpi:-2";
    if(key == "dpidn")
        return "$dpi:-1";
    if(key == "sniper")
        return "$dpi:0";
    // Everything else is a standard keypress
    return key;
}
```

Here is the caller graph for this function:

12.41.4.5 QString KeyAction::dpiAction (int *level*, int *customX* = 0, int *customY* = 0) [static]

Definition at line 153 of file keyaction.cpp.

References DPI_CUSTOM.

Referenced by RebindWidget::applyChanges().

```
153                                                                 {
154     QString action = tr("$dpi:%1").arg(level);
155     if(level == DPI_CUSTOM)
156         action += tr("+%1+%2").arg(customX).arg(customY);
157     return action;
158 }
```

Here is the caller graph for this function:

12.41.4.6 int KeyAction::dpiInfo (QPoint & *custom*) const

Definition at line 202 of file keyaction.cpp.

References _value, DPI_CUSTOM, and isDPI().

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

```
                                        {
    if(!isDPI())
        return 0;
    QString param = _value.mid(5);
    QStringList lxy = param.split("+");
    int level = lxy[0].toInt();
    if(level == DPI_CUSTOM){
        if(lxy.length() != 3)
            return 0;
        custom = QPoint(lxy[1].toInt(), lxy[2].toInt());
    }
    return level;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.7 QString KeyAction::driverName ( ) const

Definition at line 230 of file keyaction.cpp.

References _value, and isSpecial().

Referenced by KbBind::update().

```
                                        {
    if(isSpecial())
        return "";
    return _value;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.8 QString KeyAction::friendlyName (const KeyMap & *map*) const

Definition at line 79 of file keyaction.cpp.

References _value, DPI_CUSTOM, DPI_DOWN, DPI_SNIPER, DPI_UP, dpiInfo(), KeyMap::friendlyName(), KeyMap::layout(), LIGHT_DOWN, LIGHT_DOWN_WRAP, LIGHT_UP, LIGHT_UP_WRAP, LOCK_OFF, LOCK_ON, LOCK_TOGGLE, MODE_NEXT, MODE_NEXT_WRAP, MODE_PREV, and MODE_PREV_WRAP.

```
79                                                          {
80      if(_value.isEmpty())
81          return "Unbound";
82      QStringList parts = _value.split(":");
83      QString prefix = parts[0];
84      if(parts.length() < 2){
85          KeyMap::Layout layout = map.layout();
86          QString name = KeyMap::friendlyName(_value, layout);
87          if(name.isEmpty())
88              return "(Unknown)";
89          return name;
90      }
91      int suffix = parts[1].toInt();
92      if(prefix == "$mode"){
93          switch(suffix){
94          case MODE_PREV:
95          case MODE_PREV_WRAP:
96              return "Switch to previous mode";
97          case MODE_NEXT:
98          case MODE_NEXT_WRAP:
99              return "Switch to next mode";
100         default:
101             return tr("Switch to mode %1").arg(suffix + 1);
102         }
103     } else if(prefix == "$dpi"){
104         // Split off custom parameters (if any)
105         int level = parts[1].split("+")[0].toInt();
106         switch(level){
107         case DPI_UP:
108             return "DPI up";
109         case DPI_DOWN:
110             return "DPI down";
111         case DPI_SNIPER:
112             return "Sniper";
113         case DPI_CUSTOM:{
114             QPoint xy;
115             dpiInfo(xy);
116             return tr("DPI: %1, %2").arg(xy.x()).arg(xy.y());
117         }
118         default:
119             return tr("DPI stage %1").arg(level);
120         }
121     } else if(prefix == "$light"){
122         switch(suffix){
123         case LIGHT_UP:
124         case LIGHT_UP_WRAP:
125             return "Brightness up";
126         case LIGHT_DOWN:
127         case LIGHT_DOWN_WRAP:
128             return "Brightness down";
129         }
130     } else if(prefix == "$lock"){
131         switch(suffix){
132         case LOCK_TOGGLE:
133             return "Toggle Windows lock";
134         case LOCK_ON:
135             return "Windows lock on";
136         case LOCK_OFF:
```

```
            return "Windows lock off";
        }
    } else if(prefix == "$anim"){
        return "Start animation";
    } else if(prefix == "$program"){
        return "Launch program";
    } else if(prefix == "$macro"){
        return "Send G-key macro";
    }
    return "(Unknown)";
}
```

Here is the call graph for this function:

12.41.4.9 bool KeyAction::isAnim ( ) const [inline]

Definition at line 138 of file keyaction.h.

References _value.

Referenced by animInfo(), and RebindWidget::setSelection().

```
138 { return _value.startsWith("$anim:"); }
```

Here is the caller graph for this function:

12.41.4.10 bool KeyAction::isDPI ( ) const [inline]

Definition at line 141 of file keyaction.h.

References _value.

Referenced by dpiInfo(), isMouse(), and RebindWidget::setSelection().

```
141 { return _value.startsWith("$dpi:"); }
```

Here is the caller graph for this function:

12.41.4.11 bool KeyAction::isMacro ( ) const [inline]

Definition at line 139 of file keyaction.h.

References _value.

Referenced by isValidMacro(), macroDisplay(), and macroFullLine().

```
139 { return _value.startsWith("$macro:"); }
```

Here is the caller graph for this function:

12.41.4.12 bool KeyAction::isMedia ( ) const [inline]

Definition at line 135 of file keyaction.h.

References _value.

```
135 { return _value == "mute" || _value == "volup" || _value == "voldn" ||
      _value == "stop" || _value == "prev" || _value == "play" ||
      _value == "next"; }
```

12.41.4.13 bool KeyAction::isMouse ( ) const [inline]

Definition at line 142 of file keyaction.h.

References _value, isDPI(), and isNormal().

Referenced by RebindWidget::setSelection().

```
142 { return (isNormal() && (_value.startsWith("mouse") || _value.startsWith("wheel"))) ||
      isDPI(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.14 bool KeyAction::isNormal ( ) const [inline]

Definition at line 132 of file keyaction.h.

References NORMAL, and type().

Referenced by isMouse(), RebindWidget::setBind(), and RebindWidget::setSelection().

```
132 { return type() == NORMAL; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.15 bool KeyAction::isProgram ( ) const [inline]

Definition at line 137 of file keyaction.h.

References _value.

Referenced by programInfo(), and RebindWidget::setSelection().

```
137 { return _value.startsWith("$program:"); }
```

Here is the caller graph for this function:

12.41.4.16 bool KeyAction::isSpecial ( ) const [inline]

Definition at line 133 of file keyaction.h.

References SPECIAL, and type().

Referenced by driverName(), keyEvent(), and RebindWidget::setSelection().

```
133 { return type() == SPECIAL; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.17 bool KeyAction::isUnbound ( ) const [inline]

Definition at line 131 of file keyaction.h.

References type(), and UNBOUND.

```
131 { return type() == UNBOUND; }
```

Here is the call graph for this function:

12.41.4.18 bool KeyAction::isValidMacro ( ) const [inline]

Returns

bool as true iff the macro definition contains all four elements.

Definition at line 54 of file keyaction.h.

References _value, and isMacro().

Referenced by macroContent(), macroDisplay(), macroLine(), RebindWidget::setSelection(), and KbBind::update().

```
54                                          {
55          if (isMacro()) {
56              QStringList ret;
57              ret =_value.split(":");
58              return (ret.count() == 4);
59          } else {
60              return false;
61          }
62      }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.19 void KeyAction::keyEvent (KbBind * *bind*, bool *down*)

Definition at line 236 of file keyaction.cpp.

References _value, adjustDisplay(), animInfo(), KbProfile::currentMode(), Kb::currentProfile(), KbBind::devParent(), KbLight::dimming(), KbPerf::dpi(), KbPerf::DPI_COUNT, DPI_CUSTOM, DPI_DOWN, DPI_SNIPER, DPI_UP, KbPerf::dpiDown(), dpiInfo(), KbPerf::dpiUp(), KbLight::findAnim(), KbProfile::indexOf(), KbAnim::isActive(), isSpecial(), KbBind::light(), LIGHT_DOWN, LIGHT_DOWN_WRAP, LIGHT_UP, LIGHT_UP_WRAP, LOCK_OFF, LOCK_ON, LOCK_TOGGLE, KbLight::MAX_DIM, MODE_NEXT, MODE_NEXT_WRAP, MODE_PREV, MODE_PREV_WRAP, KbProfile::modeCount(), KbProfile::modes(), KbBind::perf(), KbPerf::popDpi(), preProgram, PROGRAM_PR_KPSTOP, PROGRAM_PR_KRSTOP, PROGRAM_PR_MULTI, PROGRAM_RE_KPSTOP, PROGRAM_RE_MULTI, programInfo(), KbPerf::pushDpi(), KbPerf::pushSniper(), relProgram, Kb::setCurrentMode(), sniperValue, KbAnim::stop(), KbAnim::trigger(), and KbBind::winLock().

Referenced by KbBind::keyEvent().

```
236                                                 {
237     // No need to respond to standard actions
238     if(!isSpecial())
239         return;
240     QStringList parts = _value.split(":");
241     if(parts.length() < 2)
242         return;
243     QString prefix = parts[0];
244     int suffix = parts[1].toInt();
245     if(prefix == "$mode"){
246         if(!down)
247             return;
248         // Change mode
249         Kb* device = bind->devParent();
250         KbProfile* currentProfile = device->currentProfile();
251         int mode = currentProfile->indexOf(currentProfile->currentMode());
252         int modeCount = currentProfile->modeCount();
253         switch(suffix){
254         case MODE_PREV_WRAP:
255             mode--;
256             if(mode < 0)
257                 mode = modeCount - 1;
258             break;
259         case MODE_NEXT_WRAP:
260             mode++;
261             if(mode >= modeCount)
262                 mode = 0;
263             break;
264         case MODE_PREV:
265             mode--;
266             break;
267         case MODE_NEXT:
268             mode++;
269             break;
270         default:
271             // Absolute
272             mode = suffix;
273             break;
274         }
275         if(mode < 0 || mode >= modeCount)
276             return;
277         device->setCurrentMode(currentProfile->modes()[mode]);
278     } else if(prefix == "$dpi"){
279         KbPerf* perf = bind->perf();
280         int level = parts[1].split("+")[0].toInt();
281         switch(level){
282         case DPI_UP:
```

```
            if(!down)
                return;
            perf->dpiUp();
            break;
        case DPI_DOWN:
            if(!down)
                return;
            perf->dpiDown();
            break;
        case DPI_SNIPER:
            if(down)
                sniperValue = perf->pushSniper();
            else {
                perf->popDpi(sniperValue);
                sniperValue = 0;
            }
            break;
        case DPI_CUSTOM:{
            QPoint xy;
            dpiInfo(xy);
            if(xy.x() <= 0 || xy.y() <= 0)
                break;
            if(down)
                sniperValue = perf->pushDpi(xy);
            else {
                perf->popDpi(sniperValue);
                sniperValue = 0;
            }
            break;
        }
        default:
            if(level < 1 || level >= KbPerf::DPI_COUNT
                    || !down)
                return;
            perf->dpi(level);
            break;
        }
    } else if(prefix == "$light"){
        if(!down)
            return;
        // Change brightness
        KbLight* light = bind->light();
        int dim = light->dimming();
        switch(suffix){
        case LIGHT_UP:
            if(dim > 0)
                dim--;
            break;
        case LIGHT_DOWN:
            if(dim < KbLight::MAX_DIM)
                dim++;
            break;
        case LIGHT_UP_WRAP:
            dim--;
            if(dim < 0)
                dim = KbLight::MAX_DIM;
            break;
        case LIGHT_DOWN_WRAP:
            dim++;
            if(dim > KbLight::MAX_DIM)
                dim = 0;
            break;
        }
        light->dimming(dim);
    } else if(prefix == "$lock"){
        if(!down)
            return;
        // Change win lock
        switch(suffix){
        case LOCK_TOGGLE:
            bind->winLock(!bind->winLock());
            break;
        case LOCK_ON:
            bind->winLock(true);
            break;
        case LOCK_OFF:
            bind->winLock(false);
            break;
        }
    } else if(prefix == "$anim"){
        // Start animation
        bool onlyOnce = false, stopOnRelease = false;
        QUuid id = animInfo(onlyOnce, stopOnRelease);
        KbAnim* anim = bind->light()->findAnim(id);
        if(!anim)
            return;
        if(down){
```

```
            if(!onlyOnce || !anim->isActive())
                // If "only once" is enabled, don't start the animation when it's already running
                anim->trigger(QDateTime::currentMSecsSinceEpoch(), true);
        } else if(stopOnRelease){
            // Key released - stop animation
            anim->stop();
        }
    } else if(prefix == "$program"){
        // Launch program
        QString onPress, onRelease;
        int stop = programInfo(onPress, onRelease);
        // Stop running programs based on setting
        QProcess* process = 0;
        if(down){
            if(stop & PROGRAM_PR_KPSTOP){
                process = preProgram;
                if(process)
                    process->kill();
                process = 0;
            }
            if(stop & PROGRAM_RE_KPSTOP)
                process = relProgram;
        } else {
            if(stop & PROGRAM_PR_KRSTOP)
                process = preProgram;
        }
        if(process)
            process->kill();
        // Launch new process if requested
        QString& program = down ? onPress : onRelease;
        if(program.isEmpty())
            return;
        // Check if the program is running already. If so, don't start it again.
        process = down ? preProgram : relProgram;
        if(process){
            if(process->state() == QProcess::NotRunning)
                delete process;
            else
                return;
        }

        // Adjust the selected display.
        adjustDisplay();

        // Start the program. Wrap it around sh to parse arguments.
        if((down && (stop & PROGRAM_PR_MULTI))
                || (!down && (stop & PROGRAM_RE_MULTI))){
            // Multiple instances allowed? Start detached process
            QProcess::startDetached("sh", QStringList() << "-c" << program);
        } else {
            process = new QProcess(this);
            process->start("sh", QStringList() << "-c" << program);
            if(down)
                preProgram = process;
            else
                relProgram = process;
        }
    } else if (prefix == "$macro") {
        // Do nothing, because all work is done by the keyboard itself.
        // For now, there is no reason to react on G-key press or release.
        // If u find some reason, then here is the place for it.
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.20 void KeyAction::keyRelease (KbBind * *bind*)

12.41.4.21 QString KeyAction::lightAction (int *type* = LIGHT_UP_WRAP) [static]

Definition at line 160 of file keyaction.cpp.

Referenced by RebindWidget::applyChanges().

```
160                                     {
161     return QString("$light:%1").arg(type);
162 }
```

Here is the caller graph for this function:

12.41.4.22 QString KeyAction::lockAction (int *type* = LOCK_TOGGLE) [static]

Definition at line 164 of file keyaction.cpp.

Referenced by RebindWidget::applyChanges().

```
164                                     {
165     return QString("$lock:%1").arg(type);
166 }
```

Here is the caller graph for this function:

12.41.4.23 QString KeyAction::macroAction (QString *macroDef*) [static]

KeyAction::macroAction is called when applying changes on a macro definition. macroAction ist called while being in the macro pane and clicking Apply with something in the Macro Text Box. It tags that input with "$macro:" for further recognition.

Parameters

macroDef	holds the String containing parts 2-4 of a complete macro definition.

Returns

QString holding the complete G-Key macro definition (parts 1-4)

Definition at line 504 of file keyaction.cpp.

Referenced by RebindWidget::applyChanges().

```
504                                     {
505     return QString ("$macro:%1").arg(macroDef);
506 }
```

Here is the caller graph for this function:

12.41.4.24 QString KeyAction::macroContent ( ) const [inline]

Returns

QString macroContent

Definition at line 83 of file keyaction.h.

References _value, and isValidMacro().

Referenced by RebindWidget::setSelection(), and KbBind::update().

```
83                                      {
84          return isValidMacro() ? _value.split(":")[1] : "";
85      }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.25 void KeyAction::macroDisplay ( )

KeyAction::macroDisplay is just for debugging. It shows the content of the key action and some other info.

General Info on KeyAction::_value for macros: That string consists of 4 elements, all delimited by ":".

1. Macro command indicator "$macro:"
2. Macro Key Definition (coming from pteMacroBox): This sequence will program the keyboard and is hardly readable

3. Readable Macro String: This is displayed in pteMacroText

4. Readable Macro Comment:This is displayed in pteMacroComment

Definition at line 437 of file keyaction.cpp.

References _value, isMacro(), and isValidMacro().

Referenced by RebindWidget::setSelection().

```
437                                 {
438     qDebug() << "isMacro returns" << (isMacro() ? "true" : "false");
439     qDebug() << "isValidMacro returns" << (isValidMacro() ? "true" : "false");
440     QStringList ret =_value.split(":");
441     qDebug() << "Macro definition conains" << ret.count() << "elements";
442     qDebug() << "Macro definition is" << _value;
443 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.26 QString KeyAction::macroFullLine ( ) const [inline]

Returns

QString All 4 parts are returned in one QString. If no definition exists, return ""

Definition at line 43 of file keyaction.h.

References _value, and isMacro().

```
43                                          {
44          return isMacro() ? _value.right(_value.length()-1) : "";
45      }
```

Here is the call graph for this function:

12.41.4.27 QStringList KeyAction::macroLine ( ) const [inline]

Returns

QStringList returns the Macro Key Definition, Readble Macro String and Readable Macro Comment as QStringList.

Definition at line 70 of file keyaction.h.

References _value, and isValidMacro().

Referenced by RebindWidget::setSelection().

```
70                                          {
71          if (isValidMacro()) {
72              QStringList ret =_value.split(":");
73              ret.removeFirst();
74              return ret;
75          } else return QStringList();
76      }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.28 QString KeyAction::modeAction (int *mode*) [static]

Definition at line 149 of file keyaction.cpp.

Referenced by RebindWidget::applyChanges().

```
149                                     {
150     return QString("$mode:%1").arg(mode);
151 }
```

Here is the caller graph for this function:

12.41.4.29 static QString KeyAction::noAction ( ) [inline], [static]

Definition at line 25 of file keyaction.h.

```
25 { return ""; }
```

12.41.4.30 KeyAction::operator QString ( ) const [inline]

Definition at line 20 of file keyaction.h.

References _value.

```
20 { return _value; }
```

12.41.4.31 void KeyAction::operator= (const KeyAction & *rhs*) [inline], [private]

Definition at line 165 of file keyaction.h.

```
165 {}
```

12.41.4.32 QString KeyAction::programAction (const QString & *onPress*, const QString & *onRelease*, int *stop*) [static]

Definition at line 168 of file keyaction.cpp.

Referenced by RebindWidget::applyChanges().

```
168                                                                                                    {
169     // URL-encode the commands and place them in the string (":" and "+" are both replaced, so they won't
       interfere)
170     return "$program:" + QString::fromUtf8(QUrl::toPercentEncoding(onPress.trimmed())) + "+" +
       QString::fromUtf8(QUrl::toPercentEncoding(onRelease.trimmed())) + QString("+%1").arg(stop);
171 }
```

Here is the caller graph for this function:

12.41.4.33 int KeyAction::programInfo (QString & *onPress*, QString & *onRelease*) const

Definition at line 190 of file keyaction.cpp.

References _value, and isProgram().

Referenced by keyEvent(), and RebindWidget::setSelection().

```
190                                                                                    {
191     if(!isProgram())
192         return 0;
193     QString param = _value.mid(9);
194     QStringList programs = param.split("+");
195     if(programs.length() != 3)
196         return 0;
197     onPress = QUrl::fromPercentEncoding(programs[0].toUtf8());
198     onRelease = QUrl::fromPercentEncoding(programs[1].toUtf8());
199     return programs[2].toInt();
200 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.41.4.34 QString KeyAction::specialInfo (int & *parameter*) const

Definition at line 180 of file keyaction.cpp.

References _value.

Referenced by RebindWidget::setSelection().

```
180                                                 {
181     QStringList list = _value.split(":");
182     if(list.length() < 2){
183         parameter = INT_MIN;
184         return "";
185     }
186     parameter = list[1].toInt();
187     return list[0].replace("$", "");
188 }
```

Here is the caller graph for this function:

12.41.4.35 KeyAction::Type KeyAction::type ( ) const

Definition at line 14 of file keyaction.cpp.

References _value, NORMAL, SPECIAL, and UNBOUND.

Referenced by isNormal(), isSpecial(), isUnbound(), KbBindWidget::on_copyButton_clicked(), and KbBindWidget::on_resetButton_clicked().

```
14                                      {
15     if(_value.isEmpty())
16         return UNBOUND;
17     if(_value.at(0) == '$')
18         return SPECIAL;
19     return NORMAL;
20 }
```

Here is the caller graph for this function:

12.41.4.36 QString KeyAction::value ( ) const [inline]

Definition at line 19 of file keyaction.h.

References _value.

Referenced by KbBind::action(), KbBind::KbBind(), KbBind::save(), and KbBind::update().

```
19 { return _value; }
```

Here is the caller graph for this function:

12.41.5 Field Documentation

12.41.5.1 QString KeyAction::_value [private]

Definition at line 168 of file keyaction.h.

Referenced by animInfo(), dpiInfo(), driverName(), friendlyName(), isAnim(), isDPI(), isMacro(), isMedia(), isMouse(), isProgram(), isValidMacro(), keyEvent(), macroContent(), macroDisplay(), macroFullLine(), macroLine(), operator QString(), programInfo(), specialInfo(), type(), and value().

12.41.5.2 const int KeyAction::DPI_CUSTOM = 6 [static]

Definition at line 107 of file keyaction.h.

Referenced by dpiAction(), dpiInfo(), friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.3 const int KeyAction::DPI_DOWN = -1 [static]

Definition at line 106 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.4 const int KeyAction::DPI_SNIPER = 0 [static]

Definition at line 107 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.5 const int KeyAction::DPI_UP = -2 [static]

Definition at line 106 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.6 const int KeyAction::LIGHT_DOWN = 1 [static]

Definition at line 110 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.7 const int KeyAction::LIGHT_DOWN_WRAP = 3 [static]

Definition at line 111 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.8 const int KeyAction::LIGHT_UP = 0 [static]

Definition at line 110 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.9 const int KeyAction::LIGHT_UP_WRAP = 2 [static]

Definition at line 111 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.10 const int KeyAction::LOCK_OFF = 2 [static]

Definition at line 114 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.11 const int KeyAction::LOCK_ON = 1 [static]

Definition at line 114 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.12 const int KeyAction::LOCK_TOGGLE = 0 [static]

Definition at line 114 of file keyaction.h.

Referenced by friendlyName(), and keyEvent().

12.41.5.13 const int KeyAction::MODE_NEXT = -1 [static]

Definition at line 102 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.14 const int KeyAction::MODE_NEXT_WRAP = -3 [static]

Definition at line 103 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.15 const int KeyAction::MODE_PREV = -2 [static]

Definition at line 102 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.16 const int KeyAction::MODE_PREV_WRAP = -4 [static]

Definition at line 103 of file keyaction.h.

Referenced by friendlyName(), keyEvent(), and RebindWidget::setSelection().

12.41.5.17 QProcess* KeyAction::preProgram [private]

Definition at line 171 of file keyaction.h.

Referenced by keyEvent(), and ~KeyAction().

12.41.5.18 const int KeyAction::PROGRAM_PR_INDEF = 0x00 [static]

Definition at line 117 of file keyaction.h.

12.41.5.19 const int KeyAction::PROGRAM_PR_KPSTOP = 0x02 [static]

Definition at line 117 of file keyaction.h.

Referenced by keyEvent().

12.41.5.20 const int KeyAction::PROGRAM_PR_KRSTOP = 0x01 [static]

Definition at line 117 of file keyaction.h.

Referenced by keyEvent().

12.41.5.21 const int KeyAction::PROGRAM_PR_MULTI = 0x04 [static]

Definition at line 117 of file keyaction.h.

Referenced by RebindWidget::applyChanges(), keyEvent(), and RebindWidget::setSelection().

12.41.5.22 const int KeyAction::PROGRAM_RE_INDEF = 0x00 [static]

Definition at line 118 of file keyaction.h.

Referenced by RebindWidget::applyChanges(), and RebindWidget::setSelection().

12.41.5.23 const int KeyAction::PROGRAM_RE_KPSTOP = 0x20 [static]

Definition at line 118 of file keyaction.h.

Referenced by RebindWidget::applyChanges(), keyEvent(), and RebindWidget::setSelection().

12.41.5.24 const int KeyAction::PROGRAM_RE_MULTI = 0x40 [static]

Definition at line 118 of file keyaction.h.

Referenced by RebindWidget::applyChanges(), keyEvent(), and RebindWidget::setSelection().

12.41.5.25 QProcess* KeyAction::relProgram [private]

Definition at line 172 of file keyaction.h.

Referenced by keyEvent(), and ~KeyAction().

12.41.5.26 quint64 KeyAction::sniperValue [private]

Definition at line 175 of file keyaction.h.

Referenced by keyEvent().

The documentation for this class was generated from the following files:

- src/ckb/keyaction.h
- src/ckb/keyaction.cpp

12.42 KeyMap Class Reference

```
#include <src/ckb/keymap.h>
```

Collaboration diagram for KeyMap:

Public Types

- enum Model {
  NO_MODEL = -1, K65, K70, K95,
  STRAFE, M65, SABRE, SCIMITAR,
  _MODEL_MAX }
- enum Layout {
  NO_LAYOUT = -1, DK, EU, EU_DVORAK,
  GB, GB_DVORAK, US, US_DVORAK,
  FR, DE, IT, NO,
  PL, MX, ES, SE,
  _LAYOUT_MAX }

Public Member Functions

- bool isISO () const
- bool isKeyboard () const
- bool isMouse () const
- KeyMap ()
- KeyMap (Model _keyModel, Layout _keyLayout)
- QString strLayout () const
- QString strModel () const
- Model model () const
- Layout layout () const
- QString name () const
- uint count () const
- uint width () const
- uint height () const
- Key key (const QString &name) const
- Key operator[] (const QString &name) const
- bool contains (const QString &name) const
- const QHash< QString, Key > & map () const
- operator const QHash< QString, Key > & () const
- QStringList keys () const
- QList< Key > positions () const
- QString toStorage (const QString &name)
- QString fromStorage (const QString &storage)
- QStringList byPosition () const

Static Public Member Functions

- static QStringList layoutNames ()
- static bool isISO (Layout layout)
- static Layout locale ()
- static bool isKeyboard (Model model)
- static bool isMouse (Model model)
- static KeyMap fromName (const QString &name)
- static Layout getLayout (const QString &name)
- static QString getLayout (Layout layout)
- static Model getModel (const QString &name)
- static QString getModel (Model model)
- static QString friendlyName (const QString &key, Layout layout=US)

Static Private Member Functions

- static int modelWidth (Model model)
- static int modelHeight (Model model)

Private Attributes

- QHash< QString, Key > _keys
- short keyWidth
- short keyHeight
- Model keyModel:8
- Layout keyLayout:8

12.42.1 Detailed Description

Definition at line 49 of file keymap.h.

12.42.2 Member Enumeration Documentation

12.42.2.1 enum KeyMap::Layout

Enumerator

NO_LAYOUT

DK

EU

EU_DVORAK

GB

GB_DVORAK

US

US_DVORAK

FR

DE

IT

NO

PL

MX

ES

SE

_LAYOUT_MAX

Definition at line 65 of file keymap.h.

```
65                  {
66          NO_LAYOUT = -1,
67          DK,                     // Danish
68          EU,                     // English (EU)
69          EU_DVORAK,
70          GB,                     // English (UK)
71          GB_DVORAK,
72          US,                     // English (US)
73          US_DVORAK,
74          FR,                     // French
75          DE,                     // German
76          IT,                     // Italian
77          NO,                     // Norwegian
78          PL,                     // Polish (identical to US)
79          MX,                     // Spanish (Mexico/Latin America)
80          ES,                     // Spanish (Spain)
81          SE,                     // Swedish
82          _LAYOUT_MAX
83      };
```

12.42.2.2 enum KeyMap::Model

Enumerator

NO_MODEL

K65

K70

K95

STRAFE

M65

SABRE

SCIMITAR

_MODEL_MAX

Definition at line 51 of file keymap.h.

```
51                {
52          NO_MODEL = -1,
53          // Keyboard models
54          K65,
55          K70,
56          K95,
57          STRAFE,
58          // Mouse models
59          M65,
60          SABRE,
61          SCIMITAR,
62          _MODEL_MAX
63      };
```

12.42.3 Constructor & Destructor Documentation

12.42.3.1 KeyMap::KeyMap ( )

Definition at line 583 of file keymap.cpp.

Referenced by friendlyName(), and fromName().

```
583                 :
584       keyWidth(0), keyHeight(0),
585       keyModel(NO_MODEL), keyLayout(NO_LAYOUT)
586 {}
```

Here is the caller graph for this function:

12.42.3.2 KeyMap::KeyMap (Model *_keyModel,* Layout *_keyLayout*)

Definition at line 577 of file keymap.cpp.

```
577                                                 :
578     _keys(getMap(_keyModel, _keyLayout)),
579     keyWidth(modelWidth(_keyModel)), keyHeight(
      modelHeight(_keyModel)),
580     keyModel(_keyModel), keyLayout(_keyLayout)
581 {}
```

12.42.4 Member Function Documentation

12.42.4.1 QStringList KeyMap::byPosition ( ) const

Definition at line 588 of file keymap.cpp.

References key(), Key::x, and Key::y.

Referenced by RebindWidget::setBind().

```
588                                     {
589     // Use QMaps to order the keys
590     QMap<int, QMap<int, QString> > ordered;
591     QHashIterator<QString, Key> i(*this);
592     while(i.hasNext()){
593         i.next();
594         const Key& key = i.value();
595         ordered[key.y][key.x] = i.key();
596     }
597     // Merge them into a single list
598     QStringList result;
599     QMapIterator<int, QMap<int, QString> > y(ordered);
600     while(y.hasNext()){
601         y.next();
602         QMapIterator<int, QString> x(y.value());
603         while(x.hasNext()){
604             x.next();
605             result << x.value();
606         }
607     }
608     return result;
609 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.2 bool KeyMap::contains (const QString & *name*) const [inline]

Definition at line 127 of file keymap.h.

References _keys.

Referenced by friendlyName(), and KbAnimWidget::on_keyButton_clicked().

```
127 { return _keys.contains(name); }
```

Here is the caller graph for this function:

12.42.4.3 uint KeyMap::count ( ) const [inline]

Definition at line 118 of file keymap.h.

References _keys.

Referenced by KeyWidget::map(), KbBindWidget::on_copyButton_clicked(), and KbBindWidget::on_resetButton_-clicked().

```
118 { return _keys.count(); }
```

Here is the caller graph for this function:

12.42.4.4 QString KeyMap::friendlyName (const QString & *key*, Layout *layout* = US) [static]

Definition at line 611 of file keymap.cpp.

References contains(), K95, KeyMap(), M65, map(), SCIMITAR, and STRAFE.

Referenced by KeyAction::friendlyName(), and RebindWidget::RebindWidget().

```
611                                                                 {
612     // Try K95 map first
613     // FIXME: This is an odd function and probably should be refactored
614     // it would probably be best to remove the friendly names from the maps and have a completely separate
        name->friendlyName store
615     KeyMap map(K95, layout);
```

```
    if(map.contains(key))
        return map[key].friendlyName();

    // The only key missing from it should be Fn, which is found on STRAFE
    map = KeyMap(STRAFE, layout);
    if(map.contains(key))
        return map[key].friendlyName();

    // Additionally, there are a handful of keys not present on any physical keyboard, but we need names for them
    if(key == "f13" || key == "f14" || key == "f15" || key == "f16" || key == "f17" || key == "f18" || key == "f19" || key == "f20")
        return key.toUpper();
    else if(key == "lightup")
        return "Screen Brightness Up";
    else if(key == "lightdn")
        return "Screen Brightness Down";
    else if(key == "eject" || key == "power")
        return key[0].toUpper() + key.mid(1);   // capitalize first letter

    // All other names are found on mice
    map = KeyMap(SCIMITAR, layout);
    if(map.contains(key))
        return map[key].friendlyName();
    map = KeyMap(M65, layout);
    if(map.contains(key))
        return map[key].friendlyName();

    // Not found at all
    return "";
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.5 KeyMap KeyMap::fromName (const QString & *name*) [static]

Definition at line 535 of file keymap.cpp.

References getLayout(), getModel(), and KeyMap().

Referenced by KbBind::load(), and KbLight::load().

```
535                                         {
536     QStringList list = name.trimmed().split(" ");
537     if(list.length() != 2)
538         return KeyMap();
539     return KeyMap(getModel(list[0]), getLayout(list[1]));
540 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.6 QString KeyMap::fromStorage (const QString & *storage*) [inline]

Definition at line 135 of file keymap.h.

Referenced by KbAnim::KbAnim(), KbBind::load(), and KbLight::load().

```
135 { QHashIterator<QString, Key> i(*this); while(i.hasNext()) { i.next(); const char* s = i.value().
      storageName(); if(s == storage) return i.value().name; } return storage; }
```

Here is the caller graph for this function:

12.42.4.7 KeyMap::Layout KeyMap::getLayout (const QString & *name*) [static]

Definition at line 407 of file keymap.cpp.

References DE, DK, ES, EU, EU_DVORAK, FR, GB, GB_DVORAK, IT, MX, NO, NO_LAYOUT, PL, SE, US, and US_DVORAK.

Referenced by fromName(), SettingsWidget::on_layoutBox_activated(), SettingsWidget::SettingsWidget(), and strLayout().

```
407                                                 {
408     QString lower = name.toLower();
409     if(lower == "dk")
410         return DK;
411     if(lower == "eu")
412         return EU;
413     if(lower == "eu_dvorak")
414         return EU_DVORAK;
415     if(lower == "gb_dvorak")
416         return GB_DVORAK;
417     if(lower == "us")
418         return US;
419     if(lower == "us_dvorak")
420         return US_DVORAK;
421     if(lower == "fr")
422         return FR;
423     if(lower == "de")
424         return DE;
425     if(lower == "it")
426         return IT;
427     if(lower == "no")
428         return NO;
429     if(lower == "pl")
430         return PL;
431     if(lower == "mx")
432         return MX;
433     if(lower == "es")
434         return ES;
435     if(lower == "se")
436         return SE;
437     if(lower == "gb")
438         return GB;
439     return NO_LAYOUT;
440 }
```

Here is the caller graph for this function:

12.42.4.8 QString KeyMap::getLayout (KeyMap::Layout *layout*) [static]

Definition at line 442 of file keymap.cpp.

References DE, DK, ES, EU, EU_DVORAK, FR, GB, GB_DVORAK, IT, MX, NO, PL, SE, US, and US_DVORAK.

```
{
    switch(layout){
    case DK:
        return "dk";
    case EU:
        return "eu";
    case EU_DVORAK:
        return "eu_dvorak";
    case GB:
        return "gb";
    case GB_DVORAK:
        return "gb_dvorak";
    case US:
        return "us";
    case US_DVORAK:
        return "us_dvorak";
    case FR:
        return "fr";
    case DE:
        return "de";
    case IT:
        return "it";
    case NO:
        return "no";
    case PL:
        return "pl";
    case MX:
        return "mx";
    case ES:
        return "es";
    case SE:
        return "se";
    default:
        return "";
    }
}
```

12.42.4.9 KeyMap::Model KeyMap::getModel (const QString & *name*) [static]

Definition at line 495 of file keymap.cpp.

References K65, K70, K95, M65, NO_MODEL, SABRE, SCIMITAR, and STRAFE.

Referenced by fromName(), Kb::Kb(), and strModel().

```
{
    QString lower = name.toLower();
    if(lower == "k65")
        return K65;
    if(lower == "k70")
        return K70;
    if(lower == "k95")
        return K95;
    if(lower == "strafe")
        return STRAFE;
    if(lower == "m65")
        return M65;
    if(lower == "sabre")
        return SABRE;
    if(lower == "scimitar")
        return SCIMITAR;
    return NO_MODEL;
}
```

Here is the caller graph for this function:

12.42.4.10 QString KeyMap::getModel (KeyMap::Model *model*) [static]

Definition at line 514 of file keymap.cpp.

References K65, K70, K95, M65, SABRE, SCIMITAR, and STRAFE.

```
514                                                 {
515     switch(model){
516     case K65:
517         return "k65";
518     case K70:
519         return "k70";
520     case K95:
521         return "k95";
522     case STRAFE:
523         return "strafe";
524     case M65:
525         return "m65";
526     case SABRE:
527         return "sabre";
528     case SCIMITAR:
529         return "scimitar";
530     default:
531         return "";
532     }
533 }
```

12.42.4.11 uint KeyMap::height ( ) const [inline]

Definition at line 122 of file keymap.h.

References keyHeight.

Referenced by KeyWidget::drawInfo(), and KeyWidget::map().

```
122 { return keyHeight; }
```

Here is the caller graph for this function:

12.42.4.12 static bool KeyMap::isISO (Layout *layout*) [inline],[static]

Definition at line 87 of file keymap.h.

References PL, US, and US_DVORAK.

Referenced by KbBind::isISO(), and RebindWidget::setBind().

```
87 { return layout != US && layout != US_DVORAK && layout !=
      PL; }
```

Here is the caller graph for this function:

12.42.4.13 bool KeyMap::isISO ( ) const [inline]

Definition at line 88 of file keymap.h.

References isISO(), and keyLayout.

Referenced by getMap(), isISO(), Kb::Kb(), and Kb::updateLayout().

```
88 { return isISO(keyLayout); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.14 static bool KeyMap::isKeyboard (Model *model*) [inline], [static]

Definition at line 93 of file keymap.h.

References isMouse(), and NO_MODEL.

Referenced by KbBind::isKeyboard().

```
93 { return !isMouse(model) && model != NO_MODEL; }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.15 bool KeyMap::isKeyboard ( ) const [inline]

Definition at line 94 of file keymap.h.

References isKeyboard(), and keyModel.

Referenced by Kb::isKeyboard(), and isKeyboard().

```
94 { return isKeyboard(keyModel); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.16 static bool KeyMap::isMouse (Model *model*) [inline], [static]

Definition at line 95 of file keymap.h.

References M65, SABRE, and SCIMITAR.

Referenced by KbBind::isMouse(), KeyWidget::map(), KbLightWidget::newSelection(), and KeyWidget::paintEvent().

```
95 { return model == M65 || model == SABRE || model ==
     SCIMITAR; }
```

Here is the caller graph for this function:

12.42.4.17 bool KeyMap::isMouse ( ) const [inline]

Definition at line 96 of file keymap.h.

References isMouse(), and keyModel.

Referenced by isKeyboard(), Kb::isMouse(), isMouse(), and KeyWidget::paintEvent().

```
96 { return isMouse(keyModel); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.18 Key KeyMap::key (const QString & *name*) const [inline]

Definition at line 125 of file keymap.h.

References _keys.

Referenced by AnimScript::begin(), byPosition(), AnimScript::keypress(), KbBind::noAction(), operator[]() , KbBind::setAction(), and toStorage().

```
125 { Key empty = {0,0,0,0,0,0,0,0,0}; return _keys.value(name, empty); }
```

Here is the caller graph for this function:

12.42.4.19 QStringList KeyMap::keys ( ) const [inline]

Definition at line 131 of file keymap.h.

References _keys.

Referenced by KeyWidget::mouseReleaseEvent(), KbBindWidget::on_copyButton_clicked(), KbBindWidget::on_resetButton_clicked(), KeyWidget::setAnimation(), KeyWidget::setSelection(), and KbBindWidget::updateBind().

```
131 { return _keys.keys(); }
```

Here is the caller graph for this function:

12.42.4.20 Layout KeyMap::layout ( ) const [inline]

Definition at line 114 of file keymap.h.

References keyLayout.

Referenced by KeyAction::friendlyName(), KeyWidget::paintEvent(), and RebindWidget::setBind().

```
114 { return keyLayout; }
```

Here is the caller graph for this function:

12.42.4.21 QStringList KeyMap::layoutNames ( ) [static]

Definition at line 479 of file keymap.cpp.

Referenced by LayoutDialog::LayoutDialog(), and SettingsWidget::SettingsWidget().

```
479                                {
480     return QStringList()
481             << "Danish"
482             << "English (ISO/European)" << "English (ISO/European, Dvorak)"
483             << "English (United Kingdom)" << "English (United Kingdom, Dvorak)"
484             << "English (United States)" << "English (United States, Dvorak)"
485             << "French"
486             << "German"
487             << "Italian"
488             << "Norwegian"
489             << "Polish"
490             << "Spanish (Latin America)"
491             << "Spanish (Spain)"
492             << "Swedish";
493 }
```

Here is the caller graph for this function:

12.42.4.22 KeyMap::Layout KeyMap::locale ( ) [static]

Definition at line 375 of file keymap.cpp.

References DE, DK, ES, FR, GB, IT, MX, NO, PL, SE, and US.

Referenced by SettingsWidget::SettingsWidget().

```
375                                 {
376     setlocale(LC_ALL, "");
377     QString loc = setlocale(LC_CTYPE, 0);
378     loc = loc.toLower().replace('_', '-');
379     if(loc.startsWith("dk-"))
380         return KeyMap::DK;
381     else if(loc.startsWith("fr-"))
382         return KeyMap::FR;
383     else if(loc.startsWith("de-"))
384         return KeyMap::DE;
385     else if(loc.startsWith("it-"))
386         return KeyMap::IT;
387     else if(loc.startsWith("pl-"))
388         return KeyMap::PL;
389     else if(loc.startsWith("no-"))
390         return KeyMap::NO;
391     else if(loc.startsWith("es-es"))
392         // Spain uses the ES layout
393         return KeyMap::ES;
394     else if(loc.startsWith("es-"))
395         // Other Spanish locales use MX
396         return KeyMap::MX;
397     else if(loc.startsWith("se-"))
398         return KeyMap::SE;
399     else if(loc.startsWith("en-us") || loc.startsWith("en-au") || loc.startsWith("en-ca") || loc.startsWith
      ("en-hk") || loc.startsWith("en-in") || loc.startsWith("en-nz") || loc.startsWith("en-ph") || loc.startsWith
      ("en-sg") || loc.startsWith("en-za"))
400         // Most English locales use US
401         return KeyMap::US;
402     else
403         // Default to GB
404         return KeyMap::GB;
405 }
```

Here is the caller graph for this function:

12.42.4.23 const QHash<QString, Key>& KeyMap::map ( ) const [inline]

Definition at line 129 of file keymap.h.

References _keys.

Referenced by friendlyName().

```
129 { return _keys; }
```

Here is the caller graph for this function:

12.42.4.24 Model KeyMap::model ( ) const [inline]

Definition at line 113 of file keymap.h.

References keyModel.

Referenced by KeyWidget::mouseMoveEvent(), KeyWidget::paintEvent(), and KPerfWidget::setPerf().

```
113 { return keyModel; }
```

Here is the caller graph for this function:

12.42.4.25 int KeyMap::modelHeight (Model *model*) [static],[private]

Definition at line 561 of file keymap.cpp.

References K65, K70, K95, K95_HEIGHT, M65, M65_HEIGHT, SABRE, SCIMITAR, and STRAFE.

```
561                                     {
562     switch(model){
563     case K65:
564     case K70:
565     case K95:
566     case STRAFE:
567         return K95_HEIGHT;
568     case M65:
569     case SABRE:
570     case SCIMITAR:
571         return M65_HEIGHT;
572     default:
573         return 0;
574     }
575 }
```

12.42.4.26 int KeyMap::modelWidth (Model *model*) [static],[private]

Definition at line 542 of file keymap.cpp.

References K65, K65_WIDTH, K70, K70_WIDTH, K95, K95_WIDTH, KSTRAFE_WIDTH, M65, M65_WIDTH, SABRE, SCIMITAR, and STRAFE.

```
542                                     {
543     switch(model){
544     case K65:
545         return K65_WIDTH;
546     case K70:
547         return K70_WIDTH;
548     case K95:
549         return K95_WIDTH;
550     case STRAFE:
551         return KSTRAFE_WIDTH;
552     case M65:
553     case SABRE:
554     case SCIMITAR:
555         return M65_WIDTH;
556     default:
557         return 0;
558     }
559 }
```

12.42.4.27 QString KeyMap::name ( ) const [inline]

Definition at line 115 of file keymap.h.

References strLayout(), and strModel().

Referenced by KbBind::save(), KbLight::save(), and toStorage().

```
115 { return (strModel() + " " + strLayout()).toUpper(); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.28 KeyMap::operator const QHash< QString, Key > & ( ) const [inline]

Definition at line 130 of file keymap.h.

References _keys.

```
130 { return _keys; }
```

12.42.4.29 Key KeyMap::operator[] (const QString & *name*) const [inline]

Definition at line 126 of file keymap.h.

References key().

```
126 { return key(name); }
```

Here is the call graph for this function:

12.42.4.30 QList<Key> KeyMap::positions ( ) const [inline]

Definition at line 132 of file keymap.h.

References _keys.

Referenced by ColorMap::init(), and KeyWidget::selectAll().

```
132 { return _keys.values(); }
```

Here is the caller graph for this function:

12.42.4.31 QString KeyMap::strLayout ( ) const [inline]

Definition at line 106 of file keymap.h.

References getLayout(), and keyLayout.

Referenced by name().

```
106 { return getLayout(keyLayout); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.32 QString KeyMap::strModel ( ) const [inline]

Definition at line 110 of file keymap.h.

References getModel(), and keyModel.

Referenced by name().

```
110 { return getModel(keyModel); }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.42.4.33 QString KeyMap::toStorage (const QString & *name*) [inline]

Definition at line 134 of file keymap.h.

References key(), name(), and Key::storageName().

```
134 { const char* storage = key(name).storageName(); if(!storage) return
      name; return storage; }
```

Here is the call graph for this function:

12.42.4.34 uint KeyMap::width ( ) const [inline]

Definition at line 120 of file keymap.h.

References keyWidth.

Referenced by KeyWidget::drawInfo(), and KeyWidget::map().

```
120 { return keyWidth; }
```

Here is the caller graph for this function:

12.42.5 Field Documentation

12.42.5.1 QHash<QString, Key> KeyMap::_keys [private]

Definition at line 147 of file keymap.h.

Referenced by contains(), count(), key(), keys(), map(), operator const QHash< QString, Key > &(), and positions().

12.42.5.2 short KeyMap::keyHeight [private]

Definition at line 148 of file keymap.h.

Referenced by height().

12.42.5.3 Layout KeyMap::keyLayout [private]

Definition at line 150 of file keymap.h.

Referenced by isISO(), layout(), and strLayout().

12.42.5.4 Model KeyMap::keyModel [private]

Definition at line 149 of file keymap.h.

Referenced by isKeyboard(), isMouse(), model(), and strModel().

12.42.5.5 short KeyMap::keyWidth [private]

Definition at line 148 of file keymap.h.

Referenced by width().

The documentation for this class was generated from the following files:

- src/ckb/keymap.h
- src/ckb/keymap.cpp

12.43 KeyWidget Class Reference

```
#include <src/ckb/keywidget.h>
```

Inheritance diagram for KeyWidget:

Collaboration diagram for KeyWidget:

Public Types

- typedef QHash< QString, QString > BindMap

Public Slots

- void displayColorMap (const ColorMap &newDisplayMap, const QSet< QString > &indicators=QSet< QString >())

Signals

- void selectionChanged (QStringList selected)
- void sidelightToggled ()

Public Member Functions

- KeyWidget (QWidget *parent=0, bool rgbMode=true)
- bool rgbMode ()
- void rgbMode (bool newRgbMode)
- bool monochrome ()
- void monochrome (bool newMono)
- const KeyMap & map () const
- void map (const KeyMap &newMap)
- const QColorMap & colorMap () const
- void colorMap (const QColorMap &newColorMap)
- const BindMap & bindMap () const
- void bindMap (const BindMap &newBindMap)
- void setSelection (const QStringList &keys)
- void selectAll ()
- void clearSelection ()

- void setAnimation (const QStringList &keys)
- void setAnimationToSelection ()
- void clearAnimation ()

Private Types

- enum {
  NONE, SET, ADD, SUBTRACT,
  TOGGLE }

Private Member Functions

- void paintEvent (QPaintEvent ∗)
- void mousePressEvent (QMouseEvent ∗event)
- void mouseMoveEvent (QMouseEvent ∗event)
- void mouseReleaseEvent (QMouseEvent ∗event)
- void drawInfo (float &scale, float &offsetX, float &offsetY, int ratio=1)

Private Attributes

- KeyMap keyMap
- QColorMap _colorMap
- ColorMap _displayColorMap
- BindMap _bindMap
- QSet< QString > _indicators
- QBitArray selection
- QBitArray newSelection
- QBitArray animation
- int mouseDownX
- int mouseDownY
- int mouseCurrentX
- int mouseCurrentY
- enum KeyWidget:: { ... } mouseDownMode
- bool _rgbMode
- bool _monochrome

12.43.1 Detailed Description

Definition at line 11 of file keywidget.h.

12.43.2 Member Typedef Documentation

12.43.2.1 typedef QHash<QString, QString> KeyWidget::BindMap

Definition at line 30 of file keywidget.h.

12.43.3 Member Enumeration Documentation

12.43.3.1 anonymous enum [private]

Enumerator

NONE

SET

ADD

SUBTRACT

TOGGLE

Definition at line 66 of file keywidget.h.

```
66          {
67         NONE,
68         SET,
69         ADD,
70         SUBTRACT,
71         TOGGLE,
72     } mouseDownMode;
```

12.43.4 Constructor & Destructor Documentation

12.43.4.1 KeyWidget::KeyWidget (QWidget * *parent* = 0, bool *rgbMode* = true) [explicit]

Definition at line 17 of file keywidget.cpp.

```
17                                                  :
18     QWidget(parent), mouseDownX(-1), mouseDownY(-1),
      mouseCurrentX(-1), mouseCurrentY(-1), mouseDownMode(
      NONE), _rgbMode(rgbMode), _monochrome(false)
19 {
20     setMouseTracking(true);
21     setAutoFillBackground(false);
22 }
```

12.43.5 Member Function Documentation

12.43.5.1 const BindMap& KeyWidget::bindMap ( ) const [inline]

Definition at line 31 of file keywidget.h.

References _bindMap.

Referenced by KbBindWidget::updateBind().

```
31 { return _bindMap; }
```

Here is the caller graph for this function:

12.43.5.2 void KeyWidget::bindMap (const BindMap & *newBindMap*)

Definition at line 65 of file keywidget.cpp.

References _bindMap.

```
65                                                  {
66     _bindMap = newBindMap;
67     update();
68 }
```

12.43.5.3 void KeyWidget::clearAnimation ( )

Definition at line 632 of file keywidget.cpp.

References animation.

Referenced by KbLightWidget::setLight().

```
632                                 {
633     animation.fill(false);
634     update();
635 }
```

Here is the caller graph for this function:

12.43.5.4 void KeyWidget::clearSelection ( )

Definition at line 605 of file keywidget.cpp.

References mouseDownMode, newSelection, NONE, selection, and selectionChanged().

Referenced by KbLightWidget::changeAnim(), KbBindWidget::setBind(), and KbLightWidget::setLight().

```
605                                 {
606     selection.fill(false);
607     newSelection.fill(false);
608     mouseDownMode = NONE;
609     update();
610     emit selectionChanged(QStringList());
611 }
```

Here is the caller graph for this function:

12.43.5.5 const QColorMap& KeyWidget::colorMap ( ) const [inline]

Definition at line 27 of file keywidget.h.

References _colorMap.

Referenced by KbLightWidget::changeColor(), KbLightWidget::toggleSidelight(), and KbLightWidget::updateLight().

```
27 { return _colorMap; }
```

Here is the caller graph for this function:

12.43.5.6 void KeyWidget::colorMap (const QColorMap & *newColorMap*)

Definition at line 52 of file keywidget.cpp.

References _colorMap.

```
52                                                  {
53     _colorMap = newColorMap;
54     update();
55 }
```

12.43.5.7 void KeyWidget::displayColorMap (const ColorMap & *newDisplayMap*, const QSet< QString > & *indicators* = QSet<QString>()) [slot]

Definition at line 57 of file keywidget.cpp.

References _displayColorMap, and _indicators.

Referenced by KbLightWidget::on_showAnimBox_clicked().

```
57                                                                                                  {
58     if(!isVisible())
59         return;
60     _displayColorMap = newDisplayMap;
61     _indicators = indicators;
62     update();
63 }
```

Here is the caller graph for this function:

12.43.5.8 void KeyWidget::drawInfo (float & *scale*, float & *offsetX*, float & *offsetY*, int *ratio* = 1) [private]

Definition at line 43 of file keywidget.cpp.

References KeyMap::height(), KEY_SIZE, keyMap, and KeyMap::width().

Referenced by mouseMoveEvent(), mousePressEvent(), and paintEvent().

```
43                                                                                  {
44     int w = width() * ratio, h = height() * ratio;
45     float xScale = (float)w / (keyMap.width() + KEY_SIZE);
46     float yScale = (float)h / (keyMap.height() + KEY_SIZE);
47     scale = fmin(xScale, yScale);
48     offsetX = (w / scale - keyMap.width()) / 2.f;
49     offsetY = (h / scale - keyMap.height()) / 2.f;
50 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.43.5.9 const KeyMap& KeyWidget::map ( ) const [inline]

Definition at line 24 of file keywidget.h.

References keyMap.

Referenced by KbBindWidget::newLayout(), and KbLightWidget::updateLight().

```
24 { return keyMap; }
```

Here is the caller graph for this function:

12.43.5.10 void KeyWidget::map (const KeyMap & *newMap*)

Definition at line 24 of file keywidget.cpp.

References animation, KeyMap::count(), KeyMap::height(), KeyMap::isMouse(), KEY_SIZE, keyMap, newSelection, selection, and KeyMap::width().

```
24                                          {
25     keyMap = newMap;
26     selection = QBitArray(keyMap.count());
27     newSelection = QBitArray(keyMap.count());
28     animation = QBitArray(keyMap.count());
29     int width, height;
30     if(keyMap.isMouse()){
31         width = (keyMap.width() + KEY_SIZE) * 2.6;
32         height = (keyMap.height() + KEY_SIZE) * 2.6;
33     } else {
34         width = (keyMap.width() + KEY_SIZE) * 2.3;
35         height = (keyMap.height() + KEY_SIZE) * 2.3;
36     }
37     if(width < 500)
38         width = 500;
39     setFixedSize(width, height);
40     update();
41 }
```

Here is the call graph for this function:

12.43.5.11 bool KeyWidget::monochrome ( ) [inline]

Definition at line 20 of file keywidget.h.

References _monochrome.

Referenced by KbLightWidget::setMonochrome().

```
20 { return _monochrome; }
```

Here is the caller graph for this function:

12.43.5.12 void KeyWidget::monochrome (bool *newMono*) [inline]

Definition at line 21 of file keywidget.h.

References _monochrome.

```
21 { _monochrome = newMono; update(); }
```

12.43.5.13 void KeyWidget::mouseMoveEvent (QMouseEvent * *event*) [private]

Definition at line 475 of file keywidget.cpp.

References _indicators, _rgbMode, drawInfo(), Key::friendlyName(), Key::hasLed, Key::hasScan, Key::height, keyMap, KeyMap::model(), mouseCurrentX, mouseCurrentY, mouseDownMode, mouseDownX, mouseDownY, Key::name, newSelection, NONE, KeyMap::STRAFE, Key::width, Key::x, and Key::y.

```
475                                                 {
476     event->accept();
477     QString tooltip;
478
479     // Find selection rectangle
480     mouseCurrentX = event->x();
481     mouseCurrentY = event->y();
482     float scale, offX, offY;
483     drawInfo(scale, offX, offY);
484     float mx = mouseCurrentX / scale - offX, my = mouseCurrentY / scale - offY;
485     float mx1, mx2, my1, my2;
486     if(mouseCurrentX >= mouseDownX){
487         mx1 = mouseDownX / scale - offX;
488         mx2 = mouseCurrentX / scale - offX;
489     } else {
490         mx1 = mouseCurrentX / scale - offX;
491         mx2 = mouseDownX / scale - offX;
492     }
493     if(mouseCurrentY >= mouseDownY){
494         my1 = mouseDownY / scale - offY;
495         my2 = mouseCurrentY / scale - offY;
496     } else {
497         my1 = mouseCurrentY / scale - offY;
498         my2 = mouseDownY / scale - offY;
499     }
500     // Clear new selection
501     if(mouseDownMode != NONE)
502         newSelection.fill(false);
503     // See if the event hit any keys
504     QHashIterator<QString, Key> k(keyMap);
505     uint i = -1;
506     while(k.hasNext()){
507         k.next();
508         i++;
509         const Key& key = k.value();
510         if((_rgbMode && !key.hasLed)
511                 || (!_rgbMode && !key.hasScan))
512             continue;
513         // Update tooltip with the mouse hover (if any), even if it's not selectable
514         if(fabs(key.x - mx) <= key.width / 2.f - 1.f && fabs(key.y - my) <= key.
```

```
height / 2.f - 1.f
                && tooltip.isEmpty())
            tooltip = key.friendlyName(false);
        // on STRAFE Sidelights and indicators can't be assigned color the way other keys are colored
        if(keyMap.model() == KeyMap::STRAFE && (!strcmp(key.name, "lsidel") || !strcmp(key.name, "rsidel") || _indicators.contains(key.name))) // FIX: _indicators check fails whenever _indicators is empty because "show animated" is unchecked
            continue;
        float kx1 = key.x - key.width / 2.f + 1.f;
        float ky1 = key.y - key.height / 2.f + 1.f;
        float kx2 = kx1 + key.width - 2.f;
        float ky2 = ky1 + key.height - 2.f;
        // If they overlap, add the key to the selection
        if(!(mx1 >= kx2 || kx1 >= mx2)
                && !(my1 >= ky2 || ky1 >= my2)
                && mouseDownMode != NONE)
            newSelection.setBit(i);
    }

    if(mouseDownMode != NONE)
        update();
    setToolTip(tooltip);
}
```

Here is the call graph for this function:

12.43.5.14 void KeyWidget::mousePressEvent (QMouseEvent * *event*) [private]

Definition at line 443 of file keywidget.cpp.

References _rgbMode, ADD, drawInfo(), Key::hasLed, Key::hasScan, Key::height, keyMap, mouseCurrentX, mouseCurrentY, mouseDownMode, mouseDownX, mouseDownY, Key::name, newSelection, SET, sidelightToggled(), SUBTRACT, TOGGLE, Key::width, Key::x, and Key::y.

```
443                                                 {
444     event->accept();
445     mouseDownMode = (event->modifiers() & Qt::AltModifier) ? SUBTRACT : (event->modifiers() & Qt::ControlModifier) ? TOGGLE : SET;
446     mouseDownX = mouseCurrentX = event->x();
447     mouseDownY = mouseCurrentY = event->y();
448     // See if the event hit a key
449     float scale, offX, offY;
450     drawInfo(scale, offX, offY);
451     float mx = mouseCurrentX / scale - offX, my = mouseCurrentY / scale - offY;
452     QHashIterator<QString, Key> k(keyMap);
453     uint i = -1;
454     while(k.hasNext()){
455         k.next();
456         i++;
457         const Key& key = k.value();
458         if((_rgbMode && !key.hasLed)
459                 || (!_rgbMode && !key.hasScan))
460             continue;
461         if(fabs(key.x - mx) <= key.width / 2.f - 1.f && fabs(key.y - my) <= key.height / 2.f - 1.f){
462             // Sidelights can't have a color, but they can be toggled
463             if(!strcmp(key.name, "lsidel") || !strcmp(key.name, "rsidel")){
```

```
                emit sidelightToggled(); // get the kblightwidget to record it
                update();
                break;
            }
            newSelection.setBit(i);
            update();
            break;
        }
    }
}
```

Here is the call graph for this function:

12.43.5.15 void KeyWidget::mouseReleaseEvent (QMouseEvent * *event*) [private]

Definition at line 536 of file keywidget.cpp.

References ADD, keyMap, KeyMap::keys(), mouseDownMode, newSelection, NONE, selection, selectionChanged(), SET, SUBTRACT, and TOGGLE.

```
536                                                 {
537     event->accept();
538     if(mouseDownMode == NONE)
539         return;
540     // Apply the new selection
541     switch(mouseDownMode){
542     case SET:
543         selection = newSelection;
544         break;
545     case ADD:
546         selection |= newSelection;
547         break;
548     case SUBTRACT:
549         selection &= ~newSelection;
550         break;
551     case TOGGLE:
552         selection ^= newSelection;
553         break;
554     default:;
555     }
556     // Clear mousedown state.
557     newSelection.fill(false);
558     mouseDownMode = NONE;
559     // Emit signal with the names of the keys
560     QStringList selectedNames;
561     uint i = 0;
562     foreach(const QString& key, keyMap.keys()){
563         if(selection.testBit(i++))
564             selectedNames << key;
565     }
566     emit selectionChanged(selectedNames);
567     update();
568 }
```

Here is the call graph for this function:

12.43.5.16 void KeyWidget::paintEvent (QPaintEvent *) [private]

Definition at line 70 of file keywidget.cpp.

References _bindMap, _colorMap, _displayColorMap, _indicators, _monochrome, _rgbMode, ADD, animation, ColorMap::colorForName(), KbBind::defaultAction(), drawInfo(), KeyMap::EU, KeyMap::EU_DVORAK, Key::friendlyName(), KbBind::globalRemap(), Key::hasLed, Key::hasScan, Key::height, KeyMap::isMouse(), KeyMap::K65, keyMap, KeyMap::layout(), KeyMap::M65, m65Overlay, KeyMap::model(), monoRgb(), mouseCurrentX, mouseCurrentY, mouseDownMode, mouseDownX, mouseDownY, Key::name, newSelection, NONE, sabOverlay, KeyMap::SABRE, KeyMap::SCIMITAR, scimOverlay, selection, SET, KeyMap::STRAFE, SUBTRACT, TOGGLE, Key::width, Key::x, and Key::y.

```
70                                      {
71     const QColor bgColor(68, 64, 64);
72     const QColor keyColor(112, 110, 110);
73     const QColor sniperColor(130, 90, 90);
74     const QColor thumbColor(34, 32, 32);
75     const QColor transparentColor(0, 0, 0, 0);
76     const QColor highlightColor(136, 176, 240);
77     const QColor highlightAnimColor(136, 200, 240);
78     const QColor animColor(112, 200, 110);
79
80     // Determine which keys to highlight
81     QBitArray highlight;
82     switch(mouseDownMode){
83     case SET:
84         highlight = newSelection;
85         break;
86     case ADD:
87         highlight = selection | newSelection;
88         break;
89     case SUBTRACT:
90         highlight = selection & ~newSelection;
91         break;
92     case TOGGLE:
93         highlight = selection ^ newSelection;
94         break;
95     default:
96         highlight = selection;
97     }
98
99     QPainter painter(this);
100 #if QT_VERSION >= QT_VERSION_CHECK(5, 3, 0)
101     int ratio = painter.device()->devicePixelRatio();
102 #else
103     int ratio = 1;
104 #endif
105     int wWidth = width(), wHeight = height();
106     KeyMap::Model model = keyMap.model();
107     KeyMap::Layout layout = keyMap.layout();
108     float scale, offX, offY;
109     drawInfo(scale, offX, offY, ratio);
110     // Draw background
111     painter.setPen(Qt::NoPen);
112     painter.setRenderHint(QPainter::Antialiasing, true);
113
114     if(keyMap.isMouse()){
115         // Draw mouse overlays
116         const QImage* overlay = 0;
117         float xpos = 0.f, ypos = 0.f;
118         if(model == KeyMap::M65){
```

```
            if(!m65Overlay)
                m65Overlay = new QImage(":/img/overlay_m65.png");
            overlay = m65Overlay;
            xpos = 2.f;
            ypos = -2.f;
        } else if(model == KeyMap::SABRE){
            if(!sabOverlay)
                sabOverlay = new QImage(":/img/overlay_sabre.png");
            overlay = sabOverlay;
            xpos = 1.f;
            ypos = -2.f;
        } else if(model == KeyMap::SCIMITAR){
            if(!scimOverlay)
                scimOverlay = new QImage(":/img/overlay_scimitar.png");
            overlay = scimOverlay;
            xpos = 3.5f;
            ypos = -2.f;
        }
        if(overlay){
            painter.setBrush(palette().brush(QPalette::Window));
            painter.drawRect(0, 0, width(), height());
            float oXScale = scale / 9.f, oYScale = scale / 9.f;             // The overlay has a resolution of 9px per keymap unit
            float x = (xpos + offX) * scale, y = (ypos + offY) * scale;
            int w = overlay->width() * oXScale, h = overlay->height() * oYScale;
            // We need to transform the image with QImage::scaled() because painter.drawImage() will butcher it, even with smoothing enabled
            // However, the width/height need to be rounded to integers
            int iW = round(w), iH = round(h);
            painter.drawImage(QRectF((x - (iW - w) / 2.f) / ratio, (y - (iH - h) / 2.f) / ratio, iW / ratio, iH / ratio), overlay->scaled(iW, iH, Qt::IgnoreAspectRatio, Qt::SmoothTransformation));
        }
    } else {
        // Otherwise, draw a solid background
        painter.setBrush(QBrush(bgColor));
        painter.drawRect(0, 0, width(), height());
    }

    // Draw mouse highlight (if any)
    if(mouseDownMode != NONE && (mouseDownX != mouseCurrentX || mouseDownY != mouseCurrentY)){
        int x1 = (mouseDownX > mouseCurrentX) ? mouseCurrentX : mouseDownX;
        int x2 = (mouseDownX > mouseCurrentX) ? mouseDownX : mouseCurrentX;
        int y1 = (mouseDownY > mouseCurrentY) ? mouseCurrentY : mouseDownY;
        int y2 = (mouseDownY > mouseCurrentY) ? mouseDownY : mouseCurrentY;
        painter.setPen(QPen(highlightColor, 0.5));
        QColor bColor = highlightColor;
        bColor.setAlpha(128);
        painter.setBrush(QBrush(bColor));
        painter.drawRect(x1, y1, x2 - x1, y2 - y1);
    }

    // Draw key backgrounds on a separate pixmap so that a drop shadow can be applied to them.
    QPixmap keyBG(wWidth * ratio, wHeight * ratio);
    keyBG.fill(QColor(0, 0, 0, 0));
    QPainter bgPainter(&keyBG);
    bgPainter.setRenderHints(QPainter::Antialiasing | QPainter::TextAntialiasing);
    bgPainter.setPen(Qt::NoPen);
    QHashIterator<QString, Key> k(keyMap);
    uint i = -1;
    while(k.hasNext()){
        k.next();
        i++;
        const Key& key = k.value();
        float x = key.x + offX - key.width / 2.f + 1.f;
        float y = key.y + offY - key.height / 2.f + 1.f;
        float w = key.width - 2.f;
        float h = key.height - 2.f;
        // In RGB mode, ignore keys without LEDs
        if((_rgbMode && !key.hasLed)
                || (!_rgbMode && !key.hasScan))
            continue;
        // Set color based on key highlight
        bgPainter.setOpacity(1.);
        if(highlight.testBit(i)){
            if(animation.testBit(i))
                bgPainter.setBrush(QBrush(highlightAnimColor));
            else
                bgPainter.setBrush(QBrush(highlightColor));
        } else if(animation.testBit(i)){
            bgPainter.setBrush(QBrush(animColor));
        } else {
            if(!strcmp(key.name, "sniper"))
```

```
                // Sniper key uses a reddish base color instead of the usual grey
                bgPainter.setBrush(QBrush(sniperColor));
            else if(model == KeyMap::SCIMITAR && !strncmp(key.name, "thumb", 5) && strcmp(key.name, "thumb"))
                // Thumbgrid keys use a black color
                bgPainter.setBrush(QBrush(thumbColor));
            else if(!strcmp(key.name, "lsidel") || !strcmp(key.name, "rsidel") || !strcmp(key.name, "logo"))
                // Strafe side lights have different background
                bgPainter.setBrush(QBrush(transparentColor));
            else {
                bgPainter.setBrush(QBrush(keyColor));
                if(KeyMap::isMouse(model))
                    bgPainter.setOpacity(0.7);
            }
        }
        if(model != KeyMap::STRAFE && (!strcmp(key.name, "mr") || !strcmp(key.name, "m1") || !strcmp(key.name, "m2") || !strcmp(key.name, "m3")
                || !strcmp(key.name, "light") || !strcmp(key.name, "lock") || (model == KeyMap::K65 && !strcmp(key.name, "mute")))){
            // Switch keys are circular except for Strafe. All Strafe keys are square
            x += w / 8.f;
            y += h / 8.f;
            w *= 0.75f;
            h *= 0.75f;
            bgPainter.drawEllipse(QRectF(x * scale, y * scale, w * scale, h * scale));
        } else {
            if(!strcmp(key.name, "enter")){
                if(key.height == 24){
                    // ISO enter key isn't rectangular
                    y = key.y + 1.f;
                    h = 10.f;
                    bgPainter.drawRect(QRectF((x + w - 13.f) * scale, y * scale, 13.f * scale, 22.f * scale));
                } else {
                    // US enter key isn't perfectly centered, needs an extra pixel on the left to appear correctly
                    x -= 1.f;
                    w += 1.f;
                }
            } else if(!strcmp(key.name, "rshift") || !strcmp(key.name, "stop")){
                // A few other keys also need extra pixels
                x -= 1.f;
                w += 1.f;
            } else if(!strcmp(key.name, "caps") || !strcmp(key.name, "lshift") || !strcmp(key.name, "next")){
                w += 1.f;
            }
            bgPainter.drawRect(QRectF(x * scale, y * scale, w * scale, h * scale));
        }
    }

    // Render the key decorations (RGB -> light circles, binding -> key names) on yet another layer
    QPixmap decoration(wWidth * ratio, wHeight * ratio);
    decoration.fill(QColor(0, 0, 0, 0));
    QPainter decPainter(&decoration);
    decPainter.setRenderHints(QPainter::Antialiasing | QPainter::TextAntialiasing);
    if(_rgbMode){
        // Draw key colors (RGB mode)
        QHashIterator<QString, Key> k(keyMap);
        uint i = -1;
        while(k.hasNext()){
            k.next();
            i++;
            const Key& key = k.value();
            if(!key.hasLed)
                continue;
            float x = key.x + offX - 1.8f;
            float y = key.y + offY - 1.8f;
            float w = 3.6f;
            float h = 3.6f;
            // Display a white circle around regular keys, red circle around indicators
            if(_indicators.contains(key.name))
                decPainter.setPen(QPen(QColor(255, 248, 136), 1.5));
            else
                decPainter.setPen(QPen(QColor(255, 255, 255), 1.5));
            QRgb color;
            const QRgb* inDisplay = _displayColorMap.colorForName(key.name);
            if(inDisplay)
                // Color in display map? Grab it from there
                // (monochrome conversion not necessary as this would have been done by the animation)
                color = *inDisplay;
            else {
                // Otherwise, read from base map
                color = _colorMap.value(k.key());
                if(_monochrome)
```

```
                    color = monoRgb(qRed(color), qGreen(color), qBlue(color));
            }
            decPainter.setBrush(QBrush(color));
            if (model == KeyMap::STRAFE) { // STRAFE custom design and special keys
                float kx = key.x + offX - key.width / 2.f + 1.f;
                float ky = key.y + offY - key.height / 2.f + 1.f;
                float kw = key.width - 2.f;
                float kh = key.height - 2.f;
                decPainter.setPen(QPen(QColor(255, 255, 255), 1.2)); // less invasive outline to show the key color better
                if(!strcmp(key.name, "logo")) { // stylized logo
                    float lx = key.x + offX - key.width / 2.f + 2.f;
                    float ly = key.y + offY - key.height / 2.f + 2.f;
                    float lw = key.width - 4.f;
                    float lh = key.height - 4.f;
                    QPainterPath logo;
                    logo.moveTo(lx*scale,(ly+lh)*scale);
                    logo.quadTo((lx+2.f)*scale,(ly+lh/2.f)*scale,lx*scale,ly*scale);
                    logo.quadTo((lx+lw)*scale,ly*scale,(lx+lw)*scale,(ly+lh)*scale);
                    logo.quadTo((lx+lw/2.f)*scale,(ly+lh-4.f)*scale,lx*scale,(ly+lh)*scale);
                    decPainter.drawPath(logo);
                    //decPainter.setPen(QPen(Qt::green, 1.2)); //QColor(125,125,125)
                    //decPainter.drawRect(QRectF(lx * scale, ly * scale, lw * scale, lh * scale)); // don't really know why the 12 and 24 make it work here, but they do
                } else if(!strcmp(key.name, "lsidel") || !strcmp(key.name, "rsidel")) { // Strafe side lights (toggle lights with no animation)
                    QRadialGradient gradient(QPointF(wWidth/2.f * ratio, wHeight/2.f * ratio), wWidth/2.f * ratio);//,QPointF(10, 5));
                    gradient.setColorAt(0, color);
                    gradient.setColorAt(0.9, color); // bring up intensity
                    gradient.setColorAt(1, bgColor);
                    decPainter.setBrush(QBrush(gradient));
                    decPainter.setPen(QPen(keyColor, 1.2)); //QColor(125,125,125)
                    decPainter.drawRect(QRectF(kx * scale, ky * scale - 12 , kw * scale, kh * scale+24)); // don't really know why the 12 and 24 make it work here, but they do
                } else if(_indicators.contains(key.name)) { // FIX: This check fails whenever _indicators is empty because "show animated" is unchecked
                    decPainter.setPen(QPen(QColor(0,0,0,0), 1));    // no outline for the indicators, you can't change their color the standard way
                    decPainter.drawRect(QRectF((kx+2.f) * scale, (ky+2.f) * scale, (kw-4.f) * scale, (kh-4.f) * scale)); // square indicators
                } else //everything else is a circle, just a tad bigger to show the key color better
                    decPainter.drawEllipse(QRectF((x-1.f) * scale, (y-1.f) * scale, (w+2.f) * scale, (h+2.f) * scale));
            } else
                decPainter.drawEllipse(QRectF(x * scale, y * scale, w * scale, h * scale));
        }
    } else {
        // Draw key names
        decPainter.setBrush(Qt::NoBrush);
        QFont font = painter.font();
        font.setBold(true);
        font.setPixelSize(5.25f * scale);
        QFont font0 = font;
        QHashIterator<QString, Key> k(keyMap);
        uint i = -1;
        while(k.hasNext()){
            k.next();
            i++;
            const Key& key = k.value();
            if(!key.hasScan)
                continue;
            float x = key.x + offX - key.width / 2.f + 1.f;
            float y = key.y + offY - key.height / 2.f;
            float w = key.width - 2.f;
            float h = key.height;
            // Print the key's friendly name (with some exceptions)
            QString keyName = KbBind::globalRemap(key.name);
            QString name = key.friendlyName(false);
            name = name.split(" ").last();
            struct {
                const char* keyName, *displayName;
            } names[] = {
                {"light", ""}, {"lock", ""}, {"mute", ""}, {"volup", keyMap.model() == KeyMap::K65 ? ")" : ""}, {"voldn", keyMap.model() == KeyMap::K65 ? ")" : ""},
                {"prtscn",  "PrtScn\nSysRq"}, {"scroll", "Scroll\nLock"}, {"pause", "Pause\nBreak"}, {"stop", ""}, {"prev", "|"}, {"play", "||"}, {"next", "|"},
                {"pgup", "Page\nUp"}, {"pgdn", "Page\nDown"}, {"numlock", "Num\nLock"},
                {"caps", "Caps"}, {"lshift", "Shift"}, {"rshift", "Shift"},
#ifdef Q_OS_MACX
                {"lctrl", ""}, {"rctrl", ""}, {"lwin", ""}, {"rwin", ""}, {"lalt", ""}, {"ralt", ""},
#else
                {"lctrl", "Ctrl"}, {"rctrl", "Ctrl"}, {"lwin", ""}, {"rwin", ""}, {"lalt", "Alt"}, {"ralt", "Alt"},
#endif
                {"rmenu", ""}, {"up", ""}, {"left", ""}, {"down", ""}, {"right", ""}, {"fn","Fn"},
```

```
                {"mouse1", ""}, {"mouse2", ""}, {"mouse3", ""}, {"dpiup", ""}, {"dpidn", ""}, {"wheelup", ""}, {"wheeldn", ""}, {"dpi", ""}, {"mouse5", ""}, {"mouse4", ""}, {"sniper", ""}
            };
            for(uint k = 0; k < sizeof(names) / sizeof(names[0]); k++){
                if(keyName == names[k].keyName){
                    name = names[k].displayName;
                    break;
                }
            }
            if(keyName == "thumb1" && model == KeyMap::SABRE)
                name = "";
            if(keyName == "mr" || keyName == "m1" || keyName == "m2" || keyName == "m3" || keyName == "up" || keyName == "down" || keyName == "left" || keyName == "right")
                // Use a smaller size for MR, M1 - M3, and arrow keys
                font.setPixelSize(font.pixelSize() * 0.75);
            else if(keyName == "end")
                // Use a smaller size for "End" to match everything else in that area
                font.setPixelSize(font.pixelSize() * 0.65);
            else if(keyName == "light"
#ifndef Q_OS_MACX
                    || keyName == "lwin" || keyName == "rwin"
#endif
                    )
                // Use a larger font size for Super (Linux only) and Brightness to compensate for the unicode symbols looking smaller
                font.setPixelSize(font.pixelSize() * 1.3);
            if((layout == KeyMap::EU || layout == KeyMap::EU_DVORAK) && (keyName == "hash" || keyName == "bslash_iso"))
                // Don't differentiate backslashes on the EU layout
                name = "\\";
            // Determine the appropriate size to draw the text at
            decPainter.setFont(font);
            QRectF rect(x * scale, y * scale - 1, w * scale, h * scale);
            int flags = Qt::AlignHCenter | Qt::AlignVCenter | Qt::TextWordWrap;
            QRectF bounds = decPainter.boundingRect(rect, flags, name);
            while((bounds.height() >= rect.height() - 8. || bounds.width() >= rect.width() - 2.) && font.pixelSize() >= 5){
                // Scale font size down until it fits inside the key
                font.setPixelSize(font.pixelSize() - 2);
                decPainter.setFont(font);
                bounds = decPainter.boundingRect(rect, flags, name);
            }
            // Pick color based on key function
            QString bind = _bindMap.value(key.name);
            QString def = KbBind::defaultAction(key.name);
            if(bind.isEmpty())
                // Unbound - red
                decPainter.setPen(QColor(255, 136, 136));
            else if(KeyAction(bind).isProgram())
                // Custom program - orange
                decPainter.setPen(QColor(255, 224, 192));
            else if(KeyAction(bind).isSpecial() && (bind == def || !KeyAction(def).isSpecial()))
                // Special function - blue (only if not mapped to a different function - if a special function is remapped, color it yellow)
                decPainter.setPen(QColor(128, 224, 255));
            else if(KeyAction(bind).isMedia() && (bind == def || !KeyAction(def).isMedia()))
                // Media key - green
                decPainter.setPen(QColor(160, 255, 168));
            else if(bind == def)
                // Standard key - white
                decPainter.setPen(QColor(255, 255, 255));
            else
                // Remapped key - yellow
                decPainter.setPen(QColor(255, 248, 128));
            decPainter.drawText(rect, flags, name);
            font = font0;
        }
    }
    // Create drop shadow effects
    QGraphicsDropShadowEffect* bgEffect = new QGraphicsDropShadowEffect;  // Have to use "new", creating these on the stack causes a crash...
    bgEffect->setBlurRadius(2.);
    bgEffect->setColor(QColor(0, 0, 0, 32));
    bgEffect->setOffset(0, 1);
    QGraphicsDropShadowEffect* decEffect = new QGraphicsDropShadowEffect;
    decEffect->setBlurRadius(4.);
    decEffect->setColor(QColor(0, 0, 0, 104));
    decEffect->setOffset(0, 1);
    // Apply them to the pixmaps
    QGraphicsPixmapItem* bgItem = new QGraphicsPixmapItem(keyBG);
    bgItem->setGraphicsEffect(bgEffect);
    QGraphicsPixmapItem* decItem = new QGraphicsPixmapItem(decoration);
    decItem->setGraphicsEffect(decEffect);
    // Render everything
    QGraphicsScene* scene = new QGraphicsScene;
```

```
    scene->addItem(bgItem);
    scene->addItem(decItem);
    // It has to be rendered onto yet another pixmap or else DPI scaling will look terrible...
    QPixmap final(wWidth * ratio, wHeight * ratio);
    final.fill(QColor(0, 0, 0, 0));
    QPainter finalPainter(&final);
    scene->render(&finalPainter, QRectF(0, 0, wWidth * ratio, wHeight * ratio), QRectF(0, 0, wWidth * ratio
  , wHeight * ratio));
    delete scene;   // <- Automatically cleans up the rest of the objects
#if QT_VERSION >= QT_VERSION_CHECK(5, 3, 0)
    final.setDevicePixelRatio(ratio);
#endif
    painter.drawPixmap(QPointF(0., 0.), final);
}
```

Here is the call graph for this function:

12.43.5.17 bool KeyWidget::rgbMode ( ) [inline]

Definition at line 17 of file keywidget.h.

References _rgbMode.

Referenced by KbBindWidget::KbBindWidget().

```
17 { return _rgbMode; }
```

Here is the caller graph for this function:

12.43.5.18 void KeyWidget::rgbMode (bool *newRgbMode*) [inline]

Definition at line 18 of file keywidget.h.

References _rgbMode.

```
18 { _rgbMode = newRgbMode; update(); }
```

12.43.5.19 void KeyWidget::selectAll ( )

Definition at line 584 of file keywidget.cpp.

References _rgbMode, Key::hasLed, Key::hasScan, keyMap, mouseDownMode, Key::name, newSelection, NONE, KeyMap::positions(), selection, and selectionChanged().

Referenced by KbLightWidget::on_animButton_clicked(), and KbLightWidget::on_bgButton_clicked().

```
584                         {
585     selection.fill(false);
586     // Fill the selection with all keys that have an LED/scancode (depending on widget mode)
587     int i = 0;
588     QStringList selectedNames;
589     foreach(const Key& key, keyMap.positions()){
590         // Sidelights can't be selected
591         if(strcmp(key.name, "lsidel") && strcmp(key.name, "rsidel")
592            && ((_rgbMode && key.hasLed) || !(_rgbMode && key.
      hasScan))){
593             selection.setBit(i);
594             selectedNames << key.name;
595         }
596         i++;
597     }
598     // Clear mousedown state
599     newSelection.fill(false);
600     mouseDownMode = NONE;
601     update();
602     emit selectionChanged(selectedNames);
603 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.43.5.20 void KeyWidget::selectionChanged (QStringList *selected*) [signal]

Definition at line 164 of file moc_keywidget.cpp.

Referenced by clearSelection(), mouseReleaseEvent(), selectAll(), and setSelection().

```
{
    void *_a[] = { Q_NULLPTR, const_cast<void*>(reinterpret_cast<const void*>(&_t1)) };
    QMetaObject::activate(this, &staticMetaObject, 0, _a);
}
```

Here is the caller graph for this function:

12.43.5.21 void KeyWidget::setAnimation (const QStringList & *keys*)

Definition at line 613 of file keywidget.cpp.

References animation, keyMap, and KeyMap::keys().

Referenced by KbLightWidget::changeAnimKeys(), and KbLightWidget::setLight().

```
{
    animation.fill(false);
    QStringList allNames = keyMap.keys();
    foreach(const QString& key, keys){
        // Sidelights can't be selected
        if(!strcmp(key.toLatin1(), "lsidel") || !strcmp(key.toLatin1(), "rsidel"))
            continue;
        int index = allNames.indexOf(key);
        if(index >= 0)
            animation.setBit(index);
    }
    update();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.43.5.22 void KeyWidget::setAnimationToSelection ( )

Definition at line 627 of file keywidget.cpp.

References animation, and selection.

Referenced by KbLightWidget::changeAnim().

```
627                                         {
628     animation = selection;
629     update();
630 }
```

Here is the caller graph for this function:

12.43.5.23 void KeyWidget::setSelection (const QStringList & *keys*)

Definition at line 570 of file keywidget.cpp.

References keyMap, KeyMap::keys(), mouseDownMode, newSelection, NONE, selection, and selectionChanged().

Referenced by KbLightWidget::changeAnim().

```
570                                                 {
571     selection.fill(false);
572     QStringList allNames = keyMap.keys();
573     foreach(const QString& key, keys){
574         int index = allNames.indexOf(key);
575         if(index >= 0)
```

```
            selection.setBit(index);
    }
    newSelection.fill(false);
    mouseDownMode = NONE;
    update();
    emit selectionChanged(keys);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.43.5.24 void KeyWidget::sidelightToggled ( ) [signal]

Definition at line 171 of file moc_keywidget.cpp.

Referenced by mousePressEvent().

```
{
    QMetaObject::activate(this, &staticMetaObject, 1, Q_NULLPTR);
}
```

Here is the caller graph for this function:

12.43.6 Field Documentation

12.43.6.1 BindMap KeyWidget::_bindMap [private]

Definition at line 58 of file keywidget.h.

Referenced by bindMap(), and paintEvent().

12.43.6.2 QColorMap KeyWidget::_colorMap [private]

Definition at line 56 of file keywidget.h.

Referenced by colorMap(), and paintEvent().

12.43.6.3 ColorMap KeyWidget::_displayColorMap [private]

Definition at line 57 of file keywidget.h.

Referenced by displayColorMap(), and paintEvent().

12.43.6.4 QSet<QString> KeyWidget::_indicators [private]

Definition at line 59 of file keywidget.h.

Referenced by displayColorMap(), mouseMoveEvent(), and paintEvent().

12.43.6.5 bool KeyWidget::_monochrome [private]

Definition at line 73 of file keywidget.h.

Referenced by monochrome(), and paintEvent().

12.43.6.6 bool KeyWidget::_rgbMode [private]

Definition at line 73 of file keywidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), paintEvent(), rgbMode(), and selectAll().

12.43.6.7 QBitArray KeyWidget::animation [private]

Definition at line 63 of file keywidget.h.

Referenced by clearAnimation(), map(), paintEvent(), setAnimation(), and setAnimationToSelection().

12.43.6.8 KeyMap KeyWidget::keyMap [private]

Definition at line 55 of file keywidget.h.

Referenced by drawInfo(), map(), mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), paintEvent(), selectAll(), setAnimation(), and setSelection().

12.43.6.9 int KeyWidget::mouseCurrentX [private]

Definition at line 65 of file keywidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), and paintEvent().

12.43.6.10 int KeyWidget::mouseCurrentY [private]

Definition at line 65 of file keywidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), and paintEvent().

12.43.6.11 enum { ... } KeyWidget::mouseDownMode [private]

Referenced by clearSelection(), mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), paintEvent(), selectAll(), and setSelection().

12.43.6.12 int KeyWidget::mouseDownX [private]

Definition at line 64 of file keywidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), and paintEvent().

12.43.6.13 int KeyWidget::mouseDownY [private]

Definition at line 64 of file keywidget.h.

Referenced by mouseMoveEvent(), mousePressEvent(), and paintEvent().

12.43.6.14 QBitArray KeyWidget::newSelection [private]

Definition at line 62 of file keywidget.h.

Referenced by clearSelection(), map(), mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), paintEvent(), selectAll(), and setSelection().

12.43.6.15 QBitArray KeyWidget::selection [private]

Definition at line 61 of file keywidget.h.

Referenced by clearSelection(), map(), mouseReleaseEvent(), paintEvent(), selectAll(), setAnimationToSelection(), and setSelection().

The documentation for this class was generated from the following files:

- src/ckb/keywidget.h
- src/ckb/keywidget.cpp
- src/ckb/release/moc_keywidget.cpp

12.44 Ui::KPerfWidget Class Reference

```
#include <src/ckb/ui_kperfwidget.h>
```

Inheritance diagram for Ui::KPerfWidget:

Collaboration diagram for Ui::KPerfWidget:

Public Member Functions

- void setupUi (QWidget *KPerfWidget)
- void retranslateUi (QWidget *KPerfWidget)

Data Fields

- QGridLayout * gridLayout
- QWidget * k95Spacer
- QLabel * label_10
- ColorButton * lockColorOff
- QFrame * line
- QSpacerItem * horizontalSpacer_5
- QLabel * k95Label2
- QLabel * label_12
- ColorButton * modeColorOff
- ColorButton * lightColor3
- QSpacerItem * horizontalSpacer
- QCheckBox * lockBox
- ColorButton * modeColorOn
- QCheckBox * macroBox
- ColorButton * numColorOn
- QComboBox * numBox
- QLabel * label_5
- QSpacerItem * verticalSpacer_2
- ColorButton * lightColor2
- QSpacerItem * horizontalSpacer_7
- QLabel * label_8

- QCheckBox * lightBox
- ColorButton * lightColor1
- QSpacerItem * verticalSpacer_4
- QLabel * label_6
- QLabel * label
- QSpacerItem * horizontalSpacer_6
- ColorButton * lockColorOn
- QLabel * label_4
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QCheckBox * modeBox
- ColorButton * capsColorOff
- ColorButton * numColorOff
- ColorButton * capsColorOn
- QFrame * line_3
- QLabel * label_22
- QComboBox * scrollBox
- QLabel * label_7
- ColorButton * scrollColorOn
- QComboBox * capsBox
- ColorButton * scrollColorOff
- QCheckBox * muteBox
- ColorButton * muteColorOn
- ColorButton * macroColorOff
- QLabel * label_3
- ColorButton * muteColorOff
- QLabel * k95Label3
- ColorButton * macroColorOn
- ColorButton * muteColorNA
- QLabel * label_19
- QFrame * k95Line
- QLabel * label_21
- QLabel * label_24
- QLabel * label_20
- QLabel * label_16
- QLabel * label_14
- QLabel * label_18
- QSpacerItem * horizontalSpacer_2
- QLabel * label_15
- QLabel * k95Label4
- QLabel * label_17
- QLabel * label_11
- QLabel * label_23
- QLabel * k95Label1
- QHBoxLayout * horizontalLayout_2
- QPushButton * copyButton
- QSpacerItem * horizontalSpacer_8
- QHBoxLayout * horizontalLayout
- QLabel * label_2
- QSpacerItem * horizontalSpacer_4
- QSpinBox * intensityBox
- QSpacerItem * horizontalSpacer_3
- QLabel * k95Label5
- QFrame * line_2
- QLabel * k95Label6

12.44.1 Detailed Description

Definition at line 677 of file ui_kperfwidget.h.

12.44.2 Member Function Documentation

12.44.2.1 void Ui_KPerfWidget::retranslateUi (QWidget * *KPerfWidget*) [inline],[inherited]

Definition at line 589 of file ui_kperfwidget.h.

References Ui_KPerfWidget::capsBox, Ui_KPerfWidget::capsColorOff, Ui_KPerfWidget::capsColorOn, Ui_KPerfWidget::copyButton, Ui_KPerfWidget::intensityBox, Ui_KPerfWidget::k95Label1, Ui_KPerfWidget::k95Label2, Ui_KPerfWidget::k95Label3, Ui_KPerfWidget::k95Label4, Ui_KPerfWidget::k95Label5, Ui_KPerfWidget::k95Label6, Ui_KPerfWidget::label, Ui_KPerfWidget::label_10, Ui_KPerfWidget::label_11, Ui_KPerfWidget::label_12, Ui_KPerfWidget::label_14, Ui_KPerfWidget::label_15, Ui_KPerfWidget::label_16, Ui_KPerfWidget::label_17, Ui_KPerfWidget::label_18, Ui_KPerfWidget::label_19, Ui_KPerfWidget::label_2, Ui_KPerfWidget::label_20, Ui_KPerfWidget::label_21, Ui_KPerfWidget::label_22, Ui_KPerfWidget::label_23, Ui_KPerfWidget::label_24, Ui_KPerfWidget::label_3, Ui_KPerfWidget::label_4, Ui_KPerfWidget::label_5, Ui_KPerfWidget::label_6, Ui_KPerfWidget::label_7, Ui_KPerfWidget::label_8, Ui_KPerfWidget::lightBox, Ui_KPerfWidget::lightColor1, Ui_KPerfWidget::lightColor2, Ui_KPerfWidget::lightColor3, Ui_KPerfWidget::lockBox, Ui_KPerfWidget::lockColorOff, Ui_KPerfWidget::lockColorOn, Ui_KPerfWidget::macroBox, Ui_KPerfWidget::macroColorOff, Ui_KPerfWidget::macroColorOn, Ui_KPerfWidget::modeBox, Ui_KPerfWidget::modeColorOff, Ui_KPerfWidget::modeColorOn, Ui_KPerfWidget::muteBox, Ui_KPerfWidget::muteColorNA, Ui_KPerfWidget::muteColorOff, Ui_KPerfWidget::muteColorOn, Ui_KPerfWidget::numBox, Ui_KPerfWidget::numColorOff, Ui_KPerfWidget::numColorOn, Ui_KPerfWidget::scrollBox, Ui_KPerfWidget::scrollColorOff, and Ui_KPerfWidget::scrollColorOn.

Referenced by Ui_KPerfWidget::setupUi().

```
590     {
591         KPerfWidget->setWindowTitle(QApplication::translate("KPerfWidget", "Form", Q_NULLPTR));
592         label_10->setText(QApplication::translate("KPerfWidget", "100%", Q_NULLPTR));
593         lockColorOff->setText(QString());
594         k95Label2->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
595         label_12->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
596         modeColorOff->setText(QString());
597         lightColor3->setText(QString());
598         lockBox->setText(QApplication::translate("KPerfWidget", "Indicate Windows Lock:", Q_NULLPTR)
    );
599         modeColorOn->setText(QString());
600         macroBox->setText(QApplication::translate("KPerfWidget", "Indicate macro recording:",
    Q_NULLPTR));
601         numColorOn->setText(QString());
602         numBox->clear();
603         numBox->insertItems(0, QStringList()
604          << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
605          << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
606          << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
607          << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
608          << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
609         );
610         label_5->setText(QApplication::translate("KPerfWidget", "Num lock:", Q_NULLPTR));
611         lightColor2->setText(QString());
612         label_8->setText(QApplication::translate("KPerfWidget", "Note: many desktop environments do
     not use scroll lock. The indicator may not turn on even when enabled.", Q_NULLPTR));
613         lightBox->setText(QApplication::translate("KPerfWidget", "Indicate brightness:", Q_NULLPTR)
    );
614         lightColor1->setText(QString());
615         label_6->setText(QApplication::translate("KPerfWidget", "Caps lock:", Q_NULLPTR));
616         label->setText(QApplication::translate("KPerfWidget", "Miscellaneous", Q_NULLPTR));
617         lockColorOn->setText(QString());
618         label_4->setText(QApplication::translate("KPerfWidget", "Lock lights", Q_NULLPTR));
619         modeBox->setText(QApplication::translate("KPerfWidget", "Indicate current mode:", Q_NULLPTR)
    );
620         capsColorOff->setText(QString());
621         numColorOff->setText(QString());
622         capsColorOn->setText(QString());
623         label_22->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
624         scrollBox->clear();
625         scrollBox->insertItems(0, QStringList()
626          << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
627          << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
628          << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
629          << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
```

```
         << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
        );
        label_7->setText(QApplication::translate("KPerfWidget", "Scroll lock:", Q_NULLPTR));
        scrollColorOn->setText(QString());
        capsBox->clear();
        capsBox->insertItems(0, QStringList()
         << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
         << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
         << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
         << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
         << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
        );
        scrollColorOff->setText(QString());
        muteBox->setText(QApplication::translate("KPerfWidget", "Indicate mute:", Q_NULLPTR));
        muteColorOn->setText(QString());
        macroColorOff->setText(QString());
        label_3->setText(QApplication::translate("KPerfWidget", "Top row", Q_NULLPTR));
        muteColorOff->setText(QString());
        k95Label3->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        macroColorOn->setText(QString());
#ifndef QT_NO_TOOLTIP
        muteColorNA->setToolTip(QApplication::translate("KPerfWidget", "If the sound device does not support muting, or if mute status is unknown, this color will be displayed.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        muteColorNA->setText(QString());
        label_19->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_21->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_24->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        label_20->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_16->setText(QApplication::translate("KPerfWidget", "67%", Q_NULLPTR));
        label_14->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        label_18->setText(QApplication::translate("KPerfWidget", "33%", Q_NULLPTR));
        label_15->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label4->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_17->setText(QApplication::translate("KPerfWidget", "Unknown", Q_NULLPTR));
        label_11->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_23->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label1->setText(QApplication::translate("KPerfWidget", "K95 buttons", Q_NULLPTR));
        copyButton->setText(QApplication::translate("KPerfWidget", "Copy to mode...", Q_NULLPTR)
    ;
        label_2->setText(QApplication::translate("KPerfWidget", "Indicator intensity:", Q_NULLPTR));
        intensityBox->setSuffix(QApplication::translate("KPerfWidget", "%", Q_NULLPTR));
        k95Label5->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label6->setText(QApplication::translate("KPerfWidget", "Note: macro recording not yet implemented. Indicator will always display \"off\".", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.44.2.2 void Ui_KPerfWidget::setupUi (QWidget * *KPerfWidget*) [inline],[inherited]

Definition at line 111 of file ui_kperfwidget.h.

References Ui_KPerfWidget::capsBox, Ui_KPerfWidget::capsColorOff, Ui_KPerfWidget::capsColorOn, Ui_KPerfWidget::copyButton, Ui_KPerfWidget::gridLayout, Ui_KPerfWidget::horizontalLayout, Ui_KPerfWidget::horizontalLayout_2, Ui_KPerfWidget::horizontalSpacer, Ui_KPerfWidget::horizontalSpacer_2, Ui_KPerfWidget::horizontalSpacer_3, Ui_KPerfWidget::horizontalSpacer_4, Ui_KPerfWidget::horizontalSpacer_5, Ui_KPerfWidget::horizontalSpacer_6, Ui_KPerfWidget::horizontalSpacer_7, Ui_KPerfWidget::horizontalSpacer_8, Ui_KPerfWidget::intensityBox, Ui_KPerfWidget::k95Label1, Ui_KPerfWidget::k95Label2, Ui_KPerfWidget::k95Label3, Ui_KPerfWidget::k95Label4, Ui_KPerfWidget::k95Label5, Ui_KPerfWidget::k95Label6, Ui_KPerfWidget::k95Line, Ui_KPerfWidget::k95Spacer, Ui_KPerfWidget::label, Ui_KPerfWidget::label_10, Ui_KPerfWidget::label_11, Ui_KPerfWidget::label_12, Ui_KPerfWidget::label_14, Ui_KPerfWidget::label_15, Ui_KPerfWidget::label_16, Ui_KPerfWidget::label_17, Ui_KPerfWidget::label_18, Ui_KPerfWidget::label_19, Ui_KPerfWidget::label_2, Ui_KPerfWidget::label_20, Ui_KPerfWidget::label_21, Ui_KPerfWidget::label_22, Ui_KPerfWidget::label_23, Ui_KPerfWidget::label_24, Ui_KPerfWidget::label_3, Ui_KPerfWidget::label_4, Ui_KPerfWidget::label_5, Ui_KPerfWidget::label_6, Ui_KPerfWidget-

::label_7, Ui_KPerfWidget::label_8, Ui_KPerfWidget::lightBox, Ui_KPerfWidget::lightColor1, Ui_KPerfWidget::lightColor2, Ui_KPerfWidget::lightColor3, Ui_KPerfWidget::line, Ui_KPerfWidget::line_2, Ui_KPerfWidget::line_3, Ui_KPerfWidget::lockBox, Ui_KPerfWidget::lockColorOff, Ui_KPerfWidget::lockColorOn, Ui_KPerfWidget::macroBox, Ui_KPerfWidget::macroColorOff, Ui_KPerfWidget::macroColorOn, Ui_KPerfWidget::modeBox, Ui_KPerfWidget::modeColorOff, Ui_KPerfWidget::modeColorOn, Ui_KPerfWidget::muteBox, Ui_KPerfWidget::muteColorNA, Ui_KPerfWidget::muteColorOff, Ui_KPerfWidget::muteColorOn, Ui_KPerfWidget::numBox, Ui_KPerfWidget::numColorOff, Ui_KPerfWidget::numColorOn, Ui_KPerfWidget::retranslateUi(), Ui_KPerfWidget::scrollBox, Ui_KPerfWidget::scrollColorOff, Ui_KPerfWidget::scrollColorOn, Ui_KPerfWidget::verticalSpacer, Ui_KPerfWidget::verticalSpacer_2, Ui_KPerfWidget::verticalSpacer_3, and Ui_KPerfWidget::verticalSpacer_4.

Referenced by KPerfWidget::KPerfWidget().

```
    {
        if (KPerfWidget->objectName().isEmpty())
            KPerfWidget->setObjectName(QStringLiteral("KPerfWidget"));
        KPerfWidget->resize(840, 679);
        gridLayout = new QGridLayout(KPerfWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        k95Spacer = new QWidget(KPerfWidget);
        k95Spacer->setObjectName(QStringLiteral("k95Spacer"));
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(k95Spacer->sizePolicy().hasHeightForWidth());
        k95Spacer->setSizePolicy(sizePolicy);
        k95Spacer->setMinimumSize(QSize(15, 10));
        k95Spacer->setMaximumSize(QSize(15, 10));

        gridLayout->addWidget(k95Spacer, 12, 4, 1, 1);

        label_10 = new QLabel(KPerfWidget);
        label_10->setObjectName(QStringLiteral("label_10"));

        gridLayout->addWidget(label_10, 15, 5, 1, 1);

        lockColorOff = new ColorButton(KPerfWidget);
        lockColorOff->setObjectName(QStringLiteral("lockColorOff"));
        sizePolicy.setHeightForWidth(lockColorOff->sizePolicy().hasHeightForWidth());
        lockColorOff->setSizePolicy(sizePolicy);
        lockColorOff->setMinimumSize(QSize(0, 40));
        lockColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lockColorOff, 16, 7, 1, 1);

        line = new QFrame(KPerfWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 2, 0, 1, 13);

        horizontalSpacer_5 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_5, 17, 6, 1, 1);

        k95Label2 = new QLabel(KPerfWidget);
        k95Label2->setObjectName(QStringLiteral("k95Label2"));

        gridLayout->addWidget(k95Label2, 9, 5, 1, 1);

        label_12 = new QLabel(KPerfWidget);
        label_12->setObjectName(QStringLiteral("label_12"));

        gridLayout->addWidget(label_12, 17, 5, 1, 1);

        modeColorOff = new ColorButton(KPerfWidget);
        modeColorOff->setObjectName(QStringLiteral("modeColorOff"));
        sizePolicy.setHeightForWidth(modeColorOff->sizePolicy().hasHeightForWidth());
        modeColorOff->setSizePolicy(sizePolicy);
        modeColorOff->setMinimumSize(QSize(0, 40));
        modeColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(modeColorOff, 9, 7, 1, 1);

        lightColor3 = new ColorButton(KPerfWidget);
        lightColor3->setObjectName(QStringLiteral("lightColor3"));
        sizePolicy.setHeightForWidth(lightColor3->sizePolicy().hasHeightForWidth());
        lightColor3->setSizePolicy(sizePolicy);
        lightColor3->setMinimumSize(QSize(0, 40));
        lightColor3->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor3, 15, 4, 1, 1);
```

```
        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 15, 12, 1, 1);

        lockBox = new QCheckBox(KPerfWidget);
        lockBox->setObjectName(QStringLiteral("lockBox"));

        gridLayout->addWidget(lockBox, 16, 1, 1, 2);

        modeColorOn = new ColorButton(KPerfWidget);
        modeColorOn->setObjectName(QStringLiteral("modeColorOn"));
        sizePolicy.setHeightForWidth(modeColorOn->sizePolicy().hasHeightForWidth());
        modeColorOn->setSizePolicy(sizePolicy);
        modeColorOn->setMinimumSize(QSize(0, 40));
        modeColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(modeColorOn, 9, 4, 1, 1);

        macroBox = new QCheckBox(KPerfWidget);
        macroBox->setObjectName(QStringLiteral("macroBox"));

        gridLayout->addWidget(macroBox, 10, 1, 1, 2);

        numColorOn = new ColorButton(KPerfWidget);
        numColorOn->setObjectName(QStringLiteral("numColorOn"));
        sizePolicy.setHeightForWidth(numColorOn->sizePolicy().hasHeightForWidth());
        numColorOn->setSizePolicy(sizePolicy);
        numColorOn->setMinimumSize(QSize(0, 40));
        numColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(numColorOn, 21, 4, 1, 1);

        numBox = new QComboBox(KPerfWidget);
        numBox->setObjectName(QStringLiteral("numBox"));

        gridLayout->addWidget(numBox, 21, 2, 1, 1);

        label_5 = new QLabel(KPerfWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout->addWidget(label_5, 21, 1, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 20, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_2, 4, 1, 1, 1);

        lightColor2 = new ColorButton(KPerfWidget);
        lightColor2->setObjectName(QStringLiteral("lightColor2"));
        sizePolicy.setHeightForWidth(lightColor2->sizePolicy().hasHeightForWidth());
        lightColor2->setSizePolicy(sizePolicy);
        lightColor2->setMinimumSize(QSize(0, 40));
        lightColor2->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor2, 15, 7, 1, 1);

        horizontalSpacer_7 = new QSpacerItem(10, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_7, 17, 3, 1, 1);

        label_8 = new QLabel(KPerfWidget);
        label_8->setObjectName(QStringLiteral("label_8"));
        QFont font;
        font.setPointSize(8);
        font.setItalic(true);
        label_8->setFont(font);

        gridLayout->addWidget(label_8, 25, 1, 1, 12);

        lightBox = new QCheckBox(KPerfWidget);
        lightBox->setObjectName(QStringLiteral("lightBox"));

        gridLayout->addWidget(lightBox, 15, 1, 1, 2);

        lightColor1 = new ColorButton(KPerfWidget);
        lightColor1->setObjectName(QStringLiteral("lightColor1"));
        sizePolicy.setHeightForWidth(lightColor1->sizePolicy().hasHeightForWidth());
        lightColor1->setSizePolicy(sizePolicy);
        lightColor1->setMinimumSize(QSize(0, 40));
        lightColor1->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor1, 15, 10, 1, 1);

        verticalSpacer_4 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);
```

```

        gridLayout->addItem(verticalSpacer_4, 24, 4, 1, 1);

        label_6 = new QLabel(KPerfWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 22, 1, 1, 1);

        label = new QLabel(KPerfWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font1;
        font1.setBold(true);
        font1.setWeight(75);
        label->setFont(font1);

        gridLayout->addWidget(label, 1, 0, 1, 13);

        horizontalSpacer_6 = new QSpacerItem(10, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_6, 17, 9, 1, 1);

        lockColorOn = new ColorButton(KPerfWidget);
        lockColorOn->setObjectName(QStringLiteral("lockColorOn"));
        sizePolicy.setHeightForWidth(lockColorOn->sizePolicy().hasHeightForWidth());
        lockColorOn->setSizePolicy(sizePolicy);
        lockColorOn->setMinimumSize(QSize(0, 40));
        lockColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lockColorOn, 16, 4, 1, 1);

        label_4 = new QLabel(KPerfWidget);
        label_4->setObjectName(QStringLiteral("label_4"));
        label_4->setFont(font1);

        gridLayout->addWidget(label_4, 19, 0, 1, 13);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer, 26, 2, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 20, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_3, 18, 4, 1, 1);

        modeBox = new QCheckBox(KPerfWidget);
        modeBox->setObjectName(QStringLiteral("modeBox"));

        gridLayout->addWidget(modeBox, 9, 1, 1, 2);

        capsColorOff = new ColorButton(KPerfWidget);
        capsColorOff->setObjectName(QStringLiteral("capsColorOff"));
        sizePolicy.setHeightForWidth(capsColorOff->sizePolicy().hasHeightForWidth());
        capsColorOff->setSizePolicy(sizePolicy);
        capsColorOff->setMinimumSize(QSize(0, 40));
        capsColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(capsColorOff, 22, 7, 1, 1);

        numColorOff = new ColorButton(KPerfWidget);
        numColorOff->setObjectName(QStringLiteral("numColorOff"));
        QSizePolicy sizePolicy1(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(40);
        sizePolicy1.setHeightForWidth(numColorOff->sizePolicy().hasHeightForWidth());
        numColorOff->setSizePolicy(sizePolicy1);
        numColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(numColorOff, 21, 7, 1, 1);

        capsColorOn = new ColorButton(KPerfWidget);
        capsColorOn->setObjectName(QStringLiteral("capsColorOn"));
        sizePolicy.setHeightForWidth(capsColorOn->sizePolicy().hasHeightForWidth());
        capsColorOn->setSizePolicy(sizePolicy);
        capsColorOn->setMinimumSize(QSize(0, 40));
        capsColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(capsColorOn, 22, 4, 1, 1);

        line_3 = new QFrame(KPerfWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 20, 0, 1, 13);
```

```

        label_22 = new QLabel(KPerfWidget);
        label_22->setObjectName(QStringLiteral("label_22"));

        gridLayout->addWidget(label_22, 21, 8, 1, 1);

        scrollBox = new QComboBox(KPerfWidget);
        scrollBox->setObjectName(QStringLiteral("scrollBox"));

        gridLayout->addWidget(scrollBox, 23, 2, 1, 1);

        label_7 = new QLabel(KPerfWidget);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout->addWidget(label_7, 23, 1, 1, 1);

        scrollColorOn = new ColorButton(KPerfWidget);
        scrollColorOn->setObjectName(QStringLiteral("scrollColorOn"));
        sizePolicy.setHeightForWidth(scrollColorOn->sizePolicy().hasHeightForWidth());
        scrollColorOn->setSizePolicy(sizePolicy);
        scrollColorOn->setMinimumSize(QSize(0, 40));
        scrollColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(scrollColorOn, 23, 4, 1, 1);

        capsBox = new QComboBox(KPerfWidget);
        capsBox->setObjectName(QStringLiteral("capsBox"));

        gridLayout->addWidget(capsBox, 22, 2, 1, 1);

        scrollColorOff = new ColorButton(KPerfWidget);
        scrollColorOff->setObjectName(QStringLiteral("scrollColorOff"));
        sizePolicy.setHeightForWidth(scrollColorOff->sizePolicy().hasHeightForWidth());
        scrollColorOff->setSizePolicy(sizePolicy);
        scrollColorOff->setMinimumSize(QSize(0, 40));
        scrollColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(scrollColorOff, 23, 7, 1, 1);

        muteBox = new QCheckBox(KPerfWidget);
        muteBox->setObjectName(QStringLiteral("muteBox"));

        gridLayout->addWidget(muteBox, 17, 1, 1, 2);

        muteColorOn = new ColorButton(KPerfWidget);
        muteColorOn->setObjectName(QStringLiteral("muteColorOn"));
        sizePolicy.setHeightForWidth(muteColorOn->sizePolicy().hasHeightForWidth());
        muteColorOn->setSizePolicy(sizePolicy);
        muteColorOn->setMinimumSize(QSize(0, 40));
        muteColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorOn, 17, 4, 1, 1);

        macroColorOff = new ColorButton(KPerfWidget);
        macroColorOff->setObjectName(QStringLiteral("macroColorOff"));
        QSizePolicy sizePolicy2(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(40);
        sizePolicy2.setHeightForWidth(macroColorOff->sizePolicy().hasHeightForWidth());
        macroColorOff->setSizePolicy(sizePolicy2);
        macroColorOff->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(macroColorOff, 10, 7, 1, 1);

        label_3 = new QLabel(KPerfWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        label_3->setFont(font1);

        gridLayout->addWidget(label_3, 13, 0, 1, 3);

        muteColorOff = new ColorButton(KPerfWidget);
        muteColorOff->setObjectName(QStringLiteral("muteColorOff"));
        sizePolicy.setHeightForWidth(muteColorOff->sizePolicy().hasHeightForWidth());
        muteColorOff->setSizePolicy(sizePolicy);
        muteColorOff->setMinimumSize(QSize(0, 40));
        muteColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorOff, 17, 7, 1, 1);

        k95Label3 = new QLabel(KPerfWidget);
        k95Label3->setObjectName(QStringLiteral("k95Label3"));

        gridLayout->addWidget(k95Label3, 9, 8, 1, 1);

        macroColorOn = new ColorButton(KPerfWidget);
        macroColorOn->setObjectName(QStringLiteral("macroColorOn"));
        sizePolicy2.setHeightForWidth(macroColorOn->sizePolicy().hasHeightForWidth());
```

```
        macroColorOn->setSizePolicy(sizePolicy2);
        macroColorOn->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(macroColorOn, 10, 4, 1, 1);

        muteColorNA = new ColorButton(KPerfWidget);
        muteColorNA->setObjectName(QStringLiteral("muteColorNA"));
        muteColorNA->setMinimumSize(QSize(0, 40));
        muteColorNA->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorNA, 17, 10, 1, 1);

        label_19 = new QLabel(KPerfWidget);
        label_19->setObjectName(QStringLiteral("label_19"));

        gridLayout->addWidget(label_19, 21, 5, 1, 1);

        k95Line = new QFrame(KPerfWidget);
        k95Line->setObjectName(QStringLiteral("k95Line"));
        k95Line->setFrameShape(QFrame::HLine);
        k95Line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(k95Line, 8, 0, 1, 13);

        label_21 = new QLabel(KPerfWidget);
        label_21->setObjectName(QStringLiteral("label_21"));

        gridLayout->addWidget(label_21, 23, 5, 1, 1);

        label_24 = new QLabel(KPerfWidget);
        label_24->setObjectName(QStringLiteral("label_24"));

        gridLayout->addWidget(label_24, 23, 8, 1, 1);

        label_20 = new QLabel(KPerfWidget);
        label_20->setObjectName(QStringLiteral("label_20"));

        gridLayout->addWidget(label_20, 22, 5, 1, 1);

        label_16 = new QLabel(KPerfWidget);
        label_16->setObjectName(QStringLiteral("label_16"));

        gridLayout->addWidget(label_16, 15, 8, 1, 1);

        label_14 = new QLabel(KPerfWidget);
        label_14->setObjectName(QStringLiteral("label_14"));

        gridLayout->addWidget(label_14, 17, 8, 1, 1);

        label_18 = new QLabel(KPerfWidget);
        label_18->setObjectName(QStringLiteral("label_18"));

        gridLayout->addWidget(label_18, 15, 11, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_2, 15, 0, 1, 1);

        label_15 = new QLabel(KPerfWidget);
        label_15->setObjectName(QStringLiteral("label_15"));

        gridLayout->addWidget(label_15, 16, 8, 1, 1);

        k95Label4 = new QLabel(KPerfWidget);
        k95Label4->setObjectName(QStringLiteral("k95Label4"));

        gridLayout->addWidget(k95Label4, 10, 5, 1, 1);

        label_17 = new QLabel(KPerfWidget);
        label_17->setObjectName(QStringLiteral("label_17"));

        gridLayout->addWidget(label_17, 17, 11, 1, 1);

        label_11 = new QLabel(KPerfWidget);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout->addWidget(label_11, 16, 5, 1, 1);

        label_23 = new QLabel(KPerfWidget);
        label_23->setObjectName(QStringLiteral("label_23"));

        gridLayout->addWidget(label_23, 22, 8, 1, 1);

        k95Label1 = new QLabel(KPerfWidget);
        k95Label1->setObjectName(QStringLiteral("k95Label1"));
        k95Label1->setFont(font1);
```

```
        gridLayout->addWidget(k95Label1, 7, 0, 1, 5);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        copyButton = new QPushButton(KPerfWidget);
        copyButton->setObjectName(QStringLiteral("copyButton"));

        horizontalLayout_2->addWidget(copyButton);

        horizontalSpacer_8 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_8);


        gridLayout->addLayout(horizontalLayout_2, 3, 10, 1, 3);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        label_2 = new QLabel(KPerfWidget);
        label_2->setObjectName(QStringLiteral("label_2"));

        horizontalLayout->addWidget(label_2);

        horizontalSpacer_4 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_4);

        intensityBox = new QSpinBox(KPerfWidget);
        intensityBox->setObjectName(QStringLiteral("intensityBox"));
        intensityBox->setMaximum(100);
        intensityBox->setValue(100);

        horizontalLayout->addWidget(intensityBox);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_3);


        gridLayout->addLayout(horizontalLayout, 3, 1, 1, 9);

        k95Label5 = new QLabel(KPerfWidget);
        k95Label5->setObjectName(QStringLiteral("k95Label5"));

        gridLayout->addWidget(k95Label5, 10, 8, 1, 1);

        line_2 = new QFrame(KPerfWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 14, 0, 1, 13);

        k95Label6 = new QLabel(KPerfWidget);
        k95Label6->setObjectName(QStringLiteral("k95Label6"));
        k95Label6->setFont(font);

        gridLayout->addWidget(k95Label6, 11, 1, 1, 10);


        retranslateUi(KPerfWidget);

        QMetaObject::connectSlotsByName(KPerfWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.44.3 Field Documentation

12.44.3.1 QComboBox* Ui_KPerfWidget::capsBox [inherited]

Definition at line 74 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.2 ColorButton* Ui_KPerfWidget::capsColorOff [inherited]

Definition at line 66 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.3 ColorButton* Ui_KPerfWidget::capsColorOn [inherited]

Definition at line 68 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.4 QPushButton* Ui_KPerfWidget::copyButton [inherited]

Definition at line 100 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.5 QGridLayout* Ui_KPerfWidget::gridLayout [inherited]

Definition at line 34 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.6 QHBoxLayout* Ui_KPerfWidget::horizontalLayout [inherited]

Definition at line 102 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.7 QHBoxLayout* Ui_KPerfWidget::horizontalLayout_2 [inherited]

Definition at line 99 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.8 QSpacerItem* Ui_KPerfWidget::horizontalSpacer [inherited]

Definition at line 44 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.9 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_2 [inherited]

Definition at line 92 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.10 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_3 [inherited]

Definition at line 106 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.11 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_4 [inherited]

Definition at line 104 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.12 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_5 [inherited]

Definition at line 39 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.13 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_6 [inherited]

Definition at line 60 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.14 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_7 [inherited]

Definition at line 53 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.15 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_8 [inherited]

Definition at line 101 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.16 QSpinBox* Ui_KPerfWidget::intensityBox [inherited]

Definition at line 105 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.17 QLabel* Ui_KPerfWidget::k95Label1 [inherited]

Definition at line 98 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.18 QLabel* Ui_KPerfWidget::k95Label2 [inherited]

Definition at line 40 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.19 QLabel* Ui_KPerfWidget::k95Label3 [inherited]

Definition at line 81 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.20 QLabel* Ui_KPerfWidget::k95Label4 [inherited]

Definition at line 94 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.21 QLabel* Ui_KPerfWidget::k95Label5 [inherited]

Definition at line 107 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.22 QLabel* Ui_KPerfWidget::k95Label6 [inherited]

Definition at line 109 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.23 QFrame* Ui_KPerfWidget::k95Line [inherited]

Definition at line 85 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), and Ui_KPerfWidget::setupUi().

12.44.3.24 QWidget* Ui_KPerfWidget::k95Spacer [inherited]

Definition at line 35 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), and Ui_KPerfWidget::setupUi().

12.44.3.25 QLabel* Ui_KPerfWidget::label [inherited]

Definition at line 59 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.26 QLabel* Ui_KPerfWidget::label_10 [inherited]

Definition at line 36 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.27 QLabel* Ui_KPerfWidget::label_11 [inherited]

Definition at line 96 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.28 QLabel* Ui_KPerfWidget::label_12 [inherited]

Definition at line 41 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.29 QLabel* Ui_KPerfWidget::label_14 [inherited]

Definition at line 90 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.30 QLabel* Ui_KPerfWidget::label_15 [inherited]

Definition at line 93 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.31 QLabel* Ui_KPerfWidget::label_16 [inherited]

Definition at line 89 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.32 QLabel* Ui_KPerfWidget::label_17 [inherited]

Definition at line 95 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.33 QLabel* Ui_KPerfWidget::label_18 [inherited]

Definition at line 91 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.34 QLabel* Ui_KPerfWidget::label_19 [inherited]

Definition at line 84 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.35 QLabel* Ui_KPerfWidget::label_2 [inherited]

Definition at line 103 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.36 QLabel* Ui_KPerfWidget::label_20 [inherited]

Definition at line 88 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.37 QLabel* Ui_KPerfWidget::label_21 [inherited]

Definition at line 86 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.38 QLabel* Ui_KPerfWidget::label_22 [inherited]

Definition at line 70 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.39 QLabel* Ui_KPerfWidget::label_23 [inherited]

Definition at line 97 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.40 QLabel* Ui_KPerfWidget::label_24 [inherited]

Definition at line 87 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.41 QLabel* Ui_KPerfWidget::label_3 [inherited]

Definition at line 79 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.42 QLabel* Ui_KPerfWidget::label_4 [inherited]

Definition at line 62 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.43 QLabel* Ui_KPerfWidget::label_5 [inherited]

Definition at line 50 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.44 QLabel* Ui_KPerfWidget::label_6 [inherited]

Definition at line 58 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.45 QLabel* Ui_KPerfWidget::label_7 [inherited]

Definition at line 72 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.46 QLabel* Ui_KPerfWidget::label_8 [inherited]

Definition at line 54 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.47 QCheckBox* Ui_KPerfWidget::lightBox [inherited]

Definition at line 55 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.48 ColorButton* Ui_KPerfWidget::lightColor1 [inherited]

Definition at line 56 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.49 ColorButton* Ui_KPerfWidget::lightColor2 [inherited]

Definition at line 52 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.50 ColorButton* Ui_KPerfWidget::lightColor3 [inherited]

Definition at line 43 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.51 QFrame* Ui_KPerfWidget::line [inherited]

Definition at line 38 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.52 QFrame* Ui_KPerfWidget::line_2 [inherited]

Definition at line 108 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.53 QFrame* Ui_KPerfWidget::line_3 [inherited]

Definition at line 69 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.54 QCheckBox* Ui_KPerfWidget::lockBox [inherited]

Definition at line 45 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.55 ColorButton* Ui_KPerfWidget::lockColorOff [inherited]

Definition at line 37 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.56 ColorButton* Ui_KPerfWidget::lockColorOn [inherited]

Definition at line 61 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.57 QCheckBox* Ui_KPerfWidget::macroBox [inherited]

Definition at line 47 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.58 ColorButton* Ui_KPerfWidget::macroColorOff [inherited]

Definition at line 78 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.59 ColorButton* Ui_KPerfWidget::macroColorOn [inherited]

Definition at line 82 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.60 QCheckBox* Ui_KPerfWidget::modeBox [inherited]

Definition at line 65 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.61 ColorButton* Ui_KPerfWidget::modeColorOff [inherited]

Definition at line 42 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.62 ColorButton* Ui_KPerfWidget::modeColorOn [inherited]

Definition at line 46 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.63 QCheckBox* Ui_KPerfWidget::muteBox [inherited]

Definition at line 76 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.64 ColorButton* Ui_KPerfWidget::muteColorNA [inherited]

Definition at line 83 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.65 ColorButton* Ui_KPerfWidget::muteColorOff [inherited]

Definition at line 80 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.66 ColorButton* Ui_KPerfWidget::muteColorOn [inherited]

Definition at line 77 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), KPerfWidget::setPerf(), and Ui_KPerfWidget::setupUi().

12.44.3.67 QComboBox* Ui_KPerfWidget::numBox [inherited]

Definition at line 49 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.68 ColorButton* Ui_KPerfWidget::numColorOff [inherited]

Definition at line 67 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.69 ColorButton* Ui_KPerfWidget::numColorOn [inherited]

Definition at line 48 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.70 QComboBox* Ui_KPerfWidget::scrollBox [inherited]

Definition at line 71 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.71 ColorButton* Ui_KPerfWidget::scrollColorOff [inherited]

Definition at line 75 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.72 ColorButton* Ui_KPerfWidget::scrollColorOn [inherited]

Definition at line 73 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), Ui_KPerfWidget::retranslateUi(), and Ui_KPerfWidget::setupUi().

12.44.3.73 QSpacerItem* Ui_KPerfWidget::verticalSpacer [inherited]

Definition at line 63 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.74 QSpacerItem* Ui_KPerfWidget::verticalSpacer_2 [inherited]

Definition at line 51 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.75 QSpacerItem* Ui_KPerfWidget::verticalSpacer_3 [inherited]

Definition at line 64 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

12.44.3.76 QSpacerItem* Ui_KPerfWidget::verticalSpacer_4 [inherited]

Definition at line 57 of file ui_kperfwidget.h.

Referenced by Ui_KPerfWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kperfwidget.h

12.45 KPerfWidget Class Reference

```
#include <src/ckb/kperfwidget.h>
```

Inheritance diagram for KPerfWidget:

Collaboration diagram for KPerfWidget:

Data Structures

- struct IndicatorUi

Public Types

- typedef KbPerf::indicator indicator
- typedef KbPerf::i_hw i_hw

Public Member Functions

- KPerfWidget (QWidget ∗parent=0)
- ∼KPerfWidget ()
- void setPerf (KbPerf ∗newPerf, KbProfile ∗newProfile)

Static Public Attributes

- static const int I_COUNT = KbPerf::I_COUNT
- static const int HW_I_COUNT = KbPerf::HW_I_COUNT

Private Types

- enum HwMode {
  NORMAL, ALWAYS_ON, ALWAYS_OFF, RGB,
  BOTH }

Private Slots

- void uiUpdated (int index)
- void on_intensityBox_valueChanged (int arg1)
- void on_copyButton_clicked ()

Private Member Functions

- HwMode raw2Mode (bool sw_enable, i_hw hw_enable)
- void mode2Raw (HwMode mode, bool &sw_enable, i_hw &hw_enable)

Private Attributes

- Ui::KPerfWidget * ui
- KbPerf * perf
- KbProfile * profile
- IndicatorUi indicators [I_COUNT]
- QList< QWidget * > k95Widgets
- QSignalMapper updateMapper

12.45.1 Detailed Description

Definition at line 16 of file kperfwidget.h.

12.45.2 Data Structure Documentation

12.45.2.1 struct KPerfWidget::IndicatorUi

Definition at line 48 of file kperfwidget.h.

Collaboration diagram for KPerfWidget::IndicatorUi:

Data Fields

ColorButton *	color1	
ColorButton *	color2	
ColorButton *	color3	
QCheckBox *	enable	
QComboBox *	hwEnable	

12.45.3 Member Typedef Documentation

12.45.3.1 typedef KbPerf::i_hw KPerfWidget::i_hw

Definition at line 29 of file kperfwidget.h.

12.45.3.2 typedef KbPerf::indicator KPerfWidget::indicator

Definition at line 28 of file kperfwidget.h.

12.45.4 Member Enumeration Documentation

12.45.4.1 enum KPerfWidget::HwMode [private]

Enumerator

NORMAL

ALWAYS_ON

ALWAYS_OFF

RGB

BOTH

Definition at line 38 of file kperfwidget.h.

```
38                  {
39          NORMAL,
40          ALWAYS_ON,
41          ALWAYS_OFF,
42          RGB,
43          BOTH
44      };
```

12.45.5 Constructor & Destructor Documentation

12.45.5.1 KPerfWidget::KPerfWidget (QWidget * *parent* = 0) [explicit]

Definition at line 6 of file kperfwidget.cpp.

References ColorButton::allowAlpha(), ColorButton::bigIcons(), Ui_KPerfWidget::capsBox, Ui_KPerfWidget::capsColorOff, Ui_KPerfWidget::capsColorOn, KPerfWidget::IndicatorUi::color1, KPerfWidget::IndicatorUi::color2, KPerfWidget::IndicatorUi::color3, KPerfWidget::IndicatorUi::enable, KPerfWidget::IndicatorUi::hwEnable, I_COUNT, indicators, Ui_KPerfWidget::k95Label1, Ui_KPerfWidget::k95Label2, Ui_KPerfWidget::k95Label3, Ui_KPerfWidget::k95Label4, Ui_KPerfWidget::k95Label5, Ui_KPerfWidget::k95Label6, Ui_KPerfWidget::k95Line, Ui_KPerfWidget::k95Spacer, k95Widgets, Ui_KPerfWidget::lightBox, Ui_KPerfWidget::lightColor1, Ui_KPerfWidget::lightColor2, Ui_KPerfWidget::lightColor3, Ui_KPerfWidget::lockBox, Ui_KPerfWidget::lockColorOff, Ui_KPerfWidget::lockColorOn, Ui_KPerfWidget::macroBox, Ui_KPerfWidget::macroColorOff, Ui_KPerfWidget::macroColorOn, Ui_KPerfWidget::modeBox, Ui_KPerfWidget::modeColorOff, Ui_KPerfWidget::modeColorOn, Ui_KPerfWidget::muteBox, Ui_KPerfWidget::muteColorNA, Ui_KPerfWidget::muteColorOff, Ui_KPerfWidget::muteColorOn, Ui_KPerfWidget::numBox, Ui_KPerfWidget::numColorOff, Ui_KPerfWidget::numColorOn, Ui_KPerfWidget::scrollBox, Ui_KPerfWidget::scrollColorOff, Ui_KPerfWidget::scrollColorOn, ColorButton::setLabel(), Ui_KPerfWidget::setupUi(), ui, uiUpdated(), and updateMapper.

```
6                                       :
7       QWidget(parent),
8       ui(new Ui::KPerfWidget)
9   {
10       ui->setupUi(this);
11       // Set up indicators
12       indicators[0].enable = 0; indicators[0].hwEnable =
        ui->numBox; indicators[0].color1 = ui->numColorOn;
        indicators[0].color2 = ui->numColorOff; indicators[0].
        color3 = 0;
13       indicators[1].enable = 0; indicators[1].hwEnable =
```

```
    ui->capsBox; indicators[1].color1 = ui->capsColorOn;
    indicators[1].color2 = ui->capsColorOff;
    indicators[1].color3 = 0;
    indicators[2].enable = 0; indicators[2].hwEnable =
    ui->scrollBox; indicators[2].color1 = ui->
    scrollColorOn; indicators[2].color2 = ui->
    scrollColorOff; indicators[2].color3 = 0;
    indicators[3].enable = ui->modeBox; indicators[3].
    hwEnable = 0; indicators[3].color1 = ui->modeColorOn;
    indicators[3].color2 = ui->modeColorOff;
    indicators[3].color3 = 0;
    indicators[4].enable = ui->macroBox; indicators[4].
    hwEnable = 0; indicators[4].color1 = ui->macroColorOn;
    indicators[4].color2 = ui->macroColorOff;
    indicators[4].color3 = 0;
    indicators[5].enable = ui->lightBox; indicators[5].
    hwEnable = 0; indicators[5].color1 = ui->lightColor1;
    indicators[5].color2 = ui->lightColor2; indicators[5].
    color3 = ui->lightColor3;
    indicators[6].enable = ui->lockBox; indicators[6].
    hwEnable = 0; indicators[6].color1 = ui->lockColorOn;
    indicators[6].color2 = ui->lockColorOff;
    indicators[6].color3 = 0;
    indicators[7].enable = ui->muteBox; indicators[7].
    hwEnable = 0; indicators[7].color1 = ui->muteColorOn;
    indicators[7].color2 = ui->muteColorOff;
    indicators[7].color3 = ui->muteColorNA;
    for(int i = 0; i < I_COUNT; i++){
        indicators[i].color1->setLabel(false);
        indicators[i].color1->bigIcons(true);
        indicators[i].color1->allowAlpha(true);
        indicators[i].color2->setLabel(false);
        indicators[i].color2->bigIcons(true);
        indicators[i].color2->allowAlpha(true);
        if(indicators[i].color3){
            indicators[i].color3->setLabel(false);
            indicators[i].color3->bigIcons(true);
            indicators[i].color3->allowAlpha(true);
        }
        // Map signals
        if(indicators[i].enable){
            connect(indicators[i].enable, SIGNAL(clicked(bool)), &
    updateMapper, SLOT(map()));
            updateMapper.setMapping(indicators[i].enable, i);
        }
        if(indicators[i].hwEnable){
            connect(indicators[i].hwEnable, SIGNAL(activated(int)), &
    updateMapper, SLOT(map()));
            updateMapper.setMapping(indicators[i].hwEnable, i);
        }
        connect(indicators[i].color1, SIGNAL(colorChanged(QColor)), &
    updateMapper, SLOT(map()));
        updateMapper.setMapping(indicators[i].color1, i);
        connect(indicators[i].color2, SIGNAL(colorChanged(QColor)), &
    updateMapper, SLOT(map()));
        updateMapper.setMapping(indicators[i].color2, i);
        if(indicators[i].color3){
            connect(indicators[i].color3, SIGNAL(colorChanged(QColor)), &
    updateMapper, SLOT(map()));
            updateMapper.setMapping(indicators[i].color3, i);
        }
    }
    connect(&updateMapper, SIGNAL(mapped(int)), this, SLOT(uiUpdated(int)));
    k95Widgets << ui->modeBox << ui->modeColorOn <<
    ui->modeColorOff << ui->macroBox << ui->macroColorOn <<
    ui->macroColorOff << ui->k95Label1 << ui->k95Label2 <<
    ui->k95Label3 << ui->k95Label4 << ui->k95Label5 <<
    ui->k95Label6 << ui->k95Line << ui->k95Spacer;
}
```

Here is the call graph for this function:

12.45.5.2 KPerfWidget::~KPerfWidget ( )

Definition at line 54 of file kperfwidget.cpp.

References ui.

```
54                          {
55     delete ui;
56 }
```

12.45.6 Member Function Documentation

12.45.6.1 void KPerfWidget::mode2Raw (HwMode *mode*, bool & *sw_enable*, i_hw & *hw_enable*) [private]

Definition at line 72 of file kperfwidget.cpp.

References ALWAYS_OFF, ALWAYS_ON, BOTH, NORMAL, KbPerf::NORMAL, KbPerf::OFF, KbPerf::ON, and RGB.

Referenced by uiUpdated().

```
72                                                                  {
73     switch(mode){
74     case NORMAL:
75         sw_enable = false;
76         hw_enable = KbPerf::NORMAL;
77         break;
78     case ALWAYS_ON:
79         sw_enable = false;
80         hw_enable = KbPerf::ON;
81         break;
82     case ALWAYS_OFF:
83         sw_enable = false;
84         hw_enable = KbPerf::OFF;
85         break;
86     case RGB:
87         sw_enable = true;
88         hw_enable = KbPerf::OFF;
89         break;
90     case BOTH:
91         sw_enable = true;
92         hw_enable = KbPerf::NORMAL;
93         break;
94     }
95 }
```

Here is the caller graph for this function:

12.45.6.2 void KPerfWidget::on_copyButton_clicked ( ) [private],[slot]

Definition at line 193 of file kperfwidget.cpp.

References KbProfile::currentMode(), KbProfile::modes(), perf, KbMode::perf(), profile, and ModeSelectDialog::selection().

```
193                                         {
194     ModeSelectDialog dialog(this, profile->currentMode(),
      profile->modes(), "Copy performance settings to:");
195     if(dialog.exec() != QDialog::Accepted)
196         return;
197     QList<KbMode*> selectedModes = dialog.selection();
198     foreach(KbMode* mode, selectedModes){
199         *mode->perf() = *perf;
200     }
201 }
```

Here is the call graph for this function:

12.45.6.3 void KPerfWidget::on_intensityBox_valueChanged (int *arg1*) [private],[slot]

Definition at line 187 of file kperfwidget.cpp.

References KbPerf::iOpacity(), and perf.

```
187                                                     {
188     if(!perf)
189         return;
190     perf->iOpacity(arg1 / 100.f);
191 }
```

Here is the call graph for this function:

12.45.6.4 KPerfWidget::HwMode KPerfWidget::raw2Mode (bool *sw_enable,* i_hw *hw_enable*) [private]

Definition at line 58 of file kperfwidget.cpp.

References ALWAYS_OFF, ALWAYS_ON, BOTH, NORMAL, KbPerf::NORMAL, KbPerf::OFF, KbPerf::ON, and RGB.

Referenced by setPerf().

```
58                                                                  {
59     if(sw_enable){
60         if(hw_enable == KbPerf::NORMAL)
61             return BOTH;
62         return RGB;
63     } else {
64         if(hw_enable == KbPerf::ON)
65             return ALWAYS_ON;
66         else if(hw_enable == KbPerf::OFF)
67             return ALWAYS_OFF;
68         return NORMAL;
69     }
70 }
```

Here is the caller graph for this function:

12.45.6.5 void KPerfWidget::setPerf (KbPerf * *newPerf,* KbProfile * *newProfile*)

Definition at line 97 of file kperfwidget.cpp.

References BOTH, ColorButton::color(), KPerfWidget::IndicatorUi::color1, KPerfWidget::IndicatorUi::color2, KPerfWidget::IndicatorUi::color3, KPerfWidget::IndicatorUi::enable, KbPerf::getIndicator(), HW_I_COUNT, KPerfWidget::IndicatorUi::hwEnable, I_COUNT, indicators, Ui_KPerfWidget::intensityBox, KbPerf::iOpacity(), KeyMap::K95, k95Widgets, KbProfile::keyMap(), Ui_KPerfWidget::label_12, Ui_KPerfWidget::label_14, Ui_KPerfWidget::label_17, KeyMap::model(), Ui_KPerfWidget::muteBox, Ui_KPerfWidget::muteColorNA, Ui_KPerfWidget::muteColorOff, Ui_KPerfWidget::muteColorOn, perf, profile, raw2Mode(), RGB, KeyMap::STRAFE, and ui.

Referenced by KbWidget::modeChanged().

```
97                                                          {
98     perf = newPerf;
```

```
    profile = newProfile;
    // Set intensity
    ui->intensityBox->setValue(round(perf->iOpacity() * 100.f));
    // Set hardware indicator values
    for(int i = 0; i < HW_I_COUNT; i++){
        QColor c1, c2, c3;
        bool software;
        i_hw hardware;
        perf->getIndicator((indicator)i, c1, c2, c3, software, hardware);
        HwMode mode = raw2Mode(software, hardware);
        indicators[i].hwEnable->setCurrentIndex((int)mode);
        indicators[i].color1->color(c1);
        indicators[i].color2->color(c2);
        if(mode == RGB || mode == BOTH){
            indicators[i].color1->setEnabled(true);
            indicators[i].color2->setEnabled(true);
        } else {
            indicators[i].color1->setEnabled(false);
            indicators[i].color2->setEnabled(false);
        }
    }
    // Set software indicators
    for(int i = HW_I_COUNT; i < I_COUNT; i++){
        QColor c1, c2, c3;
        bool software;
        i_hw hardware;
        perf->getIndicator((indicator)i, c1, c2, c3, software, hardware);
        indicators[i].enable->setChecked(software);
        indicators[i].color1->color(c1);
        indicators[i].color2->color(c2);
        if(indicators[i].color3) indicators[i].color3->color(c3);
        if(software){
            indicators[i].color1->setEnabled(true);
            indicators[i].color2->setEnabled(true);
            if(indicators[i].color3) indicators[i].color3->setEnabled(true);
        } else {
            indicators[i].color1->setEnabled(false);
            indicators[i].color2->setEnabled(false);
            if(indicators[i].color3) indicators[i].color3->setEnabled(false);
        }
    }
    // Hide K95 indicators on non-K95s
    if(profile->keyMap().model() == KeyMap::K95){
        foreach(QWidget* w, k95Widgets)
            w->show();
    } else {
        foreach(QWidget* w, k95Widgets)
            w->hide();
        if(profile->keyMap().model() == KeyMap::STRAFE) { // hide indicators unsupported by STRAFE
            ui->muteBox->hide();
            ui->muteColorOn->hide();
            ui->muteColorOff->hide();
            ui->muteColorNA->hide();
            ui->label_12->hide();
            ui->label_14->hide();
            ui->label_17->hide();
        }
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.45.6.6 void KPerfWidget::uiUpdated (int *index*) [private],[slot]

Definition at line 159 of file kperfwidget.cpp.

References ColorButton::color(), KPerfWidget::IndicatorUi::color1, KPerfWidget::IndicatorUi::color2, KPerfWidget::IndicatorUi::color3, KPerfWidget::IndicatorUi::enable, indicators, mode2Raw(), KbPerf::NONE, perf, and KbPerf::setIndicator().

Referenced by KPerfWidget().

```
159                                     {
160     if(!perf)
161         return;
162     // Read HW/SW enable state
163     bool software;
164     i_hw hardware;
165     if(indicators[index].enable){
166         software = indicators[index].enable->isChecked();
167         hardware = KbPerf::NONE;
168     } else {
```

```
        mode2Raw((HwMode)indicators[index].hwEnable->currentIndex(), software, hardware);
    }
    // Enable/disable color buttons based on whether or not the indicator is turned on
    if(software){
        indicators[index].color1->setEnabled(true);
        indicators[index].color2->setEnabled(true);
        if(indicators[index].color3) indicators[index].color3->setEnabled(true);
    } else {
        indicators[index].color1->setEnabled(false);
        indicators[index].color2->setEnabled(false);
        if(indicators[index].color3) indicators[index].color3->setEnabled(false);
    }
    QColor c1 = indicators[index].color1->color();
    QColor c2 = indicators[index].color2->color();
    QColor c3 = indicators[index].color3 ? indicators[index].color3->color() : QColor();
    perf->setIndicator((indicator)index, c1, c2, c3, software, hardware);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.45.7 Field Documentation

12.45.7.1 const int KPerfWidget::HW_I_COUNT = KbPerf::HW_I_COUNT [static]

Definition at line 27 of file kperfwidget.h.

Referenced by setPerf().

12.45.7.2 const int KPerfWidget::I_COUNT = KbPerf::I_COUNT [static]

Definition at line 26 of file kperfwidget.h.

Referenced by KPerfWidget(), and setPerf().

12.45.7.3 IndicatorUi KPerfWidget::indicators[I_COUNT] [private]

Definition at line 53 of file kperfwidget.h.

Referenced by KPerfWidget(), setPerf(), and uiUpdated().

12.45.7.4 QList<QWidget*> KPerfWidget::k95Widgets [private]

Definition at line 54 of file kperfwidget.h.

Referenced by KPerfWidget(), and setPerf().

12.45.7.5 KbPerf* KPerfWidget::perf [private]

Definition at line 34 of file kperfwidget.h.

Referenced by on_copyButton_clicked(), on_intensityBox_valueChanged(), setPerf(), and uiUpdated().

12.45.7.6 KbProfile* KPerfWidget::profile [private]

Definition at line 35 of file kperfwidget.h.

Referenced by on_copyButton_clicked(), and setPerf().

12.45.7.7 Ui::KPerfWidget* KPerfWidget::ui [private]

Definition at line 32 of file kperfwidget.h.

Referenced by KPerfWidget(), setPerf(), and ~KPerfWidget().

12.45.7.8 QSignalMapper KPerfWidget::updateMapper [private]

Definition at line 56 of file kperfwidget.h.

Referenced by KPerfWidget().

The documentation for this class was generated from the following files:

- src/ckb/kperfwidget.h
- src/ckb/kperfwidget.cpp

12.46 Ui::LayoutDialog Class Reference

```
#include <src/ckb/ui_layoutdialog.h>
```

Inheritance diagram for Ui::LayoutDialog:

Collaboration diagram for Ui::LayoutDialog:

Public Member Functions

- void setupUi (QDialog *LayoutDialog)
- void retranslateUi (QDialog *LayoutDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QDialogButtonBox * buttonBox
- QLabel * label
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer_2
- QSpacerItem * horizontalSpacer
- QComboBox * comboBox
- QLabel * label_2
- QSpacerItem * verticalSpacer_4

12.46.1 Detailed Description

Definition at line 119 of file ui_layoutdialog.h.

12.46.2 Member Function Documentation

12.46.2.1 void Ui_LayoutDialog::retranslateUi (QDialog * *LayoutDialog*) [inline], [inherited]

Definition at line 109 of file ui_layoutdialog.h.

References Ui_LayoutDialog::label, and Ui_LayoutDialog::label_2.

Referenced by Ui_LayoutDialog::setupUi().

```
    {
        LayoutDialog->setWindowTitle(QApplication::translate("LayoutDialog", "Keyboard Layout", Q_NULLPTR));
        label->setText(QApplication::translate("LayoutDialog", "Please select your keyboard layout:", Q_NULLPTR));
        label_2->setText(QApplication::translate("LayoutDialog", "Note: this only controls the layout within the ckb application. If your keys are typing the wrong characters, check your system preferences.", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.46.2.2 void Ui_LayoutDialog::setupUi (QDialog * *LayoutDialog*) [inline],[inherited]

Definition at line 41 of file ui_layoutdialog.h.

References Ui_LayoutDialog::buttonBox, Ui_LayoutDialog::comboBox, Ui_LayoutDialog::gridLayout, Ui_LayoutDialog::horizontalSpacer, Ui_LayoutDialog::horizontalSpacer_2, Ui_LayoutDialog::label, Ui_LayoutDialog::label_2, Ui_LayoutDialog::retranslateUi(), Ui_LayoutDialog::verticalSpacer, Ui_LayoutDialog::verticalSpacer_2, Ui_LayoutDialog::verticalSpacer_3, and Ui_LayoutDialog::verticalSpacer_4.

Referenced by LayoutDialog::LayoutDialog().

```
42     {
43         if (LayoutDialog->objectName().isEmpty())
44             LayoutDialog->setObjectName(QStringLiteral("LayoutDialog"));
45         LayoutDialog->resize(400, 240);
46         gridLayout = new QGridLayout(LayoutDialog);
47         gridLayout->setObjectName(QStringLiteral("gridLayout"));
48         verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );
49
50         gridLayout->addItem(verticalSpacer, 6, 0, 1, 3);
51
52         verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);
53
54         gridLayout->addItem(verticalSpacer_3, 0, 1, 1, 1);
55
56         buttonBox = new QDialogButtonBox(LayoutDialog);
57         buttonBox->setObjectName(QStringLiteral("buttonBox"));
58         buttonBox->setOrientation(Qt::Horizontal);
59         buttonBox->setStandardButtons(QDialogButtonBox::Ok);
60
61         gridLayout->addWidget(buttonBox, 7, 0, 1, 3);
62
63         label = new QLabel(LayoutDialog);
64         label->setObjectName(QStringLiteral("label"));
65         label->setAlignment(Qt::AlignCenter);
66
67         gridLayout->addWidget(label, 1, 0, 1, 3);
68
69         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
70
71         gridLayout->addItem(horizontalSpacer_2, 3, 2, 1, 1);
72
73         verticalSpacer_2 = new QSpacerItem(20, 15, QSizePolicy::Minimum, QSizePolicy::Fixed
    );
74
75         gridLayout->addItem(verticalSpacer_2, 4, 1, 1, 1);
76
77         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
78
79         gridLayout->addItem(horizontalSpacer, 3, 0, 1, 1);
80
81         comboBox = new QComboBox(LayoutDialog);
82         comboBox->setObjectName(QStringLiteral("comboBox"));
83
84         gridLayout->addWidget(comboBox, 3, 1, 1, 1);
85
86         label_2 = new QLabel(LayoutDialog);
87         label_2->setObjectName(QStringLiteral("label_2"));
88         QFont font;
89         font.setPointSize(8);
90         font.setItalic(true);
91         label_2->setFont(font);
92         label_2->setAlignment(Qt::AlignCenter);
93         label_2->setWordWrap(true);
94
95         gridLayout->addWidget(label_2, 5, 0, 1, 3);
96
97         verticalSpacer_4 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed)
    ;
98
99         gridLayout->addItem(verticalSpacer_4, 2, 1, 1, 1);
100
101
102         retranslateUi(LayoutDialog);
103         QObject::connect(buttonBox, SIGNAL(accepted()), LayoutDialog, SLOT(accept()));
104         QObject::connect(buttonBox, SIGNAL(rejected()), LayoutDialog, SLOT(reject()));
105
106         QMetaObject::connectSlotsByName(LayoutDialog);
107     } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.46.3 Field Documentation

12.46.3.1 QDialogButtonBox* Ui_LayoutDialog::buttonBox [inherited]

Definition at line 32 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.2 QComboBox* Ui_LayoutDialog::comboBox [inherited]

Definition at line 37 of file ui_layoutdialog.h.

Referenced by LayoutDialog::LayoutDialog(), LayoutDialog::selected(), and Ui_LayoutDialog::setupUi().

12.46.3.3 QGridLayout* Ui_LayoutDialog::gridLayout [inherited]

Definition at line 29 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.4 QSpacerItem* Ui_LayoutDialog::horizontalSpacer [inherited]

Definition at line 36 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.5 QSpacerItem* Ui_LayoutDialog::horizontalSpacer_2 [inherited]

Definition at line 34 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.6 QLabel* Ui_LayoutDialog::label [inherited]

Definition at line 33 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::retranslateUi(), and Ui_LayoutDialog::setupUi().

12.46.3.7 QLabel* Ui_LayoutDialog::label_2 [inherited]

Definition at line 38 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::retranslateUi(), and Ui_LayoutDialog::setupUi().

12.46.3.8 QSpacerItem* Ui_LayoutDialog::verticalSpacer [inherited]

Definition at line 30 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.9 QSpacerItem* Ui_LayoutDialog::verticalSpacer_2 [inherited]

Definition at line 35 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.10 QSpacerItem* Ui_LayoutDialog::verticalSpacer_3 [inherited]

Definition at line 31 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

12.46.3.11 QSpacerItem* Ui_LayoutDialog::verticalSpacer_4 [inherited]

Definition at line 39 of file ui_layoutdialog.h.

Referenced by Ui_LayoutDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_layoutdialog.h

12.47 LayoutDialog Class Reference

```
#include <src/ckb/layoutdialog.h>
```

Inheritance diagram for LayoutDialog:

Collaboration diagram for LayoutDialog:

Public Member Functions

- LayoutDialog (QWidget *parent=0)
- ~LayoutDialog ()
- KeyMap::Layout selected () const

Private Attributes

- Ui::LayoutDialog * ui

12.47.1 Detailed Description

Definition at line 13 of file layoutdialog.h.

12.47.2 Constructor & Destructor Documentation

12.47.2.1 LayoutDialog::LayoutDialog (QWidget * *parent* = 0) [explicit]

Definition at line 5 of file layoutdialog.cpp.

References Ui_LayoutDialog::comboBox, Kb::layout(), KeyMap::layoutNames(), Ui_LayoutDialog::setupUi(), and ui.

```
5                                       :
6     QDialog(parent),
7     ui(new Ui::LayoutDialog) {
8     ui->setupUi(this);
9     // Populate layout list
10     ui->comboBox->addItems(KeyMap::layoutNames());
11     ui->comboBox->setCurrentIndex((int)Kb::layout());
12 }
```

Here is the call graph for this function:

12.47.2.2 LayoutDialog::~LayoutDialog ( )

Definition at line 14 of file layoutdialog.cpp.

References ui.

```
14                              {
15     delete ui;
16 }
```

12.47.3 Member Function Documentation

12.47.3.1 KeyMap::Layout LayoutDialog::selected ( ) const

Definition at line 18 of file layoutdialog.cpp.

References Ui_LayoutDialog::comboBox, and ui.

Referenced by SettingsWidget::showLayoutDialog().

```
18                                          {
19     return (KeyMap::Layout)ui->comboBox->currentIndex();
20 }
```

Here is the caller graph for this function:

12.47.4 Field Documentation

12.47.4.1 Ui::LayoutDialog* LayoutDialog::ui [private]

Definition at line 24 of file layoutdialog.h.

Referenced by LayoutDialog(), selected(), and ~LayoutDialog().

The documentation for this class was generated from the following files:

- src/ckb/layoutdialog.h
- src/ckb/layoutdialog.cpp

12.48 MacroReader Class Reference

The MacroReader class creates a worker thread object. It does a connect do delayed deletion of thread local variables in the case the worker thread terminates.

`#include <src/ckb/macroreader.h>`

Inheritance diagram for MacroReader:

Collaboration diagram for MacroReader:

Public Member Functions

- MacroReader ()

  MacroReader Calling MacroReader without params is not allowed.
- MacroReader (int macroNumber, QString macroPath, QPlainTextEdit ∗macBox, QPlainTextEdit ∗macText)

  MacroReader This is the only allowed constructor. It only calls startWorkInAThread() with the four params.
- ∼MacroReader ()
- void startWorkInAThread (int macroNumber, QString macroPath, QPlainTextEdit ∗macBox, QPlainTextEdit ∗macText)

  startWorkInAThread This member function creates the new thread object and starts it with the four params.

Private Attributes

- MacroReaderThread ∗ macroReaderThread

12.48.1 Detailed Description

Definition at line 87 of file macroreader.h.

12.48.2 Constructor & Destructor Documentation

12.48.2.1 MacroReader::MacroReader ( )

Definition at line 8 of file macroreader.cpp.

```
8                           {
9     qDebug() << "Calling MacroReader without params is not allowed.";
10 }
```

12.48.2.2 MacroReader::MacroReader (int *macroNumber*, QString *macroPath*, QPlainTextEdit * *macBox*, QPlainTextEdit * *macText*)

Parameters

macroNumber	
macroPath	
macBox	
macText	

Definition at line 12 of file macroreader.cpp.

References startWorkInAThread().

```
12
        {
13     startWorkInAThread(macroNumber, macroPath, macBox, macText);
14 }
```

Here is the call graph for this function:

12.48.2.3 MacroReader::~MacroReader ( )

Definition at line 15 of file macroreader.cpp.

```
15 {}
```

12.48.3 Member Function Documentation

12.48.3.1 void MacroReader::startWorkInAThread (int *macroNumber*, QString *macroPath*, QPlainTextEdit * *macBox*, QPlainTextEdit * *macText*)

Parameters

macroNumber	
macroPath	
macBox	
macText	

Definition at line 17 of file macroreader.cpp.

References macroReaderThread.

Referenced by MacroReader().

```
17                                                  {
18     macroReaderThread = new MacroReaderThread(macroNumber, macroPath,
       macBox, macText);
19     connect(macroReaderThread, &MacroReaderThread::finished,
       macroReaderThread, &QObject::deleteLater);
20     macroReaderThread->start();
21 }
```

Here is the caller graph for this function:

12.48.4 Field Documentation

12.48.4.1 MacroReaderThread* MacroReader::macroReaderThread [private]

Definition at line 123 of file macroreader.h.

Referenced by startWorkInAThread().

The documentation for this class was generated from the following files:

- src/ckb/macroreader.h
- src/ckb/macroreader.cpp

12.49 MacroReaderThread Class Reference

The MacroReaderThread class is responsible for reading Macro Key Values. It is created as a separate thread (worker thread) for reading macro commands from an fresh opened notify channel. Standard notify channel for macro definitions is number 2.

`#include <src/ckb/macroreader.h>`

Inheritance diagram for MacroReaderThread:

Collaboration diagram for MacroReaderThread:

Public Member Functions

- MacroReaderThread (int macNum, QString macPath, QPlainTextEdit ∗macBox, QPlainTextEdit ∗macText)

  MacroReaderThread saves the four params to local vars with similar varNames.

- void run () Q_DECL_OVERRIDE

  run is the notification reader main loop.

Private Slots

- void readMacro (QString line)

  readMacro is called for each line received by the worker thread. The method ist called via signal (metaObject) from the worker thread, which reads the keyboard input. Just display the key code in the macroBox Widget without he trailing newline and reposition the cursor in the macro pane.

Private Attributes

- int macroNumber

  macroNumber Filenames of nofity channels have the structure <input-device-path>/ckb1/notify<number> First part is hold in macroPath, the number is hold in macroNumber. macroNumber may range from 0 to 9.
- QString macroPath

  macroPath holds the path for the notify channel
- QPlainTextEdit * macroBox

  macroBox will receive the Macro Key Values sent from the keyboard while defining a new macro.
- QPlainTextEdit * macroText

  macroText is the other textpane used in the UI while typing new macros. That variable is used for setting the focus to that textpane and to set the cursor at EOT.

12.49.1 Detailed Description

While the worker Thread gets input from the keyboard, the lines are sent via signalling (metaobject) to run a member function in the context of the Qt UI manager.

When the notify channel is closed (that's normally done by pressing "Stop"-Button in the UI), the worker thread closes the channelFile and leaves.

See Also

MacroReaderThread(), ~MacroReaderThread(), readMaco(), run()

Definition at line 22 of file macroreader.h.

12.49.2 Constructor & Destructor Documentation

12.49.2.1 MacroReaderThread::MacroReaderThread (int *macNum*, QString *macPath*, QPlainTextEdit * *macBox*, QPlainTextEdit * *macText*) [inline]

Parameters

macNum	
macPath	
macBox	
macText	

Definition at line 55 of file macroreader.h.

References macroBox, macroNumber, macroPath, and macroText.

```
55                                                                                                                    {
56         macroNumber = macNum;
57         macroPath = macPath;
58         macroBox = macBox;
59         macroText = macText;
60     }
```

12.49.3 Member Function Documentation

12.49.3.1 void MacroReaderThread::readMacro (QString *line*) [private],[slot]

This is used, because the worker thread shouldn't get access to the UI elements (and normally has none, because the pointers macroBox and macroText remain on the stack). That mechanism guarantees, that the UI does not freeze if it happens something magic to the reading function.

Parameters

line	holds the line just got from keyboard

We want to see the keys as they appear in the macroText Widget.

Because it is possible to change the Focus via keyboard, we must set the focus on each call.

Definition at line 26 of file macroreader.cpp.

References macroBox, and macroText.

```
26                                                  {
31      macroText->setFocus();
32      QTextCursor c = macroText->textCursor();
33      c.setPosition(macroText->toPlainText().length());
34      macroText->setTextCursor(c);
35      macroBox->appendPlainText(line.left(line.size()-1));
36  }
```

12.49.3.2 void MacroReaderThread::run ( )

MacroReaderThread::run is the standard main function for a thread. Tries to open a file <macroPath><macroNumber> several times (in this case, it should be possible the first time (the code was recycled from kb.cpp).

While the file is open, read lines an signal them via metaObject() to the main thread. When the file is closed by the sender, close it as reader and terminate.

Definition at line 46 of file macroreader.cpp.

References macroBox, macroNumber, macroPath, and macroText.

```
46                                  {
47      qDebug() << "MacroReader::run() started with" << macroNumber << "and" <<
        macroPath << "and" << macroBox << "and" << macroText;
48
49      QFile macroFile(macroPath);
50      // Wait a small amount of time for the node to open (100ms) (code reused from kb.cpp)
51      QThread::usleep(100000);
52      if(!macroFile.open(QIODevice::ReadOnly)){
53          // If it's still not open, try again before giving up (1s at a time, 10s total)
54          QThread::usleep(900000);
55          for(int i = 1; i < 10; i++){
56              if(macroFile.open(QIODevice::ReadOnly))
57                  break;
58              QThread::sleep(1);
59          }
60          if(!macroFile.isOpen()) {
61              qDebug() << QString("unable to open macroFile (%1)").arg(macroPath);
62              return;
63          }
64      }
65      // Read data from notification node macroPath
66      QByteArray line;
67      while(macroFile.isOpen() && (line = macroFile.readLine()).length() > 0){
68          QString text = QString::fromUtf8(line);
69          metaObject()->invokeMethod(this, "readMacro", Qt::QueuedConnection, Q_ARG(QString, text));
70      }
71      qDebug() << "MacroReader::run() ends.";
72      macroFile.close();
73      QThread::exit ();
74  }
```

12.49.4 Field Documentation

12.49.4.1 QPlainTextEdit* MacroReaderThread::macroBox [private]

Definition at line 40 of file macroreader.h.

Referenced by MacroReaderThread(), readMacro(), and run().

12.49.4.2 int MacroReaderThread::macroNumber [private]

Definition at line 31 of file macroreader.h.

Referenced by MacroReaderThread(), and run().

12.49.4.3 QString MacroReaderThread::macroPath [private]

See Also

macroNumber

Definition at line 36 of file macroreader.h.

Referenced by MacroReaderThread(), and run().

12.49.4.4 QPlainTextEdit* MacroReaderThread::macroText [private]

Definition at line 45 of file macroreader.h.

Referenced by MacroReaderThread(), readMacro(), and run().

The documentation for this class was generated from the following files:

- src/ckb/macroreader.h
- src/ckb/macroreader.cpp

12.50 Ui::MainWindow Class Reference

```
#include <src/ckb/ui_mainwindow.h>
```

Inheritance diagram for Ui::MainWindow:

Collaboration diagram for Ui::MainWindow:

Public Member Functions

- void setupUi (QMainWindow *MainWindow)
- void retranslateUi (QMainWindow *MainWindow)

Data Fields

- QAction * actionExit
- QAction * actionAbout
- QWidget * centralWidget
- QGridLayout * gridLayout
- QTabWidget * tabWidget

12.50.1 Detailed Description

Definition at line 79 of file ui_mainwindow.h.

12.50.2 Member Function Documentation

12.50.2.1 void Ui_MainWindow::retranslateUi (QMainWindow * *MainWindow*) [inline],[inherited]

Definition at line 68 of file ui_mainwindow.h.

References Ui_MainWindow::actionAbout, and Ui_MainWindow::actionExit.

Referenced by Ui_MainWindow::setupUi().

```
    {
        MainWindow->setWindowTitle(QApplication::translate("MainWindow", "ckb-next", Q_NULLPTR));
        actionExit->setText(QApplication::translate("MainWindow", "Exit", Q_NULLPTR));
        actionExit->setShortcut(QApplication::translate("MainWindow", "Ctrl+Q", Q_NULLPTR));
        actionAbout->setText(QApplication::translate("MainWindow", "About", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.50.2.2 void Ui_MainWindow::setupUi (QMainWindow * *MainWindow*) [inline],[inherited]

Definition at line 33 of file ui_mainwindow.h.

References Ui_MainWindow::actionAbout, Ui_MainWindow::actionExit, Ui_MainWindow::centralWidget, Ui_MainWindow::gridLayout, Ui_MainWindow::retranslateUi(), and Ui_MainWindow::tabWidget.

Referenced by MainWindow::MainWindow().

```
    {
        if (MainWindow->objectName().isEmpty())
            MainWindow->setObjectName(QStringLiteral("MainWindow"));
        MainWindow->resize(1000, 750);
        MainWindow->setMinimumSize(QSize(1000, 750));
        QIcon icon;
        icon.addFile(QStringLiteral(":/img/ckb-logo.png"), QSize(), QIcon::Normal, QIcon::Off);
```

```
        MainWindow->setWindowIcon(icon);
        MainWindow->setUnifiedTitleAndToolBarOnMac(true);
        actionExit = new QAction(MainWindow);
        actionExit->setObjectName(QStringLiteral("actionExit"));
        actionAbout = new QAction(MainWindow);
        actionAbout->setObjectName(QStringLiteral("actionAbout"));
        centralWidget = new QWidget(MainWindow);
        centralWidget->setObjectName(QStringLiteral("centralWidget"));
        gridLayout = new QGridLayout(centralWidget);
        gridLayout->setSpacing(6);
        gridLayout->setContentsMargins(11, 11, 11, 11);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        tabWidget = new QTabWidget(centralWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));

        gridLayout->addWidget(tabWidget, 0, 0, 1, 1);

        MainWindow->setCentralWidget(centralWidget);

        retranslateUi(MainWindow);

        tabWidget->setCurrentIndex(-1);


        QMetaObject::connectSlotsByName(MainWindow);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.50.3 Field Documentation

12.50.3.1 QAction* Ui_MainWindow::actionAbout [inherited]

Definition at line 28 of file ui_mainwindow.h.

Referenced by Ui_MainWindow::retranslateUi(), and Ui_MainWindow::setupUi().

12.50.3.2 QAction* Ui_MainWindow::actionExit [inherited]

Definition at line 27 of file ui_mainwindow.h.

Referenced by MainWindow::MainWindow(), Ui_MainWindow::retranslateUi(), and Ui_MainWindow::setupUi().

12.50.3.3 QWidget* Ui_MainWindow::centralWidget [inherited]

Definition at line 29 of file ui_mainwindow.h.

Referenced by Ui_MainWindow::setupUi().

12.50.3.4 QGridLayout* Ui_MainWindow::gridLayout [inherited]

Definition at line 30 of file ui_mainwindow.h.

Referenced by Ui_MainWindow::setupUi().

12.50.3.5 QTabWidget* Ui_MainWindow::tabWidget [inherited]

Definition at line 31 of file ui_mainwindow.h.

Referenced by MainWindow::addDevice(), MainWindow::MainWindow(), MainWindow::removeDevice(), Ui_MainWindow::setupUi(), and MainWindow::showFwUpdateNotification().

The documentation for this class was generated from the following file:

- src/ckb/ui_mainwindow.h

12.51 MainWindow Class Reference

```
#include <src/ckb/mainwindow.h>
```

Inheritance diagram for MainWindow:

Collaboration diagram for MainWindow:

Public Slots

- void showWindow ()
- void stateChange (Qt::ApplicationState state)
- void quitApp ()

Public Member Functions

- MainWindow (QWidget ∗parent=0)
- ∼MainWindow ()
- void toggleTrayIcon (bool visible)

Static Public Attributes

- static MainWindow ∗ mainWindow = 0

Private Slots

- void addDevice (Kb ∗device)
- void removeDevice (Kb ∗device)
- void updateVersion ()
- void checkFwUpdates ()
- void timerTick ()
- void iconClicked (QSystemTrayIcon::ActivationReason reason)
- void cleanup ()
- void showFwUpdateNotification (QWidget ∗widget, float version)

Private Member Functions

- void closeEvent (QCloseEvent ∗event)

Private Attributes

- SettingsWidget * settingsWidget
- QList< KbWidget * > kbWidgets
- QAction * restoreAction
- QAction * closeAction
- QMenu * trayIconMenu
- QSystemTrayIcon * trayIcon
- Ui::MainWindow * ui

12.51.1 Detailed Description

Definition at line 27 of file mainwindow.h.

12.51.2 Constructor & Destructor Documentation

12.51.2.1 MainWindow::MainWindow (QWidget * *parent* = 0) [explicit]

Definition at line 35 of file mainwindow.cpp.

References Ui_MainWindow::actionExit, addDevice(), cleanup(), closeAction, configLabel, CkbSettings::get(), iconClicked(), KbManager::init(), KbManager::kbManager(), mainWindow, quitApp(), removeDevice(), restoreAction, KbManager::scanTimer(), settingsWidget, Ui_MainWindow::setupUi(), SettingsWidget::setVersion(), showWindow(), stateChange(), Ui_MainWindow::tabWidget, timerTick(), toggleTrayIcon(), trayIcon, trayIconMenu, ui, and updateVersion().

```
35                                      :
36     QMainWindow(parent),
37     ui(new Ui::MainWindow)
38 {
39     ui->setupUi(this);
40     mainWindow = this;
41
42     // Start device manager
43     KbManager::init(CKB_VERSION_STR);
44     connect(KbManager::kbManager(), SIGNAL(kbConnected(Kb*)), this, SLOT(
      addDevice(Kb*)));
45     connect(KbManager::kbManager(), SIGNAL(kbDisconnected(Kb*)), this, SLOT(
      removeDevice(Kb*)));
46     connect(KbManager::kbManager(), SIGNAL(versionUpdated()), this, SLOT(
      updateVersion()));
47     connect(KbManager::scanTimer(), SIGNAL(timeout()), this, SLOT(
      timerTick()));
48
49     // Set up tray icon
50     restoreAction = new QAction(tr("Restore"), this);
51     closeAction = new QAction(tr("Quit ckb"), this);
52 #ifdef USE_LIBAPPINDICATOR
53     QString desktop = std::getenv("XDG_CURRENT_DESKTOP");
54     unityDesktop = (desktop.toLower() == "unity");
55
56     if(unityDesktop){
57         trayIcon = 0;
58
59         indicatorMenu = gtk_menu_new();
60         indicatorMenuRestoreItem = gtk_menu_item_new_with_label("Restore");
61         indicatorMenuQuitItem = gtk_menu_item_new_with_label("Quit ckb");
62
63         gtk_menu_shell_append(GTK_MENU_SHELL(indicatorMenu), indicatorMenuRestoreItem);
64         gtk_menu_shell_append(GTK_MENU_SHELL(indicatorMenu), indicatorMenuQuitItem);
65
66         g_signal_connect(indicatorMenuQuitItem, "activate",
67             G_CALLBACK(quitIndicator), this);
68         g_signal_connect(indicatorMenuRestoreItem, "activate",
69             G_CALLBACK(restoreIndicator), this);
70
71         gtk_widget_show(indicatorMenuRestoreItem);
72         gtk_widget_show(indicatorMenuQuitItem);
73
74         indicator = app_indicator_new("ckb", "indicator-messages",
      APP_INDICATOR_CATEGORY_APPLICATION_STATUS);
75
```

```
        app_indicator_set_status(indicator, APP_INDICATOR_STATUS_ACTIVE);
        app_indicator_set_menu(indicator, GTK_MENU(indicatorMenu));
        app_indicator_set_icon(indicator, "ckb");
    } else
#endif // USE_LIBAPPINDICATOR
    {
        trayIconMenu = new QMenu(this);
        trayIconMenu->addAction(restoreAction);
        trayIconMenu->addAction(closeAction);
        trayIcon = new QSystemTrayIcon(QIcon(":/img/ckb-logo.png"), this);
        trayIcon->setContextMenu(trayIconMenu);
        connect(trayIcon, SIGNAL(activated(QSystemTrayIcon::ActivationReason)), this, SLOT(iconClicked(QSystemTrayIcon::ActivationReason)));
    }
    toggleTrayIcon(!CkbSettings::get("Program/SuppressTrayIcon").toBool());

#ifdef Q_OS_MACX
    // Make a custom "Close" menu action for OSX, as the default one brings up the "still running" popup unnecessarily
    QMenuBar* menuBar = new QMenuBar(this);
    setMenuBar(menuBar);
    this->menuBar()->addMenu("ckb")->addAction(closeAction);
#else
    // On linux, add a handler for Ctrl+Q
    new QShortcut(QKeySequence("Ctrl+Q"), this, SLOT(quitApp()));
#endif

    connect(ui->actionExit, SIGNAL(triggered()), this, SLOT(quitApp()));
    connect(closeAction, SIGNAL(triggered()), this, SLOT(quitApp()));
    connect(restoreAction, SIGNAL(triggered()), this, SLOT(showWindow()));
    connect(qApp, SIGNAL(applicationStateChanged(Qt::ApplicationState)), this, SLOT(stateChange(Qt::ApplicationState)));

    connect(qApp, SIGNAL(aboutToQuit()), this, SLOT(cleanup()));

    ui->tabWidget->addTab(settingsWidget = new SettingsWidget(this), configLabel);
    settingsWidget->setVersion("ckb-next " CKB_VERSION_STR);
}
```

Here is the call graph for this function:

12.51.2.2 MainWindow::~MainWindow ( )

Definition at line 303 of file mainwindow.cpp.

References cleanup(), and ui.

```
303                         {
304     cleanup();
305     delete ui;
306 }
```

Here is the call graph for this function:

12.51.3 Member Function Documentation

12.51.3.1 void MainWindow::addDevice (Kb * *device*) [private],[slot]

Definition at line 121 of file mainwindow.cpp.

References KbWidget::device, kbWidgets, KbWidget::name(), Ui_MainWindow::tabWidget, ui, and updateVersion().

Referenced by MainWindow().

```
121                                     {
122     // Connected already?
123     foreach(KbWidget* w, kbWidgets){
124         if(w->device == device)
125             return;
126     }
127     // Add the keyboard
128     KbWidget* widget = new KbWidget(this, device);
129     kbWidgets.append(widget);
130     // Add to tabber; switch to this device if on the settings screen
131     int count = ui->tabWidget->count();
132     ui->tabWidget->insertTab(count - 1, widget, widget->name());
133     if(ui->tabWidget->currentIndex() == count)
134         ui->tabWidget->setCurrentIndex(count - 1);
135     // Update connected device count
136     updateVersion();
137 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.2 void MainWindow::checkFwUpdates ( ) [private],[slot]

Definition at line 172 of file mainwindow.cpp.

References KbWidget::device, Kb::features, Kb::firmware, KbWidget::hasShownNewFW, kbWidgets, mainWindow, KbWidget::updateFwButton(), and KbFirmware::versionForBoard().

Referenced by timerTick().

```
172                                 {
173     if(!mainWindow->isVisible())
174         return;
175     foreach(KbWidget* w, kbWidgets){
176         // Display firmware upgrade notification if a new version is available
177         float version = KbFirmware::versionForBoard(w->
      device->features);
178         if(version > w->device->firmware.toFloat()){
179             if(w->hasShownNewFW)
180                 continue;
181             w->hasShownNewFW = true;
182             w->updateFwButton();
183             // Don't run this method here because it will lock up the timer and prevent devices from
       working properly
184             // Use a queued invocation instead
185             metaObject()->invokeMethod(this, "showFwUpdateNotification", Qt::QueuedConnection, Q_ARG(
      QWidget*, w), Q_ARG(float, version));
186             // Don't display more than one of these at once
187             return;
188         }
189     }
190 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.3 void MainWindow::cleanup ( ) [private],[slot]

Definition at line 295 of file mainwindow.cpp.

References CkbSettings::cleanUp(), kbWidgets, and KbManager::stop().

Referenced by MainWindow(), and ~MainWindow().

```
295                         {
296     foreach(KbWidget* w, kbWidgets)
297         delete w;
298     kbWidgets.clear();
299     KbManager::stop();
300     CkbSettings::cleanUp();
301 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.4 void MainWindow::closeEvent (QCloseEvent * *event*) [private]

Definition at line 209 of file mainwindow.cpp.

References CkbSettings::get(), and CkbSettings::set().

```
209                                                 {
210     // If the window is hidden already or the event is non-spontaneous (can happen on OSX when using the
        Quit menu), accept it and close
211     if(!event->spontaneous() || isHidden()){
212         event->accept();
213         return;
214     }
215     if(!CkbSettings::get("Popups/BGWarning").toBool()){
216         QMessageBox::information(this, "ckb", "ckb will still run in the background.\nTo close it, choose
        Exit from the tray menu\nor click \"Quit ckb\" on the Settings screen.");
217         CkbSettings::set("Popups/BGWarning", true);
218     }
219     hide();
220     event->ignore();
221 }
```

Here is the call graph for this function:

12.51.3.5 void MainWindow::iconClicked (QSystemTrayIcon::ActivationReason *reason*) [private],[slot]

Definition at line 257 of file mainwindow.cpp.

References showWindow().

Referenced by MainWindow().

```
257                                                                 {
258     // On Linux, hide/show the app when the tray icon is clicked
259     // On OSX this just shows the menu
260 #ifndef Q_OS_MACX
261     if(reason == QSystemTrayIcon::DoubleClick || reason == QSystemTrayIcon::Trigger){
262         if(isVisible())
263             hide();
264         else
265             showWindow();
266     }
267 #endif
268 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.6 void MainWindow::quitApp ( ) [slot]

Definition at line 291 of file mainwindow.cpp.

Referenced by MainWindow().

```
291                         {
292     qApp->quit();
293 }
```

Here is the caller graph for this function:

12.51.3.7 void MainWindow::removeDevice (Kb * *device*) [private],[slot]

Definition at line 139 of file mainwindow.cpp.

References KbWidget::device, kbWidgets, Ui_MainWindow::tabWidget, ui, and updateVersion().

Referenced by MainWindow().

```
139                                     {
140     foreach(KbWidget* w, kbWidgets){
141         // Remove this device from the UI
142         if(w->device == device){
143             int i = kbWidgets.indexOf(w);
144             ui->tabWidget->removeTab(i);
145             kbWidgets.removeAt(i);
146             w->deleteLater();
147         }
148     }
149     // Update connected device count
150     updateVersion();
151 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.8 void MainWindow::showFwUpdateNotification (QWidget * *widget*, float *version*) [private],[slot]

Definition at line 192 of file mainwindow.cpp.

References KbWidget::device, kbWidgets, KbWidget::showFwUpdate(), KbWidget::showLastTab(), showWindow(), Ui_MainWindow::tabWidget, ui, and Kb::usbModel.

```
                                                                    {
    static bool isShowing = false;
    if(isShowing)
        return;
    isShowing = true;
    showWindow();
    KbWidget* w = (KbWidget*)widget;
    // Ask for update
    if(QMessageBox::information(this, "Firmware update", tr("A new firmware is available for your %1 (v%2)
\nWould you like to install it now?").arg(w->device->usbModel, QString::number(version, 'f', 2)
), QMessageBox::StandardButtons(QMessageBox::Yes | QMessageBox::No), QMessageBox::Yes) == QMessageBox::Yes){
        // If accepted, switch to firmware tab and bring up update window
        w->showLastTab();
        ui->tabWidget->setCurrentIndex(kbWidgets.indexOf(w));
        w->showFwUpdate();
    }
    isShowing = false;
}
```

Here is the call graph for this function:

12.51.3.9 void MainWindow::showWindow ( ) [slot]

Definition at line 270 of file mainwindow.cpp.

Referenced by iconClicked(), MainWindow(), showFwUpdateNotification(), stateChange(), and timerTick().

```
                        {
    showNormal();
    raise();
    activateWindow();
}
```

Here is the caller graph for this function:

12.51.3.10 void MainWindow::stateChange (Qt::ApplicationState *state*) [slot]

Definition at line 276 of file mainwindow.cpp.

References showWindow().

Referenced by MainWindow().

```
276                                                 {
277     // On OSX it's possible for the app to be brought to the foreground without the window actually
        reappearing.
278     // We want to make sure it's shown when this happens.
279 #ifdef Q_OS_MAC
280     static quint64 lastStateChange = 0;
281     quint64 now = QDateTime::currentMSecsSinceEpoch();
282     if(state == Qt::ApplicationActive){
283         // This happens once at startup so ignore it. Also don't allow it to be called more than once every
        2s.
284         if(lastStateChange != 0 && now >= lastStateChange + 2 * 1000)
285             showWindow();
286         lastStateChange = now;
287     }
288 #endif
289 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.11 void MainWindow::timerTick ( ) [private], [slot]

Definition at line 223 of file mainwindow.cpp.

References appShare, checkFwUpdates(), KbFirmware::checkUpdates(), CkbSettings::get(), SettingsWidget::pollUpdates(), settingsWidget, and showWindow().

Referenced by MainWindow().

```
223                                 {
224     // Check shared memory for changes
225     if(appShare.lock()){
226         void* data = appShare.data();
227         QStringList commands = QString((const char*)data).split("\n");
228         // Restore PID, remove all other data
229         snprintf((char*)appShare.data(), appShare.size(), "PID %ld", (long)getpid());
230         appShare.unlock();
```

```
        // Parse commands
        foreach(const QString& line, commands){
            // Old ckb option line - bring application to foreground
            if(line == "Open")
                showWindow();
            if(line.startsWith("Option ")){
                // New ckb option line
                QString option = line.split(" ")[1];
                if(option == "Open")
                    // Bring to foreground
                    showWindow();
                else if(option == "Close")
                    // Quit application
                    qApp->quit();
            }
        }
    }
    // Check for firmware updates (when appropriate)
    if(!CkbSettings::get("Program/DisableAutoFWCheck").toBool()){
        KbFirmware::checkUpdates();
        checkFwUpdates();
    }
    // Poll for setting updates
    settingsWidget->pollUpdates();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.3.12 void MainWindow::toggleTrayIcon (bool *visible*)

Definition at line 112 of file mainwindow.cpp.

References trayIcon.

Referenced by MainWindow(), and ExtraSettingsWidget::on_trayBox_clicked().

```
112                                                 {
113 #ifdef USE_LIBAPPINDICATOR
114     if(unityDesktop)
115         app_indicator_set_status(indicator, visible ? APP_INDICATOR_STATUS_ACTIVE :
      APP_INDICATOR_STATUS_PASSIVE);
116     else
117 #endif // USE_LIBAPPINDICATOR
118         trayIcon->setVisible(visible);
119 }
```

Here is the caller graph for this function:

12.51.3.13 void MainWindow::updateVersion ( ) [private],[slot]

Definition at line 153 of file mainwindow.cpp.

References KbManager::ckbDaemonVersion(), KbManager::ckbDaemonVersionF(), KbManager::ckbGuiVersionF(), DAEMON_UNAVAILABLE_STR, kbWidgets, SettingsWidget::setStatus(), and settingsWidget.

Referenced by addDevice(), MainWindow(), and removeDevice().

```
153                                 {
154     QString daemonVersion = KbManager::ckbDaemonVersion();
155     if(daemonVersion == DAEMON_UNAVAILABLE_STR){
156         settingsWidget->setStatus("Driver inactive");
157         return;
158     }
159     int count = kbWidgets.count();
160     // Warn if the daemon version doesn't match the GUI
161     QString daemonWarning;
162     if(daemonVersion != CKB_VERSION_STR)
163         daemonWarning = "<br /><br /><b>Warning:</b> Driver version mismatch (" + daemonVersion + ").
       Please upgrade ckb" + QString(KbManager::ckbDaemonVersionF() >
      KbManager::ckbGuiVersionF() ? "" : "-daemon") + ". If the problem persists, try
       rebooting.";
164     if(count == 0)
165         settingsWidget->setStatus("No devices connected" + daemonWarning);
166     else if(count == 1)
167         settingsWidget->setStatus("1 device connected" + daemonWarning);
168     else
169         settingsWidget->setStatus(QString("%1 devices connected").arg(count) +
      daemonWarning);
170 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.51.4 Field Documentation

12.51.4.1 QAction* MainWindow::closeAction [private]

Definition at line 44 of file mainwindow.h.

Referenced by MainWindow().

12.51.4.2 QList<KbWidget*> MainWindow::kbWidgets [private]

Definition at line 41 of file mainwindow.h.

Referenced by addDevice(), checkFwUpdates(), cleanup(), removeDevice(), showFwUpdateNotification(), and updateVersion().

12.51.4.3 MainWindow * MainWindow::mainWindow = 0 [static]

Definition at line 35 of file mainwindow.h.

Referenced by checkFwUpdates(), MainWindow(), and ExtraSettingsWidget::on_trayBox_clicked().

12.51.4.4 QAction* MainWindow::restoreAction [private]

Definition at line 43 of file mainwindow.h.

Referenced by MainWindow().

12.51.4.5 SettingsWidget* MainWindow::settingsWidget [private]

Definition at line 40 of file mainwindow.h.

Referenced by MainWindow(), timerTick(), and updateVersion().

12.51.4.6 QSystemTrayIcon* MainWindow::trayIcon [private]

Definition at line 54 of file mainwindow.h.

Referenced by MainWindow(), and toggleTrayIcon().

12.51.4.7 QMenu* MainWindow::trayIconMenu [private]

Definition at line 53 of file mainwindow.h.

Referenced by MainWindow().

12.51.4.8 Ui::MainWindow* MainWindow::ui [private]

Definition at line 75 of file mainwindow.h.

Referenced by addDevice(), MainWindow(), removeDevice(), showFwUpdateNotification(), and ~MainWindow().

The documentation for this class was generated from the following files:

- src/ckb/mainwindow.h
- src/ckb/mainwindow.cpp

12.52 Ui::ModeSelectDialog Class Reference

`#include <src/ckb/ui_modeselectdialog.h>`

Inheritance diagram for Ui::ModeSelectDialog:

Collaboration diagram for Ui::ModeSelectDialog:

Public Member Functions

- void setupUi (QDialog *ModeSelectDialog)
- void retranslateUi (QDialog *ModeSelectDialog)

Data Fields

- QGridLayout * gridLayout
- QLabel * label
- QDialogButtonBox * buttonBox
- QListWidget * modeList
- QPushButton * selAllButton
- QPushButton * selNoneButton

12.52.1 Detailed Description

Definition at line 93 of file ui_modeselectdialog.h.

12.52.2 Member Function Documentation

12.52.2.1 void Ui_ModeSelectDialog::retranslateUi (QDialog * *ModeSelectDialog*) [inline],[inherited]

Definition at line 82 of file ui_modeselectdialog.h.

References Ui_ModeSelectDialog::label, Ui_ModeSelectDialog::selAllButton, and Ui_ModeSelectDialog::selNoneButton.

Referenced by Ui_ModeSelectDialog::setupUi().

```
83     {
84         ModeSelectDialog->setWindowTitle(QApplication::translate("ModeSelectDialog", "Select Modes",
    Q_NULLPTR));
85         label->setText(QApplication::translate("ModeSelectDialog", "TextLabel", Q_NULLPTR));
```

```
        selAllButton->setText(QApplication::translate("ModeSelectDialog", "Select All", Q_NULLPTR));
        selNoneButton->setText(QApplication::translate("ModeSelectDialog", "Select None", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.52.2.2 void Ui_ModeSelectDialog::setupUi (QDialog * *ModeSelectDialog*) [inline],[inherited]

Definition at line 36 of file ui_modeselectdialog.h.

References Ui_ModeSelectDialog::buttonBox, Ui_ModeSelectDialog::gridLayout, Ui_ModeSelectDialog::label, Ui_ModeSelectDialog::modeList, Ui_ModeSelectDialog::retranslateUi(), Ui_ModeSelectDialog::selAllButton, and Ui_ModeSelectDialog::selNoneButton.

Referenced by ModeSelectDialog::ModeSelectDialog().

```
    {
        if (ModeSelectDialog->objectName().isEmpty())
            ModeSelectDialog->setObjectName(QStringLiteral("ModeSelectDialog"));
        ModeSelectDialog->resize(320, 320);
        gridLayout = new QGridLayout(ModeSelectDialog);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        label = new QLabel(ModeSelectDialog);
        label->setObjectName(QStringLiteral("label"));
        label->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignTop);

        gridLayout->addWidget(label, 0, 0, 1, 2);

        buttonBox = new QDialogButtonBox(ModeSelectDialog);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Vertical);
        buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
        buttonBox->setCenterButtons(false);

        gridLayout->addWidget(buttonBox, 0, 2, 3, 1);

        modeList = new QListWidget(ModeSelectDialog);
        modeList->setObjectName(QStringLiteral("modeList"));
        modeList->setFrameShadow(QFrame::Plain);
        modeList->setSelectionMode(QAbstractItemView::ExtendedSelection);

        gridLayout->addWidget(modeList, 1, 0, 1, 2);

        selAllButton = new QPushButton(ModeSelectDialog);
        selAllButton->setObjectName(QStringLiteral("selAllButton"));

        gridLayout->addWidget(selAllButton, 2, 0, 1, 1);

        selNoneButton = new QPushButton(ModeSelectDialog);
        selNoneButton->setObjectName(QStringLiteral("selNoneButton"));

        gridLayout->addWidget(selNoneButton, 2, 1, 1, 1);


        retranslateUi(ModeSelectDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), ModeSelectDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), ModeSelectDialog, SLOT(reject()));

        QMetaObject::connectSlotsByName(ModeSelectDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.52.3 Field Documentation

12.52.3.1 QDialogButtonBox* Ui_ModeSelectDialog::buttonBox [inherited]

Definition at line 31 of file ui_modeselectdialog.h.

Referenced by Ui_ModeSelectDialog::setupUi().

12.52.3.2 QGridLayout* Ui_ModeSelectDialog::gridLayout [inherited]

Definition at line 29 of file ui_modeselectdialog.h.

Referenced by Ui_ModeSelectDialog::setupUi().

12.52.3.3 QLabel* Ui_ModeSelectDialog::label [inherited]

Definition at line 30 of file ui_modeselectdialog.h.

Referenced by ModeSelectDialog::ModeSelectDialog(), Ui_ModeSelectDialog::retranslateUi(), and Ui_ModeSelectDialog::setupUi().

12.52.3.4 QListWidget* Ui_ModeSelectDialog::modeList [inherited]

Definition at line 32 of file ui_modeselectdialog.h.

Referenced by ModeSelectDialog::ModeSelectDialog(), ModeSelectDialog::on_selAllButton_clicked(), ModeSelectDialog::on_selNoneButton_clicked(), ModeSelectDialog::selection(), and Ui_ModeSelectDialog::setupUi().

12.52.3.5 QPushButton* Ui_ModeSelectDialog::selAllButton [inherited]

Definition at line 33 of file ui_modeselectdialog.h.

Referenced by Ui_ModeSelectDialog::retranslateUi(), and Ui_ModeSelectDialog::setupUi().

12.52.3.6 QPushButton* Ui_ModeSelectDialog::selNoneButton [inherited]

Definition at line 34 of file ui_modeselectdialog.h.

Referenced by Ui_ModeSelectDialog::retranslateUi(), and Ui_ModeSelectDialog::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_modeselectdialog.h

12.53 ModeSelectDialog Class Reference

```
#include <src/ckb/modeselectdialog.h>
```

Inheritance diagram for ModeSelectDialog:

Collaboration diagram for ModeSelectDialog:

Public Member Functions

- ModeSelectDialog (QWidget *parent, KbMode *currentMode, QList< KbMode * > modeList, const QString &textLabel)
- ~ModeSelectDialog ()
- QList< KbMode * > selection ()

Private Slots

- void on_selAllButton_clicked ()
- void on_selNoneButton_clicked ()

Private Attributes

- Ui::ModeSelectDialog * ui
- QList< KbMode * > _modeList

12.53.1 Detailed Description

Definition at line 13 of file modeselectdialog.h.

12.53.2 Constructor & Destructor Documentation

12.53.2.1 ModeSelectDialog::ModeSelectDialog (QWidget * *parent*, KbMode * *currentMode*, QList< KbMode * > *modeList*, const QString & *textLabel*)

Definition at line 4 of file modeselectdialog.cpp.

References _modeList, Ui_ModeSelectDialog::label, Ui_ModeSelectDialog::modeList, KbMode::name(), Ui_ModeSelectDialog::setupUi(), and ui.

```
4                                                   :
5       QDialog(parent), ui(new Ui::ModeSelectDialog),
6       _modeList(modeList)
7   {
8       ui->setupUi(this);
9       _modeList.removeAll(currentMode);
10       ui->label->setText(textLabel);
11       // Populate list
12       foreach(KbMode* mode, _modeList)
13           ui->modeList->addItem(mode->name());
14  }
```

Here is the call graph for this function:

12.53.2.2 ModeSelectDialog::~ModeSelectDialog ( )

Definition at line 16 of file modeselectdialog.cpp.

References ui.

```
16                                                  {
17      delete ui;
18  }
```

12.53.3 Member Function Documentation

12.53.3.1 void ModeSelectDialog::on_selAllButton_clicked ( ) [private],[slot]

Definition at line 30 of file modeselectdialog.cpp.

References Ui_ModeSelectDialog::modeList, and ui.

```
30                                                  {
31      int count = ui->modeList->count();
32      for(int i = 0; i < count; i++)
33          ui->modeList->item(i)->setSelected(true);
34  }
```

12.53.3.2 void ModeSelectDialog::on_selNoneButton_clicked ( ) [private],[slot]

Definition at line 36 of file modeselectdialog.cpp.

References Ui_ModeSelectDialog::modeList, and ui.

```
36                                                  {
37     int count = ui->modeList->count();
38     for(int i = 0; i < count; i++)
39         ui->modeList->item(i)->setSelected(false);
40 }
```

12.53.3.3 QList< KbMode * > ModeSelectDialog::selection ( )

Definition at line 20 of file modeselectdialog.cpp.

References _modeList, Ui_ModeSelectDialog::modeList, and ui.

Referenced by KbBindWidget::on_copyButton_clicked(), KPerfWidget::on_copyButton_clicked(), and MPerfWidget::on_copyButton_clicked().

```
20                                                  {
21     QList<KbMode*> res;
22     int count = ui->modeList->count();
23     for(int i = 0; i < count; i++){
24         if(ui->modeList->item(i)->isSelected())
25             res.append(_modeList[i]);
26     }
27     return res;
28 }
```

Here is the caller graph for this function:

12.53.4 Field Documentation

12.53.4.1 QList<KbMode*> ModeSelectDialog::_modeList [private]

Definition at line 31 of file modeselectdialog.h.

Referenced by ModeSelectDialog(), and selection().

12.53.4.2 Ui::ModeSelectDialog* ModeSelectDialog::ui [private]

Definition at line 30 of file modeselectdialog.h.

Referenced by ModeSelectDialog(), on_selAllButton_clicked(), on_selNoneButton_clicked(), selection(), and ~-ModeSelectDialog().

The documentation for this class was generated from the following files:

- src/ckb/modeselectdialog.h
- src/ckb/modeselectdialog.cpp

12.54 Ui::MPerfWidget Class Reference

```
#include <src/ckb/ui_mperfwidget.h>
```

Inheritance diagram for Ui::MPerfWidget:

Collaboration diagram for Ui::MPerfWidget:

Public Member Functions

- void setupUi (QWidget ∗MPerfWidget)
- void retranslateUi (QWidget ∗MPerfWidget)

Data Fields

- QVBoxLayout ∗ verticalLayout
- QLabel ∗ label
- QFrame ∗ line
- QGridLayout ∗ gridLayout
- QLabel ∗ label_25
- QHBoxLayout ∗ horizontalLayout_2
- QComboBox ∗ lHeightBox
- QSpacerItem ∗ horizontalSpacer_2
- QCheckBox ∗ eBox2
- QSlider ∗ ySlider3
- QSlider ∗ xSlider2
- QSpinBox ∗ xBox3
- QSpinBox ∗ yBox0
- QSlider ∗ ySlider0
- ColorButton ∗ iButton4
- ColorButton ∗ iButton5
- QSpacerItem ∗ horizontalSpacer_4
- QSpacerItem ∗ verticalSpacer_3
- QSpacerItem ∗ horizontalSpacer_5
- ColorButton ∗ iButton3
- QLabel ∗ label_12
- QSpinBox ∗ xBox4
- QSpinBox ∗ xBox0
- QSpinBox ∗ yBox5
- QCheckBox ∗ eBox5

- QSlider * xSlider5
- QSpinBox * xBox1
- QSpinBox * yBox2
- QSpinBox * yBox3
- QSlider * xSlider4
- QLabel * label_4
- QSlider * xSlider0
- ColorButton * iButton2
- QFrame * line_3
- ColorButton * iButtonO
- QSpinBox * yBox1
- QSlider * ySlider2
- QSpinBox * xBox2
- QSlider * xSlider1
- QSpacerItem * horizontalSpacer
- QSpinBox * yBox4
- ColorButton * iButton1
- QSlider * ySlider4
- QSlider * ySlider1
- ColorButton * iButton0
- QSlider * xSlider3
- QSpinBox * xBox5
- QLabel * label_3
- QLabel * label_6
- QSlider * ySlider5
- QLabel * label_7
- QLabel * label_8
- QLabel * label_5
- QLabel * label_15
- QLabel * label_13
- QLabel * label_14
- QCheckBox * eBox4
- QLabel * label_11
- QCheckBox * eBox3
- QCheckBox * eBox1
- QLabel * label_2
- QSpacerItem * verticalSpacer
- QCheckBox * aSnapBox
- QFrame * line_2
- QHBoxLayout * horizontalLayout_4
- QCheckBox * indicBox
- QSpacerItem * horizontalSpacer_3
- QSpinBox * spinBox
- QSpacerItem * horizontalSpacer_7
- QCheckBox * xyBox
- QSpacerItem * verticalSpacer_2
- QHBoxLayout * horizontalLayout
- QPushButton * copyButton
- QSpacerItem * horizontalSpacer_6

12.54.1 Detailed Description

Definition at line 727 of file ui_mperfwidget.h.

12.54.2 Member Function Documentation

12.54.2.1 void Ui_MPerfWidget::retranslateUi (QWidget * *MPerfWidget*) [inline],[inherited]

Definition at line 641 of file ui_mperfwidget.h.

References Ui_MPerfWidget::aSnapBox, Ui_MPerfWidget::copyButton, Ui_MPerfWidget::eBox1, Ui_MPerfWidget::eBox2, Ui_MPerfWidget::eBox3, Ui_MPerfWidget::eBox4, Ui_MPerfWidget::eBox5, Ui_MPerfWidget::iButton0, Ui_MPerfWidget::iButton1, Ui_MPerfWidget::iButton2, Ui_MPerfWidget::iButton3, Ui_MPerfWidget::iButton4, Ui_MPerfWidget::iButton5, Ui_MPerfWidget::iButtonO, Ui_MPerfWidget::indicBox, Ui_MPerfWidget::label, Ui_MPerfWidget::label_11, Ui_MPerfWidget::label_12, Ui_MPerfWidget::label_13, Ui_MPerfWidget::label_14, Ui_MPerfWidget::label_15, Ui_MPerfWidget::label_2, Ui_MPerfWidget::label_25, Ui_MPerfWidget::label_3, Ui_MPerfWidget::label_4, Ui_MPerfWidget::label_5, Ui_MPerfWidget::label_6, Ui_MPerfWidget::label_7, Ui_MPerfWidget::label_8, Ui_MPerfWidget::lHeightBox, Ui_MPerfWidget::spinBox, and Ui_MPerfWidget::xyBox.

Referenced by Ui_MPerfWidget::setupUi().

```
    {
        MPerfWidget->setWindowTitle(QApplication::translate("MPerfWidget", "Form", Q_NULLPTR));
        label->setText(QApplication::translate("MPerfWidget", "DPI", Q_NULLPTR));
        label_25->setText(QApplication::translate("MPerfWidget", "Lift height:", Q_NULLPTR));
        lHeightBox->clear();
        lHeightBox->insertItems(0, QStringList()
         << QApplication::translate("MPerfWidget", "Low", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium-low", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium-high", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "High", Q_NULLPTR)
        );
#ifndef QT_NO_TOOLTIP
        eBox2->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox2->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton4->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton4->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton5->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton5->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton3->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton3->setText(QString());
        label_12->setText(QApplication::translate("MPerfWidget", "X Value:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox5->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox5->setText(QString());
        label_4->setText(QApplication::translate("MPerfWidget", "Y Value:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        iButton2->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton2->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButtonO->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButtonO->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton1->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton1->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton0->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton0->setText(QString());
        label_3->setText(QApplication::translate("MPerfWidget", "You can assign other DPIs in the Binding tab.", Q_NULLPTR));
        label_6->setText(QApplication::translate("MPerfWidget", "2:", Q_NULLPTR));
        label_7->setText(QApplication::translate("MPerfWidget", "3:", Q_NULLPTR));
        label_8->setText(QApplication::translate("MPerfWidget", "4:", Q_NULLPTR));
```

```
        label_5->setText(QApplication::translate("MPerfWidget", "1:", Q_NULLPTR));
        label_15->setText(QApplication::translate("MPerfWidget", "Other:", Q_NULLPTR));
        label_13->setText(QApplication::translate("MPerfWidget", "5:", Q_NULLPTR));
        label_14->setText(QApplication::translate("MPerfWidget", "Sniper:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox4->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox4->setText(QString());
        label_11->setText(QApplication::translate("MPerfWidget", "DPI Stage:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox3->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox3->setText(QString());
#ifndef QT_NO_TOOLTIP
        eBox1->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox1->setText(QString());
        label_2->setText(QApplication::translate("MPerfWidget", "Movement", Q_NULLPTR));
        aSnapBox->setText(QApplication::translate("MPerfWidget", "Angle snap", Q_NULLPTR));
        indicBox->setText(QApplication::translate("MPerfWidget", "Use DPI indicator:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        spinBox->setToolTip(QApplication::translate("MPerfWidget", "Indicator intensity", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        spinBox->setSuffix(QApplication::translate("MPerfWidget", "%", Q_NULLPTR));
        xyBox->setText(QApplication::translate("MPerfWidget", "Independent X/Y states", Q_NULLPTR));
        copyButton->setText(QApplication::translate("MPerfWidget", "Copy to mode...", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.54.2.2 void Ui_MPerfWidget::setupUi (QWidget * *MPerfWidget*) [inline],[inherited]

Definition at line 111 of file ui_mperfwidget.h.

References Ui_MPerfWidget::aSnapBox, Ui_MPerfWidget::copyButton, Ui_MPerfWidget::eBox1, Ui_MPerfWidget::eBox2, Ui_MPerfWidget::eBox3, Ui_MPerfWidget::eBox4, Ui_MPerfWidget::eBox5, Ui_MPerfWidget::gridLayout, Ui_MPerfWidget::horizontalLayout, Ui_MPerfWidget::horizontalLayout_2, Ui_MPerfWidget::horizontalLayout_4, Ui_MPerfWidget::horizontalSpacer, Ui_MPerfWidget::horizontalSpacer_2, Ui_MPerfWidget::horizontalSpacer_3, Ui_MPerfWidget::horizontalSpacer_4, Ui_MPerfWidget::horizontalSpacer_5, Ui_MPerfWidget::horizontalSpacer_6, Ui_MPerfWidget::horizontalSpacer_7, Ui_MPerfWidget::iButton0, Ui_MPerfWidget::iButton1, Ui_MPerfWidget::iButton2, Ui_MPerfWidget::iButton3, Ui_MPerfWidget::iButton4, Ui_MPerfWidget::iButton5, Ui_MPerfWidget::iButtonO, Ui_MPerfWidget::indicBox, Ui_MPerfWidget::label, Ui_MPerfWidget::label_11, Ui_MPerfWidget::label_12, Ui_MPerfWidget::label_13, Ui_MPerfWidget::label_14, Ui_MPerfWidget::label_15, Ui_MPerfWidget::label_2, Ui_MPerfWidget::label_25, Ui_MPerfWidget::label_3, Ui_MPerfWidget::label_4, Ui_MPerfWidget::label_5, Ui_MPerfWidget::label_6, Ui_MPerfWidget::label_7, Ui_MPerfWidget::label_8, Ui_MPerfWidget::lHeightBox, Ui_MPerfWidget::line, Ui_MPerfWidget::line_2, Ui_MPerfWidget::line_3, Ui_MPerfWidget::retranslateUi(), Ui_MPerfWidget::spinBox, Ui_MPerfWidget::verticalLayout, Ui_MPerfWidget::verticalSpacer, Ui_MPerfWidget::verticalSpacer_2, Ui_MPerfWidget::verticalSpacer_3, Ui_MPerfWidget::xBox0, Ui_MPerfWidget::xBox1, Ui_MPerfWidget::xBox2, Ui_MPerfWidget::xBox3, Ui_MPerfWidget::xBox4, Ui_MPerfWidget::xBox5, Ui_MPerfWidget::xSlider0, Ui_MPerfWidget::xSlider1, Ui_MPerfWidget::xSlider2, Ui_MPerfWidget::xSlider3, Ui_MPerfWidget::xSlider4, Ui_MPerfWidget::xSlider5, Ui_MPerfWidget::xyBox, Ui_MPerfWidget::yBox0, Ui_MPerfWidget::yBox1, Ui_MPerfWidget::yBox2, Ui_MPerfWidget::yBox3, Ui_MPerfWidget::yBox4, Ui_MPerfWidget::yBox5, Ui_MPerfWidget::ySlider0, Ui_MPerfWidget::ySlider1, Ui_MPerfWidget::ySlider2, Ui_MPerfWidget::ySlider3, Ui_MPerfWidget::ySlider4, and Ui_MPerfWidget::ySlider5.

Referenced by MPerfWidget::MPerfWidget().

```
    {
        if (MPerfWidget->objectName().isEmpty())
            MPerfWidget->setObjectName(QStringLiteral("MPerfWidget"));
        MPerfWidget->resize(932, 637);
        verticalLayout = new QVBoxLayout(MPerfWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        label = new QLabel(MPerfWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        verticalLayout->addWidget(label);

        line = new QFrame(MPerfWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line);

        gridLayout = new QGridLayout();
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        label_25 = new QLabel(MPerfWidget);
        label_25->setObjectName(QStringLiteral("label_25"));
        label_25->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout->addWidget(label_25, 16, 5, 1, 2);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        lHeightBox = new QComboBox(MPerfWidget);
        lHeightBox->setObjectName(QStringLiteral("lHeightBox"));

        horizontalLayout_2->addWidget(lHeightBox);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_2);


        gridLayout->addLayout(horizontalLayout_2, 16, 8, 1, 3);

        eBox2 = new QCheckBox(MPerfWidget);
        eBox2->setObjectName(QStringLiteral("eBox2"));

        gridLayout->addWidget(eBox2, 7, 1, 1, 1);

        ySlider3 = new QSlider(MPerfWidget);
        ySlider3->setObjectName(QStringLiteral("ySlider3"));
        ySlider3->setMinimum(0);
        ySlider3->setMaximum(1000);
        ySlider3->setSingleStep(10);
        ySlider3->setPageStep(50);
        ySlider3->setValue(0);
        ySlider3->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider3, 8, 8, 1, 1);

        xSlider2 = new QSlider(MPerfWidget);
        xSlider2->setObjectName(QStringLiteral("xSlider2"));
        xSlider2->setMinimum(0);
        xSlider2->setMaximum(1000);
        xSlider2->setSingleStep(10);
        xSlider2->setPageStep(50);
        xSlider2->setValue(0);
        xSlider2->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider2, 7, 5, 1, 1);

        xBox3 = new QSpinBox(MPerfWidget);
        xBox3->setObjectName(QStringLiteral("xBox3"));
        xBox3->setMinimum(100);
        xBox3->setMaximum(12000);
        xBox3->setSingleStep(50);

        gridLayout->addWidget(xBox3, 8, 6, 1, 1);

        yBox0 = new QSpinBox(MPerfWidget);
        yBox0->setObjectName(QStringLiteral("yBox0"));
        yBox0->setMinimum(100);
        yBox0->setMaximum(12000);
        yBox0->setSingleStep(50);

        gridLayout->addWidget(yBox0, 11, 9, 1, 1);
```

```

        ySlider0 = new QSlider(MPerfWidget);
        ySlider0->setObjectName(QStringLiteral("ySlider0"));
        ySlider0->setMinimum(0);
        ySlider0->setMaximum(1000);
        ySlider0->setSingleStep(10);
        ySlider0->setPageStep(50);
        ySlider0->setValue(0);
        ySlider0->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider0, 11, 8, 1, 1);

        iButton4 = new ColorButton(MPerfWidget);
        iButton4->setObjectName(QStringLiteral("iButton4"));
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(iButton4->sizePolicy().hasHeightForWidth());
        iButton4->setSizePolicy(sizePolicy);
        iButton4->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton4, 9, 2, 1, 1);

        iButton5 = new ColorButton(MPerfWidget);
        iButton5->setObjectName(QStringLiteral("iButton5"));
        sizePolicy.setHeightForWidth(iButton5->sizePolicy().hasHeightForWidth());
        iButton5->setSizePolicy(sizePolicy);
        iButton5->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton5, 10, 2, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_4, 4, 4, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 15, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_3, 3, 2, 1, 1);

        horizontalSpacer_5 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_5, 4, 7, 1, 1);

        iButton3 = new ColorButton(MPerfWidget);
        iButton3->setObjectName(QStringLiteral("iButton3"));
        sizePolicy.setHeightForWidth(iButton3->sizePolicy().hasHeightForWidth());
        iButton3->setSizePolicy(sizePolicy);
        iButton3->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton3, 8, 2, 1, 1);

        label_12 = new QLabel(MPerfWidget);
        label_12->setObjectName(QStringLiteral("label_12"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(label_12->sizePolicy().hasHeightForWidth());
        label_12->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(label_12, 4, 5, 1, 1);

        xBox4 = new QSpinBox(MPerfWidget);
        xBox4->setObjectName(QStringLiteral("xBox4"));
        xBox4->setMinimum(100);
        xBox4->setMaximum(12000);
        xBox4->setSingleStep(50);

        gridLayout->addWidget(xBox4, 9, 6, 1, 1);

        xBox0 = new QSpinBox(MPerfWidget);
        xBox0->setObjectName(QStringLiteral("xBox0"));
        xBox0->setMinimum(100);
        xBox0->setMaximum(12000);
        xBox0->setSingleStep(50);

        gridLayout->addWidget(xBox0, 11, 6, 1, 1);

        yBox5 = new QSpinBox(MPerfWidget);
        yBox5->setObjectName(QStringLiteral("yBox5"));
        yBox5->setMinimum(100);
        yBox5->setMaximum(12000);
        yBox5->setSingleStep(50);

        gridLayout->addWidget(yBox5, 10, 9, 1, 1);
```

```

        eBox5 = new QCheckBox(MPerfWidget);
        eBox5->setObjectName(QStringLiteral("eBox5"));

        gridLayout->addWidget(eBox5, 10, 1, 1, 1);

        xSlider5 = new QSlider(MPerfWidget);
        xSlider5->setObjectName(QStringLiteral("xSlider5"));
        xSlider5->setMinimum(0);
        xSlider5->setMaximum(1000);
        xSlider5->setSingleStep(10);
        xSlider5->setPageStep(50);
        xSlider5->setValue(0);
        xSlider5->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider5, 10, 5, 1, 1);

        xBox1 = new QSpinBox(MPerfWidget);
        xBox1->setObjectName(QStringLiteral("xBox1"));
        sizePolicy.setHeightForWidth(xBox1->sizePolicy().hasHeightForWidth());
        xBox1->setSizePolicy(sizePolicy);
        xBox1->setMinimum(100);
        xBox1->setMaximum(12000);
        xBox1->setSingleStep(50);

        gridLayout->addWidget(xBox1, 6, 6, 1, 1);

        yBox2 = new QSpinBox(MPerfWidget);
        yBox2->setObjectName(QStringLiteral("yBox2"));
        yBox2->setMinimum(100);
        yBox2->setMaximum(12000);
        yBox2->setSingleStep(50);

        gridLayout->addWidget(yBox2, 7, 9, 1, 1);

        yBox3 = new QSpinBox(MPerfWidget);
        yBox3->setObjectName(QStringLiteral("yBox3"));
        yBox3->setMinimum(100);
        yBox3->setMaximum(12000);
        yBox3->setSingleStep(50);

        gridLayout->addWidget(yBox3, 8, 9, 1, 1);

        xSlider4 = new QSlider(MPerfWidget);
        xSlider4->setObjectName(QStringLiteral("xSlider4"));
        xSlider4->setMinimum(0);
        xSlider4->setMaximum(1000);
        xSlider4->setSingleStep(10);
        xSlider4->setPageStep(50);
        xSlider4->setValue(0);
        xSlider4->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider4, 9, 5, 1, 1);

        label_4 = new QLabel(MPerfWidget);
        label_4->setObjectName(QStringLiteral("label_4"));
        sizePolicy1.setHeightForWidth(label_4->sizePolicy().hasHeightForWidth());
        label_4->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(label_4, 4, 8, 1, 1);

        xSlider0 = new QSlider(MPerfWidget);
        xSlider0->setObjectName(QStringLiteral("xSlider0"));
        xSlider0->setMinimum(0);
        xSlider0->setMaximum(1000);
        xSlider0->setSingleStep(10);
        xSlider0->setPageStep(50);
        xSlider0->setValue(0);
        xSlider0->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider0, 11, 5, 1, 1);

        iButton2 = new ColorButton(MPerfWidget);
        iButton2->setObjectName(QStringLiteral("iButton2"));
        sizePolicy.setHeightForWidth(iButton2->sizePolicy().hasHeightForWidth());
        iButton2->setSizePolicy(sizePolicy);
        iButton2->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton2, 7, 2, 1, 1);

        line_3 = new QFrame(MPerfWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 5, 0, 1, 11);

```

```
        iButton0 = new ColorButton(MPerfWidget);
        iButton0->setObjectName(QStringLiteral("iButton0"));
        sizePolicy.setHeightForWidth(iButton0->sizePolicy().hasHeightForWidth());
        iButton0->setSizePolicy(sizePolicy);
        iButton0->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton0, 12, 2, 1, 1);

        yBox1 = new QSpinBox(MPerfWidget);
        yBox1->setObjectName(QStringLiteral("yBox1"));
        sizePolicy.setHeightForWidth(yBox1->sizePolicy().hasHeightForWidth());
        yBox1->setSizePolicy(sizePolicy);
        yBox1->setMinimum(100);
        yBox1->setMaximum(12000);
        yBox1->setSingleStep(50);

        gridLayout->addWidget(yBox1, 6, 9, 1, 1);

        ySlider2 = new QSlider(MPerfWidget);
        ySlider2->setObjectName(QStringLiteral("ySlider2"));
        ySlider2->setMinimum(0);
        ySlider2->setMaximum(1000);
        ySlider2->setSingleStep(10);
        ySlider2->setPageStep(50);
        ySlider2->setValue(0);
        ySlider2->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider2, 7, 8, 1, 1);

        xBox2 = new QSpinBox(MPerfWidget);
        xBox2->setObjectName(QStringLiteral("xBox2"));
        xBox2->setMinimum(100);
        xBox2->setMaximum(12000);
        xBox2->setSingleStep(50);

        gridLayout->addWidget(xBox2, 7, 6, 1, 1);

        xSlider1 = new QSlider(MPerfWidget);
        xSlider1->setObjectName(QStringLiteral("xSlider1"));
        QSizePolicy sizePolicy2(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(xSlider1->sizePolicy().hasHeightForWidth());
        xSlider1->setSizePolicy(sizePolicy2);
        xSlider1->setMinimum(0);
        xSlider1->setMaximum(1000);
        xSlider1->setSingleStep(10);
        xSlider1->setPageStep(50);
        xSlider1->setValue(0);
        xSlider1->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider1, 6, 5, 1, 1);

        horizontalSpacer = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);

        yBox4 = new QSpinBox(MPerfWidget);
        yBox4->setObjectName(QStringLiteral("yBox4"));
        yBox4->setMinimum(100);
        yBox4->setMaximum(12000);
        yBox4->setSingleStep(50);

        gridLayout->addWidget(yBox4, 9, 9, 1, 1);

        iButton1 = new ColorButton(MPerfWidget);
        iButton1->setObjectName(QStringLiteral("iButton1"));
        sizePolicy.setHeightForWidth(iButton1->sizePolicy().hasHeightForWidth());
        iButton1->setSizePolicy(sizePolicy);
        iButton1->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton1, 6, 2, 1, 1);

        ySlider4 = new QSlider(MPerfWidget);
        ySlider4->setObjectName(QStringLiteral("ySlider4"));
        ySlider4->setMinimum(0);
        ySlider4->setMaximum(1000);
        ySlider4->setSingleStep(10);
        ySlider4->setPageStep(50);
        ySlider4->setValue(0);
        ySlider4->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider4, 9, 8, 1, 1);

        ySlider1 = new QSlider(MPerfWidget);
        ySlider1->setObjectName(QStringLiteral("ySlider1"));
```

```
        ySlider1->setMinimum(0);
        ySlider1->setMaximum(1000);
        ySlider1->setSingleStep(10);
        ySlider1->setPageStep(50);
        ySlider1->setValue(0);
        ySlider1->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider1, 6, 8, 1, 1);

        iButton0 = new ColorButton(MPerfWidget);
        iButton0->setObjectName(QStringLiteral("iButton0"));
        sizePolicy.setHeightForWidth(iButton0->sizePolicy().hasHeightForWidth());
        iButton0->setSizePolicy(sizePolicy);
        iButton0->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton0, 11, 2, 1, 1);

        xSlider3 = new QSlider(MPerfWidget);
        xSlider3->setObjectName(QStringLiteral("xSlider3"));
        xSlider3->setMinimum(0);
        xSlider3->setMaximum(1000);
        xSlider3->setSingleStep(10);
        xSlider3->setPageStep(50);
        xSlider3->setValue(0);
        xSlider3->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider3, 8, 5, 1, 1);

        xBox5 = new QSpinBox(MPerfWidget);
        xBox5->setObjectName(QStringLiteral("xBox5"));
        xBox5->setMinimum(100);
        xBox5->setMaximum(12000);
        xBox5->setSingleStep(50);

        gridLayout->addWidget(xBox5, 10, 6, 1, 1);

        label_3 = new QLabel(MPerfWidget);
        label_3->setObjectName(QStringLiteral("label_3"));

        gridLayout->addWidget(label_3, 12, 5, 1, 5);

        label_6 = new QLabel(MPerfWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 7, 3, 1, 1);

        ySlider5 = new QSlider(MPerfWidget);
        ySlider5->setObjectName(QStringLiteral("ySlider5"));
        ySlider5->setMinimum(0);
        ySlider5->setMaximum(1000);
        ySlider5->setSingleStep(10);
        ySlider5->setPageStep(50);
        ySlider5->setValue(0);
        ySlider5->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider5, 10, 8, 1, 1);

        label_7 = new QLabel(MPerfWidget);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout->addWidget(label_7, 8, 3, 1, 1);

        label_8 = new QLabel(MPerfWidget);
        label_8->setObjectName(QStringLiteral("label_8"));

        gridLayout->addWidget(label_8, 9, 3, 1, 1);

        label_5 = new QLabel(MPerfWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout->addWidget(label_5, 6, 3, 1, 1);

        label_15 = new QLabel(MPerfWidget);
        label_15->setObjectName(QStringLiteral("label_15"));

        gridLayout->addWidget(label_15, 12, 3, 1, 1);

        label_13 = new QLabel(MPerfWidget);
        label_13->setObjectName(QStringLiteral("label_13"));

        gridLayout->addWidget(label_13, 10, 3, 1, 1);

        label_14 = new QLabel(MPerfWidget);
        label_14->setObjectName(QStringLiteral("label_14"));

        gridLayout->addWidget(label_14, 11, 3, 1, 1);

```

```
        eBox4 = new QCheckBox(MPerfWidget);
        eBox4->setObjectName(QStringLiteral("eBox4"));

        gridLayout->addWidget(eBox4, 9, 1, 1, 1);

        label_11 = new QLabel(MPerfWidget);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout->addWidget(label_11, 4, 2, 1, 2);

        eBox3 = new QCheckBox(MPerfWidget);
        eBox3->setObjectName(QStringLiteral("eBox3"));

        gridLayout->addWidget(eBox3, 8, 1, 1, 1);

        eBox1 = new QCheckBox(MPerfWidget);
        eBox1->setObjectName(QStringLiteral("eBox1"));

        gridLayout->addWidget(eBox1, 6, 1, 1, 1);

        label_2 = new QLabel(MPerfWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        gridLayout->addWidget(label_2, 14, 0, 1, 10);

        verticalSpacer = new QSpacerItem(20, 30, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer, 13, 2, 1, 1);

        aSnapBox = new QCheckBox(MPerfWidget);
        aSnapBox->setObjectName(QStringLiteral("aSnapBox"));

        gridLayout->addWidget(aSnapBox, 16, 1, 1, 4);

        line_2 = new QFrame(MPerfWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 15, 0, 1, 10);

        horizontalLayout_4 = new QHBoxLayout();
        horizontalLayout_4->setObjectName(QStringLiteral("horizontalLayout_4"));
        indicBox = new QCheckBox(MPerfWidget);
        indicBox->setObjectName(QStringLiteral("indicBox"));

        horizontalLayout_4->addWidget(indicBox);

        horizontalSpacer_3 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        horizontalLayout_4->addItem(horizontalSpacer_3);

        spinBox = new QSpinBox(MPerfWidget);
        spinBox->setObjectName(QStringLiteral("spinBox"));
        spinBox->setMaximum(100);
        spinBox->setValue(100);

        horizontalLayout_4->addWidget(spinBox);

        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout_4->addItem(horizontalSpacer_7);


        gridLayout->addLayout(horizontalLayout_4, 0, 1, 1, 9);

        xyBox = new QCheckBox(MPerfWidget);
        xyBox->setObjectName(QStringLiteral("xyBox"));

        gridLayout->addWidget(xyBox, 2, 1, 1, 9);


        verticalLayout->addLayout(gridLayout);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        copyButton = new QPushButton(MPerfWidget);
        copyButton->setObjectName(QStringLiteral("copyButton"));

```

```
        horizontalLayout->addWidget(copyButton);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_6);


        verticalLayout->addLayout(horizontalLayout);


        retranslateUi(MPerfWidget);

        QMetaObject::connectSlotsByName(MPerfWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.54.3 Field Documentation

12.54.3.1 QCheckBox* Ui_MPerfWidget::aSnapBox [inherited]

Definition at line 98 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), MPerfWidget::setPerf(), and Ui_MPerfWidget::setupUi().

12.54.3.2 QPushButton* Ui_MPerfWidget::copyButton [inherited]

Definition at line 108 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.3 QCheckBox* Ui_MPerfWidget::eBox1 [inherited]

Definition at line 95 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.4 QCheckBox* Ui_MPerfWidget::eBox2 [inherited]

Definition at line 44 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.5 QCheckBox* Ui_MPerfWidget::eBox3 [inherited]

Definition at line 94 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.6 QCheckBox* Ui_MPerfWidget::eBox4 [inherited]

Definition at line 92 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.7 QCheckBox* Ui_MPerfWidget::eBox5 [inherited]

Definition at line 60 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.8 QGridLayout* Ui_MPerfWidget::gridLayout [inherited]

Definition at line 39 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.9 QHBoxLayout* Ui_MPerfWidget::horizontalLayout [inherited]

Definition at line 107 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.10 QHBoxLayout* Ui_MPerfWidget::horizontalLayout_2 [inherited]

Definition at line 41 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.11 QHBoxLayout* Ui_MPerfWidget::horizontalLayout_4 [inherited]

Definition at line 100 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.12 QSpacerItem* Ui_MPerfWidget::horizontalSpacer [inherited]

Definition at line 75 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.13 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_2 [inherited]

Definition at line 43 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.14 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_3 [inherited]

Definition at line 102 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.15 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_4 [inherited]

Definition at line 52 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.16 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_5 [inherited]

Definition at line 54 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.17 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_6 [inherited]

Definition at line 109 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.18 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_7 [inherited]

Definition at line 104 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.19 ColorButton* Ui_MPerfWidget::iButton0 [inherited]

Definition at line 80 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.20 ColorButton* Ui_MPerfWidget::iButton1 [inherited]

Definition at line 77 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.21 ColorButton* Ui_MPerfWidget::iButton2 [inherited]

Definition at line 68 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.22 ColorButton* Ui_MPerfWidget::iButton3 [inherited]

Definition at line 55 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.23 ColorButton* Ui_MPerfWidget::iButton4 [inherited]

Definition at line 50 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.24 ColorButton* Ui_MPerfWidget::iButton5 [inherited]

Definition at line 51 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.25 ColorButton* Ui_MPerfWidget::iButtonO [inherited]

Definition at line 70 of file ui_mperfwidget.h.

Referenced by MPerfWidget::colorChanged(), MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), MPerfWidget::setPerf(), and Ui_MPerfWidget::setupUi().

12.54.3.26 QCheckBox* Ui_MPerfWidget::indicBox [inherited]

Definition at line 101 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), MPerfWidget::setPerf(), and Ui_MPerfWidget::setupUi().

12.54.3.27 QLabel* Ui_MPerfWidget::label [inherited]

Definition at line 37 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.28 QLabel* Ui_MPerfWidget::label_11 [inherited]

Definition at line 93 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.29 QLabel* Ui_MPerfWidget::label_12 [inherited]

Definition at line 56 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.30 QLabel* Ui_MPerfWidget::label_13 [inherited]

Definition at line 90 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.31 QLabel* Ui_MPerfWidget::label_14 [inherited]

Definition at line 91 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.32 QLabel* Ui_MPerfWidget::label_15 [inherited]

Definition at line 89 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.33 QLabel* Ui_MPerfWidget::label_2 [inherited]

Definition at line 96 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.34 QLabel* Ui_MPerfWidget::label_25 [inherited]

Definition at line 40 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.35 QLabel* Ui_MPerfWidget::label_3 [inherited]

Definition at line 83 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.36 QLabel* Ui_MPerfWidget::label_4 [inherited]

Definition at line 66 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.37 QLabel* Ui_MPerfWidget::label_5 [inherited]

Definition at line 88 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.38 QLabel* Ui_MPerfWidget::label_6 [inherited]

Definition at line 84 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.39 QLabel* Ui_MPerfWidget::label_7 [inherited]

Definition at line 86 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.40 QLabel* Ui_MPerfWidget::label_8 [inherited]

Definition at line 87 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), and Ui_MPerfWidget::setupUi().

12.54.3.41 QComboBox* Ui_MPerfWidget::lHeightBox [inherited]

Definition at line 42 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), MPerfWidget::setPerf(), and Ui_MPerfWidget::setupUi().

12.54.3.42 QFrame* Ui_MPerfWidget::line [inherited]

Definition at line 38 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.43 QFrame* Ui_MPerfWidget::line_2 [inherited]

Definition at line 99 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.44 QFrame* Ui_MPerfWidget::line_3 [inherited]

Definition at line 69 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.45 QSpinBox* Ui_MPerfWidget::spinBox [inherited]

Definition at line 103 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::retranslateUi(), MPerfWidget::setPerf(), and Ui_MPerfWidget::setupUi().

12.54.3.46 QVBoxLayout* Ui_MPerfWidget::verticalLayout [inherited]

Definition at line 36 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.47 QSpacerItem* Ui_MPerfWidget::verticalSpacer [inherited]

Definition at line 97 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.48 QSpacerItem* Ui_MPerfWidget::verticalSpacer_2 [inherited]

Definition at line 106 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.49 QSpacerItem* Ui_MPerfWidget::verticalSpacer_3 [inherited]

Definition at line 53 of file ui_mperfwidget.h.

Referenced by Ui_MPerfWidget::setupUi().

12.54.3.50 QSpinBox* Ui_MPerfWidget::xBox0 [inherited]

Definition at line 58 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.51 QSpinBox* Ui_MPerfWidget::xBox1 [inherited]

Definition at line 62 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.52 QSpinBox* Ui_MPerfWidget::xBox2 [inherited]

Definition at line 73 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.53 QSpinBox* Ui_MPerfWidget::xBox3 [inherited]

Definition at line 47 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.54 QSpinBox* Ui_MPerfWidget::xBox4 [inherited]

Definition at line 57 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.55 QSpinBox* Ui_MPerfWidget::xBox5 [inherited]

Definition at line 82 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.56 QSlider* Ui_MPerfWidget::xSlider0 [inherited]

Definition at line 67 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.57 QSlider* Ui_MPerfWidget::xSlider1 [inherited]

Definition at line 74 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.58 QSlider* Ui_MPerfWidget::xSlider2 [inherited]

Definition at line 46 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.59 QSlider* Ui_MPerfWidget::xSlider3 [inherited]

Definition at line 81 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.60 QSlider* Ui_MPerfWidget::xSlider4 [inherited]

Definition at line 65 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.61 QSlider* Ui_MPerfWidget::xSlider5 [inherited]

Definition at line 61 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.62 QCheckBox* Ui_MPerfWidget::xyBox [inherited]

Definition at line 105 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), Ui_MPerfWidget::retranslateUi(), Ui_MPerfWidget::setupUi(), and MPerfWidget::sliderYMoved().

12.54.3.63 QSpinBox* Ui_MPerfWidget::yBox0 [inherited]

Definition at line 48 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.64 QSpinBox* Ui_MPerfWidget::yBox1 [inherited]

Definition at line 71 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.65 QSpinBox* Ui_MPerfWidget::yBox2 [inherited]

Definition at line 63 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.66 QSpinBox* Ui_MPerfWidget::yBox3 [inherited]

Definition at line 64 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.67 QSpinBox* Ui_MPerfWidget::yBox4 [inherited]

Definition at line 76 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.68 QSpinBox* Ui_MPerfWidget::yBox5 [inherited]

Definition at line 59 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.69 QSlider* Ui_MPerfWidget::ySlider0 [inherited]

Definition at line 49 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.70 QSlider* Ui_MPerfWidget::ySlider1 [inherited]

Definition at line 79 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.71 QSlider* Ui_MPerfWidget::ySlider2 [inherited]

Definition at line 72 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.72 QSlider* Ui_MPerfWidget::ySlider3 [inherited]

Definition at line 45 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.73 QSlider* Ui_MPerfWidget::ySlider4 [inherited]

Definition at line 78 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

12.54.3.74 QSlider* Ui_MPerfWidget::ySlider5 [inherited]

Definition at line 85 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and Ui_MPerfWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_mperfwidget.h

12.55 MPerfWidget Class Reference

```
#include <src/ckb/mperfwidget.h>
```

Inheritance diagram for MPerfWidget:

Collaboration diagram for MPerfWidget:

Data Structures

- struct DpiUi

Public Member Functions

- MPerfWidget (QWidget ∗parent=0)
- ∼MPerfWidget ()
- void setPerf (KbPerf ∗newPerf, KbProfile ∗newProfile)

Static Public Attributes

- static const int DPI_COUNT = KbPerf::DPI_COUNT
- static const int DPI_MIN = KbPerf::DPI_MIN
- static const int DPI_MAX = KbPerf::DPI_MAX

Private Slots

- void colorClicked (int index)
- void colorChanged (int index)
- void sliderXMoved (int index)
- void sliderYMoved (int index)
- void boxXChanged (int index)
- void boxYChanged (int index)
- void enableChanged (int index)
- void on_xyBox_clicked (bool checked)
- void on_indicBox_clicked (bool checked)
- void on_aSnapBox_clicked (bool checked)
- void on_lHeightBox_activated (int index)
- void on_copyButton_clicked ()
- void on_spinBox_valueChanged (int arg1)

Private Attributes

- Ui::MPerfWidget * ui
- KbPerf * perf
- KbProfile * profile
- DpiUi stages [DPI_COUNT]
- bool _xyLink
- bool colorLink
- QSignalMapper buttonMapper1
- QSignalMapper buttonMapper2
- QSignalMapper sliderXMapper
- QSignalMapper sliderYMapper
- QSignalMapper boxXMapper
- QSignalMapper boxYMapper
- QSignalMapper enableMapper
- bool isSetting

12.55.1 Detailed Description

Definition at line 18 of file mperfwidget.h.

12.55.2 Data Structure Documentation

12.55.2.1 struct MPerfWidget::DpiUi

Definition at line 37 of file mperfwidget.h.

Collaboration diagram for MPerfWidget::DpiUi:

Data Fields

QCheckBox *	enableCheck	
ColorButton *	indicator	
QSpinBox *	xBox	
QSlider *	xSlider	
QSpinBox *	yBox	
QSlider *	ySlider	

12.55.3 Constructor & Destructor Documentation

12.55.3.1 MPerfWidget::MPerfWidget (QWidget * *parent* = 0) [explicit]

Definition at line 8 of file mperfwidget.cpp.

References _xyLink, ColorButton::allowAlpha(), ColorButton::bigIcons(), boxXChanged(), boxXMapper, boxYChanged(), boxYMapper, buttonMapper1, buttonMapper2, colorChanged(), colorClicked(), DPI_COUNT, Ui_MPerfWidget::eBox1, Ui_MPerfWidget::eBox2, Ui_MPerfWidget::eBox3, Ui_MPerfWidget::eBox4, Ui_MPerfWidget::eBox5, enableChanged(), MPerfWidget::DpiUi::enableCheck, enableMapper, Ui_MPerfWidget::iButton0,

Ui_MPerfWidget::iButton1, Ui_MPerfWidget::iButton2, Ui_MPerfWidget::iButton3, Ui_MPerfWidget::iButton4, Ui_MPerfWidget::iButton5, Ui_MPerfWidget::iButtonO, MPerfWidget::DpiUi::indicator, ColorButton::setLabel(), Ui_MPerfWidget::setupUi(), sliderXMapper, sliderXMoved(), sliderYMapper, sliderYMoved(), stages, ui, MPerfWidget::DpiUi::xBox, Ui_MPerfWidget::xBox0, Ui_MPerfWidget::xBox1, Ui_MPerfWidget::xBox2, Ui_MPerfWidget::xBox3, Ui_MPerfWidget::xBox4, Ui_MPerfWidget::xBox5, MPerfWidget::DpiUi::xSlider, Ui_MPerfWidget::xSlider0, Ui_MPerfWidget::xSlider1, Ui_MPerfWidget::xSlider2, Ui_MPerfWidget::xSlider3, Ui_MPerfWidget::xSlider4, Ui_MPerfWidget::xSlider5, Ui_MPerfWidget::xyBox, MPerfWidget::DpiUi::yBox, Ui_MPerfWidget::yBox0, Ui_MPerfWidget::yBox1, Ui_MPerfWidget::yBox2, Ui_MPerfWidget::yBox3, Ui_MPerfWidget::yBox4, Ui_MPerfWidget::yBox5, MPerfWidget::DpiUi::ySlider, Ui_MPerfWidget::ySlider0, Ui_MPerfWidget::ySlider1, Ui_MPerfWidget::ySlider2, Ui_MPerfWidget::ySlider3, Ui_MPerfWidget::ySlider4, and Ui_MPerfWidget::ySlider5.

```
                                        :
    QWidget(parent), ui(new Ui::MPerfWidget), perf(0), profile(0), _xyLink(!CkbSettings::get(xyLinkPath).toBool()), colorLink(false), isSetting(false) {
     ui->setupUi(this);
     ui->xyBox->setChecked(!_xyLink);
     // Set up DPI stages
     stages[0].indicator = ui->iButton0; stages[0].xSlider = ui->xSlider0; stages[0].ySlider = ui->ySlider0; stages[0].xBox = ui->xBox0; stages[0].yBox = ui->yBox0; stages[0].enableCheck = 0;
     stages[1].indicator = ui->iButton1; stages[1].xSlider = ui->xSlider1; stages[1].ySlider = ui->ySlider1; stages[1].xBox = ui->xBox1; stages[1].yBox = ui->yBox1; stages[1].enableCheck = ui->eBox1;
     stages[2].indicator = ui->iButton2; stages[2].xSlider = ui->xSlider2; stages[2].ySlider = ui->ySlider2; stages[2].xBox = ui->xBox2; stages[2].yBox = ui->yBox2; stages[2].enableCheck = ui->eBox2;
     stages[3].indicator = ui->iButton3; stages[3].xSlider = ui->xSlider3; stages[3].ySlider = ui->ySlider3; stages[3].xBox = ui->xBox3; stages[3].yBox = ui->yBox3; stages[3].enableCheck = ui->eBox3;
     stages[4].indicator = ui->iButton4; stages[4].xSlider = ui->xSlider4; stages[4].ySlider = ui->ySlider4; stages[4].xBox = ui->xBox4; stages[4].yBox = ui->yBox4; stages[4].enableCheck = ui->eBox4;
     stages[5].indicator = ui->iButton5; stages[5].xSlider = ui->xSlider5; stages[5].ySlider = ui->ySlider5; stages[5].xBox = ui->xBox5; stages[5].yBox = ui->yBox5; stages[5].enableCheck = ui->eBox5;
     ui->iButtonO->setLabel(false);
     ui->iButtonO->bigIcons(true);
     ui->iButtonO->allowAlpha(true);
     for(int i = 0; i < DPI_COUNT; i++){
         stages[i].indicator->setLabel(false);
         stages[i].indicator->bigIcons(true);
         stages[i].indicator->allowAlpha(true);
         // Map signals
         connect(stages[i].indicator, SIGNAL(clicked(bool)), &buttonMapper1, SLOT(map()));
         connect(stages[i].indicator, SIGNAL(colorChanged(QColor)), &buttonMapper2, SLOT(map()));
         connect(stages[i].xSlider, SIGNAL(valueChanged(int)), &sliderXMapper, SLOT(map()));
         connect(stages[i].ySlider, SIGNAL(valueChanged(int)), &sliderYMapper, SLOT(map()));
         connect(stages[i].xBox, SIGNAL(valueChanged(int)), &boxXMapper, SLOT(map()));
         connect(stages[i].yBox, SIGNAL(valueChanged(int)), &boxYMapper, SLOT(map()));
         if(stages[i].enableCheck)
             // Sniper has no enable
             connect(stages[i].enableCheck, SIGNAL(stateChanged(int)), &enableMapper, SLOT(map()));
         // Set names
         buttonMapper1.setMapping(stages[i].indicator, i);
         buttonMapper2.setMapping(stages[i].indicator, i);
         sliderXMapper.setMapping(stages[i].xSlider, i);
         sliderYMapper.setMapping(stages[i].ySlider, i);
         boxXMapper.setMapping(stages[i].xBox, i);
         boxYMapper.setMapping(stages[i].yBox, i);
         if(stages[i].enableCheck)
             enableMapper.setMapping(stages[i].enableCheck, i);
     }
     // Connect to slots
     connect(&buttonMapper1, SIGNAL(mapped(int)), this, SLOT(colorClicked(int)));
```

```
48     connect(&buttonMapper2, SIGNAL(mapped(int)), this, SLOT(
      colorChanged(int)));
49     connect(&sliderXMapper, SIGNAL(mapped(int)), this, SLOT(
      sliderXMoved(int)));
50     connect(&sliderYMapper, SIGNAL(mapped(int)), this, SLOT(
      sliderYMoved(int)));
51     connect(&boxXMapper, SIGNAL(mapped(int)), this, SLOT(boxXChanged(int)));
52     connect(&boxYMapper, SIGNAL(mapped(int)), this, SLOT(boxYChanged(int)));
53     connect(&enableMapper, SIGNAL(mapped(int)), this, SLOT(
      enableChanged(int)));
54 }
```

Here is the call graph for this function:

12.55.3.2 MPerfWidget::~MPerfWidget ( )

Definition at line 56 of file mperfwidget.cpp.

References ui.

```
56                          {
57     delete ui;
58 }
```

12.55.4 Member Function Documentation

12.55.4.1 void MPerfWidget::boxXChanged (int *index*) [private], [slot]

Definition at line 157 of file mperfwidget.cpp.

References _xyLink, KbPerf::dpi(), dpiLog(), perf, SET_END, SET_START, stages, MPerfWidget::DpiUi::xBox, MPerfWidget::DpiUi::xSlider, and MPerfWidget::DpiUi::yBox.

Referenced by MPerfWidget().

```
{
    SET_START;
    QSpinBox* box = stages[index].xBox;
    QSlider* slider = stages[index].xSlider;
    int value = box->value();
    slider->setValue(dpiLog(value, slider->minimum(), slider->maximum()));
    if(_xyLink)
        perf->dpi(index, value);
    else
        perf->dpi(index, QPoint(value, perf->dpi(index).y()));
    SET_END;
    if(_xyLink)
        stages[index].yBox->setValue(value);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.2 void MPerfWidget::boxYChanged (int *index*) [private],[slot]

Definition at line 172 of file mperfwidget.cpp.

References _xyLink, KbPerf::dpi(), dpiLog(), perf, SET_END, SET_START, stages, MPerfWidget::DpiUi::xBox, MPerfWidget::DpiUi::yBox, and MPerfWidget::DpiUi::ySlider.

Referenced by MPerfWidget().

```
{
    SET_START;
    QSpinBox* box = stages[index].yBox;
    QSlider* slider = stages[index].ySlider;
    int value = box->value();
    slider->setValue(dpiLog(value, slider->minimum(), slider->maximum()));
    if(_xyLink)
        perf->dpi(index, value);
    else
        perf->dpi(index, QPoint(perf->dpi(index).x(), value));
    SET_END;
    if(_xyLink)
        stages[index].xBox->setValue(value);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.3 void MPerfWidget::colorChanged (int *index*) [private],[slot]

Definition at line 86 of file mperfwidget.cpp.

References ColorButton::color(), colorLink, DPI_COUNT, KbPerf::dpiColor(), Ui_MPerfWidget::iButtonO, MPerfWidget::DpiUi::indicator, KbPerf::OTHER, perf, stages, and ui.

Referenced by MPerfWidget().

```
86                                          {
87     QColor color = stages[index].indicator->color();
88     if(colorLink){
89         // Alt was held down - set all
90         for(int i = 0; i < DPI_COUNT; i++){
91             stages[i].indicator->color(color);
92             perf->dpiColor(i, color);
93         }
94         ui->iButtonO->color(color);
95         perf->dpiColor(KbPerf::OTHER, color);
96     } else {
97         // Set one
98         perf->dpiColor(index, color);
99     }
100     colorLink = false;
101 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.4 void MPerfWidget::colorClicked (int *index*) [private],[slot]

Definition at line 81 of file mperfwidget.cpp.

References colorLink.

Referenced by MPerfWidget().

```
81                                      {
82     // Set all colors at once if Alt is held down
83     colorLink = !!(qApp->keyboardModifiers() & Qt::AltModifier);
84 }
```

Here is the caller graph for this function:

12.55.4.5 void MPerfWidget::enableChanged (int *index*) [private],[slot]

Definition at line 187 of file mperfwidget.cpp.

References KbPerf::dpiEnabled(), perf, and stages.

Referenced by MPerfWidget().

```
                                        {
    perf->dpiEnabled(index, stages[index].enableCheck->isChecked());
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.6 void MPerfWidget::on_aSnapBox_clicked (bool *checked*) [private],[slot]

Definition at line 201 of file mperfwidget.cpp.

References KbPerf::angleSnap(), and perf.

```
                                                {
    perf->angleSnap(checked);
}
```

Here is the call graph for this function:

12.55.4.7 void MPerfWidget::on_copyButton_clicked ( ) [private],[slot]

Definition at line 209 of file mperfwidget.cpp.

References KbProfile::currentMode(), KbProfile::modes(), perf, KbMode::perf(), profile, and ModeSelectDialog::selection().

```
209                                     {
210     ModeSelectDialog dialog(this, profile->currentMode(),
      profile->modes(), "Copy performance settings to:");
211     if(dialog.exec() != QDialog::Accepted)
212         return;
213     QList<KbMode*> selectedModes = dialog.selection();
214     foreach(KbMode* mode, selectedModes){
215         *mode->perf() = *perf;
216     }
217 }
```

Here is the call graph for this function:

12.55.4.8 void MPerfWidget::on_indicBox_clicked (bool *checked*) [private],[slot]

Definition at line 197 of file mperfwidget.cpp.

References KbPerf::dpiIndicator(), and perf.

```
197                                             {
198     perf->dpiIndicator(checked);
199 }
```

Here is the call graph for this function:

12.55.4.9 void MPerfWidget::on_lHeightBox_activated (int *index*) [private],[slot]

Definition at line 205 of file mperfwidget.cpp.

References KbPerf::liftHeight(), and perf.

```
205                                                 {
206     perf->liftHeight((KbPerf::height)(index + 1));
207 }
```

Here is the call graph for this function:

12.55.4.10 void MPerfWidget::on_spinBox_valueChanged (int *arg1*) [private],[slot]

Definition at line 219 of file mperfwidget.cpp.

References KbPerf::iOpacity(), and perf.

```
219                                                 {
220     if(!perf)
221         return;
222     perf->iOpacity(arg1 / 100.f);
223 }
```

Here is the call graph for this function:

12.55.4.11 void MPerfWidget::on_xyBox_clicked (bool *checked*) [private],[slot]

Definition at line 191 of file mperfwidget.cpp.

References _xyLink, CkbSettings::set(), and xyLinkPath.

```
191                                                 {
192     _xyLink = !checked;
193     CkbSettings::set(xyLinkPath, checked);
194     // FIXME: update other MPerfWidgets, since this is a global setting
195 }
```

Here is the call graph for this function:

12.55.4.12 void MPerfWidget::setPerf (KbPerf * *newPerf,* KbProfile * *newProfile*)

Definition at line 60 of file mperfwidget.cpp.

References _xyLink, KbPerf::angleSnap(), Ui_MPerfWidget::aSnapBox, ColorButton::color(), KbPerf::dpi(), DPI_COUNT, KbPerf::dpiColor(), KbPerf::dpiEnabled(), KbPerf::dpiIndicator(), MPerfWidget::DpiUi::enableCheck, Ui_MPerfWidget::iButtonO, MPerfWidget::DpiUi::indicator, Ui_MPerfWidget::indicBox, KbPerf::iOpacity(), Ui_MPerfWidget::lHeightBox, KbPerf::liftHeight(), KbPerf::OTHER, perf, profile, Ui_MPerfWidget::spinBox, stages, ui, MPerfWidget::DpiUi::xBox, and MPerfWidget::DpiUi::yBox.

Referenced by KbWidget::modeChanged().

```
60                                                                  {
61     perf = newPerf;
62     profile = newProfile;
63     ui->spinBox->setValue(round(perf->iOpacity() * 100.f));
64     for(int i = 0; i < DPI_COUNT; i++){
65         stages[i].indicator->color(perf->dpiColor(i));
66         bool oldLink = _xyLink;
67         // Don't force X/Y to the same value if they were set differently in the past
68         _xyLink = false;
69         stages[i].xBox->setValue(perf->dpi(i).x());
70         stages[i].yBox->setValue(perf->dpi(i).y());
71         _xyLink = oldLink;
72         if(stages[i].enableCheck)
73             stages[i].enableCheck->setChecked(perf->
      dpiEnabled(i));
74     }
75     ui->iButtonO->color(perf->dpiColor(KbPerf::OTHER));
76     ui->aSnapBox->setChecked(perf->angleSnap());
77     ui->lHeightBox->setCurrentIndex(perf->liftHeight() - 1);
78     ui->indicBox->setChecked(perf->dpiIndicator());
79 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.13 void MPerfWidget::sliderXMoved (int *index*) [private],[slot]

Definition at line 128 of file mperfwidget.cpp.

References _xyLink, KbPerf::dpi(), dpiExp(), dpiRound(), perf, SET_END, SET_START, stages, MPerfWidget::DpiUi::xBox, MPerfWidget::DpiUi::xSlider, and MPerfWidget::DpiUi::ySlider.

Referenced by MPerfWidget().

```
128                                     {
129     SET_START;
```

```
    QSlider* slider = stages[index].xSlider;
    int value = dpiRound(dpiExp(slider->value(), slider->minimum(), slider->maximum()));
    stages[index].xBox->setValue(value);
    if(_xyLink)
        perf->dpi(index, value);
    else
        perf->dpi(index, QPoint(value, perf->dpi(index).y()));
    SET_END;
    if(_xyLink)
        stages[index].ySlider->setValue(slider->value());
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.4.14 void MPerfWidget::sliderYMoved (int *index*) [private],[slot]

Definition at line 142 of file mperfwidget.cpp.

References _xyLink, KbPerf::dpi(), dpiExp(), dpiRound(), perf, SET_END, SET_START, stages, ui, Ui_MPerfWidget::xyBox, MPerfWidget::DpiUi::yBox, and MPerfWidget::DpiUi::ySlider.

Referenced by MPerfWidget().

```
142                                         {
143     SET_START;
144     QSlider* slider = stages[index].ySlider;
145     int value = dpiRound(dpiExp(slider->value(), slider->minimum(), slider->maximum()));
146     stages[index].yBox->setValue(value);
147     if(_xyLink)
148         perf->dpi(index, value);
149     else
150         perf->dpi(index, QPoint(perf->dpi(index).x(), value));
151     SET_END;
152     if(!ui->xyBox->isChecked())
153         // X/Y linked?
154         stages[index].xSlider->setValue(slider->value());
155 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.55.5 Field Documentation

12.55.5.1 bool MPerfWidget::_xyLink [private]

Definition at line 44 of file mperfwidget.h.

Referenced by boxXChanged(), boxYChanged(), MPerfWidget(), on_xyBox_clicked(), setPerf(), sliderXMoved(), and sliderYMoved().

12.55.5.2 QSignalMapper MPerfWidget::boxXMapper [private]

Definition at line 49 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.3 QSignalMapper MPerfWidget::boxYMapper [private]

Definition at line 49 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.4 QSignalMapper MPerfWidget::buttonMapper1 [private]

Definition at line 47 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.5 QSignalMapper MPerfWidget::buttonMapper2 [private]

Definition at line 47 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.6 bool MPerfWidget::colorLink [private]

Definition at line 45 of file mperfwidget.h.

Referenced by colorChanged(), and colorClicked().

12.55.5.7 const int MPerfWidget::DPI_COUNT = KbPerf::DPI_COUNT [static]

Definition at line 28 of file mperfwidget.h.

Referenced by colorChanged(), MPerfWidget(), and setPerf().

12.55.5.8 const int MPerfWidget::DPI_MAX = KbPerf::DPI_MAX [static]

Definition at line 29 of file mperfwidget.h.

12.55.5.9 const int MPerfWidget::DPI_MIN = KbPerf::DPI_MIN [static]

Definition at line 29 of file mperfwidget.h.

12.55.5.10 QSignalMapper MPerfWidget::enableMapper [private]

Definition at line 50 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.11 bool MPerfWidget::isSetting [private]

Definition at line 53 of file mperfwidget.h.

12.55.5.12 KbPerf* MPerfWidget::perf [private]

Definition at line 34 of file mperfwidget.h.

Referenced by boxXChanged(), boxYChanged(), colorChanged(), enableChanged(), on_aSnapBox_clicked(), on_copyButton_clicked(), on_indicBox_clicked(), on_lHeightBox_activated(), on_spinBox_valueChanged(), setPerf(), sliderXMoved(), and sliderYMoved().

12.55.5.13 KbProfile* MPerfWidget::profile [private]

Definition at line 35 of file mperfwidget.h.

Referenced by on_copyButton_clicked(), and setPerf().

12.55.5.14 QSignalMapper MPerfWidget::sliderXMapper [private]

Definition at line 48 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.15 QSignalMapper MPerfWidget::sliderYMapper [private]

Definition at line 48 of file mperfwidget.h.

Referenced by MPerfWidget().

12.55.5.16 DpiUi MPerfWidget::stages[DPI_COUNT] [private]

Definition at line 43 of file mperfwidget.h.

Referenced by boxXChanged(), boxYChanged(), colorChanged(), enableChanged(), MPerfWidget(), setPerf(), sliderXMoved(), and sliderYMoved().

12.55.5.17 Ui::MPerfWidget* MPerfWidget::ui [private]

Definition at line 32 of file mperfwidget.h.

Referenced by colorChanged(), MPerfWidget(), setPerf(), sliderYMoved(), and ~MPerfWidget().

The documentation for this class was generated from the following files:

- src/ckb/mperfwidget.h
- src/ckb/mperfwidget.cpp

12.56 GradientDialog::Preset Struct Reference

Collaboration diagram for GradientDialog::Preset:

Public Member Functions

- Preset (QString _name, bool _builtIn=false)
- Preset (QString _name, const QGradientStops &_gradient)

- Preset ()

Data Fields

- QString name
- QGradientStops gradient
- bool builtIn

12.56.1 Detailed Description

Definition at line 23 of file gradientdialog.h.

12.56.2 Constructor & Destructor Documentation

12.56.2.1 GradientDialog::Preset::Preset (QString *_name*, bool *_builtIn* = `false`) [inline]

Definition at line 27 of file gradientdialog.h.

```
27 : name(_name), builtIn(_builtIn) {}
```

12.56.2.2 GradientDialog::Preset::Preset (QString *_name*, const QGradientStops & *_gradient*) [inline]

Definition at line 28 of file gradientdialog.h.

```
28 : name(_name), gradient(_gradient), builtIn(false) {}
```

12.56.2.3 GradientDialog::Preset::Preset ( ) [inline]

Definition at line 29 of file gradientdialog.h.

```
29 : builtIn(false) {}
```

12.56.3 Field Documentation

12.56.3.1 bool GradientDialog::Preset::builtIn

Definition at line 26 of file gradientdialog.h.

Referenced by GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), GradientDialog::setPreset(), and GradientDialog::~GradientDialog().

12.56.3.2 QGradientStops GradientDialog::Preset::gradient

Definition at line 25 of file gradientdialog.h.

Referenced by GradientDialog::GradientDialog(), GradientDialog::makeIcon(), GradientDialog::setPreset(), and GradientDialog::~GradientDialog().

12.56.3.3 QString GradientDialog::Preset::name

Definition at line 24 of file gradientdialog.h.

Referenced by GradientDialog::addPreset(), GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), GradientDialog::setPreset(), GradientDialog::updatePresets(), and GradientDialog::~GradientDialog().

The documentation for this struct was generated from the following file:

- src/ckb/gradientdialog.h

12.57 QDialog Class Reference

Inheritance diagram for QDialog:

Collaboration diagram for QDialog:

The documentation for this class was generated from the following file:

- src/ckb/extrasettingswidget.h

12.58 QIODevice Class Reference

Inheritance diagram for QIODevice:

Collaboration diagram for QIODevice:

The documentation for this class was generated from the following file:

- src/ckb/quazip/quazipfile.h

12.59 QIODevice_descriptor Struct Reference

Collaboration diagram for QIODevice_descriptor:

Public Member Functions

- QIODevice_descriptor ()

Data Fields

- qint64 pos

12.59.1 Detailed Description

Definition at line 78 of file qioapi.cpp.

12.59.2 Constructor & Destructor Documentation

12.59.2.1 QIODevice_descriptor::QIODevice_descriptor ( ) [inline]

Definition at line 81 of file qioapi.cpp.

```
81                                  :
82          pos(0)
83      {}
```

12.59.3 Field Documentation

12.59.3.1 qint64 QIODevice_descriptor::pos

Definition at line 80 of file qioapi.cpp.

Referenced by qiodevice64_tell_file_func(), qiodevice_open_file_func(), qiodevice_read_file_func(), qiodevice_tell-_file_func(), and qiodevice_write_file_func().

The documentation for this struct was generated from the following file:

- src/ckb/quazip/qioapi.cpp

12.60 QListWidget Class Reference

Inheritance diagram for QListWidget:

Collaboration diagram for QListWidget:

The documentation for this class was generated from the following file:

- src/ckb/rlistwidget.h

12.61 QMainWindow Class Reference

Inheritance diagram for QMainWindow:

Collaboration diagram for QMainWindow:

The documentation for this class was generated from the following file:

- src/ckb/mainwindow.h

12.62 QObject Class Reference

Inheritance diagram for QObject:

Collaboration diagram for QObject:

The documentation for this class was generated from the following file:

- src/ckb/kbprofile.h

12.63 QPushButton Class Reference

Inheritance diagram for QPushButton:

Collaboration diagram for QPushButton:

The documentation for this class was generated from the following file:

- src/ckb/colorbutton.h

12.64 QThread Class Reference

Inheritance diagram for QThread:

Collaboration diagram for QThread:

The documentation for this class was generated from the following file:

- src/ckb/macroreader.h

12.65 QuaAdler32 Class Reference

Adler32 checksum.

`#include <quazip/quaadler32.h>`

Inheritance diagram for QuaAdler32:

Collaboration diagram for QuaAdler32:

Public Member Functions

- QuaAdler32 ()
- quint32 calculate (const QByteArray &data)

  Calculates the checksum for data.
- void reset ()

  Resets the calculation on a checksun for a stream.
- void update (const QByteArray &buf)

  Updates the calculated checksum for the stream.
- quint32 value ()

  Value of the checksum calculated for the stream passed throw update().

Private Attributes

- quint32 checksum

12.65.1 Detailed Description

This class wrappers the adler32 function with the QuaChecksum32 interface. See QuaChecksum32 for more info.

Definition at line 38 of file quaadler32.h.

12.65.2 Constructor & Destructor Documentation

12.65.2.1 QuaAdler32::QuaAdler32 ( )

Definition at line 30 of file quaadler32.cpp.

References reset().

```
31 {
32     reset();
33 }
```

Here is the call graph for this function:

12.65.3 Member Function Documentation

12.65.3.1 quint32 QuaAdler32::calculate (const QByteArray & *data*) [virtual]

data source data

Returns

data checksum

This function has no efect on the value returned by value().

Implements QuaChecksum32.

Definition at line 35 of file quaadler32.cpp.

```
36 {
37     return adler32( adler32(0L, Z_NULL, 0), (const Bytef*)data.data(), data.size() );
38 }
```

12.65.3.2 void QuaAdler32::reset ( ) [virtual]

Implements QuaChecksum32.

Definition at line 40 of file quaadler32.cpp.

References checksum.

Referenced by QuaAdler32().

```
41 {
42     checksum = adler32(0L, Z_NULL, 0);
43 }
```

Here is the caller graph for this function:

12.65.3.3 void QuaAdler32::update (const QByteArray & *buf*) [virtual]

buf next portion of data from the stream

Implements QuaChecksum32.

Definition at line 45 of file quaadler32.cpp.

References checksum.

```
46 {
47     checksum = adler32( checksum, (const Bytef*)buf.data(), buf.size() );
48 }
```

12.65.3.4 quint32 QuaAdler32::value ( ) [virtual]

Returns

checksum

Implements QuaChecksum32.

Definition at line 50 of file quaadler32.cpp.

References checksum.

```
51 {
52     return checksum;
53 }
```

12.65.4 Field Documentation

12.65.4.1 quint32 QuaAdler32::checksum [private]

Definition at line 51 of file quaadler32.h.

Referenced by reset(), update(), and value().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quaadler32.h
- src/ckb/quazip/quaadler32.cpp

12.66 QuaChecksum32 Class Reference

Checksum interface.

```
#include <quazip/quachecksum32.h>
```

Inheritance diagram for QuaChecksum32:

Collaboration diagram for QuaChecksum32:

Public Member Functions

- virtual quint32 calculate (const QByteArray &data)=0

  Calculates the checksum for data.
- virtual void reset ()=0

  Resets the calculation on a checksun for a stream.
- virtual void update (const QByteArray &buf)=0

Updates the calculated checksum for the stream.

- virtual quint32 value ()=0

  Value of the checksum calculated for the stream passed throw update().

12.66.1 Detailed Description

This is an interface for 32 bit checksums. Classes implementing this interface can calcunate a certin checksum in a single step:

```
QChecksum32 *crc32 = new QuaCrc32();
rasoult = crc32->calculate(data);
```

or by streaming the data:

```
QChecksum32 *crc32 = new QuaCrc32();
while(!fileA.atEnd())
    crc32->update(fileA.read(bufSize));
resoultA = crc32->value();
crc32->reset();
while(!fileB.atEnd())
    crc32->update(fileB.read(bufSize));
resoultB = crc32->value();
```

Definition at line 52 of file quachecksum32.h.

12.66.2 Member Function Documentation

12.66.2.1 virtual quint32 QuaChecksum32::calculate (const QByteArray & *data*) [pure virtual]

data source data

Returns

data checksum

This function has no efect on the value returned by value().

Implemented in QuaAdler32, and QuaCrc32.

12.66.2.2 virtual void QuaChecksum32::reset ( ) [pure virtual]

Implemented in QuaAdler32, and QuaCrc32.

12.66.2.3 virtual void QuaChecksum32::update (const QByteArray & *buf*) [pure virtual]

buf next portion of data from the stream

Implemented in QuaAdler32, and QuaCrc32.

12.66.2.4 virtual quint32 QuaChecksum32::value ( ) [pure virtual]

Returns

checksum

Implemented in QuaAdler32, and QuaCrc32.

The documentation for this class was generated from the following file:

- src/ckb/quazip/quachecksum32.h

12.67 QuaCrc32 Class Reference

CRC32 checksum.

```
#include <quazip/quacrc32.h>
```

Inheritance diagram for QuaCrc32:

Collaboration diagram for QuaCrc32:

Public Member Functions

- QuaCrc32 ()
- quint32 calculate (const QByteArray &data)

  Calculates the checksum for data.
- void reset ()

  Resets the calculation on a checksun for a stream.
- void update (const QByteArray &buf)

  Updates the calculated checksum for the stream.
- quint32 value ()

  Value of the checksum calculated for the stream passed throw update().

Private Attributes

- quint32 checksum

12.67.1 Detailed Description

This class wrappers the crc32 function with the QuaChecksum32 interface. See QuaChecksum32 for more info.

Definition at line 35 of file quacrc32.h.

12.67.2 Constructor & Destructor Documentation

12.67.2.1 QuaCrc32::QuaCrc32 ( )

Definition at line 29 of file quacrc32.cpp.

References reset().

```
30 {
31     reset();
32 }
```

Here is the call graph for this function:

12.67.3 Member Function Documentation

12.67.3.1 quint32 QuaCrc32::calculate (const QByteArray & *data*) [virtual]

data source data

Returns

data checksum

This function has no efect on the value returned by value().

Implements QuaChecksum32.

Definition at line 34 of file quacrc32.cpp.

```
35 {
36     return crc32( crc32(0L, Z_NULL, 0), (const Bytef*)data.data(), data.size() );
37 }
```

12.67.3.2 void QuaCrc32::reset ( ) [virtual]

Implements QuaChecksum32.

Definition at line 39 of file quacrc32.cpp.

References checksum.

Referenced by QuaCrc32().

```
40 {
41     checksum = crc32(0L, Z_NULL, 0);
42 }
```

Here is the caller graph for this function:

12.67.3.3 void QuaCrc32::update (const QByteArray & *buf*) [virtual]

buf next portion of data from the stream

Implements QuaChecksum32.

Definition at line 44 of file quacrc32.cpp.

References checksum.

```
45 {
46     checksum = crc32( checksum, (const Bytef*)buf.data(), buf.size() );
47 }
```

12.67.3.4 quint32 QuaCrc32::value ( ) [virtual]

Returns

checksum

Implements QuaChecksum32.

Definition at line 49 of file quacrc32.cpp.

References checksum.

```
50 {
51     return checksum;
52 }
```

12.67.4 Field Documentation

12.67.4.1 quint32 QuaCrc32::checksum [private]

Definition at line 47 of file quacrc32.h.

Referenced by reset(), update(), and value().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quacrc32.h
- src/ckb/quazip/quacrc32.cpp

12.68 QuaGzipFile Class Reference

GZIP file.

```
#include <src/ckb/quazip/quagzipfile.h>
```

Inheritance diagram for QuaGzipFile:

Collaboration diagram for QuaGzipFile:

Public Member Functions

- QuaGzipFile ()

  Empty constructor.
- QuaGzipFile (QObject ∗parent)

  Empty constructor with a parent.
- QuaGzipFile (const QString &fileName, QObject ∗parent=NULL)

  Constructor.
- virtual ∼QuaGzipFile ()

  Destructor.
- void setFileName (const QString &fileName)

  Sets the name of the GZIP file to be opened.
- QString getFileName () const

  Returns the name of the GZIP file.
- virtual bool isSequential () const

  Returns true.
- virtual bool open (QIODevice::OpenMode mode)

  Opens the file.

- virtual bool open (int fd, QIODevice::OpenMode mode)

  Opens the file.
- virtual bool flush ()

  Flushes data to file.
- virtual void close ()

  Closes the file.

Protected Member Functions

- virtual qint64 readData (char *data, qint64 maxSize)

  Implementation of QIODevice::readData().
- virtual qint64 writeData (const char *data, qint64 maxSize)

  Implementation of QIODevice::writeData().

Private Member Functions

- QuaGzipFile (const QuaGzipFile &that)
- QuaGzipFile & operator= (const QuaGzipFile &that)

Private Attributes

- QuaGzipFilePrivate * d

12.68.1 Detailed Description

This class is a wrapper around GZIP file access functions in zlib. Unlike QuaZip classes, it doesn't allow reading from a GZIP file opened as QIODevice, for example, if your GZIP file is in QBuffer. It only provides QIODevice access to a GZIP file contents, but the GZIP file itself must be identified by its name on disk or by descriptor id.

Definition at line 39 of file quagzipfile.h.

12.68.2 Constructor & Destructor Documentation

12.68.2.1 QuaGzipFile::QuaGzipFile ( )

Must call setFileName() before trying to open.

Definition at line 87 of file quagzipfile.cpp.

```
87                          :
88 d(new QuaGzipFilePrivate())
89 {
90 }
```

12.68.2.2 QuaGzipFile::QuaGzipFile (QObject * *parent*)

Must call setFileName() before trying to open.

Parameters

parent	The parent object, as per QObject logic.

Definition at line 92 of file quagzipfile.cpp.

```
92                                        :
93 QIODevice(parent),
94 d(new QuaGzipFilePrivate())
95 {
96 }
```

12.68.2.3 QuaGzipFile::QuaGzipFile (const QString & *fileName*, QObject * *parent* = NULL)

Parameters

fileName	The name of the GZIP file.
parent	The parent object, as per QObject logic.

Definition at line 98 of file quagzipfile.cpp.

```
98                                                                  :
99   QIODevice(parent),
100 d(new QuaGzipFilePrivate(fileName))
101 {
102 }
```

12.68.2.4 QuaGzipFile::~QuaGzipFile ( ) [virtual]

Definition at line 104 of file quagzipfile.cpp.

References close(), and d.

```
105 {
106   if (isOpen()) {
107     close();
108   }
109   delete d;
110 }
```

Here is the call graph for this function:

12.68.2.5 QuaGzipFile::QuaGzipFile (const QuaGzipFile & *that*) [private]

12.68.3 Member Function Documentation

12.68.3.1 void QuaGzipFile::close ( ) [virtual]

Definition at line 152 of file quagzipfile.cpp.

References d.

Referenced by ~QuaGzipFile().

```
{
  QIODevice::close();
  gzclose(d->gzd);
}
```

Here is the caller graph for this function:

12.68.3.2 bool QuaGzipFile::flush ( ) [virtual]

The data is written using Z_SYNC_FLUSH mode. Doesn't make any sense when reading.

Definition at line 147 of file quagzipfile.cpp.

References d.

```
{
    return gzflush(d->gzd, Z_SYNC_FLUSH) == Z_OK;
}
```

12.68.3.3 QString QuaGzipFile::getFileName ( ) const

Definition at line 117 of file quagzipfile.cpp.

References d.

```
{
    return d->fileName;
}
```

12.68.3.4 bool QuaGzipFile::isSequential ( ) const [virtual]

Strictly speaking, zlib supports seeking for GZIP files, but it is poorly implemented, because there is no way to implement it properly. For reading, seeking backwards is very slow, and for writing, it is downright impossible. Therefore, QuaGzipFile does not support seeking at all.

Definition at line 122 of file quagzipfile.cpp.

```
{
  return true;
}
```

12.68.3.5 bool QuaGzipFile::open (QIODevice::OpenMode *mode*) [virtual]

Parameters

mode	Can be either QIODevice::Write or QIODevice::Read. ReadWrite and Append aren't supported.

Definition at line 127 of file quagzipfile.cpp.

References d.

```
128 {
129     QString error;
130     if (!d->open(d->fileName, mode, error)) {
131         setErrorString(error);
132         return false;
133     }
134     return QIODevice::open(mode);
135 }
```

12.68.3.6 bool QuaGzipFile::open (int *fd*, QIODevice::OpenMode *mode*) [virtual]

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Parameters

fd	The file descriptor to read/write the GZIP file from/to.
mode	Can be either QIODevice::Write or QIODevice::Read. ReadWrite and Append aren't supported.

Definition at line 137 of file quagzipfile.cpp.

References d.

```
138 {
139     QString error;
140     if (!d->open(fd, mode, error)) {
141         setErrorString(error);
142         return false;
143     }
144     return QIODevice::open(mode);
145 }
```

12.68.3.7 QuaGzipFile& QuaGzipFile::operator= (const QuaGzipFile & *that*) [private]

12.68.3.8 qint64 QuaGzipFile::readData (char * *data*, qint64 *maxSize*) [protected], [virtual]

Definition at line 158 of file quagzipfile.cpp.

References d.

```
159 {
160     return gzread(d->gzd, (voidp)data, (unsigned)maxSize);
161 }
```

12.68.3.9 void QuaGzipFile::setFileName (const QString & *fileName*)

Definition at line 112 of file quagzipfile.cpp.

References d.

```
113 {
114     d->fileName = fileName;
115 }
```

12.68.3.10 qint64 QuaGzipFile::writeData (const char * *data*, qint64 *maxSize*) [protected],[virtual]

Definition at line 163 of file quagzipfile.cpp.

References d.

```
{
    if (maxSize == 0)
        return 0;
    int written = gzwrite(d->gzd, (voidp)data, (unsigned)maxSize);
    if (written == 0)
        return -1;
    else
        return written;
}
```

12.68.4 Field Documentation

12.68.4.1 QuaGzipFilePrivate* QuaGzipFile::d [private]

Definition at line 105 of file quagzipfile.h.

Referenced by close(), flush(), getFileName(), open(), readData(), setFileName(), writeData(), and ~QuaGzipFile().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quagzipfile.h
- src/ckb/quazip/quagzipfile.cpp

12.69 QuaZIODevice Class Reference

A class to compress/decompress QIODevice.

`#include <src/ckb/quazip/quaziodevice.h>`

Inheritance diagram for QuaZIODevice:

Collaboration diagram for QuaZIODevice:

Public Member Functions

- QuaZIODevice (QIODevice ∗io, QObject ∗parent=NULL)

  Constructor.
- ∼QuaZIODevice ()

  Destructor.
- virtual bool flush ()

  Flushes data waiting to be written.
- virtual bool open (QIODevice::OpenMode mode)

  Opens the device.
- virtual void close ()

  Closes this device, but not the underlying one.
- QIODevice ∗ getIoDevice () const

  Returns the underlying device.
- virtual bool isSequential () const

  Returns true.

Protected Member Functions

- virtual qint64 readData (char ∗data, qint64 maxSize)

  Implementation of QIODevice::readData().
- virtual qint64 writeData (const char ∗data, qint64 maxSize)

  Implementation of QIODevice::writeData().

Private Attributes

- QuaZIODevicePrivate * d

12.69.1 Detailed Description

This class can be used to compress any data written to QIODevice or decompress it back. Compressing data sent over a QTcpSocket is a good example.

Definition at line 41 of file quaziodevice.h.

12.69.2 Constructor & Destructor Documentation

12.69.2.1 QuaZIODevice::QuaZIODevice (QIODevice * io, QObject * parent = NULL)

Parameters

io	The QIODevice to read/write.
parent	The parent object, as per QObject logic.

Definition at line 123 of file quaziodevice.cpp.

```
123                                                     :
124     QIODevice(parent),
125     d(new QuaZIODevicePrivate(io))
126 {
127   connect(io, SIGNAL(readyRead()), SIGNAL(readyRead()));
128 }
```

12.69.2.2 QuaZIODevice::~QuaZIODevice ( )

Definition at line 130 of file quaziodevice.cpp.

References close(), and d.

```
131 {
132     if (isOpen())
133         close();
134     delete d;
135 }
```

Here is the call graph for this function:

12.69.3 Member Function Documentation

12.69.3.1 void QuaZIODevice::close ( ) [virtual]

The underlying QIODevice is not closed in case you want to write something else to it.

Definition at line 169 of file quaziodevice.cpp.

References d, and flush().

Referenced by ~QuaZIODevice().

```
{
    if ((openMode() & QIODevice::ReadOnly) != 0) {
        if (inflateEnd(&d->zins) != Z_OK) {
            setErrorString(d->zins.msg);
        }
    }
    if ((openMode() & QIODevice::WriteOnly) != 0) {
        flush();
        if (deflateEnd(&d->zouts) != Z_OK) {
            setErrorString(d->zouts.msg);
        }
    }
    QIODevice::close();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.69.3.2 bool QuaZIODevice::flush ( ) [virtual]

Unfortunately, as QIODevice doesn't support flush() by itself, the only thing this method does is write the compressed data into the device using Z_SYNC_FLUSH mode. If you need the compressed data to actually be flushed from the buffer of the underlying QIODevice, you need to call its flush() method as well, providing it supports it (like QTcpSocket does). Example:

```
QuaZIODevice dev(&sock);
dev.open(QIODevice::Write);
dev.write(yourDataGoesHere);
dev.flush();
sock->flush(); // this actually sends data to network
```

This may change in the future versions of QuaZIP by implementing an ugly hack: trying to cast the QIODevice using qobject_cast to known flush()-supporting subclasses, and calling flush if the resulting pointer is not zero.

Definition at line 281 of file quaziodevice.cpp.

References d, and QUAZIO_OUTBUFSIZE.

Referenced by close().

```
{
    QString error;
    if (d->doFlush(error) < 0) {
```

```
        setErrorString(error);
        return false;
    }
    // can't flush buffer, some data is still waiting
    if (d->outBufPos < d->outBufSize)
        return true;
    Bytef c = 0;
    d->zouts.next_in = &c; // fake input buffer
    d->zouts.avail_in = 0; // of zero size
    do {
        d->zouts.next_out = (Bytef *) d->outBuf;
        d->zouts.avail_out = QUAZIO_OUTBUFSIZE;
        switch (deflate(&d->zouts, Z_SYNC_FLUSH)) {
        case Z_OK:
          d->outBufSize = (char *) d->zouts.next_out - d->outBuf;
          if (d->doFlush(error) < 0) {
              setErrorString(error);
              return false;
          }
          if (d->outBufPos < d->outBufSize)
              return true;
          break;
        case Z_BUF_ERROR: // nothing to write?
          return true;
        default:
          setErrorString(QString::fromLocal8Bit(d->zouts.msg));
          return false;
        }
    } while (d->zouts.avail_out == 0);
    return true;
}
```

Here is the caller graph for this function:

12.69.3.3 QIODevice * QuaZIODevice::getIoDevice ( ) const

Definition at line 137 of file quaziodevice.cpp.

References d.

```
{
    return d->io;
}
```

12.69.3.4 bool QuaZIODevice::isSequential ( ) const [virtual]

Definition at line 317 of file quaziodevice.cpp.

```
{
  return true;
}
```

12.69.3.5 bool QuaZIODevice::open (QIODevice::OpenMode *mode*) [virtual]

Parameters

mode	Neither QIODevice::ReadWrite nor QIODevice::Append are not supported.

Definition at line 142 of file quaziodevice.cpp.

References d.

```
{
    if ((mode & QIODevice::Append) != 0) {
        setErrorString(trUtf8("QIODevice::Append is not supported for"
                    " QuaZIODevice"));
        return false;
    }
    if ((mode & QIODevice::ReadWrite) == QIODevice::ReadWrite) {
        setErrorString(trUtf8("QIODevice::ReadWrite is not supported for"
                    " QuaZIODevice"));
        return false;
    }
    if ((mode & QIODevice::ReadOnly) != 0) {
        if (inflateInit(&d->zins) != Z_OK) {
            setErrorString(d->zins.msg);
            return false;
        }
    }
    if ((mode & QIODevice::WriteOnly) != 0) {
        if (deflateInit(&d->zouts, Z_DEFAULT_COMPRESSION) != Z_OK) {
            setErrorString(d->zouts.msg);
            return false;
        }
    }
    return QIODevice::open(mode);
}
```

12.69.3.6 qint64 QuaZIODevice::readData (char * *data*, qint64 *maxSize*) [protected],[virtual]

Definition at line 185 of file quaziodevice.cpp.

References d, and QUAZIO_INBUFSIZE.

```
{
  int read = 0;
  while (read < maxSize) {
    if (d->inBufPos == d->inBufSize) {
      d->inBufPos = 0;
      d->inBufSize = d->io->read(d->inBuf, QUAZIO_INBUFSIZE);
      if (d->inBufSize == -1) {
        d->inBufSize = 0;
        setErrorString(d->io->errorString());
        return -1;
      }
      if (d->inBufSize == 0)
        break;
    }
    while (read < maxSize && d->inBufPos < d->inBufSize) {
      d->zins.next_in = (Bytef *) (d->inBuf + d->inBufPos);
      d->zins.avail_in = d->inBufSize - d->inBufPos;
      d->zins.next_out = (Bytef *) (data + read);
      d->zins.avail_out = (uInt) (maxSize - read); // hope it's less than 2GB
      int more = 0;
      switch (inflate(&d->zins, Z_SYNC_FLUSH)) {
      case Z_OK:
        read = (char *) d->zins.next_out - data;
        d->inBufPos = (char *) d->zins.next_in - d->inBuf;
        break;
      case Z_STREAM_END:
        read = (char *) d->zins.next_out - data;
        d->inBufPos = (char *) d->zins.next_in - d->inBuf;
        return read;
      case Z_BUF_ERROR: // this should never happen, but just in case
        if (!d->zBufError) {
          qWarning("Z_BUF_ERROR detected with %d/%d in/out, weird",
              d->zins.avail_in, d->zins.avail_out);
          d->zBufError = true;
        }
        memmove(d->inBuf, d->inBuf + d->inBufPos, d->inBufSize - d->inBufPos);
        d->inBufSize -= d->inBufPos;
        d->inBufPos = 0;
        more = d->io->read(d->inBuf + d->inBufSize, QUAZIO_INBUFSIZE -
d->inBufSize);
```

```
225         if (more == -1) {
226           setErrorString(d->io->errorString());
227           return -1;
228         }
229         if (more == 0)
230           return read;
231         d->inBufSize += more;
232         break;
233       default:
234         setErrorString(QString::fromLocal8Bit(d->zins.msg));
235         return -1;
236       }
237     }
238   }
239 #ifdef QUAZIP_ZIODEVICE_DEBUG_INPUT
240   indebug.write(data, read);
241 #endif
242   return read;
243 }
```

12.69.3.7 qint64 QuaZIODevice::writeData (const char * *data*, qint64 *maxSize*) [protected], [virtual]

Definition at line 245 of file quaziodevice.cpp.

References d, and QUAZIO_OUTBUFSIZE.

```
246 {
247   int written = 0;
248   QString error;
249   if (d->doFlush(error) == -1) {
250     setErrorString(error);
251     return -1;
252   }
253   while (written < maxSize) {
254       // there is some data waiting in the output buffer
255     if (d->outBufPos < d->outBufSize)
256       return written;
257     d->zouts.next_in = (Bytef *) (data + written);
258     d->zouts.avail_in = (uInt) (maxSize - written); // hope it's less than 2GB
259     d->zouts.next_out = (Bytef *) d->outBuf;
260     d->zouts.avail_out = QUAZIO_OUTBUFSIZE;
261     switch (deflate(&d->zouts, Z_NO_FLUSH)) {
262     case Z_OK:
263       written = (char *) d->zouts.next_in - data;
264       d->outBufSize = (char *) d->zouts.next_out - d->outBuf;
265       break;
266     default:
267       setErrorString(QString::fromLocal8Bit(d->zouts.msg));
268       return -1;
269     }
270     if (d->doFlush(error) == -1) {
271       setErrorString(error);
272       return -1;
273     }
274   }
275 #ifdef QUAZIP_ZIODEVICE_DEBUG_OUTPUT
276   debug.write(data, written);
277 #endif
278   return written;
279 }
```

12.69.4 Field Documentation

12.69.4.1 QuaZIODevicePrivate* QuaZIODevice::d [private]

Definition at line 96 of file quaziodevice.h.

Referenced by close(), flush(), getIoDevice(), open(), readData(), writeData(), and ~QuaZIODevice().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quaziodevice.h
- src/ckb/quazip/quaziodevice.cpp

12.70 QuaZip Class Reference

ZIP archive.

`#include <quazip/quazip.h>`

Collaboration diagram for QuaZip:

Public Types

- enum Constants { MAX_FILE_NAME_LENGTH =256 }

  Useful constants.
- enum Mode {
  mdNotOpen, mdUnzip, mdCreate, mdAppend,
  mdAdd }

  Open mode of the ZIP file.
- enum CaseSensitivity { csDefault =0, csSensitive =1, csInsensitive =2 }

  Case sensitivity for the file names.

Public Member Functions

- QuaZip ()

  Constructs QuaZip object.
- QuaZip (const QString &zipName)

  Constructs QuaZip object associated with ZIP file zipName.
- QuaZip (QIODevice ∗ioDevice)

  Constructs QuaZip object associated with ZIP file represented by ioDevice.
- ∼QuaZip ()

  Destroys QuaZip object.
- bool open (Mode mode, zlib_filefunc_def ∗ioApi=NULL)

  Opens ZIP file.
- void close ()

  Closes ZIP file.
- void setFileNameCodec (QTextCodec ∗fileNameCodec)

  Sets the codec used to encode/decode file names inside archive.
- void setFileNameCodec (const char ∗fileNameCodecName)

Sets the codec used to encode/decode file names inside archive.

- QTextCodec * getFileNameCodec () const

  Returns the codec used to encode/decode comments inside archive.
- void setCommentCodec (QTextCodec *commentCodec)

  Sets the codec used to encode/decode comments inside archive.
- void setCommentCodec (const char *commentCodecName)

  Sets the codec used to encode/decode comments inside archive.
- QTextCodec * getCommentCodec () const

  Returns the codec used to encode/decode comments inside archive.
- QString getZipName () const

  Returns the name of the ZIP file.
- void setZipName (const QString &zipName)

  Sets the name of the ZIP file.
- QIODevice * getIoDevice () const

  Returns the device representing this ZIP file.
- void setIoDevice (QIODevice *ioDevice)

  Sets the device representing the ZIP file.
- Mode getMode () const

  Returns the mode in which ZIP file was opened.
- bool isOpen () const

  Returns `true` if ZIP file is open, `false` otherwise.
- int getZipError () const

  Returns the error code of the last operation.
- int getEntriesCount () const

  Returns number of the entries in the ZIP central directory.
- QString getComment () const

  Returns global comment in the ZIP file.
- void setComment (const QString &comment)

  Sets the global comment in the ZIP file.
- bool goToFirstFile ()

  Sets the current file to the first file in the archive.
- bool goToNextFile ()

  Sets the current file to the next file in the archive.
- bool setCurrentFile (const QString &fileName, CaseSensitivity cs=csDefault)

  Sets current file by its name.
- bool hasCurrentFile () const

  Returns `true` if the current file has been set.
- bool getCurrentFileInfo (QuaZipFileInfo *info) const

  Retrieves information about the current file.
- bool getCurrentFileInfo (QuaZipFileInfo64 *info) const

  Retrieves information about the current file.
- QString getCurrentFileName () const

  Returns the current file name.
- unzFile getUnzFile ()

  Returns `unzFile` handle.
- zipFile getZipFile ()

  Returns `zipFile` handle.
- void setDataDescriptorWritingEnabled (bool enabled)

  Changes the data descriptor writing mode.
- bool isDataDescriptorWritingEnabled () const

  Returns the data descriptor default writing mode.

- QStringList getFileNameList () const

  Returns a list of files inside the archive.
- QList< QuaZipFileInfo > getFileInfoList () const

  Returns information list about all files inside the archive.
- QList< QuaZipFileInfo64 > getFileInfoList64 () const

  Returns information list about all files inside the archive.
- void setZip64Enabled (bool zip64)

  Enables the zip64 mode.
- bool isZip64Enabled () const

  Returns whether the zip64 mode is enabled.
- bool isAutoClose () const

  Returns the auto-close flag.
- void setAutoClose (bool autoClose) const

  Sets or unsets the auto-close flag.

Static Public Member Functions

- static Qt::CaseSensitivity convertCaseSensitivity (CaseSensitivity cs)

  Returns the actual case sensitivity for the specified QuaZIP one.
- static void setDefaultFileNameCodec (QTextCodec *codec)

  Sets the default file name codec to use.
- static void setDefaultFileNameCodec (const char *codecName)

  This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Equivalent to calling setDefltFileNameCodec(QTextCodec::codecForName(codecName)).

Private Member Functions

- QuaZip (const QuaZip &that)
- QuaZip & operator= (const QuaZip &that)

Private Attributes

- QuaZipPrivate * p

Friends

- class QuaZipPrivate

12.70.1 Detailed Description

This class implements basic interface to the ZIP archive. It can be used to read table contents of the ZIP archive and retreiving information about the files inside it.

You can also use this class to open files inside archive by passing pointer to the instance of this class to the constructor of the QuaZipFile class. But see QuaZipFile::QuaZipFile(QuaZip*, QObject*) for the possible pitfalls.

This class is indended to provide interface to the ZIP subpackage of the ZIP/UNZIP package as well as to the UNZIP subpackage. But currently it supports only UNZIP.

The use of this class is simple - just create instance using constructor, then set ZIP archive file name using setFile() function (if you did not passed the name to the constructor), then open() and then use different functions to work with it! Well, if you are paranoid, you may also wish to call close before destructing the instance, to check for errors on close.

You may also use getUnzFile() and getZipFile() functions to get the ZIP archive handle and use it with ZIP/UNZIP package API directly.

This class supports localized file names inside ZIP archive, but you have to set up proper codec with setCodec() function. By default, locale codec will be used, which is probably ok for UNIX systems, but will almost certainly fail with ZIP archives created in Windows. This is because Windows ZIP programs have strange habit of using DOS encoding for file names in ZIP archives. For example, ZIP archive with cyrillic names created in Windows will have file names in `IBM866` encoding instead of `WINDOWS-1251`. I think that calling one function is not much trouble, but for true platform independency it would be nice to have some mechanism for file name encoding auto detection using locale information. Does anyone know a good way to do it?

Definition at line 84 of file quazip.h.

12.70.2 Member Enumeration Documentation

12.70.2.1 enum QuaZip::CaseSensitivity

This is what you specify when accessing files in the archive. Works perfectly fine with any characters thanks to Qt's great unicode support. This is different from ZIP/UNZIP API, where only US-ASCII characters was supported.

Enumerator

csDefault Default for platform. Case sensitive for UNIX, not for Windows.

csSensitive Case sensitive.

csInsensitive Case insensitive.

Definition at line 114 of file quazip.h.

```
114                         {
115       csDefault=0,
116       csSensitive=1,
117       csInsensitive=2
118     };
```

12.70.2.2 enum QuaZip::Constants

Enumerator

MAX_FILE_NAME_LENGTH Maximum file name length. Taken from `UNZ_MAXFILENAMEINZIP` constant in unzip.c.

Definition at line 88 of file quazip.h.

```
88                    {
89       MAX_FILE_NAME_LENGTH=256
92     };
```

12.70.2.3 enum QuaZip::Mode

Enumerator

mdNotOpen ZIP file is not open. This is the initial mode.

mdUnzip ZIP file is open for reading files inside it.

mdCreate ZIP file was created with open() call.

mdAppend ZIP file was opened in append mode. This refers to `APPEND_STATUS_CREATEAFTER` mode in ZIP/UNZIP package and means that zip is appended to some existing file what is useful when that file contains self-extractor code. This is obviously *not* what you whant to use to add files to the existing ZIP archive.

mdAdd ZIP file was opened for adding files in the archive.

Definition at line 94 of file quazip.h.

```
94              {
95       mdNotOpen,
96       mdUnzip,
97       mdCreate,
98       mdAppend,
106       mdAdd
107     };
```

12.70.3 Constructor & Destructor Documentation

12.70.3.1 QuaZip::QuaZip (const QuaZip & *that*) [private]

12.70.3.2 QuaZip::QuaZip ( )

Call setName() before opening constructed object.

Definition at line 193 of file quazip.cpp.

```
193              :
194   p(new QuaZipPrivate(this))
195 {
196 }
```

12.70.3.3 QuaZip::QuaZip (const QString & *zipName*)

Definition at line 198 of file quazip.cpp.

```
198                                  :
199   p(new QuaZipPrivate(this, zipName))
200 {
201 }
```

12.70.3.4 QuaZip::QuaZip (QIODevice * *ioDevice*)

The IO device must be seekable, otherwise an error will occur when opening.

Definition at line 203 of file quazip.cpp.

```
203                                 :
204   p(new QuaZipPrivate(this, ioDevice))
205 {
206 }
```

12.70.3.5 QuaZip::~QuaZip ( )

Calls close() if necessary.

Definition at line 208 of file quazip.cpp.

References close(), isOpen(), and p.

```
209 {
210   if(isOpen())
211     close();
212   delete p;
213 }
```

Here is the call graph for this function:

12.70.4 Member Function Documentation

12.70.4.1 void QuaZip::close ( )

Call getZipError() to determine if the close was successful.

If the file was opened by name, then the underlying QIODevice is closed and deleted.

If the underlying QIODevice was set explicitly using setIoDevice() or the appropriate constructor, then it is closed if the auto-close flag is set (which it is by default). Call setAutoClose() to clear the auto-close flag if this behavior is undesirable.

Since Qt 5.1, the QSaveFile was introduced. It breaks the QIODevice API by making close() private and crashing the application if it is called from the base class where it is public. It is an excellent example of poor design that illustrates why you should never ever break an is-a relationship between the base class and a subclass. QuaZIP works around this bug by checking if the QIODevice is an instance of QSaveFile, using qobject_cast<>, and if it is, calls QSaveFile::commit() instead of close(). It is a really ugly hack, but at least it makes your programs work instead of crashing. Note that if the auto-close flag is cleared, then this is a non-issue, and commit() isn't called.

Definition at line 324 of file quazip.cpp.

References QuaZipPrivate::clearDirectoryMap(), QuaZipPrivate::comment, QuaZipPrivate::commentCodec, QuaZipPrivate::ioDevice, mdAdd, mdAppend, mdCreate, mdNotOpen, mdUnzip, QuaZipPrivate::mode, p, UNZ_OK, unzClose(), zipClose(), QuaZipPrivate::zipError, and QuaZipPrivate::zipName.

Referenced by QuaZipFile::close(), JlCompress::compressDir(), JlCompress::compressFile(), JlCompress::compressFiles(), JlCompress::extractDir(), JlCompress::extractFile(), JlCompress::extractFiles(), JlCompress::getFileList(), QuaZipFile::open(), and ~QuaZip().

```
{
  p->zipError=UNZ_OK;
  switch(p->mode) {
    case mdNotOpen:
      qWarning("QuaZip::close(): ZIP is not open");
      return;
    case mdUnzip:
      p->zipError=unzClose(p->unzFile_f);
      break;
    case mdCreate:
    case mdAppend:
    case mdAdd:
      p->zipError=zipClose(p->zipFile_f,
          p->comment.isNull() ? NULL
          : p->commentCodec->fromUnicode(p->comment).constData());
      break;
    default:
      qWarning("QuaZip::close(): unknown mode: %d", (int)p->mode);
      return;
  }
  // opened by name, need to delete the internal IO device
  if (!p->zipName.isEmpty()) {
      delete p->ioDevice;
      p->ioDevice = NULL;
  }
  p->clearDirectoryMap();
  if(p->zipError==UNZ_OK)
    p->mode=mdNotOpen;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.2 Qt::CaseSensitivity QuaZip::convertCaseSensitivity (QuaZip::CaseSensitivity *cs*) [static]

Parameters

cs	The value to convert.

Returns

If CaseSensitivity::csDefault, then returns the default file name case sensitivity for the platform. Otherwise, just returns the appropriate value from the Qt::CaseSensitivity enum.

Definition at line 747 of file quazip.cpp.

References csDefault, and csSensitive.

Referenced by QuaZipDir::exists(), and setCurrentFile().

```
{
  if (cs == csDefault) {
#ifdef Q_WS_WIN
      return Qt::CaseInsensitive;
#else
```

```
        return Qt::CaseSensitive;
#endif
    } else {
        return cs == csSensitive ? Qt::CaseSensitive : Qt::CaseInsensitive;
    }
}
```

Here is the caller graph for this function:

12.70.4.3 QString QuaZip::getComment ( ) const

Definition at line 389 of file quazip.cpp.

References QuaZipPrivate::commentCodec, mdUnzip, QuaZipPrivate::mode, p, unz_global_info64_s::size_comment, UNZ_OK, unzGetGlobalComment(), unzGetGlobalInfo64(), and QuaZipPrivate::zipError.

```
{
  QuaZip *fakeThis=(QuaZip*)this; // non-const
  fakeThis->p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::getComment(): ZIP is not open in mdUnzip mode");
    return QString();
  }
  unz_global_info64 globalInfo;
  QByteArray comment;
  if((fakeThis->p->zipError=unzGetGlobalInfo64(p->unzFile_f, &globalInfo))!=
  UNZ_OK)
    return QString();
  comment.resize(globalInfo.size_comment);
  if((fakeThis->p->zipError=unzGetGlobalComment(p->unzFile_f, comment.data(),
  comment.size())) < 0)
    return QString();
  fakeThis->p->zipError = UNZ_OK;
  return p->commentCodec->toUnicode(comment);
}
```

Here is the call graph for this function:

12.70.4.4 QTextCodec * QuaZip::getCommentCodec ( ) const

Definition at line 597 of file quazip.cpp.

References QuaZipPrivate::commentCodec, and p.

Referenced by QuaZipFile::open().

```
{
  return p->commentCodec;
}
```

Here is the caller graph for this function:

12.70.4.5 bool QuaZip::getCurrentFileInfo (QuaZipFileInfo * *info*) const

Fills the structure pointed by *info*. Returns `true` on success, `false` otherwise. In the latter case structure pointed by *info* remains untouched. If there was an error, getZipError() returns error code.

Should be used only in QuaZip::mdUnzip mode.

Does nothing and returns `false` in any of the following cases.

- ZIP is not open;
- ZIP does not have current file.

In both cases getZipError() returns `UNZ_OK` since there is no ZIP/UNZIP API call.

This overload doesn't support zip64, but will work OK on zip64 archives except that if one of the sizes (compressed or uncompressed) is greater than 0xFFFFFFFFu, it will be set to exactly 0xFFFFFFFFu.

See Also

getCurrentFileInfo(QuaZipFileInfo64* info)const
QuaZipFileInfo64::toQuaZipFileInfo(QuaZipFileInfo&)const

Definition at line 492 of file quazip.cpp.

References QuaZipFileInfo64::toQuaZipFileInfo().

Referenced by JlCompress::extractFile(), QuaZipFile::getFileInfo(), JlCompress::getFileList(), QuaZip_getFileInfo(), and QuaZipDir_getFileInfo().

```
{
    QuaZipFileInfo64 info64;
    if (info == NULL) { // Very unlikely because of the overloads
        return false;
    }
    if (getCurrentFileInfo(&info64)) {
        info64.toQuaZipFileInfo(*info);
        return true;
    } else {
        return false;
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.6 bool QuaZip::getCurrentFileInfo (QuaZipFileInfo64 ∗ *info*) const

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

This function supports zip64. If the archive doesn't use zip64, it is completely equivalent to getCurrentFileInfo(QuaZipFileInfo∗ info) except for the argument type.

See Also

Definition at line 506 of file quazip.cpp.

References QuaZipPrivate::addCurrentFileToDirectoryMap(), QuaZipFileInfo64::comment, QuaZipPrivate::commentCodec, unz_file_info64_s::compressed_size, QuaZipFileInfo64::compressedSize, unz_file_info64_s::compression_method, QuaZipFileInfo64::crc, unz_file_info64_s::crc, QuaZipFileInfo64::dateTime, unz_file_info64_s::disk_num_start, QuaZipFileInfo64::diskNumberStart, unz_file_info64_s::external_fa, QuaZipFileInfo64::externalAttr, QuaZipFileInfo64::extra, QuaZipPrivate::fileNameCodec, unz_file_info64_s::flag, QuaZipFileInfo64::flags, hasCurrentFile(), unz_file_info64_s::internal_fa, QuaZipFileInfo64::internalAttr, isOpen(), mdUnzip, QuaZipFileInfo64::method, QuaZipPrivate::mode, QuaZipFileInfo64::name, p, unz_file_info64_s::size_file_comment, unz_file_info64_s::size_file_extra, unz_file_info64_s::size_filename, tm_unz_s::tm_hour, tm_unz_s::tm_mday, tm_unz_s::tm_min, tm_unz_s::tm_mon, tm_unz_s::tm_sec, tm_unz_s::tm_year, unz_file_info64_s::tmu_date, unz_file_info64_s::uncompressed_size, QuaZipFileInfo64::uncompressedSize, UNZ_OK, unzGetCurrentFileInfo64(), unz_file_info64_s::version, unz_file_info64_s::version_needed, QuaZipFileInfo64::versionCreated, QuaZipFileInfo64::versionNeeded, and QuaZipPrivate::zipError.

```
{
  QuaZip *fakeThis=(QuaZip*)this; // non-const
  fakeThis->p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::getCurrentFileInfo(): ZIP is not open in mdUnzip mode");
    return false;
  }
  unz_file_info64 info_z;
  QByteArray fileName;
  QByteArray extra;
  QByteArray comment;
  if(info==NULL) return false;
  if(!isOpen()||!hasCurrentFile()) return false;
  if((fakeThis->p->zipError=unzGetCurrentFileInfo64(
  p->unzFile_f, &info_z, NULL, 0, NULL, 0, NULL, 0))!=UNZ_OK)
    return false;
  fileName.resize(info_z.size_filename);
  extra.resize(info_z.size_file_extra);
  comment.resize(info_z.size_file_comment);
  if((fakeThis->p->zipError=unzGetCurrentFileInfo64(
  p->unzFile_f, NULL,
      fileName.data(), fileName.size(),
      extra.data(), extra.size(),
      comment.data(), comment.size()))!=UNZ_OK)
    return false;
  info->versionCreated=info_z.version;
  info->versionNeeded=info_z.version_needed;
  info->flags=info_z.flag;
  info->method=info_z.compression_method;
  info->crc=info_z.crc;
  info->compressedSize=info_z.compressed_size;
  info->uncompressedSize=info_z.uncompressed_size;
  info->diskNumberStart=info_z.disk_num_start;
  info->internalAttr=info_z.internal_fa;
  info->externalAttr=info_z.external_fa;
  info->name=p->fileNameCodec->toUnicode(fileName);
  info->comment=p->commentCodec->toUnicode(comment);
  info->extra=extra;
  info->dateTime=QDateTime(
      QDate(info_z.tmu_date.tm_year, info_z.tmu_date.
  tm_mon+1, info_z.tmu_date.tm_mday),
      QTime(info_z.tmu_date.tm_hour, info_z.tmu_date.
  tm_min, info_z.tmu_date.tm_sec));
  // Add to directory map
  p->addCurrentFileToDirectoryMap(info->name);
  return true;
}
```

Here is the call graph for this function:

12.70.4.7 QString QuaZip::getCurrentFileName ( ) const

Equivalent to calling getCurrentFileInfo() and then getting `name` field of the QuaZipFileInfo structure, but faster and more convenient.

Should be used only in QuaZip::mdUnzip mode.

Definition at line 551 of file quazip.cpp.

References QuaZipPrivate::addCurrentFileToDirectoryMap(), QuaZipPrivate::fileNameCodec, hasCurrentFile(), isOpen(), MAX_FILE_NAME_LENGTH, mdUnzip, QuaZipPrivate::mode, p, UNZ_OK, unzGetCurrentFileInfo64(), and QuaZipPrivate::zipError.

Referenced by JlCompress::extractDir(), QuaZipFile::getActualFileName(), QuaZipPrivate::getFileInfoList(), QuaZip_getFileInfo(), and setCurrentFile().

```
{
  QuaZip *fakeThis=(QuaZip*)this; // non-const
  fakeThis->p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::getCurrentFileName(): ZIP is not open in mdUnzip mode");
    return QString();
  }
  if(!isOpen()||!hasCurrentFile()) return QString();
  QByteArray fileName(MAX_FILE_NAME_LENGTH, 0);
  if((fakeThis->p->zipError=unzGetCurrentFileInfo64(
  p->unzFile_f, NULL, fileName.data(), fileName.size(),
      NULL, 0, NULL, 0))!=UNZ_OK)
    return QString();
  QString result = p->fileNameCodec->toUnicode(fileName.constData());
  if (result.isEmpty())
      return result;
  // Add to directory map
  p->addCurrentFileToDirectoryMap(result);
  return result;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.8 int QuaZip::getEntriesCount ( ) const

Returns negative error code in the case of error. The same error code will be returned by subsequent getZipError() call.

Definition at line 375 of file quazip.cpp.

References mdUnzip, QuaZipPrivate::mode, unz_global_info64_s::number_entry, p, UNZ_OK, unzGetGlobalInfo64(), and QuaZipPrivate::zipError.

```
{
  QuaZip *fakeThis=(QuaZip*)this; // non-const
  fakeThis->p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::getEntriesCount(): ZIP is not open in mdUnzip mode");
    return -1;
```

```
  }
  unz_global_info64 globalInfo;
  if((fakeThis->p->zipError=unzGetGlobalInfo64(p->unzFile_f, &globalInfo))!=
  UNZ_OK)
    return p->zipError;
  return (int)globalInfo.number_entry;
}
```

Here is the call graph for this function:

12.70.4.9 QList< QuaZipFileInfo > QuaZip::getFileInfoList ( ) const

Returns

A list of QuaZipFileInfo objects or an empty list if there was an error or if the archive is empty (call getZipError() to figure out which).

This function doesn't support zip64, but will still work with zip64 archives, converting results using QuaZipFileInfo64::toQuaZipFileInfo(). If all file sizes are below 4 GB, it will work just fine.

See Also

getFileNameList()
getFileInfoList64()

Definition at line 729 of file quazip.cpp.

References QuaZipPrivate::getFileInfoList(), and p.

```
{
    QList<QuaZipFileInfo> list;
    if (p->getFileInfoList(&list))
        return list;
    else
        return QList<QuaZipFileInfo>();
}
```

Here is the call graph for this function:

12.70.4.10 QList< QuaZipFileInfo64 > QuaZip::getFileInfoList64 ( ) const

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

This function supports zip64.

See Also

getFileNameList()
getFileInfoList()

Definition at line 738 of file quazip.cpp.

References QuaZipPrivate::getFileInfoList(), and p.

```
739 {
740     QList<QuaZipFileInfo64> list;
741     if (p->getFileInfoList(&list))
742         return list;
743     else
744         return QList<QuaZipFileInfo64>();
745 }
```

Here is the call graph for this function:

12.70.4.11 QTextCodec * QuaZip::getFileNameCodec ( ) const

Definition at line 582 of file quazip.cpp.

References QuaZipPrivate::fileNameCodec, and p.

Referenced by QuaZipFile::open().

```
583 {
584   return p->fileNameCodec;
585 }
```

Here is the caller graph for this function:

12.70.4.12 QStringList QuaZip::getFileNameList ( ) const

Returns

A list of file names or an empty list if there was an error or if the archive is empty (call getZipError() to figure out which).

See Also

getFileInfoList()

Definition at line 720 of file quazip.cpp.

References QuaZipPrivate::getFileInfoList(), and p.

```
721 {
722     QStringList list;
723     if (p->getFileInfoList(&list))
724         return list;
725     else
726         return QStringList();
727 }
```

Here is the call graph for this function:

12.70.4.13 QIODevice * QuaZip::getIoDevice ( ) const

Returns null string if no device has been set explicitly, for example when opening a ZIP file by name.

See Also

setIoDevice(), getZipName(), setZipName()

Definition at line 607 of file quazip.cpp.

References QuaZipPrivate::ioDevice, p, and QuaZipPrivate::zipName.

```
608 {
609   if (!p->zipName.isEmpty()) // opened by name, using an internal QIODevice
610     return NULL;
611   return p->ioDevice;
612 }
```

12.70.4.14 QuaZip::Mode QuaZip::getMode ( ) const

Definition at line 614 of file quazip.cpp.

References QuaZipPrivate::mode, and p.

Referenced by JlCompress::compressFile(), JlCompress::compressSubDir(), QuaZipFile::csize(), JlCompress::extractFile(), QuaZipFile::getFileInfo(), QuaZipFile::open(), and QuaZipFile::usize().

```
{
  return p->mode;
}
```

Here is the caller graph for this function:

12.70.4.15 unzFile QuaZip::getUnzFile ( )

You can use this handle to directly call UNZIP part of the ZIP/UNZIP package functions (see unzip.h).

Warning

When using the handle returned by this function, please keep in mind that QuaZip class is unable to detect any changes you make in the ZIP file state (e. g. changing current file, or closing the handle). So please do not do anything with this handle that is possible to do with the functions of this class. Or at least return the handle in the original state before calling some another function of this class (including implicit destructor calls and calls from the QuaZipFile objects that refer to this QuaZip instance!). So if you have changed the current file in the ZIP archive - then change it back or you may experience some strange behavior or even crashes.

Definition at line 639 of file quazip.cpp.

References p.

Referenced by QuaZipFile::atEnd(), QuaZipFile::close(), QuaZipFile::csize(), QuaZipFile::open(), QuaZipFile::pos(), QuaZipFile::readData(), and QuaZipFile::usize().

```
{
  return p->unzFile_f;
}
```

Here is the caller graph for this function:

12.70.4.16 int QuaZip::getZipError ( ) const

Returns `UNZ_OK` if the last operation was successful.

Error code resets to `UNZ_OK` every time you call any function that accesses something inside ZIP archive, even if it is `const` (like getEntriesCount()). open() and close() calls reset error code too. See documentation for the specific functions for details on error detection.

Definition at line 624 of file quazip.cpp.

References p, and QuaZipPrivate::zipError.

Referenced by QuaZipFile::close(), JlCompress::compressDir(), JlCompress::compressFile(), JlCompress::compressFiles(), JlCompress::extractDir(), JlCompress::extractFile(), JlCompress::extractFiles(), QuaZipFile::getActualFileName(), QuaZipFile::getFileInfo(), JlCompress::getFileList(), and QuaZipFile::open().

```
{
  return p->zipError;
}
```

Here is the caller graph for this function:

12.70.4.17 zipFile QuaZip::getZipFile ( )

You can use this handle to directly call ZIP part of the ZIP/UNZIP package functions (see zip.h). Warnings about the getUnzFile() function also apply to this function.

Definition at line 644 of file quazip.cpp.

References p.

Referenced by QuaZipFile::close(), QuaZipFile::open(), and QuaZipFile::writeData().

```
{
  return p->zipFile_f;
}
```

Here is the caller graph for this function:

12.70.4.18 QString QuaZip::getZipName ( ) const

Returns null string if no ZIP file name has been set, for example when the QuaZip instance is set up to use a QIODevice instead.

See Also

setZipName(), setIoDevice(), getIoDevice()

Definition at line 602 of file quazip.cpp.

References p, and QuaZipPrivate::zipName.

Referenced by JlCompress::compressSubDir(), and QuaZipFile::getZipName().

```
603 {
604   return p->zipName;
605 }
```

Here is the caller graph for this function:

12.70.4.19 bool QuaZip::goToFirstFile ( )

Returns `true` on success, `false` otherwise. Call getZipError() to get the error code.

Definition at line 466 of file quazip.cpp.

References QuaZipPrivate::hasCurrentFile_f, mdUnzip, QuaZipPrivate::mode, p, UNZ_OK, unzGoToFirstFile(), and QuaZipPrivate::zipError.

Referenced by JlCompress::extractDir(), QuaZipPrivate::getFileInfoList(), and JlCompress::getFileList().

```
467 {
468   p->zipError=UNZ_OK;
469   if(p->mode!=mdUnzip) {
470     qWarning("QuaZip::goToFirstFile(): ZIP is not open in mdUnzip mode");
471     return false;
472   }
473   p->zipError=unzGoToFirstFile(p->unzFile_f);
474   p->hasCurrentFile_f=p->zipError==UNZ_OK;
475   return p->hasCurrentFile_f;
476 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.20 bool QuaZip::goToNextFile ( )

Returns `true` on success, `false` otherwise. Call getZipError() to determine if there was an error.

Should be used only in QuaZip::mdUnzip mode.

Note

If the end of file was reached, getZipError() will return `UNZ_OK` instead of `UNZ_END_OF_LIST_OF_FILE`. This is to make things like this easier:

```
for(bool more=zip.goToFirstFile(); more; more=zip.goToNextFile()) {
  // do something
}
if(zip.getZipError()==UNZ_OK) {
  // ok, there was no error
}
```

Definition at line 478 of file quazip.cpp.

References QuaZipPrivate::hasCurrentFile_f, mdUnzip, QuaZipPrivate::mode, p, UNZ_END_OF_LIST_OF_FILE, UNZ_OK, unzGoToNextFile(), and QuaZipPrivate::zipError.

Referenced by JlCompress::extractDir(), QuaZipPrivate::getFileInfoList(), JlCompress::getFileList(), and setCurrentFile().

```
{
  p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::goToFirstFile(): ZIP is not open in mdUnzip mode");
    return false;
  }
  p->zipError=unzGoToNextFile(p->unzFile_f);
  p->hasCurrentFile_f=p->zipError==UNZ_OK;
  if(p->zipError==UNZ_END_OF_LIST_OF_FILE)
    p->zipError=UNZ_OK;
  return p->hasCurrentFile_f;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.21 bool QuaZip::hasCurrentFile ( ) const

Definition at line 634 of file quazip.cpp.

References QuaZipPrivate::hasCurrentFile_f, and p.

Referenced by getCurrentFileInfo(), getCurrentFileName(), QuaZipPrivate::getFileInfoList(), and QuaZipFile::open().

```
635 {
636   return p->hasCurrentFile_f;
637 }
```

Here is the caller graph for this function:

12.70.4.22 bool QuaZip::isAutoClose ( ) const

See Also

setAutoClose()

Definition at line 780 of file quazip.cpp.

References QuaZipPrivate::autoClose, and p.

```
781 {
782     return p->autoClose;
783 }
```

12.70.4.23 bool QuaZip::isDataDescriptorWritingEnabled ( ) const

See Also

setDataDescriptorWritingEnabled()

Definition at line 654 of file quazip.cpp.

References QuaZipPrivate::dataDescriptorWritingEnabled, and p.

Referenced by QuaZipFile::open().

```
{
    return p->dataDescriptorWritingEnabled;
}
```

Here is the caller graph for this function:

12.70.4.24 bool QuaZip::isOpen ( ) const

Definition at line 619 of file quazip.cpp.

References mdNotOpen, QuaZipPrivate::mode, and p.

Referenced by QuaZipFile::close(), getCurrentFileInfo(), getCurrentFileName(), open(), setIoDevice(), setZipName(), and ~QuaZip().

```
{
  return p->mode!=mdNotOpen;
}
```

Here is the caller graph for this function:

12.70.4.25 bool QuaZip::isZip64Enabled ( ) const

Returns

`true` if and only if the zip64 mode is enabled.

See Also

setZip64Enabled()

Definition at line 775 of file quazip.cpp.

References p, and QuaZipPrivate::zip64.

Referenced by QuaZipFile::open().

```
776 {
777     return p->zip64;
778 }
```

Here is the caller graph for this function:

12.70.4.26 bool QuaZip::open (Mode *mode*, zlib_filefunc_def * *ioApi* = NULL)

Argument *mode* specifies open mode of the ZIP archive. See Mode for details. Note that there is zipOpen2() function in the ZIP/UNZIP API which accepts *globalcomment* argument, but it does not use it anywhere, so this open() function does not have this argument. See setComment() if you need to set global comment.

If the ZIP file is accessed via explicitly set QIODevice, then this device is opened in the necessary mode. If the device was already opened by some other means, then QuaZIP checks if the open mode is compatible to the mode needed for the requested operation. If necessary, seeking is performed to position the device properly.

Returns

`true` if successful, `false` otherwise.

Note

ZIP/UNZIP API open calls do not return error code - they just return `NULL` indicating an error. But to make things easier, quazip.h header defines additional error code `UNZ_ERROROPEN` and getZipError() will return it if the open call of the ZIP/UNZIP API returns `NULL`.

Argument *ioApi* specifies IO function set for ZIP/UNZIP package to use. See unzip.h, zip.h and ioapi.h for details. Note that IO API for QuaZip is different from the original package. The file path argument was changed to be of type `voidpf`, and QuaZip passes a QIODevice pointer there. This QIODevice is either set explicitly via setIoDevice() or the QuaZip(QIODevice*) constructor, or it is created internally when opening the archive by its file name. The default API (qioapi.cpp) just delegates everything to the QIODevice API. Not only this allows to use a QIODevice instead of file name, but also has a nice side effect of raising the file size limit from 2G to 4G (in non-zip64 archives).

Note

If the zip64 support is needed, the ioApi argument *must* be NULL because due to the backwards compatibility issues it can be used to provide a 32-bit API only.
If the no-auto-close feature is used, then the *ioApi* argument *should* be NULL because the old API doesn't support the 'fake close' operation, causing slight memory leaks and other possible troubles (like closing the output device in case when an error occurs during opening).

In short: just forget about the *ioApi* argument and you'll be fine.

Definition at line 215 of file quazip.cpp.

References APPEND_STATUS_ADDINZIP, APPEND_STATUS_CREATE, APPEND_STATUS_CREATEAFTER, QuaZipPrivate::autoClose, QuaZipPrivate::dataDescriptorWritingEnabled, QuaZipPrivate::ioDevice, isOpen(), mdAdd, mdAppend, mdCreate, mdUnzip, QuaZipPrivate::mode, p, UNZ_AUTO_CLOSE, UNZ_OK, UNZ_OPENERROR, unzClearFlags(), unzClose(), unzOpen2(), unzOpenInternal(), unzSetFlags(), ZIP_AUTO_CLOSE, ZIP_SEQUENTIAL, ZIP_WRITE_DATA_DESCRIPTOR, zipClose(), QuaZipPrivate::zipError, QuaZipPrivate::zipName, zipOpen2(), zipOpen3(), and zipSetFlags().

Referenced by KbFirmware::_fileForBoard(), JlCompress::compressDir(), JlCompress::compressFile(), JlCompress::compressFiles(), JlCompress::extractDir(), JlCompress::extractFile(), JlCompress::extractFiles(), JlCompress::getFileList(), and QuaZipFile::open().

```
{
  p->zipError=UNZ_OK;
  if(isOpen()) {
    qWarning("QuaZip::open(): ZIP already opened");
    return false;
  }
  QIODevice *ioDevice = p->ioDevice;
  if (ioDevice == NULL) {
    if (p->zipName.isEmpty()) {
      qWarning("QuaZip::open(): set either ZIP file name or IO device first");
      return false;
    } else {
      ioDevice = new QFile(p->zipName);
    }
  }
  unsigned flags = 0;
  switch(mode) {
    case mdUnzip:
      if (ioApi == NULL) {
          if (p->autoClose)
              flags |= UNZ_AUTO_CLOSE;
          p->unzFile_f=unzOpenInternal(ioDevice, NULL, 1, flags);
      } else {
          // QuaZIP pre-zip64 compatibility mode
          p->unzFile_f=unzOpen2(ioDevice, ioApi);
          if (p->unzFile_f != NULL) {
              if (p->autoClose) {
                  unzSetFlags(p->unzFile_f, UNZ_AUTO_CLOSE);
              } else {
                  unzClearFlags(p->unzFile_f, UNZ_AUTO_CLOSE);
              }
          }
      }
      if(p->unzFile_f!=NULL) {
        if (ioDevice->isSequential()) {
            unzClose(p->unzFile_f);
            if (!p->zipName.isEmpty())
                delete ioDevice;
            qWarning("QuaZip::open(): "
                     "only mdCreate can be used with "
                     "sequential devices");
            return false;
        }
        p->mode=mode;
        p->ioDevice = ioDevice;
        return true;
      } else {
        p->zipError=UNZ_OPENERROR;
        if (!p->zipName.isEmpty())
          delete ioDevice;
        return false;
      }
    case mdCreate:
    case mdAppend:
    case mdAdd:
      if (ioApi == NULL) {
```

```
272             if (p->autoClose)
273                 flags |= ZIP_AUTO_CLOSE;
274             if (p->dataDescriptorWritingEnabled)
275                 flags |= ZIP_WRITE_DATA_DESCRIPTOR;
276             p->zipFile_f=zipOpen3(ioDevice,
277                 mode==mdCreate?APPEND_STATUS_CREATE:
278                 mode==mdAppend?APPEND_STATUS_CREATEAFTER:
279                 APPEND_STATUS_ADDINZIP,
280                 NULL, NULL, flags);
281         } else {
282             // QuaZIP pre-zip64 compatibility mode
283             p->zipFile_f=zipOpen2(ioDevice,
284                 mode==mdCreate?APPEND_STATUS_CREATE:
285                 mode==mdAppend?APPEND_STATUS_CREATEAFTER:
286                 APPEND_STATUS_ADDINZIP,
287                 NULL,
288                 ioApi);
289             if (p->zipFile_f != NULL) {
290                 zipSetFlags(p->zipFile_f, flags);
291             }
292         }
293         if(p->zipFile_f!=NULL) {
294           if (ioDevice->isSequential()) {
295               if (mode != mdCreate) {
296                   zipClose(p->zipFile_f, NULL);
297                   qWarning("QuaZip::open(): "
298                           "only mdCreate can be used with "
299                            "sequential devices");
300                   if (!p->zipName.isEmpty())
301                       delete ioDevice;
302                   return false;
303               }
304               zipSetFlags(p->zipFile_f, ZIP_SEQUENTIAL);
305           }
306           p->mode=mode;
307           p->ioDevice = ioDevice;
308           return true;
309         } else {
310           p->zipError=UNZ_OPENERROR;
311           if (!p->zipName.isEmpty())
312             delete ioDevice;
313           return false;
314         }
315       default:
316         qWarning("QuaZip::open(): unknown mode: %d", (int)mode);
317         if (!p->zipName.isEmpty())
318           delete ioDevice;
319         return false;
320         break;
321     }
322 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.27 QuaZip& QuaZip::operator= (const QuaZip & *that*) [private]

12.70.4.28 void QuaZip::setAutoClose (bool *autoClose*) const

By default, QuaZIP opens the underlying QIODevice when open() is called, and closes it when close() is called. In some cases, when the device is set explicitly using setIoDevice(), it may be desirable to leave the device open. If the auto-close flag is unset using this method, then the device isn't closed automatically if it was set explicitly.

If it is needed to clear this flag, it is recommended to do so before opening the archive because otherwise QuaZIP may close the device during the open() call if an error is encountered after the device is opened.

If the device was not set explicitly, but rather the setZipName() or the appropriate constructor was used to set the

ZIP file name instead, then the auto-close flag has no effect, and the internal device is closed nevertheless because there is no other way to close it.

See Also

isAutoClose()
setIoDevice()

Definition at line 785 of file quazip.cpp.

References QuaZipPrivate::autoClose, and p.

```
786 {
787     p->autoClose = autoClose;
788 }
```

12.70.4.29 void QuaZip::setComment (const QString & *comment*)

The comment will be written to the archive on close operation. QuaZip makes a distinction between a null QByteArray() comment and an empty "" comment in the QuaZip::mdAdd mode. A null comment is the default and it means "don't change the comment". An empty comment removes the original comment.

See Also

open()

Definition at line 629 of file quazip.cpp.

References QuaZipPrivate::comment, and p.

```
630 {
631   p->comment=comment;
632 }
```

12.70.4.30 void QuaZip::setCommentCodec (QTextCodec * *commentCodec*)

This codec defaults to locale codec, which is probably ok.

Definition at line 587 of file quazip.cpp.

References QuaZipPrivate::commentCodec, and p.

```
588 {
589   p->commentCodec=commentCodec;
590 }
```

12.70.4.31 void QuaZip::setCommentCodec (const char * *commentCodecName*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Equivalent to calling setCommentCodec(QTextCodec::codecForName(codecName));

Definition at line 592 of file quazip.cpp.

References QuaZipPrivate::commentCodec, and p.

```
593 {
594   p->commentCodec=QTextCodec::codecForName(commentCodecName);
595 }
```

12.70.4.32 bool QuaZip::setCurrentFile (const QString & *fileName*, CaseSensitivity *cs* = csDefault)

Returns `true` if successful, `false` otherwise. Argument *cs* specifies case sensitivity of the file name. Call getZipError() in the case of a failure to get error code.

This is not a wrapper to unzLocateFile() function. That is because I had to implement locale-specific case-insensitive comparison.

Here are the differences from the original implementation:

- If the file was not found, error code is `UNZ_OK`, not `UNZ_END_OF_LIST_OF_FILE` (see also goToNextFile()).
- If this function fails, it unsets the current file rather than resetting it back to what it was before the call.

If *fileName* is null string then this function unsets the current file and return `true`. Note that you should close the file first if it is open! See QuaZipFile::QuaZipFile(QuaZip∗,QObject∗) for the details.

Should be used only in QuaZip::mdUnzip mode.

See Also

setFileNameCodec(), CaseSensitivity

Definition at line 408 of file quazip.cpp.

References convertCaseSensitivity(), QuaZipPrivate::directoryCaseInsensitive, QuaZipPrivate::directoryCaseSensitive, getCurrentFileName(), QuaZipPrivate::goToFirstUnmappedFile(), goToNextFile(), QuaZipPrivate::hasCurrentFile_f, MAX_FILE_NAME_LENGTH, mdUnzip, QuaZipPrivate::mode, p, unz64_file_pos_s::pos_in_zip_directory, UNZ_OK, UNZ_PARAMERROR, unzGoToFilePos64(), and QuaZipPrivate::zipError.

Referenced by KbFirmware::_fileForBoard(), JlCompress::extractFile(), QuaZipPrivate::getFileInfoList(), and QuaZipFile::open().

```
{
  p->zipError=UNZ_OK;
  if(p->mode!=mdUnzip) {
    qWarning("QuaZip::setCurrentFile(): ZIP is not open in mdUnzip mode");
    return false;
  }
  if(fileName.isEmpty()) {
    p->hasCurrentFile_f=false;
    return true;
  }
  // Unicode-aware reimplementation of the unzLocateFile function
  if(p->unzFile_f==NULL) {
    p->zipError=UNZ_PARAMERROR;
    return false;
  }
  if(fileName.length()>MAX_FILE_NAME_LENGTH) {
    p->zipError=UNZ_PARAMERROR;
    return false;
  }
  // Find the file by name
  bool sens = convertCaseSensitivity(cs) == Qt::CaseSensitive;
  QString lower, current;
  if(!sens) lower=fileName.toLower();
  p->hasCurrentFile_f=false;

  // Check the appropriate Map
  unz64_file_pos fileDirPos;
  fileDirPos.pos_in_zip_directory = 0;
  if (sens) {
      if (p->directoryCaseSensitive.contains(fileName))
          fileDirPos = p->directoryCaseSensitive.value(fileName);
  } else {
      if (p->directoryCaseInsensitive.contains(lower))
          fileDirPos = p->directoryCaseInsensitive.value(lower);
  }

  if (fileDirPos.pos_in_zip_directory != 0) {
      p->zipError = unzGoToFilePos64(p->unzFile_f, &fileDirPos);
      p->hasCurrentFile_f = p->zipError == UNZ_OK;
  }
```

```
  if (p->hasCurrentFile_f)
      return p->hasCurrentFile_f;

  // Not mapped yet, start from where we have got to so far
  for(bool more=p->goToFirstUnmappedFile(); more; more=
  goToNextFile()) {
    current=getCurrentFileName();
    if(current.isEmpty()) return false;
    if(sens) {
      if(current==fileName) break;
    } else {
      if(current.toLower()==lower) break;
    }
  }
  return p->hasCurrentFile_f;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.70.4.33 void QuaZip::setDataDescriptorWritingEnabled (bool *enabled*)

According to the ZIP format specification, a file inside archive may have a data descriptor immediately following the file data. This is reflected by a special flag in the local file header and in the central directory. By default, QuaZIP sets this flag and writes the data descriptor unless both method and level were set to 0, in which case it operates in 1.0-compatible mode and never writes data descriptors.

By setting this flag to false, it is possible to disable data descriptor writing, thus increasing compatibility with archive readers that don't understand this feature of the ZIP file format.

Setting this flag affects all the QuaZipFile instances that are opened after this flag is set.

The data descriptor writing mode is enabled by default.

Note that if the ZIP archive is written into a QIODevice for which QIODevice::isSequential() returns `true`, then the data descriptor is mandatory and will be written even if this flag is set to false.

Parameters

enabled	If `true`, enable local descriptor writing, disable it otherwise.

See Also

QuaZipFile::isDataDescriptorWritingEnabled()

Definition at line 649 of file quazip.cpp.

References QuaZipPrivate::dataDescriptorWritingEnabled, and p.

```
{
    p->dataDescriptorWritingEnabled = enabled;
}
```

12.70.4.34 void QuaZip::setDefaultFileNameCodec (QTextCodec * *codec*) [static]

The default codec is used by the constructors, so calling this function won't affect the QuaZip instances already created at that moment.

The codec specified here can be overriden by calling setFileNameCodec(). If neither function is called, QTextCodec::codecForLocale() will be used to decode or encode file names. Use this function with caution if the application uses other libraries that depend on QuaZIP. Those libraries can either call this function by themselves, thus overriding your setting or can rely on the default encoding, thus failing mysteriously if you change it. For these reasons, it isn't recommended to use this function if you are developing a library, not an application. Instead, ask your library users to call it in case they need specific encoding.

In most cases, using setFileNameCodec() instead is the right choice. However, if you depend on third-party code that uses QuaZIP, then the reasons stated above can actually become a reason to use this function in case the third-party code in question fails because it doesn't understand the encoding you need and doesn't provide a way to specify it. This applies to the JlCompress class as well, as it was contributed and doesn't support explicit encoding parameters.

In short: use setFileNameCodec() when you can, resort to setDefaultFileNameCodec() when you don't have access to the QuaZip instance.

Parameters

codec	The codec to use by default. If NULL, resets to default.

Definition at line 760 of file quazip.cpp.

References QuaZipPrivate::defaultFileNameCodec.

Referenced by setDefaultFileNameCodec().

```
{
    QuaZipPrivate::defaultFileNameCodec = codec;
}
```

Here is the caller graph for this function:

12.70.4.35 void QuaZip::setDefaultFileNameCodec (const char * *codecName*) [static]

Definition at line 765 of file quazip.cpp.

References setDefaultFileNameCodec().

```
766 {
767     setDefaultFileNameCodec(QTextCodec::codecForName(codecName));
768 }
```

Here is the call graph for this function:

12.70.4.36 void QuaZip::setFileNameCodec (QTextCodec * *fileNameCodec*)

This is necessary to access files in the ZIP archive created under Windows with non-latin characters in file names. For example, file names with cyrillic letters will be in `IBM866` encoding.

Definition at line 572 of file quazip.cpp.

References QuaZipPrivate::fileNameCodec, and p.

```
573 {
574   p->fileNameCodec=fileNameCodec;
575 }
```

12.70.4.37 void QuaZip::setFileNameCodec (const char * *fileNameCodecName*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Equivalent to calling setFileNameCodec(QTextCodec::codecForName(codecName));

Definition at line 577 of file quazip.cpp.

References QuaZipPrivate::fileNameCodec, and p.

```
578 {
579   p->fileNameCodec=QTextCodec::codecForName(fileNameCodecName);
580 }
```

12.70.4.38 void QuaZip::setIoDevice (QIODevice * *ioDevice*)

Does nothing if the ZIP file is open.

Does not reset error code returned by getZipError().

See Also

getIoDevice(), getZipName(), setZipName()

Definition at line 365 of file quazip.cpp.

References QuaZipPrivate::ioDevice, isOpen(), p, and QuaZipPrivate::zipName.

```
{
  if(isOpen()) {
    qWarning("QuaZip::setIoDevice(): ZIP is already open!");
    return;
  }
  p->ioDevice = ioDevice;
  p->zipName = QString();
}
```

Here is the call graph for this function:

12.70.4.39 void QuaZip::setZip64Enabled (bool *zip64*)

Parameters

zip64	If `true`, the zip64 mode is enabled, disabled otherwise.

Once this is enabled, all new files (until the mode is disabled again) will be created in the zip64 mode, thus enabling the ability to write files larger than 4 GB. By default, the zip64 mode is off due to compatibility reasons.

Note that this does not affect the ability to read zip64 archives in any way.

See Also

isZip64Enabled()

Definition at line 770 of file quazip.cpp.

References p, and QuaZipPrivate::zip64.

```
{
    p->zip64 = zip64;
}
```

12.70.4.40 void QuaZip::setZipName (const QString & *zipName*)

Does nothing if the ZIP file is open.

Does not reset error code returned by getZipError().

See Also

setIoDevice(), getIoDevice(), getZipName()

Definition at line 355 of file quazip.cpp.

References QuaZipPrivate::ioDevice, isOpen(), p, and QuaZipPrivate::zipName.

```
{
  if(isOpen()) {
    qWarning("QuaZip::setZipName(): ZIP is already open!");
    return;
  }
  p->zipName=zipName;
  p->ioDevice = NULL;
}
```

Here is the call graph for this function:

12.70.5 Friends And Related Function Documentation

12.70.5.1 friend class QuaZipPrivate [friend]

Definition at line 85 of file quazip.h.

12.70.6 Field Documentation

12.70.6.1 QuaZipPrivate* QuaZip::p [private]

Definition at line 129 of file quazip.h.

Referenced by close(), getComment(), getCommentCodec(), getCurrentFileInfo(), getCurrentFileName(), getEntriesCount(), getFileInfoList(), getFileInfoList64(), getFileNameCodec(), getFileNameList(), getIoDevice(), getMode(), getUnzFile(), getZipError(), getZipFile(), getZipName(), goToFirstFile(), goToNextFile(), hasCurrentFile(), isAutoClose(), isDataDescriptorWritingEnabled(), isOpen(), isZip64Enabled(), open(), setAutoClose(), setComment(), setCommentCodec(), setCurrentFile(), setDataDescriptorWritingEnabled(), setFileNameCodec(), setIoDevice(), setZip64Enabled(), setZipName(), and ~QuaZip().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quazip.h
- src/ckb/quazip/quazip.cpp

12.71 QuaZipDir Class Reference

Provides ZIP archive navigation.

`#include <src/ckb/quazip/quazipdir.h>`

Collaboration diagram for QuaZipDir:

Public Member Functions

- QuaZipDir (const QuaZipDir &that)

  The copy constructor.
- QuaZipDir (QuaZip *zip, const QString &dir=QString())

  Constructs a QuaZipDir instance pointing to the specified directory.
- ~QuaZipDir ()

  Destructor.
- bool operator== (const QuaZipDir &that)

  The assignment operator.
- bool operator!= (const QuaZipDir &that)

  operator!=
- QuaZipDir & operator= (const QuaZipDir &that)

  operator==
- QString operator[] (int pos) const

  Returns the name of the entry at the specified position.
- QuaZip::CaseSensitivity caseSensitivity () const

  Returns the current case sensitivity mode.
- bool cd (const QString &dirName)

  Changes the 'current' directory.

- bool cdUp ()

  Goes up.
- uint count () const

  Returns the number of entries in the directory.
- QString dirName () const

  Returns the current directory name.
- QList< QuaZipFileInfo > entryInfoList (const QStringList &nameFilters, QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entries in the directory.
- QList< QuaZipFileInfo > entryInfoList (QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entries in the directory.
- QList< QuaZipFileInfo64 > entryInfoList64 (const QStringList &nameFilters, QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entries in the directory with zip64 support.
- QList< QuaZipFileInfo64 > entryInfoList64 (QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entries in the directory with zip64 support.
- QStringList entryList (const QStringList &nameFilters, QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entry names in the directory.
- QStringList entryList (QDir::Filters filters=QDir::NoFilter, QDir::SortFlags sort=QDir::NoSort) const

  Returns the list of the entry names in the directory.
- bool exists (const QString &fileName) const

  Returns `true` if the entry with the specified name exists.
- bool exists () const

  Return `true` if the directory pointed by this QuaZipDir exists.
- QString filePath (const QString &fileName) const

  Returns the full path to the specified file.
- QDir::Filters filter ()

  Returns the default filter.
- bool isRoot () const

  Returns if the QuaZipDir points to the root of the archive.
- QStringList nameFilters () const

  Return the default name filter.
- QString path () const

  Returns the path to the current dir.
- QString relativeFilePath (const QString &fileName) const

  Returns the path to the specified file relative to the current dir.
- void setCaseSensitivity (QuaZip::CaseSensitivity caseSensitivity)

  Sets the default case sensitivity mode.
- void setFilter (QDir::Filters filters)

  Sets the default filter.
- void setNameFilters (const QStringList &nameFilters)

  Sets the default name filter.
- void setPath (const QString &path)

  Goes to the specified path.
- void setSorting (QDir::SortFlags sort)

  Sets the default sorting mode.
- QDir::SortFlags sorting () const

  Returns the default sorting mode.

Private Attributes

- QSharedDataPointer
  < QuaZipDirPrivate > d

12.71.1 Detailed Description

This class is modelled after QDir, and is designed to provide similar features for ZIP archives.

The only significant difference from QDir is that the root path is not '/', but an empty string since that's how the file paths are stored in the archive. However, QuaZipDir understands the paths starting with '/'. It is important in a few places:

- In the cd() function.
- In the constructor.
- In the exists() function.
- In the relativePath() function.

Note that since ZIP uses '/' on all platforms, the '\' separator is not supported.

Definition at line 54 of file quazipdir.h.

12.71.2 Constructor & Destructor Documentation

12.71.2.1 QuaZipDir::QuaZipDir (const QuaZipDir & *that*)

Definition at line 50 of file quazipdir.cpp.

Referenced by exists().

```
50                                                  :
51     d(that.d)
52 {
53 }
```

Here is the caller graph for this function:

12.71.2.2 QuaZipDir::QuaZipDir (QuaZip * *zip*, const QString & *dir* = `QString()`)

If *dir* is not specified, points to the root of the archive. The same happens if the *dir* is "/".

Definition at line 55 of file quazipdir.cpp.

References d.

```
55                                                          :
56     d(new QuaZipDirPrivate(zip, dir))
57 {
58     if (d->dir.startsWith('/'))
59         d->dir = d->dir.mid(1);
60 }
```

12.71.2.3 QuaZipDir::~QuaZipDir ( )

Definition at line 62 of file quazipdir.cpp.

```
63 {
64 }
```

12.71.3 Member Function Documentation

12.71.3.1 QuaZip::CaseSensitivity QuaZipDir::caseSensitivity ( ) const

Definition at line 82 of file quazipdir.cpp.

References d.

Referenced by setCaseSensitivity().

```
83 {
84     return d->caseSensitivity;
85 }
```

Here is the caller graph for this function:

12.71.3.2 bool QuaZipDir::cd (const QString & *dirName*)

If the path starts with '/', it is interpreted as an absolute path from the root of the archive. Otherwise, it is interpreted as a path relative to the current directory as was set by the previous cd() or the constructor.

Note that the subsequent path() call will not return a path starting with '/' in all cases.

Definition at line 87 of file quazipdir.cpp.

References cd(), d, dirName(), exists(), isRoot(), and path().

Referenced by cd(), and cdUp().

```
88 {
89     if (directoryName == "/") {
90         d->dir = "";
91         return true;
92     }
93     QString dirName = directoryName;
94     if (dirName.endsWith('/'))
95         dirName.chop(1);
96     if (dirName.contains('/')) {
97         QuaZipDir dir(*this);
98         if (dirName.startsWith('/')) {
99 #ifdef QUAZIP_QUAZIPDIR_DEBUG
100             qDebug("QuaZipDir::cd(%s): going to /",
101                     dirName.toUtf8().constData());
102 #endif
103             if (!dir.cd("/"))
104                 return false;
105         }
106         QStringList path = dirName.split('/', QString::SkipEmptyParts);
107         for (QStringList::const_iterator i = path.constBegin();
108                 i != path.end();
```

```
                ++i) {
            const QString &step = *i;
#ifdef QUAZIP_QUAZIPDIR_DEBUG
            qDebug("QuaZipDir::cd(%s): going to %s",
                    dirName.toUtf8().constData(),
                    step.toUtf8().constData());
#endif
            if (!dir.cd(step))
                return false;
        }
        d->dir = dir.path();
        return true;
    } else { // no '/'
        if (dirName == ".") {
            return true;
        } else if (dirName == "..") {
            if (isRoot()) {
                return false;
            } else {
                int slashPos = d->dir.lastIndexOf('/');
                if (slashPos == -1) {
                    d->dir = "";
                } else {
                    d->dir = d->dir.left(slashPos);
                }
                return true;
            }
        } else { // a simple subdirectory
            if (exists(dirName)) {
                if (isRoot())
                    d->dir = dirName;
                else
                    d->dir += "/" + dirName;
                return true;
            } else {
                return false;
            }
        }
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.71.3.3 bool QuaZipDir::cdUp ( )

Definition at line 150 of file quazipdir.cpp.

References cd().

```
151 {
152     return cd("..");
153 }
```

Here is the call graph for this function:

12.71.3.4 uint QuaZipDir::count ( ) const

Definition at line 155 of file quazipdir.cpp.

References entryList().

```
156 {
157     return entryList().count();
158 }
```

Here is the call graph for this function:

12.71.3.5 QString QuaZipDir::dirName ( ) const

The name doesn't include the path.

Definition at line 160 of file quazipdir.cpp.

References d.

Referenced by cd().

```
161 {
162     return QDir(d->dir).dirName();
163 }
```

Here is the caller graph for this function:

12.71.3.6 QList< QuaZipFileInfo > QuaZipDir::entryInfoList (const QStringList & *nameFilters*, QDir::Filters *filters* = QDir::NoFilter, QDir::SortFlags *sort* = QDir::NoSort) const

Parameters

nameFilters	The list of file patterns to list, uses the same syntax as QDir.
filters	The entry type filters, only Files and Dirs are accepted.
sort	Sorting mode.

Definition at line 401 of file quazipdir.cpp.

References d.

Referenced by entryInfoList().

```
403 {
404     QList<QuaZipFileInfo> result;
405     if (d->entryInfoList(nameFilters, filters, sort, result))
406         return result;
407     else
408         return QList<QuaZipFileInfo>();
409 }
```

Here is the caller graph for this function:

12.71.3.7 QList< QuaZipFileInfo > QuaZipDir::entryInfoList (QDir::Filters *filters* = `QDir::NoFilter`, QDir::SortFlags *sort* = `QDir::NoSort`) const

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

The same as entryInfoList(QStringList(), filters, sort).

Definition at line 411 of file quazipdir.cpp.

References entryInfoList().

```
413 {
414     return entryInfoList(QStringList(), filters, sort);
415 }
```

Here is the call graph for this function:

12.71.3.8 QList< QuaZipFileInfo64 > QuaZipDir::entryInfoList64 (const QStringList & *nameFilters*, QDir::Filters *filters* = `QDir::NoFilter`, QDir::SortFlags *sort* = `QDir::NoSort`) const

Parameters

nameFilters	The list of file patterns to list, uses the same syntax as QDir.
filters	The entry type filters, only Files and Dirs are accepted.
sort	Sorting mode.

Definition at line 417 of file quazipdir.cpp.

References d.

Referenced by entryInfoList64().

```
419 {
420     QList<QuaZipFileInfo64> result;
421     if (d->entryInfoList(nameFilters, filters, sort, result))
422         return result;
423     else
424         return QList<QuaZipFileInfo64>();
425 }
```

Here is the caller graph for this function:

12.71.3.9 QList< QuaZipFileInfo64 > QuaZipDir::entryInfoList64 (QDir::Filters *filters* = `QDir::NoFilter`, QDir::SortFlags *sort* = `QDir::NoSort`) const

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

The same as entryInfoList64(QStringList(), filters, sort).

Definition at line 427 of file quazipdir.cpp.

References entryInfoList64().

```
{
    return entryInfoList64(QStringList(), filters, sort);
}
```

Here is the call graph for this function:

12.71.3.10 QStringList QuaZipDir::entryList (const QStringList & *nameFilters*, QDir::Filters *filters* = `QDir::NoFilter`, QDir::SortFlags *sort* = `QDir::NoSort`) const

The same as entryInfoList(nameFilters, filters, sort), but only returns entry names.

Definition at line 433 of file quazipdir.cpp.

References d.

Referenced by count(), entryList(), exists(), and operator[]().

```
{
    QStringList result;
    if (d->entryInfoList(nameFilters, filters, sort, result))
        return result;
    else
        return QStringList();
}
```

Here is the caller graph for this function:

12.71.3.11 QStringList QuaZipDir::entryList (QDir::Filters *filters* = `QDir::NoFilter`, QDir::SortFlags *sort* = `QDir::NoSort`) const

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

The same as entryList(QStringList(), filters, sort).

Definition at line 443 of file quazipdir.cpp.

References entryList().

```
{
    return entryList(QStringList(), filters, sort);
}
```

Here is the call graph for this function:

12.71.3.12 bool QuaZipDir::exists (const QString & *fileName*) const

The ".." is considered to exist if the current directory is not root. The "." and "/" are considered to always exist. Paths starting with "/" are relative to the archive root, other paths are relative to the current dir.

Definition at line 449 of file quazipdir.cpp.

References QuaZip::convertCaseSensitivity(), d, entryList(), filePath(), and isRoot().

```
{
    if (filePath == "/" || filePath.isEmpty())
        return true;
    QString fileName = filePath;
    if (fileName.endsWith('/'))
        fileName.chop(1);
    if (fileName.contains('/')) {
        QFileInfo fileInfo(fileName);
#ifdef QUAZIP_QUAZIPDIR_DEBUG
        qDebug("QuaZipDir::exists(): fileName=%s, fileInfo.fileName()=%s, "
                "fileInfo.path()=%s", fileName.toUtf8().constData(),
                fileInfo.fileName().toUtf8().constData(),
                fileInfo.path().toUtf8().constData());
#endif
        QuaZipDir dir(*this);
        return dir.cd(fileInfo.path()) && dir.exists(fileInfo.fileName());
    } else {
        if (fileName == "..") {
            return !isRoot();
        } else if (fileName == ".") {
            return true;
        } else {
            QStringList entries = entryList(QDir::AllEntries, QDir::NoSort);
#ifdef QUAZIP_QUAZIPDIR_DEBUG
            qDebug("QuaZipDir::exists(): looking for %s",
                    fileName.toUtf8().constData());
            for (QStringList::const_iterator i = entries.constBegin();
                    i != entries.constEnd();
                    ++i) {
                qDebug("QuaZipDir::exists(): entry: %s",
                        i->toUtf8().constData());
            }
#endif
            Qt::CaseSensitivity cs = QuaZip::convertCaseSensitivity(
                    d->caseSensitivity);
            if (filePath.endsWith('/')) {
                return entries.contains(filePath, cs);
            } else {
                return entries.contains(fileName, cs)
                    || entries.contains(fileName + "/", cs);
            }
        }
    }
}
```

Here is the call graph for this function:

12.71.3.13 bool QuaZipDir::exists ( ) const

Definition at line 495 of file quazipdir.cpp.

References d, and QuaZipDir().

Referenced by cd().

```
496 {
497     return QuaZipDir(d->zip).exists(d->dir);
498 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.71.3.14 QString QuaZipDir::filePath (const QString & *fileName*) const

Doesn't check if the file actually exists.

Definition at line 500 of file quazipdir.cpp.

References d.

Referenced by exists().

```
501 {
502     return QDir(d->dir).filePath(fileName);
503 }
```

Here is the caller graph for this function:

12.71.3.15 QDir::Filters QuaZipDir::filter ( )

Definition at line 505 of file quazipdir.cpp.

References d.

```
506 {
507     return d->filter;
508 }
```

12.71.3.16 bool QuaZipDir::isRoot ( ) const

Not that the root path is the empty string, not '/'.

Definition at line 510 of file quazipdir.cpp.

References d.

Referenced by cd(), and exists().

```
511 {
512     return d->simplePath().isEmpty();
513 }
```

Here is the caller graph for this function:

12.71.3.17 QStringList QuaZipDir::nameFilters ( ) const

Definition at line 515 of file quazipdir.cpp.

References d.

Referenced by setNameFilters().

```
516 {
517     return d->nameFilters;
518 }
```

Here is the caller graph for this function:

12.71.3.18 bool QuaZipDir::operator!= (const QuaZipDir & *that*) [inline]

Returns

`true` if either this and *that* use different QuaZip instances or if they point to different directories.

Definition at line 75 of file quazipdir.h.

```
75 {return !operator==(that);}
```

12.71.3.19 QuaZipDir & QuaZipDir::operator= (const QuaZipDir & *that*)

Returns

`true` if both this and *that* use the same QuaZip instance and point to the same directory.

Definition at line 71 of file quazipdir.cpp.

References d.

```
72 {
73     this->d = that.d;
74     return *this;
75 }
```

12.71.3.20 bool QuaZipDir::operator== (const QuaZipDir & *that*)

Definition at line 66 of file quazipdir.cpp.

References d.

```
67 {
68     return d->zip == that.d->zip && d->dir == that.d->dir;
69 }
```

12.71.3.21 QString QuaZipDir::operator[] (int *pos*) const

Definition at line 77 of file quazipdir.cpp.

References entryList().

```
78 {
79     return entryList().at(pos);
80 }
```

Here is the call graph for this function:

12.71.3.22 QString QuaZipDir::path ( ) const

The path never starts with '/', and the root path is an empty string.

Definition at line 520 of file quazipdir.cpp.

References d.

Referenced by cd(), and setPath().

```
521 {
522     return d->dir;
523 }
```

Here is the caller graph for this function:

12.71.3.23 QString QuaZipDir::relativeFilePath (const QString & *fileName*) const

This function is mostly useless, provided only for the sake of completeness.

Parameters

fileName	The path to the file, should start with "/" if relative to the archive root.

Returns

Path relative to the current dir.

Definition at line 525 of file quazipdir.cpp.

References d.

```
526 {
527     return QDir("/" + d->dir).relativeFilePath(fileName);
528 }
```

12.71.3.24 void QuaZipDir::setCaseSensitivity (QuaZip::CaseSensitivity *caseSensitivity*)

Definition at line 530 of file quazipdir.cpp.

References caseSensitivity(), and d.

```
531 {
532     d->caseSensitivity = caseSensitivity;
533 }
```

Here is the call graph for this function:

12.71.3.25 void QuaZipDir::setFilter (QDir::Filters *filters*)

Definition at line 535 of file quazipdir.cpp.

References d.

```
536 {
537     d->filter = filters;
538 }
```

12.71.3.26 void QuaZipDir::setNameFilters (const QStringList & *nameFilters*)

Definition at line 540 of file quazipdir.cpp.

References d, and nameFilters().

```
541 {
542     d->nameFilters = nameFilters;
543 }
```

Here is the call graph for this function:

12.71.3.27 void QuaZipDir::setPath (const QString & *path*)

The difference from cd() is that this function never checks if the path actually exists and doesn't use relative paths, so it's possible to go to the root directory with setPath("").

Note that this function still chops the trailing and/or leading '/' and treats a single '/' as the root path (path() will still return an empty string).

Definition at line 545 of file quazipdir.cpp.

References d, and path().

```
546 {
547     QString newDir = path;
```

```
    if (newDir == "/") {
        d->dir = "";
    } else {
        if (newDir.endsWith('/'))
            newDir.chop(1);
        if (newDir.startsWith('/'))
            newDir = newDir.mid(1);
        d->dir = newDir;
    }
}
```

Here is the call graph for this function:

12.71.3.28 void QuaZipDir::setSorting (QDir::SortFlags *sort*)

Definition at line 559 of file quazipdir.cpp.

References d.

```
{
    d->sorting = sort;
}
```

12.71.3.29 QDir::SortFlags QuaZipDir::sorting ( ) const

Definition at line 564 of file quazipdir.cpp.

References d.

```
{
    return d->sorting;
}
```

12.71.4 Field Documentation

12.71.4.1 QSharedDataPointer<QuaZipDirPrivate> QuaZipDir::d [private]

Definition at line 56 of file quazipdir.h.

Referenced by caseSensitivity(), cd(), dirName(), entryInfoList(), entryInfoList64(), entryList(), exists(), filePath(), filter(), isRoot(), nameFilters(), operator=(), operator==(), path(), QuaZipDir(), relativeFilePath(), setCaseSensitivity(), setFilter(), setNameFilters(), setPath(), setSorting(), and sorting().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quazipdir.h
- src/ckb/quazip/quazipdir.cpp

12.72 QuaZipFile Class Reference

A file inside ZIP archive.

```
#include <quazip/quazipfile.h>
```

Inheritance diagram for QuaZipFile:

Collaboration diagram for QuaZipFile:

Public Member Functions

- QuaZipFile ()

  Constructs a QuaZipFile instance.
- QuaZipFile (QObject *parent)

  Constructs a QuaZipFile instance.
- QuaZipFile (const QString &zipName, QObject *parent=NULL)

  Constructs a QuaZipFile instance.
- QuaZipFile (const QString &zipName, const QString &fileName, QuaZip::CaseSensitivity cs=QuaZip::cs-Default, QObject *parent=NULL)

  Constructs a QuaZipFile instance.
- QuaZipFile (QuaZip *zip, QObject *parent=NULL)

  Constructs a QuaZipFile instance.
- virtual ~QuaZipFile ()

  Destroys a QuaZipFile instance.
- QString getZipName () const

  Returns the ZIP archive file name.
- QuaZip * getZip () const

  Returns a pointer to the associated QuaZip object.
- QString getFileName () const

  Returns file name.
- QuaZip::CaseSensitivity getCaseSensitivity () const

  Returns case sensitivity of the file name.
- QString getActualFileName () const

  Returns the actual file name in the archive.
- void setZipName (const QString &zipName)

  Sets the ZIP archive file name.
- bool isRaw () const

  Returns `true` if the file was opened in raw mode.
- void setZip (QuaZip *zip)

  Binds to the existing QuaZip instance.
- void setFileName (const QString &fileName, QuaZip::CaseSensitivity cs=QuaZip::csDefault)

  Sets the file name.
- virtual bool open (OpenMode mode)

  Opens a file for reading.
- bool open (OpenMode mode, const char *password)

  Opens a file for reading.
- bool open (OpenMode mode, int *method, int *level, bool raw, const char *password=NULL)

  Opens a file for reading.
- bool open (OpenMode mode, const QuaZipNewInfo &info, const char *password=NULL, quint32 crc=0, int method=Z_DEFLATED, int level=Z_DEFAULT_COMPRESSION, bool raw=false, int windowBits=-MAX_WB-ITS, int memLevel=MAX_MEM_LEVEL, int strategy=Z_DEFAULT_STRATEGY)

  Opens a file for writing.
- virtual bool isSequential () const

  Returns `true`, but beware!
- virtual qint64 pos () const

  Returns current position in the file.
- virtual bool atEnd () const

  Returns `true` if the end of file was reached.
- virtual qint64 size () const

  Returns file size.

- qint64 csize () const

  Returns compressed file size.
- qint64 usize () const

  Returns uncompressed file size.
- bool getFileInfo (QuaZipFileInfo *info)

  Gets information about current file.
- bool getFileInfo (QuaZipFileInfo64 *info)

  Gets information about current file with zip64 support.
- virtual void close ()

  Closes the file.
- int getZipError () const

  Returns the error code returned by the last ZIP/UNZIP API call.
- virtual qint64 bytesAvailable () const

  Returns the number of bytes available for reading.

Protected Member Functions

- qint64 readData (char *data, qint64 maxSize)

  Implementation of the QIODevice::readData().
- qint64 writeData (const char *data, qint64 maxSize)

  Implementation of the QIODevice::writeData().

Private Member Functions

- QuaZipFile (const QuaZipFile &that)
- QuaZipFile & operator= (const QuaZipFile &that)

Private Attributes

- QuaZipFilePrivate * p

Friends

- class QuaZipFilePrivate

12.72.1 Detailed Description

This is the most interesting class. Not only it provides C++ interface to the ZIP/UNZIP package, but also integrates it with Qt by subclassing QIODevice. This makes possible to access files inside ZIP archive using QTextStream or QDataStream, for example. Actually, this is the main purpose of the whole QuaZIP library.

You can either use existing QuaZip instance to create instance of this class or pass ZIP archive file name to this class, in which case it will create internal QuaZip object. See constructors' descriptions for details. Writing is only possible with the existing instance.

Note that due to the underlying library's limitation it is not possible to use multiple QuaZipFile instances to open several files in the same archive at the same time. If you need to write to multiple files in parallel, then you should write to temporary files first, then pack them all at once when you have finished writing. If you need to read multiple files inside the same archive in parallel, you should extract them all into a temporary directory first.

12.72.2 Sequential or random-access?

At the first thought, QuaZipFile has fixed size, the start and the end and should be therefore considered random-access device. But there is one major obstacle to making it random-access: ZIP/UNZIP API does not support seek() operation and the only way to implement it is through reopening the file and re-reading to the required position, but this is prohibitively slow.

Therefore, QuaZipFile is considered to be a sequential device. This has advantage of availability of the ungetChar() operation (QIODevice does not implement it properly for non-sequential devices unless they support seek()). Disadvantage is a somewhat strange behaviour of the size() and pos() functions. This should be kept in mind while using this class.

Definition at line 74 of file quazipfile.h.

12.72.3 Constructor & Destructor Documentation

12.72.3.1 QuaZipFile::QuaZipFile (const QuaZipFile & *that*) [private]

12.72.3.2 QuaZipFile::QuaZipFile ( )

You should use setZipName() and setFileName() or setZip() before trying to call open() on the constructed object.

Definition at line 108 of file quazipfile.cpp.

```
108                         :
109   p(new QuaZipFilePrivate(this))
110 {
111 }
```

12.72.3.3 QuaZipFile::QuaZipFile (QObject * *parent*)

parent argument specifies this object's parent object.

You should use setZipName() and setFileName() or setZip() before trying to call open() on the constructed object.

Definition at line 113 of file quazipfile.cpp.

```
113                                     :
114   QIODevice(parent),
115   p(new QuaZipFilePrivate(this))
116 {
117 }
```

12.72.3.4 QuaZipFile::QuaZipFile (const QString & *zipName*, QObject * *parent* = NULL)

parent argument specifies this object's parent object and *zipName* specifies ZIP archive file name.

You should use setFileName() before trying to call open() on the constructed object.

QuaZipFile constructed by this constructor can be used for read only access. Use QuaZipFile(QuaZip*,QObject*) for writing.

Definition at line 119 of file quazipfile.cpp.

```
119                                                         :
120   QIODevice(parent),
121   p(new QuaZipFilePrivate(this, zipName))
122 {
123 }
```

12.72.3.5 QuaZipFile::QuaZipFile (const QString & *zipName*, const QString & *fileName*, QuaZip::CaseSensitivity *cs* = QuaZip::csDefault, QObject * *parent* = NULL)

parent argument specifies this object's parent object, *zipName* specifies ZIP archive file name and *fileName* and *cs* specify a name of the file to open inside archive.

QuaZipFile constructed by this constructor can be used for read only access. Use QuaZipFile(QuaZip*,QObject*) for writing.

See Also

QuaZip::setCurrentFile()

Definition at line 125 of file quazipfile.cpp.

```
126                                                 :
127   QIODevice(parent),
128   p(new QuaZipFilePrivate(this, zipName, fileName, cs))
129 {
130 }
```

12.72.3.6 QuaZipFile::QuaZipFile (QuaZip * *zip*, QObject * *parent* = NULL)

parent argument specifies this object's parent object.

zip is the pointer to the existing QuaZip object. This QuaZipFile object then can be used to read current file in the *zip* or to write to the file inside it.

Warning

Using this constructor for reading current file can be tricky. Let's take the following example:

```
QuaZip zip("archive.zip");
zip.open(QuaZip::mdUnzip);
zip.setCurrentFile("file-in-archive");
QuaZipFile file(&zip);
file.open(QIODevice::ReadOnly);
// ok, now we can read from the file
file.read(somewhere, some);
zip.setCurrentFile("another-file-in-archive"); // oops...
QuaZipFile anotherFile(&zip);
anotherFile.open(QIODevice::ReadOnly);
anotherFile.read(somewhere, some); // this is still ok...
file.read(somewhere, some); // and this is NOT
```

So, what exactly happens here? When we change current file in the `zip` archive, `file` that references it becomes invalid (actually, as far as I understand ZIP/UNZIP sources, it becomes closed, but QuaZipFile has no means to detect it).

Summary: do not close `zip` object or change its current file as long as QuaZipFile is open. Even better - use another constructors which create internal QuaZip instances, one per object, and therefore do not cause unnecessary trouble. This constructor may be useful, though, if you already have a QuaZip instance and do not want to access several files at once. Good example:

```
QuaZip zip("archive.zip");
zip.open(QuaZip::mdUnzip);
// first, we need some information about archive itself
QByteArray comment=zip.getComment();
// and now we are going to access files inside it
QuaZipFile file(&zip);
for(bool more=zip.goToFirstFile(); more; more=zip.goToNextFile()) {
  file.open(QIODevice::ReadOnly);
  // do something cool with file here
  file.close(); // do not forget to close!
}
zip.close();
```

Definition at line 132 of file quazipfile.cpp.

```
                                                    :
  QIODevice(parent),
  p(new QuaZipFilePrivate(this, zip))
{
}
```

12.72.3.7 QuaZipFile::~QuaZipFile ( ) [virtual]

Closes file if open, destructs internal QuaZip object (if it exists and *is* internal, of course).

Definition at line 138 of file quazipfile.cpp.

References close(), and p.

```
{
  if (isOpen())
    close();
  delete p;
}
```

Here is the call graph for this function:

12.72.4 Member Function Documentation

12.72.4.1 bool QuaZipFile::atEnd ( ) const [virtual]

This function returns `false` in the case of error. This means that you called this function on either not open file, or a file in the not open archive or even on a QuaZipFile instance that does not even have QuaZip instance associated. Do not do that because there is no means to determine whether `false` is returned because of error or because end of file was reached. Well, on the other side you may interpret `false` return value as "there is no file open to check for end of file and there is no end of file therefore".

When writing, this function always returns `true` (because you are always writing to the end of file).

Error code returned by getZipError() is not affected by this function call.

Definition at line 361 of file quazipfile.cpp.

References QuaZip::getUnzFile(), p, unzeof(), and QuaZipFilePrivate::zip.

```
{
  if(p->zip==NULL) {
    qWarning("QuaZipFile::atEnd(): call setZipName() or setZip() first");
    return false;
  }
  if(!isOpen()) {
    qWarning("QuaZipFile::atEnd(): file is not open");
    return false;
  }
  if(openMode()&ReadOnly)
      // the same problem as with pos()
    return QIODevice::bytesAvailable() == 0
        && unzeof(p->zip->getUnzFile())==1;
```

```
  else
    return true;
}
```

Here is the call graph for this function:

12.72.4.2 qint64 QuaZipFile::bytesAvailable ( ) const [virtual]

Definition at line 499 of file quazipfile.cpp.

References pos(), and size().

```
{
    return size() - pos();
}
```

Here is the call graph for this function:

12.72.4.3 void QuaZipFile::close ( ) [virtual]

Call getZipError() to determine if the close was successful.

Definition at line 432 of file quazipfile.cpp.

References QuaZip::close(), QuaZipFilePrivate::crc, QuaZip::getUnzFile(), QuaZip::getZipError(), QuaZip::getZipFile(), QuaZipFilePrivate::internal, QuaZip::isOpen(), isRaw(), p, QuaZipFilePrivate::resetZipError(), QuaZipFilePrivate::setZipError(), QuaZipFilePrivate::uncompressedSize, UNZ_OK, unzCloseCurrentFile(), QuaZipFilePrivate::zip, zipCloseFileInZip(), zipCloseFileInZipRaw64(), and QuaZipFilePrivate::zipError.

Referenced by JlCompress::compressFile(), JlCompress::compressSubDir(), JlCompress::extractFile(), and ~QuaZipFile().

```
{
  p->resetZipError();
  if(p->zip==NULL||!p->zip->isOpen()) return;
```

```
  if(!isOpen()) {
    qWarning("QuaZipFile::close(): file isn't open");
    return;
  }
  if(openMode()&ReadOnly)
    p->setZipError(unzCloseCurrentFile(p->zip->getUnzFile()));
  else if(openMode()&WriteOnly)
    if(isRaw()) p->setZipError(zipCloseFileInZipRaw64(p->zip->getZipFile(), p->uncompressedSize, p->crc));
    else p->setZipError(zipCloseFileInZip(p->zip->getZipFile()));
  else {
    qWarning("Wrong open mode: %d", (int)openMode());
    return;
  }
  if(p->zipError==UNZ_OK) setOpenMode(QIODevice::NotOpen);
  else return;
  if(p->internal) {
    p->zip->close();
    p->setZipError(p->zip->getZipError());
  }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.72.4.4 qint64 QuaZipFile::csize ( ) const

Equivalent to calling getFileInfo() and then getting compressedSize field, but more convenient and faster.

File must be open for reading before calling this function.

Returns -1 on error, call getZipError() to get error code.

Definition at line 391 of file quazipfile.cpp.

References unz_file_info64_s::compressed_size, QuaZip::getMode(), QuaZip::getUnzFile(), QuaZip::mdUnzip, p, QuaZipFilePrivate::setZipError(), UNZ_OK, unzGetCurrentFileInfo64(), QuaZipFilePrivate::zip, and QuaZipFilePrivate::zipError.

Referenced by size().

```
{
  unz_file_info64 info_z;
  p->setZipError(UNZ_OK);
  if(p->zip==NULL||p->zip->getMode()!=QuaZip::mdUnzip) return -1;
  p->setZipError(unzGetCurrentFileInfo64(p->
  zip->getUnzFile(), &info_z, NULL, 0, NULL, 0, NULL, 0));
  if(p->zipError!=UNZ_OK)
    return -1;
  return info_z.compressed_size;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.72.4.5 QString QuaZipFile::getActualFileName ( ) const

This is *not* a ZIP archive file name, but a name of file inside archive. It is not necessary the same name that you have passed to the QuaZipFile(const QString&,const QString&,QuaZip::CaseSensitivity,QObject*), setFileName() or QuaZip::setCurrentFile() - this is the real file name inside archive, so it may differ in case if the file name search was case-insensitive.

Equivalent to calling getCurrentFileName() on the associated QuaZip object. Returns null string if there is no associated QuaZip object or if it does not have a current file yet. And this is the case if you called setFileName() but did not open the file yet. So this is perfectly fine:

```
QuaZipFile file("somezip.zip");
file.setFileName("somefile");
QString name=file.getName(); // name=="somefile"
QString actual=file.getActualFileName(); // actual is null string
file.open(QIODevice::ReadOnly);
QString actual=file.getActualFileName(); // actual can be "SoMeFiLe" on Windows
```

See Also

getZipName(), getFileName(), QuaZip::CaseSensitivity

Definition at line 155 of file quazipfile.cpp.

References QuaZip::getCurrentFileName(), QuaZip::getZipError(), p, QuaZipFilePrivate::setZipError(), UNZ_OK, and QuaZipFilePrivate::zip.

```
{
  p->setZipError(UNZ_OK);
  if (p->zip == NULL || (openMode() & WriteOnly))
    return QString();
  QString name=p->zip->getCurrentFileName();
  if(name.isNull())
    p->setZipError(p->zip->getZipError());
  return name;
}
```

Here is the call graph for this function:

12.72.4.6 QuaZip::CaseSensitivity QuaZipFile::getCaseSensitivity ( ) const

This function returns case sensitivity argument you passed to this object either by using QuaZipFile(const QString&,const QString&,QuaZip::CaseSensitivity,QObject*) or by calling setFileName().

Returns unpredictable value if getFileName() returns null string (this is the case when you did not used setFileName() or constructor above).

See Also

getFileName

Definition at line 484 of file quazipfile.cpp.

References QuaZipFilePrivate::caseSensitivity, and p.

```
{
  return p->caseSensitivity;
}
```

12.72.4.7 bool QuaZipFile::getFileInfo (QuaZipFileInfo * *info*)

This function does the same thing as calling QuaZip::getCurrentFileInfo() on the associated QuaZip object, but you can not call getCurrentFileInfo() if the associated QuaZip is internal (because you do not have access to it), while you still can call this function in that case.

File must be open for reading before calling this function.

Returns

`false` in the case of an error.

This function doesn't support zip64, but will still work fine on zip64 archives if file sizes are below 4 GB, otherwise the values will be set as if converted using QuaZipFileInfo64::toQuaZipFileInfo().

See Also

getFileInfo(QuaZipFileInfo64∗)

Definition at line 413 of file quazipfile.cpp.

References QuaZipFileInfo64::toQuaZipFileInfo().

```
414 {
415     QuaZipFileInfo64 info64;
416     if (getFileInfo(&info64)) {
417         info64.toQuaZipFileInfo(*info);
418         return true;
419     } else {
420         return false;
421     }
422 }
```

Here is the call graph for this function:

12.72.4.8 bool QuaZipFile::getFileInfo (QuaZipFileInfo64 ∗ *info*)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

See Also

getFileInfo(QuaZipFileInfo∗)

Definition at line 424 of file quazipfile.cpp.

References QuaZip::getCurrentFileInfo(), QuaZip::getMode(), QuaZip::getZipError(), QuaZip::mdUnzip, p, QuaZipFilePrivate::setZipError(), UNZ_OK, QuaZipFilePrivate::zip, and QuaZipFilePrivate::zipError.

```
425 {
426     if(p->zip==NULL||p->zip->getMode()!=QuaZip::mdUnzip) return false;
427     p->zip->getCurrentFileInfo(info);
428     p->setZipError(p->zip->getZipError());
429     return p->zipError==UNZ_OK;
430 }
```

Here is the call graph for this function:

12.72.4.9 QString QuaZipFile::getFileName ( ) const

This function returns file name you passed to this object either by using QuaZipFile(const QString&,const QString&,-QuaZip::CaseSensitivity,QObject∗) or by calling setFileName(). Real name of the file may differ in case if you used case-insensitivity.

Returns null string if there is no file name set yet. This is the case when this QuaZipFile operates on the existing QuaZip object (constructor QuaZipFile(QuaZip∗,QObject∗) or setZip() was used).

See Also

getActualFileName

Definition at line 479 of file quazipfile.cpp.

References QuaZipFilePrivate::fileName, and p.

```
{
  return p->fileName;
}
```

12.72.4.10 QuaZip ∗ QuaZipFile::getZip ( ) const

Returns NULL if there is no associated QuaZip or it is internal (so you will not mess with it).

Definition at line 150 of file quazipfile.cpp.

References QuaZipFilePrivate::internal, p, and QuaZipFilePrivate::zip.

```
{
    return p->internal ? NULL : p->zip;
}
```

12.72.4.11 int QuaZipFile::getZipError ( ) const

Definition at line 494 of file quazipfile.cpp.

References p, and QuaZipFilePrivate::zipError.

Referenced by JlCompress::compressFile(), and JlCompress::extractFile().

```
{
  return p->zipError;
}
```

Here is the caller graph for this function:

12.72.4.12 QString QuaZipFile::getZipName ( ) const

If this object was created by passing QuaZip pointer to the constructor, this function will return that QuaZip's file name (or null string if that object does not have file name yet).

Otherwise, returns associated ZIP archive file name or null string if there are no name set yet.

See Also

setZipName() getFileName()

Definition at line 145 of file quazipfile.cpp.

References QuaZip::getZipName(), p, and QuaZipFilePrivate::zip.

```
{
  return p->zip==NULL ? QString() : p->zip->getZipName();
}
```

Here is the call graph for this function:

12.72.4.13 bool QuaZipFile::isRaw ( ) const

If the file is not open, the returned value is undefined.

See Also

open(OpenMode,int*,int*,bool,const char*)

Definition at line 489 of file quazipfile.cpp.

References p, and QuaZipFilePrivate::raw.

Referenced by close().

```
490 {
491   return p->raw;
492 }
```

Here is the caller graph for this function:

12.72.4.14 bool QuaZipFile::isSequential ( ) const [virtual]

Definition at line 337 of file quazipfile.cpp.

```
338 {
339   return true;
340 }
```

12.72.4.15 bool QuaZipFile::open (OpenMode *mode*) [virtual]

Returns `true` on success, `false` otherwise. Call getZipError() to get error code.

Note

Since ZIP/UNZIP API provides buffered reading only, QuaZipFile does not support unbuffered reading. So do not pass QIODevice::Unbuffered flag in *mode*, or open will fail.

Definition at line 221 of file quazipfile.cpp.

Referenced by KbFirmware::_fileForBoard(), JICompress::compressFile(), JICompress::compressSubDir(), and JICompress::extractFile().

```
222 {
223   return open(mode, NULL);
224 }
```

Here is the caller graph for this function:

12.72.4.16 bool QuaZipFile::open (OpenMode *mode*, const char * *password*) [inline]

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Argument *password* specifies a password to decrypt the file. If it is NULL then this function behaves just like open(OpenMode).

Definition at line 298 of file quazipfile.h.

```
299     {return open(mode, NULL, NULL, false, password);}
```

12.72.4.17 bool QuaZipFile::open (OpenMode *mode*, int * *method*, int * *level*, bool *raw*, const char * *password* = NULL)

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts. Argument *password* specifies a password to decrypt the file.

An integers pointed by *method* and *level* will receive codes of the compression method and level used. See unzip.h.

If raw is `true` then no decompression is performed.

method should not be `NULL`. *level* can be `NULL` if you don't want to know the compression level.

Definition at line 226 of file quazipfile.cpp.

References QuaZipFilePrivate::caseSensitivity, QuaZip::close(), QuaZipFilePrivate::fileName, QuaZip::getMode(), QuaZip::getUnzFile(), QuaZip::getZipError(), QuaZip::hasCurrentFile(), QuaZipFilePrivate::internal, QuaZip::mdUnzip, QuaZip::open(), p, QuaZipFilePrivate::raw, QuaZipFilePrivate::resetZipError(), QuaZip::setCurrentFile(), QuaZipFilePrivate::setZipError(), UNZ_OK, unzOpenCurrentFile3(), QuaZipFilePrivate::zip, and QuaZipFilePrivate::zipError.

```
227 {
228   p->resetZipError();
229   if(isOpen()) {
230     qWarning("QuaZipFile::open(): already opened");
231     return false;
232   }
233   if(mode&Unbuffered) {
234     qWarning("QuaZipFile::open(): Unbuffered mode is not supported");
235     return false;
236   }
237   if((mode&ReadOnly)&&!(mode&WriteOnly)) {
238     if(p->internal) {
239       if(!p->zip->open(QuaZip::mdUnzip)) {
240         p->setZipError(p->zip->getZipError());
241         return false;
242       }
243       if(!p->zip->setCurrentFile(p->fileName, p->
      caseSensitivity)) {
244         p->setZipError(p->zip->getZipError());
245         p->zip->close();
246         return false;
247       }
248     } else {
249       if(p->zip==NULL) {
250         qWarning("QuaZipFile::open(): zip is NULL");
251         return false;
```

```
      }
      if(p->zip->getMode()!=QuaZip::mdUnzip) {
        qWarning("QuaZipFile::open(): file open mode %d incompatible with ZIP open mode %d",
            (int)mode, (int)p->zip->getMode());
        return false;
      }
      if(!p->zip->hasCurrentFile()) {
        qWarning("QuaZipFile::open(): zip does not have current file");
        return false;
      }
    }
    p->setZipError(unzOpenCurrentFile3(p->zip->
  getUnzFile(), method, level, (int)raw, password));
    if(p->zipError==UNZ_OK) {
      setOpenMode(mode);
      p->raw=raw;
      return true;
    } else
      return false;
  }
  qWarning("QuaZipFile::open(): open mode %d not supported by this function", (int)mode);
  return false;
}
```

Here is the call graph for this function:

12.72.4.18 bool QuaZipFile::open (OpenMode *mode*, const QuaZipNewInfo & *info*, const char * *password* = NULL, quint32 *crc* = 0, int *method* = Z_DEFLATED, int *level* = Z_DEFAULT_COMPRESSION, bool *raw* = false, int *windowBits* = -MAX_WBITS, int *memLevel* = MAX_MEM_LEVEL, int *strategy* = Z_DEFAULT_STRATEGY)

info argument specifies information about file. It should at least specify a correct file name. Also, it is a good idea to specify correct timestamp (by default, current time will be used). See QuaZipNewInfo.

The *password* argument specifies the password for crypting. Pass NULL if you don't need any crypting. The *crc* argument was supposed to be used for crypting too, but then it turned out that it's false information, so you need to set it to 0 unless you want to use the raw mode (see below).

Arguments *method* and *level* specify compression method and level. The only method supported is Z_DEFLATED, but you may also specify 0 for no compression. If all of the files in the archive use both method 0 and either level 0 is explicitly specified or data descriptor writing is disabled with QuaZip::setDataDescriptorWritingEnabled(), then the resulting archive is supposed to be compatible with the 1.0 ZIP format version, should you need that. Except for this, *level* has no other effects with method 0.

If *raw* is `true`, no compression is performed. In this case, *crc* and uncompressedSize field of the *info* are required.

Arguments *windowBits*, *memLevel*, *strategy* provide zlib algorithms tuning. See deflateInit2() in zlib.

Definition at line 275 of file quazipfile.cpp.

References QuaZipNewInfo::comment, QuaZipFilePrivate::crc, QuaZipNewInfo::dateTime, zip_fileinfo::dosDate, zip_fileinfo::external_fa, QuaZipNewInfo::externalAttr, QuaZipNewInfo::extraGlobal, QuaZipNewInfo::extraLocal, QuaZip::getCommentCodec(), QuaZip::getFileNameCodec(), QuaZip::getMode(), QuaZip::getZipFile(), QuaZipFilePrivate::internal, zip_fileinfo::internal_fa, QuaZipNewInfo::internalAttr, QuaZip::isDataDescriptorWritingEnabled(), QuaZip::isZip64Enabled(), QuaZip::mdAdd, QuaZip::mdAppend, QuaZip::mdCreate, QuaZipNewInfo::name, p, QuaZipFilePrivate::raw, QuaZipFilePrivate::resetZipError(), QuaZipFilePrivate::setZipError(), tm_zip_s::tm_hour, tm_zip_s::tm_mday, tm_zip_s::tm_min, tm_zip_s::tm_mon, tm_zip_s::tm_sec, tm_zip_s::tm_year, zip_fileinfo::tmz_date, QuaZipFilePrivate::uncompressedSize, QuaZipNewInfo::uncompressedSize, UNZ_OK, QuaZipFilePrivate::writePos, QuaZipFilePrivate::zip, ZIP_WRITE_DATA_DESCRIPTOR, zipClearFlags(), QuaZipFilePrivate::zipError, zipOpenNewFileInZip3_64(), and zipSetFlags().

```
{
  zip_fileinfo info_z;
  p->resetZipError();
  if(isOpen()) {
    qWarning("QuaZipFile::open(): already opened");
    return false;
  }
  if((mode&WriteOnly)&&!(mode&ReadOnly)) {
    if(p->internal) {
      qWarning("QuaZipFile::open(): write mode is incompatible with internal QuaZip approach");
      return false;
    }
    if(p->zip==NULL) {
      qWarning("QuaZipFile::open(): zip is NULL");
      return false;
    }
    if(p->zip->getMode()!=QuaZip::mdCreate&&p->zip->getMode()!=QuaZip::mdAppend&&p->zip->getMode()!=QuaZip::mdAdd) {
      qWarning("QuaZipFile::open(): file open mode %d incompatible with ZIP open mode %d",
          (int)mode, (int)p->zip->getMode());
      return false;
    }
    info_z.tmz_date.tm_year=info.dateTime.date().year();
    info_z.tmz_date.tm_mon=info.dateTime.date().month() - 1;
    info_z.tmz_date.tm_mday=info.dateTime.date().day();
    info_z.tmz_date.tm_hour=info.dateTime.time().hour();
    info_z.tmz_date.tm_min=info.dateTime.time().minute();
    info_z.tmz_date.tm_sec=info.dateTime.time().second();
    info_z.dosDate = 0;
    info_z.internal_fa=(uLong)info.internalAttr;
    info_z.external_fa=(uLong)info.externalAttr;
    if (p->zip->isDataDescriptorWritingEnabled())
        zipSetFlags(p->zip->getZipFile(), ZIP_WRITE_DATA_DESCRIPTOR);
    else
        zipClearFlags(p->zip->getZipFile(), ZIP_WRITE_DATA_DESCRIPTOR);
    p->setZipError(zipOpenNewFileInZip3_64(p->zip->getZipFile(),
            p->zip->getFileNameCodec()->fromUnicode(info.name).constData(), &info_z,
            info.extraLocal.constData(), info.extraLocal.length(),
            info.extraGlobal.constData(), info.extraGlobal.length(),
            p->zip->getCommentCodec()->fromUnicode(info.comment).constData(),
            method, level, (int)raw,
            windowBits, memLevel, strategy,
            password, (uLong)crc, p->zip->isZip64Enabled()));
    if(p->zipError==UNZ_OK) {
      p->writePos=0;
      setOpenMode(mode);
      p->raw=raw;
      if(raw) {
        p->crc=crc;
        p->uncompressedSize=info.uncompressedSize;
      }
      return true;
    } else
      return false;
  }
  qWarning("QuaZipFile::open(): open mode %d not supported by this function", (int)mode);
  return false;
}
```

Here is the call graph for this function:

12.72.4.19 QuaZipFile& QuaZipFile::operator= (const QuaZipFile & *that*) [private]

12.72.4.20 qint64 QuaZipFile::pos ( ) const [virtual]

Implementation of the QIODevice::pos(). When reading, this function is a wrapper to the ZIP/UNZIP unztell(), therefore it is unable to keep track of the ungetChar() calls (which is non-virtual and therefore is dangerous to reimplement). So if you are using ungetChar() feature of the QIODevice, this function reports incorrect value until you get back characters which you ungot.

When writing, pos() returns number of bytes already written (uncompressed unless you use raw mode).

Note

> Although QuaZipFile is a sequential device and therefore pos() should always return zero, it does not, because it would be misguiding. Keep this in mind.

This function returns -1 if the file or archive is not open.

Error code returned by getZipError() is not affected by this function call.

Definition at line 342 of file quazipfile.cpp.

References QuaZip::getUnzFile(), p, unztell(), QuaZipFilePrivate::writePos, and QuaZipFilePrivate::zip.

Referenced by bytesAvailable().

```
{
  if(p->zip==NULL) {
    qWarning("QuaZipFile::pos(): call setZipName() or setZip() first");
    return -1;
  }
  if(!isOpen()) {
    qWarning("QuaZipFile::pos(): file is not open");
    return -1;
  }
  if(openMode()&ReadOnly)
      // QIODevice::pos() is broken for sequential devices,
      // but thankfully bytesAvailable() returns the number of
      // bytes buffered, so we know how far ahead we are.
    return unztell(p->zip->getUnzFile()) - QIODevice::bytesAvailable();
  else
    return p->writePos;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.72.4.21 qint64 QuaZipFile::readData (char * *data*, qint64 *maxSize*) [protected]

Definition at line 457 of file quazipfile.cpp.

References QuaZip::getUnzFile(), p, QuaZipFilePrivate::setZipError(), UNZ_OK, unzReadCurrentFile(), and QuaZipFilePrivate::zip.

```
{
  p->setZipError(UNZ_OK);
  qint64 bytesRead=unzReadCurrentFile(p->zip->getUnzFile(), data, (unsigned
  )maxSize);
  if (bytesRead < 0) {
    p->setZipError((int) bytesRead);
    return -1;
  }
  return bytesRead;
}
```

Here is the call graph for this function:

12.72.4.22 void QuaZipFile::setFileName (const QString & *fileName*, QuaZip::CaseSensitivity *cs* = QuaZip::csDefault)

Will do nothing if at least one of the following conditions is met:

- ZIP name has not been set yet (getZipName() returns null string).
- This QuaZipFile is associated with external QuaZip. In this case you should call that QuaZip's setCurrentFile() function instead!
- File is already open so setting the name is meaningless.

See Also

QuaZip::setCurrentFile

Definition at line 191 of file quazipfile.cpp.

References QuaZipFilePrivate::caseSensitivity, QuaZipFilePrivate::fileName, QuaZipFilePrivate::internal, p, and QuaZipFilePrivate::zip.

```
{
  if(p->zip==NULL) {
    qWarning("QuaZipFile::setFileName(): call setZipName() first");
    return;
  }
  if(!p->internal) {
    qWarning("QuaZipFile::setFileName(): should not be used when not using internal QuaZip");
    return;
  }
  if(isOpen()) {
    qWarning("QuaZipFile::setFileName(): can not set file name for already opened file");
    return;
  }
  p->fileName=fileName;
  if (p->fileName.startsWith('/'))
      p->fileName = p->fileName.mid(1);
  p->caseSensitivity=cs;
}
```

12.72.4.23 void QuaZipFile::setZip (QuaZip * *zip*)

This function destroys internal QuaZip object, if any, and makes this QuaZipFile to use current file in the *zip* object for any further operations. See QuaZipFile(QuaZip*,QObject*) for the possible pitfalls.

Will do nothing if the file is currently open. You must close() it first.

Definition at line 178 of file quazipfile.cpp.

References QuaZipFilePrivate::fileName, QuaZipFilePrivate::internal, p, and QuaZipFilePrivate::zip.

```
{
  if(isOpen()) {
    qWarning("QuaZipFile::setZip(): file is already open - can not set ZIP");
    return;
  }
  if(p->zip!=NULL && p->internal)
    delete p->zip;
  p->zip=zip;
  p->fileName=QString();
  p->internal=false;
}
```

12.72.4.24 void QuaZipFile::setZipName (const QString & *zipName*)

Automatically creates internal QuaZip object and destroys previously created internal QuaZip object, if any.

Will do nothing if this file is already open. You must close() it first.

Definition at line 166 of file quazipfile.cpp.

References QuaZipFilePrivate::internal, p, and QuaZipFilePrivate::zip.

```
{
  if(isOpen()) {
    qWarning("QuaZipFile::setZipName(): file is already open - can not set ZIP name");
    return;
  }
  if(p->zip!=NULL && p->internal)
    delete p->zip;
  p->zip=new QuaZip(zipName);
  p->internal=true;
}
```

12.72.4.25 qint64 QuaZipFile::size ( ) const [virtual]

This function returns csize() if the file is open for reading in raw mode, usize() if it is open for reading in normal mode and pos() if it is open for writing.

Returns -1 on error, call getZipError() to get error code.

Note

> This function returns file size despite that QuaZipFile is considered to be sequential device, for which size() should return bytesAvailable() instead. But its name would be very misguiding otherwise, so just keep in mind this inconsistence.

Definition at line 379 of file quazipfile.cpp.

References csize(), p, QuaZipFilePrivate::raw, usize(), and QuaZipFilePrivate::writePos.

Referenced by bytesAvailable().

```
{
  if(!isOpen()) {
    qWarning("QuaZipFile::atEnd(): file is not open");
    return -1;
  }
  if(openMode()&ReadOnly)
    return p->raw?csize():usize();
  else
    return p->writePos;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.72.4.26 qint64 QuaZipFile::usize ( ) const

Equivalent to calling getFileInfo() and then getting uncompressedSize field, but more convenient and faster. See getFileInfo() for a warning.

File must be open for reading before calling this function.

Returns -1 on error, call getZipError() to get error code.

Definition at line 402 of file quazipfile.cpp.

References QuaZip::getMode(), QuaZip::getUnzFile(), QuaZip::mdUnzip, p, QuaZipFilePrivate::setZipError(), unz_file_info64_s::uncompressed_size, UNZ_OK, unzGetCurrentFileInfo64(), QuaZipFilePrivate::zip, and QuaZipFilePrivate::zipError.

Referenced by size().

```
{
  unz_file_info64 info_z;
  p->setZipError(UNZ_OK);
  if(p->zip==NULL||p->zip->getMode()!=QuaZip::mdUnzip) return -1;
  p->setZipError(unzGetCurrentFileInfo64(p->zip->getUnzFile(), &info_z, NULL, 0, NULL, 0, NULL, 0));
  if(p->zipError!=UNZ_OK)
    return -1;
  return info_z.uncompressed_size;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.72.4.27 qint64 QuaZipFile::writeData (const char * *data*, qint64 *maxSize*) [protected]

Definition at line 468 of file quazipfile.cpp.

References QuaZip::getZipFile(), p, QuaZipFilePrivate::setZipError(), QuaZipFilePrivate::writePos, QuaZipFilePrivate::zip, ZIP_OK, QuaZipFilePrivate::zipError, and zipWriteInFileInZip().

```
469 {
470   p->setZipError(ZIP_OK);
471   p->setZipError(zipWriteInFileInZip(p->zip->
      getZipFile(), data, (uint)maxSize));
472   if(p->zipError!=ZIP_OK) return -1;
473   else {
474     p->writePos+=maxSize;
475     return maxSize;
476   }
477 }
```

Here is the call graph for this function:

12.72.5 Friends And Related Function Documentation

12.72.5.1 friend class QuaZipFilePrivate [friend]

Definition at line 75 of file quazipfile.h.

12.72.6 Field Documentation

12.72.6.1 QuaZipFilePrivate* QuaZipFile::p [private]

Definition at line 78 of file quazipfile.h.

Referenced by atEnd(), close(), csize(), getActualFileName(), getCaseSensitivity(), getFileInfo(), getFileName(), getZip(), getZipError(), getZipName(), isRaw(), open(), pos(), readData(), setFileName(), setZip(), setZipName(), size(), usize(), writeData(), and ~QuaZipFile().

The documentation for this class was generated from the following files:

- src/ckb/quazip/quazipfile.h
- src/ckb/quazip/quazipfile.cpp

12.73 QuaZipFileInfo Struct Reference

Information about a file inside archive.

```
#include <src/ckb/quazip/quazipfileinfo.h>
```

Collaboration diagram for QuaZipFileInfo:

Public Member Functions

- QFile::Permissions getPermissions () const

  Get the file permissions.

Data Fields

- QString name

  File name.
- quint16 versionCreated

Version created by.

- quint16 versionNeeded

  Version needed to extract.

- quint16 flags

  General purpose flags.

- quint16 method

  Compression method.

- QDateTime dateTime

  Last modification date and time.

- quint32 crc

  CRC.

- quint32 compressedSize

  Compressed file size.

- quint32 uncompressedSize

  Uncompressed file size.

- quint16 diskNumberStart

  Disk number start.

- quint16 internalAttr

  Internal file attributes.

- quint32 externalAttr

  External file attributes.

- QString comment

  Comment.

- QByteArray extra

  Extra field.

12.73.1 Detailed Description

Deprecated Use QuaZipFileInfo64 instead. Not only it supports large files, but also more convenience methods as well.

Call QuaZip::getCurrentFileInfo() or QuaZipFile::getFileInfo() to fill this structure.

Definition at line 41 of file quazipfileinfo.h.

12.73.2 Member Function Documentation

12.73.2.1 QFile::Permissions QuaZipFileInfo::getPermissions ( ) const

Returns the high 16 bits of external attributes converted to QFile::Permissions.

Definition at line 52 of file quazipfileinfo.cpp.

References externalAttr, and permissionsFromExternalAttr().

```
53 {
54     return permissionsFromExternalAttr(externalAttr);
55 }
```

Here is the call graph for this function:

12.73.3 Field Documentation

12.73.3.1 QString QuaZipFileInfo::comment

Definition at line 67 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.2 quint32 QuaZipFileInfo::compressedSize

Definition at line 57 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.3 quint32 QuaZipFileInfo::crc

Definition at line 55 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.4 QDateTime QuaZipFileInfo::dateTime

Definition at line 53 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.5 quint16 QuaZipFileInfo::diskNumberStart

Definition at line 61 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.6 quint32 QuaZipFileInfo::externalAttr

Definition at line 65 of file quazipfileinfo.h.

Referenced by getPermissions(), and QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.7 QByteArray QuaZipFileInfo::extra

Definition at line 69 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.8 quint16 QuaZipFileInfo::flags

Definition at line 49 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.9 quint16 QuaZipFileInfo::internalAttr

Definition at line 63 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.10 quint16 QuaZipFileInfo::method

Definition at line 51 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.11 QString QuaZipFileInfo::name

Definition at line 43 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.12 quint32 QuaZipFileInfo::uncompressedSize

Definition at line 59 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.13 quint16 QuaZipFileInfo::versionCreated

Definition at line 45 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

12.73.3.14 quint16 QuaZipFileInfo::versionNeeded

Definition at line 47 of file quazipfileinfo.h.

Referenced by QuaZipFileInfo64::toQuaZipFileInfo().

The documentation for this struct was generated from the following files:

- src/ckb/quazip/quazipfileinfo.h
- src/ckb/quazip/quazipfileinfo.cpp

12.74 QuaZipFileInfo64 Struct Reference

Information about a file inside archive (with zip64 support).

```
#include <src/ckb/quazip/quazipfileinfo.h>
```

Collaboration diagram for QuaZipFileInfo64:

Public Member Functions

- QFile::Permissions getPermissions () const

  Get the file permissions.
- bool toQuaZipFileInfo (QuaZipFileInfo &info) const

  Converts to QuaZipFileInfo.
- QDateTime getNTFSmTime (int ∗fineTicks=NULL) const

  Returns the NTFS modification time.
- QDateTime getNTFSaTime (int ∗fineTicks=NULL) const

  Returns the NTFS access time.
- QDateTime getNTFScTime (int ∗fineTicks=NULL) const

  Returns the NTFS creation time.
- bool isEncrypted () const

  Checks whether the file is encrypted.

Data Fields

- QString name

  File name.
- quint16 versionCreated

  Version created by.
- quint16 versionNeeded

  Version needed to extract.
- quint16 flags

  General purpose flags.
- quint16 method

  Compression method.
- QDateTime dateTime

  Last modification date and time.
- quint32 crc

  CRC.

- quint64 compressedSize

  Compressed file size.
- quint64 uncompressedSize

  Uncompressed file size.
- quint16 diskNumberStart

  Disk number start.
- quint16 internalAttr

  Internal file attributes.
- quint32 externalAttr

  External file attributes.
- QString comment

  Comment.
- QByteArray extra

  Extra field.

12.74.1 Detailed Description

Call QuaZip::getCurrentFileInfo() or QuaZipFile::getFileInfo() to fill this structure.

Definition at line 81 of file quazipfileinfo.h.

12.74.2 Member Function Documentation

12.74.2.1 QDateTime QuaZipFileInfo64::getNTFSaTime (int * *fineTicks* = NULL) const

The getNTFS*Time() functions only work if there is an NTFS extra field present. Otherwise, they all return invalid null timestamps.

Parameters

fineTicks	If not NULL, the fractional part of milliseconds returned there, measured in 100-nanosecond ticks. Will be set to zero if there is no NTFS extra field.

See Also

dateTime
getNTFSmTime()
getNTFScTime()

Returns

The NTFS access time, UTC

Definition at line 168 of file quazipfileinfo.cpp.

References extra, and getNTFSTime().

```
{
    return getNTFSTime(extra, 8, fineTicks);
}
```

Here is the call graph for this function:

12.74.2.2 QDateTime QuaZipFileInfo64::getNTFScTime (int * *fineTicks* = NULL) const

The getNTFS*Time() functions only work if there is an NTFS extra field present. Otherwise, they all return invalid null timestamps.

Parameters

fineTicks	If not NULL, the fractional part of milliseconds returned there, measured in 100-nanosecond ticks. Will be set to zero if there is no NTFS extra field.

See Also

dateTime
getNTFSmTime()
getNTFSaTime()

Returns

The NTFS creation time, UTC

Definition at line 173 of file quazipfileinfo.cpp.

References extra, and getNTFSTime().

```
174 {
175     return getNTFSTime(extra, 16, fineTicks);
176 }
```

Here is the call graph for this function:

12.74.2.3 QDateTime QuaZipFileInfo64::getNTFSmTime (int * *fineTicks* = NULL) const

The getNTFS*Time() functions only work if there is an NTFS extra field present. Otherwise, they all return invalid null timestamps.

Parameters

fineTicks	If not NULL, the fractional part of milliseconds returned there, measured in 100-nanosecond ticks. Will be set to zero if there is no NTFS extra field.

See Also

dateTime
getNTFSaTime()
getNTFScTime()

Returns

The NTFS modification time, UTC

Definition at line 163 of file quazipfileinfo.cpp.

References extra, and getNTFSTime().

```
164 {
165     return getNTFSTime(extra, 0, fineTicks);
166 }
```

Here is the call graph for this function:

12.74.2.4 QFile::Permissions QuaZipFileInfo64::getPermissions ( ) const

Returns the high 16 bits of external attributes converted to QFile::Permissions.

Definition at line 57 of file quazipfileinfo.cpp.

References externalAttr, and permissionsFromExternalAttr().

Referenced by JlCompress::extractFile().

```
58 {
59     return permissionsFromExternalAttr(externalAttr);
60 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.74.2.5 bool QuaZipFileInfo64::isEncrypted ( ) const [inline]

Definition at line 175 of file quazipfileinfo.h.

```
175 {return (flags & 1) != 0;}
```

12.74.2.6 bool QuaZipFileInfo64::toQuaZipFileInfo (QuaZipFileInfo & *info*) const

If any of the fields are greater than 0xFFFFFFFFu, they are set to 0xFFFFFFFFu exactly, not just truncated. This function should be mainly used for compatibility with the old code expecting QuaZipFileInfo, in the cases when it's impossible or otherwise unadvisable (due to ABI compatibility reasons, for example) to modify that old code to use QuaZipFileInfo64.

Returns

`true` if all fields converted correctly, `false` if an overflow occured.

Definition at line 62 of file quazipfileinfo.cpp.

References QuaZipFileInfo::comment, comment, QuaZipFileInfo::compressedSize, compressedSize, QuaZipFileInfo::crc, crc, QuaZipFileInfo::dateTime, dateTime, QuaZipFileInfo::diskNumberStart, diskNumberStart, QuaZipFileInfo::externalAttr, externalAttr, QuaZipFileInfo::extra, extra, QuaZipFileInfo::flags, flags, QuaZipFileInfo::internalAttr, internalAttr, QuaZipFileInfo::method, method, QuaZipFileInfo::name, name, QuaZipFileInfo::uncompressedSize, uncompressedSize, QuaZipFileInfo::versionCreated, versionCreated, QuaZipFileInfo::versionNeeded, and versionNeeded.

Referenced by QuaZip::getCurrentFileInfo(), and QuaZipFile::getFileInfo().

```
63 {
64     bool noOverflow = true;
65     info.name = name;
66     info.versionCreated = versionCreated;
67     info.versionNeeded = versionNeeded;
68     info.flags = flags;
69     info.method = method;
70     info.dateTime = dateTime;
71     info.crc = crc;
72     if (compressedSize > 0xFFFFFFFFu) {
73         info.compressedSize = 0xFFFFFFFFu;
74         noOverflow = false;
75     } else {
76         info.compressedSize = compressedSize;
77     }
78     if (uncompressedSize > 0xFFFFFFFFu) {
79         info.uncompressedSize = 0xFFFFFFFFu;
80         noOverflow = false;
81     } else {
82         info.uncompressedSize = uncompressedSize;
83     }
84     info.diskNumberStart = diskNumberStart;
85     info.internalAttr = internalAttr;
```

```
    info.externalAttr = externalAttr;
    info.comment = comment;
    info.extra = extra;
    return noOverflow;
}
```

Here is the caller graph for this function:

12.74.3 Field Documentation

12.74.3.1 QString QuaZipFileInfo64::comment

Definition at line 114 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), and toQuaZipFileInfo().

12.74.3.2 quint64 QuaZipFileInfo64::compressedSize

Definition at line 104 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.3 quint32 QuaZipFileInfo64::crc

Definition at line 102 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.4 QDateTime QuaZipFileInfo64::dateTime

This is the time stored in the standard ZIP header. This format only allows to store time with 2-second precision, so the seconds will always be even and the milliseconds will always be zero. If you need more precise date and time, you can try to call the getNTFSmTime() function or its siblings, provided that the archive itself contains these NTFS times.

Definition at line 100 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), and toQuaZipFileInfo().

12.74.3.5 quint16 QuaZipFileInfo64::diskNumberStart

Definition at line 108 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.6 quint32 QuaZipFileInfo64::externalAttr

Definition at line 112 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), getPermissions(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.7 QByteArray QuaZipFileInfo64::extra

Definition at line 116 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), getNTFSaTime(), getNTFScTime(), getNTFSmTime(), and toQuaZipFileInfo().

12.74.3.8 quint16 QuaZipFileInfo64::flags

Definition at line 89 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.9 quint16 QuaZipFileInfo64::internalAttr

Definition at line 110 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.10 quint16 QuaZipFileInfo64::method

Definition at line 91 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.11 QString QuaZipFileInfo64::name

Definition at line 83 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), JlCompress::getFileList(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.12 quint64 QuaZipFileInfo64::uncompressedSize

Definition at line 106 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.13 quint16 QuaZipFileInfo64::versionCreated

Definition at line 85 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

12.74.3.14 quint16 QuaZipFileInfo64::versionNeeded

Definition at line 87 of file quazipfileinfo.h.

Referenced by QuaZip::getCurrentFileInfo(), QuaZipDir_getFileInfo(), and toQuaZipFileInfo().

The documentation for this struct was generated from the following files:

- src/ckb/quazip/quazipfileinfo.h
- src/ckb/quazip/quazipfileinfo.cpp

12.75 QuaZipFilePrivate Class Reference

The implementation class for QuaZip.

Collaboration diagram for QuaZipFilePrivate:

Private Member Functions

- void resetZipError () const

  Resets zipError.
- void setZipError (int zipError) const

  Sets the zip error.
- QuaZipFilePrivate (QuaZipFile *q)

  The constructor for the corresponding QuaZipFile constructor.
- QuaZipFilePrivate (QuaZipFile *q, const QString &zipName)

  The constructor for the corresponding QuaZipFile constructor.
- QuaZipFilePrivate (QuaZipFile *q, const QString &zipName, const QString &fileName, QuaZip::CaseSensitivity cs)

  The constructor for the corresponding QuaZipFile constructor.
- QuaZipFilePrivate (QuaZipFile *q, QuaZip *zip)

  The constructor for the QuaZipFile constructor accepting a file name.
- ~QuaZipFilePrivate ()

  The destructor.

Private Attributes

- QuaZipFile * q

  The pointer to the associated QuaZipFile instance.
- QuaZip * zip

  The QuaZip object to work with.
- QString fileName

  The file name.

- QuaZip::CaseSensitivity caseSensitivity

  Case sensitivity mode.
- bool raw

  Whether this file is opened in the raw mode.
- qint64 writePos

  Write position to keep track of.
- quint64 uncompressedSize

  Uncompressed size to write along with a raw file.
- quint32 crc

  CRC to write along with a raw file.
- bool internal

  Whether zip points to an internal QuaZip instance.
- int zipError

  The last error.

Friends

- class QuaZipFile

12.75.1 Detailed Description

This class contains all the private stuff for the QuaZipFile class, thus allowing to preserve binary compatibility between releases, the technique known as the Pimpl (private implementation) idiom.

Definition at line 37 of file quazipfile.cpp.

12.75.2 Constructor & Destructor Documentation

12.75.2.1 QuaZipFilePrivate::QuaZipFilePrivate (QuaZipFile * *q*) [inline],[private]

Definition at line 78 of file quazipfile.cpp.

```
78                                          :
79        q(q), zip(NULL), internal(true), zipError(UNZ_OK) {}
```

12.75.2.2 QuaZipFilePrivate::QuaZipFilePrivate (QuaZipFile * *q*, const QString & *zipName*) [inline],[private]

Definition at line 81 of file quazipfile.cpp.

```
81                                                                  :
82        q(q), internal(true), zipError(UNZ_OK)
83        {
84          zip=new QuaZip(zipName);
85        }
```

12.75.2.3 QuaZipFilePrivate::QuaZipFilePrivate (QuaZipFile * *q*, const QString & *zipName*, const QString & *fileName*, QuaZip::CaseSensitivity *cs*) [inline],[private]

Definition at line 87 of file quazipfile.cpp.

```
                                :
    q(q), internal(true), zipError(UNZ_OK)
    {
      zip=new QuaZip(zipName);
      this->fileName=fileName;
      if (this->fileName.startsWith('/'))
          this->fileName = this->fileName.mid(1);
      this->caseSensitivity=cs;
    }
```

12.75.2.4 QuaZipFilePrivate::QuaZipFilePrivate (QuaZipFile * *q*, QuaZip * *zip*) [inline],[private]

Definition at line 98 of file quazipfile.cpp.

```
                                                    :
    q(q), zip(zip), internal(false), zipError(UNZ_OK) {}
```

12.75.2.5 QuaZipFilePrivate::~QuaZipFilePrivate ( ) [inline],[private]

Definition at line 101 of file quazipfile.cpp.

```
  {
    if (internal)
      delete zip;
  }
```

12.75.3 Member Function Documentation

12.75.3.1 void QuaZipFilePrivate::resetZipError ( ) const [inline],[private]

Definition at line 69 of file quazipfile.cpp.

References UNZ_OK.

Referenced by QuaZipFile::close(), and QuaZipFile::open().

```
{setZipError(UNZ_OK);}
```

Here is the caller graph for this function:

12.75.3.2 void QuaZipFilePrivate::setZipError (int *zipError*) const [private]

This function is marked as const although it changes one field. This allows to call it from const functions that don't change anything by themselves.

Definition at line 211 of file quazipfile.cpp.

References q, UNZ_OK, and zipError.

Referenced by QuaZipFile::close(), QuaZipFile::csize(), QuaZipFile::getActualFileName(), QuaZipFile::getFileInfo(), QuaZipFile::open(), QuaZipFile::readData(), QuaZipFile::usize(), and QuaZipFile::writeData().

```
{
  QuaZipFilePrivate *fakeThis = const_cast<QuaZipFilePrivate*>(this); //
   non-const
  fakeThis->zipError=zipError;
  if(zipError==UNZ_OK)
    q->setErrorString(QString());
  else
    q->setErrorString(QuaZipFile::tr("ZIP/UNZIP API error %1").arg(zipError));
}
```

Here is the caller graph for this function:

12.75.4 Friends And Related Function Documentation

12.75.4.1 friend class QuaZipFile [friend]

Definition at line 38 of file quazipfile.cpp.

12.75.5 Field Documentation

12.75.5.1 QuaZip::CaseSensitivity QuaZipFilePrivate::caseSensitivity [private]

Definition at line 47 of file quazipfile.cpp.

Referenced by QuaZipFile::getCaseSensitivity(), QuaZipFile::open(), and QuaZipFile::setFileName().

12.75.5.2 quint32 QuaZipFilePrivate::crc [private]

Definition at line 59 of file quazipfile.cpp.

Referenced by QuaZipFile::close(), and QuaZipFile::open().

12.75.5.3 QString QuaZipFilePrivate::fileName [private]

Definition at line 45 of file quazipfile.cpp.

Referenced by QuaZipFile::getFileName(), QuaZipFile::open(), QuaZipFile::setFileName(), and QuaZipFile::setZip().

12.75.5.4 bool QuaZipFilePrivate::internal [private]

This is true if the archive was opened by name, rather than by supplying an existing QuaZip instance.

Definition at line 65 of file quazipfile.cpp.

Referenced by QuaZipFile::close(), QuaZipFile::getZip(), QuaZipFile::open(), QuaZipFile::setFileName(), QuaZipFile::setZip(), and QuaZipFile::setZipName().

12.75.5.5 QuaZipFile* QuaZipFilePrivate::q [private]

Definition at line 41 of file quazipfile.cpp.

Referenced by setZipError().

12.75.5.6 bool QuaZipFilePrivate::raw [private]

Definition at line 49 of file quazipfile.cpp.

Referenced by QuaZipFile::isRaw(), QuaZipFile::open(), and QuaZipFile::size().

12.75.5.7 quint64 QuaZipFilePrivate::uncompressedSize [private]

Definition at line 57 of file quazipfile.cpp.

Referenced by QuaZipFile::close(), and QuaZipFile::open().

12.75.5.8 qint64 QuaZipFilePrivate::writePos [private]

QIODevice::pos() is broken for non-seekable devices, so we need our own position.

Definition at line 55 of file quazipfile.cpp.

Referenced by QuaZipFile::open(), QuaZipFile::pos(), QuaZipFile::size(), and QuaZipFile::writeData().

12.75.5.9 QuaZip* QuaZipFilePrivate::zip [private]

Definition at line 43 of file quazipfile.cpp.

Referenced by QuaZipFile::atEnd(), QuaZipFile::close(), QuaZipFile::csize(), QuaZipFile::getActualFileName(), QuaZipFile::getFileInfo(), QuaZipFile::getZip(), QuaZipFile::getZipName(), QuaZipFile::open(), QuaZipFile::pos(), QuaZipFile::readData(), QuaZipFile::setFileName(), QuaZipFile::setZip(), QuaZipFile::setZipName(), QuaZipFile::usize(), and QuaZipFile::writeData().

12.75.5.10 int QuaZipFilePrivate::zipError [private]

Definition at line 67 of file quazipfile.cpp.

Referenced by QuaZipFile::close(), QuaZipFile::csize(), QuaZipFile::getFileInfo(), QuaZipFile::getZipError(), QuaZipFile::open(), setZipError(), QuaZipFile::usize(), and QuaZipFile::writeData().

The documentation for this class was generated from the following file:

- src/ckb/quazip/quazipfile.cpp

12.76 QuaZipNewInfo Struct Reference

Information about a file to be created.

`#include <src/ckb/quazip/quazipnewinfo.h>`

Collaboration diagram for QuaZipNewInfo:

Public Member Functions

- QuaZipNewInfo (const QString &name)

  Constructs QuaZipNewInfo instance.
- QuaZipNewInfo (const QString &name, const QString &file)

  Constructs QuaZipNewInfo instance.
- QuaZipNewInfo (const QuaZipFileInfo &existing)

  Initializes the new instance from existing file info.
- QuaZipNewInfo (const QuaZipFileInfo64 &existing)

  Initializes the new instance from existing file info.
- void setFileDateTime (const QString &file)

  Sets the file timestamp from the existing file.
- void setFilePermissions (const QString &file)

  Sets the file permissions from the existing file.
- void setPermissions (QFile::Permissions permissions)

  Sets the file permissions.
- void setFileNTFSTimes (const QString &fileName)

  Sets the NTFS times from an existing file.
- void setFileNTFSmTime (const QDateTime &mTime, int fineTicks=0)

  Sets the NTFS modification time.
- void setFileNTFSaTime (const QDateTime &aTime, int fineTicks=0)

  Sets the NTFS access time.
- void setFileNTFScTime (const QDateTime &cTime, int fineTicks=0)

  Sets the NTFS creation time.

Data Fields

- QString name

  File name.
- QDateTime dateTime

  File timestamp.
- quint16 internalAttr

  File internal attributes.
- quint32 externalAttr

  File external attributes.
- QString comment

  File comment.
- QByteArray extraLocal

  File local extra field.
- QByteArray extraGlobal

  File global extra field.
- ulong uncompressedSize

  Uncompressed file size.

12.76.1 Detailed Description

This structure holds information about a file to be created inside ZIP archive. At least name should be set to something correct before passing this structure to QuaZipFile::open(OpenMode,const QuaZipNewInfo&,int,int,bool).

Zip64 support of this structure is slightly limited: in the raw mode (when a pre-compressed file is written into a ZIP file as-is), it is necessary to specify the uncompressed file size and the appropriate field is 32 bit. Since the raw mode is used extremely rare, there is no real need to have a separate QuaZipNewInfo64 structure like QuaZipFileInfo64. It may be added in the future though, if there is a demand for the raw mode with zip64 archives.

Definition at line 50 of file quazipnewinfo.h.

12.76.2 Constructor & Destructor Documentation

12.76.2.1 QuaZipNewInfo::QuaZipNewInfo (const QString & *name*)

Initializes name with *name*, dateTime with current date and time. Attributes are initialized with zeros, comment and extra field with null values.

Definition at line 79 of file quazipnewinfo.cpp.

```
79                                                  :
80   name(name), dateTime(QDateTime::currentDateTime()),
      internalAttr(0), externalAttr(0),
81   uncompressedSize(0)
82 {
83 }
```

12.76.2.2 QuaZipNewInfo::QuaZipNewInfo (const QString & *name*, const QString & *file*)

Initializes name with *name*. Timestamp and permissions are taken from the specified file. If the *file* does not exists or its timestamp is inaccessible (e. g. you do not have read permission for the directory file in), uses current time and zero permissions. Other attributes are initialized with zeros, comment and extra field with null values.

See Also

setFileDateTime()

Definition at line 85 of file quazipnewinfo.cpp.

References dateTime, and QuaZipNewInfo_setPermissions().

```
85                                                                  :
86   name(name), internalAttr(0), externalAttr(0),
      uncompressedSize(0)
87 {
88   QFileInfo info(file);
89   QDateTime lm = info.lastModified();
90   if (!info.exists()) {
91     dateTime = QDateTime::currentDateTime();
92   } else {
93     dateTime = lm;
94     QuaZipNewInfo_setPermissions(this, info.permissions(), info.isDir());
95   }
96 }
```

Here is the call graph for this function:

12.76.2.3 QuaZipNewInfo::QuaZipNewInfo (const QuaZipFileInfo & *existing*)

Mainly used when copying files between archives.

Both extra fields are initialized to existing.extra. QuaZipNewInfo

Parameters

existing	

Definition at line 69 of file quazipnewinfo.cpp.

References QuaZipNewInfo_init().

```
70 {
71     QuaZipNewInfo_init(*this, existing);
72 }
```

Here is the call graph for this function:

12.76.2.4 QuaZipNewInfo::QuaZipNewInfo (const QuaZipFileInfo64 & *existing*)

Mainly used when copying files between archives.

Both extra fields are initialized to existing.extra. QuaZipNewInfo

Parameters

existing	

Definition at line 74 of file quazipnewinfo.cpp.

References QuaZipNewInfo_init().

```
75 {
76     QuaZipNewInfo_init(*this, existing);
77 }
```

Here is the call graph for this function:

12.76.3 Member Function Documentation

12.76.3.1 void QuaZipNewInfo::setFileDateTime (const QString & *file*)

Use this function to set the file timestamp from the existing file. Use it like this:

```
QuaZipFile zipFile(&zip);
QFile file("file-to-add");
file.open(QIODevice::ReadOnly);
QuaZipNewInfo info("file-name-in-archive");
info.setFileDateTime("file-to-add"); // take the timestamp from file
zipFile.open(QIODevice::WriteOnly, info);
```

This function does not change dateTime if some error occured (e. g. file is inaccessible).

Definition at line 98 of file quazipnewinfo.cpp.

References dateTime.

```
99 {
100   QFileInfo info(file);
101   QDateTime lm = info.lastModified();
102   if (info.exists())
103     dateTime = lm;
104 }
```

12.76.3.2 void QuaZipNewInfo::setFileNTFSaTime (const QDateTime & *aTime*, int *fineTicks* = 0)

The time is written into the NTFS record in both the local and the global extra fields, updating the existing record if there is one, or creating a new one and appending it to the end of each extra field. When updating an existing record, all other fields are left intact.

Parameters

aTime	The new access time.
fineTicks	The fractional part of milliseconds, in 100-nanosecond ticks (i. e. 9999 ticks = 999.9 microsecond). Values greater than 9999 will add milliseconds or even seconds, but this can be confusing and therefore is discouraged.

Definition at line 267 of file quazipnewinfo.cpp.

References extraGlobal, extraLocal, and setNTFSTime().

Referenced by setFileNTFSTimes().

```
268 {
269     setNTFSTime(extraLocal, aTime, 8, fineTicks);
270     setNTFSTime(extraGlobal, aTime, 8, fineTicks);
271 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.76.3.3 void QuaZipNewInfo::setFileNTFScTime (const QDateTime & *cTime*, int *fineTicks* = 0)

The time is written into the NTFS record in both the local and the global extra fields, updating the existing record if there is one, or creating a new one and appending it to the end of each extra field. When updating an existing record, all other fields are left intact.

Parameters

cTime	The new creation time.
fineTicks	The fractional part of milliseconds, in 100-nanosecond ticks (i. e. 9999 ticks = 999.9 microsecond). Values greater than 9999 will add milliseconds or even seconds, but this can be confusing and therefore is discouraged.

Definition at line 273 of file quazipnewinfo.cpp.

References extraGlobal, extraLocal, and setNTFSTime().

Referenced by setFileNTFSTimes().

```
274 {
275     setNTFSTime(extraLocal, cTime, 16, fineTicks);
276     setNTFSTime(extraGlobal, cTime, 16, fineTicks);
277 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.76.3.4 void QuaZipNewInfo::setFileNTFSmTime (const QDateTime & *mTime*, int *fineTicks* = 0)

The time is written into the NTFS record in both the local and the global extra fields, updating the existing record if there is one, or creating a new one and appending it to the end of each extra field. When updating an existing record, all other fields are left intact.

Parameters

mTime	The new modification time.
fineTicks	The fractional part of milliseconds, in 100-nanosecond ticks (i. e. 9999 ticks = 999.9 microsecond). Values greater than 9999 will add milliseconds or even seconds, but this can be confusing and therefore is discouraged.

Definition at line 261 of file quazipnewinfo.cpp.

References extraGlobal, extraLocal, and setNTFSTime().

Referenced by setFileNTFSTimes().

```
{
    setNTFSTime(extraLocal, mTime, 0, fineTicks);
    setNTFSTime(extraGlobal, mTime, 0, fineTicks);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.76.3.5 void QuaZipNewInfo::setFileNTFSTimes (const QString & *fileName*)

If the file doesn't exist, a warning is printed to the stderr and nothing is done. Otherwise, all three times, as reported by QFileInfo::lastModified(), QFileInfo::lastRead() and QFileInfo::created(), are written to the NTFS extra field record.

The NTFS record is written to both the local and the global extra fields, updating the existing record if there is one, or creating a new one and appending it to the end of each extra field.

The microseconds will be zero, as they aren't reported by QFileInfo.

Parameters

fileName	

Definition at line 118 of file quazipnewinfo.cpp.

References setFileNTFSaTime(), setFileNTFScTime(), and setFileNTFSmTime().

```
119 {
120     QFileInfo fi(fileName);
121     if (!fi.exists()) {
122         qWarning("QuaZipNewInfo::setFileNTFSTimes(): '%s' doesn't exist",
123                  fileName.toUtf8().constData());
124         return;
125     }
126     setFileNTFSmTime(fi.lastModified());
127     setFileNTFSaTime(fi.lastRead());
128     setFileNTFScTime(fi.created());
129 }
```

Here is the call graph for this function:

12.76.3.6 void QuaZipNewInfo::setFilePermissions (const QString & *file*)

Takes permissions from the file and sets the high 16 bits of external attributes. Uses QFileInfo to get permissions on all platforms.

Definition at line 106 of file quazipnewinfo.cpp.

References QuaZipNewInfo_setPermissions().

```
{
    QFileInfo info = QFileInfo(file);
    QFile::Permissions perm = info.permissions();
    QuaZipNewInfo_setPermissions(this, perm, info.isDir());
}
```

Here is the call graph for this function:

12.76.3.7 void QuaZipNewInfo::setPermissions (QFile::Permissions *permissions*)

Modifies the highest 16 bits of external attributes. The type part is set to dir if the name ends with a slash, and to regular file otherwise.

Definition at line 113 of file quazipnewinfo.cpp.

References name, and QuaZipNewInfo_setPermissions().

```
{
    QuaZipNewInfo_setPermissions(this, permissions,
  name.endsWith('/'));
}
```

Here is the call graph for this function:

12.76.4 Field Documentation

12.76.4.1 QString QuaZipNewInfo::comment

Will be encoded using QuaZip::getCommentCodec().

Definition at line 75 of file quazipnewinfo.h.

Referenced by QuaZipFile::open().

12.76.4.2 QDateTime QuaZipNewInfo::dateTime

This is the last file modification date and time. Will be stored in the archive central directory. It is a good practice to set it to the source file timestamp instead of archive creating time. Use setFileDateTime() or QuaZipNewInfo(const QString&, const QString&).

Definition at line 62 of file quazipnewinfo.h.

Referenced by QuaZipFile::open(), QuaZipNewInfo(), and setFileDateTime().

12.76.4.3 quint32 QuaZipNewInfo::externalAttr

The highest 16 bits contain Unix file permissions and type (dir or file). The constructor QuaZipNewInfo(const QString&, const QString&) takes permissions from the provided file.

Definition at line 71 of file quazipnewinfo.h.

Referenced by QuaZipFile::open(), and QuaZipNewInfo_setPermissions().

12.76.4.4 QByteArray QuaZipNewInfo::extraGlobal

Definition at line 79 of file quazipnewinfo.h.

Referenced by QuaZipFile::open(), setFileNTFSaTime(), setFileNTFScTime(), and setFileNTFSmTime().

12.76.4.5 QByteArray QuaZipNewInfo::extraLocal

Definition at line 77 of file quazipnewinfo.h.

Referenced by QuaZipFile::open(), setFileNTFSaTime(), setFileNTFScTime(), and setFileNTFSmTime().

12.76.4.6 quint16 QuaZipNewInfo::internalAttr

Definition at line 64 of file quazipnewinfo.h.

Referenced by QuaZipFile::open().

12.76.4.7 QString QuaZipNewInfo::name

This field holds file name inside archive, including path relative to archive root.

Definition at line 55 of file quazipnewinfo.h.

Referenced by QuaZipFile::open(), and setPermissions().

12.76.4.8 ulong QuaZipNewInfo::uncompressedSize

This is only needed if you are using raw file zipping mode, i. e. adding precompressed file in the zip archive.

Definition at line 84 of file quazipnewinfo.h.

Referenced by QuaZipFile::open().

The documentation for this struct was generated from the following files:

- src/ckb/quazip/quazipnewinfo.h
- src/ckb/quazip/quazipnewinfo.cpp

12.77 QuaZipPrivate Class Reference

All the internal stuff for the QuaZip class.

Collaboration diagram for QuaZipPrivate:

Private Member Functions

- QTextCodec ∗ getDefaultFileNameCodec ()
- QuaZipPrivate (QuaZip ∗q)

  The constructor for the corresponding QuaZip constructor.
- QuaZipPrivate (QuaZip ∗q, const QString &zipName)

  The constructor for the corresponding QuaZip constructor.
- QuaZipPrivate (QuaZip ∗q, QIODevice ∗ioDevice)

  The constructor for the corresponding QuaZip constructor.
- template<typename TFileInfo >
  bool getFileInfoList (QList< TFileInfo > ∗result) const

  Returns either a list of file names or a list of QuaZipFileInfo.
- void clearDirectoryMap ()

  Stores map of filenames and file locations for unzipping.
- void addCurrentFileToDirectoryMap (const QString &fileName)
- bool goToFirstUnmappedFile ()

Private Attributes

- QuaZip ∗ q

  The pointer to the corresponding QuaZip instance.
- QTextCodec ∗ fileNameCodec

  The codec for file names.
- QTextCodec ∗ commentCodec

  The codec for comments.
- QString zipName

  The archive file name.
- QIODevice ∗ ioDevice

  The device to access the archive.

- QString comment

  The global comment.
- QuaZip::Mode mode

  The open mode.
- union {
  unzFile **unzFile_f**
  The internal handle for UNZIP modes.
  zipFile **zipFile_f**
  The internal handle for ZIP modes.
  };

- bool hasCurrentFile_f

  Whether a current file is set.
- int zipError

  The last error.
- bool dataDescriptorWritingEnabled

  Whether the data descriptor writing mode is enabled.
- bool zip64

  The zip64 mode.
- bool autoClose

  The auto-close flag.
- QHash< QString, unz64_file_pos > directoryCaseSensitive
- QHash< QString, unz64_file_pos > directoryCaseInsensitive
- unz64_file_pos lastMappedDirectoryEntry

Static Private Attributes

- static QTextCodec * defaultFileNameCodec = NULL

Friends

- class QuaZip

12.77.1 Detailed Description

This class keeps all the private stuff for the QuaZip class so it can be changed without breaking binary compatibility, according to the Pimpl idiom.

Definition at line 39 of file quazip.cpp.

12.77.2 Constructor & Destructor Documentation

12.77.2.1 QuaZipPrivate::QuaZipPrivate (QuaZip * *q*) [inline],[private]

Definition at line 81 of file quazip.cpp.

References lastMappedDirectoryEntry, unz64_file_pos_s::num_of_file, and unz64_file_pos_s::pos_in_zip_directory.

```
81                                  :
82        q(q),
83        fileNameCodec(getDefaultFileNameCodec()),
84        commentCodec(QTextCodec::codecForLocale()),
85        ioDevice(NULL),
86        mode(QuaZip::mdNotOpen),
```

```
87        hasCurrentFile_f(false),
88        zipError(UNZ_OK),
89        dataDescriptorWritingEnabled(true),
90        zip64(false),
91        autoClose(true)
92      {
93          lastMappedDirectoryEntry.num_of_file = 0;
94          lastMappedDirectoryEntry.pos_in_zip_directory = 0;
95      }
```

12.77.2.2 QuaZipPrivate::QuaZipPrivate (QuaZip * *q*, const QString & *zipName*) [inline],[private]

Definition at line 97 of file quazip.cpp.

References lastMappedDirectoryEntry, unz64_file_pos_s::num_of_file, and unz64_file_pos_s::pos_in_zip_directory.

```
97                                                          :
98        q(q),
99        fileNameCodec(getDefaultFileNameCodec()),
100        commentCodec(QTextCodec::codecForLocale()),
101        zipName(zipName),
102        ioDevice(NULL),
103        mode(QuaZip::mdNotOpen),
104        hasCurrentFile_f(false),
105        zipError(UNZ_OK),
106        dataDescriptorWritingEnabled(true),
107        zip64(false),
108        autoClose(true)
109      {
110          lastMappedDirectoryEntry.num_of_file = 0;
111          lastMappedDirectoryEntry.pos_in_zip_directory = 0;
112      }
```

12.77.2.3 QuaZipPrivate::QuaZipPrivate (QuaZip * *q*, QIODevice * *ioDevice*) [inline],[private]

Definition at line 114 of file quazip.cpp.

References lastMappedDirectoryEntry, unz64_file_pos_s::num_of_file, and unz64_file_pos_s::pos_in_zip_directory.

```
114                                                          :
115          q(q),
116        fileNameCodec(getDefaultFileNameCodec()),
117        commentCodec(QTextCodec::codecForLocale()),
118        ioDevice(ioDevice),
119        mode(QuaZip::mdNotOpen),
120        hasCurrentFile_f(false),
121        zipError(UNZ_OK),
122        dataDescriptorWritingEnabled(true),
123        zip64(false),
124        autoClose(true)
125      {
126          lastMappedDirectoryEntry.num_of_file = 0;
127          lastMappedDirectoryEntry.pos_in_zip_directory = 0;
128      }
```

12.77.3 Member Function Documentation

12.77.3.1 void QuaZipPrivate::addCurrentFileToDirectoryMap (const QString & *fileName*) [inline],[private]

Definition at line 153 of file quazip.cpp.

References directoryCaseInsensitive, directoryCaseSensitive, hasCurrentFile_f, lastMappedDirectoryEntry, unz64_file_pos_s::pos_in_zip_directory, and unzGetFilePos64().

Referenced by QuaZip::getCurrentFileInfo(), and QuaZip::getCurrentFileName().

```
{
    if (!hasCurrentFile_f || fileName.isEmpty()) {
        return;
    }
    // Adds current file to filename map as fileName
    unz64_file_pos fileDirectoryPos;
    unzGetFilePos64(unzFile_f, &fileDirectoryPos);
    directoryCaseSensitive.insert(fileName, fileDirectoryPos);
    // Only add lowercase to directory map if not already there
    // ensures only map the first one seen
    QString lower = fileName.toLower();
    if (!directoryCaseInsensitive.contains(lower))
        directoryCaseInsensitive.insert(lower, fileDirectoryPos);
    // Mark last one
    if (fileDirectoryPos.pos_in_zip_directory >
  lastMappedDirectoryEntry.pos_in_zip_directory)
        lastMappedDirectoryEntry = fileDirectoryPos;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.77.3.2 void QuaZipPrivate::clearDirectoryMap ( ) [inline],[private]

Definition at line 145 of file quazip.cpp.

References directoryCaseInsensitive, directoryCaseSensitive, lastMappedDirectoryEntry, unz64_file_pos_s::num_of_file, and unz64_file_pos_s::pos_in_zip_directory.

Referenced by QuaZip::close().

```
{
    directoryCaseInsensitive.clear();
    directoryCaseSensitive.clear();
    lastMappedDirectoryEntry.num_of_file = 0;
    lastMappedDirectoryEntry.pos_in_zip_directory = 0;
}
```

Here is the caller graph for this function:

12.77.3.3 QTextCodec* QuaZipPrivate::getDefaultFileNameCodec ( ) [inline],[private]

Definition at line 72 of file quazip.cpp.

References defaultFileNameCodec.

```
73     {
74         if (defaultFileNameCodec == NULL) {
75             return QTextCodec::codecForLocale();
76         } else {
77             return defaultFileNameCodec;
78         }
79     }
```

12.77.3.4 template<typename TFileInfo > bool QuaZipPrivate::getFileInfoList (QList< TFileInfo > * *result*) const [private]

Definition at line 687 of file quazip.cpp.

References QuaZip::getCurrentFileName(), QuaZip::goToFirstFile(), QuaZip::goToNextFile(), QuaZip::hasCurrentFile(), QuaZip::mdUnzip, mode, q, QuaZip::setCurrentFile(), UNZ_OK, and zipError.

Referenced by QuaZip::getFileInfoList(), QuaZip::getFileInfoList64(), and QuaZip::getFileNameList().

```
688 {
689   QuaZipPrivate *fakeThis=const_cast<QuaZipPrivate*>(this);
690   fakeThis->zipError=UNZ_OK;
691   if (mode!=QuaZip::mdUnzip) {
692     qWarning("QuaZip::getFileNameList/getFileInfoList(): "
693              "ZIP is not open in mdUnzip mode");
694     return false;
695   }
696   QString currentFile;
697   if (q->hasCurrentFile()) {
698       currentFile = q->getCurrentFileName();
699   }
700   if (q->goToFirstFile()) {
701       do {
702           bool ok;
703           result->append(QuaZip_getFileInfo<TFileInfo>(q, &ok));
704           if (!ok)
705               return false;
706       } while (q->goToNextFile());
707   }
708   if (zipError != UNZ_OK)
709       return false;
```

```
    if (currentFile.isEmpty()) {
        if (!q->goToFirstFile())
            return false;
    } else {
        if (!q->setCurrentFile(currentFile))
            return false;
    }
    return true;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.77.3.5 bool QuaZipPrivate::goToFirstUnmappedFile ( ) [private]

Definition at line 172 of file quazip.cpp.

References hasCurrentFile_f, lastMappedDirectoryEntry, QuaZip::mdUnzip, mode, unz64_file_pos_s::pos_in_zip_directory, UNZ_END_OF_LIST_OF_FILE, UNZ_OK, unzGoToFilePos64(), unzGoToFirstFile(), unzGoToNextFile(), and zipError.

Referenced by QuaZip::setCurrentFile().

```
{
    zipError = UNZ_OK;
    if (mode != QuaZip::mdUnzip) {
        qWarning("QuaZipPrivate::goToNextUnmappedFile(): ZIP is not open in mdUnzip mode");
        return false;
    }
    // If not mapped anything, go to beginning
    if (lastMappedDirectoryEntry.pos_in_zip_directory == 0) {
        unzGoToFirstFile(unzFile_f);
    } else {
        // Goto the last one mapped, plus one
        unzGoToFilePos64(unzFile_f, &lastMappedDirectoryEntry);
        unzGoToNextFile(unzFile_f);
    }
```

```
    hasCurrentFile_f=zipError==UNZ_OK;
    if(zipError==UNZ_END_OF_LIST_OF_FILE)
      zipError=UNZ_OK;
    return hasCurrentFile_f;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.77.4 Friends And Related Function Documentation

12.77.4.1 friend class QuaZip [friend]

Definition at line 40 of file quazip.cpp.

12.77.5 Field Documentation

12.77.5.1 union { ... } [private]

12.77.5.2 bool QuaZipPrivate::autoClose [private]

Definition at line 71 of file quazip.cpp.

Referenced by QuaZip::isAutoClose(), QuaZip::open(), and QuaZip::setAutoClose().

12.77.5.3 QString QuaZipPrivate::comment [private]

Definition at line 53 of file quazip.cpp.

Referenced by QuaZip::close(), and QuaZip::setComment().

12.77.5.4 QTextCodec* QuaZipPrivate::commentCodec [private]

Definition at line 47 of file quazip.cpp.

Referenced by QuaZip::close(), QuaZip::getComment(), QuaZip::getCommentCodec(), QuaZip::getCurrentFileInfo(), and QuaZip::setCommentCodec().

12.77.5.5 bool QuaZipPrivate::dataDescriptorWritingEnabled [private]

Definition at line 67 of file quazip.cpp.

Referenced by QuaZip::isDataDescriptorWritingEnabled(), QuaZip::open(), and QuaZip::setDataDescriptorWritingEnabled().

12.77.5.6 QTextCodec * QuaZipPrivate::defaultFileNameCodec = NULL [static], [private]

Definition at line 140 of file quazip.cpp.

Referenced by getDefaultFileNameCodec(), and QuaZip::setDefaultFileNameCodec().

12.77.5.7 QHash<QString, unz64_file_pos> QuaZipPrivate::directoryCaseInsensitive [private]

Definition at line 138 of file quazip.cpp.

Referenced by addCurrentFileToDirectoryMap(), clearDirectoryMap(), and QuaZip::setCurrentFile().

12.77.5.8 QHash<QString, unz64_file_pos> QuaZipPrivate::directoryCaseSensitive [private]

Definition at line 137 of file quazip.cpp.

Referenced by addCurrentFileToDirectoryMap(), clearDirectoryMap(), and QuaZip::setCurrentFile().

12.77.5.9 QTextCodec* QuaZipPrivate::fileNameCodec [private]

Definition at line 45 of file quazip.cpp.

Referenced by QuaZip::getCurrentFileInfo(), QuaZip::getCurrentFileName(), QuaZip::getFileNameCodec(), and QuaZip::setFileNameCodec().

12.77.5.10 bool QuaZipPrivate::hasCurrentFile_f [private]

Definition at line 63 of file quazip.cpp.

Referenced by addCurrentFileToDirectoryMap(), QuaZip::goToFirstFile(), goToFirstUnmappedFile(), QuaZip::goToNextFile(), QuaZip::hasCurrentFile(), and QuaZip::setCurrentFile().

12.77.5.11 QIODevice* QuaZipPrivate::ioDevice [private]

Definition at line 51 of file quazip.cpp.

Referenced by QuaZip::close(), QuaZip::getIoDevice(), QuaZip::open(), QuaZip::setIoDevice(), and QuaZip::setZipName().

12.77.5.12 unz64_file_pos QuaZipPrivate::lastMappedDirectoryEntry [private]

Definition at line 139 of file quazip.cpp.

Referenced by addCurrentFileToDirectoryMap(), clearDirectoryMap(), goToFirstUnmappedFile(), and QuaZipPrivate().

12.77.5.13 QuaZip::Mode QuaZipPrivate::mode [private]

Definition at line 55 of file quazip.cpp.

Referenced by QuaZip::close(), QuaZip::getComment(), QuaZip::getCurrentFileInfo(), QuaZip::getCurrentFileName(), QuaZip::getEntriesCount(), getFileInfoList(), QuaZip::getMode(), QuaZip::goToFirstFile(), goToFirstUnmappedFile(), QuaZip::goToNextFile(), QuaZip::isOpen(), QuaZip::open(), and QuaZip::setCurrentFile().

12.77.5.14 QuaZip* QuaZipPrivate::q [private]

Definition at line 43 of file quazip.cpp.

Referenced by getFileInfoList().

12.77.5.15 bool QuaZipPrivate::zip64 [private]

Definition at line 69 of file quazip.cpp.

Referenced by QuaZip::isZip64Enabled(), and QuaZip::setZip64Enabled().

12.77.5.16 int QuaZipPrivate::zipError [private]

Definition at line 65 of file quazip.cpp.

Referenced by QuaZip::close(), QuaZip::getComment(), QuaZip::getCurrentFileInfo(), QuaZip::getCurrentFileName(), QuaZip::getEntriesCount(), getFileInfoList(), QuaZip::getZipError(), QuaZip::goToFirstFile(), goToFirstUnmappedFile(), QuaZip::goToNextFile(), QuaZip::open(), and QuaZip::setCurrentFile().

12.77.5.17 QString QuaZipPrivate::zipName [private]

Definition at line 49 of file quazip.cpp.

Referenced by QuaZip::close(), QuaZip::getIoDevice(), QuaZip::getZipName(), QuaZip::open(), QuaZip::setIoDevice(), and QuaZip::setZipName().

The documentation for this class was generated from the following file:

- src/ckb/quazip/quazip.cpp

12.78 QWidget Class Reference

Inheritance diagram for QWidget:

Collaboration diagram for QWidget:

The documentation for this class was generated from the following file:

- src/ckb/keywidget.h

12.79 Ui::RebindWidget Class Reference

```
#include <src/ckb/ui_rebindwidget.h>
```

Inheritance diagram for Ui::RebindWidget:

Collaboration diagram for Ui::RebindWidget:

Public Member Functions

- void setupUi (QWidget *RebindWidget)
- void retranslateUi (QWidget *RebindWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QTabWidget * tabWidget
- QWidget * keyTab
- QGridLayout * gridLayout_2
- QComboBox * numBox
- QComboBox * typingBox
- QComboBox * fnBox
- QSpacerItem * verticalSpacer_10
- QSpacerItem * verticalSpacer_3
- QSpacerItem * horizontalSpacer_2
- QRadioButton * typingButton
- QComboBox * modBox
- QSpacerItem * horizontalSpacer_3
- QRadioButton * mediaButton
- QSpacerItem * verticalSpacer_4
- QSpacerItem * horizontalSpacer_9
- QSpacerItem * horizontalSpacer_4
- QRadioButton * modButton
- QRadioButton * fnButton
- QComboBox * mediaBox
- QRadioButton * numButton
- QSpacerItem * horizontalSpacer_17
- QWidget * mouseTab
- QGridLayout * gridLayout
- QRadioButton * dpiButton
- QSpacerItem * verticalSpacer_2
- QSpacerItem * verticalSpacer_8
- QSpacerItem * horizontalSpacer_18
- QSpacerItem * horizontalSpacer_20
- QComboBox * mb2Box
- QComboBox * dpiBox
- QSpinBox * dpiCustYBox
- QComboBox * mbBox

- QComboBox * wheelBox
- QRadioButton * mbButton
- QSpinBox * dpiCustXBox
- QLabel * dpiWarning
- QRadioButton * wheelButton
- QSpacerItem * horizontalSpacer_22
- QRadioButton * mb2Button
- QLabel * dpiCustLabel
- QSpacerItem * horizontalSpacer_19
- QSpacerItem * horizontalSpacer_21
- QWidget * animTab
- QGridLayout * gridLayout_5
- QSpacerItem * verticalSpacer_11
- QComboBox * animBox
- QSpacerItem * horizontalSpacer_24
- QSpacerItem * horizontalSpacer_25
- QCheckBox * animKrBox
- QCheckBox * animOnceBox
- QSpacerItem * horizontalSpacer_26
- QRadioButton * animButton
- QSpacerItem * horizontalSpacer_23
- QWidget * actionTab
- QGridLayout * gridLayout_3
- QSpacerItem * horizontalSpacer_5
- QRadioButton * modeButton
- QCheckBox * modeWrapBox
- QCheckBox * lightWrapBox
- QSpacerItem * verticalSpacer_7
- QSpacerItem * verticalSpacer_6
- QRadioButton * lockButton
- QSpacerItem * verticalSpacer_5
- QComboBox * lightBox
- QComboBox * lockBox
- QRadioButton * lightButton
- QComboBox * modeBox
- QSpacerItem * horizontalSpacer_8
- QSpacerItem * horizontalSpacer_10
- QSpacerItem * horizontalSpacer_7
- QSpacerItem * horizontalSpacer_6
- QWidget * programTab
- QGridLayout * gridLayout_4
- QSpacerItem * verticalSpacer
- QSpacerItem * horizontalSpacer
- QCheckBox * programKpButton
- QLineEdit * programKpBox
- QSpacerItem * horizontalSpacer_11
- QSpacerItem * horizontalSpacer_13
- QLineEdit * programKrBox
- QCheckBox * programKrButton
- QSpacerItem * horizontalSpacer_12
- QWidget * programKpExtra
- QHBoxLayout * horizontalLayout_2
- QCheckBox * programKpSIBox
- QComboBox * programKpModeBox
- QSpacerItem * horizontalSpacer_15

- QWidget * programKrExtra
- QHBoxLayout * horizontalLayout_3
- QCheckBox * programKrSIBox
- QComboBox * programKrModeBox
- QSpacerItem * horizontalSpacer_16
- QLabel * progTipLabel
- QWidget * macroTab
- QWidget * layoutWidget1
- QGridLayout * gridLayout_8
- QGroupBox * groupBox_2
- QPlainTextEdit * pteMacroBox
- QPlainTextEdit * pteMacroComment
- QPlainTextEdit * pteMacroText
- QWidget * layoutWidget
- QVBoxLayout * verticalLayout_2
- QGroupBox * groupBox_3
- QGroupBox * groupBox_4
- QWidget * layoutWidget_2
- QGridLayout * gridLayout_10
- QGroupBox * groupBox
- QPushButton * btnStopMacro
- QPushButton * btnStartMacro
- QPushButton * btnClearMacro
- QLabel * lbl_macro
- QHBoxLayout * horizontalLayout
- QSpacerItem * horizontalSpacer_14
- QPushButton * unbindButton
- QPushButton * resetButton
- QPushButton * cancelButton
- QPushButton * applyButton

12.79.1 Detailed Description

Definition at line 971 of file ui_rebindwidget.h.

12.79.2 Member Function Documentation

12.79.2.1 void Ui_RebindWidget::retranslateUi (QWidget * *RebindWidget*) [inline],[inherited]

Definition at line 825 of file ui_rebindwidget.h.

References Ui_RebindWidget::actionTab, Ui_RebindWidget::animBox, Ui_RebindWidget::animButton, Ui_RebindWidget::animKrBox, Ui_RebindWidget::animOnceBox, Ui_RebindWidget::animTab, Ui_RebindWidget::applyButton, Ui_RebindWidget::btnClearMacro, Ui_RebindWidget::btnStartMacro, Ui_RebindWidget::btnStopMacro, Ui_RebindWidget::cancelButton, Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiButton, Ui_RebindWidget::dpiCustLabel, Ui_RebindWidget::dpiWarning, Ui_RebindWidget::fnBox, Ui_RebindWidget::fnButton, Ui_RebindWidget::groupBox, Ui_RebindWidget::groupBox_2, Ui_RebindWidget::groupBox_3, Ui_RebindWidget::groupBox_4, Ui_RebindWidget::keyTab, Ui_RebindWidget::lbl_macro, Ui_RebindWidget::lightBox, Ui_RebindWidget::lightButton, Ui_RebindWidget::lightWrapBox, Ui_RebindWidget::lockBox, Ui_RebindWidget::lockButton, Ui_RebindWidget::macroTab, Ui_RebindWidget::mb2Box, Ui_RebindWidget::mb2Button, Ui_RebindWidget::mbBox, Ui_RebindWidget::mbButton, Ui_RebindWidget::mediaBox, Ui_RebindWidget::mediaButton, Ui_RebindWidget::modBox, Ui_RebindWidget::modButton, Ui_RebindWidget::modeBox, Ui_RebindWidget::modeButton, Ui_RebindWidget::modeWrapBox, Ui_RebindWidget::mouseTab, Ui_RebindWidget::numBox, Ui_RebindWidget::numButton,

Ui_RebindWidget::programKpButton, Ui_RebindWidget::programKpModeBox, Ui_RebindWidget::programKpSIBox, Ui_RebindWidget::programKrButton, Ui_RebindWidget::programKrModeBox, Ui_RebindWidget::programKrSIBox, Ui_RebindWidget::programTab, Ui_RebindWidget::progTipLabel, Ui_RebindWidget::pteMacroComment, Ui_RebindWidget::pteMacroText, Ui_RebindWidget::resetButton, Ui_RebindWidget::tabWidget, Ui_RebindWidget::typingBox, Ui_RebindWidget::typingButton, Ui_RebindWidget::unbindButton, Ui_RebindWidget::wheelBox, and Ui_RebindWidget::wheelButton.

Referenced by Ui_RebindWidget::setupUi().

```
    {
        numBox->clear();
        numBox->insertItems(0, QStringList()
         << QString()
        );
        typingBox->clear();
        typingBox->insertItems(0, QStringList()
         << QString()
        );
        fnBox->clear();
        fnBox->insertItems(0, QStringList()
         << QString()
        );
        typingButton->setText(QApplication::translate("RebindWidget", "Typing:", Q_NULLPTR));
        modBox->clear();
        modBox->insertItems(0, QStringList()
         << QString()
        );
        mediaButton->setText(QApplication::translate("RebindWidget", "Media:", Q_NULLPTR));
        modButton->setText(QApplication::translate("RebindWidget", "Modifier:", Q_NULLPTR));
        fnButton->setText(QApplication::translate("RebindWidget", "Miscellaneous:", Q_NULLPTR));
        mediaBox->clear();
        mediaBox->insertItems(0, QStringList()
         << QString()
        );
        numButton->setText(QApplication::translate("RebindWidget", "Number pad:", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(keyTab), QApplication::translate("
    RebindWidget", "Keyboard", Q_NULLPTR));
        dpiButton->setText(QApplication::translate("RebindWidget", "Change DPI:", Q_NULLPTR));
        mb2Box->clear();
        mb2Box->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "4 (Back)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "5 (Forward)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "6", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "7", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "8", Q_NULLPTR)
        );
        dpiBox->clear();
        dpiBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "(Up)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "(Down)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Sniper", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "1:", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "2:", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "3:", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "4:", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "5:", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Custom:", Q_NULLPTR)
        );
        mbBox->clear();
        mbBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "Left", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Right", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Middle", Q_NULLPTR)
        );
        wheelBox->clear();
        wheelBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "Up", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Down", Q_NULLPTR)
        );
        mbButton->setText(QApplication::translate("RebindWidget", "Standard button:", Q_NULLPTR));
        dpiWarning->setText(QApplication::translate("RebindWidget", "DPI is only available for
     mice.", Q_NULLPTR));
        wheelButton->setText(QApplication::translate("RebindWidget", "Wheel:", Q_NULLPTR));
        mb2Button->setText(QApplication::translate("RebindWidget", "Special button:", Q_NULLPTR));
        dpiCustLabel->setText(QApplication::translate("RebindWidget", "x", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(mouseTab),
    QApplication::translate("RebindWidget", "Mouse", Q_NULLPTR));
        animBox->clear();
        animBox->insertItems(0, QStringList()
         << QString()
```

```
        );
        animKrBox->setText(QApplication::translate("RebindWidget", "Stop on key release", Q_NULLPTR));
        animOnceBox->setText(QApplication::translate("RebindWidget", "Restart every time", Q_NULLPTR));
        animButton->setText(QApplication::translate("RebindWidget", "Start animation on keypress:", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(animTab), QApplication::translate("RebindWidget", "Animation", Q_NULLPTR));
        modeButton->setText(QApplication::translate("RebindWidget", "Switch to mode:", Q_NULLPTR);
        modeWrapBox->setText(QApplication::translate("RebindWidget", "Wrap-around", Q_NULLPTR));
        lightWrapBox->setText(QApplication::translate("RebindWidget", "Wrap-around", Q_NULLPTR);
        lockButton->setText(QApplication::translate("RebindWidget", "Windows lock:", Q_NULLPTR));
        lightBox->clear();
        lightBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "Up", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Down", Q_NULLPTR)
        );
        lockBox->clear();
        lockBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "Toggle", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "On", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Off", Q_NULLPTR)
        );
        lightButton->setText(QApplication::translate("RebindWidget", "Brightness:", Q_NULLPTR));
        modeBox->clear();
        modeBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "(Previous)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "(Next)", Q_NULLPTR)
        );
        tabWidget->setTabText(tabWidget->indexOf(actionTab), QApplication::translate("RebindWidget", "Special", Q_NULLPTR));
        programKpButton->setText(QApplication::translate("RebindWidget", "Launch program on key press:", Q_NULLPTR));
        programKrButton->setText(QApplication::translate("RebindWidget", "Launch program on key release:", Q_NULLPTR));
        programKpSIBox->setText(QApplication::translate("RebindWidget", "Single instance", Q_NULLPTR));
        programKpModeBox->clear();
        programKpModeBox->insertItems(0, QStringList()
         << QApplication::translate("RebindWidget", "Run indefinitely", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Stop on release", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Stop on re-press", Q_NULLPTR)
        );
        programKrSIBox->setText(QApplication::translate("RebindWidget", "Single instance", Q_NULLPTR));
        programKrModeBox->clear();
        programKrModeBox->insertItems(0, QStringList()
         << QApplication::translate("RebindWidget", "Run indefinitely", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Stop on re-press", Q_NULLPTR)
        );
        progTipLabel->setText(QApplication::translate("RebindWidget", "Tip", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(programTab), QApplication::translate("RebindWidget", "Program", Q_NULLPTR));
        groupBox_2->setTitle(QApplication::translate("RebindWidget", "Macro Key Actions", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        pteMacroComment->setToolTip(QApplication::translate("RebindWidget", "What is this macro for?", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        pteMacroComment->setDocumentTitle(QString());
        pteMacroComment->setPlainText(QString());
        pteMacroText->setDocumentTitle(QString());
        pteMacroText->setPlainText(QString());
        groupBox_3->setTitle(QApplication::translate("RebindWidget", "Macro Comment", Q_NULLPTR);
        groupBox_4->setTitle(QApplication::translate("RebindWidget", "Macro Text", Q_NULLPTR));
        groupBox->setTitle(QApplication::translate("RebindWidget", "Macro recording", Q_NULLPTR));
        btnStopMacro->setText(QApplication::translate("RebindWidget", "Stop", Q_NULLPTR));
        btnStartMacro->setText(QApplication::translate("RebindWidget", "Start", Q_NULLPTR));
        btnClearMacro->setText(QApplication::translate("RebindWidget", "Clear", Q_NULLPTR));
        lbl_macro->setText(QApplication::translate("RebindWidget", "Comment label for help", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(macroTab), QApplication::translate("RebindWidget", "Macro", Q_NULLPTR));
        unbindButton->setText(QApplication::translate("RebindWidget", "Unbind", Q_NULLPTR));
        resetButton->setText(QApplication::translate("RebindWidget", "Reset to Default", Q_NULLPTR));
        cancelButton->setText(QApplication::translate("RebindWidget", "Cancel", Q_NULLPTR));
        applyButton->setText(QApplication::translate("RebindWidget", "Apply", Q_NULLPTR));
        Q_UNUSED(RebindWidget);
    } // retranslateUi
```

Here is the caller graph for this function:

12.79.2.2 void Ui_RebindWidget::setupUi (QWidget * *RebindWidget*) [inline],[inherited]

Definition at line 157 of file ui_rebindwidget.h.

References Ui_RebindWidget::actionTab, Ui_RebindWidget::animBox, Ui_RebindWidget::animButton, Ui_RebindWidget::animKrBox, Ui_RebindWidget::animOnceBox, Ui_RebindWidget::animTab, Ui_RebindWidget::applyButton, Ui_RebindWidget::btnClearMacro, Ui_RebindWidget::btnStartMacro, Ui_RebindWidget::btnStopMacro, Ui_RebindWidget::cancelButton, Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiButton, Ui_RebindWidget::dpiCustLabel, Ui_RebindWidget::dpiCustXBox, Ui_RebindWidget::dpiCustYBox, Ui_RebindWidget::dpiWarning, Ui_RebindWidget::fnBox, Ui_RebindWidget::fnButton, Ui_RebindWidget::gridLayout, Ui_RebindWidget::gridLayout_10, Ui_RebindWidget::gridLayout_2, Ui_RebindWidget::gridLayout_3, Ui_RebindWidget::gridLayout_4, Ui_RebindWidget::gridLayout_5, Ui_RebindWidget::gridLayout_8, Ui_RebindWidget::groupBox, Ui_RebindWidget::groupBox_2, Ui_RebindWidget::groupBox_3, Ui_RebindWidget::groupBox_4, Ui_RebindWidget::horizontalLayout, Ui_RebindWidget::horizontalLayout_2, Ui_RebindWidget::horizontalLayout_3, Ui_RebindWidget::horizontalSpacer, Ui_RebindWidget::horizontalSpacer_10, Ui_RebindWidget::horizontalSpacer_11, Ui_RebindWidget::horizontalSpacer_12, Ui_RebindWidget::horizontalSpacer_13, Ui_RebindWidget::horizontalSpacer_14, Ui_RebindWidget::horizontalSpacer_15, Ui_RebindWidget::horizontalSpacer_16, Ui_RebindWidget::horizontalSpacer_17, Ui_RebindWidget::horizontalSpacer_18, Ui_RebindWidget::horizontalSpacer_19, Ui_RebindWidget::horizontalSpacer_2, Ui_RebindWidget::horizontalSpacer_20, Ui_RebindWidget::horizontalSpacer_21, Ui_RebindWidget::horizontalSpacer_22, Ui_RebindWidget::horizontalSpacer_23, Ui_RebindWidget::horizontalSpacer_24, Ui_RebindWidget::horizontalSpacer_25, Ui_RebindWidget::horizontalSpacer_26, Ui_RebindWidget::horizontalSpacer_3, Ui_RebindWidget::horizontalSpacer_4, Ui_RebindWidget::horizontalSpacer_5, Ui_RebindWidget::horizontalSpacer_6, Ui_RebindWidget::horizontalSpacer_7, Ui_RebindWidget::horizontalSpacer_8, Ui_RebindWidget::horizontalSpacer_9, Ui_RebindWidget::keyTab, Ui_RebindWidget::layoutWidget, Ui_RebindWidget::layoutWidget1, Ui_RebindWidget::layoutWidget_2, Ui_RebindWidget::lbl_macro, Ui_RebindWidget::lightBox, Ui_RebindWidget::lightButton, Ui_RebindWidget::lightWrapBox, Ui_RebindWidget::lockBox, Ui_RebindWidget::lockButton, Ui_RebindWidget::macroTab, Ui_RebindWidget::mb2Box, Ui_RebindWidget::mb2Button, Ui_RebindWidget::mbBox, Ui_RebindWidget::mbButton, Ui_RebindWidget::mediaBox, Ui_RebindWidget::mediaButton, Ui_RebindWidget::modBox, Ui_RebindWidget::modButton, Ui_RebindWidget::modeBox, Ui_RebindWidget::modeButton, Ui_RebindWidget::modeWrapBox, Ui_RebindWidget::mouseTab, Ui_RebindWidget::numBox, Ui_RebindWidget::numButton, Ui_RebindWidget::programKpBox, Ui_RebindWidget::programKpButton, Ui_RebindWidget::programKpExtra, Ui_RebindWidget::programKpModeBox, Ui_RebindWidget::programKpSIBox, Ui_RebindWidget::programKrBox, Ui_RebindWidget::programKrButton, Ui_RebindWidget::programKrExtra, Ui_RebindWidget::programKrModeBox, Ui_RebindWidget::programKrSIBox, Ui_RebindWidget::programTab, Ui_RebindWidget::progTipLabel, Ui_RebindWidget::pteMacroBox, Ui_RebindWidget::pteMacroComment, Ui_RebindWidget::pteMacroText, Ui_RebindWidget::resetButton, Ui_RebindWidget::retranslateUi(), Ui_RebindWidget::tabWidget, Ui_RebindWidget::typingBox, Ui_RebindWidget::typingButton, Ui_RebindWidget::unbindButton, Ui_RebindWidget::verticalLayout, Ui_RebindWidget::verticalLayout_2, Ui_RebindWidget::verticalSpacer, Ui_RebindWidget::verticalSpacer_10, Ui_RebindWidget::verticalSpacer_11, Ui_RebindWidget::verticalSpacer_2, Ui_RebindWidget::verticalSpacer_3, Ui_RebindWidget::verticalSpacer_4, Ui_RebindWidget::verticalSpacer_5, Ui_RebindWidget::verticalSpacer_6, Ui_RebindWidget::verticalSpacer_7, Ui_RebindWidget::verticalSpacer_8, Ui_RebindWidget::wheelBox, and Ui_RebindWidget::wheelButton.

Referenced by RebindWidget::RebindWidget().

```
    {
        if (RebindWidget->objectName().isEmpty())
            RebindWidget->setObjectName(QStringLiteral("RebindWidget"));
        RebindWidget->resize(687, 342);
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
```

```
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(RebindWidget->sizePolicy().hasHeightForWidth());
        RebindWidget->setSizePolicy(sizePolicy);
        verticalLayout = new QVBoxLayout(RebindWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        tabWidget = new QTabWidget(RebindWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));
        keyTab = new QWidget();
        keyTab->setObjectName(QStringLiteral("keyTab"));
        sizePolicy.setHeightForWidth(keyTab->sizePolicy().hasHeightForWidth());
        keyTab->setSizePolicy(sizePolicy);
        gridLayout_2 = new QGridLayout(keyTab);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(-1, -1, -1, 0);
        numBox = new QComboBox(keyTab);
        numBox->setObjectName(QStringLiteral("numBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(numBox->sizePolicy().hasHeightForWidth());
        numBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(numBox, 6, 4, 1, 1);

        typingBox = new QComboBox(keyTab);
        typingBox->setObjectName(QStringLiteral("typingBox"));
        sizePolicy1.setHeightForWidth(typingBox->sizePolicy().hasHeightForWidth());
        typingBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(typingBox, 1, 1, 1, 1);

        fnBox = new QComboBox(keyTab);
        fnBox->setObjectName(QStringLiteral("fnBox"));
        sizePolicy1.setHeightForWidth(fnBox->sizePolicy().hasHeightForWidth());
        fnBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(fnBox, 6, 1, 1, 1);

        verticalSpacer_10 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed
);

        gridLayout_2->addItem(verticalSpacer_10, 9, 1, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
QSizePolicy::Expanding);

        gridLayout_2->addItem(verticalSpacer_3, 15, 2, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_2, 1, 3, 1, 1);

        typingButton = new QRadioButton(keyTab);
        typingButton->setObjectName(QStringLiteral("typingButton"));
        typingButton->setAutoExclusive(false);

        gridLayout_2->addWidget(typingButton, 0, 0, 1, 2);

        modBox = new QComboBox(keyTab);
        modBox->setObjectName(QStringLiteral("modBox"));
        sizePolicy1.setHeightForWidth(modBox->sizePolicy().hasHeightForWidth());
        modBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(modBox, 1, 4, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 1, 0, 1, 1);

        mediaButton = new QRadioButton(keyTab);
        mediaButton->setObjectName(QStringLiteral("mediaButton"));
        mediaButton->setAutoExclusive(false);

        gridLayout_2->addWidget(mediaButton, 10, 0, 1, 2);

        verticalSpacer_4 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed)
;

        gridLayout_2->addItem(verticalSpacer_4, 2, 1, 1, 1);

        horizontalSpacer_9 = new QSpacerItem(0, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_9, 1, 5, 1, 2);
```

```
        horizontalSpacer_4 = new QSpacerItem(0, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_4, 1, 2, 1, 1);

        modButton = new QRadioButton(keyTab);
        modButton->setObjectName(QStringLiteral("modButton"));

        gridLayout_2->addWidget(modButton, 0, 3, 1, 2);

        fnButton = new QRadioButton(keyTab);
        fnButton->setObjectName(QStringLiteral("fnButton"));
        fnButton->setAutoExclusive(false);

        gridLayout_2->addWidget(fnButton, 5, 0, 1, 2);

        mediaBox = new QComboBox(keyTab);
        mediaBox->setObjectName(QStringLiteral("mediaBox"));
        sizePolicy1.setHeightForWidth(mediaBox->sizePolicy().hasHeightForWidth());
        mediaBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(mediaBox, 11, 1, 1, 1);

        numButton = new QRadioButton(keyTab);
        numButton->setObjectName(QStringLiteral("numButton"));
        numButton->setAutoExclusive(false);

        gridLayout_2->addWidget(numButton, 5, 3, 1, 2);

        horizontalSpacer_17 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_17, 1, 7, 1, 1);

        tabWidget->addTab(keyTab, QString());
        mouseTab = new QWidget();
        mouseTab->setObjectName(QStringLiteral("mouseTab"));
        gridLayout = new QGridLayout(mouseTab);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        dpiButton = new QRadioButton(mouseTab);
        dpiButton->setObjectName(QStringLiteral("dpiButton"));
        dpiButton->setAutoExclusive(false);

        gridLayout->addWidget(dpiButton, 3, 3, 1, 5);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer_2, 5, 1, 1, 1);

        verticalSpacer_8 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 2, 1, 1, 1);

        horizontalSpacer_18 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_18, 1, 0, 1, 1);

        horizontalSpacer_20 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_20, 1, 3, 1, 1);

        mb2Box = new QComboBox(mouseTab);
        mb2Box->setObjectName(QStringLiteral("mb2Box"));
        sizePolicy1.setHeightForWidth(mb2Box->sizePolicy().hasHeightForWidth());
        mb2Box->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(mb2Box, 1, 4, 1, 4);

        dpiBox = new QComboBox(mouseTab);
        dpiBox->setObjectName(QStringLiteral("dpiBox"));

        gridLayout->addWidget(dpiBox, 4, 4, 1, 1);

        dpiCustYBox = new QSpinBox(mouseTab);
        dpiCustYBox->setObjectName(QStringLiteral("dpiCustYBox"));
        dpiCustYBox->setMinimum(400);
        dpiCustYBox->setMaximum(8500);
        dpiCustYBox->setSingleStep(50);

        gridLayout->addWidget(dpiCustYBox, 4, 7, 1, 1);

        mbBox = new QComboBox(mouseTab);
```

```
        mbBox->setObjectName(QStringLiteral("mbBox"));
        sizePolicy1.setHeightForWidth(mbBox->sizePolicy().hasHeightForWidth());
        mbBox->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(mbBox, 1, 1, 1, 1);

        wheelBox = new QComboBox(mouseTab);
        wheelBox->setObjectName(QStringLiteral("wheelBox"));

        gridLayout->addWidget(wheelBox, 4, 1, 1, 1);

        mbButton = new QRadioButton(mouseTab);
        mbButton->setObjectName(QStringLiteral("mbButton"));
        mbButton->setAutoExclusive(false);

        gridLayout->addWidget(mbButton, 0, 0, 1, 2);

        dpiCustXBox = new QSpinBox(mouseTab);
        dpiCustXBox->setObjectName(QStringLiteral("dpiCustXBox"));
        dpiCustXBox->setMinimum(400);
        dpiCustXBox->setMaximum(8500);
        dpiCustXBox->setSingleStep(50);

        gridLayout->addWidget(dpiCustXBox, 4, 5, 1, 1);

        dpiWarning = new QLabel(mouseTab);
        dpiWarning->setObjectName(QStringLiteral("dpiWarning"));
        QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(dpiWarning->sizePolicy().hasHeightForWidth());
        dpiWarning->setSizePolicy(sizePolicy2);

        gridLayout->addWidget(dpiWarning, 6, 0, 1, 10);

        wheelButton = new QRadioButton(mouseTab);
        wheelButton->setObjectName(QStringLiteral("wheelButton"));

        gridLayout->addWidget(wheelButton, 3, 0, 1, 2);

        horizontalSpacer_22 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_22, 1, 8, 1, 1);

        mb2Button = new QRadioButton(mouseTab);
        mb2Button->setObjectName(QStringLiteral("mb2Button"));
        mb2Button->setAutoExclusive(false);

        gridLayout->addWidget(mb2Button, 0, 3, 1, 5);

        dpiCustLabel = new QLabel(mouseTab);
        dpiCustLabel->setObjectName(QStringLiteral("dpiCustLabel"));

        gridLayout->addWidget(dpiCustLabel, 4, 6, 1, 1);

        horizontalSpacer_19 = new QSpacerItem(0, 0, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_19, 1, 2, 1, 1);

        horizontalSpacer_21 = new QSpacerItem(0, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_21, 1, 9, 1, 1);

        tabWidget->addTab(mouseTab, QString());
        animTab = new QWidget();
        animTab->setObjectName(QStringLiteral("animTab"));
        gridLayout_5 = new QGridLayout(animTab);
        gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
        verticalSpacer_11 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        gridLayout_5->addItem(verticalSpacer_11, 6, 2, 1, 1);

        animBox = new QComboBox(animTab);
        animBox->setObjectName(QStringLiteral("animBox"));
        sizePolicy1.setHeightForWidth(animBox->sizePolicy().hasHeightForWidth());
        animBox->setSizePolicy(sizePolicy1);

        gridLayout_5->addWidget(animBox, 4, 2, 1, 1);

        horizontalSpacer_24 = new QSpacerItem(20, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_24, 4, 3, 1, 1);
```

```
        horizontalSpacer_25 = new QSpacerItem(438, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_25, 4, 7, 1, 1);

        animKrBox = new QCheckBox(animTab);
        animKrBox->setObjectName(QStringLiteral("animKrBox"));

        gridLayout_5->addWidget(animKrBox, 4, 6, 1, 1);

        animOnceBox = new QCheckBox(animTab);
        animOnceBox->setObjectName(QStringLiteral("animOnceBox"));

        gridLayout_5->addWidget(animOnceBox, 4, 4, 1, 1);

        horizontalSpacer_26 = new QSpacerItem(20, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_26, 4, 5, 1, 1);

        animButton = new QRadioButton(animTab);
        animButton->setObjectName(QStringLiteral("animButton"));
        sizePolicy1.setHeightForWidth(animButton->sizePolicy().hasHeightForWidth());
        animButton->setSizePolicy(sizePolicy1);

        gridLayout_5->addWidget(animButton, 0, 1, 1, 2);

        horizontalSpacer_23 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_23, 4, 1, 1, 1);

        tabWidget->addTab(animTab, QString());
        actionTab = new QWidget();
        actionTab->setObjectName(QStringLiteral("actionTab"));
        sizePolicy.setHeightForWidth(actionTab->sizePolicy().hasHeightForWidth());
        actionTab->setSizePolicy(sizePolicy);
        gridLayout_3 = new QGridLayout(actionTab);
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        gridLayout_3->setContentsMargins(-1, -1, -1, 0);
        horizontalSpacer_5 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_5, 1, 0, 1, 1);

        modeButton = new QRadioButton(actionTab);
        modeButton->setObjectName(QStringLiteral("modeButton"));
        modeButton->setAutoExclusive(false);

        gridLayout_3->addWidget(modeButton, 0, 0, 1, 2);

        modeWrapBox = new QCheckBox(actionTab);
        modeWrapBox->setObjectName(QStringLiteral("modeWrapBox"));
        modeWrapBox->setChecked(true);

        gridLayout_3->addWidget(modeWrapBox, 1, 3, 1, 1);

        lightWrapBox = new QCheckBox(actionTab);
        lightWrapBox->setObjectName(QStringLiteral("lightWrapBox"));
        lightWrapBox->setChecked(true);

        gridLayout_3->addWidget(lightWrapBox, 4, 3, 1, 1);

        verticalSpacer_7 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_3->addItem(verticalSpacer_7, 2, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_3->addItem(verticalSpacer_6, 5, 1, 1, 1);

        lockButton = new QRadioButton(actionTab);
        lockButton->setObjectName(QStringLiteral("lockButton"));
        lockButton->setAutoExclusive(false);

        gridLayout_3->addWidget(lockButton, 6, 0, 1, 2);

        verticalSpacer_5 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout_3->addItem(verticalSpacer_5, 8, 1, 1, 1);

        lightBox = new QComboBox(actionTab);
        lightBox->setObjectName(QStringLiteral("lightBox"));
```

```
        sizePolicy1.setHeightForWidth(lightBox->sizePolicy().hasHeightForWidth());
        lightBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(lightBox, 4, 1, 1, 1);

        lockBox = new QComboBox(actionTab);
        lockBox->setObjectName(QStringLiteral("lockBox"));
        sizePolicy1.setHeightForWidth(lockBox->sizePolicy().hasHeightForWidth());
        lockBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(lockBox, 7, 1, 1, 1);

        lightButton = new QRadioButton(actionTab);
        lightButton->setObjectName(QStringLiteral("lightButton"));
        lightButton->setAutoExclusive(false);

        gridLayout_3->addWidget(lightButton, 3, 0, 1, 2);

        modeBox = new QComboBox(actionTab);
        modeBox->setObjectName(QStringLiteral("modeBox"));
        sizePolicy1.setHeightForWidth(modeBox->sizePolicy().hasHeightForWidth());
        modeBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(modeBox, 1, 1, 1, 1);

        horizontalSpacer_8 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_8, 1, 2, 1, 1);

        horizontalSpacer_10 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_10, 7, 3, 1, 1);

        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_7, 1, 4, 1, 1);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_6, 1, 5, 1, 1);

        tabWidget->addTab(actionTab, QString());
        programTab = new QWidget();
        programTab->setObjectName(QStringLiteral("programTab"));
        gridLayout_4 = new QGridLayout(programTab);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        verticalSpacer = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_4->addItem(verticalSpacer, 2, 1, 1, 1);

        horizontalSpacer = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer, 1, 0, 1, 1);

        programKpButton = new QCheckBox(programTab);
        programKpButton->setObjectName(QStringLiteral("programKpButton"));

        gridLayout_4->addWidget(programKpButton, 0, 0, 1, 2);

        programKpBox = new QLineEdit(programTab);
        programKpBox->setObjectName(QStringLiteral("programKpBox"));

        gridLayout_4->addWidget(programKpBox, 1, 1, 1, 1);

        horizontalSpacer_11 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_11, 0, 2, 1, 2);

        horizontalSpacer_13 = new QSpacerItem(20, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_13, 1, 2, 1, 1);

        programKrBox = new QLineEdit(programTab);
        programKrBox->setObjectName(QStringLiteral("programKrBox"));

        gridLayout_4->addWidget(programKrBox, 4, 1, 1, 1);

        programKrButton = new QCheckBox(programTab);
        programKrButton->setObjectName(QStringLiteral("programKrButton"));

```

```
        gridLayout_4->addWidget(programKrButton, 3, 0, 1, 2);

        horizontalSpacer_12 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_12, 0, 4, 1, 1);

        programKpExtra = new QWidget(programTab);
        programKpExtra->setObjectName(QStringLiteral("programKpExtra"));
        horizontalLayout_2 = new QHBoxLayout(programKpExtra);
        horizontalLayout_2->setSpacing(12);
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        horizontalLayout_2->setContentsMargins(0, 0, 0, 0);
        programKpSIBox = new QCheckBox(programKpExtra);
        programKpSIBox->setObjectName(QStringLiteral("programKpSIBox"));

        horizontalLayout_2->addWidget(programKpSIBox);

        programKpModeBox = new QComboBox(programKpExtra);
        programKpModeBox->setObjectName(QStringLiteral("programKpModeBox"));

        horizontalLayout_2->addWidget(programKpModeBox);

        horizontalSpacer_15 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_15);


        gridLayout_4->addWidget(programKpExtra, 1, 3, 1, 2);

        programKrExtra = new QWidget(programTab);
        programKrExtra->setObjectName(QStringLiteral("programKrExtra"));
        horizontalLayout_3 = new QHBoxLayout(programKrExtra);
        horizontalLayout_3->setSpacing(12);
        horizontalLayout_3->setObjectName(QStringLiteral("horizontalLayout_3"));
        horizontalLayout_3->setContentsMargins(0, 0, 0, 0);
        programKrSIBox = new QCheckBox(programKrExtra);
        programKrSIBox->setObjectName(QStringLiteral("programKrSIBox"));

        horizontalLayout_3->addWidget(programKrSIBox);

        programKrModeBox = new QComboBox(programKrExtra);
        programKrModeBox->setObjectName(QStringLiteral("programKrModeBox"));

        horizontalLayout_3->addWidget(programKrModeBox);

        horizontalSpacer_16 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_3->addItem(horizontalSpacer_16);


        gridLayout_4->addWidget(programKrExtra, 4, 3, 1, 2);

        progTipLabel = new QLabel(programTab);
        progTipLabel->setObjectName(QStringLiteral("progTipLabel"));
        QSizePolicy sizePolicy3(QSizePolicy::Preferred, QSizePolicy::Expanding);
        sizePolicy3.setHorizontalStretch(0);
        sizePolicy3.setVerticalStretch(0);
        sizePolicy3.setHeightForWidth(progTipLabel->sizePolicy().hasHeightForWidth());
        progTipLabel->setSizePolicy(sizePolicy3);
        progTipLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|Qt::TextSelectableByMouse);

        gridLayout_4->addWidget(progTipLabel, 5, 1, 1, 4);

        tabWidget->addTab(programTab, QString());
        macroTab = new QWidget();
        macroTab->setObjectName(QStringLiteral("macroTab"));
        layoutWidget1 = new QWidget(macroTab);
        layoutWidget1->setObjectName(QStringLiteral("layoutWidget1"));
        layoutWidget1->setGeometry(QRect(40, 12, 241, 171));
        gridLayout_8 = new QGridLayout(layoutWidget1);
        gridLayout_8->setObjectName(QStringLiteral("gridLayout_8"));
        gridLayout_8->setContentsMargins(0, 0, 0, 0);
        groupBox_2 = new QGroupBox(layoutWidget1);
        groupBox_2->setObjectName(QStringLiteral("groupBox_2"));

        gridLayout_8->addWidget(groupBox_2, 0, 0, 1, 1);

        pteMacroBox = new QPlainTextEdit(layoutWidget1);
        pteMacroBox->setObjectName(QStringLiteral("pteMacroBox"));
        pteMacroBox->setFocusPolicy(Qt::WheelFocus);
        pteMacroBox->setTabChangesFocus(true);

        gridLayout_8->addWidget(pteMacroBox, 1, 0, 1, 1);
```

```qt_ui_macro_tab_setup_ui_1
        pteMacroComment = new QPlainTextEdit(macroTab);
        pteMacroComment->setObjectName(QStringLiteral("pteMacroComment"));
        pteMacroComment->setEnabled(true);
        pteMacroComment->setGeometry(QRect(420, 20, 311, 31));
        pteMacroComment->setFocusPolicy(Qt::WheelFocus);
        pteMacroComment->setContextMenuPolicy(Qt::NoContextMenu);
        pteMacroComment->setAcceptDrops(true);
        pteMacroComment->setToolTipDuration(1);
        pteMacroComment->setInputMethodHints(Qt::ImhNone);
        pteMacroComment->setVerticalScrollBarPolicy(Qt::ScrollBarAlwaysOff);
        pteMacroComment->setTabChangesFocus(true);
        pteMacroComment->setUndoRedoEnabled(true);
        pteMacroComment->setReadOnly(false);
        pteMacroComment->setTabStopWidth(1);
        pteMacroText = new QPlainTextEdit(macroTab);
        pteMacroText->setObjectName(QStringLiteral("pteMacroText"));
        pteMacroText->setGeometry(QRect(420, 60, 311, 61));
        pteMacroText->setFocusPolicy(Qt::StrongFocus);
        pteMacroText->setContextMenuPolicy(Qt::NoContextMenu);
        pteMacroText->setAcceptDrops(false);
        pteMacroText->setInputMethodHints(Qt::ImhNoAutoUppercase);
        pteMacroText->setUndoRedoEnabled(false);
        pteMacroText->setReadOnly(false);
        pteMacroText->setTabStopWidth(1);
        layoutWidget = new QWidget(macroTab);
        layoutWidget->setObjectName(QStringLiteral("layoutWidget"));
        layoutWidget->setGeometry(QRect(300, 20, 119, 81));
        verticalLayout_2 = new QVBoxLayout(layoutWidget);
        verticalLayout_2->setObjectName(QStringLiteral("verticalLayout_2"));
        verticalLayout_2->setContentsMargins(0, 0, 0, 0);
        groupBox_3 = new QGroupBox(layoutWidget);
        groupBox_3->setObjectName(QStringLiteral("groupBox_3"));

        verticalLayout_2->addWidget(groupBox_3);

        groupBox_4 = new QGroupBox(layoutWidget);
        groupBox_4->setObjectName(QStringLiteral("groupBox_4"));

        verticalLayout_2->addWidget(groupBox_4);

        layoutWidget_2 = new QWidget(macroTab);
        layoutWidget_2->setObjectName(QStringLiteral("layoutWidget_2"));
        layoutWidget_2->setGeometry(QRect(300, 160, 436, 30));
        gridLayout_10 = new QGridLayout(layoutWidget_2);
        gridLayout_10->setObjectName(QStringLiteral("gridLayout_10"));
        gridLayout_10->setContentsMargins(0, 0, 0, 0);
        groupBox = new QGroupBox(layoutWidget_2);
        groupBox->setObjectName(QStringLiteral("groupBox"));

        gridLayout_10->addWidget(groupBox, 0, 0, 1, 1);

        btnStopMacro = new QPushButton(layoutWidget_2);
        btnStopMacro->setObjectName(QStringLiteral("btnStopMacro"));
        btnStopMacro->setEnabled(false);

        gridLayout_10->addWidget(btnStopMacro, 0, 2, 1, 1);

        btnStartMacro = new QPushButton(layoutWidget_2);
        btnStartMacro->setObjectName(QStringLiteral("btnStartMacro"));

        gridLayout_10->addWidget(btnStartMacro, 0, 1, 1, 1);

        btnClearMacro = new QPushButton(layoutWidget_2);
        btnClearMacro->setObjectName(QStringLiteral("btnClearMacro"));

        gridLayout_10->addWidget(btnClearMacro, 0, 3, 1, 1);

        lbl_macro = new QLabel(macroTab);
        lbl_macro->setObjectName(QStringLiteral("lbl_macro"));
        lbl_macro->setGeometry(QRect(300, 130, 431, 27));
        tabWidget->addTab(macroTab, QString());
        pteMacroComment->raise();
        layoutWidget1->raise();
        layoutWidget->raise();
        pteMacroText->raise();
        layoutWidget_2->raise();
        lbl_macro->raise();

        verticalLayout->addWidget(tabWidget);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        horizontalSpacer_14 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_14);
```

```

        unbindButton = new QPushButton(RebindWidget);
        unbindButton->setObjectName(QStringLiteral("unbindButton"));

        horizontalLayout->addWidget(unbindButton);

        resetButton = new QPushButton(RebindWidget);
        resetButton->setObjectName(QStringLiteral("resetButton"));

        horizontalLayout->addWidget(resetButton);

        cancelButton = new QPushButton(RebindWidget);
        cancelButton->setObjectName(QStringLiteral("cancelButton"));

        horizontalLayout->addWidget(cancelButton);

        applyButton = new QPushButton(RebindWidget);
        applyButton->setObjectName(QStringLiteral("applyButton"));

        horizontalLayout->addWidget(applyButton);


        verticalLayout->addLayout(horizontalLayout);

        QWidget::setTabOrder(tabWidget, pteMacroComment);
        QWidget::setTabOrder(pteMacroComment, pteMacroBox);
        QWidget::setTabOrder(pteMacroBox, dpiButton);
        QWidget::setTabOrder(dpiButton, mb2Box);
        QWidget::setTabOrder(mb2Box, btnStartMacro);
        QWidget::setTabOrder(btnStartMacro, fnBox);
        QWidget::setTabOrder(fnBox, dpiCustYBox);
        QWidget::setTabOrder(dpiCustYBox, dpiBox);
        QWidget::setTabOrder(dpiBox, applyButton);
        QWidget::setTabOrder(applyButton, mbBox);
        QWidget::setTabOrder(mbBox, cancelButton);
        QWidget::setTabOrder(cancelButton, wheelBox);
        QWidget::setTabOrder(wheelBox, btnStopMacro);
        QWidget::setTabOrder(btnStopMacro, mbButton);
        QWidget::setTabOrder(mbButton, dpiCustXBox);
        QWidget::setTabOrder(dpiCustXBox, btnClearMacro);
        QWidget::setTabOrder(btnClearMacro, wheelButton);
        QWidget::setTabOrder(wheelButton, mb2Button);
        QWidget::setTabOrder(mb2Button, animBox);
        QWidget::setTabOrder(animBox, animKrBox);
        QWidget::setTabOrder(animKrBox, animOnceBox);
        QWidget::setTabOrder(animOnceBox, animButton);
        QWidget::setTabOrder(animButton, modeButton);
        QWidget::setTabOrder(modeButton, modeWrapBox);
        QWidget::setTabOrder(modeWrapBox, lightWrapBox);
        QWidget::setTabOrder(lightWrapBox, lockButton);
        QWidget::setTabOrder(lockButton, lightBox);
        QWidget::setTabOrder(lightBox, resetButton);
        QWidget::setTabOrder(resetButton, lockBox);
        QWidget::setTabOrder(lockBox, lightButton);
        QWidget::setTabOrder(lightButton, modeBox);
        QWidget::setTabOrder(modeBox, unbindButton);
        QWidget::setTabOrder(unbindButton, programKpButton);
        QWidget::setTabOrder(programKpButton, programKpBox);
        QWidget::setTabOrder(programKpBox, programKrBox);
        QWidget::setTabOrder(programKrBox, programKrButton);
        QWidget::setTabOrder(programKrButton, programKpSIBox);
        QWidget::setTabOrder(programKpSIBox, programKpModeBox);
        QWidget::setTabOrder(programKpModeBox, programKrSIBox);
        QWidget::setTabOrder(programKrSIBox, programKrModeBox);
        QWidget::setTabOrder(programKrModeBox, typingBox);
        QWidget::setTabOrder(typingBox, numBox);
        QWidget::setTabOrder(numBox, pteMacroText);
        QWidget::setTabOrder(pteMacroText, typingButton);
        QWidget::setTabOrder(typingButton, mediaButton);
        QWidget::setTabOrder(mediaButton, modBox);
        QWidget::setTabOrder(modBox, modButton);
        QWidget::setTabOrder(modButton, fnButton);
        QWidget::setTabOrder(fnButton, mediaBox);
        QWidget::setTabOrder(mediaBox, numButton);

        retranslateUi(RebindWidget);
        QObject::connect(cancelButton, SIGNAL(clicked()), pteMacroBox, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroBox, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroText, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroComment, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), btnStopMacro, SLOT(animateClick()));

```

```
        tabWidget->setCurrentIndex(0);
        applyButton->setDefault(true);


        QMetaObject::connectSlotsByName(RebindWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.79.3 Field Documentation

12.79.3.1 QWidget* Ui_RebindWidget::actionTab [inherited]

Definition at line 92 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.2 QComboBox* Ui_RebindWidget::animBox [inherited]

Definition at line 84 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_animBox_currentIndexChanged(), RebindWidget::on_animButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.3 QRadioButton* Ui_RebindWidget::animButton [inherited]

Definition at line 90 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_animBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.4 QCheckBox* Ui_RebindWidget::animKrBox [inherited]

Definition at line 87 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.5 QCheckBox* Ui_RebindWidget::animOnceBox [inherited]

Definition at line 88 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.6 QWidget* Ui_RebindWidget::animTab [inherited]

Definition at line 81 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.7 QPushButton* Ui_RebindWidget::applyButton [inherited]

Definition at line 155 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), Ui_-RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.8 QPushButton* Ui_RebindWidget::btnClearMacro [inherited]

Definition at line 148 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.9 QPushButton* Ui_RebindWidget::btnStartMacro [inherited]

Definition at line 147 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), Ui_-RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.10 QPushButton* Ui_RebindWidget::btnStopMacro [inherited]

Definition at line 146 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), Ui_-RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.11 QPushButton* Ui_RebindWidget::cancelButton [inherited]

Definition at line 154 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.12 QComboBox* Ui_RebindWidget::dpiBox [inherited]

Definition at line 68 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget-::on_dpiButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.13 QRadioButton* Ui_RebindWidget::dpiButton [inherited]

Definition at line 62 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_dpiBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), and Ui_RebindWidget::setupUi().

12.79.3.14 QLabel* Ui_RebindWidget::dpiCustLabel [inherited]

Definition at line 78 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_dpiBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), and Ui_RebindWidget::setupUi().

12.79.3.15 QSpinBox* Ui_RebindWidget::dpiCustXBox [inherited]

Definition at line 73 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget::setBind(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.16 QSpinBox* Ui_RebindWidget::dpiCustYBox [inherited]

Definition at line 69 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget::setBind(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.17 QLabel* Ui_RebindWidget::dpiWarning [inherited]

Definition at line 74 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), and Ui_RebindWidget::setupUi().

12.79.3.18 QComboBox* Ui_RebindWidget::fnBox [inherited]

Definition at line 44 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_fnBox_currentIndexChanged(), RebindWidget::on_fnButton_clicked(), RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.19 QRadioButton* Ui_RebindWidget::fnButton [inherited]

Definition at line 56 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_fnBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.20 QGridLayout* Ui_RebindWidget::gridLayout [inherited]

Definition at line 61 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.21 QGridLayout* Ui_RebindWidget::gridLayout_10 [inherited]

Definition at line 144 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.22 QGridLayout* Ui_RebindWidget::gridLayout_2 [inherited]

Definition at line 41 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.23 QGridLayout* Ui_RebindWidget::gridLayout_3 [inherited]

Definition at line 93 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.24 QGridLayout* Ui_RebindWidget::gridLayout_4 [inherited]

Definition at line 111 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.25 QGridLayout* Ui_RebindWidget::gridLayout_5 [inherited]

Definition at line 82 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.26 QGridLayout* Ui_RebindWidget::gridLayout_8 [inherited]

Definition at line 134 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.27 QGroupBox* Ui_RebindWidget::groupBox [inherited]

Definition at line 145 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.28 QGroupBox* Ui_RebindWidget::groupBox_2 [inherited]

Definition at line 135 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.29 QGroupBox* Ui_RebindWidget::groupBox_3 [inherited]

Definition at line 141 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.30 QGroupBox* Ui_RebindWidget::groupBox_4 [inherited]

Definition at line 142 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.31 QHBoxLayout* Ui_RebindWidget::horizontalLayout [inherited]

Definition at line 150 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.32 QHBoxLayout* Ui_RebindWidget::horizontalLayout_2 [inherited]

Definition at line 122 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.33 QHBoxLayout* Ui_RebindWidget::horizontalLayout_3 [inherited]

Definition at line 127 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.34 QSpacerItem* Ui_RebindWidget::horizontalSpacer [inherited]

Definition at line 113 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.35 QSpacerItem* Ui_RebindWidget::horizontalSpacer_10 [inherited]

Definition at line 107 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.36 QSpacerItem* Ui_RebindWidget::horizontalSpacer_11 [inherited]

Definition at line 116 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.37 QSpacerItem* Ui_RebindWidget::horizontalSpacer_12 [inherited]

Definition at line 120 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.38 QSpacerItem* Ui_RebindWidget::horizontalSpacer_13 [inherited]

Definition at line 117 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.39 QSpacerItem* Ui_RebindWidget::horizontalSpacer_14 [inherited]

Definition at line 151 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.40 QSpacerItem* Ui_RebindWidget::horizontalSpacer_15 [inherited]

Definition at line 125 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.41 QSpacerItem* Ui_RebindWidget::horizontalSpacer_16 [inherited]

Definition at line 130 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.42 QSpacerItem* Ui_RebindWidget::horizontalSpacer_17 [inherited]

Definition at line 59 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.43 QSpacerItem* Ui_RebindWidget::horizontalSpacer_18 [inherited]

Definition at line 65 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.44 QSpacerItem* Ui_RebindWidget::horizontalSpacer_19 [inherited]

Definition at line 79 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.45 QSpacerItem* Ui_RebindWidget::horizontalSpacer_2 [inherited]

Definition at line 47 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.46 QSpacerItem* Ui_RebindWidget::horizontalSpacer_20 [inherited]

Definition at line 66 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.47 QSpacerItem* Ui_RebindWidget::horizontalSpacer_21 [inherited]

Definition at line 80 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.48 QSpacerItem* Ui_RebindWidget::horizontalSpacer_22 [inherited]

Definition at line 76 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.49 QSpacerItem* Ui_RebindWidget::horizontalSpacer_23 [inherited]

Definition at line 91 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.50 QSpacerItem* Ui_RebindWidget::horizontalSpacer_24 [inherited]

Definition at line 85 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.51 QSpacerItem* Ui_RebindWidget::horizontalSpacer_25 [inherited]

Definition at line 86 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.52 QSpacerItem* Ui_RebindWidget::horizontalSpacer_26 [inherited]

Definition at line 89 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.53 QSpacerItem* Ui_RebindWidget::horizontalSpacer_3 [inherited]

Definition at line 50 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.54 QSpacerItem* Ui_RebindWidget::horizontalSpacer_4 [inherited]

Definition at line 54 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.55 QSpacerItem* Ui_RebindWidget::horizontalSpacer_5 [inherited]

Definition at line 94 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.56 QSpacerItem* Ui_RebindWidget::horizontalSpacer_6 [inherited]

Definition at line 109 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.57 QSpacerItem* Ui_RebindWidget::horizontalSpacer_7 [inherited]

Definition at line 108 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.58 QSpacerItem* Ui_RebindWidget::horizontalSpacer_8 [inherited]

Definition at line 106 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.59 QSpacerItem* Ui_RebindWidget::horizontalSpacer_9 [inherited]

Definition at line 53 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.60 QWidget* Ui_RebindWidget::keyTab [inherited]

Definition at line 40 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.61 QWidget* Ui_RebindWidget::layoutWidget [inherited]

Definition at line 139 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.62 QWidget* Ui_RebindWidget::layoutWidget1 [inherited]

Definition at line 133 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.63 QWidget* Ui_RebindWidget::layoutWidget_2 [inherited]

Definition at line 143 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.64 QLabel* Ui_RebindWidget::lbl_macro [inherited]

Definition at line 149 of file ui_rebindwidget.h.

Referenced by RebindWidget::helpStatus(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.65 QComboBox* Ui_RebindWidget::lightBox [inherited]

Definition at line 102 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lightBox_currentIndexChanged(), RebindWidget::on_lightButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.66 QRadioButton* Ui_RebindWidget::lightButton [inherited]

Definition at line 104 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_lightBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_-RebindWidget::setupUi().

12.79.3.67 QCheckBox* Ui_RebindWidget::lightWrapBox [inherited]

Definition at line 97 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lightBox_currentIndexChanged(), Rebind-Widget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget-::setupUi().

12.79.3.68 QComboBox* Ui_RebindWidget::lockBox [inherited]

Definition at line 103 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lockBox_currentIndexChanged(), Rebind-Widget::on_lockButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::set-Selection(), and Ui_RebindWidget::setupUi().

12.79.3.69 QRadioButton* Ui_RebindWidget::lockButton [inherited]

Definition at line 100 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_lockBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_-RebindWidget::setupUi().

12.79.3.70 QWidget* Ui_RebindWidget::macroTab [inherited]

Definition at line 132 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.71 QComboBox* Ui_RebindWidget::mb2Box [inherited]

Definition at line 67 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mb2Box_currentIndexChanged(), Rebind-Widget::on_mb2Button_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::set-Selection(), and Ui_RebindWidget::setupUi().

12.79.3.72 QRadioButton* Ui_RebindWidget::mb2Button [inherited]

Definition at line 77 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mb2Box_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_-RebindWidget::setupUi().

12.79.3.73 QComboBox* Ui_RebindWidget::mbBox [inherited]

Definition at line 70 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mbBox_currentIndexChanged(), RebindWidget::on_mbButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.74 QRadioButton* Ui_RebindWidget::mbButton [inherited]

Definition at line 72 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mbBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.75 QComboBox* Ui_RebindWidget::mediaBox [inherited]

Definition at line 57 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mediaBox_currentIndexChanged(), RebindWidget::on_mediaButton_clicked(), RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.76 QRadioButton* Ui_RebindWidget::mediaButton [inherited]

Definition at line 51 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mediaBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.77 QComboBox* Ui_RebindWidget::modBox [inherited]

Definition at line 49 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modBox_currentIndexChanged(), RebindWidget::on_modButton_clicked(), RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.78 QRadioButton* Ui_RebindWidget::modButton [inherited]

Definition at line 55 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_modBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.79 QComboBox* Ui_RebindWidget::modeBox [inherited]

Definition at line 105 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modeBox_currentIndexChanged(), RebindWidget::on_modeButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.80 QRadioButton* Ui_RebindWidget::modeButton [inherited]

Definition at line 95 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_modeBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.81 QCheckBox* Ui_RebindWidget::modeWrapBox [inherited]

Definition at line 96 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modeBox_currentIndexChanged(), RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.82 QWidget* Ui_RebindWidget::mouseTab [inherited]

Definition at line 60 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.83 QComboBox* Ui_RebindWidget::numBox [inherited]

Definition at line 42 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_numBox_currentIndexChanged(), RebindWidget::on_numButton_clicked(), RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.84 QRadioButton* Ui_RebindWidget::numButton [inherited]

Definition at line 58 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_numBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.85 QLineEdit* Ui_RebindWidget::programKpBox [inherited]

Definition at line 115 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKpBox_textChanged(), RebindWidget::on_programKpButton_clicked(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.86 QCheckBox* Ui_RebindWidget::programKpButton [inherited]

Definition at line 114 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKpBox_textChanged(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), and Ui_RebindWidget::setupUi().

12.79.3.87 QWidget* Ui_RebindWidget::programKpExtra [inherited]

Definition at line 121 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKpBox_textChanged(), RebindWidget::RebindWidget(), and Ui_RebindWidget::setupUi().

12.79.3.88 QComboBox* Ui_RebindWidget::programKpModeBox [inherited]

Definition at line 124 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKpSIBox_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.89 QCheckBox* Ui_RebindWidget::programKpSlBox [inherited]

Definition at line 123 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.90 QLineEdit* Ui_RebindWidget::programKrBox [inherited]

Definition at line 118 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKrBox_textChanged(), RebindWidget::on_programKrButton_clicked(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.91 QCheckBox* Ui_RebindWidget::programKrButton [inherited]

Definition at line 119 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKrBox_textChanged(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), and Ui_RebindWidget::setupUi().

12.79.3.92 QWidget* Ui_RebindWidget::programKrExtra [inherited]

Definition at line 126 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKrBox_textChanged(), RebindWidget::RebindWidget(), and Ui_RebindWidget::setupUi().

12.79.3.93 QComboBox* Ui_RebindWidget::programKrModeBox [inherited]

Definition at line 129 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKrSlBox_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.94 QCheckBox* Ui_RebindWidget::programKrSlBox [inherited]

Definition at line 128 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.95 QWidget* Ui_RebindWidget::programTab [inherited]

Definition at line 110 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.96 QLabel* Ui_RebindWidget::progTipLabel [inherited]

Definition at line 131 of file ui_rebindwidget.h.

Referenced by RebindWidget::RebindWidget(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.97 QPlainTextEdit* Ui_RebindWidget::pteMacroBox [inherited]

Definition at line 136 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::convertMacroBox(), RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_pteMacroBox_textChanged(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.98 QPlainTextEdit* Ui_RebindWidget::pteMacroComment [inherited]

Definition at line 137 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.99 QPlainTextEdit* Ui_RebindWidget::pteMacroText [inherited]

Definition at line 138 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_btnStartMacro_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.100 QPushButton* Ui_RebindWidget::resetButton [inherited]

Definition at line 153 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.101 QTabWidget* Ui_RebindWidget::tabWidget [inherited]

Definition at line 39 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::retranslateUi(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.102 QComboBox* Ui_RebindWidget::typingBox [inherited]

Definition at line 43 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_typingBox_currentIndexChanged(), RebindWidget::on_typingButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.103 QRadioButton* Ui_RebindWidget::typingButton [inherited]

Definition at line 48 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_typingBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.104 QPushButton* Ui_RebindWidget::unbindButton [inherited]

Definition at line 152 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

12.79.3.105 QVBoxLayout* Ui_RebindWidget::verticalLayout [inherited]

Definition at line 38 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.106 QVBoxLayout* Ui_RebindWidget::verticalLayout_2 [inherited]

Definition at line 140 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.107 QSpacerItem* Ui_RebindWidget::verticalSpacer [inherited]

Definition at line 112 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.108 QSpacerItem* Ui_RebindWidget::verticalSpacer_10 [inherited]

Definition at line 45 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.109 QSpacerItem* Ui_RebindWidget::verticalSpacer_11 [inherited]

Definition at line 83 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.110 QSpacerItem* Ui_RebindWidget::verticalSpacer_2 [inherited]

Definition at line 63 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.111 QSpacerItem* Ui_RebindWidget::verticalSpacer_3 [inherited]

Definition at line 46 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.112 QSpacerItem* Ui_RebindWidget::verticalSpacer_4 [inherited]

Definition at line 52 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.113 QSpacerItem* Ui_RebindWidget::verticalSpacer_5 [inherited]

Definition at line 101 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.114 QSpacerItem* Ui_RebindWidget::verticalSpacer_6 [inherited]

Definition at line 99 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.115 QSpacerItem* Ui_RebindWidget::verticalSpacer_7 [inherited]

Definition at line 98 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.116 QSpacerItem* Ui_RebindWidget::verticalSpacer_8 [inherited]

Definition at line 64 of file ui_rebindwidget.h.

Referenced by Ui_RebindWidget::setupUi().

12.79.3.117 QComboBox* Ui_RebindWidget::wheelBox [inherited]

Definition at line 71 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_wheelBox_currentIndexChanged(), RebindWidget::on_wheelButton_clicked(), Ui_RebindWidget::retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and Ui_RebindWidget::setupUi().

12.79.3.118 QRadioButton* Ui_RebindWidget::wheelButton [inherited]

Definition at line 75 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_wheelBox_currentIndexChanged(), Ui_RebindWidget::retranslateUi(), and Ui_RebindWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_rebindwidget.h

12.80 RebindWidget Class Reference

```
#include <src/ckb/rebindwidget.h>
```

Inheritance diagram for RebindWidget:

Collaboration diagram for RebindWidget:

Public Member Functions

- RebindWidget (QWidget ∗parent)
- ∼RebindWidget ()
- void setBind (KbBind ∗newBind, KbProfile ∗newProfile)
- void setSelection (const QStringList &newSelection, bool applyPrevious=false)

Private Slots

- void applyChanges (const QStringList &keys, bool doUnbind)
- void on_applyButton_clicked ()
- void on_cancelButton_clicked ()
- void on_resetButton_clicked ()
- void on_unbindButton_clicked ()
- void on_typingBox_currentIndexChanged (int index)
- void on_modBox_currentIndexChanged (int index)
- void on_fnBox_currentIndexChanged (int index)
- void on_numBox_currentIndexChanged (int index)
- void on_mediaBox_currentIndexChanged (int index)
- void on_mbBox_currentIndexChanged (int index)
- void on_mb2Box_currentIndexChanged (int index)
- void on_wheelBox_currentIndexChanged (int index)
- void on_dpiBox_currentIndexChanged (int index)
- void on_modeBox_currentIndexChanged (int index)
- void on_lightBox_currentIndexChanged (int index)
- void on_lockBox_currentIndexChanged (int index)
- void on_programKpBox_textChanged (const QString &arg1)
- void on_programKrBox_textChanged (const QString &arg1)
- void on_animBox_currentIndexChanged (int index)
- void on_typingButton_clicked (bool checked)
- void on_modButton_clicked (bool checked)
- void on_fnButton_clicked (bool checked)

- void on_numButton_clicked (bool checked)
- void on_mediaButton_clicked (bool checked)
- void on_mbButton_clicked (bool checked)
- void on_mb2Button_clicked (bool checked)
- void on_wheelButton_clicked (bool checked)
- void on_dpiButton_clicked (bool checked)
- void on_modeButton_clicked (bool checked)
- void on_lightButton_clicked (bool checked)
- void on_lockButton_clicked (bool checked)
- void on_programKpButton_clicked (bool checked)
- void on_programKrButton_clicked (bool checked)
- void on_programKpSIBox_clicked (bool checked)
- void on_programKrSIBox_clicked (bool checked)
- void on_animButton_clicked (bool checked)
- void on_pteMacroBox_textChanged ()
- void on_btnStartMacro_clicked ()

  RebindWidget::on_btnStartMacro_clicked starts macro recording. A new notification channel and MacroReader are created to do the job.
- void on_btnStopMacro_clicked ()

  RebindWidget::on_btnStopMacro_clicked ends the macro recording. Notify channel ist closed, the ReaderThread is deleted if the notification is really down.
- void on_btnClearMacro_clicked ()

  RebindWidget::on_btnClearMacro_clicked changes the help info an the panel. The job of clearing the input panels is triggerd with signal/slot via the RebindWidget.ui file.

Private Member Functions

- void setBox (QWidget *box)
- void convertMacroBox ()

  RebindWidget::convertMacroBox converts the macroBox content. The KB sends each keypress as "key [+|-]<keyname><newline>".
- void helpStatus (int status)

  RebindWidget::helpStatus shows a help line in the ui.

Private Attributes

- Ui::RebindWidget * ui
- KbBind * bind
- KbProfile * profile
- QStringList selection
- QStringList typingKeys
- QStringList modKeys
- QStringList fnKeys
- QStringList numKeys
- QStringList mediaKeys
- QStringList mouseKeys
- QStringList mouseExtKeys
- QStringList wheelKeys
- MacroReader * macReader

  macReader holds the MacroReader when macro recording starts.

Static Private Attributes

- static const int TAB_KB = 0
- static const int TAB_MOUSE = 1
- static const int TAB_ANIM = 2
- static const int TAB_SPECIAL = 3
- static const int TAB_PROGRAM = 4
- static const int TAB_MACRO = 5

12.80.1 Detailed Description

Definition at line 15 of file rebindwidget.h.

12.80.2 Constructor & Destructor Documentation

12.80.2.1 RebindWidget::RebindWidget (QWidget * *parent*) [explicit]

Definition at line 9 of file rebindwidget.cpp.

References Ui_RebindWidget::fnBox, fnKeys, KeyMap::friendlyName(), Ui_RebindWidget::lightWrapBox, Ui_RebindWidget::mediaBox, mediaKeys, Ui_RebindWidget::modBox, Ui_RebindWidget::modeWrapBox, modKeys, mouseExtKeys, mouseKeys, Ui_RebindWidget::numBox, numKeys, Ui_RebindWidget::programKpExtra, Ui_RebindWidget::programKrExtra, Ui_RebindWidget::progTipLabel, Ui_RebindWidget::setupUi(), ui, and wheelKeys.

```
9                                       :
10     QWidget(parent),
11     ui(new Ui::RebindWidget),
12     bind(0), profile(0), macReader(0)
13 {
14     ui->setupUi(this);
15     ui->lightWrapBox->hide();
16     ui->modeWrapBox->hide();
17     ui->programKpExtra->hide();
18     ui->programKrExtra->hide();
19
20     // Populate key lists
21     modKeys << "caps" << "lshift" << "rshift" << "lctrl" << "rctrl" << "lwin" << "rwin" << "lalt" <<
       "ralt" << "rmenu" << "fn";
22     fnKeys << "esc" << "f1" << "f2" << "f3" << "f4" << "f5" << "f6" << "f7" << "f8" << "f9" << "f10"
      << "f11" << "f12" << "prtscn" << "scroll" << "pause" << "f13" << "f14" << "f15" << "f16" << "f17" << "f18" <
      < "f19" << "f20" << "ins" << "del" << "home" << "end" << "pgup" << "pgdn" << "power" << "lightup" << "
      lightdn" << "up" << "down" << "left" << "right";
23     numKeys << "numlock" << "num0" << "num1" << "num2" << "num3" << "num4" << "num5" << "num6" << "
      num7" << "num8" << "num9" << "numslash" << "numstar" << "numminus" << "numplus" << "numdot" << "numenter";
24     mediaKeys << "stop" << "prev" << "play" << "next" << "volup" << "voldn" << "mute" << "eject";
25     mouseKeys << "mouse1" << "mouse2" << "mouse3";
26     mouseExtKeys << "mouse4" << "mouse5" << "mouse6" << "mouse7" << "mouse8";
27     wheelKeys << "wheelup" << "wheeldn";
28     // Populate boxes
29     foreach(const QString& key, modKeys)
30         ui->modBox->addItem(KeyMap::friendlyName(key));
31     foreach(const QString& key, fnKeys)
32         ui->fnBox->addItem(KeyMap::friendlyName(key).replace("\n", " / "));
33     foreach(const QString& key, numKeys)
34         ui->numBox->addItem(KeyMap::friendlyName(key).remove("NumPad "));
35     foreach(const QString& key, mediaKeys)
36         ui->mediaBox->addItem(KeyMap::friendlyName(key));
37 #ifdef Q_OS_MACX
38     // Replace some OSX keys with their actual meanings
39     ui->modBox->setItemText(modKeys.indexOf("lwin") + 1, "Left Cmd");
40     ui->modBox->setItemText(modKeys.indexOf("rwin") + 1, "Right Cmd");
41     ui->modBox->setItemText(modKeys.indexOf("lalt") + 1, "Left Option");
42     ui->modBox->setItemText(modKeys.indexOf("ralt") + 1, "Right Option");
43     ui->fnBox->setItemText(fnKeys.indexOf("prtscn") + 1, "F13");
44     ui->fnBox->setItemText(fnKeys.indexOf("scroll") + 1, "F14");
45     ui->fnBox->setItemText(fnKeys.indexOf("pause") + 1, "F15");
46     ui->fnBox->setItemText(fnKeys.indexOf("f13") + 1, "F13 (Windows/Linux)");
47     ui->fnBox->setItemText(fnKeys.indexOf("f14") + 1, "F14 (Windows/Linux)");
48     ui->fnBox->setItemText(fnKeys.indexOf("f15") + 1, "F15 (Windows/Linux)");
49     ui->fnBox->setItemText(fnKeys.indexOf("ins") + 1, "Help");
50     ui->numBox->setItemText(numKeys.indexOf("numlock") + 1, "Clear");
51
52     // Add tip label
```

```
    ui->progTipLabel->setText("<p style=\"line-height:150%\">Tip: use the <font face=\"monospace\">open</font> command to launch a file, directory, or app. For instance, to start Safari:<br /><font face=\"monospace\">  open /Applications/Safari.app</font></p>");
#else
    ui->progTipLabel->setText("<p style=\"line-height:150%\">Tip: use <font face=\"monospace\">xdg-open</font> to launch a file or directory. For instance, to open your home folder:<br /><font face=\"monospace\">  xdg-open " + QStandardPaths::writableLocation(QStandardPaths::HomeLocation) + "</font></p>");
#endif
}
```

Here is the call graph for this function:

12.80.2.2 RebindWidget::~RebindWidget ( )

Definition at line 59 of file rebindwidget.cpp.

References ui.

```
59                              {
60     delete ui;
61 }
```

12.80.3 Member Function Documentation

12.80.3.1 void RebindWidget::applyChanges (const QStringList & *keys*, bool *doUnbind*) [private],[slot]

Definition at line 327 of file rebindwidget.cpp.

References KeyAction::animAction(), Ui_RebindWidget::animBox, Ui_RebindWidget::animKrBox, KbLight::animList(), Ui_RebindWidget::animOnceBox, bind, DPI_OFFSET, KeyAction::dpiAction(), Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiCustXBox, Ui_RebindWidget::dpiCustYBox, Ui_RebindWidget::fnBox, fnKeys, KbAnim::guid(), KbBind::light(), KeyAction::lightAction(), Ui_RebindWidget::lightBox, Ui_RebindWidget::lightWrapBox, KeyAction::lockAction(), Ui_RebindWidget::lockBox, KeyAction::macroAction(), Ui_RebindWidget::mb2Box, Ui_RebindWidget::mbBox, Ui_RebindWidget::mediaBox, mediaKeys, Ui_RebindWidget::modBox, KeyAction::modeAction(), Ui_RebindWidget::modeBox, Ui_RebindWidget::modeWrapBox, modKeys, mouseExtKeys, mouseKeys, KbBind::noAction(), Ui_RebindWidget::numBox, numKeys, KeyAction::PROGRAM_PR_MULTI, KeyAction::PROGRAM_RE_INDEF, KeyAction::PROGRAM_RE_KPSTOP, KeyAction::PROGRAM_RE_MULTI, KeyAction::programAction(), Ui_RebindWidget::programKpBox, Ui_RebindWidget::programKpModeBox, Ui_RebindWidget::programKpSIBox, Ui_RebindWidget::programKrBox, Ui_RebindWidget::programKrModeBox, Ui_RebindWidget::programKrSIBox, Ui_RebindWidget::pteMacroBox, Ui_RebindWidget::pteMacroComment, Ui_RebindWidget::pteMacroText, KbBind::setAction(), Ui_RebindWidget::typingBox, typingKeys, ui, Ui_RebindWidget::wheelBox, and wheelKeys.

Referenced by on_applyButton_clicked(), and setSelection().

```
327                                                                 {
328     if(ui->typingBox->currentIndex() > 0)
329         bind->setAction(keys, typingKeys[ui->typingBox->currentIndex() -
```

```
1]);
  else if(ui->modBox->currentIndex() > 0)
      bind->setAction(keys, modKeys[ui->modBox->currentIndex() - 1]);
  else if(ui->fnBox->currentIndex() > 0)
      bind->setAction(keys, fnKeys[ui->fnBox->currentIndex() - 1]);
  else if(ui->numBox->currentIndex() > 0)
      bind->setAction(keys, numKeys[ui->numBox->currentIndex() - 1]);
  else if(ui->mediaBox->currentIndex() > 0)
      bind->setAction(keys, mediaKeys[ui->mediaBox->currentIndex() - 1]);
  else if(ui->mbBox->currentIndex() > 0)
      bind->setAction(keys, mouseKeys[ui->mbBox->currentIndex() - 1]);
  else if(ui->mb2Box->currentIndex() > 0)
      bind->setAction(keys, mouseExtKeys[ui->mb2Box->currentIndex() - 1]);
  else if(ui->wheelBox->currentIndex() > 0)
      bind->setAction(keys, wheelKeys[ui->wheelBox->currentIndex() - 1]);
  else if(ui->dpiBox->currentIndex() > 0)
      bind->setAction(keys, KeyAction::dpiAction(ui->dpiBox->currentIndex() - DPI_OFFSET, ui->dpiCustXBox->value(), ui->dpiCustYBox->value()));
  else if(ui->modeBox->currentIndex() > 0)
      bind->setAction(keys, KeyAction::modeAction(ui->modeBox->currentIndex() - 3 - (ui->modeWrapBox->isChecked() && ui->modeBox->currentIndex() < 3 ? 2 : 0)));
  else if(ui->lightBox->currentIndex() > 0)
      bind->setAction(keys, KeyAction::lightAction(ui->lightBox->currentIndex() - 1 + (ui->lightWrapBox->isChecked() ? 2 : 0)));
  else if(ui->lockBox->currentIndex() > 0)
      bind->setAction(keys, KeyAction::lockAction(ui->lockBox->currentIndex() - 1));
  else if(ui->animBox->currentIndex() > 0){
      KbAnim* anim = bind->light()->animList().at(ui->animBox->currentIndex() - 1);
      bind->setAction(keys, KeyAction::animAction(anim->guid(), !ui->animOnceBox->isChecked(), ui->animKrBox->isChecked()));
  } else if(!ui->programKpBox->text().isEmpty() || !ui->programKrBox->text().isEmpty()){
      int kpStop = 0, krStop = 0;
      if(!ui->programKpBox->text().isEmpty()){
          if(!ui->programKpSIBox->isChecked())
              kpStop = KeyAction::PROGRAM_PR_MULTI;
          else
              kpStop = ui->programKpModeBox->currentIndex();
      }
      if(!ui->programKrBox->text().isEmpty()){
          if(!ui->programKrSIBox->isChecked())
              krStop = KeyAction::PROGRAM_RE_MULTI;
          else if(ui->programKrModeBox->currentIndex() == 0)
              krStop = KeyAction::PROGRAM_RE_INDEF;
          else
              krStop = KeyAction::PROGRAM_RE_KPSTOP;
      }
      bind->setAction(keys, KeyAction::programAction(ui->programKpBox->text(), ui->programKrBox->text(), kpStop | krStop));
  } else if (ui->pteMacroBox->toPlainText().length() > 0) {
      // G-key macro handling:
      // Set the macro definiton for all keys selected (indeed, it may be multiple keys).
      // First, concat the Macro Key Definion and the Macro plain text
      // after escaping possible colos in the parts for Macro Text and Macro Comment.
      QString mac;
      mac = ui->pteMacroComment->toPlainText().replace(":", "&das_IST_31N_col0n;");
      mac = ui->pteMacroText->toPlainText().replace(":", "&das_IST_31N_col0n;") + ":" + mac;
      mac = ui->pteMacroBox->toPlainText() + ":" + mac;
      bind->setAction(keys, KeyAction::macroAction(mac));
  } else if(doUnbind)
      bind->noAction(keys);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.80.3.2 void RebindWidget::convertMacroBox ( ) [private]

the ckb-daemon needs a shorter format, only " [+|-]<keyname>"

That function does the conversion.

Definition at line 776 of file rebindwidget.cpp.

References Ui_RebindWidget::pteMacroBox, and ui.

Referenced by on_btnStopMacro_clicked().

```
776                                 {
777     QString in;
778
779     in = ui->pteMacroBox->toPlainText();
780     in.replace (QRegExp("\n"), ",");
781     in.replace (QRegExp("key "), "");
782     ui->pteMacroBox->setPlainText(in);
783 }
```

Here is the caller graph for this function:

12.80.3.3 void RebindWidget::helpStatus (int *status*) [private]

Parameters

status	determines what to display.

Definition at line 752 of file rebindwidget.cpp.

References Ui_RebindWidget::lbl_macro, and ui.

Referenced by on_btnClearMacro_clicked(), on_btnStartMacro_clicked(), on_btnStopMacro_clicked(), and setBox().

```
752                                         {
753     switch (status) {
754     case 1:
755         ui->lbl_macro->setText("Type in a macro name in the comment box and click start.");
756         break;
757     case 2:
758         ui->lbl_macro->setText("Type your macro and click stop when finished.");
759         break;
760     case 3:
761         ui->lbl_macro->setText("Click Apply or change values in Macro Key Actions in advance.");
762         break;
763     default:
764         ui->lbl_macro->setText(QString("Oops: Some magic in RebindWidget::helpStatus (%1)").arg(
      status));
765     }
766 }
```

Here is the caller graph for this function:

12.80.3.4 void RebindWidget::on_animBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 592 of file rebindwidget.cpp.

References Ui_RebindWidget::animBox, Ui_RebindWidget::animButton, setBox(), and ui.

```
592                                                 {
593     if(index == 0)
```

```
        ui->animButton->setChecked(false);
    else {
        ui->animButton->setChecked(true);
        setBox(ui->animBox);
    }
}
```

Here is the call graph for this function:

12.80.3.5 void RebindWidget::on_animButton_clicked (bool *checked*) [private],[slot]

Definition at line 689 of file rebindwidget.cpp.

References Ui_RebindWidget::animBox, and ui.

```
689                                                 {
690     if(checked && ui->animBox->currentIndex() == 0)
691         ui->animBox->setCurrentIndex(1);
692 }
```

12.80.3.6 void RebindWidget::on_applyButton_clicked ( ) [private],[slot]

Definition at line 386 of file rebindwidget.cpp.

References applyChanges(), on_btnStopMacro_clicked(), and selection.

```
386                                         {
387     // Normally, this should be done via signalling.
388     // Because there is no serarate thread, we have to call it directly
389     // (otherwise we could do Key char conversion step by step,
390     // but so it is more easy to change the key definition):
391     on_btnStopMacro_clicked();
392     applyChanges(selection, true);
393 }
```

Here is the call graph for this function:

12.80.3.7 void RebindWidget::on_btnClearMacro_clicked ( ) [private],[slot]

Definition at line 744 of file rebindwidget.cpp.

References helpStatus().

```
744                                                 {
745     helpStatus(1);
746 }
```

Here is the call graph for this function:

12.80.3.8 void RebindWidget::on_btnStartMacro_clicked ( ) [private],[slot]

The UI is protected against false clicking (e.g. if you type start and than Apply, the channel is closed in wrong order).

At this time, all neccessary params like macroNumber, macroPath, cmdFile etc. had been cached.

Definition at line 703 of file rebindwidget.cpp.

References Ui_RebindWidget::applyButton, bind, Ui_RebindWidget::btnStartMacro, Ui_RebindWidget::btnStopMacro, KbBind::getMacroNumber(), KbBind::getMacroPath(), KbBind::handleNotificationChannel(), helpStatus(), macReader, Ui_RebindWidget::pteMacroBox, Ui_RebindWidget::pteMacroText, Ui_RebindWidget::resetButton, ui, and Ui_RebindWidget::unbindButton.

```
703                                                 {
704     if (!macReader) {
705         bind->handleNotificationChannel(true);
706         macReader = new MacroReader(bind->getMacroNumber(),
      bind->getMacroPath(), ui->pteMacroBox, ui->
      pteMacroText);
707         // because of the second thread we need to disable three of the four bottom buttons.
708         // Clicking "Stop" will enable them again.
709         ui->applyButton->setEnabled(false);
710         ui->resetButton->setEnabled(false);
711         ui->unbindButton->setEnabled(false);
712         ui->btnStartMacro->setEnabled(false);
713         ui->btnStopMacro->setEnabled(true);
714         helpStatus(2);
715     }
716 }
```

Here is the call graph for this function:

12.80.3.9 void RebindWidget::on_btnStopMacro_clicked ( ) [private],[slot]

Afterwards, the characters in the MacroBox are changed from KB-out format to cmd-in format. At last the UI changes to the new state.

Definition at line 725 of file rebindwidget.cpp.

References Ui_RebindWidget::applyButton, bind, Ui_RebindWidget::btnStartMacro, Ui_RebindWidget::btnStopMacro, convertMacroBox(), KbBind::handleNotificationChannel(), helpStatus(), macReader, Ui_RebindWidget::resetButton, ui, and Ui_RebindWidget::unbindButton.

Referenced by on_applyButton_clicked().

```
725                                         {
726     if (macReader) {
727         bind->handleNotificationChannel(false);
728         delete macReader;
729         macReader = 0;
730         convertMacroBox();
731         ui->applyButton->setEnabled(true);
732         ui->resetButton->setEnabled(true);
733         ui->unbindButton->setEnabled(true);
734         ui->btnStartMacro->setEnabled(true);
735         ui->btnStopMacro->setEnabled(false);
736         helpStatus(3);
737     }
738 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.80.3.10 void RebindWidget::on_cancelButton_clicked ( ) [private],[slot]

Definition at line 395 of file rebindwidget.cpp.

References selection, and setSelection().

```
395                                         {
396     // Re-load selection
397     setSelection(selection);
398 }
```

Here is the call graph for this function:

12.80.3.11 void RebindWidget::on_dpiBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 518 of file rebindwidget.cpp.

References DPI_CUST_IDX, Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiButton, Ui_RebindWidget::dpiCustLabel, Ui_RebindWidget::dpiCustXBox, Ui_RebindWidget::dpiCustYBox, setBox(), and ui.

```
518                                                     {
519     if(index != DPI_CUST_IDX){
520         // Clear custom DPI
521         ui->dpiCustXBox->setEnabled(false);
522         ui->dpiCustYBox->setEnabled(false);
523         ui->dpiCustLabel->setEnabled(false);
524     } else {
525         ui->dpiCustXBox->setEnabled(true);
526         ui->dpiCustYBox->setEnabled(true);
527         ui->dpiCustLabel->setEnabled(true);
528     }
529     if(index == 0)
530         ui->dpiButton->setChecked(false);
531     else {
532         ui->dpiButton->setChecked(true);
533         setBox(ui->dpiBox);
534     }
535 }
```

Here is the call graph for this function:

12.80.3.12 void RebindWidget::on_dpiButton_clicked (bool *checked*) [private],[slot]

Definition at line 674 of file rebindwidget.cpp.

References Ui_RebindWidget::dpiBox, and ui.

```
674                                                 {
675     if(checked && ui->dpiBox->currentIndex() == 0)
676         ui->dpiBox->setCurrentIndex(1);
677 }
```

12.80.3.13 void RebindWidget::on_fnBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 464 of file rebindwidget.cpp.

References Ui_RebindWidget::fnBox, Ui_RebindWidget::fnButton, setBox(), and ui.

```
464                                                         {
465     if(index == 0)
466         ui->fnButton->setChecked(false);
467     else {
468         ui->fnButton->setChecked(true);
469         setBox(ui->fnBox);
470     }
471 }
```

Here is the call graph for this function:

12.80.3.14 void RebindWidget::on_fnButton_clicked (bool *checked*) [private],[slot]

Definition at line 611 of file rebindwidget.cpp.

References Ui_RebindWidget::fnBox, and ui.

```
611                                                 {
612     if(checked && ui->fnBox->currentIndex() == 0)
613         ui->fnBox->setCurrentIndex(1);
614 }
```

12.80.3.15 void RebindWidget::on_lightBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 550 of file rebindwidget.cpp.

References Ui_RebindWidget::lightBox, Ui_RebindWidget::lightButton, Ui_RebindWidget::lightWrapBox, setBox(), and ui.

```
550                                                         {
551     if(index == 0){
552         ui->lightButton->setChecked(false);
553         ui->lightWrapBox->hide();
554     } else {
555         ui->lightWrapBox->show();
556         ui->lightButton->setChecked(true);
557         setBox(ui->lightBox);
558     }
559 }
```

Here is the call graph for this function:

12.80.3.16 void RebindWidget::on_lightButton_clicked (bool *checked*) [private],[slot]

Definition at line 631 of file rebindwidget.cpp.

References Ui_RebindWidget::lightBox, and ui.

```
631                                                 {
632     if(checked && ui->lightBox->currentIndex() == 0)
633         ui->lightBox->setCurrentIndex(1);
634 }
```

12.80.3.17 void RebindWidget::on_lockBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 561 of file rebindwidget.cpp.

References Ui_RebindWidget::lockBox, Ui_RebindWidget::lockButton, setBox(), and ui.

```
561                                                         {
562     if(index == 0)
563         ui->lockButton->setChecked(false);
564     else {
565         ui->lockButton->setChecked(true);
566         setBox(ui->lockBox);
567     }
568 }
```

Here is the call graph for this function:

12.80.3.18 void RebindWidget::on_lockButton_clicked (bool *checked*) [private],[slot]

Definition at line 636 of file rebindwidget.cpp.

References Ui_RebindWidget::lockBox, and ui.

```
636                                                 {
637     if(checked && ui->lockBox->currentIndex() == 0)
638         ui->lockBox->setCurrentIndex(1);
639 }
```

12.80.3.19 void RebindWidget::on_mb2Box_currentIndexChanged (int *index*) [private],[slot]

Definition at line 500 of file rebindwidget.cpp.

References Ui_RebindWidget::mb2Box, Ui_RebindWidget::mb2Button, setBox(), and ui.

```
500                                                         {
501     if(index == 0)
502         ui->mb2Button->setChecked(false);
503     else {
504         ui->mb2Button->setChecked(true);
505         setBox(ui->mb2Box);
506     }
507 }
```

Here is the call graph for this function:

12.80.3.20 void RebindWidget::on_mb2Button_clicked (bool *checked*) [private],[slot]

Definition at line 664 of file rebindwidget.cpp.

References Ui_RebindWidget::mb2Box, and ui.

```
664                                                 {
665     if(checked && ui->mb2Box->currentIndex() == 0)
666         ui->mb2Box->setCurrentIndex(1);
667 }
```

12.80.3.21 void RebindWidget::on_mbBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 491 of file rebindwidget.cpp.

References Ui_RebindWidget::mbBox, Ui_RebindWidget::mbButton, setBox(), and ui.

```
491                                                         {
492     if(index == 0)
493         ui->mbButton->setChecked(false);
494     else {
495         ui->mbButton->setChecked(true);
496         setBox(ui->mbBox);
497     }
498 }
```

Here is the call graph for this function:

12.80.3.22 void RebindWidget::on_mbButton_clicked (bool *checked*) [private],[slot]

Definition at line 659 of file rebindwidget.cpp.

References Ui_RebindWidget::mbBox, and ui.

```
659                                                 {
660     if(checked && ui->mbBox->currentIndex() == 0)
661         ui->mbBox->setCurrentIndex(1);
662 }
```

12.80.3.23 void RebindWidget::on_mediaBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 482 of file rebindwidget.cpp.

References Ui_RebindWidget::mediaBox, Ui_RebindWidget::mediaButton, setBox(), and ui.

```
482                                                                 {
483     if(index == 0)
484         ui->mediaButton->setChecked(false);
485     else {
486         ui->mediaButton->setChecked(true);
487         setBox(ui->mediaBox);
488     }
489 }
```

Here is the call graph for this function:

12.80.3.24 void RebindWidget::on_mediaButton_clicked (bool *checked*) [private],[slot]

Definition at line 621 of file rebindwidget.cpp.

References Ui_RebindWidget::mediaBox, and ui.

```
621                                                 {
622     if(checked && ui->mediaBox->currentIndex() == 0)
623         ui->mediaBox->setCurrentIndex(1);
624 }
```

12.80.3.25 void RebindWidget::on_modBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 455 of file rebindwidget.cpp.

References Ui_RebindWidget::modBox, Ui_RebindWidget::modButton, setBox(), and ui.

```
455                                                     {
456     if(index == 0)
457         ui->modButton->setChecked(false);
458     else {
459         ui->modButton->setChecked(true);
460         setBox(ui->modBox);
461     }
462 }
```

Here is the call graph for this function:

12.80.3.26 void RebindWidget::on_modButton_clicked (bool *checked*) [private],[slot]

Definition at line 606 of file rebindwidget.cpp.

References Ui_RebindWidget::modBox, and ui.

```
606                                             {
607     if(checked && ui->modBox->currentIndex() == 0)
608         ui->modBox->setCurrentIndex(1);
609 }
```

12.80.3.27 void RebindWidget::on_modeBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 537 of file rebindwidget.cpp.

References Ui_RebindWidget::modeBox, Ui_RebindWidget::modeButton, Ui_RebindWidget::modeWrapBox, setBox(), and ui.

```
537                                                     {
538     if(index == 1 || index == 2)
539         ui->modeWrapBox->show();
540     else
541         ui->modeWrapBox->hide();
542     if(index == 0)
543         ui->modeButton->setChecked(false);
544     else {
545         ui->modeButton->setChecked(true);
546         setBox(ui->modeBox);
547     }
548 }
```

Here is the call graph for this function:

12.80.3.28 void RebindWidget::on_modeButton_clicked (bool *checked*) [private],[slot]

Definition at line 626 of file rebindwidget.cpp.

References Ui_RebindWidget::modeBox, and ui.

```
626                                                 {
627     if(checked && ui->modeBox->currentIndex() == 0)
628         ui->modeBox->setCurrentIndex(1);
629 }
```

12.80.3.29 void RebindWidget::on_numBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 473 of file rebindwidget.cpp.

References Ui_RebindWidget::numBox, Ui_RebindWidget::numButton, setBox(), and ui.

```
473                                                         {
474     if(index == 0)
475         ui->numButton->setChecked(false);
476     else {
477         ui->numButton->setChecked(true);
478         setBox(ui->numBox);
479     }
480 }
```

Here is the call graph for this function:

12.80.3.30 void RebindWidget::on_numButton_clicked (bool *checked*) [private],[slot]

Definition at line 616 of file rebindwidget.cpp.

References Ui_RebindWidget::numBox, and ui.

```
616                                                 {
617     if(checked && ui->numBox->currentIndex() == 0)
618         ui->numBox->setCurrentIndex(1);
619 }
```

12.80.3.31 void RebindWidget::on_programKpBox_textChanged (const QString & *arg1*) [private],[slot]

Definition at line 570 of file rebindwidget.cpp.

References Ui_RebindWidget::programKpBox, Ui_RebindWidget::programKpButton, Ui_RebindWidget::programKpExtra, setBox(), and ui.

```
570                                                         {
571     if(arg1.isEmpty()){
572         ui->programKpButton->setChecked(false);
573         ui->programKpExtra->hide();
574     } else {
575         ui->programKpButton->setChecked(true);
576         setBox(ui->programKpBox);
577         ui->programKpExtra->show();
578     }
579 }
```

Here is the call graph for this function:

12.80.3.32 void RebindWidget::on_programKpButton_clicked (bool *checked*) [private],[slot]

Definition at line 641 of file rebindwidget.cpp.

References Ui_RebindWidget::programKpBox, setBox(), and ui.

```
641                                                     {
642     if(!checked){
643         ui->programKpBox->setText("");
644     } else if(ui->programKpBox->text().isEmpty()){
645         ui->programKpBox->setFocus();
646         setBox(ui->programKpBox);
647     }
648 }
```

Here is the call graph for this function:

12.80.3.33 void RebindWidget::on_programKpSlBox_clicked (bool *checked*) [private],[slot]

Definition at line 679 of file rebindwidget.cpp.

References Ui_RebindWidget::programKpModeBox, and ui.

```
679                                                     {
680     ui->programKpModeBox->setCurrentIndex(0);
681     ui->programKpModeBox->setEnabled(checked);
682 }
```

12.80.3.34 void RebindWidget::on_programKrBox_textChanged (const QString & *arg1*) [private],[slot]

Definition at line 581 of file rebindwidget.cpp.

References Ui_RebindWidget::programKrBox, Ui_RebindWidget::programKrButton, Ui_RebindWidget::programKrExtra, setBox(), and ui.

```
581                                                     {
582     if(arg1.isEmpty()){
583         ui->programKrButton->setChecked(false);
584         ui->programKrExtra->hide();
585     } else {
586         ui->programKrButton->setChecked(true);
587         setBox(ui->programKrBox);
588         ui->programKrExtra->show();
589     }
590 }
```

Here is the call graph for this function:

12.80.3.35 void RebindWidget::on_programKrButton_clicked (bool *checked*) [private],[slot]

Definition at line 650 of file rebindwidget.cpp.

References Ui_RebindWidget::programKrBox, setBox(), and ui.

```
650                                                         {
651     if(!checked){
652         ui->programKrBox->setText("");
653     } else if(ui->programKrBox->text().isEmpty()){
654         ui->programKrBox->setFocus();
655         setBox(ui->programKrBox);
656     }
657 }
```

Here is the call graph for this function:

12.80.3.36 void RebindWidget::on_programKrSlBox_clicked (bool *checked*) [private],[slot]

Definition at line 684 of file rebindwidget.cpp.

References Ui_RebindWidget::programKrModeBox, and ui.

```
684                                                         {
685     ui->programKrModeBox->setCurrentIndex(0);
686     ui->programKrModeBox->setEnabled(checked);
687 }
```

12.80.3.37 void RebindWidget::on_pteMacroBox_textChanged ( ) [private],[slot]

Definition at line 449 of file rebindwidget.cpp.

References Ui_RebindWidget::pteMacroBox, setBox(), and ui.

```
449                                                 {
450     if (ui->pteMacroBox->toPlainText().length() > 0) {
451         setBox(ui->pteMacroBox);
452     }
453 }
```

Here is the call graph for this function:

12.80.3.38 void RebindWidget::on_resetButton_clicked ( ) [private],[slot]

Definition at line 400 of file rebindwidget.cpp.

References bind, KbBind::resetAction(), and selection.

```
400                                         {
401     bind->resetAction(selection);
402 }
```

Here is the call graph for this function:

12.80.3.39 void RebindWidget::on_typingBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 440 of file rebindwidget.cpp.

References setBox(), Ui_RebindWidget::typingBox, Ui_RebindWidget::typingButton, and ui.

```
440                                                         {
441     if(index == 0)
442         ui->typingButton->setChecked(false);
443     else {
444         ui->typingButton->setChecked(true);
445         setBox(ui->typingBox);
446     }
447 }
```

Here is the call graph for this function:

12.80.3.40 void RebindWidget::on_typingButton_clicked (bool *checked*) [private],[slot]

Definition at line 601 of file rebindwidget.cpp.

References Ui_RebindWidget::typingBox, and ui.

```
601                                                 {
602     if(checked && ui->typingBox->currentIndex() == 0)
603         ui->typingBox->setCurrentIndex(1);
604 }
```

12.80.3.41 void RebindWidget::on_unbindButton_clicked ( ) [private],[slot]

Definition at line 404 of file rebindwidget.cpp.

References bind, KbBind::noAction(), and selection.

```
404                                         {
405     bind->noAction(selection);
406 }
```

Here is the call graph for this function:

12.80.3.42 void RebindWidget::on_wheelBox_currentIndexChanged (int *index*) [private],[slot]

Definition at line 509 of file rebindwidget.cpp.

References setBox(), ui, Ui_RebindWidget::wheelBox, and Ui_RebindWidget::wheelButton.

```
509                                                     {
510     if(index == 0)
511         ui->wheelButton->setChecked(false);
512     else {
513         ui->wheelButton->setChecked(true);
514         setBox(ui->wheelBox);
515     }
516 }
```

Here is the call graph for this function:

12.80.3.43 void RebindWidget::on_wheelButton_clicked (bool *checked*) [private],[slot]

Definition at line 669 of file rebindwidget.cpp.

References ui, and Ui_RebindWidget::wheelBox.

```
669                                                 {
670     if(checked && ui->wheelBox->currentIndex() == 0)
671         ui->wheelBox->setCurrentIndex(1);
672 }
```

12.80.3.44 void RebindWidget::setBind (KbBind * *newBind,* KbProfile * *newProfile*)

Definition at line 63 of file rebindwidget.cpp.

References bind, KeyMap::byPosition(), KbBind::defaultAction(), KbPerf::dpi(), KbPerf::DPI_COUNT, Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiButton, Ui_RebindWidget::dpiCustLabel, Ui_RebindWidget::dpiCustXBox, Ui_RebindWidget::dpiCustYBox, Ui_RebindWidget::dpiWarning, fnKeys, Key::friendlyName(), KeyMap::isISO(), KbBind::isMouse(), KeyAction::isNormal(), KeyMap::K95, KeyMap::layout(), KbBind::map(), mediaKeys, Ui_RebindWidget::modeBox, KbProfile::modes(), modKeys, KbMode::name(), numKeys, KbBind::perf(), profile, setSelection(), Ui_RebindWidget::typingBox, typingKeys, and ui.

Referenced by KbBindWidget::newLayout(), and KbBindWidget::setBind().

```
63                                                                  {
64     bind = newBind;
65     profile = newProfile;
66     setSelection(QStringList());
67
68     // Populate typing keys by position
69     ui->typingBox->clear();
70     ui->typingBox->addItem(" ");
71     typingKeys.clear();
72     // Use the K95 map as it has all keys
73     const KeyMap& map = KeyMap(KeyMap::K95, bind->map().
      layout());
74     foreach(const QString& name, map.byPosition()){
75         KeyAction action(KbBind::defaultAction(name));
76         if(action.isNormal() && !modKeys.contains(name) && !fnKeys.contains(name) && !
      numKeys.contains(name) && !mediaKeys.contains(name) && name != "enter" && name != "tab" &&
      name != "bspace"){
77             const Key& pos = map[name];
78             QString friendly = pos.friendlyName();
79             ui->typingBox->addItem(friendly);
80             typingKeys.append(name);
81         }
82     }
83     typingKeys << "enter" << "tab" << "bspace";
84     ui->typingBox->addItem("Enter");
85     ui->typingBox->addItem("Tab");
86     ui->typingBox->addItem("Backspace");
87     if(!map.isISO()){
88         // Add ISO backslash (aka KEY_102ND) to ANSI options
89         typingKeys << "bslash_iso";
90         ui->typingBox->addItem("Backslash (ISO layout)");
91     }
92
93     // Populate mode list
94     ui->modeBox->clear();
95     ui->modeBox->addItem(" ");
96     ui->modeBox->addItem("(Previous)");
97     ui->modeBox->addItem("(Next)");
98     int idx = 1;
99     foreach(KbMode* mode, newProfile->modes())
100         ui->modeBox->addItem(QString("%1: %2").arg(idx++).arg(mode->
      name()));
101
102     // Enable/disable DPI based on device
103     if(bind->isMouse()){
104         ui->dpiButton->setEnabled(true);
105         ui->dpiBox->setEnabled(true);
106         ui->dpiWarning->hide();
107         // Fill DPI slots
108         const KbPerf* perf = bind->perf();
109         for(int i = 0; i < KbPerf::DPI_COUNT; i++){
110             bool sniper = (i == 0);
111             int boxIdx = i + 3;
```

```
            QPoint dpi = perf->dpi(i);
            QString text = tr(sniper ? "Sniper:\t%1 x %2" : "%3:\t%1 x %2").arg(dpi.x()).arg(dpi.y());
            if(!sniper) text = text.arg(i);
            ui->dpiBox->setItemText(boxIdx, text);
        }
    } else {
        ui->dpiButton->setEnabled(false);
        ui->dpiBox->setEnabled(false);
        ui->dpiWarning->show();
    }
    // Always disable custom DPI boxes until selected
    ui->dpiCustXBox->setEnabled(false);
    ui->dpiCustYBox->setEnabled(false);
    ui->dpiCustLabel->setEnabled(false);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.80.3.45 void RebindWidget::setBox (QWidget * *box*) [private]

Definition at line 408 of file rebindwidget.cpp.

References Ui_RebindWidget::animBox, Ui_RebindWidget::dpiBox, Ui_RebindWidget::fnBox, helpStatus(), Ui_RebindWidget::lightBox, Ui_RebindWidget::lockBox, Ui_RebindWidget::mb2Box, Ui_RebindWidget::mbBox, Ui_RebindWidget::mediaBox, Ui_RebindWidget::modBox, Ui_RebindWidget::modeBox, Ui_RebindWidget::numBox, Ui_RebindWidget::programKpBox, Ui_RebindWidget::programKpButton, Ui_RebindWidget::programKrBox, Ui_RebindWidget::programKrButton, Ui_RebindWidget::pteMacroBox, Ui_RebindWidget::typingBox, ui, and Ui_RebindWidget::wheelBox.

Referenced by on_animBox_currentIndexChanged(), on_dpiBox_currentIndexChanged(), on_fnBox_currentIndexChanged(), on_lightBox_currentIndexChanged(), on_lockBox_currentIndexChanged(), on_mb2Box_currentIndexChanged(), on_mbBox_currentIndexChanged(), on_mediaBox_currentIndexChanged(), on_modBox_currentIndexChanged(), on_modeBox_currentIndexChanged(), on_numBox_currentIndexChanged(), on_programKpBox_textChanged(), on_programKpButton_clicked(), on_programKrBox_textChanged(), on_programKrButton_clicked(), on_pteMacroBox_textChanged(), on_typingBox_currentIndexChanged(), on_wheelBox_currentIndexChanged(), and setSelection().

```
408                                     {
409     // Un-select every item except for the current one.
410     // on_*_currentIndexChanged will take care of deselecting the checkbox.
411     // Key
412     if(box != ui->typingBox) ui->typingBox->setCurrentIndex(0);
413     if(box != ui->modBox) ui->modBox->setCurrentIndex(0);
414     if(box != ui->fnBox) ui->fnBox->setCurrentIndex(0);
415     if(box != ui->numBox) ui->numBox->setCurrentIndex(0);
416     if(box != ui->mediaBox) ui->mediaBox->setCurrentIndex(0);
417     // Mouse
418     if(box != ui->mbBox) ui->mbBox->setCurrentIndex(0);
419     if(box != ui->mb2Box) ui->mb2Box->setCurrentIndex(0);
420     if(box != ui->wheelBox) ui->wheelBox->setCurrentIndex(0);
421     if(box != ui->dpiBox) ui->dpiBox->setCurrentIndex(0);
422     // Anim
423     if(box != ui->animBox) ui->animBox->setCurrentIndex(0);
424     // Special
425     if(box != ui->modeBox) ui->modeBox->setCurrentIndex(0);
426     if(box != ui->lightBox) ui->lightBox->setCurrentIndex(0);
427     if(box != ui->lockBox) ui->lockBox->setCurrentIndex(0);
428     // Program
429     if(box != ui->programKpBox && box != ui->programKrBox){
430         ui->programKpButton->setChecked(false);
431         ui->programKrButton->setChecked(false);
432     }
433     // Clear macro panel
434     if (box != ui->pteMacroBox) {
435         ui->pteMacroBox->setPlainText("");
436         helpStatus(1);
437     }
438 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.80.3.46 void RebindWidget::setSelection (const QStringList & *newSelection,* bool *applyPrevious* = `false`)

Definition at line 128 of file rebindwidget.cpp.

References KbBind::action(), Ui_RebindWidget::animBox, KeyAction::animInfo(), Ui_RebindWidget::animKrBox, KbLight::animList(), Ui_RebindWidget::animOnceBox, applyChanges(), bind, KeyAction::DPI_CUSTOM, DPI_OFFSET, Ui_RebindWidget::dpiBox, Ui_RebindWidget::dpiCustXBox, Ui_RebindWidget::dpiCustYBox, KeyAction::dpiInfo(), KbLight::findAnimIdx(), Ui_RebindWidget::fnBox, fnKeys, KeyAction::isAnim(), KeyAction::isDPI(), KeyAction::isMouse(), KeyAction::isNormal(), KeyAction::isProgram(), KeyAction::isSpecial(), KeyAction::isValidMacro(), KbBind::light(), KeyAction::LIGHT_DOWN, KeyAction::LIGHT_DOWN_WRAP, KeyAction::LIGHT_UP, KeyAction::LIGHT_UP_WRAP, Ui_RebindWidget::lightBox, Ui_RebindWidget::lightWrapBox, Ui_RebindWidget::lockBox, KeyAction::macroContent(), KeyAction::macroDisplay(), KeyAction::macroLine(), Ui_RebindWidget::mb2Box, Ui_RebindWidget::mbBox, Ui_RebindWidget::mediaBox, mediaKeys, Ui_RebindWidget::modBox, KeyAction::MODE_NEXT, KeyAction::MODE_NEXT_WRAP, KeyAction::MODE_PREV, KeyAction::MODE_PREV_WRAP, Ui_RebindWidget::modeBox, Ui_RebindWidget::modeWrapBox, modKeys, mouseExtKeys, mouseKeys, KbAnim::name(), Ui_RebindWidget::numBox, numKeys, KeyAction::PROGRAM_PR_MULTI, KeyAction::PROGRAM_RE_INDEF, KeyAction::PROGRAM_RE_KPSTOP, KeyAction::PROGRAM_RE_MULTI, KeyAction::programInfo(),

Ui_RebindWidget::programKpBox, Ui_RebindWidget::programKpModeBox, Ui_RebindWidget::programKpSIBox, Ui_RebindWidget::programKrBox, Ui_RebindWidget::programKrModeBox, Ui_RebindWidget::programKrSIBox, Ui_RebindWidget::pteMacroBox, Ui_RebindWidget::pteMacroComment, Ui_RebindWidget::pteMacroText, selection, setBox(), KeyAction::specialInfo(), TAB_ANIM, TAB_KB, TAB_MACRO, TAB_MOUSE, TAB_PROGRAM, TAB_SPECIAL, Ui_RebindWidget::tabWidget, Ui_RebindWidget::typingBox, typingKeys, ui, Ui_RebindWidget::wheelBox, and wheelKeys.

Referenced by KbBindWidget::newSelection(), on_cancelButton_clicked(), setBind(), and KbBindWidget::updateBind().

```
{
    if(bind){
        // Populate animation list
        // FIXME: There should be a trigger to update this whenever an animation is added/removed, even if the key selection hasn't changed
        ui->animBox->clear();
        ui->animBox->addItem(" ");
        foreach(KbAnim* anim, bind->light()->animList())
            ui->animBox->addItem(anim->name());
    }

    // Apply changes to previous selection (if any)
    if(!selection.isEmpty() && applyPrevious){
        QStringList previous = selection;
        selection = QStringList();
        applyChanges(previous, false);
    }

    selection = newSelection;
    if(newSelection.isEmpty()){
        hide();
        return;
    } else
        show();

    bool hasAction = false;
    QString action;
    if(selection.count() == 1){
        // Select action from the UI
        action = bind->action(selection.first());
        if(!action.isEmpty())
            hasAction = true;
    } else {
        // Select an action from the UI if all keys are the same.
        // Select nothing if any are unbound or different
        foreach(const QString& key, selection){
            QString keyAction = bind->action(key);
            if(keyAction.isEmpty() || (hasAction && keyAction != action)){
                hasAction = false;
                break;
            } else if(action.isEmpty()){
                action = keyAction;
                hasAction = true;
            }
        }
    }

    if(!hasAction)
        action = "";
    KeyAction act(action);
    // Clear everything
    setBox(0);
    ui->dpiCustXBox->setValue(400);
    ui->dpiCustYBox->setValue(400);
    ui->animOnceBox->setChecked(false);
    ui->animKrBox->setChecked(false);
    ui->programKpBox->setText("");
    ui->programKrBox->setText("");
    ui->programKpSIBox->setChecked(false);
    ui->programKrSIBox->setChecked(false);
    ui->programKpModeBox->setCurrentIndex(0);
    ui->programKrModeBox->setCurrentIndex(0);
    ui->programKpModeBox->setEnabled(false);
    ui->programKrModeBox->setEnabled(false);
    // Clear neu UI elements in MacroTab
    ui->pteMacroBox->setPlainText("");
    ui->pteMacroText->setPlainText("");
    ui->pteMacroComment->setPlainText("");
    // Fill in field and select tab according to action type
    bool mouse = act.isMouse();
    if(mouse){
        // Mouse buttons
        ui->tabWidget->setCurrentIndex(TAB_MOUSE);
        // Set mouse buttons (indexOf returns -1 if not found, index zero is blank)
```

```
        ui->mbBox->setCurrentIndex(mouseKeys.indexOf(action) + 1);
        ui->mb2Box->setCurrentIndex(mouseExtKeys.indexOf(action) + 1);
        ui->wheelBox->setCurrentIndex(wheelKeys.indexOf(action) + 1);
        if(act.isDPI()){
            QPoint custom;
            int value = act.dpiInfo(custom);
            if(value <= -DPI_OFFSET || value > KeyAction::DPI_CUSTOM)
                return;
            ui->dpiBox->setCurrentIndex(value + DPI_OFFSET);
            if(value == KeyAction::DPI_CUSTOM){
                ui->dpiCustXBox->setValue(custom.x());
                ui->dpiCustYBox->setValue(custom.y());
            }
        }
    } else if(act.isNormal()){
        // Standard key
        ui->tabWidget->setCurrentIndex(TAB_KB);
        ui->typingBox->setCurrentIndex(typingKeys.indexOf(action) + 1);
        ui->modBox->setCurrentIndex(modKeys.indexOf(action) + 1);
        ui->fnBox->setCurrentIndex(fnKeys.indexOf(action) + 1);
        ui->numBox->setCurrentIndex(numKeys.indexOf(action) + 1);
        ui->mediaBox->setCurrentIndex(mediaKeys.indexOf(action) + 1);
    } else if(act.isProgram()){
        // Program key
        ui->tabWidget->setCurrentIndex(TAB_PROGRAM);
        QString onPress, onRelease;
        int stop = act.programInfo(onPress, onRelease);
        ui->programKpBox->setText(onPress);
        ui->programKrBox->setText(onRelease);
        switch(stop & 0x0F){
        case KeyAction::PROGRAM_PR_MULTI:
            ui->programKpSIBox->setChecked(false);
            ui->programKpModeBox->setCurrentIndex(0);
            ui->programKpModeBox->setEnabled(false);
            break;
        default:
            ui->programKpSIBox->setChecked(true);
            ui->programKpModeBox->setCurrentIndex(stop & 0x0F);
            ui->programKpModeBox->setEnabled(true);
            break;
        }
        switch(stop & 0xF0){
        case KeyAction::PROGRAM_RE_MULTI:
            ui->programKrSIBox->setChecked(false);
            ui->programKrModeBox->setCurrentIndex(0);
            ui->programKrModeBox->setEnabled(false);
            break;
        case KeyAction::PROGRAM_RE_INDEF:
            ui->programKrSIBox->setChecked(true);
            ui->programKrModeBox->setCurrentIndex(0);
            ui->programKrModeBox->setEnabled(true);
            break;
        case KeyAction::PROGRAM_RE_KPSTOP:
            ui->programKrSIBox->setChecked(true);
            ui->programKrModeBox->setCurrentIndex(1);
            ui->programKrModeBox->setEnabled(true);
            break;
        }
    } else if(act.isAnim()){
        // Animation key
        ui->tabWidget->setCurrentIndex(TAB_ANIM);
        bool onlyOnce = false, stopOnRelease = false;
        QUuid id = act.animInfo(onlyOnce, stopOnRelease);
        // Find this animation in the list. If not found, -1 will be returned, resulting in the blank space
    being selected
        int index = bind->light()->findAnimIdx(id);
        ui->animBox->setCurrentIndex(index + 1);
        ui->animOnceBox->setChecked(!onlyOnce);
        ui->animKrBox->setChecked(stopOnRelease);
    } else if(act.isSpecial()){
        // Other special keys
        ui->tabWidget->setCurrentIndex(TAB_SPECIAL);
        int param;
        QString sAction = act.specialInfo(param);
        // Mode selection. Check wrap-around flag
        ui->modeWrapBox->setChecked(true);
        if(sAction == "mode"){
            ui->modeWrapBox->setChecked(true);
            if(param == KeyAction::MODE_PREV_WRAP)
                param = KeyAction::MODE_PREV;
            else if(param == KeyAction::MODE_NEXT_WRAP)
                param = KeyAction::MODE_NEXT;
            else if(param < 0)
                ui->modeWrapBox->setChecked(false);
            // Set mode box to current selection, or to mode 1 if invalid
            param += 3;
            if(param >= 0 && param < ui->modeBox->count())
```

```
                ui->modeBox->setCurrentIndex(param);
            else
                // 0 -> "", 1 -> Prev, 2 -> Next, 3 -> Mode 1
                ui->modeBox->setCurrentIndex(3);
        } else if (sAction == "macro") {
            ui->tabWidget->setCurrentIndex(TAB_MACRO);
            if (act.isValidMacro()) {
                ui->pteMacroBox->setPlainText(act.macroContent());
                ui->pteMacroText->setPlainText(act.macroLine()[1].replace("
    &das_IST_31N_col0n;", ":"));
                ui->pteMacroComment->setPlainText(act.macroLine()[2].replace("
    &das_IST_31N_col0n;", ":"));
            } else {
                qDebug("RebindWidget::setSelection found invalid macro definition.");
                act.macroDisplay();
            }
        } else
            ui->modeBox->setCurrentIndex(0);
        // Brightness control. Also check wrap
        if(sAction == "light"){
            ui->lightWrapBox->setChecked(true);
            if(param == KeyAction::LIGHT_DOWN_WRAP)
                param = KeyAction::LIGHT_DOWN;
            else if(param == KeyAction::LIGHT_UP_WRAP)
                param = KeyAction::LIGHT_UP;
            else
                ui->lightWrapBox->setChecked(false);
            if(param < 0 || param > 1)
                param = -1;
            ui->lightBox->setCurrentIndex(param + 1);
        } else
            ui->lightBox->setCurrentIndex(0);
        // Win lock
        if(sAction == "lock"){
            if(param < 0 || param > 2)
                param = -1;
            ui->lockBox->setCurrentIndex(param + 1);
        } else
            ui->lockBox->setCurrentIndex(0);
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.80.4 Field Documentation

12.80.4.1 KbBind* RebindWidget::bind [private]

Definition at line 86 of file rebindwidget.h.

Referenced by applyChanges(), on_btnStartMacro_clicked(), on_btnStopMacro_clicked(), on_resetButton_clicked(), on_unbindButton_clicked(), setBind(), and setSelection().

12.80.4.2 QStringList RebindWidget::fnKeys [private]

Definition at line 92 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), setBind(), and setSelection().

12.80.4.3 MacroReader* RebindWidget::macReader [private]

Definition at line 98 of file rebindwidget.h.

Referenced by on_btnStartMacro_clicked(), and on_btnStopMacro_clicked().

12.80.4.4 QStringList RebindWidget::mediaKeys [private]

Definition at line 94 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), setBind(), and setSelection().

12.80.4.5 QStringList RebindWidget::modKeys [private]

Definition at line 91 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), setBind(), and setSelection().

12.80.4.6 QStringList RebindWidget::mouseExtKeys [private]

Definition at line 96 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), and setSelection().

12.80.4.7 QStringList RebindWidget::mouseKeys [private]

Definition at line 95 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), and setSelection().

12.80.4.8 QStringList RebindWidget::numKeys [private]

Definition at line 93 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), setBind(), and setSelection().

12.80.4.9 KbProfile* RebindWidget::profile [private]

Definition at line 87 of file rebindwidget.h.

Referenced by setBind().

12.80.4.10 QStringList RebindWidget::selection [private]

Definition at line 88 of file rebindwidget.h.

Referenced by on_applyButton_clicked(), on_cancelButton_clicked(), on_resetButton_clicked(), on_unbindButton-_clicked(), and setSelection().

12.80.4.11 const int RebindWidget::TAB_ANIM = 2 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.12 const int RebindWidget::TAB_KB = 0 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.13 const int RebindWidget::TAB_MACRO = 5 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.14 const int RebindWidget::TAB_MOUSE = 1 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.15 const int RebindWidget::TAB_PROGRAM = 4 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.16 const int RebindWidget::TAB_SPECIAL = 3 [static], [private]

Definition at line 77 of file rebindwidget.h.

Referenced by setSelection().

12.80.4.17 QStringList RebindWidget::typingKeys [private]

Definition at line 90 of file rebindwidget.h.

Referenced by applyChanges(), setBind(), and setSelection().

12.80.4.18 Ui::RebindWidget* RebindWidget::ui [private]

Definition at line 74 of file rebindwidget.h.

Referenced by applyChanges(), convertMacroBox(), helpStatus(), on_animBox_currentIndexChanged(), on_animButton_clicked(), on_btnStartMacro_clicked(), on_btnStopMacro_clicked(), on_dpiBox_currentIndexChanged(), on_dpiButton_clicked(), on_fnBox_currentIndexChanged(), on_fnButton_clicked(), on_lightBox_currentIndexChanged(), on_lightButton_clicked(), on_lockBox_currentIndexChanged(), on_lockButton_clicked(), on_mb2Box_currentIndexChanged(), on_mb2Button_clicked(), on_mbBox_currentIndexChanged(), on_mbButton_clicked(), on_mediaBox_currentIndexChanged(), on_mediaButton_clicked(), on_modBox_currentIndexChanged(), on_modButton_clicked(), on_modeBox_currentIndexChanged(), on_modeButton_clicked(), on_numBox_currentIndexChanged(), on_numButton_clicked(), on_programKpBox_textChanged(), on_programKpButton_clicked(), on_programKpSIBox_clicked(), on_programKrBox_textChanged(), on_programKrButton_clicked(), on_programKrSIBox_clicked(), on_pteMacroBox_textChanged(), on_typingBox_currentIndexChanged(), on_typingButton_clicked(), on_wheelBox_currentIndexChanged(), on_wheelButton_clicked(), RebindWidget(), setBind(), setBox(), setSelection(), and ~RebindWidget().

12.80.4.19 QStringList RebindWidget::wheelKeys [private]

Definition at line 97 of file rebindwidget.h.

Referenced by applyChanges(), RebindWidget(), and setSelection().

The documentation for this class was generated from the following files:

- src/ckb/rebindwidget.h
- src/ckb/rebindwidget.cpp

12.81 RListWidget Class Reference

```
#include <src/ckb/rlistwidget.h>
```

Inheritance diagram for RListWidget:

Collaboration diagram for RListWidget:

Signals

- void orderChanged ()

Public Member Functions

- RListWidget (QWidget ∗parent=0)

Private Slots

- void timerTick ()
- void enter (QListWidgetItem ∗item)
- void change (QListWidgetItem ∗item)

Private Member Functions

- void rescanItems ()

Private Attributes

- QVariant currentData
- QList< QVariant > previousItems
- QVariant dragged
- QTimer reorderTimer

Static Private Attributes

- static const int DATA_ROLE = Qt::UserRole + 100

12.81.1 Detailed Description

Definition at line 9 of file rlistwidget.h.

12.81.2 Constructor & Destructor Documentation

12.81.2.1 RListWidget::RListWidget (QWidget * *parent* = 0) [explicit]

Definition at line 4 of file rlistwidget.cpp.

References change(), enter(), reorderTimer, and timerTick().

```
4                                       :
5     QListWidget(parent)
6 {
7     setDragDropMode(QAbstractItemView::InternalMove);
8     setMovement(QListView::Snap);
9
10     reorderTimer.setSingleShot(true);
11     reorderTimer.setInterval(100);
12     connect(&reorderTimer, SIGNAL(timeout()), this, SLOT(timerTick()));
13
14     connect(this, SIGNAL(itemEntered(QListWidgetItem*)), this, SLOT(enter(QListWidgetItem*)));
15     connect(this, SIGNAL(itemChanged(QListWidgetItem*)), this, SLOT(change(QListWidgetItem*)));
16 }
```

Here is the call graph for this function:

12.81.3 Member Function Documentation

12.81.3.1 void RListWidget::change (QListWidgetItem * *item*) [private],[slot]

Definition at line 54 of file rlistwidget.cpp.

References reorderTimer.

Referenced by RListWidget().

```
54                                      {
55     reorderTimer.stop();
56     reorderTimer.start();
57 }
```

Here is the caller graph for this function:

12.81.3.2 void RListWidget::enter (QListWidgetItem * *item*) [private],[slot]

Definition at line 47 of file rlistwidget.cpp.

References DATA_ROLE, dragged, and rescanItems().

Referenced by RListWidget().

```
47                                          {
48     rescanItems();
49     // Check for drag+drop setup
50     if(item)
51         dragged = item->data(DATA_ROLE);
52 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.81.3.3 void RListWidget::orderChanged ( ) [signal]

Definition at line 141 of file moc_rlistwidget.cpp.

Referenced by timerTick().

```
142 {
143     QMetaObject::activate(this, &staticMetaObject, 0, Q_NULLPTR);
144 }
```

Here is the caller graph for this function:

12.81.3.4 void RListWidget::rescanItems ( ) [private]

Definition at line 59 of file rlistwidget.cpp.

References DATA_ROLE, and previousItems.

Referenced by enter().

```
59                                {
60     QList<QVariant> newItems;
61     int c = count();
62     for(int i = 0; i < c; i++){
63         QVariant data = this->item(i)->data(DATA_ROLE);
64         if(data.isNull()){
65             // Generate the ID for this item if it doesn't already exist
66             data = QUuid::createUuid();
67             this->item(i)->setData(DATA_ROLE, data);
68         }
69         newItems.append(data);
70     }
71     previousItems = newItems;
72 }
```

Here is the caller graph for this function:

12.81.3.5 void RListWidget::timerTick ( ) [private], [slot]

Definition at line 18 of file rlistwidget.cpp.

References DATA_ROLE, dragged, orderChanged(), and previousItems.

Referenced by RListWidget().

```
18                                {
19     bool reordered = false;
20     QListWidgetItem* reselect = 0;
21     QList<QVariant> newItems;
22     // Scan the item list to see if they changed
23     int c = count();
24     for(int i = 0; i < c; i++){
25         QListWidgetItem* itm = item(i);
26         QVariant data = itm->data(DATA_ROLE);
27         newItems.append(data);
28         if(i >= previousItems.count() || data != previousItems[i])
29             reordered = true;
30         // Re-select the dragged item (if any)
31         if(data == dragged)
32             reselect = itm;
33     }
34     if(previousItems.length() != newItems.length())
35         return;
36     if(reordered){
37         previousItems = newItems;
38         emit orderChanged();
39         if(reselect){
40             reselect->setSelected(true);
41             setCurrentItem(reselect);
42             dragged = QVariant();
43         }
44     }
45 }
```

Here is the caller graph for this function:

12.81.4 Field Documentation

12.81.4.1 QVariant RListWidget::currentData [private]

Definition at line 24 of file rlistwidget.h.

12.81.4.2 const int RListWidget::DATA_ROLE = Qt::UserRole + 100 [static], [private]

Definition at line 29 of file rlistwidget.h.

Referenced by enter(), rescanItems(), and timerTick().

12.81.4.3 QVariant RListWidget::dragged [private]

Definition at line 26 of file rlistwidget.h.

Referenced by enter(), and timerTick().

12.81.4.4 QList<QVariant> RListWidget::previousItems [private]

Definition at line 25 of file rlistwidget.h.

Referenced by rescanItems(), and timerTick().

12.81.4.5 QTimer RListWidget::reorderTimer [private]

Definition at line 27 of file rlistwidget.h.

Referenced by change(), and RListWidget().

The documentation for this class was generated from the following files:

- src/ckb/rlistwidget.h
- src/ckb/release/moc_rlistwidget.cpp
- src/ckb/rlistwidget.cpp

12.82 SettingsWidget Class Reference

```
#include <src/ckb/settingswidget.h>
```

Inheritance diagram for SettingsWidget:

Collaboration diagram for SettingsWidget:

Public Member Functions

- SettingsWidget (QWidget *parent=0)
- ~SettingsWidget ()
- void setVersion (const QString &version)
- void setStatus (const QString &text)
- void pollUpdates ()

Private Slots

- void on_pushButton_clicked ()
- void on_capsBox_activated (int index)
- void on_shiftBox_activated (int index)
- void on_ctrlBox_activated (int index)
- void on_altBox_activated (int index)
- void on_winBox_activated (int index)
- void on_autoFWBox_clicked (bool checked)
- void on_loginItemBox_clicked (bool checked)
- void on_layoutBox_activated (int index)
- void showLayoutDialog ()
- void on_extraButton_clicked ()

Private Member Functions

- void updateModifiers ()

Private Attributes

- Ui::SettingsWidget * ui
- ExtraSettingsWidget * extra

Friends

- class MainWindow

12.82.1 Detailed Description

Definition at line 11 of file settingswidget.h.

12.82.2 Constructor & Destructor Documentation

12.82.2.1 SettingsWidget::SettingsWidget (QWidget * *parent* = 0) [explicit]

Definition at line 15 of file settingswidget.cpp.

References Ui_SettingsWidget::altBox, Ui_SettingsWidget::autoFWBox, AutoRun::available(), Ui_SettingsWidget::capsBox, Ui_SettingsWidget::ctrlBox, AutoRun::enable(), extra, KeyMap::getLayout(), KbBind::globalRemap(), AutoRun::isEnabled(), Kb::layout(), Ui_SettingsWidget::layoutBox, KeyMap::layoutNames(), KbBind::loadGlobalRemap(), KeyMap::locale(), Ui_SettingsWidget::loginItemBox, modKeys, modNames, KeyMap::NO_LAYOUT, AutoRun::once(), CkbSettings::remove(), Ui_SettingsWidget::setupUi(), CkbSettings::setValue(), Ui_SettingsWidget::shiftBox, showLayoutDialog(), ui, updateModifiers(), CkbSettings::value(), and Ui_SettingsWidget::winBox.

```
15                                                  :
16     QWidget(parent),
17     ui(new Ui::SettingsWidget)
18 {
19     ui->setupUi(this);
20     CkbSettings settings("Program");
21
22     // Read keyboard layout
23     ui->layoutBox->addItems(KeyMap::layoutNames());
24     KeyMap::Layout layout = KeyMap::getLayout(settings.value("KbdLayout").
      toString());
25     if(layout == KeyMap::NO_LAYOUT){
26         // If the layout hasn't been set yet, show a dialog to let the user choose it
27         layout = KeyMap::locale();
28         QTimer::singleShot(1000, this, SLOT(showLayoutDialog()));   // Run the function
      after a delay as the dialog may not appear correctly otherwise
29         settings.setValue("KbdLayout", KeyMap::getLayout(layout));
30     }
31     Kb::layout(layout);
32     ui->layoutBox->setCurrentIndex((int)layout);
33
34     // Load modifier remap
35     KbBind::loadGlobalRemap();
36     if(modKeys.isEmpty()){
37         modKeys << "caps" << "lshift" << "lctrl" << "lalt" << "lwin";
38 #ifdef Q_OS_MACX
39         modNames << "Caps Lock" << "Shift" << "Control ()" << "Option ()" << "Command ()";
40 #else
41         modNames << "Caps Lock" << "Shift" << "Control" << "Alt" << "Super";
42 #endif
43     }
44     foreach(const QString& name, modNames){
45         ui->capsBox->addItem(name);
46         ui->shiftBox->addItem(name);
47         ui->ctrlBox->addItem(name);
48         ui->altBox->addItem(name);
49         ui->winBox->addItem(name);
50     }
51
52     int idx = modKeys.indexOf(KbBind::globalRemap("caps"));
53     if(idx >= 0)
54         ui->capsBox->setCurrentIndex(idx);
55     idx = modKeys.indexOf(KbBind::globalRemap("lshift"));
56     if(idx >= 0)
57         ui->shiftBox->setCurrentIndex(idx);
58     idx = modKeys.indexOf(KbBind::globalRemap("lctrl"));
59     if(idx >= 0)
60         ui->ctrlBox->setCurrentIndex(idx);
61     idx = modKeys.indexOf(KbBind::globalRemap("lwin"));
62     if(idx >= 0)
63         ui->winBox->setCurrentIndex(idx);
64     idx = modKeys.indexOf(KbBind::globalRemap("lalt"));
65     if(idx >= 0)
66         ui->altBox->setCurrentIndex(idx);
```

```
#ifdef Q_OS_MACX
    if(settings.value("osxCmdSwap").toBool()){
        // ckb <0.0.41
        settings.remove("osxCmdSwap");
        ui->ctrlBox->setCurrentIndex(modKeys.indexOf("lwin"));
        ui->winBox->setCurrentIndex(modKeys.indexOf("lctrl"));
        updateModifiers();
    }
#endif

    // Read auto update settings
    ui->autoFWBox->setChecked(!settings.value("DisableAutoFWCheck").toBool());

    // Read auto run settings
    if(!AutoRun::available())
        ui->loginItemBox->hide();
    else {
        if(!AutoRun::once())
            // If this is the first time running the app, enable auto run by default
            AutoRun::enable();
        ui->loginItemBox->setChecked(AutoRun::isEnabled());
    }

    // Prepare extra settings
    extra = new ExtraSettingsWidget(this);
}
```

Here is the call graph for this function:

12.82.2.2 SettingsWidget::~SettingsWidget ( )

Definition at line 94 of file settingswidget.cpp.

References ui.

```
94                                  {
95     delete ui;
96 }
```

12.82.3 Member Function Documentation

12.82.3.1 void SettingsWidget::on_altBox_activated (int *index*) [private],[slot]

Definition at line 155 of file settingswidget.cpp.

References updateModifiers().

```
155                                                 {
156     updateModifiers();
157 }
```

Here is the call graph for this function:

12.82.3.2 void SettingsWidget::on_autoFWBox_clicked (bool *checked*) [private],[slot]

Definition at line 163 of file settingswidget.cpp.

References CkbSettings::set().

```
163                                                 {
164     CkbSettings::set("Program/DisableAutoFWCheck", !checked);
165 }
```

Here is the call graph for this function:

12.82.3.3 void SettingsWidget::on_capsBox_activated (int *index*) [private],[slot]

Definition at line 143 of file settingswidget.cpp.

References updateModifiers().

```
143                                                 {
144     updateModifiers();
145 }
```

Here is the call graph for this function:

12.82.3.4 void SettingsWidget::on_ctrlBox_activated (int *index*) [private],[slot]

Definition at line 151 of file settingswidget.cpp.

References updateModifiers().

```
151                                                 {
152     updateModifiers();
153 }
```

Here is the call graph for this function:

12.82.3.5 void SettingsWidget::on_extraButton_clicked ( ) [private],[slot]

Definition at line 180 of file settingswidget.cpp.

References extra.

```
180                                             {
181     extra->exec();
182 }
```

12.82.3.6 void SettingsWidget::on_layoutBox_activated (int *index*) [private],[slot]

Definition at line 174 of file settingswidget.cpp.

References KeyMap::getLayout(), Kb::layout(), and CkbSettings::set().

Referenced by showLayoutDialog().

```
174                                                 {
175     KeyMap::Layout layout = (KeyMap::Layout)index;
176     CkbSettings::set("Program/KbdLayout", KeyMap::getLayout(layout));
177     Kb::layout(layout);
178 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.82.3.7 void SettingsWidget::on_loginItemBox_clicked (bool *checked*) [private],[slot]

Definition at line 167 of file settingswidget.cpp.

References AutoRun::disable(), and AutoRun::enable().

```
167                                                     {
168     if(checked)
169         AutoRun::enable();
170     else
171         AutoRun::disable();
172 }
```

Here is the call graph for this function:

12.82.3.8 void SettingsWidget::on_pushButton_clicked ( ) [private],[slot]

Definition at line 139 of file settingswidget.cpp.

```
139                                         {
140     qApp->quit();
141 }
```

12.82.3.9 void SettingsWidget::on_shiftBox_activated (int *index*) [private],[slot]

Definition at line 147 of file settingswidget.cpp.

References updateModifiers().

```
147                                                 {
148     updateModifiers();
149 }
```

Here is the call graph for this function:

12.82.3.10 void SettingsWidget::on_winBox_activated (int *index*) [private],[slot]

Definition at line 159 of file settingswidget.cpp.

References updateModifiers().

```
159                                                 {
160     updateModifiers();
161 }
```

Here is the call graph for this function:

12.82.3.11 void SettingsWidget::pollUpdates ( )

Definition at line 106 of file settingswidget.cpp.

References extra, and ExtraSettingsWidget::pollUpdates().

Referenced by MainWindow::timerTick().

```
106                                 {
107     extra->pollUpdates();
108 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.82.3.12 void SettingsWidget::setStatus (const QString & *text*)

Definition at line 110 of file settingswidget.cpp.

References Ui_SettingsWidget::devicesLabel, and ui.

Referenced by MainWindow::updateVersion().

```
110                                                 {
111     ui->devicesLabel->setText(text);
112 }
```

Here is the caller graph for this function:

12.82.3.13 void SettingsWidget::setVersion (const QString & *version*)

Definition at line 114 of file settingswidget.cpp.

References ui, and Ui_SettingsWidget::versionLabel.

Referenced by MainWindow::MainWindow().

```
114                                                 {
115     ui->versionLabel->setText(version);
116 }
```

Here is the caller graph for this function:

12.82.3.14 void SettingsWidget::showLayoutDialog ( ) [private],[slot]

Definition at line 98 of file settingswidget.cpp.

References Ui_SettingsWidget::layoutBox, on_layoutBox_activated(), LayoutDialog::selected(), and ui.

Referenced by SettingsWidget().

```
98                                  {
99     LayoutDialog dialog(this);
100     dialog.exec();
101     // Set selected layout
102     ui->layoutBox->setCurrentIndex((int)dialog.selected());
103     on_layoutBox_activated((int)dialog.selected());         // Call activated()
       signal manually to trigger save
104 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.82.3.15 void SettingsWidget::updateModifiers ( ) [private]

Definition at line 124 of file settingswidget.cpp.

References Ui_SettingsWidget::altBox, Ui_SettingsWidget::capsBox, Ui_SettingsWidget::ctrlBox, modKeys, right(), KbBind::saveGlobalRemap(), KbBind::setGlobalRemap(), Ui_SettingsWidget::shiftBox, ui, and Ui_SettingsWidget::winBox.

Referenced by on_altBox_activated(), on_capsBox_activated(), on_ctrlBox_activated(), on_shiftBox_activated(), on_winBox_activated(), and SettingsWidget().

```
{
    QHash<QString, QString> newMods;
    newMods["caps"] = modKeys[ui->capsBox->currentIndex()];
    newMods["lshift"] = modKeys[ui->shiftBox->currentIndex()];
    newMods["rshift"] = right(modKeys[ui->shiftBox->currentIndex()]);
    newMods["lctrl"] = modKeys[ui->ctrlBox->currentIndex()];
    newMods["rctrl"] = right(modKeys[ui->ctrlBox->currentIndex()]);
    newMods["lalt"] = modKeys[ui->altBox->currentIndex()];
    newMods["ralt"] = right(modKeys[ui->altBox->currentIndex()]);
    newMods["lwin"] = modKeys[ui->winBox->currentIndex()];
    newMods["rwin"] = right(modKeys[ui->winBox->currentIndex()]);
    KbBind::setGlobalRemap(newMods);
    KbBind::saveGlobalRemap();
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.82.4 Friends And Related Function Documentation

12.82.4.1 friend class MainWindow [friend]

Definition at line 44 of file settingswidget.h.

12.82.5 Field Documentation

12.82.5.1 ExtraSettingsWidget* SettingsWidget::extra [private]

Definition at line 46 of file settingswidget.h.

Referenced by on_extraButton_clicked(), pollUpdates(), and SettingsWidget().

12.82.5.2 Ui::SettingsWidget* SettingsWidget::ui [private]

Definition at line 43 of file settingswidget.h.

Referenced by setStatus(), SettingsWidget(), setVersion(), showLayoutDialog(), updateModifiers(), and ~SettingsWidget().

The documentation for this class was generated from the following files:

- src/ckb/settingswidget.h
- src/ckb/settingswidget.cpp

12.83 Ui::SettingsWidget Class Reference

```
#include <src/ckb/ui_settingswidget.h>
```

Inheritance diagram for Ui::SettingsWidget:

Collaboration diagram for Ui::SettingsWidget:

Public Member Functions

- void setupUi (QWidget *SettingsWidget)
- void retranslateUi (QWidget *SettingsWidget)

Data Fields

- QGridLayout * gridLayout
- QLabel * label_2
- QLabel * label
- QLabel * label_6
- QGridLayout * gridLayout_5
- QSpacerItem * horizontalSpacer_7
- QLabel * devicesLabel
- QLabel * label_5
- QComboBox * layoutBox
- QSpacerItem * verticalSpacer_10
- QHBoxLayout * horizontalLayout_2
- QLabel * label_3
- QSpacerItem * horizontalSpacer
- QPushButton * pushButton
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_8
- QCheckBox * loginItemBox
- QSpacerItem * verticalSpacer_6
- QCheckBox * autoFWBox
- QFrame * line_2
- QLabel * label_8
- QGridLayout * gridLayout_3
- QLabel * shiftLabel
- QLabel * capsLabel

- QSpacerItem * horizontalSpacer_10
- QComboBox * capsBox
- QLabel * ctrlLabel
- QSpacerItem * horizontalSpacer_9
- QComboBox * ctrlBox
- QComboBox * shiftBox
- QLabel * winLabel
- QComboBox * winBox
- QComboBox * altBox
- QLabel * altLabel
- QFrame * line
- QSpacerItem * verticalSpacer_3
- QSpacerItem * verticalSpacer_5
- QFrame * line_3
- QSpacerItem * verticalSpacer_4
- QSpacerItem * verticalSpacer_2
- QLabel * versionLabel
- QHBoxLayout * horizontalLayout
- QPushButton * extraButton
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer_7

12.83.1 Detailed Description

Definition at line 378 of file ui_settingswidget.h.

12.83.2 Member Function Documentation

12.83.2.1 void Ui_SettingsWidget::retranslateUi (QWidget * *SettingsWidget*) [inline],[inherited]

Definition at line 347 of file ui_settingswidget.h.

References Ui_SettingsWidget::altLabel, Ui_SettingsWidget::autoFWBox, Ui_SettingsWidget::capsLabel, Ui_SettingsWidget::ctrlLabel, Ui_SettingsWidget::devicesLabel, Ui_SettingsWidget::extraButton, Ui_SettingsWidget::label, Ui_SettingsWidget::label_2, Ui_SettingsWidget::label_3, Ui_SettingsWidget::label_5, Ui_SettingsWidget::label_6, Ui_SettingsWidget::label_8, Ui_SettingsWidget::loginItemBox, Ui_SettingsWidget::pushButton, Ui_SettingsWidget::shiftLabel, Ui_SettingsWidget::versionLabel, and Ui_SettingsWidget::winLabel.

Referenced by Ui_SettingsWidget::setupUi().

```
348     {
349         SettingsWidget->setWindowTitle(QApplication::translate("SettingsWidget", "Form", Q_NULLPTR));
350         label_2->setText(QApplication::translate("SettingsWidget", "\302\251 2014-2016 <a href=\"
      https://github.com/ccMSC/\" style=\"text-decoration:none;\">ccMSC</a>.<br/>\302\251 2017 <a href=\"
      https://github.com/mattanger/ckb-next/graphs/contributors\" style=\"text-decoration:none;\">The ckb-next development
       team</a>.", Q_NULLPTR));
351         label->setText(QApplication::translate("SettingsWidget", "Modifier keys", Q_NULLPTR));
352         label_6->setText(QApplication::translate("SettingsWidget", "Application", Q_NULLPTR));
353         devicesLabel->setText(QApplication::translate("SettingsWidget", "No devices connected",
       Q_NULLPTR));
354         label_5->setText(QApplication::translate("SettingsWidget", "Keyboard layout:", Q_NULLPTR));
355         label_3->setText(QApplication::translate("SettingsWidget", "<a href=\"
      https://github.com/mattanger/ckb-next\" style=\"text-decoration:none;\">https://github.com/mattanger/ckb-next</a>", Q_NU
356         pushButton->setText(QApplication::translate("SettingsWidget", "Quit", Q_NULLPTR));
357 #ifndef QT_NO_TOOLTIP
358         loginItemBox->setToolTip(QApplication::translate("SettingsWidget", "ckb-next will be
       started when you log in to your computer.", Q_NULLPTR));
359 #endif // QT_NO_TOOLTIP
360         loginItemBox->setText(QApplication::translate("SettingsWidget", "Start ckb-next at
       login", Q_NULLPTR));
361 #ifndef QT_NO_TOOLTIP
362         autoFWBox->setToolTip(QApplication::translate("SettingsWidget", "You will be notified when
       new firmware versions are available. You'll have the option to install them immediately or wait until
       later.", Q_NULLPTR));
```

```
#endif // QT_NO_TOOLTIP
        autoFWBox->setText(QApplication::translate("SettingsWidget", "Check for new firmware automatically", Q_NULLPTR));
        label_8->setText(QApplication::translate("SettingsWidget", "These will override the keyboard profile. See \"Binding\" tab for more settings.", Q_NULLPTR));
        shiftLabel->setText(QApplication::translate("SettingsWidget", "Shift:", Q_NULLPTR));
        capsLabel->setText(QApplication::translate("SettingsWidget", "Caps Lock:", Q_NULLPTR));
        ctrlLabel->setText(QApplication::translate("SettingsWidget", "Ctrl:", Q_NULLPTR));
        winLabel->setText(QApplication::translate("SettingsWidget", "Windows:", Q_NULLPTR));
        altLabel->setText(QApplication::translate("SettingsWidget", "Alt:", Q_NULLPTR));
        versionLabel->setText(QApplication::translate("SettingsWidget", "ckb-next", Q_NULLPTR));
        extraButton->setText(QApplication::translate("SettingsWidget", "More settings", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.83.2.2 void Ui_SettingsWidget::setupUi (QWidget * *SettingsWidget*) [inline],[inherited]

Definition at line 78 of file ui_settingswidget.h.

References Ui_SettingsWidget::altBox, Ui_SettingsWidget::altLabel, Ui_SettingsWidget::autoFWBox, Ui_SettingsWidget::capsBox, Ui_SettingsWidget::capsLabel, Ui_SettingsWidget::ctrlBox, Ui_SettingsWidget::ctrlLabel, Ui_SettingsWidget::devicesLabel, Ui_SettingsWidget::extraButton, Ui_SettingsWidget::gridLayout, Ui_SettingsWidget::gridLayout_3, Ui_SettingsWidget::gridLayout_5, Ui_SettingsWidget::horizontalLayout, Ui_SettingsWidget::horizontalLayout_2, Ui_SettingsWidget::horizontalSpacer, Ui_SettingsWidget::horizontalSpacer_10, Ui_SettingsWidget::horizontalSpacer_2, Ui_SettingsWidget::horizontalSpacer_7, Ui_SettingsWidget::horizontalSpacer_9, Ui_SettingsWidget::label, Ui_SettingsWidget::label_2, Ui_SettingsWidget::label_3, Ui_SettingsWidget::label_5, Ui_SettingsWidget::label_6, Ui_SettingsWidget::label_8, Ui_SettingsWidget::layoutBox, Ui_SettingsWidget::line, Ui_SettingsWidget::line_2, Ui_SettingsWidget::line_3, Ui_SettingsWidget::loginItemBox, Ui_SettingsWidget::pushButton, Ui_SettingsWidget::retranslateUi(), Ui_SettingsWidget::shiftBox, Ui_SettingsWidget::shiftLabel, Ui_SettingsWidget::versionLabel, Ui_SettingsWidget::verticalSpacer, Ui_SettingsWidget::verticalSpacer_10, Ui_SettingsWidget::verticalSpacer_2, Ui_SettingsWidget::verticalSpacer_3, Ui_SettingsWidget::verticalSpacer_4, Ui_SettingsWidget::verticalSpacer_5, Ui_SettingsWidget::verticalSpacer_6, Ui_SettingsWidget::verticalSpacer_7, Ui_SettingsWidget::verticalSpacer_8, Ui_SettingsWidget::winBox, and Ui_SettingsWidget::winLabel.

Referenced by SettingsWidget::SettingsWidget().

```
    {
        if (SettingsWidget->objectName().isEmpty())
            SettingsWidget->setObjectName(QStringLiteral("SettingsWidget"));
        SettingsWidget->resize(827, 654);
        gridLayout = new QGridLayout(SettingsWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        label_2 = new QLabel(SettingsWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setOpenExternalLinks(true);
        label_2->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignVCenter);

        gridLayout->addWidget(label_2, 20, 0, 1, 2);

        label = new QLabel(SettingsWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        gridLayout->addWidget(label, 6, 0, 1, 2);

```

```
        label_6 = new QLabel(SettingsWidget);
        label_6->setObjectName(QStringLiteral("label_6"));
        label_6->setFont(font);

        gridLayout->addWidget(label_6, 12, 0, 1, 2);

        gridLayout_5 = new QGridLayout();
        gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_7, 2, 2, 1, 1);

        devicesLabel = new QLabel(SettingsWidget);
        devicesLabel->setObjectName(QStringLiteral("devicesLabel"));

        gridLayout_5->addWidget(devicesLabel, 0, 0, 1, 3);

        label_5 = new QLabel(SettingsWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout_5->addWidget(label_5, 2, 0, 1, 1);

        layoutBox = new QComboBox(SettingsWidget);
        layoutBox->setObjectName(QStringLiteral("layoutBox"));

        gridLayout_5->addWidget(layoutBox, 2, 1, 1, 1);

        verticalSpacer_10 = new QSpacerItem(20, 6, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_5->addItem(verticalSpacer_10, 1, 0, 1, 1);


        gridLayout->addLayout(gridLayout_5, 4, 1, 1, 1);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        label_3 = new QLabel(SettingsWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        label_3->setOpenExternalLinks(true);

        horizontalLayout_2->addWidget(label_3);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer);

        pushButton = new QPushButton(SettingsWidget);
        pushButton->setObjectName(QStringLiteral("pushButton"));
        pushButton->setFlat(false);

        horizontalLayout_2->addWidget(pushButton);


        gridLayout->addLayout(horizontalLayout_2, 21, 0, 1, 2);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer, 19, 0, 1, 2);

        verticalSpacer_8 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 16, 0, 1, 1);

        loginItemBox = new QCheckBox(SettingsWidget);
        loginItemBox->setObjectName(QStringLiteral("loginItemBox"));

        gridLayout->addWidget(loginItemBox, 16, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_6, 15, 0, 1, 1);

        autoFWBox = new QCheckBox(SettingsWidget);
        autoFWBox->setObjectName(QStringLiteral("autoFWBox"));
        autoFWBox->setChecked(true);

        gridLayout->addWidget(autoFWBox, 15, 1, 1, 1);

        line_2 = new QFrame(SettingsWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
```

```
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 13, 0, 1, 2);

        label_8 = new QLabel(SettingsWidget);
        label_8->setObjectName(QStringLiteral("label_8"));
        QFont font1;
        font1.setItalic(true);
        label_8->setFont(font1);

        gridLayout->addWidget(label_8, 8, 1, 1, 1);

        gridLayout_3 = new QGridLayout();
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        shiftLabel = new QLabel(SettingsWidget);
        shiftLabel->setObjectName(QStringLiteral("shiftLabel"));
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(shiftLabel->sizePolicy().hasHeightForWidth());
        shiftLabel->setSizePolicy(sizePolicy);
        shiftLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(shiftLabel, 0, 3, 1, 1);

        capsLabel = new QLabel(SettingsWidget);
        capsLabel->setObjectName(QStringLiteral("capsLabel"));
        capsLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(capsLabel, 0, 1, 1, 1);

        horizontalSpacer_10 = new QSpacerItem(0, 0, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_10, 0, 0, 1, 1);

        capsBox = new QComboBox(SettingsWidget);
        capsBox->setObjectName(QStringLiteral("capsBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(capsBox->sizePolicy().hasHeightForWidth());
        capsBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(capsBox, 0, 2, 1, 1);

        ctrlLabel = new QLabel(SettingsWidget);
        ctrlLabel->setObjectName(QStringLiteral("ctrlLabel"));
        ctrlLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(ctrlLabel, 1, 1, 1, 1);

        horizontalSpacer_9 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_9, 1, 7, 1, 1);

        ctrlBox = new QComboBox(SettingsWidget);
        ctrlBox->setObjectName(QStringLiteral("ctrlBox"));

        gridLayout_3->addWidget(ctrlBox, 1, 2, 1, 1);

        shiftBox = new QComboBox(SettingsWidget);
        shiftBox->setObjectName(QStringLiteral("shiftBox"));
        sizePolicy1.setHeightForWidth(shiftBox->sizePolicy().hasHeightForWidth());
        shiftBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(shiftBox, 0, 4, 1, 1);

        winLabel = new QLabel(SettingsWidget);
        winLabel->setObjectName(QStringLiteral("winLabel"));
        sizePolicy.setHeightForWidth(winLabel->sizePolicy().hasHeightForWidth());
        winLabel->setSizePolicy(sizePolicy);
        winLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(winLabel, 1, 3, 1, 1);

        winBox = new QComboBox(SettingsWidget);
        winBox->setObjectName(QStringLiteral("winBox"));
        sizePolicy1.setHeightForWidth(winBox->sizePolicy().hasHeightForWidth());
        winBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(winBox, 1, 4, 1, 1);

        altBox = new QComboBox(SettingsWidget);
        altBox->setObjectName(QStringLiteral("altBox"));
        sizePolicy1.setHeightForWidth(altBox->sizePolicy().hasHeightForWidth());
```

```
        altBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(altBox, 1, 6, 1, 1);

        altLabel = new QLabel(SettingsWidget);
        altLabel->setObjectName(QStringLiteral("altLabel"));
        sizePolicy.setHeightForWidth(altLabel->sizePolicy().hasHeightForWidth());
        altLabel->setSizePolicy(sizePolicy);
        altLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(altLabel, 1, 5, 1, 1);


        gridLayout->addLayout(gridLayout_3, 10, 1, 1, 1);

        line = new QFrame(SettingsWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 1, 0, 1, 2);

        verticalSpacer_3 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_3, 2, 1, 1, 1);

        verticalSpacer_5 = new QSpacerItem(20, 12, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_5, 11, 1, 1, 1);

        line_3 = new QFrame(SettingsWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        QSizePolicy sizePolicy2(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(line_3->sizePolicy().hasHeightForWidth());
        line_3->setSizePolicy(sizePolicy2);
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 7, 0, 1, 2);

        verticalSpacer_4 = new QSpacerItem(20, 6, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_4, 9, 1, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 12, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_2, 5, 1, 1, 1);

        versionLabel = new QLabel(SettingsWidget);
        versionLabel->setObjectName(QStringLiteral("versionLabel"));
        versionLabel->setFont(font);

        gridLayout->addWidget(versionLabel, 0, 0, 1, 2);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        extraButton = new QPushButton(SettingsWidget);
        extraButton->setObjectName(QStringLiteral("extraButton"));

        horizontalLayout->addWidget(extraButton);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_2);


        gridLayout->addLayout(horizontalLayout, 17, 1, 1, 1);

        verticalSpacer_7 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_7, 17, 0, 1, 1);


        retranslateUi(SettingsWidget);

        QMetaObject::connectSlotsByName(SettingsWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.83.3 Field Documentation

12.83.3.1 QComboBox* Ui_SettingsWidget::altBox [inherited]

Definition at line 64 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::updateModifiers().

12.83.3.2 QLabel* Ui_SettingsWidget::altLabel [inherited]

Definition at line 65 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.3 QCheckBox* Ui_SettingsWidget::autoFWBox [inherited]

Definition at line 50 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), SettingsWidget::SettingsWidget(), and Ui_SettingsWidget::setupUi().

12.83.3.4 QComboBox* Ui_SettingsWidget::capsBox [inherited]

Definition at line 57 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::updateModifiers().

12.83.3.5 QLabel* Ui_SettingsWidget::capsLabel [inherited]

Definition at line 55 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.6 QComboBox* Ui_SettingsWidget::ctrlBox [inherited]

Definition at line 60 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::updateModifiers().

12.83.3.7 QLabel* Ui_SettingsWidget::ctrlLabel [inherited]

Definition at line 58 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.8 QLabel* Ui_SettingsWidget::devicesLabel [inherited]

Definition at line 38 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), SettingsWidget::setStatus(), and Ui_SettingsWidget::setupUi().

12.83.3.9 QPushButton* Ui_SettingsWidget::extraButton [inherited]

Definition at line 74 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.10 QGridLayout* Ui_SettingsWidget::gridLayout [inherited]

Definition at line 32 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.11 QGridLayout* Ui_SettingsWidget::gridLayout_3 [inherited]

Definition at line 53 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.12 QGridLayout* Ui_SettingsWidget::gridLayout_5 [inherited]

Definition at line 36 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.13 QHBoxLayout* Ui_SettingsWidget::horizontalLayout [inherited]

Definition at line 73 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.14 QHBoxLayout* Ui_SettingsWidget::horizontalLayout_2 [inherited]

Definition at line 42 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.15 QSpacerItem* Ui_SettingsWidget::horizontalSpacer [inherited]

Definition at line 44 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.16 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_10 [inherited]

Definition at line 56 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.17 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_2 [inherited]

Definition at line 75 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.18 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_7 [inherited]

Definition at line 37 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.19 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_9 [inherited]

Definition at line 59 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.20 QLabel* Ui_SettingsWidget::label [inherited]

Definition at line 34 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.21 QLabel* Ui_SettingsWidget::label_2 [inherited]

Definition at line 33 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.22 QLabel* Ui_SettingsWidget::label_3 [inherited]

Definition at line 43 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.23 QLabel* Ui_SettingsWidget::label_5 [inherited]

Definition at line 39 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.24 QLabel* Ui_SettingsWidget::label_6 [inherited]

Definition at line 35 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.25 QLabel* Ui_SettingsWidget::label_8 [inherited]

Definition at line 52 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.26 QComboBox* Ui_SettingsWidget::layoutBox [inherited]

Definition at line 40 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::showLayoutDialog().

12.83.3.27 QFrame* Ui_SettingsWidget::line [inherited]

Definition at line 66 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.28 QFrame* Ui_SettingsWidget::line_2 [inherited]

Definition at line 51 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.29 QFrame* Ui_SettingsWidget::line_3 [inherited]

Definition at line 69 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.30 QCheckBox* Ui_SettingsWidget::loginItemBox [inherited]

Definition at line 48 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), SettingsWidget::SettingsWidget(), and Ui_SettingsWidget::setupUi().

12.83.3.31 QPushButton* Ui_SettingsWidget::pushButton [inherited]

Definition at line 45 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.32 QComboBox* Ui_SettingsWidget::shiftBox [inherited]

Definition at line 61 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::updateModifiers().

12.83.3.33 QLabel* Ui_SettingsWidget::shiftLabel [inherited]

Definition at line 54 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

12.83.3.34 QLabel* Ui_SettingsWidget::versionLabel [inherited]

Definition at line 72 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), Ui_SettingsWidget::setupUi(), and SettingsWidget::setVersion().

12.83.3.35 QSpacerItem* Ui_SettingsWidget::verticalSpacer [inherited]

Definition at line 46 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.36 QSpacerItem* Ui_SettingsWidget::verticalSpacer_10 [inherited]

Definition at line 41 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.37 QSpacerItem* Ui_SettingsWidget::verticalSpacer_2 [inherited]

Definition at line 71 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.38 QSpacerItem* Ui_SettingsWidget::verticalSpacer_3 [inherited]

Definition at line 67 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.39 QSpacerItem* Ui_SettingsWidget::verticalSpacer_4 [inherited]

Definition at line 70 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.40 QSpacerItem* Ui_SettingsWidget::verticalSpacer_5 [inherited]

Definition at line 68 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.41 QSpacerItem* Ui_SettingsWidget::verticalSpacer_6 [inherited]

Definition at line 49 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.42 QSpacerItem* Ui_SettingsWidget::verticalSpacer_7 [inherited]

Definition at line 76 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.43 QSpacerItem* Ui_SettingsWidget::verticalSpacer_8 [inherited]

Definition at line 47 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::setupUi().

12.83.3.44 QComboBox* Ui_SettingsWidget::winBox [inherited]

Definition at line 63 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), Ui_SettingsWidget::setupUi(), and SettingsWidget::updateModifiers().

12.83.3.45 QLabel* Ui_SettingsWidget::winLabel [inherited]

Definition at line 62 of file ui_settingswidget.h.

Referenced by Ui_SettingsWidget::retranslateUi(), and Ui_SettingsWidget::setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_settingswidget.h

12.84 SGroup Class Reference

```
#include <src/ckb/ckbsettings.h>
```

Collaboration diagram for SGroup:

Public Member Functions

- SGroup (CkbSettings &settings, const QString &prefix)
- ~SGroup ()

Private Attributes

- CkbSettings & _settings

12.84.1 Detailed Description

Definition at line 57 of file ckbsettings.h.

12.84.2 Constructor & Destructor Documentation

12.84.2.1 SGroup::SGroup (CkbSettings & *settings*, const QString & *prefix*) [inline]

Definition at line 60 of file ckbsettings.h.

References CkbSettings::beginGroup().

```
60 : _settings(settings) { settings.beginGroup(prefix); }
```

Here is the call graph for this function:

12.84.2.2 SGroup::~SGroup ( ) [inline]

Definition at line 61 of file ckbsettings.h.

References _settings, and CkbSettings::endGroup().

```
61 { _settings.endGroup(); }
```

Here is the call graph for this function:

12.84.3 Field Documentation

12.84.3.1 CkbSettings& SGroup::_settings [private]

Definition at line 64 of file ckbsettings.h.

Referenced by ~SGroup().

The documentation for this class was generated from the following file:

- src/ckb/ckbsettings.h

12.85 Ui_AnimAddDialog Class Reference

`#include <src/ckb/ui_animadddialog.h>`

Inheritance diagram for Ui_AnimAddDialog:

Collaboration diagram for Ui_AnimAddDialog:

Public Member Functions

- void setupUi (QDialog *AnimAddDialog)
- void retranslateUi (QDialog *AnimAddDialog)

Data Fields

- QGridLayout * gridLayout
- QHBoxLayout * horizontalLayout
- QDialogButtonBox * buttonBox
- QSpacerItem * horizontalSpacer_2
- QComboBox * animBox
- QLabel * label_2
- QSpacerItem * verticalSpacer_2
- QLabel * label
- QSpacerItem * verticalSpacer_3
- QComboBox * presetBox
- QSpacerItem * horizontalSpacer
- QCheckBox * previewBox

12.85.1 Detailed Description

Definition at line 28 of file ui_animadddialog.h.

12.85.2 Member Function Documentation

12.85.2.1 void Ui_AnimAddDialog::retranslateUi (QDialog * *AnimAddDialog*) [inline]

Definition at line 135 of file ui_animadddialog.h.

References label, label_2, and previewBox.

Referenced by setupUi().

```
136     {
137         AnimAddDialog->setWindowTitle(QApplication::translate("AnimAddDialog", "Add Animation", Q_NULLPTR))
    ;
138         label_2->setText(QApplication::translate("AnimAddDialog", "Preset:", Q_NULLPTR));
139         label->setText(QApplication::translate("AnimAddDialog", "Animation:", Q_NULLPTR));
140         previewBox->setText(QApplication::translate("AnimAddDialog", "Show preview", Q_NULLPTR));
141     } // retranslateUi
```

Here is the caller graph for this function:

12.85.2.2 void Ui_AnimAddDialog::setupUi (QDialog * *AnimAddDialog*) [inline]

Definition at line 44 of file ui_animadddialog.h.

References animBox, buttonBox, gridLayout, horizontalLayout, horizontalSpacer, horizontalSpacer_2, label, label_2, presetBox, previewBox, retranslateUi(), verticalSpacer_2, and verticalSpacer_3.

Referenced by AnimAddDialog::AnimAddDialog().

```
45     {
46         if (AnimAddDialog->objectName().isEmpty())
47             AnimAddDialog->setObjectName(QStringLiteral("AnimAddDialog"));
48         AnimAddDialog->resize(350, 205);
```

```
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(AnimAddDialog->sizePolicy().hasHeightForWidth());
        AnimAddDialog->setSizePolicy(sizePolicy);
        gridLayout = new QGridLayout(AnimAddDialog);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        buttonBox = new QDialogButtonBox(AnimAddDialog);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
        buttonBox->setCenterButtons(false);

        horizontalLayout->addWidget(buttonBox);


        gridLayout->addLayout(horizontalLayout, 5, 0, 1, 4);

        horizontalSpacer_2 = new QSpacerItem(50, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_2, 1, 3, 1, 1);

        animBox = new QComboBox(AnimAddDialog);
        animBox->setObjectName(QStringLiteral("animBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(animBox->sizePolicy().hasHeightForWidth());
        animBox->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(animBox, 1, 2, 1, 1);

        label_2 = new QLabel(AnimAddDialog);
        label_2->setObjectName(QStringLiteral("label_2"));
        QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Preferred);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(label_2->sizePolicy().hasHeightForWidth());
        label_2->setSizePolicy(sizePolicy2);
        label_2->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout->addWidget(label_2, 2, 1, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer_2, 4, 2, 1, 1);

        label = new QLabel(AnimAddDialog);
        label->setObjectName(QStringLiteral("label"));
        sizePolicy2.setHeightForWidth(label->sizePolicy().hasHeightForWidth());
        label->setSizePolicy(sizePolicy2);
        label->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout->addWidget(label, 1, 1, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer_3, 0, 2, 1, 1);

        presetBox = new QComboBox(AnimAddDialog);
        presetBox->setObjectName(QStringLiteral("presetBox"));
        sizePolicy1.setHeightForWidth(presetBox->sizePolicy().hasHeightForWidth());
        presetBox->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(presetBox, 2, 2, 1, 1);

        horizontalSpacer = new QSpacerItem(50, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 1, 0, 1, 1);

        previewBox = new QCheckBox(AnimAddDialog);
        previewBox->setObjectName(QStringLiteral("previewBox"));
        previewBox->setChecked(true);

        gridLayout->addWidget(previewBox, 3, 2, 1, 1);


        retranslateUi(AnimAddDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), AnimAddDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), AnimAddDialog, SLOT(reject()));

```

```
        QMetaObject::connectSlotsByName(AnimAddDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.85.3 Field Documentation

12.85.3.1 QComboBox* Ui_AnimAddDialog::animBox

Definition at line 35 of file ui_animadddialog.h.

Referenced by AnimAddDialog::AnimAddDialog(), AnimAddDialog::chosenScript(), and setupUi().

12.85.3.2 QDialogButtonBox* Ui_AnimAddDialog::buttonBox

Definition at line 33 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.3 QGridLayout* Ui_AnimAddDialog::gridLayout

Definition at line 31 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.4 QHBoxLayout* Ui_AnimAddDialog::horizontalLayout

Definition at line 32 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.5 QSpacerItem* Ui_AnimAddDialog::horizontalSpacer

Definition at line 41 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.6 QSpacerItem* Ui_AnimAddDialog::horizontalSpacer_2

Definition at line 34 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.7 QLabel* Ui_AnimAddDialog::label

Definition at line 38 of file ui_animadddialog.h.

Referenced by retranslateUi(), and setupUi().

12.85.3.8 QLabel* Ui_AnimAddDialog::label_2

Definition at line 36 of file ui_animadddialog.h.

Referenced by retranslateUi(), and setupUi().

12.85.3.9 QComboBox* Ui_AnimAddDialog::presetBox

Definition at line 40 of file ui_animadddialog.h.

Referenced by AnimAddDialog::chosenPreset(), AnimAddDialog::on_animBox_activated(), AnimAddDialog::on_previewBox_clicked(), and setupUi().

12.85.3.10 QCheckBox* Ui_AnimAddDialog::previewBox

Definition at line 42 of file ui_animadddialog.h.

Referenced by retranslateUi(), and setupUi().

12.85.3.11 QSpacerItem* Ui_AnimAddDialog::verticalSpacer_2

Definition at line 37 of file ui_animadddialog.h.

Referenced by setupUi().

12.85.3.12 QSpacerItem* Ui_AnimAddDialog::verticalSpacer_3

Definition at line 39 of file ui_animadddialog.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_animadddialog.h

12.86 Ui_AnimSettingDialog Class Reference

```
#include <src/ckb/ui_animsettingdialog.h>
```

Inheritance diagram for Ui_AnimSettingDialog:

Collaboration diagram for Ui_AnimSettingDialog:

Public Member Functions

- void setupUi (QDialog *AnimSettingDialog)
- void retranslateUi (QDialog *AnimSettingDialog)

Data Fields

- QGridLayout * gridLayout
- QDialogButtonBox * buttonBox
- QTabWidget * tabWidget
- QWidget * settingTab
- QGridLayout * settingsGrid
- QLabel * label_2
- QSpacerItem * horizontalSpacer_3
- QLineEdit * animName
- QWidget * timeTab
- QGridLayout * timeGrid
- QSpacerItem * horizontalSpacer_5
- QLabel * kpRepeatLabel
- QLabel * repeatLabel
- QDoubleSpinBox * repeatBox
- QLabel * repeatLabel_2
- QFrame * line
- QLabel * kpRepeatLabel_2
- QLabel * label_4
- QLabel * label_8
- QDoubleSpinBox * kpDelayBox
- QLabel * label_13
- QLabel * label_12
- QDoubleSpinBox * delayBox
- QCheckBox * kpModeStopBox
- QLabel * label_10
- QSpacerItem * verticalSpacer_3
- QSpacerItem * horizontalSpacer_4
- QCheckBox * kpReleaseBox
- QLabel * label_6
- QDoubleSpinBox * kpRepeatBox
- QSpacerItem * verticalSpacer_2
- QFrame * line_2
- QSpacerItem * horizontalSpacer_6
- QWidget * infoTab
- QGridLayout * gridLayout_2
- QLabel * sNameLabel
- QLabel * label_7
- QLabel * label_11
- QLabel * sAuthorLabel
- QLabel * label_9
- QLabel * label_5
- QLabel * sYearLabel
- QLabel * label_3
- QSpacerItem * horizontalSpacer
- QSpacerItem * horizontalSpacer_2
- QLabel * sVerLabel
- QLabel * sLicenseLabel
- QLabel * label
- QSpacerItem * verticalSpacer
- QLabel * sDescLabel

12.86.1 Detailed Description

Definition at line 31 of file ui_animsettingdialog.h.

12.86.2 Member Function Documentation

12.86.2.1 void Ui_AnimSettingDialog::retranslateUi (QDialog * *AnimSettingDialog*) [inline]

Definition at line 349 of file ui_animsettingdialog.h.

References infoTab, kpModeStopBox, kpReleaseBox, kpRepeatLabel, kpRepeatLabel_2, label, label_10, label_11, label_12, label_13, label_2, label_3, label_4, label_5, label_6, label_7, label_8, label_9, repeatLabel, repeatLabel_2, sAuthorLabel, sDescLabel, settingTab, sLicenseLabel, sNameLabel, sVerLabel, sYearLabel, tabWidget, and timeTab.

Referenced by setupUi().

```
    {
        AnimSettingDialog->setWindowTitle(QApplication::translate("AnimSettingDialog", "Dialog", Q_NULLPTR));
        label_2->setText(QApplication::translate("AnimSettingDialog", "Name:", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(settingTab), QApplication::translate("AnimSettingDialog", "Settings", Q_NULLPTR));
        kpRepeatLabel->setText(QApplication::translate("AnimSettingDialog", "Repeat every:", Q_NULLPTR));
        repeatLabel->setText(QApplication::translate("AnimSettingDialog", "Repeat every:", Q_NULLPTR));
        repeatLabel_2->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        kpRepeatLabel_2->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        label_4->setText(QApplication::translate("AnimSettingDialog", "<b>On mode start</b>", Q_NULLPTR));
        label_8->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        label_13->setText(QApplication::translate("AnimSettingDialog", "seconds", Q_NULLPTR));
        label_12->setText(QApplication::translate("AnimSettingDialog", "Start delay:", Q_NULLPTR));
        kpModeStopBox->setText(QApplication::translate("AnimSettingDialog", "Stop on key press", Q_NULLPTR));
        label_10->setText(QApplication::translate("AnimSettingDialog", "Start delay:", Q_NULLPTR));
        kpReleaseBox->setText(QApplication::translate("AnimSettingDialog", "Stop on key release", Q_NULLPTR));
        label_6->setText(QApplication::translate("AnimSettingDialog", "<b>On key press</b>", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(timeTab), QApplication::translate("AnimSettingDialog", "Timing", Q_NULLPTR));
        sNameLabel->setText(QApplication::translate("AnimSettingDialog", "Name", Q_NULLPTR));
        label_7->setText(QApplication::translate("AnimSettingDialog", "Year:", Q_NULLPTR));
        label_11->setText(QApplication::translate("AnimSettingDialog", "Description:", Q_NULLPTR));
        sAuthorLabel->setText(QApplication::translate("AnimSettingDialog", "Author", Q_NULLPTR));
        label_9->setText(QApplication::translate("AnimSettingDialog", "License:", Q_NULLPTR));
        label_5->setText(QApplication::translate("AnimSettingDialog", "Version:", Q_NULLPTR));
        sYearLabel->setText(QApplication::translate("AnimSettingDialog", "Year", Q_NULLPTR));
        label_3->setText(QApplication::translate("AnimSettingDialog", "Author:", Q_NULLPTR));
        sVerLabel->setText(QApplication::translate("AnimSettingDialog", "Version", Q_NULLPTR));
        sLicenseLabel->setText(QApplication::translate("AnimSettingDialog", "License", Q_NULLPTR));
        label->setText(QApplication::translate("AnimSettingDialog", "Script name:", Q_NULLPTR));
        sDescLabel->setText(QApplication::translate("AnimSettingDialog", "Description", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(infoTab), QApplication::translate("AnimSettingDialog", "About", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.86.2.2 void Ui_AnimSettingDialog::setupUi (QDialog * *AnimSettingDialog*) [inline]

Definition at line 85 of file ui_animsettingdialog.h.

References animName, buttonBox, delayBox, gridLayout, gridLayout_2, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, horizontalSpacer_6, infoTab, kpDelayBox, kpModeStopBox, kpReleaseBox, kpRepeatBox, kpRepeatLabel, kpRepeatLabel_2, label, label_10, label_11, label_12, label_13, label_2, label_3, label_4, label_5, label_6, label_7, label_8, label_9, line, line_2, repeatBox, repeatLabel, repeatLabel_2, retranslateUi(), sAuthorLabel, sDescLabel, settingsGrid, settingTab, sLicenseLabel, sNameLabel, sVerLabel, sYearLabel, tabWidget, timeGrid, timeTab, verticalSpacer, verticalSpacer_2, and verticalSpacer_3.

Referenced by AnimSettingDialog::AnimSettingDialog().

```
86     {
87         if (AnimSettingDialog->objectName().isEmpty())
88             AnimSettingDialog->setObjectName(QStringLiteral("AnimSettingDialog"));
89         AnimSettingDialog->resize(480, 457);
90         AnimSettingDialog->setMinimumSize(QSize(480, 0));
91         AnimSettingDialog->setFocusPolicy(Qt::ClickFocus);
92         gridLayout = new QGridLayout(AnimSettingDialog);
93         gridLayout->setObjectName(QStringLiteral("gridLayout"));
94         buttonBox = new QDialogButtonBox(AnimSettingDialog);
95         buttonBox->setObjectName(QStringLiteral("buttonBox"));
96         buttonBox->setOrientation(Qt::Horizontal);
97         buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
98
99         gridLayout->addWidget(buttonBox, 2, 0, 1, 1);
100
101         tabWidget = new QTabWidget(AnimSettingDialog);
102         tabWidget->setObjectName(QStringLiteral("tabWidget"));
103         settingTab = new QWidget();
104         settingTab->setObjectName(QStringLiteral("settingTab"));
105         settingsGrid = new QGridLayout(settingTab);
106         settingsGrid->setSpacing(12);
107         settingsGrid->setObjectName(QStringLiteral("settingsGrid"));
108         settingsGrid->setContentsMargins(12, 12, 12, 12);
109         label_2 = new QLabel(settingTab);
110         label_2->setObjectName(QStringLiteral("label_2"));
111
112         settingsGrid->addWidget(label_2, 0, 1, 1, 1);
113
114         horizontalSpacer_3 = new QSpacerItem(5, 0, QSizePolicy::Fixed,
    QSizePolicy::Minimum);
115
116         settingsGrid->addItem(horizontalSpacer_3, 0, 2, 1, 1);
117
118         animName = new QLineEdit(settingTab);
119         animName->setObjectName(QStringLiteral("animName"));
120
121         settingsGrid->addWidget(animName, 0, 3, 1, 3);
122
123         tabWidget->addTab(settingTab, QString());
124         timeTab = new QWidget();
125         timeTab->setObjectName(QStringLiteral("timeTab"));
126         timeGrid = new QGridLayout(timeTab);
127         timeGrid->setSpacing(12);
128         timeGrid->setObjectName(QStringLiteral("timeGrid"));
129         timeGrid->setContentsMargins(12, 12, 12, 12);
130         horizontalSpacer_5 = new QSpacerItem(15, 0, QSizePolicy::Fixed,
    QSizePolicy::Minimum);
131
132         timeGrid->addItem(horizontalSpacer_5, 3, 2, 1, 1);
133
134         kpRepeatLabel = new QLabel(timeTab);
135         kpRepeatLabel->setObjectName(QStringLiteral("kpRepeatLabel"));
136
137         timeGrid->addWidget(kpRepeatLabel, 11, 1, 1, 1);
138
139         repeatLabel = new QLabel(timeTab);
140         repeatLabel->setObjectName(QStringLiteral("repeatLabel"));
141
142         timeGrid->addWidget(repeatLabel, 3, 1, 1, 1);
143
144         repeatBox = new QDoubleSpinBox(timeTab);
145         repeatBox->setObjectName(QStringLiteral("repeatBox"));
146         repeatBox->setDecimals(1);
147         repeatBox->setMinimum(0.1);
148         repeatBox->setMaximum(86400);
149
150         timeGrid->addWidget(repeatBox, 3, 3, 1, 1);
151
152         repeatLabel_2 = new QLabel(timeTab);
153         repeatLabel_2->setObjectName(QStringLiteral("repeatLabel_2"));
```

```
        timeGrid->addWidget(repeatLabel_2, 3, 4, 1, 1);

        line = new QFrame(timeTab);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        timeGrid->addWidget(line, 1, 0, 1, 6);

        kpRepeatLabel_2 = new QLabel(timeTab);
        kpRepeatLabel_2->setObjectName(QStringLiteral("kpRepeatLabel_2"));

        timeGrid->addWidget(kpRepeatLabel_2, 11, 4, 1, 1);

        label_4 = new QLabel(timeTab);
        label_4->setObjectName(QStringLiteral("label_4"));

        timeGrid->addWidget(label_4, 0, 0, 1, 6);

        label_8 = new QLabel(timeTab);
        label_8->setObjectName(QStringLiteral("label_8"));

        timeGrid->addWidget(label_8, 2, 4, 1, 1);

        kpDelayBox = new QDoubleSpinBox(timeTab);
        kpDelayBox->setObjectName(QStringLiteral("kpDelayBox"));
        kpDelayBox->setDecimals(1);
        kpDelayBox->setMaximum(86400);

        timeGrid->addWidget(kpDelayBox, 10, 3, 1, 1);

        label_13 = new QLabel(timeTab);
        label_13->setObjectName(QStringLiteral("label_13"));

        timeGrid->addWidget(label_13, 10, 4, 1, 1);

        label_12 = new QLabel(timeTab);
        label_12->setObjectName(QStringLiteral("label_12"));

        timeGrid->addWidget(label_12, 10, 1, 1, 1);

        delayBox = new QDoubleSpinBox(timeTab);
        delayBox->setObjectName(QStringLiteral("delayBox"));
        delayBox->setDecimals(1);
        delayBox->setMaximum(86400);

        timeGrid->addWidget(delayBox, 2, 3, 1, 1);

        kpModeStopBox = new QCheckBox(timeTab);
        kpModeStopBox->setObjectName(QStringLiteral("kpModeStopBox"));

        timeGrid->addWidget(kpModeStopBox, 5, 1, 1, 3);

        label_10 = new QLabel(timeTab);
        label_10->setObjectName(QStringLiteral("label_10"));

        timeGrid->addWidget(label_10, 2, 1, 1, 1);

        verticalSpacer_3 = new QSpacerItem(0, 10, QSizePolicy::Minimum, QSizePolicy::Fixed)
;

        timeGrid->addItem(verticalSpacer_3, 7, 1, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        timeGrid->addItem(horizontalSpacer_4, 2, 5, 1, 1);

        kpReleaseBox = new QCheckBox(timeTab);
        kpReleaseBox->setObjectName(QStringLiteral("kpReleaseBox"));

        timeGrid->addWidget(kpReleaseBox, 14, 1, 1, 3);

        label_6 = new QLabel(timeTab);
        label_6->setObjectName(QStringLiteral("label_6"));

        timeGrid->addWidget(label_6, 8, 0, 1, 6);

        kpRepeatBox = new QDoubleSpinBox(timeTab);
        kpRepeatBox->setObjectName(QStringLiteral("kpRepeatBox"));
        kpRepeatBox->setDecimals(1);
        kpRepeatBox->setMinimum(0.1);
        kpRepeatBox->setMaximum(86400);

        timeGrid->addWidget(kpRepeatBox, 11, 3, 1, 1);

```

```
        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        timeGrid->addItem(verticalSpacer_2, 15, 1, 1, 1);

        line_2 = new QFrame(timeTab);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        timeGrid->addWidget(line_2, 9, 0, 1, 6);

        horizontalSpacer_6 = new QSpacerItem(0, 0, QSizePolicy::Fixed, QSizePolicy::Minimum);

        timeGrid->addItem(horizontalSpacer_6, 12, 2, 1, 1);

        tabWidget->addTab(timeTab, QString());
        infoTab = new QWidget();
        infoTab->setObjectName(QStringLiteral("infoTab"));
        gridLayout_2 = new QGridLayout(infoTab);
        gridLayout_2->setSpacing(12);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(12, 12, 12, 12);
        sNameLabel = new QLabel(infoTab);
        sNameLabel->setObjectName(QStringLiteral("sNameLabel"));

        gridLayout_2->addWidget(sNameLabel, 0, 2, 1, 1);

        label_7 = new QLabel(infoTab);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout_2->addWidget(label_7, 3, 0, 1, 1);

        label_11 = new QLabel(infoTab);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout_2->addWidget(label_11, 5, 0, 1, 1);

        sAuthorLabel = new QLabel(infoTab);
        sAuthorLabel->setObjectName(QStringLiteral("sAuthorLabel"));

        gridLayout_2->addWidget(sAuthorLabel, 2, 2, 1, 1);

        label_9 = new QLabel(infoTab);
        label_9->setObjectName(QStringLiteral("label_9"));

        gridLayout_2->addWidget(label_9, 4, 0, 1, 1);

        label_5 = new QLabel(infoTab);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout_2->addWidget(label_5, 1, 0, 1, 1);

        sYearLabel = new QLabel(infoTab);
        sYearLabel->setObjectName(QStringLiteral("sYearLabel"));

        gridLayout_2->addWidget(sYearLabel, 3, 2, 1, 1);

        label_3 = new QLabel(infoTab);
        label_3->setObjectName(QStringLiteral("label_3"));

        gridLayout_2->addWidget(label_3, 2, 0, 1, 1);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer, 0, 3, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(20, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_2, 0, 1, 1, 1);

        sVerLabel = new QLabel(infoTab);
        sVerLabel->setObjectName(QStringLiteral("sVerLabel"));

        gridLayout_2->addWidget(sVerLabel, 1, 2, 1, 1);

        sLicenseLabel = new QLabel(infoTab);
        sLicenseLabel->setObjectName(QStringLiteral("sLicenseLabel"));

        gridLayout_2->addWidget(sLicenseLabel, 4, 2, 1, 1);

        label = new QLabel(infoTab);
        label->setObjectName(QStringLiteral("label"));

```

```
        gridLayout_2->addWidget(label, 0, 0, 1, 1);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

        gridLayout_2->addItem(verticalSpacer, 6, 0, 1, 1);

        sDescLabel = new QLabel(infoTab);
        sDescLabel->setObjectName(QStringLiteral("sDescLabel"));
        sDescLabel->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignTop);

        gridLayout_2->addWidget(sDescLabel, 5, 2, 2, 2);

        tabWidget->addTab(infoTab, QString());

        gridLayout->addWidget(tabWidget, 0, 0, 1, 1);


        retranslateUi(AnimSettingDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), AnimSettingDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), AnimSettingDialog, SLOT(reject()));

        tabWidget->setCurrentIndex(0);


        QMetaObject::connectSlotsByName(AnimSettingDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.86.3 Field Documentation

12.86.3.1 QLineEdit* Ui_AnimSettingDialog::animName

Definition at line 41 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), AnimSettingDialog::name(), and setupUi().

12.86.3.2 QDialogButtonBox* Ui_AnimSettingDialog::buttonBox

Definition at line 35 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.3 QDoubleSpinBox* Ui_AnimSettingDialog::delayBox

Definition at line 56 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.4 QGridLayout* Ui_AnimSettingDialog::gridLayout

Definition at line 34 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.5 QGridLayout* Ui_AnimSettingDialog::gridLayout_2

Definition at line 68 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.6 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer

Definition at line 77 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.7 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_2

Definition at line 78 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.8 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_3

Definition at line 40 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.9 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_4

Definition at line 60 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.10 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_5

Definition at line 44 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.11 QSpacerItem* Ui_AnimSettingDialog::horizontalSpacer_6

Definition at line 66 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.12 QWidget* Ui_AnimSettingDialog::infoTab

Definition at line 67 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.13 QDoubleSpinBox* Ui_AnimSettingDialog::kpDelayBox

Definition at line 53 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.14 QCheckBox* Ui_AnimSettingDialog::kpModeStopBox

Definition at line 57 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.15 QCheckBox* Ui_AnimSettingDialog::kpReleaseBox

Definition at line 61 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.16 QDoubleSpinBox* Ui_AnimSettingDialog::kpRepeatBox

Definition at line 63 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.17 QLabel* Ui_AnimSettingDialog::kpRepeatLabel

Definition at line 45 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.18 QLabel* Ui_AnimSettingDialog::kpRepeatLabel_2

Definition at line 50 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.19 QLabel* Ui_AnimSettingDialog::label

Definition at line 81 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.20 QLabel* Ui_AnimSettingDialog::label_10

Definition at line 58 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.21 QLabel* Ui_AnimSettingDialog::label_11

Definition at line 71 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.22 QLabel* Ui_AnimSettingDialog::label_12

Definition at line 55 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.23 QLabel* Ui_AnimSettingDialog::label_13

Definition at line 54 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.24 QLabel* Ui_AnimSettingDialog::label_2

Definition at line 39 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.25 QLabel* Ui_AnimSettingDialog::label_3

Definition at line 76 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.26 QLabel* Ui_AnimSettingDialog::label_4

Definition at line 51 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.27 QLabel* Ui_AnimSettingDialog::label_5

Definition at line 74 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.28 QLabel* Ui_AnimSettingDialog::label_6

Definition at line 62 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.29 QLabel* Ui_AnimSettingDialog::label_7

Definition at line 70 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.30 QLabel* Ui_AnimSettingDialog::label_8

Definition at line 52 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.31 QLabel* Ui_AnimSettingDialog::label_9

Definition at line 73 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.32 QFrame* Ui_AnimSettingDialog::line

Definition at line 49 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.33 QFrame* Ui_AnimSettingDialog::line_2

Definition at line 65 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.34 QDoubleSpinBox* Ui_AnimSettingDialog::repeatBox

Definition at line 47 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.35 QLabel* Ui_AnimSettingDialog::repeatLabel

Definition at line 46 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.36 QLabel* Ui_AnimSettingDialog::repeatLabel_2

Definition at line 48 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.37 QLabel* Ui_AnimSettingDialog::sAuthorLabel

Definition at line 72 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.38 QLabel* Ui_AnimSettingDialog::sDescLabel

Definition at line 83 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.39 QGridLayout* Ui_AnimSettingDialog::settingsGrid

Definition at line 38 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.40 QWidget* Ui_AnimSettingDialog::settingTab

Definition at line 37 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.41 QLabel* Ui_AnimSettingDialog::sLicenseLabel

Definition at line 80 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.42 QLabel* Ui_AnimSettingDialog::sNameLabel

Definition at line 69 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.43 QLabel* Ui_AnimSettingDialog::sVerLabel

Definition at line 79 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.44 QLabel* Ui_AnimSettingDialog::sYearLabel

Definition at line 75 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), retranslateUi(), and setupUi().

12.86.3.45 QTabWidget* Ui_AnimSettingDialog::tabWidget

Definition at line 36 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.46 QGridLayout* Ui_AnimSettingDialog::timeGrid

Definition at line 43 of file ui_animsettingdialog.h.

Referenced by AnimSettingDialog::AnimSettingDialog(), and setupUi().

12.86.3.47 QWidget* Ui_AnimSettingDialog::timeTab

Definition at line 42 of file ui_animsettingdialog.h.

Referenced by retranslateUi(), and setupUi().

12.86.3.48 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer

Definition at line 82 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.49 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer_2

Definition at line 64 of file ui_animsettingdialog.h.

Referenced by setupUi().

12.86.3.50 QSpacerItem* Ui_AnimSettingDialog::verticalSpacer_3

Definition at line 59 of file ui_animsettingdialog.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_animsettingdialog.h

12.87 Ui_ExtraSettingsWidget Class Reference

```
#include <src/ckb/ui_extrasettingswidget.h>
```

Inheritance diagram for Ui_ExtraSettingsWidget:

Collaboration diagram for Ui_ExtraSettingsWidget:

Public Member Functions

- void setupUi (QDialog *ExtraSettingsWidget)
- void retranslateUi (QDialog *ExtraSettingsWidget)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QSpacerItem * verticalSpacer_2
- QLabel * fpsWarnLabel
- QSpacerItem * horizontalSpacer_3
- QLabel * label_3
- QSpinBox * fpsBox
- QSpacerItem * verticalSpacer_4
- QSpacerItem * verticalSpacer_9
- QLabel * label_6
- QSpacerItem * verticalSpacer_6
- QSpacerItem * verticalSpacer_5
- QCheckBox * sAccelBox
- QSpacerItem * verticalSpacer_7
- QSpacerItem * verticalSpacer_8
- QSpacerItem * verticalSpacer_10
- QSpacerItem * verticalSpacer_11
- QSpacerItem * horizontalSpacer
- QFrame * line_2
- QHBoxLayout * horizontalLayout
- QLabel * animPathLabel
- QLabel * animCountLabel
- QPushButton * animScanButton
- QCheckBox * brightnessBox
- QCheckBox * trayBox
- QLabel * label
- QFrame * line
- QLabel * label_5
- QFrame * line_3
- QLabel * label_2
- QCheckBox * ditherBox
- QCheckBox * delayBox
- QLabel * osxLabel
- QFrame * osxLine
- QCheckBox * mAccelBox
- QWidget * sSpeedWidget
- QHBoxLayout * horizontalLayout_2
- QLabel * label_10
- QSpinBox * sSpeedBox
- QLabel * label_11
- QDialogButtonBox * buttonBox

12.87.1 Detailed Description

Definition at line 31 of file ui_extrasettingswidget.h.

12.87.2 Member Function Documentation

12.87.2.1 void Ui_ExtraSettingsWidget::retranslateUi (QDialog * *ExtraSettingsWidget*) [inline]

Definition at line 322 of file ui_extrasettingswidget.h.

References animCountLabel, animPathLabel, animScanButton, brightnessBox, delayBox, ditherBox, fpsWarnLabel, label, label_10, label_11, label_2, label_3, label_5, label_6, mAccelBox, osxLabel, sAccelBox, and trayBox.

Referenced by setupUi().

```
    {
        ExtraSettingsWidget->setWindowTitle(QApplication::translate("ExtraSettingsWidget", "Application Settings", Q_NULLPTR));
        fpsWarnLabel->setText(QApplication::translate("ExtraSettingsWidget", "Warning: high frame rates may cause stability issues", Q_NULLPTR));
        label_3->setText(QApplication::translate("ExtraSettingsWidget", "Frame rate (FPS):", Q_NULLPTR));
        label_6->setText(QApplication::translate("ExtraSettingsWidget", "Location:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        sAccelBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "Try this if you're having problems with the scroll wheel.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        sAccelBox->setText(QApplication::translate("ExtraSettingsWidget", "Disable scroll acceleration", Q_NULLPTR));
        animPathLabel->setText(QApplication::translate("ExtraSettingsWidget", "/path/to/animations", Q_NULLPTR));
        animCountLabel->setText(QApplication::translate("ExtraSettingsWidget", "0 animations found", Q_NULLPTR));
        animScanButton->setText(QApplication::translate("ExtraSettingsWidget", "Re-scan", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        brightnessBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "By default, the same brightness level will be applied to all profiles and all devices. Enable this to store it with the lighting mode instead.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        brightnessBox->setText(QApplication::translate("ExtraSettingsWidget", "Set brightness per-mode", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        trayBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "The tray icon will not be displayed. The application will still run in the background; re-launch the app to see the GUI again.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        trayBox->setText(QApplication::translate("ExtraSettingsWidget", "Hide tray icon", Q_NULLPTR));
        label->setText(QApplication::translate("ExtraSettingsWidget", "Behavior", Q_NULLPTR));
        label_5->setText(QApplication::translate("ExtraSettingsWidget", "Animation scripts", Q_NULLPTR));
        label_2->setText(QApplication::translate("ExtraSettingsWidget", "Hardware", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        ditherBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "May improve appearance on some keyboards.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        ditherBox->setText(QApplication::translate("ExtraSettingsWidget", "Use spatial dithering to simulate extra color resolution", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        delayBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "When using macros with strings longer than 25 chars, some OS may lose characters (e.g. Mint 17.2). Select to prevent that bug.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        delayBox->setText(QApplication::translate("ExtraSettingsWidget", "Use delay for very long macros", Q_NULLPTR));
        osxLabel->setText(QApplication::translate("ExtraSettingsWidget", "OS X tweaks", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        mAccelBox->setToolTip(QApplication::translate("ExtraSettingsWidget", "Try this if you're having problems with mouse movement.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        mAccelBox->setText(QApplication::translate("ExtraSettingsWidget", "Disable mouse acceleration", Q_NULLPTR));
        label_10->setText(QApplication::translate("ExtraSettingsWidget", "Scroll", Q_NULLPTR));
        label_11->setText(QApplication::translate("ExtraSettingsWidget", "line(s) at a time", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.87.2.2 void Ui_ExtraSettingsWidget::setupUi (QDialog * *ExtraSettingsWidget*) [inline]

Definition at line 78 of file ui_extrasettingswidget.h.

References animCountLabel, animPathLabel, animScanButton, brightnessBox, buttonBox, delayBox, ditherBox, fpsBox, fpsWarnLabel, gridLayout, horizontalLayout, horizontalLayout_2, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, label, label_10, label_11, label_2, label_3, label_5, label_6, line, line_2, line_3, mAccelBox, osxLabel, osxLine, retranslateUi(), sAccelBox, sSpeedBox, sSpeedWidget, trayBox, verticalSpacer, verticalSpacer_10, verticalSpacer_11, verticalSpacer_2, verticalSpacer_3, verticalSpacer_4, verticalSpacer_5, verticalSpacer_6, verticalSpacer_7, verticalSpacer_8, and verticalSpacer_9.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget().

```
79     {
80         if (ExtraSettingsWidget->objectName().isEmpty())
81             ExtraSettingsWidget->setObjectName(QStringLiteral("ExtraSettingsWidget"));
82         ExtraSettingsWidget->resize(650, 515);
83         gridLayout = new QGridLayout(ExtraSettingsWidget);
84         gridLayout->setObjectName(QStringLiteral("gridLayout"));
85         horizontalSpacer_2 = new QSpacerItem(30, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);
86
87         gridLayout->addItem(horizontalSpacer_2, 12, 2, 1, 1);
88
89         verticalSpacer = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);
90
91         gridLayout->addItem(verticalSpacer, 2, 0, 1, 1);
92
93         verticalSpacer_3 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed)
    ;
94
95         gridLayout->addItem(verticalSpacer_3, 3, 0, 1, 1);
96
97         verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);
98
99         gridLayout->addItem(verticalSpacer_2, 19, 5, 1, 1);
100
101         fpsWarnLabel = new QLabel(ExtraSettingsWidget);
102         fpsWarnLabel->setObjectName(QStringLiteral("fpsWarnLabel"));
103         QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
104         sizePolicy.setHorizontalStretch(0);
105         sizePolicy.setVerticalStretch(0);
106         sizePolicy.setHeightForWidth(fpsWarnLabel->sizePolicy().hasHeightForWidth());
107         fpsWarnLabel->setSizePolicy(sizePolicy);
108
109         gridLayout->addWidget(fpsWarnLabel, 12, 5, 1, 1);
110
111         horizontalSpacer_3 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);
112
113         gridLayout->addItem(horizontalSpacer_3, 12, 4, 1, 1);
114
115         label_3 = new QLabel(ExtraSettingsWidget);
116         label_3->setObjectName(QStringLiteral("label_3"));
117
118         gridLayout->addWidget(label_3, 12, 1, 1, 1);
119
120         fpsBox = new QSpinBox(ExtraSettingsWidget);
121         fpsBox->setObjectName(QStringLiteral("fpsBox"));
122         fpsBox->setMinimum(5);
123         fpsBox->setMaximum(60);
124         fpsBox->setValue(30);
125
```

```
        gridLayout->addWidget(fpsBox, 12, 3, 1, 1);

        verticalSpacer_4 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_4, 7, 0, 1, 1);

        verticalSpacer_9 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_9, 12, 0, 1, 1);

        label_6 = new QLabel(ExtraSettingsWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 7, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_6, 8, 1, 1, 1);

        verticalSpacer_5 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_5, 4, 1, 1, 1);

        sAccelBox = new QCheckBox(ExtraSettingsWidget);
        sAccelBox->setObjectName(QStringLiteral("sAccelBox"));

        gridLayout->addWidget(sAccelBox, 18, 1, 1, 4);

        verticalSpacer_7 = new QSpacerItem(20, 10, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_7, 14, 1, 1, 1);

        verticalSpacer_8 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 13, 0, 1, 1);

        verticalSpacer_10 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_10, 17, 0, 1, 1);

        verticalSpacer_11 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_11, 18, 0, 1, 1);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 12, 6, 1, 1);

        line_2 = new QFrame(ExtraSettingsWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 10, 0, 1, 7);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        animPathLabel = new QLabel(ExtraSettingsWidget);
        animPathLabel->setObjectName(QStringLiteral("animPathLabel"));

        horizontalLayout->addWidget(animPathLabel);

        animCountLabel = new QLabel(ExtraSettingsWidget);
        animCountLabel->setObjectName(QStringLiteral("animCountLabel"));
        sizePolicy.setHeightForWidth(animCountLabel->sizePolicy().hasHeightForWidth());
        animCountLabel->setSizePolicy(sizePolicy);
        animCountLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        horizontalLayout->addWidget(animCountLabel);

        animScanButton = new QPushButton(ExtraSettingsWidget);
        animScanButton->setObjectName(QStringLiteral("animScanButton"));

        horizontalLayout->addWidget(animScanButton);


        gridLayout->addLayout(horizontalLayout, 7, 3, 1, 4);

```

```
        brightnessBox = new QCheckBox(ExtraSettingsWidget);
        brightnessBox->setObjectName(QStringLiteral("brightnessBox"));

        gridLayout->addWidget(brightnessBox, 3, 1, 1, 6);

        trayBox = new QCheckBox(ExtraSettingsWidget);
        trayBox->setObjectName(QStringLiteral("trayBox"));

        gridLayout->addWidget(trayBox, 2, 1, 1, 6);

        label = new QLabel(ExtraSettingsWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        gridLayout->addWidget(label, 0, 0, 1, 7);

        line = new QFrame(ExtraSettingsWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 1, 0, 1, 7);

        label_5 = new QLabel(ExtraSettingsWidget);
        label_5->setObjectName(QStringLiteral("label_5"));
        label_5->setFont(font);

        gridLayout->addWidget(label_5, 5, 0, 1, 7);

        line_3 = new QFrame(ExtraSettingsWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 6, 0, 1, 7);

        label_2 = new QLabel(ExtraSettingsWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        gridLayout->addWidget(label_2, 9, 0, 1, 7);

        ditherBox = new QCheckBox(ExtraSettingsWidget);
        ditherBox->setObjectName(QStringLiteral("ditherBox"));

        gridLayout->addWidget(ditherBox, 13, 1, 1, 6);

        delayBox = new QCheckBox(ExtraSettingsWidget);
        delayBox->setObjectName(QStringLiteral("delayBox"));

        gridLayout->addWidget(delayBox, 14, 1, 1, 6);

        osxLabel = new QLabel(ExtraSettingsWidget);
        osxLabel->setObjectName(QStringLiteral("osxLabel"));
        osxLabel->setFont(font);

        gridLayout->addWidget(osxLabel, 15, 0, 1, 7);

        osxLine = new QFrame(ExtraSettingsWidget);
        osxLine->setObjectName(QStringLiteral("osxLine"));
        osxLine->setFrameShape(QFrame::HLine);
        osxLine->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(osxLine, 16, 0, 1, 7);

        mAccelBox = new QCheckBox(ExtraSettingsWidget);
        mAccelBox->setObjectName(QStringLiteral("mAccelBox"));

        gridLayout->addWidget(mAccelBox, 17, 1, 1, 6);

        sSpeedWidget = new QWidget(ExtraSettingsWidget);
        sSpeedWidget->setObjectName(QStringLiteral("sSpeedWidget"));
        sizePolicy.setHeightForWidth(sSpeedWidget->sizePolicy().hasHeightForWidth());
        sSpeedWidget->setSizePolicy(sizePolicy);
        horizontalLayout_2 = new QHBoxLayout(sSpeedWidget);
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        horizontalLayout_2->setContentsMargins(0, 0, 0, 0);
        label_10 = new QLabel(sSpeedWidget);
        label_10->setObjectName(QStringLiteral("label_10"));

        horizontalLayout_2->addWidget(label_10);

        sSpeedBox = new QSpinBox(sSpeedWidget);
        sSpeedBox->setObjectName(QStringLiteral("sSpeedBox"));
```

```
        sSpeedBox->setMinimum(1);
        sSpeedBox->setMaximum(10);
        sSpeedBox->setValue(3);

        horizontalLayout_2->addWidget(sSpeedBox);

        label_11 = new QLabel(sSpeedWidget);
        label_11->setObjectName(QStringLiteral("label_11"));
        sizePolicy.setHeightForWidth(label_11->sizePolicy().hasHeightForWidth());
        label_11->setSizePolicy(sizePolicy);

        horizontalLayout_2->addWidget(label_11);


        gridLayout->addWidget(sSpeedWidget, 18, 5, 1, 2);

        buttonBox = new QDialogButtonBox(ExtraSettingsWidget);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Ok);

        gridLayout->addWidget(buttonBox, 20, 0, 1, 7);


        retranslateUi(ExtraSettingsWidget);
        QObject::connect(buttonBox, SIGNAL(accepted()), ExtraSettingsWidget, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), ExtraSettingsWidget, SLOT(reject()));

        QMetaObject::connectSlotsByName(ExtraSettingsWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.87.3 Field Documentation

12.87.3.1 QLabel* Ui_ExtraSettingsWidget::animCountLabel

Definition at line 57 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::on_animScanButton_clicked(), retranslateUi(), and setupUi().

12.87.3.2 QLabel* Ui_ExtraSettingsWidget::animPathLabel

Definition at line 56 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.3 QPushButton* Ui_ExtraSettingsWidget::animScanButton

Definition at line 58 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.4 QCheckBox* Ui_ExtraSettingsWidget::brightnessBox

Definition at line 59 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.5 QDialogButtonBox* Ui_ExtraSettingsWidget::buttonBox

Definition at line 76 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.6 QCheckBox* Ui_ExtraSettingsWidget::delayBox

Definition at line 67 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.7 QCheckBox* Ui_ExtraSettingsWidget::ditherBox

Definition at line 66 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.8 QSpinBox* Ui_ExtraSettingsWidget::fpsBox

Definition at line 42 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and setupUi().

12.87.3.9 QLabel* Ui_ExtraSettingsWidget::fpsWarnLabel

Definition at line 39 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_fpsBox_valueChanged(), retranslateUi(), and setupUi().

12.87.3.10 QGridLayout* Ui_ExtraSettingsWidget::gridLayout

Definition at line 34 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.11 QHBoxLayout* Ui_ExtraSettingsWidget::horizontalLayout

Definition at line 55 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.12 QHBoxLayout* Ui_ExtraSettingsWidget::horizontalLayout_2

Definition at line 72 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.13 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer

Definition at line 53 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.14 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer_2

Definition at line 35 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.15 QSpacerItem* Ui_ExtraSettingsWidget::horizontalSpacer_3

Definition at line 40 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.16 QLabel* Ui_ExtraSettingsWidget::label

Definition at line 61 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.17 QLabel* Ui_ExtraSettingsWidget::label_10

Definition at line 73 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.18 QLabel* Ui_ExtraSettingsWidget::label_11

Definition at line 75 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.19 QLabel* Ui_ExtraSettingsWidget::label_2

Definition at line 65 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.20 QLabel* Ui_ExtraSettingsWidget::label_3

Definition at line 41 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.21 QLabel* Ui_ExtraSettingsWidget::label_5

Definition at line 63 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.22 QLabel* Ui_ExtraSettingsWidget::label_6

Definition at line 45 of file ui_extrasettingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.87.3.23 QFrame* Ui_ExtraSettingsWidget::line

Definition at line 62 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.24 QFrame* Ui_ExtraSettingsWidget::line_2

Definition at line 54 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.25 QFrame* Ui_ExtraSettingsWidget::line_3

Definition at line 64 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.26 QCheckBox* Ui_ExtraSettingsWidget::mAccelBox

Definition at line 70 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.27 QLabel* Ui_ExtraSettingsWidget::osxLabel

Definition at line 68 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.28 QFrame* Ui_ExtraSettingsWidget::osxLine

Definition at line 69 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and setupUi().

12.87.3.29 QCheckBox* Ui_ExtraSettingsWidget::sAccelBox

Definition at line 48 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sSpeedBox_valueChanged(), retranslateUi(), and setupUi().

12.87.3.30 QSpinBox* Ui_ExtraSettingsWidget::sSpeedBox

Definition at line 74 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sAccelBox_clicked(), and setupUi().

12.87.3.31 QWidget* Ui_ExtraSettingsWidget::sSpeedWidget

Definition at line 71 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), ExtraSettingsWidget::on_sAccelBox_clicked(), and setupUi().

12.87.3.32 QCheckBox* Ui_ExtraSettingsWidget::trayBox

Definition at line 60 of file ui_extrasettingswidget.h.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), retranslateUi(), and setupUi().

12.87.3.33 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer

Definition at line 36 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.34 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_10

Definition at line 51 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.35 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_11

Definition at line 52 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.36 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_2

Definition at line 38 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.37 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_3

Definition at line 37 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.38 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_4

Definition at line 43 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.39 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_5

Definition at line 47 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.40 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_6

Definition at line 46 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.41 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_7

Definition at line 49 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.42 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_8

Definition at line 50 of file ui_extrasettingswidget.h.

Referenced by setupUi().

12.87.3.43 QSpacerItem* Ui_ExtraSettingsWidget::verticalSpacer_9

Definition at line 44 of file ui_extrasettingswidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_extrasettingswidget.h

12.88 Ui_FwUpgradeDialog Class Reference

```
#include <src/ckb/ui_fwupgradedialog.h>
```

Inheritance diagram for Ui_FwUpgradeDialog:

Collaboration diagram for Ui_FwUpgradeDialog:

Public Member Functions

- void setupUi (QDialog *FwUpgradeDialog)
- void retranslateUi (QDialog *FwUpgradeDialog)

Data Fields

- QGridLayout * gridLayout_2
- QSpacerItem * horizontalSpacer
- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer_3
- QLabel * label_4
- QSpacerItem * horizontalSpacer_4
- QLabel * label_2
- QLabel * curLabel
- QLabel * newLabel
- QLabel * statusLabel
- QSpacerItem * horizontalSpacer_2
- QLabel * devLabel
- QProgressBar * progressBar
- QPushButton * actionButton
- QPushButton * cancelButton

12.88.1 Detailed Description

Definition at line 26 of file ui_fwupgradedialog.h.

12.88.2 Member Function Documentation

12.88.2.1 void Ui_FwUpgradeDialog::retranslateUi (QDialog * *FwUpgradeDialog*) [inline]

Definition at line 155 of file ui_fwupgradedialog.h.

References actionButton, cancelButton, curLabel, devLabel, label_2, label_4, newLabel, and statusLabel.

Referenced by setupUi().

```
    {
        FwUpgradeDialog->setWindowTitle(QApplication::translate("FwUpgradeDialog", "Firmware update", Q_NULLPTR));
        label_4->setText(QApplication::translate("FwUpgradeDialog", "New:", Q_NULLPTR));
        label_2->setText(QApplication::translate("FwUpgradeDialog", "Current:", Q_NULLPTR));
        curLabel->setText(QApplication::translate("FwUpgradeDialog", "0.00", Q_NULLPTR));
        newLabel->setText(QApplication::translate("FwUpgradeDialog", "0.00", Q_NULLPTR));
        statusLabel->setText(QApplication::translate("FwUpgradeDialog", "Downloading new firmware, please wait...", Q_NULLPTR));
        devLabel->setText(QApplication::translate("FwUpgradeDialog", "Device", Q_NULLPTR));
        actionButton->setText(QApplication::translate("FwUpgradeDialog", "Start", Q_NULLPTR));
        cancelButton->setText(QApplication::translate("FwUpgradeDialog", "Cancel", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.88.2.2 void Ui_FwUpgradeDialog::setupUi (QDialog * *FwUpgradeDialog*) [inline]

Definition at line 45 of file ui_fwupgradedialog.h.

References actionButton, cancelButton, curLabel, devLabel, gridLayout, gridLayout_2, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, horizontalSpacer_4, label_2, label_4, newLabel, progressBar, retranslateUi(), and statusLabel.

Referenced by FwUpgradeDialog::FwUpgradeDialog().

```
46     {
47         if (FwUpgradeDialog->objectName().isEmpty())
48             FwUpgradeDialog->setObjectName(QStringLiteral("FwUpgradeDialog"));
49         FwUpgradeDialog->resize(420, 240);
50         QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
51         sizePolicy.setHorizontalStretch(0);
52         sizePolicy.setVerticalStretch(0);
53         sizePolicy.setHeightForWidth(FwUpgradeDialog->sizePolicy().hasHeightForWidth());
54         FwUpgradeDialog->setSizePolicy(sizePolicy);
55         gridLayout_2 = new QGridLayout(FwUpgradeDialog);
56         gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
57         horizontalSpacer = new QSpacerItem(127, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
58
59         gridLayout_2->addItem(horizontalSpacer, 1, 0, 1, 1);
60
61         gridLayout = new QGridLayout();
62         gridLayout->setObjectName(QStringLiteral("gridLayout"));
63         horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
64
65         gridLayout->addItem(horizontalSpacer_3, 1, 0, 1, 1);
66
67         label_4 = new QLabel(FwUpgradeDialog);
68         label_4->setObjectName(QStringLiteral("label_4"));
69         QFont font;
70         font.setBold(true);
71         font.setWeight(75);
72         label_4->setFont(font);
73
74         gridLayout->addWidget(label_4, 1, 4, 1, 1);
75
76         horizontalSpacer_4 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
77
78         gridLayout->addItem(horizontalSpacer_4, 1, 6, 1, 1);
79
80         label_2 = new QLabel(FwUpgradeDialog);
81         label_2->setObjectName(QStringLiteral("label_2"));
82         label_2->setFont(font);
83
84         gridLayout->addWidget(label_2, 1, 1, 1, 1);
85
86         curLabel = new QLabel(FwUpgradeDialog);
87         curLabel->setObjectName(QStringLiteral("curLabel"));
88
89         gridLayout->addWidget(curLabel, 1, 2, 1, 1);
90
91         newLabel = new QLabel(FwUpgradeDialog);
92         newLabel->setObjectName(QStringLiteral("newLabel"));
93
94         gridLayout->addWidget(newLabel, 1, 5, 1, 1);
95
96         statusLabel = new QLabel(FwUpgradeDialog);
97         statusLabel->setObjectName(QStringLiteral("statusLabel"));
98         QSizePolicy sizePolicy1(QSizePolicy::Preferred, QSizePolicy::Expanding);
99         sizePolicy1.setHorizontalStretch(0);
100         sizePolicy1.setVerticalStretch(0);
101         sizePolicy1.setHeightForWidth(statusLabel->sizePolicy().hasHeightForWidth());
102         statusLabel->setSizePolicy(sizePolicy1);
103         statusLabel->setAlignment(Qt::AlignCenter);
104         statusLabel->setWordWrap(true);
105
106         gridLayout->addWidget(statusLabel, 2, 0, 1, 7);
107
108         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
109
110         gridLayout->addItem(horizontalSpacer_2, 1, 3, 1, 1);
111
112         devLabel = new QLabel(FwUpgradeDialog);
113         devLabel->setObjectName(QStringLiteral("devLabel"));
114         QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Minimum);
115         sizePolicy2.setHorizontalStretch(0);
```

```
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(devLabel->sizePolicy().hasHeightForWidth());
        devLabel->setSizePolicy(sizePolicy2);
        devLabel->setFont(font);
        devLabel->setAlignment(Qt::AlignCenter);

        gridLayout->addWidget(devLabel, 0, 0, 1, 7);

        progressBar = new QProgressBar(FwUpgradeDialog);
        progressBar->setObjectName(QStringLiteral("progressBar"));
        progressBar->setMaximum(0);
        progressBar->setValue(0);

        gridLayout->addWidget(progressBar, 3, 0, 1, 7);


        gridLayout_2->addLayout(gridLayout, 0, 0, 1, 3);

        actionButton = new QPushButton(FwUpgradeDialog);
        actionButton->setObjectName(QStringLiteral("actionButton"));
        actionButton->setEnabled(false);

        gridLayout_2->addWidget(actionButton, 1, 2, 1, 1);

        cancelButton = new QPushButton(FwUpgradeDialog);
        cancelButton->setObjectName(QStringLiteral("cancelButton"));
        cancelButton->setEnabled(false);

        gridLayout_2->addWidget(cancelButton, 1, 1, 1, 1);


        retranslateUi(FwUpgradeDialog);

        actionButton->setDefault(true);


        QMetaObject::connectSlotsByName(FwUpgradeDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.88.3 Field Documentation

12.88.3.1 QPushButton* Ui_FwUpgradeDialog::actionButton

Definition at line 42 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::on_actionButton_clicked(), retranslateUi(), and setupUi().

12.88.3.2 QPushButton* Ui_FwUpgradeDialog::cancelButton

Definition at line 43 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::on_actionButton_clicked(), retranslateUi(), and setupUi().

12.88.3.3 QLabel* Ui_FwUpgradeDialog::curLabel

Definition at line 36 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), retranslateUi(), and setupUi().

12.88.3.4 QLabel* Ui_FwUpgradeDialog::devLabel

Definition at line 40 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), retranslateUi(), and setupUi().

12.88.3.5 QGridLayout* Ui_FwUpgradeDialog::gridLayout

Definition at line 31 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.6 QGridLayout* Ui_FwUpgradeDialog::gridLayout_2

Definition at line 29 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.7 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer

Definition at line 30 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.8 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_2

Definition at line 39 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.9 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_3

Definition at line 32 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.10 QSpacerItem* Ui_FwUpgradeDialog::horizontalSpacer_4

Definition at line 34 of file ui_fwupgradedialog.h.

Referenced by setupUi().

12.88.3.11 QLabel* Ui_FwUpgradeDialog::label_2

Definition at line 35 of file ui_fwupgradedialog.h.

Referenced by retranslateUi(), and setupUi().

12.88.3.12 QLabel* Ui_FwUpgradeDialog::label_4

Definition at line 33 of file ui_fwupgradedialog.h.

Referenced by retranslateUi(), and setupUi().

12.88.3.13 QLabel* Ui_FwUpgradeDialog::newLabel

Definition at line 37 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::FwUpgradeDialog(), retranslateUi(), and setupUi().

12.88.3.14 QProgressBar* Ui_FwUpgradeDialog::progressBar

Definition at line 41 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::fwUpdateProgress(), FwUpgradeDialog::on_actionButton_clicked(), and setupUi().

12.88.3.15 QLabel* Ui_FwUpgradeDialog::statusLabel

Definition at line 38 of file ui_fwupgradedialog.h.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::fwUpdateFinished(), FwUpgradeDialog::on_actionButton_clicked(), retranslateUi(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_fwupgradedialog.h

12.89 Ui_GradientDialog Class Reference

```
#include <src/ckb/ui_gradientdialog.h>
```

Inheritance diagram for Ui_GradientDialog:

Collaboration diagram for Ui_GradientDialog:

Public Member Functions

- void setupUi (QDialog *GradientDialog)
- void retranslateUi (QDialog *GradientDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_2
- GradientDialogWidget * widget
- QDialogButtonBox * buttonBox
- QGroupBox * stopBox
- QGridLayout * gridLayout_2
- QHBoxLayout * horizontalLayout_2
- ColorButton * stopColor
- QSpinBox * stopOpacity
- QSpacerItem * horizontalSpacer_2
- QLabel * label
- QHBoxLayout * horizontalLayout
- QSpinBox * stopPos
- QSpacerItem * horizontalSpacer
- QLabel * label_2
- QSpacerItem * horizontalSpacer_3
- QGroupBox * groupBox_2
- QGridLayout * gridLayout_3
- QListWidget * presetList
- QLineEdit * presetName
- QPushButton * presetSave
- QPushButton * presetDelete

12.89.1 Detailed Description

Definition at line 33 of file ui_gradientdialog.h.

12.89.2 Member Function Documentation

12.89.2.1 void Ui_GradientDialog::retranslateUi (QDialog * *GradientDialog*) [inline]

Definition at line 207 of file ui_gradientdialog.h.

References groupBox_2, label, label_2, presetDelete, presetName, presetSave, stopBox, stopColor, stopOpacity, and stopPos.

Referenced by setupUi().

```
208     {
209         GradientDialog->setWindowTitle(QApplication::translate("GradientDialog", "Pick Gradient", Q_NULLPTR
    ));
210         stopBox->setTitle(QApplication::translate("GradientDialog", "Point X of Y", Q_NULLPTR));
211         stopColor->setText(QApplication::translate("GradientDialog", "Pick Color...", Q_NULLPTR));
212         stopOpacity->setSuffix(QApplication::translate("GradientDialog", "%", Q_NULLPTR));
213         label->setText(QApplication::translate("GradientDialog", "Position:", Q_NULLPTR));
214         stopPos->setSuffix(QApplication::translate("GradientDialog", "%", Q_NULLPTR));
215         label_2->setText(QApplication::translate("GradientDialog", "Color:", Q_NULLPTR));
216         groupBox_2->setTitle(QApplication::translate("GradientDialog", "Presets", Q_NULLPTR));
217         presetName->setPlaceholderText(QApplication::translate("GradientDialog", "Name",
    Q_NULLPTR));
218         presetSave->setText(QApplication::translate("GradientDialog", "Save", Q_NULLPTR));
219         presetDelete->setText(QApplication::translate("GradientDialog", "Delete", Q_NULLPTR));
220     } // retranslateUi
```

Here is the caller graph for this function:

12.89.2.2 void Ui_GradientDialog::setupUi (QDialog * *GradientDialog*) [inline]

Definition at line 60 of file ui_gradientdialog.h.

References buttonBox, gridLayout, gridLayout_2, gridLayout_3, groupBox_2, horizontalLayout, horizontalLayout_2, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, label, label_2, presetDelete, presetList, presetName, presetSave, retranslateUi(), stopBox, stopColor, stopOpacity, stopPos, verticalSpacer, verticalSpacer_2, and widget.

Referenced by GradientDialog::GradientDialog().

```
61     {
62         if (GradientDialog->objectName().isEmpty())
63             GradientDialog->setObjectName(QStringLiteral("GradientDialog"));
64         GradientDialog->resize(400, 440);
65         GradientDialog->setMinimumSize(QSize(400, 440));
66         GradientDialog->setMaximumSize(QSize(400, 440));
67         GradientDialog->setFocusPolicy(Qt::ClickFocus);
68         gridLayout = new QGridLayout(GradientDialog);
69         gridLayout->setObjectName(QStringLiteral("gridLayout"));
70         verticalSpacer = new QSpacerItem(0, 0, QSizePolicy::Minimum, QSizePolicy::Expanding);
71
72         gridLayout->addItem(verticalSpacer, 1, 0, 1, 1);
73
74         verticalSpacer_2 = new QSpacerItem(0, 15, QSizePolicy::Minimum, QSizePolicy::Fixed)
    ;
75
76         gridLayout->addItem(verticalSpacer_2, 3, 0, 1, 1);
77
78         widget = new GradientDialogWidget(GradientDialog);
79         widget->setObjectName(QStringLiteral("widget"));
80         QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Fixed);
81         sizePolicy.setHorizontalStretch(0);
82         sizePolicy.setVerticalStretch(0);
83         sizePolicy.setHeightForWidth(widget->sizePolicy().hasHeightForWidth());
84         widget->setSizePolicy(sizePolicy);
85         widget->setMinimumSize(QSize(0, 74));
86         widget->setMaximumSize(QSize(16777215, 74));
87
88         gridLayout->addWidget(widget, 2, 0, 1, 1);
89
90         buttonBox = new QDialogButtonBox(GradientDialog);
91         buttonBox->setObjectName(QStringLiteral("buttonBox"));
92         buttonBox->setOrientation(Qt::Horizontal);
93         buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
94
95         gridLayout->addWidget(buttonBox, 5, 0, 1, 1);
96
97         stopBox = new QGroupBox(GradientDialog);
98         stopBox->setObjectName(QStringLiteral("stopBox"));
99         sizePolicy.setHeightForWidth(stopBox->sizePolicy().hasHeightForWidth());
100         stopBox->setSizePolicy(sizePolicy);
101         gridLayout_2 = new QGridLayout(stopBox);
102         gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
103         horizontalLayout_2 = new QHBoxLayout();
104         horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
105         stopColor = new ColorButton(stopBox);
106         stopColor->setObjectName(QStringLiteral("stopColor"));
107
108         horizontalLayout_2->addWidget(stopColor);
109
110         stopOpacity = new QSpinBox(stopBox);
111         stopOpacity->setObjectName(QStringLiteral("stopOpacity"));
112         stopOpacity->setMaximum(100);
113
```

```
        horizontalLayout_2->addWidget(stopOpacity);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_2);


        gridLayout_2->addLayout(horizontalLayout_2, 1, 2, 1, 1);

        label = new QLabel(stopBox);
        label->setObjectName(QStringLiteral("label"));

        gridLayout_2->addWidget(label, 0, 0, 1, 1);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        stopPos = new QSpinBox(stopBox);
        stopPos->setObjectName(QStringLiteral("stopPos"));
        stopPos->setMaximum(100);

        horizontalLayout->addWidget(stopPos);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer);


        gridLayout_2->addLayout(horizontalLayout, 0, 2, 1, 1);

        label_2 = new QLabel(stopBox);
        label_2->setObjectName(QStringLiteral("label_2"));

        gridLayout_2->addWidget(label_2, 1, 0, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(10, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 0, 1, 1, 1);


        gridLayout->addWidget(stopBox, 4, 0, 1, 1);

        groupBox_2 = new QGroupBox(GradientDialog);
        groupBox_2->setObjectName(QStringLiteral("groupBox_2"));
        sizePolicy.setHeightForWidth(groupBox_2->sizePolicy().hasHeightForWidth());
        groupBox_2->setSizePolicy(sizePolicy);
        gridLayout_3 = new QGridLayout(groupBox_2);
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        presetList = new QListWidget(groupBox_2);
        presetList->setObjectName(QStringLiteral("presetList"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(presetList->sizePolicy().hasHeightForWidth());
        presetList->setSizePolicy(sizePolicy1);
        presetList->setFrameShadow(QFrame::Plain);
        presetList->setHorizontalScrollBarPolicy(Qt::ScrollBarAlwaysOn);
        presetList->setIconSize(QSize(64, 64));
        presetList->setHorizontalScrollMode(QAbstractItemView::ScrollPerPixel);
        presetList->setFlow(QListView::TopToBottom);
        presetList->setViewMode(QListView::IconMode);
        presetList->setUniformItemSizes(true);

        gridLayout_3->addWidget(presetList, 0, 0, 3, 1);

        presetName = new QLineEdit(groupBox_2);
        presetName->setObjectName(QStringLiteral("presetName"));
        presetName->setMaxLength(30);

        gridLayout_3->addWidget(presetName, 0, 1, 1, 1);

        presetSave = new QPushButton(groupBox_2);
        presetSave->setObjectName(QStringLiteral("presetSave"));
        presetSave->setAutoDefault(false);

        gridLayout_3->addWidget(presetSave, 1, 1, 1, 1);

        presetDelete = new QPushButton(groupBox_2);
        presetDelete->setObjectName(QStringLiteral("presetDelete"));
        presetDelete->setAutoDefault(false);

        gridLayout_3->addWidget(presetDelete, 2, 1, 1, 1);


        gridLayout->addWidget(groupBox_2, 0, 0, 1, 1);
```

```


        retranslateUi(GradientDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), GradientDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), GradientDialog, SLOT(reject()));

        QMetaObject::connectSlotsByName(GradientDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.89.3 Field Documentation

12.89.3.1 QDialogButtonBox* Ui_GradientDialog::buttonBox

Definition at line 40 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.2 QGridLayout* Ui_GradientDialog::gridLayout

Definition at line 36 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.3 QGridLayout* Ui_GradientDialog::gridLayout_2

Definition at line 42 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.4 QGridLayout* Ui_GradientDialog::gridLayout_3

Definition at line 54 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.5 QGroupBox* Ui_GradientDialog::groupBox_2

Definition at line 53 of file ui_gradientdialog.h.

Referenced by retranslateUi(), and setupUi().

12.89.3.6 QHBoxLayout* Ui_GradientDialog::horizontalLayout

Definition at line 48 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.7 QHBoxLayout* Ui_GradientDialog::horizontalLayout_2

Definition at line 43 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.8 QSpacerItem* Ui_GradientDialog::horizontalSpacer

Definition at line 50 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.9 QSpacerItem* Ui_GradientDialog::horizontalSpacer_2

Definition at line 46 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.10 QSpacerItem* Ui_GradientDialog::horizontalSpacer_3

Definition at line 52 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.11 QLabel* Ui_GradientDialog::label

Definition at line 47 of file ui_gradientdialog.h.

Referenced by retranslateUi(), and setupUi().

12.89.3.12 QLabel* Ui_GradientDialog::label_2

Definition at line 51 of file ui_gradientdialog.h.

Referenced by retranslateUi(), and setupUi().

12.89.3.13 QPushButton* Ui_GradientDialog::presetDelete

Definition at line 58 of file ui_gradientdialog.h.

Referenced by GradientDialog::getGradient(), GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), retranslateUi(), GradientDialog::setPreset(), and setupUi().

12.89.3.14 QListWidget* Ui_GradientDialog::presetList

Definition at line 55 of file ui_gradientdialog.h.

Referenced by GradientDialog::setPreset(), setupUi(), and GradientDialog::updatePresets().

12.89.3.15 QLineEdit* Ui_GradientDialog::presetName

Definition at line 56 of file ui_gradientdialog.h.

Referenced by GradientDialog::on_presetSave_clicked(), retranslateUi(), GradientDialog::setPreset(), and setupUi().

12.89.3.16 QPushButton* Ui_GradientDialog::presetSave

Definition at line 57 of file ui_gradientdialog.h.

Referenced by GradientDialog::getGradient(), GradientDialog::on_presetDelete_clicked(), GradientDialog::on_presetSave_clicked(), retranslateUi(), GradientDialog::setPreset(), and setupUi().

12.89.3.17 QGroupBox* Ui_GradientDialog::stopBox

Definition at line 41 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), retranslateUi(), and setupUi().

12.89.3.18 ColorButton* Ui_GradientDialog::stopColor

Definition at line 44 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), GradientDialog::GradientDialog(), GradientDialog::on_stopOpacity_valueChanged(), retranslateUi(), and setupUi().

12.89.3.19 QSpinBox* Ui_GradientDialog::stopOpacity

Definition at line 45 of file ui_gradientdialog.h.

Referenced by GradientDialog::colorChanged(), GradientDialog::currentChanged(), retranslateUi(), and setupUi().

12.89.3.20 QSpinBox* Ui_GradientDialog::stopPos

Definition at line 49 of file ui_gradientdialog.h.

Referenced by GradientDialog::currentChanged(), GradientDialog::on_stopPos_valueChanged(), retranslateUi(), and setupUi().

12.89.3.21 QSpacerItem* Ui_GradientDialog::verticalSpacer

Definition at line 37 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.22 QSpacerItem* Ui_GradientDialog::verticalSpacer_2

Definition at line 38 of file ui_gradientdialog.h.

Referenced by setupUi().

12.89.3.23 GradientDialogWidget* Ui_GradientDialog::widget

Definition at line 39 of file ui_gradientdialog.h.

Referenced by GradientDialog::colorChanged(), GradientDialog::currentChanged(), GradientDialog::getGradient(), GradientDialog::GradientDialog(), GradientDialog::on_presetSave_clicked(), GradientDialog::on_stopPos_valueChanged(), GradientDialog::setPreset(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_gradientdialog.h

12.90 Ui_KbAnimWidget Class Reference

```
#include <src/ckb/ui_kbanimwidget.h>
```

Inheritance diagram for Ui_KbAnimWidget:

Collaboration diagram for Ui_KbAnimWidget:

Public Member Functions

- void setupUi (QWidget ∗KbAnimWidget)
- void retranslateUi (QWidget ∗KbAnimWidget)

Data Fields

- QGridLayout ∗ gridLayout
- QStackedWidget ∗ selectionStack
- QWidget ∗ noSelPage
- QGridLayout ∗ gridLayout_2
- QLabel ∗ noAnimLabel
- QSpacerItem ∗ verticalSpacer
- QWidget ∗ animPage
- QVBoxLayout ∗ verticalLayout
- QHBoxLayout ∗ horizontalLayout
- QLabel ∗ aNameLabel
- QLabel ∗ aVerLabel
- QSpacerItem ∗ horizontalSpacer
- QLabel ∗ aCopyLabel
- QSpacerItem ∗ verticalSpacer_3
- QGridLayout ∗ gridLayout_3
- QLineEdit ∗ nameBox
- QDoubleSpinBox ∗ opacityBox
- QComboBox ∗ blendBox
- QLabel ∗ label_6
- QSpacerItem ∗ horizontalSpacer_4
- QSpacerItem ∗ horizontalSpacer_2
- QLabel ∗ label_5
- QSpacerItem ∗ horizontalSpacer_3
- QLabel ∗ label_7
- QPushButton ∗ keyButton
- QPushButton ∗ deleteButton
- QPushButton ∗ propertyButton
- QSpacerItem ∗ horizontalSpacer_5
- QSpacerItem ∗ verticalSpacer_2
- QWidget ∗ aMissingPage
- QGridLayout ∗ gridLayout_4
- QLabel ∗ aMissingLabel
- RListWidget ∗ animList

12.90.1 Detailed Description

Definition at line 32 of file ui_kbanimwidget.h.

12.90.2 Member Function Documentation

12.90.2.1 void Ui_KbAnimWidget::retranslateUi (QWidget * *KbAnimWidget*) [inline]

Definition at line 241 of file ui_kbanimwidget.h.

References aCopyLabel, aMissingLabel, aNameLabel, aVerLabel, blendBox, deleteButton, keyButton, label_5, label_6, label_7, noAnimLabel, opacityBox, and propertyButton.

Referenced by setupUi().

```
242     {
243         KbAnimWidget->setWindowTitle(QApplication::translate("KbAnimWidget", "Form", Q_NULLPTR));
244         noAnimLabel->setText(QApplication::translate("KbAnimWidget", "No animations in this mode
    ", Q_NULLPTR));
245         aNameLabel->setText(QApplication::translate("KbAnimWidget", "Animation name", Q_NULLPTR))
    ;
246         aVerLabel->setText(QApplication::translate("KbAnimWidget", "v0.0", Q_NULLPTR));
247         aCopyLabel->setText(QApplication::translate("KbAnimWidget", "Copyright \302\251",
    Q_NULLPTR));
248         opacityBox->setSuffix(QApplication::translate("KbAnimWidget", "%", Q_NULLPTR));
249         blendBox->clear();
250         blendBox->insertItems(0, QStringList()
251          << QApplication::translate("KbAnimWidget", "Normal", Q_NULLPTR)
252          << QApplication::translate("KbAnimWidget", "Add", Q_NULLPTR)
253          << QApplication::translate("KbAnimWidget", "Subtract", Q_NULLPTR)
254          << QApplication::translate("KbAnimWidget", "Multiply", Q_NULLPTR)
255          << QApplication::translate("KbAnimWidget", "Divide", Q_NULLPTR)
256         );
257         label_6->setText(QApplication::translate("KbAnimWidget", "Blend mode:", Q_NULLPTR));
258         label_5->setText(QApplication::translate("KbAnimWidget", "Opacity:", Q_NULLPTR));
259         label_7->setText(QApplication::translate("KbAnimWidget", "Name:", Q_NULLPTR));
260         keyButton->setText(QApplication::translate("KbAnimWidget", "Set keys", Q_NULLPTR));
261         deleteButton->setText(QApplication::translate("KbAnimWidget", "Delete animation",
    Q_NULLPTR));
262         propertyButton->setText(QApplication::translate("KbAnimWidget", "Edit properties",
    Q_NULLPTR));
263         aMissingLabel->setText(QApplication::translate("KbAnimWidget", "Mising animation",
    Q_NULLPTR));
264     } // retranslateUi
```

Here is the caller graph for this function:

12.90.2.2 void Ui_KbAnimWidget::setupUi (QWidget * *KbAnimWidget*) [inline]

Definition at line 69 of file ui_kbanimwidget.h.

References aCopyLabel, aMissingLabel, aMissingPage, aNameLabel, animList, animPage, aVerLabel, blendBox, deleteButton, gridLayout, gridLayout_2, gridLayout_3, gridLayout_4, horizontalLayout, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, keyButton, label_5, label_6, label_7, nameBox, noAnimLabel, noSelPage, opacityBox, propertyButton, retranslateUi(), selectionStack, verticalLayout, verticalSpacer, verticalSpacer_2, and verticalSpacer_3.

Referenced by KbAnimWidget::KbAnimWidget().

```
70     {
```

```
        if (KbAnimWidget->objectName().isEmpty())
            KbAnimWidget->setObjectName(QStringLiteral("KbAnimWidget"));
        KbAnimWidget->resize(613, 300);
        gridLayout = new QGridLayout(KbAnimWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        gridLayout->setContentsMargins(0, 0, 0, 0);
        selectionStack = new QStackedWidget(KbAnimWidget);
        selectionStack->setObjectName(QStringLiteral("selectionStack"));
        noSelPage = new QWidget();
        noSelPage->setObjectName(QStringLiteral("noSelPage"));
        gridLayout_2 = new QGridLayout(noSelPage);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(6, 6, 6, 6);
        noAnimLabel = new QLabel(noSelPage);
        noAnimLabel->setObjectName(QStringLiteral("noAnimLabel"));

        gridLayout_2->addWidget(noAnimLabel, 0, 0, 1, 1);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout_2->addItem(verticalSpacer, 1, 0, 1, 1);

        selectionStack->addWidget(noSelPage);
        animPage = new QWidget();
        animPage->setObjectName(QStringLiteral("animPage"));
        verticalLayout = new QVBoxLayout(animPage);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        verticalLayout->setContentsMargins(6, 0, 0, 0);
        horizontalLayout = new QHBoxLayout();
         horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
         aNameLabel = new QLabel(animPage);
         aNameLabel->setObjectName(QStringLiteral("aNameLabel"));
         QFont font;
         font.setBold(true);
         font.setWeight(75);
         aNameLabel->setFont(font);

         horizontalLayout->addWidget(aNameLabel);

         aVerLabel = new QLabel(animPage);
         aVerLabel->setObjectName(QStringLiteral("aVerLabel"));

         horizontalLayout->addWidget(aVerLabel);

         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

         horizontalLayout->addItem(horizontalSpacer);

         aCopyLabel = new QLabel(animPage);
         aCopyLabel->setObjectName(QStringLiteral("aCopyLabel"));

         horizontalLayout->addWidget(aCopyLabel);


         verticalLayout->addLayout(horizontalLayout);

         verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

         verticalLayout->addItem(verticalSpacer_3);

         gridLayout_3 = new QGridLayout();
         gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
         nameBox = new QLineEdit(animPage);
         nameBox->setObjectName(QStringLiteral("nameBox"));
         QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
         sizePolicy.setHorizontalStretch(0);
         sizePolicy.setVerticalStretch(0);
         sizePolicy.setHeightForWidth(nameBox->sizePolicy().hasHeightForWidth());
         nameBox->setSizePolicy(sizePolicy);
         nameBox->setMinimumSize(QSize(150, 0));
         nameBox->setMaximumSize(QSize(150, 16777215));

         gridLayout_3->addWidget(nameBox, 0, 3, 1, 2);

         opacityBox = new QDoubleSpinBox(animPage);
         opacityBox->setObjectName(QStringLiteral("opacityBox"));
         opacityBox->setDecimals(1);
         opacityBox->setValue(100);

         gridLayout_3->addWidget(opacityBox, 1, 3, 1, 1);

         blendBox = new QComboBox(animPage);
         blendBox->setObjectName(QStringLiteral("blendBox"));

```

```
        gridLayout_3->addWidget(blendBox, 2, 3, 1, 2);

        label_6 = new QLabel(animPage);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout_3->addWidget(label_6, 2, 1, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(0, 0, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_4, 0, 0, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(30, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_2, 0, 2, 1, 1);

        label_5 = new QLabel(animPage);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout_3->addWidget(label_5, 1, 1, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_3, 0, 5, 1, 1);

        label_7 = new QLabel(animPage);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout_3->addWidget(label_7, 0, 1, 1, 1);

        keyButton = new QPushButton(animPage);
        keyButton->setObjectName(QStringLiteral("keyButton"));

        gridLayout_3->addWidget(keyButton, 1, 6, 1, 1);

        deleteButton = new QPushButton(animPage);
        deleteButton->setObjectName(QStringLiteral("deleteButton"));

        gridLayout_3->addWidget(deleteButton, 2, 6, 1, 1);

        propertyButton = new QPushButton(animPage);
        propertyButton->setObjectName(QStringLiteral("propertyButton"));

        gridLayout_3->addWidget(propertyButton, 0, 6, 1, 1);

        horizontalSpacer_5 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_5, 1, 4, 1, 1);


        verticalLayout->addLayout(gridLayout_3);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        selectionStack->addWidget(animPage);
        aMissingPage = new QWidget();
        aMissingPage->setObjectName(QStringLiteral("aMissingPage"));
        gridLayout_4 = new QGridLayout(aMissingPage);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        aMissingLabel = new QLabel(aMissingPage);
        aMissingLabel->setObjectName(QStringLiteral("aMissingLabel"));
        aMissingLabel->setFont(font);

        gridLayout_4->addWidget(aMissingLabel, 0, 0, 1, 1);

        selectionStack->addWidget(aMissingPage);

        gridLayout->addWidget(selectionStack, 0, 2, 2, 1);

        animList = new RListWidget(KbAnimWidget);
        animList->setObjectName(QStringLiteral("animList"));
        animList->setMaximumSize(QSize(130, 16777215));
        animList->setContextMenuPolicy(Qt::CustomContextMenu);
        animList->setFrameShadow(QFrame::Plain);
        animList->setDragDropMode(QAbstractItemView::InternalMove);
        animList->setMovement(QListView::Snap);

        gridLayout->addWidget(animList, 0, 0, 2, 1);


        retranslateUi(KbAnimWidget);
```

```
        QMetaObject::connectSlotsByName(KbAnimWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.90.3 Field Documentation

12.90.3.1 QLabel* Ui_KbAnimWidget::aCopyLabel

Definition at line 47 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.2 QLabel* Ui_KbAnimWidget::aMissingLabel

Definition at line 66 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.3 QWidget* Ui_KbAnimWidget::aMissingPage

Definition at line 64 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.4 QLabel* Ui_KbAnimWidget::aNameLabel

Definition at line 44 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.5 RListWidget* Ui_KbAnimWidget::animList

Definition at line 67 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::addAnim(), KbAnimWidget::clearSelection(), KbAnimWidget::duplicateAnim(), KbAnimWidget::KbAnimWidget(), KbAnimWidget::on_animList_customContextMenuRequested(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::on_nameBox_textEdited(), KbAnimWidget::refreshList(), KbAnimWidget::reorderAnims(), and setupUi().

12.90.3.6 QWidget* Ui_KbAnimWidget::animPage

Definition at line 41 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.7 QLabel* Ui_KbAnimWidget::aVerLabel

Definition at line 45 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.8 QComboBox* Ui_KbAnimWidget::blendBox

Definition at line 52 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.9 QPushButton* Ui_KbAnimWidget::deleteButton

Definition at line 60 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), and setupUi().

12.90.3.10 QGridLayout* Ui_KbAnimWidget::gridLayout

Definition at line 35 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.11 QGridLayout* Ui_KbAnimWidget::gridLayout_2

Definition at line 38 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.12 QGridLayout* Ui_KbAnimWidget::gridLayout_3

Definition at line 49 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.13 QGridLayout* Ui_KbAnimWidget::gridLayout_4

Definition at line 65 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.14 QHBoxLayout* Ui_KbAnimWidget::horizontalLayout

Definition at line 43 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.15 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer

Definition at line 46 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.16 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_2

Definition at line 55 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.17 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_3

Definition at line 57 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.18 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_4

Definition at line 54 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.19 QSpacerItem* Ui_KbAnimWidget::horizontalSpacer_5

Definition at line 62 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.20 QPushButton* Ui_KbAnimWidget::keyButton

Definition at line 59 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setSelectedKeys(), and setupUi().

12.90.3.21 QLabel* Ui_KbAnimWidget::label_5

Definition at line 56 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), and setupUi().

12.90.3.22 QLabel* Ui_KbAnimWidget::label_6

Definition at line 53 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), and setupUi().

12.90.3.23 QLabel* Ui_KbAnimWidget::label_7

Definition at line 58 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), and setupUi().

12.90.3.24 QLineEdit* Ui_KbAnimWidget::nameBox

Definition at line 50 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::on_animList_itemChanged(), KbAnimWidget::on_propertyButton_clicked(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.25 QLabel* Ui_KbAnimWidget::noAnimLabel

Definition at line 39 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::addAnim(), KbAnimWidget::duplicateAnim(), KbAnimWidget::on_deleteButton_clicked(), KbAnimWidget::refreshList(), retranslateUi(), and setupUi().

12.90.3.26 QWidget* Ui_KbAnimWidget::noSelPage

Definition at line 37 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.27 QDoubleSpinBox* Ui_KbAnimWidget::opacityBox

Definition at line 51 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), KbAnimWidget::setCurrent(), and setupUi().

12.90.3.28 QPushButton* Ui_KbAnimWidget::propertyButton

Definition at line 61 of file ui_kbanimwidget.h.

Referenced by retranslateUi(), and setupUi().

12.90.3.29 QStackedWidget* Ui_KbAnimWidget::selectionStack

Definition at line 36 of file ui_kbanimwidget.h.

Referenced by KbAnimWidget::setCurrent(), and setupUi().

12.90.3.30 QVBoxLayout* Ui_KbAnimWidget::verticalLayout

Definition at line 42 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.31 QSpacerItem* Ui_KbAnimWidget::verticalSpacer

Definition at line 40 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.32 QSpacerItem* Ui_KbAnimWidget::verticalSpacer_2

Definition at line 63 of file ui_kbanimwidget.h.

Referenced by setupUi().

12.90.3.33 QSpacerItem* Ui_KbAnimWidget::verticalSpacer_3

Definition at line 48 of file ui_kbanimwidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbanimwidget.h

12.91 Ui_KbBindWidget Class Reference

```
#include <src/ckb/ui_kbbindwidget.h>
```

Inheritance diagram for Ui_KbBindWidget:

Collaboration diagram for Ui_KbBindWidget:

Public Member Functions

- void setupUi (QWidget ∗KbBindWidget)
- void retranslateUi (QWidget ∗KbBindWidget)

Data Fields

- QVBoxLayout ∗ verticalLayout
- QLabel ∗ label
- QFrame ∗ line
- QGridLayout ∗ gridLayout
- QSpacerItem ∗ horizontalSpacer_2
- KeyWidget ∗ keyWidget
- QSpacerItem ∗ horizontalSpacer
- QHBoxLayout ∗ horizontalLayout_2
- QPushButton ∗ copyButton
- QLabel ∗ selectLabel
- QPushButton ∗ resetButton
- QSpacerItem ∗ verticalSpacer
- QLabel ∗ label_2
- QFrame ∗ line_2
- QWidget ∗ widget
- QGridLayout ∗ gridLayout_2
- RebindWidget ∗ rbWidget

12.91.1 Detailed Description

Definition at line 30 of file ui_kbbindwidget.h.

12.91.2 Member Function Documentation

12.91.2.1 void Ui_KbBindWidget::retranslateUi (QWidget * *KbBindWidget*) [inline]

Definition at line 193 of file ui_kbbindwidget.h.

References copyButton, label, label_2, resetButton, and selectLabel.

Referenced by setupUi().

```
194     {
195         KbBindWidget->setWindowTitle(QApplication::translate("KbBindWidget", "Form", Q_NULLPTR));
196         label->setText(QApplication::translate("KbBindWidget", "Keys", Q_NULLPTR));
197         copyButton->setText(QApplication::translate("KbBindWidget", "Copy to mode...", Q_NULLPTR)
    );
198         selectLabel->setText(QApplication::translate("KbBindWidget", "Click to select keys",
    Q_NULLPTR));
199         resetButton->setText(QApplication::translate("KbBindWidget", "Reset", Q_NULLPTR));
200         label_2->setText(QApplication::translate("KbBindWidget", "Binding", Q_NULLPTR));
201     } // retranslateUi
```

Here is the caller graph for this function:

12.91.2.2 void Ui_KbBindWidget::setupUi (QWidget * *KbBindWidget*) [inline]

Definition at line 51 of file ui_kbbindwidget.h.

References copyButton, gridLayout, gridLayout_2, horizontalLayout_2, horizontalSpacer, horizontalSpacer_2, keyWidget, label, label_2, line, line_2, rbWidget, resetButton, retranslateUi(), selectLabel, verticalLayout, verticalSpacer, and widget.

Referenced by KbBindWidget::KbBindWidget().

```
52     {
53         if (KbBindWidget->objectName().isEmpty())
54             KbBindWidget->setObjectName(QStringLiteral("KbBindWidget"));
55         KbBindWidget->resize(581, 473);
56         verticalLayout = new QVBoxLayout(KbBindWidget);
57         verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
58         verticalLayout->setContentsMargins(0, 0, 0, -1);
59         label = new QLabel(KbBindWidget);
60         label->setObjectName(QStringLiteral("label"));
61         QFont font;
62         font.setBold(true);
63         font.setWeight(75);
64         label->setFont(font);
65
66         verticalLayout->addWidget(label);
67
68         line = new QFrame(KbBindWidget);
69         line->setObjectName(QStringLiteral("line"));
70         line->setFrameShape(QFrame::HLine);
71         line->setFrameShadow(QFrame::Sunken);
72
73         verticalLayout->addWidget(line);
74
75         gridLayout = new QGridLayout();
76         gridLayout->setObjectName(QStringLiteral("gridLayout"));
77         horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
78
79         gridLayout->addItem(horizontalSpacer_2, 0, 4, 1, 1);
80
81         keyWidget = new KeyWidget(KbBindWidget);
82         keyWidget->setObjectName(QStringLiteral("keyWidget"));
```

```
        QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(keyWidget->sizePolicy().hasHeightForWidth());
        keyWidget->setSizePolicy(sizePolicy);

        gridLayout->addWidget(keyWidget, 0, 1, 1, 3);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setSpacing(0);
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        copyButton = new QPushButton(KbBindWidget);
        copyButton->setObjectName(QStringLiteral("copyButton"));
         QSizePolicy sizePolicy1(QSizePolicy::Fixed, QSizePolicy::Fixed);
         sizePolicy1.setHorizontalStretch(0);
         sizePolicy1.setVerticalStretch(0);
         sizePolicy1.setHeightForWidth(copyButton->sizePolicy().hasHeightForWidth());
         copyButton->setSizePolicy(sizePolicy1);
         copyButton->setMinimumSize(QSize(140, 0));
         copyButton->setMaximumSize(QSize(140, 16777215));

         horizontalLayout_2->addWidget(copyButton);

         selectLabel = new QLabel(KbBindWidget);
         selectLabel->setObjectName(QStringLiteral("selectLabel"));
         QSizePolicy sizePolicy2(QSizePolicy::Expanding, QSizePolicy::Preferred);
         sizePolicy2.setHorizontalStretch(0);
         sizePolicy2.setVerticalStretch(0);
         sizePolicy2.setHeightForWidth(selectLabel->sizePolicy().hasHeightForWidth());
         selectLabel->setSizePolicy(sizePolicy2);
         selectLabel->setAlignment(Qt::AlignCenter);

         horizontalLayout_2->addWidget(selectLabel);

         resetButton = new QPushButton(KbBindWidget);
         resetButton->setObjectName(QStringLiteral("resetButton"));
         QSizePolicy sizePolicy3(QSizePolicy::Expanding, QSizePolicy::Fixed);
         sizePolicy3.setHorizontalStretch(0);
         sizePolicy3.setVerticalStretch(0);
         sizePolicy3.setHeightForWidth(resetButton->sizePolicy().hasHeightForWidth());
         resetButton->setSizePolicy(sizePolicy3);
         resetButton->setMinimumSize(QSize(140, 0));
         resetButton->setMaximumSize(QSize(140, 16777215));

         horizontalLayout_2->addWidget(resetButton);


         gridLayout->addLayout(horizontalLayout_2, 1, 1, 1, 3);


         verticalLayout->addLayout(gridLayout);

         verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

         verticalLayout->addItem(verticalSpacer);

         label_2 = new QLabel(KbBindWidget);
         label_2->setObjectName(QStringLiteral("label_2"));
         label_2->setFont(font);

         verticalLayout->addWidget(label_2);

         line_2 = new QFrame(KbBindWidget);
         line_2->setObjectName(QStringLiteral("line_2"));
         line_2->setFrameShape(QFrame::HLine);
         line_2->setFrameShadow(QFrame::Sunken);

         verticalLayout->addWidget(line_2);

         widget = new QWidget(KbBindWidget);
         widget->setObjectName(QStringLiteral("widget"));
         QSizePolicy sizePolicy4(QSizePolicy::Preferred, QSizePolicy::Fixed);
         sizePolicy4.setHorizontalStretch(0);
         sizePolicy4.setVerticalStretch(0);
         sizePolicy4.setHeightForWidth(widget->sizePolicy().hasHeightForWidth());
         widget->setSizePolicy(sizePolicy4);
         widget->setMinimumSize(QSize(0, 280));
         widget->setMaximumSize(QSize(16777215, 280));
         gridLayout_2 = new QGridLayout(widget);
         gridLayout_2->setSpacing(0);
         gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
```

```
        gridLayout_2->setContentsMargins(0, 0, 0, 0);
        rbWidget = new RebindWidget(widget);
        rbWidget->setObjectName(QStringLiteral("rbWidget"));
        QSizePolicy sizePolicy5(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy5.setHorizontalStretch(0);
        sizePolicy5.setVerticalStretch(0);
        sizePolicy5.setHeightForWidth(rbWidget->sizePolicy().hasHeightForWidth());
        rbWidget->setSizePolicy(sizePolicy5);

        gridLayout_2->addWidget(rbWidget, 0, 0, 1, 1);


        verticalLayout->addWidget(widget);

        label->raise();
        line->raise();
        label_2->raise();
        line_2->raise();
        widget->raise();

        retranslateUi(KbBindWidget);

        QMetaObject::connectSlotsByName(KbBindWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.91.3 Field Documentation

12.91.3.1 QPushButton* Ui_KbBindWidget::copyButton

Definition at line 41 of file ui_kbbindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.91.3.2 QGridLayout* Ui_KbBindWidget::gridLayout

Definition at line 36 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.3 QGridLayout* Ui_KbBindWidget::gridLayout_2

Definition at line 48 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.4 QHBoxLayout* Ui_KbBindWidget::horizontalLayout_2

Definition at line 40 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.5 QSpacerItem* Ui_KbBindWidget::horizontalSpacer

Definition at line 39 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.6 QSpacerItem* Ui_KbBindWidget::horizontalSpacer_2

Definition at line 37 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.7 KeyWidget* Ui_KbBindWidget::keyWidget

Definition at line 38 of file ui_kbbindwidget.h.

Referenced by KbBindWidget::KbBindWidget(), KbBindWidget::newLayout(), KbBindWidget::setBind(), setupUi(), and KbBindWidget::updateBind().

12.91.3.8 QLabel* Ui_KbBindWidget::label

Definition at line 34 of file ui_kbbindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.91.3.9 QLabel* Ui_KbBindWidget::label_2

Definition at line 45 of file ui_kbbindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.91.3.10 QFrame* Ui_KbBindWidget::line

Definition at line 35 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.11 QFrame* Ui_KbBindWidget::line_2

Definition at line 46 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.12 RebindWidget* Ui_KbBindWidget::rbWidget

Definition at line 49 of file ui_kbbindwidget.h.

Referenced by KbBindWidget::newLayout(), KbBindWidget::newSelection(), KbBindWidget::setBind(), setupUi(), and KbBindWidget::updateBind().

12.91.3.13 QPushButton* Ui_KbBindWidget::resetButton

Definition at line 43 of file ui_kbbindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.91.3.14 QLabel* Ui_KbBindWidget::selectLabel

Definition at line 42 of file ui_kbbindwidget.h.

Referenced by retranslateUi(), setupUi(), and KbBindWidget::updateSelDisplay().

12.91.3.15 QVBoxLayout* Ui_KbBindWidget::verticalLayout

Definition at line 33 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.16 QSpacerItem* Ui_KbBindWidget::verticalSpacer

Definition at line 44 of file ui_kbbindwidget.h.

Referenced by setupUi().

12.91.3.17 QWidget* Ui_KbBindWidget::widget

Definition at line 47 of file ui_kbbindwidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbbindwidget.h

12.92 Ui_KbLightWidget Class Reference

```
#include <src/ckb/ui_kblightwidget.h>
```

Inheritance diagram for Ui_KbLightWidget:

Collaboration diagram for Ui_KbLightWidget:

Public Member Functions

- void setupUi (QWidget *KbLightWidget)
- void retranslateUi (QWidget *KbLightWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QHBoxLayout * horizontalLayout_3
- QLabel * label_3
- QCheckBox * showAnimBox
- QFrame * line_2
- QHBoxLayout * horizontalLayout_2
- QSpacerItem * horizontalSpacer_5
- QGridLayout * gridLayout
- KeyWidget * keyWidget
- QHBoxLayout * horizontalLayout
- ColorButton * bgButton
- QLabel * selLabel
- QPushButton * animButton
- QSpacerItem * horizontalSpacer_6
- QSpacerItem * verticalSpacer_2
- QGridLayout * gridLayout_2
- QComboBox * brightnessBox
- QLabel * label
- QSpacerItem * horizontalSpacer_3
- QSpacerItem * horizontalSpacer_4
- QSpacerItem * verticalSpacer_3
- QLabel * label_2
- QFrame * line
- QWidget * widget
- QGridLayout * gridLayout_4
- KbAnimWidget * animWidget

12.92.1 Detailed Description

Definition at line 33 of file ui_kblightwidget.h.

12.92.2 Member Function Documentation

12.92.2.1 void Ui_KbLightWidget::retranslateUi (QWidget * *KbLightWidget*) [inline]

Definition at line 238 of file ui_kblightwidget.h.

References animButton, bgButton, brightnessBox, label, label_2, label_3, selLabel, and showAnimBox.

Referenced by setupUi().

```
    {
        KbLightWidget->setWindowTitle(QApplication::translate("KbLightWidget", "Form", Q_NULLPTR));
        label_3->setText(QApplication::translate("KbLightWidget", "Colors", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        showAnimBox->setToolTip(QApplication::translate("KbLightWidget", "If enabled, the same colors will be displayed here as on the keyboard. If disabled, the base colors will be shown.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        showAnimBox->setText(QApplication::translate("KbLightWidget", "Show animated", Q_NULLPTR));
        bgButton->setText(QApplication::translate("KbLightWidget", "Change color...", Q_NULLPTR));
        selLabel->setText(QApplication::translate("KbLightWidget", "Click to select", Q_NULLPTR));
        animButton->setText(QApplication::translate("KbLightWidget", "New animation...", Q_NULLPTR));
        brightnessBox->clear();
        brightnessBox->insertItems(0, QStringList()
         << QApplication::translate("KbLightWidget", "100%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "67%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "33%", Q_NULLPTR)
         << QApplication::translate("KbLightWidget", "Off", Q_NULLPTR)
```

```
        );
        label->setText(QApplication::translate("KbLightWidget", "\342\230\274", Q_NULLPTR));
        label_2->setText(QApplication::translate("KbLightWidget", "Animations", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.92.2.2 void Ui_KbLightWidget::setupUi (QWidget * *KbLightWidget*) [inline]

Definition at line 63 of file ui_kblightwidget.h.

References animButton, animWidget, bgButton, brightnessBox, gridLayout, gridLayout_2, gridLayout_4, horizontalLayout, horizontalLayout_2, horizontalLayout_3, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, horizontalSpacer_6, keyWidget, label, label_2, label_3, line, line_2, retranslateUi(), selLabel, showAnimBox, verticalLayout, verticalSpacer_2, verticalSpacer_3, and widget.

Referenced by KbLightWidget::KbLightWidget().

```
    {
        if (KbLightWidget->objectName().isEmpty())
            KbLightWidget->setObjectName(QStringLiteral("KbLightWidget"));
        KbLightWidget->resize(632, 540);
        KbLightWidget->setFocusPolicy(Qt::ClickFocus);
        verticalLayout = new QVBoxLayout(KbLightWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        verticalLayout->setContentsMargins(0, 0, 0, -1);
        horizontalLayout_3 = new QHBoxLayout();
        horizontalLayout_3->setObjectName(QStringLiteral("horizontalLayout_3"));
        label_3 = new QLabel(KbLightWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(label_3->sizePolicy().hasHeightForWidth());
        label_3->setSizePolicy(sizePolicy);
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label_3->setFont(font);

        horizontalLayout_3->addWidget(label_3);

        showAnimBox = new QCheckBox(KbLightWidget);
        showAnimBox->setObjectName(QStringLiteral("showAnimBox"));
        showAnimBox->setChecked(true);

        horizontalLayout_3->addWidget(showAnimBox);


        verticalLayout->addLayout(horizontalLayout_3);

        line_2 = new QFrame(KbLightWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
         line_2->setFrameShadow(QFrame::Sunken);

         verticalLayout->addWidget(line_2);

         horizontalLayout_2 = new QHBoxLayout();
         horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
         horizontalSpacer_5 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

         horizontalLayout_2->addItem(horizontalSpacer_5);

         gridLayout = new QGridLayout();
         gridLayout->setObjectName(QStringLiteral("gridLayout"));
         keyWidget = new KeyWidget(KbLightWidget);
```

```
        keyWidget->setObjectName(QStringLiteral("keyWidget"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(keyWidget->sizePolicy().hasHeightForWidth());
        keyWidget->setSizePolicy(sizePolicy1);
        keyWidget->setMinimumSize(QSize(100, 100));
        keyWidget->setFocusPolicy(Qt::ClickFocus);

        gridLayout->addWidget(keyWidget, 0, 0, 1, 3);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        bgButton = new ColorButton(KbLightWidget);
        bgButton->setObjectName(QStringLiteral("bgButton"));
        QSizePolicy sizePolicy2(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(bgButton->sizePolicy().hasHeightForWidth());
        bgButton->setSizePolicy(sizePolicy2);
        bgButton->setMinimumSize(QSize(140, 0));
        bgButton->setMaximumSize(QSize(140, 16777215));

        horizontalLayout->addWidget(bgButton);

        selLabel = new QLabel(KbLightWidget);
        selLabel->setObjectName(QStringLiteral("selLabel"));
        sizePolicy.setHeightForWidth(selLabel->sizePolicy().hasHeightForWidth());
        selLabel->setSizePolicy(sizePolicy);
        selLabel->setAlignment(Qt::AlignCenter);

        horizontalLayout->addWidget(selLabel);

        animButton = new QPushButton(KbLightWidget);
        animButton->setObjectName(QStringLiteral("animButton"));
        sizePolicy2.setHeightForWidth(animButton->sizePolicy().hasHeightForWidth());
        animButton->setSizePolicy(sizePolicy2);
        animButton->setMinimumSize(QSize(140, 0));
        animButton->setMaximumSize(QSize(140, 16777215));

        horizontalLayout->addWidget(animButton);


        gridLayout->addLayout(horizontalLayout, 1, 0, 1, 3);


        horizontalLayout_2->addLayout(gridLayout);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_6);


        verticalLayout->addLayout(horizontalLayout_2);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        gridLayout_2 = new QGridLayout();
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        brightnessBox = new QComboBox(KbLightWidget);
        brightnessBox->setObjectName(QStringLiteral("brightnessBox"));
        sizePolicy2.setHeightForWidth(brightnessBox->sizePolicy().hasHeightForWidth());
        brightnessBox->setSizePolicy(sizePolicy2);

        gridLayout_2->addWidget(brightnessBox, 1, 3, 1, 1);

        label = new QLabel(KbLightWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font1;
        font1.setPointSize(20);
        label->setFont(font1);
        label->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_2->addWidget(label, 1, 2, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(0, 0, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 0, 4, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(0, 0, QSizePolicy::Expanding,
QSizePolicy::Minimum);

```

```
        gridLayout_2->addItem(horizontalSpacer_4, 0, 2, 1, 1);


        verticalLayout->addLayout(gridLayout_2);

        verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_3);

        label_2 = new QLabel(KbLightWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);

        verticalLayout->addWidget(label_2);

        line = new QFrame(KbLightWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line);

        widget = new QWidget(KbLightWidget);
        widget->setObjectName(QStringLiteral("widget"));
        widget->setMinimumSize(QSize(0, 170));
        gridLayout_4 = new QGridLayout(widget);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        gridLayout_4->setContentsMargins(-1, 0, -1, 0);
        animWidget = new KbAnimWidget(widget);
        animWidget->setObjectName(QStringLiteral("animWidget"));

        gridLayout_4->addWidget(animWidget, 0, 0, 1, 1);


        verticalLayout->addWidget(widget);


        retranslateUi(KbLightWidget);

        QMetaObject::connectSlotsByName(KbLightWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.92.3 Field Documentation

12.92.3.1 QPushButton* Ui_KbLightWidget::animButton

Definition at line 48 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), retranslateUi(), and setupUi().

12.92.3.2 KbAnimWidget* Ui_KbLightWidget::animWidget

Definition at line 61 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), KbLightWidget::newSelection(), KbLightWidget::on_animButton_clicked(), KbLightWidget::setLight(), and setupUi().

12.92.3.3 ColorButton* Ui_KbLightWidget::bgButton

Definition at line 46 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), KbLightWidget::newSelection(), retranslateUi(), and setupUi().

12.92.3.4 QComboBox* Ui_KbLightWidget::brightnessBox

Definition at line 52 of file ui_kblightwidget.h.

Referenced by retranslateUi(), setupUi(), and KbLightWidget::updateLight().

12.92.3.5 QGridLayout* Ui_KbLightWidget::gridLayout

Definition at line 43 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.6 QGridLayout* Ui_KbLightWidget::gridLayout_2

Definition at line 51 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.7 QGridLayout* Ui_KbLightWidget::gridLayout_4

Definition at line 60 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.8 QHBoxLayout* Ui_KbLightWidget::horizontalLayout

Definition at line 45 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.9 QHBoxLayout* Ui_KbLightWidget::horizontalLayout_2

Definition at line 41 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.10 QHBoxLayout* Ui_KbLightWidget::horizontalLayout_3

Definition at line 37 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.11 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_3

Definition at line 54 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.12 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_4

Definition at line 55 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.13 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_5

Definition at line 42 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.14 QSpacerItem* Ui_KbLightWidget::horizontalSpacer_6

Definition at line 49 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.15 KeyWidget* Ui_KbLightWidget::keyWidget

Definition at line 44 of file ui_kblightwidget.h.

Referenced by KbLightWidget::changeAnim(), KbLightWidget::changeAnimKeys(), KbLightWidget::changeColor(), KbLightWidget::KbLightWidget(), KbLightWidget::on_animButton_clicked(), KbLightWidget::on_bgButton_clicked(), KbLightWidget::on_showAnimBox_clicked(), KbLightWidget::setLight(), KbLightWidget::setMonochrome(), setupUi(), KbLightWidget::toggleSidelight(), and KbLightWidget::updateLight().

12.92.3.16 QLabel* Ui_KbLightWidget::label

Definition at line 53 of file ui_kblightwidget.h.

Referenced by retranslateUi(), and setupUi().

12.92.3.17 QLabel* Ui_KbLightWidget::label_2

Definition at line 57 of file ui_kblightwidget.h.

Referenced by retranslateUi(), and setupUi().

12.92.3.18 QLabel* Ui_KbLightWidget::label_3

Definition at line 38 of file ui_kblightwidget.h.

Referenced by retranslateUi(), and setupUi().

12.92.3.19 QFrame* Ui_KbLightWidget::line

Definition at line 58 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.20 QFrame* Ui_KbLightWidget::line_2

Definition at line 40 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.21 QLabel* Ui_KbLightWidget::selLabel

Definition at line 47 of file ui_kblightwidget.h.

Referenced by KbLightWidget::newSelection(), retranslateUi(), and setupUi().

12.92.3.22 QCheckBox* Ui_KbLightWidget::showAnimBox

Definition at line 39 of file ui_kblightwidget.h.

Referenced by KbLightWidget::KbLightWidget(), retranslateUi(), KbLightWidget::setLight(), and setupUi().

12.92.3.23 QVBoxLayout* Ui_KbLightWidget::verticalLayout

Definition at line 36 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.24 QSpacerItem* Ui_KbLightWidget::verticalSpacer_2

Definition at line 50 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.25 QSpacerItem* Ui_KbLightWidget::verticalSpacer_3

Definition at line 56 of file ui_kblightwidget.h.

Referenced by setupUi().

12.92.3.26 QWidget* Ui_KbLightWidget::widget

Definition at line 59 of file ui_kblightwidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kblightwidget.h

12.93 Ui_KbProfileDialog Class Reference

```
#include <src/ckb/ui_kbprofiledialog.h>
```

Inheritance diagram for Ui_KbProfileDialog:

Collaboration diagram for Ui_KbProfileDialog:

Public Member Functions

- void setupUi (QDialog *KbProfileDialog)
- void retranslateUi (QDialog *KbProfileDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * horizontalSpacer
- QSpacerItem * horizontalSpacer_2
- RListWidget * profileList
- QDialogButtonBox * buttonBox

12.93.1 Detailed Description

Definition at line 25 of file ui_kbprofiledialog.h.

12.93.2 Member Function Documentation

12.93.2.1 void Ui_KbProfileDialog::retranslateUi (QDialog * *KbProfileDialog*) [inline]

Definition at line 73 of file ui_kbprofiledialog.h.

Referenced by setupUi().

```
74     {
75         KbProfileDialog->setWindowTitle(QApplication::translate("KbProfileDialog", "Keyboard Profiles",
    Q_NULLPTR));
76     } // retranslateUi
```

Here is the caller graph for this function:

12.93.2.2 void Ui_KbProfileDialog::setupUi (QDialog * *KbProfileDialog*) [inline]

Definition at line 34 of file ui_kbprofiledialog.h.

References buttonBox, gridLayout, horizontalSpacer, horizontalSpacer_2, profileList, and retranslateUi().

Referenced by KbProfileDialog::KbProfileDialog().

```
35     {
36         if (KbProfileDialog->objectName().isEmpty())
37             KbProfileDialog->setObjectName(QStringLiteral("KbProfileDialog"));
38         KbProfileDialog->resize(400, 300);
39         KbProfileDialog->setFocusPolicy(Qt::ClickFocus);
40         gridLayout = new QGridLayout(KbProfileDialog);
41         gridLayout->setObjectName(QStringLiteral("gridLayout"));
42         horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);
43
44         gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);
```

```
        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_2, 0, 2, 1, 1);

        profileList = new RListWidget(KbProfileDialog);
        profileList->setObjectName(QStringLiteral("profileList"));
        profileList->setContextMenuPolicy(Qt::CustomContextMenu);
        profileList->setFrameShadow(QFrame::Plain);
        profileList->setIconSize(QSize(24, 24));

        gridLayout->addWidget(profileList, 0, 1, 1, 1);

        buttonBox = new QDialogButtonBox(KbProfileDialog);
        buttonBox->setObjectName(QStringLiteral("buttonBox"));
        buttonBox->setOrientation(Qt::Horizontal);
        buttonBox->setStandardButtons(QDialogButtonBox::Ok);

        gridLayout->addWidget(buttonBox, 1, 0, 1, 3);


        retranslateUi(KbProfileDialog);
        QObject::connect(buttonBox, SIGNAL(accepted()), KbProfileDialog, SLOT(accept()));
        QObject::connect(buttonBox, SIGNAL(rejected()), KbProfileDialog, SLOT(reject()));

        QMetaObject::connectSlotsByName(KbProfileDialog);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.93.3 Field Documentation

12.93.3.1 QDialogButtonBox* Ui_KbProfileDialog::buttonBox

Definition at line 32 of file ui_kbprofiledialog.h.

Referenced by setupUi().

12.93.3.2 QGridLayout* Ui_KbProfileDialog::gridLayout

Definition at line 28 of file ui_kbprofiledialog.h.

Referenced by setupUi().

12.93.3.3 QSpacerItem* Ui_KbProfileDialog::horizontalSpacer

Definition at line 29 of file ui_kbprofiledialog.h.

Referenced by setupUi().

12.93.3.4 QSpacerItem* Ui_KbProfileDialog::horizontalSpacer_2

Definition at line 30 of file ui_kbprofiledialog.h.

Referenced by setupUi().

12.93.3.5 RListWidget* Ui_KbProfileDialog::profileList

Definition at line 31 of file ui_kbprofiledialog.h.

Referenced by KbProfileDialog::addNewProfileItem(), KbProfileDialog::KbProfileDialog(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemClicked(), KbProfileDialog::profileList_reordered(), KbProfileDialog::repopulate(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbprofiledialog.h

12.94 Ui_KbWidget Class Reference

```
#include <src/ckb/ui_kbwidget.h>
```

Inheritance diagram for Ui_KbWidget:

Collaboration diagram for Ui_KbWidget:

Public Member Functions

- void setupUi (QWidget *KbWidget)
- void retranslateUi (QWidget *KbWidget)

Data Fields

- QGridLayout * gridLayout
- QComboBox * profileBox
- QTabWidget * tabWidget
- QWidget * lightTab
- QGridLayout * gridLayout_2
- KbLightWidget * lightWidget
- QLabel * label_3
- QWidget * bindTab
- QGridLayout * gridLayout_5
- KbBindWidget * bindWidget
- QWidget * kPerfTab
- QGridLayout * gridLayout_4
- KPerfWidget * kPerfWidget
- QWidget * mPerfTab
- QGridLayout * gridLayout_7
- MPerfWidget * mPerfWidget
- QWidget * devTab
- QGridLayout * gridLayout_3
- QLabel * fwUpdLabel
- QSpacerItem * verticalSpacer
- QLabel * fwLabel
- QLabel * label_4
- QSpacerItem * horizontalSpacer_2
- QLabel * label_9
- QLabel * serialLabel
- QHBoxLayout * fwUpdLayout
- QPushButton * fwUpdButton
- QSpacerItem * horizontalSpacer_3
- QLabel * pollLabel2
- QLabel * pollLabel
- RListWidget * modesList
- QPushButton * hwSaveButton

12.94.1 Detailed Description

Definition at line 33 of file ui_kbwidget.h.

12.94.2 Member Function Documentation

12.94.2.1 void Ui_KbWidget::retranslateUi (QWidget * *KbWidget*) [inline]

Definition at line 268 of file ui_kbwidget.h.

References bindTab, devTab, fwLabel, fwUpdButton, fwUpdLabel, hwSaveButton, kPerfTab, label_3, label_4, label_9, lightTab, mPerfTab, pollLabel, pollLabel2, serialLabel, and tabWidget.

Referenced by setupUi().

```
    {
        KbWidget->setWindowTitle(QApplication::translate("KbWidget", "Form", Q_NULLPTR));
        label_3->setText(QApplication::translate("KbWidget", "Tip: Drag+drop items to reorder. Right-click for menu.", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(lightTab), QApplication::translate("KbWidget", "Lighting", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(bindTab), QApplication::translate("KbWidget", "Binding", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(kPerfTab), QApplication::translate("KbWidget", "Performance", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(mPerfTab), QApplication::translate("KbWidget", "Performance", Q_NULLPTR));
        fwUpdLabel->setText(QApplication::translate("KbWidget", "Status:", Q_NULLPTR));
        fwLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        label_4->setText(QApplication::translate("KbWidget", "USB device ID:", Q_NULLPTR));
        label_9->setText(QApplication::translate("KbWidget", "Firmware version:", Q_NULLPTR));
        serialLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        fwUpdButton->setText(QApplication::translate("KbWidget", "Check for updates", Q_NULLPTR));
        pollLabel2->setText(QApplication::translate("KbWidget", "Poll rate:", Q_NULLPTR));
        pollLabel->setText(QApplication::translate("KbWidget", "N/A", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(devTab), QApplication::translate("KbWidget", "Device", Q_NULLPTR));
        hwSaveButton->setText(QApplication::translate("KbWidget", "Save to hardware", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.94.2.2 void Ui_KbWidget::setupUi (QWidget * *KbWidget*) [inline]

Definition at line 69 of file ui_kbwidget.h.

References bindTab, bindWidget, devTab, fwLabel, fwUpdButton, fwUpdLabel, fwUpdLayout, gridLayout, gridLayout_2, gridLayout_3, gridLayout_4, gridLayout_5, gridLayout_7, horizontalSpacer_2, horizontalSpacer_3, hwSaveButton, kPerfTab, kPerfWidget, label_3, label_4, label_9, lightTab, lightWidget, modesList, mPerfTab, mPerfWidget, pollLabel, pollLabel2, profileBox, retranslateUi(), serialLabel, tabWidget, and verticalSpacer.

Referenced by KbWidget::KbWidget().

```
    {
        if (KbWidget->objectName().isEmpty())
            KbWidget->setObjectName(QStringLiteral("KbWidget"));
        KbWidget->resize(773, 539);
        gridLayout = new QGridLayout(KbWidget);
        gridLayout->setSpacing(9);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        gridLayout->setContentsMargins(9, -1, 9, 9);
        profileBox = new QComboBox(KbWidget);
        profileBox->setObjectName(QStringLiteral("profileBox"));
        QSizePolicy sizePolicy(QSizePolicy::Preferred, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(18);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(profileBox->sizePolicy().hasHeightForWidth());
        profileBox->setSizePolicy(sizePolicy);
        profileBox->setIconSize(QSize(24, 24));

        gridLayout->addWidget(profileBox, 0, 0, 1, 1);

        tabWidget = new QTabWidget(KbWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy1.setHorizontalStretch(82);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(tabWidget->sizePolicy().hasHeightForWidth());
        tabWidget->setSizePolicy(sizePolicy1);
        lightTab = new QWidget();
```

```
        lightTab->setObjectName(QStringLiteral("lightTab"));
        gridLayout_2 = new QGridLayout(lightTab);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
         gridLayout_2->setHorizontalSpacing(0);
         gridLayout_2->setVerticalSpacing(6);
         gridLayout_2->setContentsMargins(6, 6, 6, 6);
         lightWidget = new KbLightWidget(lightTab);
         lightWidget->setObjectName(QStringLiteral("lightWidget"));
         QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Expanding);
         sizePolicy2.setHorizontalStretch(0);
         sizePolicy2.setVerticalStretch(0);
         sizePolicy2.setHeightForWidth(lightWidget->sizePolicy().hasHeightForWidth());
         lightWidget->setSizePolicy(sizePolicy2);

         gridLayout_2->addWidget(lightWidget, 0, 0, 1, 1);

         label_3 = new QLabel(lightTab);
         label_3->setObjectName(QStringLiteral("label_3"));
         QSizePolicy sizePolicy3(QSizePolicy::Preferred, QSizePolicy::Minimum);
         sizePolicy3.setHorizontalStretch(0);
         sizePolicy3.setVerticalStretch(0);
         sizePolicy3.setHeightForWidth(label_3->sizePolicy().hasHeightForWidth());
         label_3->setSizePolicy(sizePolicy3);

         gridLayout_2->addWidget(label_3, 1, 0, 1, 1);

         tabWidget->addTab(lightTab, QString());
         bindTab = new QWidget();
         bindTab->setObjectName(QStringLiteral("bindTab"));
         gridLayout_5 = new QGridLayout(bindTab);
         gridLayout_5->setSpacing(0);
         gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
         gridLayout_5->setContentsMargins(6, 6, 6, 6);
         bindWidget = new KbBindWidget(bindTab);
         bindWidget->setObjectName(QStringLiteral("bindWidget"));
         sizePolicy2.setHeightForWidth(bindWidget->sizePolicy().hasHeightForWidth());
         bindWidget->setSizePolicy(sizePolicy2);

         gridLayout_5->addWidget(bindWidget, 0, 0, 1, 1);

         tabWidget->addTab(bindTab, QString());
         kPerfTab = new QWidget();
         kPerfTab->setObjectName(QStringLiteral("kPerfTab"));
         gridLayout_4 = new QGridLayout(kPerfTab);
         gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
         gridLayout_4->setContentsMargins(6, 6, 6, 6);
         kPerfWidget = new KPerfWidget(kPerfTab);
         kPerfWidget->setObjectName(QStringLiteral("kPerfWidget"));

         gridLayout_4->addWidget(kPerfWidget, 0, 0, 1, 1);

         tabWidget->addTab(kPerfTab, QString());
         mPerfTab = new QWidget();
         mPerfTab->setObjectName(QStringLiteral("mPerfTab"));
         gridLayout_7 = new QGridLayout(mPerfTab);
         gridLayout_7->setObjectName(QStringLiteral("gridLayout_7"));
         gridLayout_7->setContentsMargins(6, 6, 6, 6);
         mPerfWidget = new MPerfWidget(mPerfTab);
         mPerfWidget->setObjectName(QStringLiteral("mPerfWidget"));

         gridLayout_7->addWidget(mPerfWidget, 0, 0, 1, 1);

         tabWidget->addTab(mPerfTab, QString());
         devTab = new QWidget();
         devTab->setObjectName(QStringLiteral("devTab"));
         gridLayout_3 = new QGridLayout(devTab);
         gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
         gridLayout_3->setContentsMargins(6, 6, 6, 6);
         fwUpdLabel = new QLabel(devTab);
         fwUpdLabel->setObjectName(QStringLiteral("fwUpdLabel"));
         fwUpdLabel->setMinimumSize(QSize(0, 34));

         gridLayout_3->addWidget(fwUpdLabel, 4, 0, 1, 1);

         verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

         gridLayout_3->addItem(verticalSpacer, 6, 2, 1, 1);

         fwLabel = new QLabel(devTab);
         fwLabel->setObjectName(QStringLiteral("fwLabel"));
         fwLabel->setCursor(QCursor(Qt::IBeamCursor));
         fwLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|Qt::TextSelectableByMouse);

         gridLayout_3->addWidget(fwLabel, 2, 2, 1, 1);

         label_4 = new QLabel(devTab);
```

```
        label_4->setObjectName(QStringLiteral("label_4"));
        label_4->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(label_4, 0, 0, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(40, 1, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_2, 2, 1, 1, 1);

        label_9 = new QLabel(devTab);
        label_9->setObjectName(QStringLiteral("label_9"));
        label_9->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(label_9, 2, 0, 1, 1);

        serialLabel = new QLabel(devTab);
        serialLabel->setObjectName(QStringLiteral("serialLabel"));
        serialLabel->setCursor(QCursor(Qt::IBeamCursor));
        serialLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|Qt::TextSelectableByMouse);

        gridLayout_3->addWidget(serialLabel, 0, 2, 1, 1);

        fwUpdLayout = new QHBoxLayout();
        fwUpdLayout->setObjectName(QStringLiteral("fwUpdLayout"));
        fwUpdButton = new QPushButton(devTab);
        fwUpdButton->setObjectName(QStringLiteral("fwUpdButton"));

        fwUpdLayout->addWidget(fwUpdButton);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        fwUpdLayout->addItem(horizontalSpacer_3);


        gridLayout_3->addLayout(fwUpdLayout, 4, 2, 1, 1);

        pollLabel2 = new QLabel(devTab);
        pollLabel2->setObjectName(QStringLiteral("pollLabel2"));
        pollLabel2->setMinimumSize(QSize(0, 34));

        gridLayout_3->addWidget(pollLabel2, 1, 0, 1, 1);

        pollLabel = new QLabel(devTab);
        pollLabel->setObjectName(QStringLiteral("pollLabel"));

        gridLayout_3->addWidget(pollLabel, 1, 2, 1, 1);

        tabWidget->addTab(devTab, QString());

        gridLayout->addWidget(tabWidget, 0, 1, 3, 1);

        modesList = new RListWidget(KbWidget);
        modesList->setObjectName(QStringLiteral("modesList"));
        QSizePolicy sizePolicy4(QSizePolicy::Expanding, QSizePolicy::Expanding);
        sizePolicy4.setHorizontalStretch(18);
        sizePolicy4.setVerticalStretch(0);
        sizePolicy4.setHeightForWidth(modesList->sizePolicy().hasHeightForWidth());
        modesList->setSizePolicy(sizePolicy4);
        modesList->setContextMenuPolicy(Qt::CustomContextMenu);
        modesList->setFrameShadow(QFrame::Plain);
        modesList->setDragDropMode(QAbstractItemView::InternalMove);
        modesList->setIconSize(QSize(24, 24));
        modesList->setMovement(QListView::Snap);

        gridLayout->addWidget(modesList, 1, 0, 1, 1);

        hwSaveButton = new QPushButton(KbWidget);
        hwSaveButton->setObjectName(QStringLiteral("hwSaveButton"));
        QSizePolicy sizePolicy5(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy5.setHorizontalStretch(18);
        sizePolicy5.setVerticalStretch(0);
        sizePolicy5.setHeightForWidth(hwSaveButton->sizePolicy().hasHeightForWidth());
        hwSaveButton->setSizePolicy(sizePolicy5);

        gridLayout->addWidget(hwSaveButton, 2, 0, 1, 1);


        retranslateUi(KbWidget);

        tabWidget->setCurrentIndex(0);


        QMetaObject::connectSlotsByName(KbWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.94.3 Field Documentation

12.94.3.1 QWidget* Ui_KbWidget::bindTab

Definition at line 43 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.2 KbBindWidget* Ui_KbWidget::bindWidget

Definition at line 45 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and setupUi().

12.94.3.3 QWidget* Ui_KbWidget::devTab

Definition at line 52 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.4 QLabel* Ui_KbWidget::fwLabel

Definition at line 56 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), retranslateUi(), and setupUi().

12.94.3.5 QPushButton* Ui_KbWidget::fwUpdButton

Definition at line 62 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::on_fwUpdButton_clicked(), retranslateUi(), setupUi(), and KbWidget::updateFwButton().

12.94.3.6 QLabel* Ui_KbWidget::fwUpdLabel

Definition at line 54 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.7 QHBoxLayout* Ui_KbWidget::fwUpdLayout

Definition at line 61 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), and setupUi().

12.94.3.8 QGridLayout* Ui_KbWidget::gridLayout

Definition at line 36 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.9 QGridLayout* Ui_KbWidget::gridLayout_2

Definition at line 40 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.10 QGridLayout* Ui_KbWidget::gridLayout_3

Definition at line 53 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.11 QGridLayout* Ui_KbWidget::gridLayout_4

Definition at line 47 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.12 QGridLayout* Ui_KbWidget::gridLayout_5

Definition at line 44 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.13 QGridLayout* Ui_KbWidget::gridLayout_7

Definition at line 50 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.14 QSpacerItem* Ui_KbWidget::horizontalSpacer_2

Definition at line 58 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.15 QSpacerItem* Ui_KbWidget::horizontalSpacer_3

Definition at line 63 of file ui_kbwidget.h.

Referenced by setupUi().

12.94.3.16 QPushButton* Ui_KbWidget::hwSaveButton

Definition at line 67 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.17 QWidget* Ui_KbWidget::kPerfTab

Definition at line 46 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.18 KPerfWidget* Ui_KbWidget::kPerfWidget

Definition at line 48 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and setupUi().

12.94.3.19 QLabel* Ui_KbWidget::label_3

Definition at line 42 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.20 QLabel* Ui_KbWidget::label_4

Definition at line 57 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.21 QLabel* Ui_KbWidget::label_9

Definition at line 59 of file ui_kbwidget.h.

Referenced by retranslateUi(), and setupUi().

12.94.3.22 QWidget* Ui_KbWidget::lightTab

Definition at line 39 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.23 KbLightWidget* Ui_KbWidget::lightWidget

Definition at line 41 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::modeChanged(), and setupUi().

12.94.3.24 RListWidget* Ui_KbWidget::modesList

Definition at line 66 of file ui_kbwidget.h.

Referenced by KbWidget::addNewModeItem(), KbWidget::KbWidget(), KbWidget::modeChanged(), KbWidget::modesList_reordered(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemClicked(), KbWidget::profileChanged(), and setupUi().

12.94.3.25 QWidget* Ui_KbWidget::mPerfTab

Definition at line 49 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.26 MPerfWidget* Ui_KbWidget::mPerfWidget

Definition at line 51 of file ui_kbwidget.h.

Referenced by KbWidget::modeChanged(), and setupUi().

12.94.3.27 QLabel* Ui_KbWidget::pollLabel

Definition at line 65 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.28 QLabel* Ui_KbWidget::pollLabel2

Definition at line 64 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), retranslateUi(), and setupUi().

12.94.3.29 QComboBox* Ui_KbWidget::profileBox

Definition at line 37 of file ui_kbwidget.h.

Referenced by setupUi(), and KbWidget::updateProfileList().

12.94.3.30 QLabel* Ui_KbWidget::serialLabel

Definition at line 60 of file ui_kbwidget.h.

Referenced by KbWidget::devUpdate(), retranslateUi(), and setupUi().

12.94.3.31 QTabWidget* Ui_KbWidget::tabWidget

Definition at line 38 of file ui_kbwidget.h.

Referenced by KbWidget::KbWidget(), KbWidget::on_tabWidget_currentChanged(), retranslateUi(), setupUi(), KbWidget::showFirstTab(), and KbWidget::showLastTab().

12.94.3.32 QSpacerItem* Ui_KbWidget::verticalSpacer

Definition at line 55 of file ui_kbwidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kbwidget.h

12.95 Ui_KPerfWidget Class Reference

```
#include <src/ckb/ui_kperfwidget.h>
```

Inheritance diagram for Ui_KPerfWidget:

Collaboration diagram for Ui_KPerfWidget:

Public Member Functions

- void setupUi (QWidget *KPerfWidget)
- void retranslateUi (QWidget *KPerfWidget)

Data Fields

- QGridLayout * gridLayout
- QWidget * k95Spacer
- QLabel * label_10
- ColorButton * lockColorOff
- QFrame * line
- QSpacerItem * horizontalSpacer_5
- QLabel * k95Label2
- QLabel * label_12
- ColorButton * modeColorOff
- ColorButton * lightColor3
- QSpacerItem * horizontalSpacer
- QCheckBox * lockBox
- ColorButton * modeColorOn
- QCheckBox * macroBox
- ColorButton * numColorOn
- QComboBox * numBox
- QLabel * label_5
- QSpacerItem * verticalSpacer_2
- ColorButton * lightColor2
- QSpacerItem * horizontalSpacer_7
- QLabel * label_8
- QCheckBox * lightBox
- ColorButton * lightColor1

- QSpacerItem * verticalSpacer_4
- QLabel * label_6
- QLabel * label
- QSpacerItem * horizontalSpacer_6
- ColorButton * lockColorOn
- QLabel * label_4
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QCheckBox * modeBox
- ColorButton * capsColorOff
- ColorButton * numColorOff
- ColorButton * capsColorOn
- QFrame * line_3
- QLabel * label_22
- QComboBox * scrollBox
- QLabel * label_7
- ColorButton * scrollColorOn
- QComboBox * capsBox
- ColorButton * scrollColorOff
- QCheckBox * muteBox
- ColorButton * muteColorOn
- ColorButton * macroColorOff
- QLabel * label_3
- ColorButton * muteColorOff
- QLabel * k95Label3
- ColorButton * macroColorOn
- ColorButton * muteColorNA
- QLabel * label_19
- QFrame * k95Line
- QLabel * label_21
- QLabel * label_24
- QLabel * label_20
- QLabel * label_16
- QLabel * label_14
- QLabel * label_18
- QSpacerItem * horizontalSpacer_2
- QLabel * label_15
- QLabel * k95Label4
- QLabel * label_17
- QLabel * label_11
- QLabel * label_23
- QLabel * k95Label1
- QHBoxLayout * horizontalLayout_2
- QPushButton * copyButton
- QSpacerItem * horizontalSpacer_8
- QHBoxLayout * horizontalLayout
- QLabel * label_2
- QSpacerItem * horizontalSpacer_4
- QSpinBox * intensityBox
- QSpacerItem * horizontalSpacer_3
- QLabel * k95Label5
- QFrame * line_2
- QLabel * k95Label6

12.95.1 Detailed Description

Definition at line 31 of file ui_kperfwidget.h.

12.95.2 Member Function Documentation

12.95.2.1 void Ui_KPerfWidget::retranslateUi (QWidget * *KPerfWidget*) [inline]

Definition at line 589 of file ui_kperfwidget.h.

References capsBox, capsColorOff, capsColorOn, copyButton, intensityBox, k95Label1, k95Label2, k95Label3, k95Label4, k95Label5, k95Label6, label, label_10, label_11, label_12, label_14, label_15, label_16, label_17, label_18, label_19, label_2, label_20, label_21, label_22, label_23, label_24, label_3, label_4, label_5, label_6, label_7, label_8, lightBox, lightColor1, lightColor2, lightColor3, lockBox, lockColorOff, lockColorOn, macroBox, macroColorOff, macroColorOn, modeBox, modeColorOff, modeColorOn, muteBox, muteColorNA, muteColorOff, muteColorOn, numBox, numColorOff, numColorOn, scrollBox, scrollColorOff, and scrollColorOn.

Referenced by setupUi().

```
590     {
591         KPerfWidget->setWindowTitle(QApplication::translate("KPerfWidget", "Form", Q_NULLPTR));
592         label_10->setText(QApplication::translate("KPerfWidget", "100%", Q_NULLPTR));
593         lockColorOff->setText(QString());
594         k95Label2->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
595         label_12->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
596         modeColorOff->setText(QString());
597         lightColor3->setText(QString());
598         lockBox->setText(QApplication::translate("KPerfWidget", "Indicate Windows Lock:", Q_NULLPTR)
    );
599         modeColorOn->setText(QString());
600         macroBox->setText(QApplication::translate("KPerfWidget", "Indicate macro recording:",
    Q_NULLPTR));
601         numColorOn->setText(QString());
602         numBox->clear();
603         numBox->insertItems(0, QStringList()
604          << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
605          << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
606          << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
607          << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
608          << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
609         );
610         label_5->setText(QApplication::translate("KPerfWidget", "Num lock:", Q_NULLPTR));
611         lightColor2->setText(QString());
612         label_8->setText(QApplication::translate("KPerfWidget", "Note: many desktop environments do
     not use scroll lock. The indicator may not turn on even when enabled.", Q_NULLPTR));
613         lightBox->setText(QApplication::translate("KPerfWidget", "Indicate brightness:", Q_NULLPTR)
    );
614         lightColor1->setText(QString());
615         label_6->setText(QApplication::translate("KPerfWidget", "Caps lock:", Q_NULLPTR));
616         label->setText(QApplication::translate("KPerfWidget", "Miscellaneous", Q_NULLPTR));
617         lockColorOn->setText(QString());
618         label_4->setText(QApplication::translate("KPerfWidget", "Lock lights", Q_NULLPTR));
619         modeBox->setText(QApplication::translate("KPerfWidget", "Indicate current mode:", Q_NULLPTR)
    );
620         capsColorOff->setText(QString());
621         numColorOff->setText(QString());
622         capsColorOn->setText(QString());
623         label_22->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
624         scrollBox->clear();
625         scrollBox->insertItems(0, QStringList()
626          << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
627          << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
628          << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
629          << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
630          << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
631         );
632         label_7->setText(QApplication::translate("KPerfWidget", "Scroll lock:", Q_NULLPTR));
633         scrollColorOn->setText(QString());
634         capsBox->clear();
635         capsBox->insertItems(0, QStringList()
636          << QApplication::translate("KPerfWidget", "Normal", Q_NULLPTR)
637          << QApplication::translate("KPerfWidget", "Always on", Q_NULLPTR)
638          << QApplication::translate("KPerfWidget", "Always off", Q_NULLPTR)
639          << QApplication::translate("KPerfWidget", "RGB indicator", Q_NULLPTR)
640          << QApplication::translate("KPerfWidget", "RGB + normal", Q_NULLPTR)
641         );
642         scrollColorOff->setText(QString());
643         muteBox->setText(QApplication::translate("KPerfWidget", "Indicate mute:", Q_NULLPTR));
```

```
        muteColorOn->setText(QString());
        macroColorOff->setText(QString());
        label_3->setText(QApplication::translate("KPerfWidget", "Top row", Q_NULLPTR));
        muteColorOff->setText(QString());
        k95Label3->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        macroColorOn->setText(QString());
#ifndef QT_NO_TOOLTIP
        muteColorNA->setToolTip(QApplication::translate("KPerfWidget", "If the sound device does not support muting, or if mute status is unknown, this color will be displayed.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        muteColorNA->setText(QString());
        label_19->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_21->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_24->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        label_20->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_16->setText(QApplication::translate("KPerfWidget", "67%", Q_NULLPTR));
        label_14->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        label_18->setText(QApplication::translate("KPerfWidget", "33%", Q_NULLPTR));
        label_15->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label4->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_17->setText(QApplication::translate("KPerfWidget", "Unknown", Q_NULLPTR));
        label_11->setText(QApplication::translate("KPerfWidget", "On", Q_NULLPTR));
        label_23->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label1->setText(QApplication::translate("KPerfWidget", "K95 buttons", Q_NULLPTR));
        copyButton->setText(QApplication::translate("KPerfWidget", "Copy to mode...", Q_NULLPTR));
        label_2->setText(QApplication::translate("KPerfWidget", "Indicator intensity:", Q_NULLPTR));
        intensityBox->setSuffix(QApplication::translate("KPerfWidget", "%", Q_NULLPTR));
        k95Label5->setText(QApplication::translate("KPerfWidget", "Off", Q_NULLPTR));
        k95Label6->setText(QApplication::translate("KPerfWidget", "Note: macro recording not yet implemented. Indicator will always display \"off\".", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.95.2.2 void Ui_KPerfWidget::setupUi (QWidget * *KPerfWidget*) [inline]

Definition at line 111 of file ui_kperfwidget.h.

References capsBox, capsColorOff, capsColorOn, copyButton, gridLayout, horizontalLayout, horizontalLayout_2, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, horizontalSpacer_6, horizontalSpacer_7, horizontalSpacer_8, intensityBox, k95Label1, k95Label2, k95Label3, k95Label4, k95Label5, k95Label6, k95Line, k95Spacer, label, label_10, label_11, label_12, label_14, label_15, label_16, label_17, label_18, label_19, label_2, label_20, label_21, label_22, label_23, label_24, label_3, label_4, label_5, label_6, label_7, label_8, lightBox, lightColor1, lightColor2, lightColor3, line, line_2, line_3, lockBox, lockColorOff, lockColorOn, macroBox, macroColorOff, macroColorOn, modeBox, modeColorOff, modeColorOn, muteBox, muteColorNA, muteColorOff, muteColorOn, numBox, numColorOff, numColorOn, retranslateUi(), scrollBox, scrollColorOff, scrollColorOn, verticalSpacer, verticalSpacer_2, verticalSpacer_3, and verticalSpacer_4.

Referenced by KPerfWidget::KPerfWidget().

```
    {
        if (KPerfWidget->objectName().isEmpty())
            KPerfWidget->setObjectName(QStringLiteral("KPerfWidget"));
        KPerfWidget->resize(840, 679);
        gridLayout = new QGridLayout(KPerfWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        k95Spacer = new QWidget(KPerfWidget);
        k95Spacer->setObjectName(QStringLiteral("k95Spacer"));
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(k95Spacer->sizePolicy().hasHeightForWidth());
        k95Spacer->setSizePolicy(sizePolicy);
        k95Spacer->setMinimumSize(QSize(15, 10));
```

```
        k95Spacer->setMaximumSize(QSize(15, 10));

        gridLayout->addWidget(k95Spacer, 12, 4, 1, 1);

        label_10 = new QLabel(KPerfWidget);
        label_10->setObjectName(QStringLiteral("label_10"));

        gridLayout->addWidget(label_10, 15, 5, 1, 1);

        lockColorOff = new ColorButton(KPerfWidget);
        lockColorOff->setObjectName(QStringLiteral("lockColorOff"));
        sizePolicy.setHeightForWidth(lockColorOff->sizePolicy().hasHeightForWidth());
        lockColorOff->setSizePolicy(sizePolicy);
        lockColorOff->setMinimumSize(QSize(0, 40));
        lockColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lockColorOff, 16, 7, 1, 1);

        line = new QFrame(KPerfWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 2, 0, 1, 13);

        horizontalSpacer_5 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_5, 17, 6, 1, 1);

        k95Label2 = new QLabel(KPerfWidget);
        k95Label2->setObjectName(QStringLiteral("k95Label2"));

        gridLayout->addWidget(k95Label2, 9, 5, 1, 1);

        label_12 = new QLabel(KPerfWidget);
        label_12->setObjectName(QStringLiteral("label_12"));

        gridLayout->addWidget(label_12, 17, 5, 1, 1);

        modeColorOff = new ColorButton(KPerfWidget);
        modeColorOff->setObjectName(QStringLiteral("modeColorOff"));
        sizePolicy.setHeightForWidth(modeColorOff->sizePolicy().hasHeightForWidth());
        modeColorOff->setSizePolicy(sizePolicy);
        modeColorOff->setMinimumSize(QSize(0, 40));
        modeColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(modeColorOff, 9, 7, 1, 1);

        lightColor3 = new ColorButton(KPerfWidget);
        lightColor3->setObjectName(QStringLiteral("lightColor3"));
        sizePolicy.setHeightForWidth(lightColor3->sizePolicy().hasHeightForWidth());
        lightColor3->setSizePolicy(sizePolicy);
        lightColor3->setMinimumSize(QSize(0, 40));
        lightColor3->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor3, 15, 4, 1, 1);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 15, 12, 1, 1);

        lockBox = new QCheckBox(KPerfWidget);
        lockBox->setObjectName(QStringLiteral("lockBox"));

        gridLayout->addWidget(lockBox, 16, 1, 1, 2);

        modeColorOn = new ColorButton(KPerfWidget);
        modeColorOn->setObjectName(QStringLiteral("modeColorOn"));
        sizePolicy.setHeightForWidth(modeColorOn->sizePolicy().hasHeightForWidth());
        modeColorOn->setSizePolicy(sizePolicy);
        modeColorOn->setMinimumSize(QSize(0, 40));
        modeColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(modeColorOn, 9, 4, 1, 1);

        macroBox = new QCheckBox(KPerfWidget);
        macroBox->setObjectName(QStringLiteral("macroBox"));

        gridLayout->addWidget(macroBox, 10, 1, 1, 2);

        numColorOn = new ColorButton(KPerfWidget);
        numColorOn->setObjectName(QStringLiteral("numColorOn"));
        sizePolicy.setHeightForWidth(numColorOn->sizePolicy().hasHeightForWidth());
        numColorOn->setSizePolicy(sizePolicy);
        numColorOn->setMinimumSize(QSize(0, 40));
```

```
        numColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(numColorOn, 21, 4, 1, 1);

        numBox = new QComboBox(KPerfWidget);
        numBox->setObjectName(QStringLiteral("numBox"));

        gridLayout->addWidget(numBox, 21, 2, 1, 1);

        label_5 = new QLabel(KPerfWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout->addWidget(label_5, 21, 1, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 20, QSizePolicy::Minimum, QSizePolicy::Fixed
);

        gridLayout->addItem(verticalSpacer_2, 4, 1, 1, 1);

        lightColor2 = new ColorButton(KPerfWidget);
        lightColor2->setObjectName(QStringLiteral("lightColor2"));
        sizePolicy.setHeightForWidth(lightColor2->sizePolicy().hasHeightForWidth());
        lightColor2->setSizePolicy(sizePolicy);
        lightColor2->setMinimumSize(QSize(0, 40));
        lightColor2->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor2, 15, 7, 1, 1);

        horizontalSpacer_7 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_7, 17, 3, 1, 1);

        label_8 = new QLabel(KPerfWidget);
        label_8->setObjectName(QStringLiteral("label_8"));
        QFont font;
        font.setPointSize(8);
        font.setItalic(true);
        label_8->setFont(font);

        gridLayout->addWidget(label_8, 25, 1, 1, 12);

        lightBox = new QCheckBox(KPerfWidget);
        lightBox->setObjectName(QStringLiteral("lightBox"));

        gridLayout->addWidget(lightBox, 15, 1, 1, 2);

        lightColor1 = new ColorButton(KPerfWidget);
        lightColor1->setObjectName(QStringLiteral("lightColor1"));
        sizePolicy.setHeightForWidth(lightColor1->sizePolicy().hasHeightForWidth());
        lightColor1->setSizePolicy(sizePolicy);
        lightColor1->setMinimumSize(QSize(0, 40));
        lightColor1->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lightColor1, 15, 10, 1, 1);

        verticalSpacer_4 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_4, 24, 4, 1, 1);

        label_6 = new QLabel(KPerfWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 22, 1, 1, 1);

        label = new QLabel(KPerfWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font1;
        font1.setBold(true);
        font1.setWeight(75);
        label->setFont(font1);

        gridLayout->addWidget(label, 1, 0, 1, 13);

        horizontalSpacer_6 = new QSpacerItem(10, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_6, 17, 9, 1, 1);

        lockColorOn = new ColorButton(KPerfWidget);
        lockColorOn->setObjectName(QStringLiteral("lockColorOn"));
        sizePolicy.setHeightForWidth(lockColorOn->sizePolicy().hasHeightForWidth());
        lockColorOn->setSizePolicy(sizePolicy);
        lockColorOn->setMinimumSize(QSize(0, 40));
        lockColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(lockColorOn, 16, 4, 1, 1);
```

```
        label_4 = new QLabel(KPerfWidget);
        label_4->setObjectName(QStringLiteral("label_4"));
        label_4->setFont(font1);

        gridLayout->addWidget(label_4, 19, 0, 1, 13);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding
    );

        gridLayout->addItem(verticalSpacer, 26, 2, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 20, QSizePolicy::Minimum, QSizePolicy::Fixed
    );

        gridLayout->addItem(verticalSpacer_3, 18, 4, 1, 1);

        modeBox = new QCheckBox(KPerfWidget);
        modeBox->setObjectName(QStringLiteral("modeBox"));

        gridLayout->addWidget(modeBox, 9, 1, 1, 2);

        capsColorOff = new ColorButton(KPerfWidget);
        capsColorOff->setObjectName(QStringLiteral("capsColorOff"));
        sizePolicy.setHeightForWidth(capsColorOff->sizePolicy().hasHeightForWidth());
        capsColorOff->setSizePolicy(sizePolicy);
        capsColorOff->setMinimumSize(QSize(0, 40));
        capsColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(capsColorOff, 22, 7, 1, 1);

        numColorOff = new ColorButton(KPerfWidget);
        numColorOff->setObjectName(QStringLiteral("numColorOff"));
        QSizePolicy sizePolicy1(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(40);
        sizePolicy1.setHeightForWidth(numColorOff->sizePolicy().hasHeightForWidth());
        numColorOff->setSizePolicy(sizePolicy1);
        numColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(numColorOff, 21, 7, 1, 1);

        capsColorOn = new ColorButton(KPerfWidget);
        capsColorOn->setObjectName(QStringLiteral("capsColorOn"));
        sizePolicy.setHeightForWidth(capsColorOn->sizePolicy().hasHeightForWidth());
        capsColorOn->setSizePolicy(sizePolicy);
        capsColorOn->setMinimumSize(QSize(0, 40));
        capsColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(capsColorOn, 22, 4, 1, 1);

        line_3 = new QFrame(KPerfWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 20, 0, 1, 13);

        label_22 = new QLabel(KPerfWidget);
        label_22->setObjectName(QStringLiteral("label_22"));

        gridLayout->addWidget(label_22, 21, 8, 1, 1);

        scrollBox = new QComboBox(KPerfWidget);
        scrollBox->setObjectName(QStringLiteral("scrollBox"));

        gridLayout->addWidget(scrollBox, 23, 2, 1, 1);

        label_7 = new QLabel(KPerfWidget);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout->addWidget(label_7, 23, 1, 1, 1);

        scrollColorOn = new ColorButton(KPerfWidget);
        scrollColorOn->setObjectName(QStringLiteral("scrollColorOn"));
        sizePolicy.setHeightForWidth(scrollColorOn->sizePolicy().hasHeightForWidth());
        scrollColorOn->setSizePolicy(sizePolicy);
        scrollColorOn->setMinimumSize(QSize(0, 40));
        scrollColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(scrollColorOn, 23, 4, 1, 1);

        capsBox = new QComboBox(KPerfWidget);
        capsBox->setObjectName(QStringLiteral("capsBox"));

        gridLayout->addWidget(capsBox, 22, 2, 1, 1);

```

```
        scrollColorOff = new ColorButton(KPerfWidget);
        scrollColorOff->setObjectName(QStringLiteral("scrollColorOff"));
        sizePolicy.setHeightForWidth(scrollColorOff->sizePolicy().hasHeightForWidth());
        scrollColorOff->setSizePolicy(sizePolicy);
        scrollColorOff->setMinimumSize(QSize(0, 40));
        scrollColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(scrollColorOff, 23, 7, 1, 1);

        muteBox = new QCheckBox(KPerfWidget);
        muteBox->setObjectName(QStringLiteral("muteBox"));

        gridLayout->addWidget(muteBox, 17, 1, 1, 2);

        muteColorOn = new ColorButton(KPerfWidget);
        muteColorOn->setObjectName(QStringLiteral("muteColorOn"));
        sizePolicy.setHeightForWidth(muteColorOn->sizePolicy().hasHeightForWidth());
        muteColorOn->setSizePolicy(sizePolicy);
        muteColorOn->setMinimumSize(QSize(0, 40));
        muteColorOn->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorOn, 17, 4, 1, 1);

        macroColorOff = new ColorButton(KPerfWidget);
        macroColorOff->setObjectName(QStringLiteral("macroColorOff"));
        QSizePolicy sizePolicy2(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(40);
        sizePolicy2.setHeightForWidth(macroColorOff->sizePolicy().hasHeightForWidth());
        macroColorOff->setSizePolicy(sizePolicy2);
        macroColorOff->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(macroColorOff, 10, 7, 1, 1);

        label_3 = new QLabel(KPerfWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        label_3->setFont(font1);

        gridLayout->addWidget(label_3, 13, 0, 1, 3);

        muteColorOff = new ColorButton(KPerfWidget);
        muteColorOff->setObjectName(QStringLiteral("muteColorOff"));
        sizePolicy.setHeightForWidth(muteColorOff->sizePolicy().hasHeightForWidth());
        muteColorOff->setSizePolicy(sizePolicy);
        muteColorOff->setMinimumSize(QSize(0, 40));
        muteColorOff->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorOff, 17, 7, 1, 1);

        k95Label3 = new QLabel(KPerfWidget);
        k95Label3->setObjectName(QStringLiteral("k95Label3"));

        gridLayout->addWidget(k95Label3, 9, 8, 1, 1);

        macroColorOn = new ColorButton(KPerfWidget);
        macroColorOn->setObjectName(QStringLiteral("macroColorOn"));
        sizePolicy2.setHeightForWidth(macroColorOn->sizePolicy().hasHeightForWidth());
        macroColorOn->setSizePolicy(sizePolicy2);
        macroColorOn->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(macroColorOn, 10, 4, 1, 1);

        muteColorNA = new ColorButton(KPerfWidget);
        muteColorNA->setObjectName(QStringLiteral("muteColorNA"));
        muteColorNA->setMinimumSize(QSize(0, 40));
        muteColorNA->setMaximumSize(QSize(16777215, 40));

        gridLayout->addWidget(muteColorNA, 17, 10, 1, 1);

        label_19 = new QLabel(KPerfWidget);
        label_19->setObjectName(QStringLiteral("label_19"));

        gridLayout->addWidget(label_19, 21, 5, 1, 1);

        k95Line = new QFrame(KPerfWidget);
        k95Line->setObjectName(QStringLiteral("k95Line"));
        k95Line->setFrameShape(QFrame::HLine);
        k95Line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(k95Line, 8, 0, 1, 13);

        label_21 = new QLabel(KPerfWidget);
        label_21->setObjectName(QStringLiteral("label_21"));

        gridLayout->addWidget(label_21, 23, 5, 1, 1);

        label_24 = new QLabel(KPerfWidget);
```

```
        label_24->setObjectName(QStringLiteral("label_24"));

        gridLayout->addWidget(label_24, 23, 8, 1, 1);

        label_20 = new QLabel(KPerfWidget);
        label_20->setObjectName(QStringLiteral("label_20"));

        gridLayout->addWidget(label_20, 22, 5, 1, 1);

        label_16 = new QLabel(KPerfWidget);
        label_16->setObjectName(QStringLiteral("label_16"));

        gridLayout->addWidget(label_16, 15, 8, 1, 1);

        label_14 = new QLabel(KPerfWidget);
        label_14->setObjectName(QStringLiteral("label_14"));

        gridLayout->addWidget(label_14, 17, 8, 1, 1);

        label_18 = new QLabel(KPerfWidget);
        label_18->setObjectName(QStringLiteral("label_18"));

        gridLayout->addWidget(label_18, 15, 11, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_2, 15, 0, 1, 1);

        label_15 = new QLabel(KPerfWidget);
        label_15->setObjectName(QStringLiteral("label_15"));

        gridLayout->addWidget(label_15, 16, 8, 1, 1);

        k95Label4 = new QLabel(KPerfWidget);
        k95Label4->setObjectName(QStringLiteral("k95Label4"));

        gridLayout->addWidget(k95Label4, 10, 5, 1, 1);

        label_17 = new QLabel(KPerfWidget);
        label_17->setObjectName(QStringLiteral("label_17"));

        gridLayout->addWidget(label_17, 17, 11, 1, 1);

        label_11 = new QLabel(KPerfWidget);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout->addWidget(label_11, 16, 5, 1, 1);

        label_23 = new QLabel(KPerfWidget);
        label_23->setObjectName(QStringLiteral("label_23"));

        gridLayout->addWidget(label_23, 22, 8, 1, 1);

        k95Label1 = new QLabel(KPerfWidget);
        k95Label1->setObjectName(QStringLiteral("k95Label1"));
        k95Label1->setFont(font1);

        gridLayout->addWidget(k95Label1, 7, 0, 1, 5);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        copyButton = new QPushButton(KPerfWidget);
        copyButton->setObjectName(QStringLiteral("copyButton"));

        horizontalLayout_2->addWidget(copyButton);

        horizontalSpacer_8 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_8);


        gridLayout->addLayout(horizontalLayout_2, 3, 10, 1, 3);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        label_2 = new QLabel(KPerfWidget);
        label_2->setObjectName(QStringLiteral("label_2"));

        horizontalLayout->addWidget(label_2);

        horizontalSpacer_4 = new QSpacerItem(10, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_4);

```

```
        intensityBox = new QSpinBox(KPerfWidget);
        intensityBox->setObjectName(QStringLiteral("intensityBox"));
        intensityBox->setMaximum(100);
        intensityBox->setValue(100);

        horizontalLayout->addWidget(intensityBox);

        horizontalSpacer_3 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_3);


        gridLayout->addLayout(horizontalLayout, 3, 1, 1, 9);

        k95Label5 = new QLabel(KPerfWidget);
        k95Label5->setObjectName(QStringLiteral("k95Label5"));

        gridLayout->addWidget(k95Label5, 10, 8, 1, 1);

        line_2 = new QFrame(KPerfWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 14, 0, 1, 13);

        k95Label6 = new QLabel(KPerfWidget);
        k95Label6->setObjectName(QStringLiteral("k95Label6"));
        k95Label6->setFont(font);

        gridLayout->addWidget(k95Label6, 11, 1, 1, 10);


        retranslateUi(KPerfWidget);

        QMetaObject::connectSlotsByName(KPerfWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.95.3 Field Documentation

12.95.3.1 QComboBox* Ui_KPerfWidget::capsBox

Definition at line 74 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.2 ColorButton* Ui_KPerfWidget::capsColorOff

Definition at line 66 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.3 ColorButton* Ui_KPerfWidget::capsColorOn

Definition at line 68 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.4 QPushButton* Ui_KPerfWidget::copyButton

Definition at line 100 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.5 QGridLayout* Ui_KPerfWidget::gridLayout

Definition at line 34 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.6 QHBoxLayout* Ui_KPerfWidget::horizontalLayout

Definition at line 102 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.7 QHBoxLayout* Ui_KPerfWidget::horizontalLayout_2

Definition at line 99 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.8 QSpacerItem* Ui_KPerfWidget::horizontalSpacer

Definition at line 44 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.9 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_2

Definition at line 92 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.10 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_3

Definition at line 106 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.11 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_4

Definition at line 104 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.12 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_5

Definition at line 39 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.13 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_6

Definition at line 60 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.14 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_7

Definition at line 53 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.15 QSpacerItem* Ui_KPerfWidget::horizontalSpacer_8

Definition at line 101 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.16 QSpinBox* Ui_KPerfWidget::intensityBox

Definition at line 105 of file ui_kperfwidget.h.

Referenced by retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.17 QLabel* Ui_KPerfWidget::k95Label1

Definition at line 98 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.18 QLabel* Ui_KPerfWidget::k95Label2

Definition at line 40 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.19 QLabel* Ui_KPerfWidget::k95Label3

Definition at line 81 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.20 QLabel* Ui_KPerfWidget::k95Label4

Definition at line 94 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.21 QLabel* Ui_KPerfWidget::k95Label5

Definition at line 107 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.22 QLabel* Ui_KPerfWidget::k95Label6

Definition at line 109 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.23 QFrame* Ui_KPerfWidget::k95Line

Definition at line 85 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), and setupUi().

12.95.3.24 QWidget* Ui_KPerfWidget::k95Spacer

Definition at line 35 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), and setupUi().

12.95.3.25 QLabel* Ui_KPerfWidget::label

Definition at line 59 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.26 QLabel* Ui_KPerfWidget::label_10

Definition at line 36 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.27 QLabel* Ui_KPerfWidget::label_11

Definition at line 96 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.28 QLabel* Ui_KPerfWidget::label_12

Definition at line 41 of file ui_kperfwidget.h.

Referenced by retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.29 QLabel* Ui_KPerfWidget::label_14

Definition at line 90 of file ui_kperfwidget.h.

Referenced by retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.30 QLabel* Ui_KPerfWidget::label_15

Definition at line 93 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.31 QLabel* Ui_KPerfWidget::label_16

Definition at line 89 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.32 QLabel* Ui_KPerfWidget::label_17

Definition at line 95 of file ui_kperfwidget.h.

Referenced by retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.33 QLabel* Ui_KPerfWidget::label_18

Definition at line 91 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.34 QLabel* Ui_KPerfWidget::label_19

Definition at line 84 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.35 QLabel* Ui_KPerfWidget::label_2

Definition at line 103 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.36 QLabel* Ui_KPerfWidget::label_20

Definition at line 88 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.37 QLabel* Ui_KPerfWidget::label_21

Definition at line 86 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.38 QLabel* Ui_KPerfWidget::label_22

Definition at line 70 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.39 QLabel* Ui_KPerfWidget::label_23

Definition at line 97 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.40 QLabel* Ui_KPerfWidget::label_24

Definition at line 87 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.41 QLabel* Ui_KPerfWidget::label_3

Definition at line 79 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.42 QLabel* Ui_KPerfWidget::label_4

Definition at line 62 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.43 QLabel* Ui_KPerfWidget::label_5

Definition at line 50 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.44 QLabel* Ui_KPerfWidget::label_6

Definition at line 58 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.45 QLabel* Ui_KPerfWidget::label_7

Definition at line 72 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.46 QLabel* Ui_KPerfWidget::label_8

Definition at line 54 of file ui_kperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.95.3.47 QCheckBox* Ui_KPerfWidget::lightBox

Definition at line 55 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.48 ColorButton* Ui_KPerfWidget::lightColor1

Definition at line 56 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.49 ColorButton* Ui_KPerfWidget::lightColor2

Definition at line 52 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.50 ColorButton* Ui_KPerfWidget::lightColor3

Definition at line 43 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.51 QFrame* Ui_KPerfWidget::line

Definition at line 38 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.52 QFrame* Ui_KPerfWidget::line_2

Definition at line 108 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.53 QFrame* Ui_KPerfWidget::line_3

Definition at line 69 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.54 QCheckBox* Ui_KPerfWidget::lockBox

Definition at line 45 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.55 ColorButton* Ui_KPerfWidget::lockColorOff

Definition at line 37 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.56 ColorButton* Ui_KPerfWidget::lockColorOn

Definition at line 61 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.57 QCheckBox* Ui_KPerfWidget::macroBox

Definition at line 47 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.58 ColorButton* Ui_KPerfWidget::macroColorOff

Definition at line 78 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.59 ColorButton* Ui_KPerfWidget::macroColorOn

Definition at line 82 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.60 QCheckBox* Ui_KPerfWidget::modeBox

Definition at line 65 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.61 ColorButton* Ui_KPerfWidget::modeColorOff

Definition at line 42 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.62 ColorButton* Ui_KPerfWidget::modeColorOn

Definition at line 46 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.63 QCheckBox* Ui_KPerfWidget::muteBox

Definition at line 76 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.64 ColorButton* Ui_KPerfWidget::muteColorNA

Definition at line 83 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.65 ColorButton* Ui_KPerfWidget::muteColorOff

Definition at line 80 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.66 ColorButton* Ui_KPerfWidget::muteColorOn

Definition at line 77 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), KPerfWidget::setPerf(), and setupUi().

12.95.3.67 QComboBox* Ui_KPerfWidget::numBox

Definition at line 49 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.68 ColorButton* Ui_KPerfWidget::numColorOff

Definition at line 67 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.69 ColorButton* Ui_KPerfWidget::numColorOn

Definition at line 48 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.70 QComboBox* Ui_KPerfWidget::scrollBox

Definition at line 71 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.71 ColorButton* Ui_KPerfWidget::scrollColorOff

Definition at line 75 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.72 ColorButton* Ui_KPerfWidget::scrollColorOn

Definition at line 73 of file ui_kperfwidget.h.

Referenced by KPerfWidget::KPerfWidget(), retranslateUi(), and setupUi().

12.95.3.73 QSpacerItem* Ui_KPerfWidget::verticalSpacer

Definition at line 63 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.74 QSpacerItem* Ui_KPerfWidget::verticalSpacer_2

Definition at line 51 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.75 QSpacerItem* Ui_KPerfWidget::verticalSpacer_3

Definition at line 64 of file ui_kperfwidget.h.

Referenced by setupUi().

12.95.3.76 QSpacerItem* Ui_KPerfWidget::verticalSpacer_4

Definition at line 57 of file ui_kperfwidget.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_kperfwidget.h

12.96 Ui_LayoutDialog Class Reference

```
#include <src/ckb/ui_layoutdialog.h>
```

Inheritance diagram for Ui_LayoutDialog:

Collaboration diagram for Ui_LayoutDialog:

Public Member Functions

- void setupUi (QDialog *LayoutDialog)

- void retranslateUi (QDialog *LayoutDialog)

Data Fields

- QGridLayout * gridLayout
- QSpacerItem * verticalSpacer
- QSpacerItem * verticalSpacer_3
- QDialogButtonBox * buttonBox
- QLabel * label
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer_2
- QSpacerItem * horizontalSpacer
- QComboBox * comboBox
- QLabel * label_2
- QSpacerItem * verticalSpacer_4

12.96.1 Detailed Description

Definition at line 26 of file ui_layoutdialog.h.

12.96.2 Member Function Documentation

12.96.2.1 void Ui_LayoutDialog::retranslateUi (QDialog * *LayoutDialog*) [inline]

Definition at line 109 of file ui_layoutdialog.h.

References label, and label_2.

Referenced by setupUi().

```
110     {
111         LayoutDialog->setWindowTitle(QApplication::translate("LayoutDialog", "Keyboard Layout", Q_NULLPTR))
    ;
112         label->setText(QApplication::translate("LayoutDialog", "Please select your keyboard layout:",
    Q_NULLPTR));
113         label_2->setText(QApplication::translate("LayoutDialog", "Note: this only controls the
     layout within the ckb application. If your keys are typing the wrong characters, check your system preferences.",
     Q_NULLPTR));
114     } // retranslateUi
```

Here is the caller graph for this function:

12.96.2.2 void Ui_LayoutDialog::setupUi (QDialog * *LayoutDialog*) [inline]

Definition at line 41 of file ui_layoutdialog.h.

References buttonBox, comboBox, gridLayout, horizontalSpacer, horizontalSpacer_2, label, label_2, retranslateUi(), verticalSpacer, verticalSpacer_2, verticalSpacer_3, and verticalSpacer_4.

Referenced by LayoutDialog::LayoutDialog().

```
 {
     if (LayoutDialog->objectName().isEmpty())
         LayoutDialog->setObjectName(QStringLiteral("LayoutDialog"));
     LayoutDialog->resize(400, 240);
     gridLayout = new QGridLayout(LayoutDialog);
     gridLayout->setObjectName(QStringLiteral("gridLayout"));
     verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

     gridLayout->addItem(verticalSpacer, 6, 0, 1, 3);

     verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

     gridLayout->addItem(verticalSpacer_3, 0, 1, 1, 1);

     buttonBox = new QDialogButtonBox(LayoutDialog);
     buttonBox->setObjectName(QStringLiteral("buttonBox"));
     buttonBox->setOrientation(Qt::Horizontal);
     buttonBox->setStandardButtons(QDialogButtonBox::Ok);

     gridLayout->addWidget(buttonBox, 7, 0, 1, 3);

     label = new QLabel(LayoutDialog);
     label->setObjectName(QStringLiteral("label"));
     label->setAlignment(Qt::AlignCenter);

     gridLayout->addWidget(label, 1, 0, 1, 3);

     horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

     gridLayout->addItem(horizontalSpacer_2, 3, 2, 1, 1);

     verticalSpacer_2 = new QSpacerItem(20, 15, QSizePolicy::Minimum, QSizePolicy::Fixed);

     gridLayout->addItem(verticalSpacer_2, 4, 1, 1, 1);

     horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

     gridLayout->addItem(horizontalSpacer, 3, 0, 1, 1);

     comboBox = new QComboBox(LayoutDialog);
     comboBox->setObjectName(QStringLiteral("comboBox"));

     gridLayout->addWidget(comboBox, 3, 1, 1, 1);

     label_2 = new QLabel(LayoutDialog);
     label_2->setObjectName(QStringLiteral("label_2"));
     QFont font;
     font.setPointSize(8);
     font.setItalic(true);
     label_2->setFont(font);
     label_2->setAlignment(Qt::AlignCenter);
     label_2->setWordWrap(true);

     gridLayout->addWidget(label_2, 5, 0, 1, 3);

     verticalSpacer_4 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

     gridLayout->addItem(verticalSpacer_4, 2, 1, 1, 1);


      retranslateUi(LayoutDialog);
      QObject::connect(buttonBox, SIGNAL(accepted()), LayoutDialog, SLOT(accept()));
      QObject::connect(buttonBox, SIGNAL(rejected()), LayoutDialog, SLOT(reject()));

      QMetaObject::connectSlotsByName(LayoutDialog);
  } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.96.3 Field Documentation

12.96.3.1 QDialogButtonBox* Ui_LayoutDialog::buttonBox

Definition at line 32 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.2 QComboBox* Ui_LayoutDialog::comboBox

Definition at line 37 of file ui_layoutdialog.h.

Referenced by LayoutDialog::LayoutDialog(), LayoutDialog::selected(), and setupUi().

12.96.3.3 QGridLayout* Ui_LayoutDialog::gridLayout

Definition at line 29 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.4 QSpacerItem* Ui_LayoutDialog::horizontalSpacer

Definition at line 36 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.5 QSpacerItem* Ui_LayoutDialog::horizontalSpacer_2

Definition at line 34 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.6 QLabel* Ui_LayoutDialog::label

Definition at line 33 of file ui_layoutdialog.h.

Referenced by retranslateUi(), and setupUi().

12.96.3.7 QLabel* Ui_LayoutDialog::label_2

Definition at line 38 of file ui_layoutdialog.h.

Referenced by retranslateUi(), and setupUi().

12.96.3.8 QSpacerItem* Ui_LayoutDialog::verticalSpacer

Definition at line 30 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.9 QSpacerItem* Ui_LayoutDialog::verticalSpacer_2

Definition at line 35 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.10 QSpacerItem* Ui_LayoutDialog::verticalSpacer_3

Definition at line 31 of file ui_layoutdialog.h.

Referenced by setupUi().

12.96.3.11 QSpacerItem* Ui_LayoutDialog::verticalSpacer_4

Definition at line 39 of file ui_layoutdialog.h.

Referenced by setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_layoutdialog.h

12.97 Ui_MainWindow Class Reference

```
#include <src/ckb/ui_mainwindow.h>
```

Inheritance diagram for Ui_MainWindow:

Collaboration diagram for Ui_MainWindow:

Public Member Functions

- void setupUi (QMainWindow *MainWindow)
- void retranslateUi (QMainWindow *MainWindow)

Data Fields

- QAction ∗ actionExit
- QAction ∗ actionAbout
- QWidget ∗ centralWidget
- QGridLayout ∗ gridLayout
- QTabWidget ∗ tabWidget

12.97.1 Detailed Description

Definition at line 24 of file ui_mainwindow.h.

12.97.2 Member Function Documentation

12.97.2.1 void Ui_MainWindow::retranslateUi (QMainWindow ∗ *MainWindow*) [inline]

Definition at line 68 of file ui_mainwindow.h.

References actionAbout, and actionExit.

Referenced by setupUi().

```
69     {
70         MainWindow->setWindowTitle(QApplication::translate("MainWindow", "ckb-next", Q_NULLPTR));
71         actionExit->setText(QApplication::translate("MainWindow", "Exit", Q_NULLPTR));
72         actionExit->setShortcut(QApplication::translate("MainWindow", "Ctrl+Q", Q_NULLPTR));
73         actionAbout->setText(QApplication::translate("MainWindow", "About", Q_NULLPTR));
74     } // retranslateUi
```

Here is the caller graph for this function:

12.97.2.2 void Ui_MainWindow::setupUi (QMainWindow ∗ *MainWindow*) [inline]

Definition at line 33 of file ui_mainwindow.h.

References actionAbout, actionExit, centralWidget, gridLayout, retranslateUi(), and tabWidget.

Referenced by MainWindow::MainWindow().

```
34     {
35         if (MainWindow->objectName().isEmpty())
36             MainWindow->setObjectName(QStringLiteral("MainWindow"));
37         MainWindow->resize(1000, 750);
38         MainWindow->setMinimumSize(QSize(1000, 750));
39         QIcon icon;
40         icon.addFile(QStringLiteral(":/img/ckb-logo.png"), QSize(), QIcon::Normal, QIcon::Off);
41         MainWindow->setWindowIcon(icon);
42         MainWindow->setUnifiedTitleAndToolBarOnMac(true);
43         actionExit = new QAction(MainWindow);
44         actionExit->setObjectName(QStringLiteral("actionExit"));
45         actionAbout = new QAction(MainWindow);
46         actionAbout->setObjectName(QStringLiteral("actionAbout"));
47         centralWidget = new QWidget(MainWindow);
48         centralWidget->setObjectName(QStringLiteral("centralWidget"));
49         gridLayout = new QGridLayout(centralWidget);
50         gridLayout->setSpacing(6);
```

```
        gridLayout->setContentsMargins(11, 11, 11, 11);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        tabWidget = new QTabWidget(centralWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));

        gridLayout->addWidget(tabWidget, 0, 0, 1, 1);

        MainWindow->setCentralWidget(centralWidget);

        retranslateUi(MainWindow);

        tabWidget->setCurrentIndex(-1);


        QMetaObject::connectSlotsByName(MainWindow);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.97.3 Field Documentation

12.97.3.1 QAction* Ui_MainWindow::actionAbout

Definition at line 28 of file ui_mainwindow.h.

Referenced by retranslateUi(), and setupUi().

12.97.3.2 QAction* Ui_MainWindow::actionExit

Definition at line 27 of file ui_mainwindow.h.

Referenced by MainWindow::MainWindow(), retranslateUi(), and setupUi().

12.97.3.3 QWidget* Ui_MainWindow::centralWidget

Definition at line 29 of file ui_mainwindow.h.

Referenced by setupUi().

12.97.3.4 QGridLayout* Ui_MainWindow::gridLayout

Definition at line 30 of file ui_mainwindow.h.

Referenced by setupUi().

12.97.3.5 QTabWidget* Ui_MainWindow::tabWidget

Definition at line 31 of file ui_mainwindow.h.

Referenced by MainWindow::addDevice(), MainWindow::MainWindow(), MainWindow::removeDevice(), setupUi(), and MainWindow::showFwUpdateNotification().

The documentation for this class was generated from the following file:

- src/ckb/ui_mainwindow.h

12.98 Ui_ModeSelectDialog Class Reference

```
#include <src/ckb/ui_modeselectdialog.h>
```

Inheritance diagram for Ui_ModeSelectDialog:

Collaboration diagram for Ui_ModeSelectDialog:

Public Member Functions

- void setupUi (QDialog ∗ModeSelectDialog)
- void retranslateUi (QDialog ∗ModeSelectDialog)

Data Fields

- QGridLayout ∗ gridLayout
- QLabel ∗ label
- QDialogButtonBox ∗ buttonBox
- QListWidget ∗ modeList
- QPushButton ∗ selAllButton
- QPushButton ∗ selNoneButton

12.98.1 Detailed Description

Definition at line 26 of file ui_modeselectdialog.h.

12.98.2 Member Function Documentation

12.98.2.1 void Ui_ModeSelectDialog::retranslateUi (QDialog ∗ *ModeSelectDialog*) [inline]

Definition at line 82 of file ui_modeselectdialog.h.

References label, selAllButton, and selNoneButton.

Referenced by setupUi().

```
83     {
84         ModeSelectDialog->setWindowTitle(QApplication::translate("ModeSelectDialog", "Select Modes",
     Q_NULLPTR));
85         label->setText(QApplication::translate("ModeSelectDialog", "TextLabel", Q_NULLPTR));
86         selAllButton->setText(QApplication::translate("ModeSelectDialog", "Select All",
     Q_NULLPTR));
87         selNoneButton->setText(QApplication::translate("ModeSelectDialog", "Select None",
     Q_NULLPTR));
88     } // retranslateUi
```

Here is the caller graph for this function:

12.98.2.2 void Ui_ModeSelectDialog::setupUi (QDialog * *ModeSelectDialog*) [inline]

Definition at line 36 of file ui_modeselectdialog.h.

References buttonBox, gridLayout, label, modeList, retranslateUi(), selAllButton, and selNoneButton.

Referenced by ModeSelectDialog::ModeSelectDialog().

```
37      {
38          if (ModeSelectDialog->objectName().isEmpty())
39              ModeSelectDialog->setObjectName(QStringLiteral("ModeSelectDialog"));
40          ModeSelectDialog->resize(320, 320);
41          gridLayout = new QGridLayout(ModeSelectDialog);
42          gridLayout->setObjectName(QStringLiteral("gridLayout"));
43          label = new QLabel(ModeSelectDialog);
44          label->setObjectName(QStringLiteral("label"));
45          label->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignTop);
46
47          gridLayout->addWidget(label, 0, 0, 1, 2);
48
49          buttonBox = new QDialogButtonBox(ModeSelectDialog);
50          buttonBox->setObjectName(QStringLiteral("buttonBox"));
51          buttonBox->setOrientation(Qt::Vertical);
52          buttonBox->setStandardButtons(QDialogButtonBox::Cancel|QDialogButtonBox::Ok);
53          buttonBox->setCenterButtons(false);
54
55          gridLayout->addWidget(buttonBox, 0, 2, 3, 1);
56
57          modeList = new QListWidget(ModeSelectDialog);
58          modeList->setObjectName(QStringLiteral("modeList"));
59          modeList->setFrameShadow(QFrame::Plain);
60          modeList->setSelectionMode(QAbstractItemView::ExtendedSelection);
61
62          gridLayout->addWidget(modeList, 1, 0, 1, 2);
63
64          selAllButton = new QPushButton(ModeSelectDialog);
65          selAllButton->setObjectName(QStringLiteral("selAllButton"));
66
67          gridLayout->addWidget(selAllButton, 2, 0, 1, 1);
68
69          selNoneButton = new QPushButton(ModeSelectDialog);
70          selNoneButton->setObjectName(QStringLiteral("selNoneButton"));
71
72          gridLayout->addWidget(selNoneButton, 2, 1, 1, 1);
73
74
75          retranslateUi(ModeSelectDialog);
76          QObject::connect(buttonBox, SIGNAL(accepted()), ModeSelectDialog, SLOT(accept()));
77          QObject::connect(buttonBox, SIGNAL(rejected()), ModeSelectDialog, SLOT(reject()));
78
79          QMetaObject::connectSlotsByName(ModeSelectDialog);
80      } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.98.3 Field Documentation

12.98.3.1 QDialogButtonBox* Ui_ModeSelectDialog::buttonBox

Definition at line 31 of file ui_modeselectdialog.h.

Referenced by setupUi().

12.98.3.2 QGridLayout* Ui_ModeSelectDialog::gridLayout

Definition at line 29 of file ui_modeselectdialog.h.

Referenced by setupUi().

12.98.3.3 QLabel* Ui_ModeSelectDialog::label

Definition at line 30 of file ui_modeselectdialog.h.

Referenced by ModeSelectDialog::ModeSelectDialog(), retranslateUi(), and setupUi().

12.98.3.4 QListWidget* Ui_ModeSelectDialog::modeList

Definition at line 32 of file ui_modeselectdialog.h.

Referenced by ModeSelectDialog::ModeSelectDialog(), ModeSelectDialog::on_selAllButton_clicked(), ModeSelectDialog::on_selNoneButton_clicked(), ModeSelectDialog::selection(), and setupUi().

12.98.3.5 QPushButton* Ui_ModeSelectDialog::selAllButton

Definition at line 33 of file ui_modeselectdialog.h.

Referenced by retranslateUi(), and setupUi().

12.98.3.6 QPushButton* Ui_ModeSelectDialog::selNoneButton

Definition at line 34 of file ui_modeselectdialog.h.

Referenced by retranslateUi(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_modeselectdialog.h

12.99 Ui_MPerfWidget Class Reference

```
#include <src/ckb/ui_mperfwidget.h>
```

Inheritance diagram for Ui_MPerfWidget:

Collaboration diagram for Ui_MPerfWidget:

Public Member Functions

- void setupUi (QWidget *MPerfWidget)
- void retranslateUi (QWidget *MPerfWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QLabel * label
- QFrame * line
- QGridLayout * gridLayout
- QLabel * label_25
- QHBoxLayout * horizontalLayout_2
- QComboBox * lHeightBox
- QSpacerItem * horizontalSpacer_2
- QCheckBox * eBox2
- QSlider * ySlider3
- QSlider * xSlider2
- QSpinBox * xBox3
- QSpinBox * yBox0
- QSlider * ySlider0
- ColorButton * iButton4
- ColorButton * iButton5
- QSpacerItem * horizontalSpacer_4
- QSpacerItem * verticalSpacer_3
- QSpacerItem * horizontalSpacer_5
- ColorButton * iButton3
- QLabel * label_12
- QSpinBox * xBox4
- QSpinBox * xBox0
- QSpinBox * yBox5
- QCheckBox * eBox5
- QSlider * xSlider5
- QSpinBox * xBox1

- QSpinBox * yBox2
- QSpinBox * yBox3
- QSlider * xSlider4
- QLabel * label_4
- QSlider * xSlider0
- ColorButton * iButton2
- QFrame * line_3
- ColorButton * iButtonO
- QSpinBox * yBox1
- QSlider * ySlider2
- QSpinBox * xBox2
- QSlider * xSlider1
- QSpacerItem * horizontalSpacer
- QSpinBox * yBox4
- ColorButton * iButton1
- QSlider * ySlider4
- QSlider * ySlider1
- ColorButton * iButton0
- QSlider * xSlider3
- QSpinBox * xBox5
- QLabel * label_3
- QLabel * label_6
- QSlider * ySlider5
- QLabel * label_7
- QLabel * label_8
- QLabel * label_5
- QLabel * label_15
- QLabel * label_13
- QLabel * label_14
- QCheckBox * eBox4
- QLabel * label_11
- QCheckBox * eBox3
- QCheckBox * eBox1
- QLabel * label_2
- QSpacerItem * verticalSpacer
- QCheckBox * aSnapBox
- QFrame * line_2
- QHBoxLayout * horizontalLayout_4
- QCheckBox * indicBox
- QSpacerItem * horizontalSpacer_3
- QSpinBox * spinBox
- QSpacerItem * horizontalSpacer_7
- QCheckBox * xyBox
- QSpacerItem * verticalSpacer_2
- QHBoxLayout * horizontalLayout
- QPushButton * copyButton
- QSpacerItem * horizontalSpacer_6

12.99.1 Detailed Description

Definition at line 33 of file ui_mperfwidget.h.

12.99.2 Member Function Documentation

12.99.2.1 void Ui_MPerfWidget::retranslateUi (QWidget * *MPerfWidget*) [inline]

Definition at line 641 of file ui_mperfwidget.h.

References aSnapBox, copyButton, eBox1, eBox2, eBox3, eBox4, eBox5, iButton0, iButton1, iButton2, iButton3, iButton4, iButton5, iButtonO, indicBox, label, label_11, label_12, label_13, label_14, label_15, label_2, label_25, label_3, label_4, label_5, label_6, label_7, label_8, lHeightBox, spinBox, and xyBox.

Referenced by setupUi().

```
    {
        MPerfWidget->setWindowTitle(QApplication::translate("MPerfWidget", "Form", Q_NULLPTR));
        label->setText(QApplication::translate("MPerfWidget", "DPI", Q_NULLPTR));
        label_25->setText(QApplication::translate("MPerfWidget", "Lift height:", Q_NULLPTR));
        lHeightBox->clear();
        lHeightBox->insertItems(0, QStringList()
         << QApplication::translate("MPerfWidget", "Low", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium-low", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "Medium-high", Q_NULLPTR)
         << QApplication::translate("MPerfWidget", "High", Q_NULLPTR)
        );
#ifndef QT_NO_TOOLTIP
        eBox2->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox2->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton4->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton4->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton5->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton5->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton3->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton3->setText(QString());
        label_12->setText(QApplication::translate("MPerfWidget", "X Value:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox5->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox5->setText(QString());
        label_4->setText(QApplication::translate("MPerfWidget", "Y Value:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        iButton2->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton2->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButtonO->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButtonO->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton1->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton1->setText(QString());
#ifndef QT_NO_TOOLTIP
        iButton0->setToolTip(QApplication::translate("MPerfWidget", "Tip: alt+click to set all colors at once", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        iButton0->setText(QString());
        label_3->setText(QApplication::translate("MPerfWidget", "You can assign other DPIs in the Binding tab.", Q_NULLPTR));
        label_6->setText(QApplication::translate("MPerfWidget", "2:", Q_NULLPTR));
        label_7->setText(QApplication::translate("MPerfWidget", "3:", Q_NULLPTR));
        label_8->setText(QApplication::translate("MPerfWidget", "4:", Q_NULLPTR));
        label_5->setText(QApplication::translate("MPerfWidget", "1:", Q_NULLPTR));
        label_15->setText(QApplication::translate("MPerfWidget", "Other:", Q_NULLPTR));
        label_13->setText(QApplication::translate("MPerfWidget", "5:", Q_NULLPTR));
        label_14->setText(QApplication::translate("MPerfWidget", "Sniper:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox4->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
```

```
#endif // QT_NO_TOOLTIP
        eBox4->setText(QString());
        label_11->setText(QApplication::translate("MPerfWidget", "DPI Stage:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        eBox3->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox3->setText(QString());
#ifndef QT_NO_TOOLTIP
        eBox1->setToolTip(QApplication::translate("MPerfWidget", "Uncheck this box to skip the stage while moving up or down.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        eBox1->setText(QString());
        label_2->setText(QApplication::translate("MPerfWidget", "Movement", Q_NULLPTR));
        aSnapBox->setText(QApplication::translate("MPerfWidget", "Angle snap", Q_NULLPTR));
        indicBox->setText(QApplication::translate("MPerfWidget", "Use DPI indicator:", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        spinBox->setToolTip(QApplication::translate("MPerfWidget", "Indicator intensity", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        spinBox->setSuffix(QApplication::translate("MPerfWidget", "%", Q_NULLPTR));
        xyBox->setText(QApplication::translate("MPerfWidget", "Independent X/Y states", Q_NULLPTR));
        copyButton->setText(QApplication::translate("MPerfWidget", "Copy to mode...", Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.99.2.2 void Ui_MPerfWidget::setupUi (QWidget * *MPerfWidget*) [inline]

Definition at line 111 of file ui_mperfwidget.h.

References aSnapBox, copyButton, eBox1, eBox2, eBox3, eBox4, eBox5, gridLayout, horizontalLayout, horizontalLayout_2, horizontalLayout_4, horizontalSpacer, horizontalSpacer_2, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, horizontalSpacer_6, horizontalSpacer_7, iButton0, iButton1, iButton2, iButton3, iButton4, iButton5, iButtonO, indicBox, label, label_11, label_12, label_13, label_14, label_15, label_2, label_25, label_3, label_4, label_5, label_6, label_7, label_8, lHeightBox, line, line_2, line_3, retranslateUi(), spinBox, verticalLayout, verticalSpacer, verticalSpacer_2, verticalSpacer_3, xBox0, xBox1, xBox2, xBox3, xBox4, xBox5, xSlider0, xSlider1, xSlider2, xSlider3, xSlider4, xSlider5, xyBox, yBox0, yBox1, yBox2, yBox3, yBox4, yBox5, ySlider0, ySlider1, ySlider2, ySlider3, ySlider4, and ySlider5.

Referenced by MPerfWidget::MPerfWidget().

```
    {
        if (MPerfWidget->objectName().isEmpty())
            MPerfWidget->setObjectName(QStringLiteral("MPerfWidget"));
        MPerfWidget->resize(932, 637);
        verticalLayout = new QVBoxLayout(MPerfWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        label = new QLabel(MPerfWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        verticalLayout->addWidget(label);

        line = new QFrame(MPerfWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        verticalLayout->addWidget(line);

        gridLayout = new QGridLayout();
```

```
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        label_25 = new QLabel(MPerfWidget);
        label_25->setObjectName(QStringLiteral("label_25"));
        label_25->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout->addWidget(label_25, 16, 5, 1, 2);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        lHeightBox = new QComboBox(MPerfWidget);
        lHeightBox->setObjectName(QStringLiteral("lHeightBox"));

        horizontalLayout_2->addWidget(lHeightBox);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_2);


        gridLayout->addLayout(horizontalLayout_2, 16, 8, 1, 3);

        eBox2 = new QCheckBox(MPerfWidget);
        eBox2->setObjectName(QStringLiteral("eBox2"));

        gridLayout->addWidget(eBox2, 7, 1, 1, 1);

        ySlider3 = new QSlider(MPerfWidget);
        ySlider3->setObjectName(QStringLiteral("ySlider3"));
        ySlider3->setMinimum(0);
        ySlider3->setMaximum(1000);
        ySlider3->setSingleStep(10);
        ySlider3->setPageStep(50);
        ySlider3->setValue(0);
        ySlider3->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider3, 8, 8, 1, 1);

        xSlider2 = new QSlider(MPerfWidget);
        xSlider2->setObjectName(QStringLiteral("xSlider2"));
        xSlider2->setMinimum(0);
        xSlider2->setMaximum(1000);
        xSlider2->setSingleStep(10);
        xSlider2->setPageStep(50);
        xSlider2->setValue(0);
        xSlider2->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider2, 7, 5, 1, 1);

        xBox3 = new QSpinBox(MPerfWidget);
        xBox3->setObjectName(QStringLiteral("xBox3"));
        xBox3->setMinimum(100);
        xBox3->setMaximum(12000);
        xBox3->setSingleStep(50);

        gridLayout->addWidget(xBox3, 8, 6, 1, 1);

        yBox0 = new QSpinBox(MPerfWidget);
        yBox0->setObjectName(QStringLiteral("yBox0"));
        yBox0->setMinimum(100);
        yBox0->setMaximum(12000);
        yBox0->setSingleStep(50);

        gridLayout->addWidget(yBox0, 11, 9, 1, 1);

        ySlider0 = new QSlider(MPerfWidget);
        ySlider0->setObjectName(QStringLiteral("ySlider0"));
        ySlider0->setMinimum(0);
        ySlider0->setMaximum(1000);
        ySlider0->setSingleStep(10);
        ySlider0->setPageStep(50);
        ySlider0->setValue(0);
        ySlider0->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider0, 11, 8, 1, 1);

        iButton4 = new ColorButton(MPerfWidget);
        iButton4->setObjectName(QStringLiteral("iButton4"));
        QSizePolicy sizePolicy(QSizePolicy::Fixed, QSizePolicy::Fixed);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(iButton4->sizePolicy().hasHeightForWidth());
        iButton4->setSizePolicy(sizePolicy);
        iButton4->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton4, 9, 2, 1, 1);

```

```
        iButton5 = new ColorButton(MPerfWidget);
        iButton5->setObjectName(QStringLiteral("iButton5"));
        sizePolicy.setHeightForWidth(iButton5->sizePolicy().hasHeightForWidth());
        iButton5->setSizePolicy(sizePolicy);
        iButton5->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton5, 10, 2, 1, 1);

        horizontalSpacer_4 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_4, 4, 4, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 15, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_3, 3, 2, 1, 1);

        horizontalSpacer_5 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_5, 4, 7, 1, 1);

        iButton3 = new ColorButton(MPerfWidget);
        iButton3->setObjectName(QStringLiteral("iButton3"));
        sizePolicy.setHeightForWidth(iButton3->sizePolicy().hasHeightForWidth());
        iButton3->setSizePolicy(sizePolicy);
        iButton3->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton3, 8, 2, 1, 1);

        label_12 = new QLabel(MPerfWidget);
        label_12->setObjectName(QStringLiteral("label_12"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(label_12->sizePolicy().hasHeightForWidth());
        label_12->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(label_12, 4, 5, 1, 1);

        xBox4 = new QSpinBox(MPerfWidget);
        xBox4->setObjectName(QStringLiteral("xBox4"));
        xBox4->setMinimum(100);
        xBox4->setMaximum(12000);
        xBox4->setSingleStep(50);

        gridLayout->addWidget(xBox4, 9, 6, 1, 1);

        xBox0 = new QSpinBox(MPerfWidget);
        xBox0->setObjectName(QStringLiteral("xBox0"));
        xBox0->setMinimum(100);
        xBox0->setMaximum(12000);
        xBox0->setSingleStep(50);

        gridLayout->addWidget(xBox0, 11, 6, 1, 1);

        yBox5 = new QSpinBox(MPerfWidget);
        yBox5->setObjectName(QStringLiteral("yBox5"));
        yBox5->setMinimum(100);
        yBox5->setMaximum(12000);
        yBox5->setSingleStep(50);

        gridLayout->addWidget(yBox5, 10, 9, 1, 1);

        eBox5 = new QCheckBox(MPerfWidget);
        eBox5->setObjectName(QStringLiteral("eBox5"));

        gridLayout->addWidget(eBox5, 10, 1, 1, 1);

        xSlider5 = new QSlider(MPerfWidget);
        xSlider5->setObjectName(QStringLiteral("xSlider5"));
        xSlider5->setMinimum(0);
        xSlider5->setMaximum(1000);
        xSlider5->setSingleStep(10);
        xSlider5->setPageStep(50);
        xSlider5->setValue(0);
        xSlider5->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider5, 10, 5, 1, 1);

        xBox1 = new QSpinBox(MPerfWidget);
        xBox1->setObjectName(QStringLiteral("xBox1"));
        sizePolicy.setHeightForWidth(xBox1->sizePolicy().hasHeightForWidth());
        xBox1->setSizePolicy(sizePolicy);
        xBox1->setMinimum(100);
        xBox1->setMaximum(12000);
```

```
        xBox1->setSingleStep(50);

        gridLayout->addWidget(xBox1, 6, 6, 1, 1);

        yBox2 = new QSpinBox(MPerfWidget);
        yBox2->setObjectName(QStringLiteral("yBox2"));
        yBox2->setMinimum(100);
        yBox2->setMaximum(12000);
        yBox2->setSingleStep(50);

        gridLayout->addWidget(yBox2, 7, 9, 1, 1);

        yBox3 = new QSpinBox(MPerfWidget);
        yBox3->setObjectName(QStringLiteral("yBox3"));
        yBox3->setMinimum(100);
        yBox3->setMaximum(12000);
        yBox3->setSingleStep(50);

        gridLayout->addWidget(yBox3, 8, 9, 1, 1);

        xSlider4 = new QSlider(MPerfWidget);
        xSlider4->setObjectName(QStringLiteral("xSlider4"));
        xSlider4->setMinimum(0);
        xSlider4->setMaximum(1000);
        xSlider4->setSingleStep(10);
        xSlider4->setPageStep(50);
        xSlider4->setValue(0);
        xSlider4->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider4, 9, 5, 1, 1);

        label_4 = new QLabel(MPerfWidget);
        label_4->setObjectName(QStringLiteral("label_4"));
        sizePolicy1.setHeightForWidth(label_4->sizePolicy().hasHeightForWidth());
        label_4->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(label_4, 4, 8, 1, 1);

        xSlider0 = new QSlider(MPerfWidget);
        xSlider0->setObjectName(QStringLiteral("xSlider0"));
        xSlider0->setMinimum(0);
        xSlider0->setMaximum(1000);
        xSlider0->setSingleStep(10);
        xSlider0->setPageStep(50);
        xSlider0->setValue(0);
        xSlider0->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider0, 11, 5, 1, 1);

        iButton2 = new ColorButton(MPerfWidget);
        iButton2->setObjectName(QStringLiteral("iButton2"));
        sizePolicy.setHeightForWidth(iButton2->sizePolicy().hasHeightForWidth());
        iButton2->setSizePolicy(sizePolicy);
        iButton2->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton2, 7, 2, 1, 1);

        line_3 = new QFrame(MPerfWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 5, 0, 1, 11);

        iButton0 = new ColorButton(MPerfWidget);
        iButton0->setObjectName(QStringLiteral("iButton0"));
        sizePolicy.setHeightForWidth(iButton0->sizePolicy().hasHeightForWidth());
        iButton0->setSizePolicy(sizePolicy);
        iButton0->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton0, 12, 2, 1, 1);

        yBox1 = new QSpinBox(MPerfWidget);
        yBox1->setObjectName(QStringLiteral("yBox1"));
        sizePolicy.setHeightForWidth(yBox1->sizePolicy().hasHeightForWidth());
        yBox1->setSizePolicy(sizePolicy);
        yBox1->setMinimum(100);
        yBox1->setMaximum(12000);
        yBox1->setSingleStep(50);

        gridLayout->addWidget(yBox1, 6, 9, 1, 1);

        ySlider2 = new QSlider(MPerfWidget);
        ySlider2->setObjectName(QStringLiteral("ySlider2"));
        ySlider2->setMinimum(0);
        ySlider2->setMaximum(1000);
        ySlider2->setSingleStep(10);
```

```
        ySlider2->setPageStep(50);
        ySlider2->setValue(0);
        ySlider2->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider2, 7, 8, 1, 1);

        xBox2 = new QSpinBox(MPerfWidget);
        xBox2->setObjectName(QStringLiteral("xBox2"));
        xBox2->setMinimum(100);
        xBox2->setMaximum(12000);
        xBox2->setSingleStep(50);

        gridLayout->addWidget(xBox2, 7, 6, 1, 1);

        xSlider1 = new QSlider(MPerfWidget);
        xSlider1->setObjectName(QStringLiteral("xSlider1"));
        QSizePolicy sizePolicy2(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(xSlider1->sizePolicy().hasHeightForWidth());
        xSlider1->setSizePolicy(sizePolicy2);
        xSlider1->setMinimum(0);
        xSlider1->setMaximum(1000);
        xSlider1->setSingleStep(10);
        xSlider1->setPageStep(50);
        xSlider1->setValue(0);
        xSlider1->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider1, 6, 5, 1, 1);

        horizontalSpacer = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer, 0, 0, 1, 1);

        yBox4 = new QSpinBox(MPerfWidget);
        yBox4->setObjectName(QStringLiteral("yBox4"));
        yBox4->setMinimum(100);
        yBox4->setMaximum(12000);
        yBox4->setSingleStep(50);

        gridLayout->addWidget(yBox4, 9, 9, 1, 1);

        iButton1 = new ColorButton(MPerfWidget);
        iButton1->setObjectName(QStringLiteral("iButton1"));
        sizePolicy.setHeightForWidth(iButton1->sizePolicy().hasHeightForWidth());
        iButton1->setSizePolicy(sizePolicy);
        iButton1->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton1, 6, 2, 1, 1);

        ySlider4 = new QSlider(MPerfWidget);
        ySlider4->setObjectName(QStringLiteral("ySlider4"));
        ySlider4->setMinimum(0);
        ySlider4->setMaximum(1000);
        ySlider4->setSingleStep(10);
        ySlider4->setPageStep(50);
        ySlider4->setValue(0);
        ySlider4->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider4, 9, 8, 1, 1);

        ySlider1 = new QSlider(MPerfWidget);
        ySlider1->setObjectName(QStringLiteral("ySlider1"));
        ySlider1->setMinimum(0);
        ySlider1->setMaximum(1000);
        ySlider1->setSingleStep(10);
        ySlider1->setPageStep(50);
        ySlider1->setValue(0);
        ySlider1->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider1, 6, 8, 1, 1);

        iButton0 = new ColorButton(MPerfWidget);
        iButton0->setObjectName(QStringLiteral("iButton0"));
        sizePolicy.setHeightForWidth(iButton0->sizePolicy().hasHeightForWidth());
        iButton0->setSizePolicy(sizePolicy);
        iButton0->setMinimumSize(QSize(0, 40));

        gridLayout->addWidget(iButton0, 11, 2, 1, 1);

        xSlider3 = new QSlider(MPerfWidget);
        xSlider3->setObjectName(QStringLiteral("xSlider3"));
        xSlider3->setMinimum(0);
        xSlider3->setMaximum(1000);
        xSlider3->setSingleStep(10);
        xSlider3->setPageStep(50);
```

```
        xSlider3->setValue(0);
        xSlider3->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(xSlider3, 8, 5, 1, 1);

        xBox5 = new QSpinBox(MPerfWidget);
        xBox5->setObjectName(QStringLiteral("xBox5"));
        xBox5->setMinimum(100);
        xBox5->setMaximum(12000);
        xBox5->setSingleStep(50);

        gridLayout->addWidget(xBox5, 10, 6, 1, 1);

        label_3 = new QLabel(MPerfWidget);
        label_3->setObjectName(QStringLiteral("label_3"));

        gridLayout->addWidget(label_3, 12, 5, 1, 5);

        label_6 = new QLabel(MPerfWidget);
        label_6->setObjectName(QStringLiteral("label_6"));

        gridLayout->addWidget(label_6, 7, 3, 1, 1);

        ySlider5 = new QSlider(MPerfWidget);
        ySlider5->setObjectName(QStringLiteral("ySlider5"));
        ySlider5->setMinimum(0);
        ySlider5->setMaximum(1000);
        ySlider5->setSingleStep(10);
        ySlider5->setPageStep(50);
        ySlider5->setValue(0);
        ySlider5->setOrientation(Qt::Horizontal);

        gridLayout->addWidget(ySlider5, 10, 8, 1, 1);

        label_7 = new QLabel(MPerfWidget);
        label_7->setObjectName(QStringLiteral("label_7"));

        gridLayout->addWidget(label_7, 8, 3, 1, 1);

        label_8 = new QLabel(MPerfWidget);
        label_8->setObjectName(QStringLiteral("label_8"));

        gridLayout->addWidget(label_8, 9, 3, 1, 1);

        label_5 = new QLabel(MPerfWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

        gridLayout->addWidget(label_5, 6, 3, 1, 1);

        label_15 = new QLabel(MPerfWidget);
        label_15->setObjectName(QStringLiteral("label_15"));

        gridLayout->addWidget(label_15, 12, 3, 1, 1);

        label_13 = new QLabel(MPerfWidget);
        label_13->setObjectName(QStringLiteral("label_13"));

        gridLayout->addWidget(label_13, 10, 3, 1, 1);

        label_14 = new QLabel(MPerfWidget);
        label_14->setObjectName(QStringLiteral("label_14"));

        gridLayout->addWidget(label_14, 11, 3, 1, 1);

        eBox4 = new QCheckBox(MPerfWidget);
        eBox4->setObjectName(QStringLiteral("eBox4"));

        gridLayout->addWidget(eBox4, 9, 1, 1, 1);

        label_11 = new QLabel(MPerfWidget);
        label_11->setObjectName(QStringLiteral("label_11"));

        gridLayout->addWidget(label_11, 4, 2, 1, 2);

        eBox3 = new QCheckBox(MPerfWidget);
        eBox3->setObjectName(QStringLiteral("eBox3"));

        gridLayout->addWidget(eBox3, 8, 1, 1, 1);

        eBox1 = new QCheckBox(MPerfWidget);
        eBox1->setObjectName(QStringLiteral("eBox1"));

        gridLayout->addWidget(eBox1, 6, 1, 1, 1);

        label_2 = new QLabel(MPerfWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setFont(font);
```

```

        gridLayout->addWidget(label_2, 14, 0, 1, 10);

        verticalSpacer = new QSpacerItem(20, 30, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer, 13, 2, 1, 1);

        aSnapBox = new QCheckBox(MPerfWidget);
        aSnapBox->setObjectName(QStringLiteral("aSnapBox"));

        gridLayout->addWidget(aSnapBox, 16, 1, 1, 4);

        line_2 = new QFrame(MPerfWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 15, 0, 1, 10);

        horizontalLayout_4 = new QHBoxLayout();
        horizontalLayout_4->setObjectName(QStringLiteral("horizontalLayout_4"));
        indicBox = new QCheckBox(MPerfWidget);
        indicBox->setObjectName(QStringLiteral("indicBox"));

        horizontalLayout_4->addWidget(indicBox);

        horizontalSpacer_3 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        horizontalLayout_4->addItem(horizontalSpacer_3);

        spinBox = new QSpinBox(MPerfWidget);
        spinBox->setObjectName(QStringLiteral("spinBox"));
        spinBox->setMaximum(100);
        spinBox->setValue(100);

        horizontalLayout_4->addWidget(spinBox);

        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout_4->addItem(horizontalSpacer_7);


        gridLayout->addLayout(horizontalLayout_4, 0, 1, 1, 9);

        xyBox = new QCheckBox(MPerfWidget);
        xyBox->setObjectName(QStringLiteral("xyBox"));

        gridLayout->addWidget(xyBox, 2, 1, 1, 9);


        verticalLayout->addLayout(gridLayout);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        verticalLayout->addItem(verticalSpacer_2);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        copyButton = new QPushButton(MPerfWidget);
        copyButton->setObjectName(QStringLiteral("copyButton"));

        horizontalLayout->addWidget(copyButton);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_6);


        verticalLayout->addLayout(horizontalLayout);


        retranslateUi(MPerfWidget);

        QMetaObject::connectSlotsByName(MPerfWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.99.3 Field Documentation

12.99.3.1 QCheckBox∗ Ui_MPerfWidget::aSnapBox

Definition at line 98 of file ui_mperfwidget.h.

Referenced by retranslateUi(), MPerfWidget::setPerf(), and setupUi().

12.99.3.2 QPushButton∗ Ui_MPerfWidget::copyButton

Definition at line 108 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.3 QCheckBox∗ Ui_MPerfWidget::eBox1

Definition at line 95 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.4 QCheckBox∗ Ui_MPerfWidget::eBox2

Definition at line 44 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.5 QCheckBox∗ Ui_MPerfWidget::eBox3

Definition at line 94 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.6 QCheckBox* Ui_MPerfWidget::eBox4

Definition at line 92 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.7 QCheckBox* Ui_MPerfWidget::eBox5

Definition at line 60 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.8 QGridLayout* Ui_MPerfWidget::gridLayout

Definition at line 39 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.9 QHBoxLayout* Ui_MPerfWidget::horizontalLayout

Definition at line 107 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.10 QHBoxLayout* Ui_MPerfWidget::horizontalLayout_2

Definition at line 41 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.11 QHBoxLayout* Ui_MPerfWidget::horizontalLayout_4

Definition at line 100 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.12 QSpacerItem* Ui_MPerfWidget::horizontalSpacer

Definition at line 75 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.13 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_2

Definition at line 43 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.14 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_3

Definition at line 102 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.15 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_4

Definition at line 52 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.16 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_5

Definition at line 54 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.17 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_6

Definition at line 109 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.18 QSpacerItem* Ui_MPerfWidget::horizontalSpacer_7

Definition at line 104 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.19 ColorButton* Ui_MPerfWidget::iButton0

Definition at line 80 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.20 ColorButton* Ui_MPerfWidget::iButton1

Definition at line 77 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.21 ColorButton* Ui_MPerfWidget::iButton2

Definition at line 68 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.22 ColorButton* Ui_MPerfWidget::iButton3

Definition at line 55 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.23 ColorButton* Ui_MPerfWidget::iButton4

Definition at line 50 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.24 ColorButton* Ui_MPerfWidget::iButton5

Definition at line 51 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), and setupUi().

12.99.3.25 ColorButton* Ui_MPerfWidget::iButtonO

Definition at line 70 of file ui_mperfwidget.h.

Referenced by MPerfWidget::colorChanged(), MPerfWidget::MPerfWidget(), retranslateUi(), MPerfWidget::setPerf(), and setupUi().

12.99.3.26 QCheckBox* Ui_MPerfWidget::indicBox

Definition at line 101 of file ui_mperfwidget.h.

Referenced by retranslateUi(), MPerfWidget::setPerf(), and setupUi().

12.99.3.27 QLabel* Ui_MPerfWidget::label

Definition at line 37 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.28 QLabel* Ui_MPerfWidget::label_11

Definition at line 93 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.29 QLabel* Ui_MPerfWidget::label_12

Definition at line 56 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.30 QLabel* Ui_MPerfWidget::label_13

Definition at line 90 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.31 QLabel* Ui_MPerfWidget::label_14

Definition at line 91 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.32 QLabel* Ui_MPerfWidget::label_15

Definition at line 89 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.33 QLabel* Ui_MPerfWidget::label_2

Definition at line 96 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.34 QLabel* Ui_MPerfWidget::label_25

Definition at line 40 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.35 QLabel* Ui_MPerfWidget::label_3

Definition at line 83 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.36 QLabel* Ui_MPerfWidget::label_4

Definition at line 66 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.37 QLabel* Ui_MPerfWidget::label_5

Definition at line 88 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.38 QLabel* Ui_MPerfWidget::label_6

Definition at line 84 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.39 QLabel* Ui_MPerfWidget::label_7

Definition at line 86 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.40 QLabel* Ui_MPerfWidget::label_8

Definition at line 87 of file ui_mperfwidget.h.

Referenced by retranslateUi(), and setupUi().

12.99.3.41 QComboBox* Ui_MPerfWidget::lHeightBox

Definition at line 42 of file ui_mperfwidget.h.

Referenced by retranslateUi(), MPerfWidget::setPerf(), and setupUi().

12.99.3.42 QFrame* Ui_MPerfWidget::line

Definition at line 38 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.43 QFrame* Ui_MPerfWidget::line_2

Definition at line 99 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.44 QFrame* Ui_MPerfWidget::line_3

Definition at line 69 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.45 QSpinBox* Ui_MPerfWidget::spinBox

Definition at line 103 of file ui_mperfwidget.h.

Referenced by retranslateUi(), MPerfWidget::setPerf(), and setupUi().

12.99.3.46 QVBoxLayout* Ui_MPerfWidget::verticalLayout

Definition at line 36 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.47 QSpacerItem* Ui_MPerfWidget::verticalSpacer

Definition at line 97 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.48 QSpacerItem* Ui_MPerfWidget::verticalSpacer_2

Definition at line 106 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.49 QSpacerItem* Ui_MPerfWidget::verticalSpacer_3

Definition at line 53 of file ui_mperfwidget.h.

Referenced by setupUi().

12.99.3.50 QSpinBox* Ui_MPerfWidget::xBox0

Definition at line 58 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.51 QSpinBox* Ui_MPerfWidget::xBox1

Definition at line 62 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.52 QSpinBox* Ui_MPerfWidget::xBox2

Definition at line 73 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.53 QSpinBox* Ui_MPerfWidget::xBox3

Definition at line 47 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.54 QSpinBox* Ui_MPerfWidget::xBox4

Definition at line 57 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.55 QSpinBox* Ui_MPerfWidget::xBox5

Definition at line 82 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.56 QSlider* Ui_MPerfWidget::xSlider0

Definition at line 67 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.57 QSlider* Ui_MPerfWidget::xSlider1

Definition at line 74 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.58 QSlider* Ui_MPerfWidget::xSlider2

Definition at line 46 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.59 QSlider* Ui_MPerfWidget::xSlider3

Definition at line 81 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.60 QSlider* Ui_MPerfWidget::xSlider4

Definition at line 65 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.61 QSlider* Ui_MPerfWidget::xSlider5

Definition at line 61 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.62 QCheckBox* Ui_MPerfWidget::xyBox

Definition at line 105 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), retranslateUi(), setupUi(), and MPerfWidget::sliderYMoved().

12.99.3.63 QSpinBox* Ui_MPerfWidget::yBox0

Definition at line 48 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.64 QSpinBox* Ui_MPerfWidget::yBox1

Definition at line 71 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.65 QSpinBox* Ui_MPerfWidget::yBox2

Definition at line 63 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.66 QSpinBox* Ui_MPerfWidget::yBox3

Definition at line 64 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.67 QSpinBox* Ui_MPerfWidget::yBox4

Definition at line 76 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.68 QSpinBox* Ui_MPerfWidget::yBox5

Definition at line 59 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.69 QSlider* Ui_MPerfWidget::ySlider0

Definition at line 49 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.70 QSlider* Ui_MPerfWidget::ySlider1

Definition at line 79 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.71 QSlider* Ui_MPerfWidget::ySlider2

Definition at line 72 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.72 QSlider* Ui_MPerfWidget::ySlider3

Definition at line 45 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.73 QSlider* Ui_MPerfWidget::ySlider4

Definition at line 78 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

12.99.3.74 QSlider* Ui_MPerfWidget::ySlider5

Definition at line 85 of file ui_mperfwidget.h.

Referenced by MPerfWidget::MPerfWidget(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_mperfwidget.h

12.100 Ui_RebindWidget Class Reference

```
#include <src/ckb/ui_rebindwidget.h>
```

Inheritance diagram for Ui_RebindWidget:

Collaboration diagram for Ui_RebindWidget:

Public Member Functions

- void setupUi (QWidget *RebindWidget)
- void retranslateUi (QWidget *RebindWidget)

Data Fields

- QVBoxLayout * verticalLayout
- QTabWidget * tabWidget
- QWidget * keyTab

- QGridLayout * gridLayout_2
- QComboBox * numBox
- QComboBox * typingBox
- QComboBox * fnBox
- QSpacerItem * verticalSpacer_10
- QSpacerItem * verticalSpacer_3
- QSpacerItem * horizontalSpacer_2
- QRadioButton * typingButton
- QComboBox * modBox
- QSpacerItem * horizontalSpacer_3
- QRadioButton * mediaButton
- QSpacerItem * verticalSpacer_4
- QSpacerItem * horizontalSpacer_9
- QSpacerItem * horizontalSpacer_4
- QRadioButton * modButton
- QRadioButton * fnButton
- QComboBox * mediaBox
- QRadioButton * numButton
- QSpacerItem * horizontalSpacer_17
- QWidget * mouseTab
- QGridLayout * gridLayout
- QRadioButton * dpiButton
- QSpacerItem * verticalSpacer_2
- QSpacerItem * verticalSpacer_8
- QSpacerItem * horizontalSpacer_18
- QSpacerItem * horizontalSpacer_20
- QComboBox * mb2Box
- QComboBox * dpiBox
- QSpinBox * dpiCustYBox
- QComboBox * mbBox
- QComboBox * wheelBox
- QRadioButton * mbButton
- QSpinBox * dpiCustXBox
- QLabel * dpiWarning
- QRadioButton * wheelButton
- QSpacerItem * horizontalSpacer_22
- QRadioButton * mb2Button
- QLabel * dpiCustLabel
- QSpacerItem * horizontalSpacer_19
- QSpacerItem * horizontalSpacer_21
- QWidget * animTab
- QGridLayout * gridLayout_5
- QSpacerItem * verticalSpacer_11
- QComboBox * animBox
- QSpacerItem * horizontalSpacer_24
- QSpacerItem * horizontalSpacer_25
- QCheckBox * animKrBox
- QCheckBox * animOnceBox
- QSpacerItem * horizontalSpacer_26
- QRadioButton * animButton
- QSpacerItem * horizontalSpacer_23
- QWidget * actionTab
- QGridLayout * gridLayout_3
- QSpacerItem * horizontalSpacer_5
- QRadioButton * modeButton

- QCheckBox * modeWrapBox
- QCheckBox * lightWrapBox
- QSpacerItem * verticalSpacer_7
- QSpacerItem * verticalSpacer_6
- QRadioButton * lockButton
- QSpacerItem * verticalSpacer_5
- QComboBox * lightBox
- QComboBox * lockBox
- QRadioButton * lightButton
- QComboBox * modeBox
- QSpacerItem * horizontalSpacer_8
- QSpacerItem * horizontalSpacer_10
- QSpacerItem * horizontalSpacer_7
- QSpacerItem * horizontalSpacer_6
- QWidget * programTab
- QGridLayout * gridLayout_4
- QSpacerItem * verticalSpacer
- QSpacerItem * horizontalSpacer
- QCheckBox * programKpButton
- QLineEdit * programKpBox
- QSpacerItem * horizontalSpacer_11
- QSpacerItem * horizontalSpacer_13
- QLineEdit * programKrBox
- QCheckBox * programKrButton
- QSpacerItem * horizontalSpacer_12
- QWidget * programKpExtra
- QHBoxLayout * horizontalLayout_2
- QCheckBox * programKpSIBox
- QComboBox * programKpModeBox
- QSpacerItem * horizontalSpacer_15
- QWidget * programKrExtra
- QHBoxLayout * horizontalLayout_3
- QCheckBox * programKrSIBox
- QComboBox * programKrModeBox
- QSpacerItem * horizontalSpacer_16
- QLabel * progTipLabel
- QWidget * macroTab
- QWidget * layoutWidget1
- QGridLayout * gridLayout_8
- QGroupBox * groupBox_2
- QPlainTextEdit * pteMacroBox
- QPlainTextEdit * pteMacroComment
- QPlainTextEdit * pteMacroText
- QWidget * layoutWidget
- QVBoxLayout * verticalLayout_2
- QGroupBox * groupBox_3
- QGroupBox * groupBox_4
- QWidget * layoutWidget_2
- QGridLayout * gridLayout_10
- QGroupBox * groupBox
- QPushButton * btnStopMacro
- QPushButton * btnStartMacro
- QPushButton * btnClearMacro
- QLabel * lbl_macro
- QHBoxLayout * horizontalLayout

- QSpacerItem * horizontalSpacer_14
- QPushButton * unbindButton
- QPushButton * resetButton
- QPushButton * cancelButton
- QPushButton * applyButton

12.100.1 Detailed Description

Definition at line 35 of file ui_rebindwidget.h.

12.100.2 Member Function Documentation

12.100.2.1 void Ui_RebindWidget::retranslateUi (QWidget * *RebindWidget*) [inline]

Definition at line 825 of file ui_rebindwidget.h.

References actionTab, animBox, animButton, animKrBox, animOnceBox, animTab, applyButton, btnClearMacro, btnStartMacro, btnStopMacro, cancelButton, dpiBox, dpiButton, dpiCustLabel, dpiWarning, fnBox, fnButton, groupBox, groupBox_2, groupBox_3, groupBox_4, keyTab, lbl_macro, lightBox, lightButton, lightWrapBox, lockBox, lockButton, macroTab, mb2Box, mb2Button, mbBox, mbButton, mediaBox, mediaButton, modBox, modButton, modeBox, modeButton, modeWrapBox, mouseTab, numBox, numButton, programKpButton, programKpModeBox, programKpSIBox, programKrButton, programKrModeBox, programKrSIBox, programTab, progTipLabel, pteMacroComment, pteMacroText, resetButton, tabWidget, typingBox, typingButton, unbindButton, wheelBox, and wheelButton.

Referenced by setupUi().

```
    {
        numBox->clear();
        numBox->insertItems(0, QStringList()
         << QString()
        );
        typingBox->clear();
        typingBox->insertItems(0, QStringList()
         << QString()
        );
        fnBox->clear();
        fnBox->insertItems(0, QStringList()
         << QString()
        );
        typingButton->setText(QApplication::translate("RebindWidget", "Typing:", Q_NULLPTR));
        modBox->clear();
        modBox->insertItems(0, QStringList()
         << QString()
        );
        mediaButton->setText(QApplication::translate("RebindWidget", "Media:", Q_NULLPTR));
        modButton->setText(QApplication::translate("RebindWidget", "Modifier:", Q_NULLPTR));
        fnButton->setText(QApplication::translate("RebindWidget", "Miscellaneous:", Q_NULLPTR));
        mediaBox->clear();
        mediaBox->insertItems(0, QStringList()
         << QString()
        );
        numButton->setText(QApplication::translate("RebindWidget", "Number pad:", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(keyTab), QApplication::translate("
    RebindWidget", "Keyboard", Q_NULLPTR));
        dpiButton->setText(QApplication::translate("RebindWidget", "Change DPI:", Q_NULLPTR));
        mb2Box->clear();
        mb2Box->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "4 (Back)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "5 (Forward)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "6", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "7", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "8", Q_NULLPTR)
        );
        dpiBox->clear();
        dpiBox->insertItems(0, QStringList()
         << QString()
         << QApplication::translate("RebindWidget", "(Up)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "(Down)", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "Sniper", Q_NULLPTR)
         << QApplication::translate("RebindWidget", "1:", Q_NULLPTR)
```

```
        << QApplication::translate("RebindWidget", "2:", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "3:", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "4:", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "5:", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Custom:", Q_NULLPTR)
      );
      mbBox->clear();
      mbBox->insertItems(0, QStringList()
        << QString()
        << QApplication::translate("RebindWidget", "Left", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Right", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Middle", Q_NULLPTR)
      );
      wheelBox->clear();
      wheelBox->insertItems(0, QStringList()
        << QString()
        << QApplication::translate("RebindWidget", "Up", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Down", Q_NULLPTR)
      );
      mbButton->setText(QApplication::translate("RebindWidget", "Standard button:", Q_NULLPTR));
      dpiWarning->setText(QApplication::translate("RebindWidget", "DPI is only available for mice.", Q_NULLPTR));
      wheelButton->setText(QApplication::translate("RebindWidget", "Wheel:", Q_NULLPTR));
      mb2Button->setText(QApplication::translate("RebindWidget", "Special button:", Q_NULLPTR));
      dpiCustLabel->setText(QApplication::translate("RebindWidget", "x", Q_NULLPTR));
      tabWidget->setTabText(tabWidget->indexOf(mouseTab), QApplication::translate("RebindWidget", "Mouse", Q_NULLPTR));
      animBox->clear();
      animBox->insertItems(0, QStringList()
        << QString()
      );
      animKrBox->setText(QApplication::translate("RebindWidget", "Stop on key release", Q_NULLPTR));
      animOnceBox->setText(QApplication::translate("RebindWidget", "Restart every time", Q_NULLPTR));
      animButton->setText(QApplication::translate("RebindWidget", "Start animation on keypress:", Q_NULLPTR));
      tabWidget->setTabText(tabWidget->indexOf(animTab), QApplication::translate("RebindWidget", "Animation", Q_NULLPTR));
      modeButton->setText(QApplication::translate("RebindWidget", "Switch to mode:", Q_NULLPTR));
      modeWrapBox->setText(QApplication::translate("RebindWidget", "Wrap-around", Q_NULLPTR));
      lightWrapBox->setText(QApplication::translate("RebindWidget", "Wrap-around", Q_NULLPTR));
      lockButton->setText(QApplication::translate("RebindWidget", "Windows lock:", Q_NULLPTR));
      lightBox->clear();
      lightBox->insertItems(0, QStringList()
        << QString()
        << QApplication::translate("RebindWidget", "Up", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Down", Q_NULLPTR)
      );
      lockBox->clear();
      lockBox->insertItems(0, QStringList()
        << QString()
        << QApplication::translate("RebindWidget", "Toggle", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "On", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Off", Q_NULLPTR)
      );
      lightButton->setText(QApplication::translate("RebindWidget", "Brightness:", Q_NULLPTR));
      modeBox->clear();
      modeBox->insertItems(0, QStringList()
        << QString()
        << QApplication::translate("RebindWidget", "(Previous)", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "(Next)", Q_NULLPTR)
      );
      tabWidget->setTabText(tabWidget->indexOf(actionTab), QApplication::translate("RebindWidget", "Special", Q_NULLPTR));
      programKpButton->setText(QApplication::translate("RebindWidget", "Launch program on key press:", Q_NULLPTR));
      programKrButton->setText(QApplication::translate("RebindWidget", "Launch program on key release:", Q_NULLPTR));
      programKpSIBox->setText(QApplication::translate("RebindWidget", "Single instance", Q_NULLPTR));
      programKpModeBox->clear();
      programKpModeBox->insertItems(0, QStringList()
        << QApplication::translate("RebindWidget", "Run indefinitely", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Stop on release", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Stop on re-press", Q_NULLPTR)
      );
      programKrSIBox->setText(QApplication::translate("RebindWidget", "Single instance", Q_NULLPTR));
      programKrModeBox->clear();
      programKrModeBox->insertItems(0, QStringList()
        << QApplication::translate("RebindWidget", "Run indefinitely", Q_NULLPTR)
        << QApplication::translate("RebindWidget", "Stop on re-press", Q_NULLPTR)
      );
      progTipLabel->setText(QApplication::translate("RebindWidget", "Tip", Q_NULLPTR));
```

```
        tabWidget->setTabText(tabWidget->indexOf(programTab), QApplication::translate("RebindWidget", "Program", Q_NULLPTR));
        groupBox_2->setTitle(QApplication::translate("RebindWidget", "Macro Key Actions", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        pteMacroComment->setToolTip(QApplication::translate("RebindWidget", "What is this macro for?", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        pteMacroComment->setDocumentTitle(QString());
        pteMacroComment->setPlainText(QString());
        pteMacroText->setDocumentTitle(QString());
        pteMacroText->setPlainText(QString());
        groupBox_3->setTitle(QApplication::translate("RebindWidget", "Macro Comment", Q_NULLPTR));
        groupBox_4->setTitle(QApplication::translate("RebindWidget", "Macro Text", Q_NULLPTR));
        groupBox->setTitle(QApplication::translate("RebindWidget", "Macro recording", Q_NULLPTR));
        btnStopMacro->setText(QApplication::translate("RebindWidget", "Stop", Q_NULLPTR));
        btnStartMacro->setText(QApplication::translate("RebindWidget", "Start", Q_NULLPTR));
        btnClearMacro->setText(QApplication::translate("RebindWidget", "Clear", Q_NULLPTR));
        lbl_macro->setText(QApplication::translate("RebindWidget", "Comment label for help", Q_NULLPTR));
        tabWidget->setTabText(tabWidget->indexOf(macroTab), QApplication::translate("RebindWidget", "Macro", Q_NULLPTR));
        unbindButton->setText(QApplication::translate("RebindWidget", "Unbind", Q_NULLPTR));
        resetButton->setText(QApplication::translate("RebindWidget", "Reset to Default", Q_NULLPTR));
        cancelButton->setText(QApplication::translate("RebindWidget", "Cancel", Q_NULLPTR));
        applyButton->setText(QApplication::translate("RebindWidget", "Apply", Q_NULLPTR));
        Q_UNUSED(RebindWidget);
    } // retranslateUi
```

Here is the caller graph for this function:

12.100.2.2 void Ui_RebindWidget::setupUi (QWidget * *RebindWidget*) [inline]

Definition at line 157 of file ui_rebindwidget.h.

References actionTab, animBox, animButton, animKrBox, animOnceBox, animTab, applyButton, btnClearMacro, btnStartMacro, btnStopMacro, cancelButton, dpiBox, dpiButton, dpiCustLabel, dpiCustXBox, dpiCustYBox, dpiWarning, fnBox, fnButton, gridLayout, gridLayout_10, gridLayout_2, gridLayout_3, gridLayout_4, gridLayout_5, gridLayout_8, groupBox, groupBox_2, groupBox_3, groupBox_4, horizontalLayout, horizontalLayout_2, horizontalLayout_3, horizontalSpacer, horizontalSpacer_10, horizontalSpacer_11, horizontalSpacer_12, horizontalSpacer_13, horizontalSpacer_14, horizontalSpacer_15, horizontalSpacer_16, horizontalSpacer_17, horizontalSpacer_18, horizontalSpacer_19, horizontalSpacer_2, horizontalSpacer_20, horizontalSpacer_21, horizontalSpacer_22, horizontalSpacer_23, horizontalSpacer_24, horizontalSpacer_25, horizontalSpacer_26, horizontalSpacer_3, horizontalSpacer_4, horizontalSpacer_5, horizontalSpacer_6, horizontalSpacer_7, horizontalSpacer_8, horizontalSpacer_9, keyTab, layoutWidget, layoutWidget1, layoutWidget_2, lbl_macro, lightBox, lightButton, lightWrapBox, lockBox, lockButton, macroTab, mb2Box, mb2Button, mbBox, mbButton, mediaBox, mediaButton, modBox, modButton, modeBox, modeButton, modeWrapBox, mouseTab, numBox, numButton, programKpBox, programKpButton, programKpExtra, programKpModeBox, programKpSIBox, programKrBox, programKrButton, programKrExtra, programKrModeBox, programKrSIBox, programTab, progTipLabel, pteMacroBox, pteMacroComment, pteMacroText, resetButton, retranslateUi(), tabWidget, typingBox, typingButton, unbindButton, verticalLayout, verticalLayout_2, verticalSpacer, verticalSpacer_10, verticalSpacer_11, verticalSpacer_2, verticalSpacer_3, verticalSpacer_4, verticalSpacer_5, verticalSpacer_6, verticalSpacer_7, verticalSpacer_8, wheelBox, and wheelButton.

Referenced by RebindWidget::RebindWidget().

```
    {
        if (RebindWidget->objectName().isEmpty())
            RebindWidget->setObjectName(QStringLiteral("RebindWidget"));
        RebindWidget->resize(687, 342);
```

```
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(RebindWidget->sizePolicy().hasHeightForWidth());
        RebindWidget->setSizePolicy(sizePolicy);
        verticalLayout = new QVBoxLayout(RebindWidget);
        verticalLayout->setObjectName(QStringLiteral("verticalLayout"));
        tabWidget = new QTabWidget(RebindWidget);
        tabWidget->setObjectName(QStringLiteral("tabWidget"));
        keyTab = new QWidget();
        keyTab->setObjectName(QStringLiteral("keyTab"));
        sizePolicy.setHeightForWidth(keyTab->sizePolicy().hasHeightForWidth());
        keyTab->setSizePolicy(sizePolicy);
        gridLayout_2 = new QGridLayout(keyTab);
        gridLayout_2->setObjectName(QStringLiteral("gridLayout_2"));
        gridLayout_2->setContentsMargins(-1, -1, -1, 0);
        numBox = new QComboBox(keyTab);
        numBox->setObjectName(QStringLiteral("numBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(numBox->sizePolicy().hasHeightForWidth());
        numBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(numBox, 6, 4, 1, 1);

        typingBox = new QComboBox(keyTab);
        typingBox->setObjectName(QStringLiteral("typingBox"));
        sizePolicy1.setHeightForWidth(typingBox->sizePolicy().hasHeightForWidth());
        typingBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(typingBox, 1, 1, 1, 1);

        fnBox = new QComboBox(keyTab);
        fnBox->setObjectName(QStringLiteral("fnBox"));
        sizePolicy1.setHeightForWidth(fnBox->sizePolicy().hasHeightForWidth());
        fnBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(fnBox, 6, 1, 1, 1);

        verticalSpacer_10 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed
);

        gridLayout_2->addItem(verticalSpacer_10, 9, 1, 1, 1);

        verticalSpacer_3 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
QSizePolicy::Expanding);

        gridLayout_2->addItem(verticalSpacer_3, 15, 2, 1, 1);

        horizontalSpacer_2 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_2, 1, 3, 1, 1);

        typingButton = new QRadioButton(keyTab);
        typingButton->setObjectName(QStringLiteral("typingButton"));
        typingButton->setAutoExclusive(false);

        gridLayout_2->addWidget(typingButton, 0, 0, 1, 2);

        modBox = new QComboBox(keyTab);
        modBox->setObjectName(QStringLiteral("modBox"));
        sizePolicy1.setHeightForWidth(modBox->sizePolicy().hasHeightForWidth());
        modBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(modBox, 1, 4, 1, 1);

        horizontalSpacer_3 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_3, 1, 0, 1, 1);

        mediaButton = new QRadioButton(keyTab);
        mediaButton->setObjectName(QStringLiteral("mediaButton"));
        mediaButton->setAutoExclusive(false);

        gridLayout_2->addWidget(mediaButton, 10, 0, 1, 2);

        verticalSpacer_4 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed)
;

        gridLayout_2->addItem(verticalSpacer_4, 2, 1, 1, 1);

        horizontalSpacer_9 = new QSpacerItem(0, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

```

```
        gridLayout_2->addItem(horizontalSpacer_9, 1, 5, 1, 2);

        horizontalSpacer_4 = new QSpacerItem(0, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_4, 1, 2, 1, 1);

        modButton = new QRadioButton(keyTab);
        modButton->setObjectName(QStringLiteral("modButton"));

        gridLayout_2->addWidget(modButton, 0, 3, 1, 2);

        fnButton = new QRadioButton(keyTab);
        fnButton->setObjectName(QStringLiteral("fnButton"));
        fnButton->setAutoExclusive(false);

        gridLayout_2->addWidget(fnButton, 5, 0, 1, 2);

        mediaBox = new QComboBox(keyTab);
        mediaBox->setObjectName(QStringLiteral("mediaBox"));
        sizePolicy1.setHeightForWidth(mediaBox->sizePolicy().hasHeightForWidth());
        mediaBox->setSizePolicy(sizePolicy1);

        gridLayout_2->addWidget(mediaBox, 11, 1, 1, 1);

        numButton = new QRadioButton(keyTab);
        numButton->setObjectName(QStringLiteral("numButton"));
        numButton->setAutoExclusive(false);

        gridLayout_2->addWidget(numButton, 5, 3, 1, 2);

        horizontalSpacer_17 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_2->addItem(horizontalSpacer_17, 1, 7, 1, 1);

        tabWidget->addTab(keyTab, QString());
        mouseTab = new QWidget();
        mouseTab->setObjectName(QStringLiteral("mouseTab"));
        gridLayout = new QGridLayout(mouseTab);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        dpiButton = new QRadioButton(mouseTab);
        dpiButton->setObjectName(QStringLiteral("dpiButton"));
        dpiButton->setAutoExclusive(false);

        gridLayout->addWidget(dpiButton, 3, 3, 1, 5);

        verticalSpacer_2 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer_2, 5, 1, 1, 1);

        verticalSpacer_8 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 2, 1, 1, 1);

        horizontalSpacer_18 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_18, 1, 0, 1, 1);

        horizontalSpacer_20 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_20, 1, 3, 1, 1);

        mb2Box = new QComboBox(mouseTab);
        mb2Box->setObjectName(QStringLiteral("mb2Box"));
        sizePolicy1.setHeightForWidth(mb2Box->sizePolicy().hasHeightForWidth());
        mb2Box->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(mb2Box, 1, 4, 1, 4);

        dpiBox = new QComboBox(mouseTab);
        dpiBox->setObjectName(QStringLiteral("dpiBox"));

        gridLayout->addWidget(dpiBox, 4, 4, 1, 1);

        dpiCustYBox = new QSpinBox(mouseTab);
        dpiCustYBox->setObjectName(QStringLiteral("dpiCustYBox"));
        dpiCustYBox->setMinimum(400);
        dpiCustYBox->setMaximum(8500);
        dpiCustYBox->setSingleStep(50);

        gridLayout->addWidget(dpiCustYBox, 4, 7, 1, 1);

```

```
        mbBox = new QComboBox(mouseTab);
        mbBox->setObjectName(QStringLiteral("mbBox"));
        sizePolicy1.setHeightForWidth(mbBox->sizePolicy().hasHeightForWidth());
        mbBox->setSizePolicy(sizePolicy1);

        gridLayout->addWidget(mbBox, 1, 1, 1, 1);

        wheelBox = new QComboBox(mouseTab);
        wheelBox->setObjectName(QStringLiteral("wheelBox"));

        gridLayout->addWidget(wheelBox, 4, 1, 1, 1);

        mbButton = new QRadioButton(mouseTab);
        mbButton->setObjectName(QStringLiteral("mbButton"));
        mbButton->setAutoExclusive(false);

        gridLayout->addWidget(mbButton, 0, 0, 1, 2);

        dpiCustXBox = new QSpinBox(mouseTab);
        dpiCustXBox->setObjectName(QStringLiteral("dpiCustXBox"));
        dpiCustXBox->setMinimum(400);
        dpiCustXBox->setMaximum(8500);
        dpiCustXBox->setSingleStep(50);

        gridLayout->addWidget(dpiCustXBox, 4, 5, 1, 1);

        dpiWarning = new QLabel(mouseTab);
        dpiWarning->setObjectName(QStringLiteral("dpiWarning"));
        QSizePolicy sizePolicy2(QSizePolicy::Preferred, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(dpiWarning->sizePolicy().hasHeightForWidth());
        dpiWarning->setSizePolicy(sizePolicy2);

        gridLayout->addWidget(dpiWarning, 6, 0, 1, 10);

        wheelButton = new QRadioButton(mouseTab);
        wheelButton->setObjectName(QStringLiteral("wheelButton"));

        gridLayout->addWidget(wheelButton, 3, 0, 1, 2);

        horizontalSpacer_22 = new QSpacerItem(5, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_22, 1, 8, 1, 1);

        mb2Button = new QRadioButton(mouseTab);
        mb2Button->setObjectName(QStringLiteral("mb2Button"));
        mb2Button->setAutoExclusive(false);

        gridLayout->addWidget(mb2Button, 0, 3, 1, 5);

        dpiCustLabel = new QLabel(mouseTab);
        dpiCustLabel->setObjectName(QStringLiteral("dpiCustLabel"));

        gridLayout->addWidget(dpiCustLabel, 4, 6, 1, 1);

        horizontalSpacer_19 = new QSpacerItem(0, 0, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_19, 1, 2, 1, 1);

        horizontalSpacer_21 = new QSpacerItem(0, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout->addItem(horizontalSpacer_21, 1, 9, 1, 1);

        tabWidget->addTab(mouseTab, QString());
        animTab = new QWidget();
        animTab->setObjectName(QStringLiteral("animTab"));
        gridLayout_5 = new QGridLayout(animTab);
        gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
        verticalSpacer_11 = new QSpacerItem(20, 40, QSizePolicy::Minimum,
    QSizePolicy::Expanding);

        gridLayout_5->addItem(verticalSpacer_11, 6, 2, 1, 1);

        animBox = new QComboBox(animTab);
        animBox->setObjectName(QStringLiteral("animBox"));
        sizePolicy1.setHeightForWidth(animBox->sizePolicy().hasHeightForWidth());
        animBox->setSizePolicy(sizePolicy1);

        gridLayout_5->addWidget(animBox, 4, 2, 1, 1);

        horizontalSpacer_24 = new QSpacerItem(20, 20, QSizePolicy::Fixed,
    QSizePolicy::Minimum);

```

```
        gridLayout_5->addItem(horizontalSpacer_24, 4, 3, 1, 1);

        horizontalSpacer_25 = new QSpacerItem(438, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_25, 4, 7, 1, 1);

        animKrBox = new QCheckBox(animTab);
        animKrBox->setObjectName(QStringLiteral("animKrBox"));

        gridLayout_5->addWidget(animKrBox, 4, 6, 1, 1);

        animOnceBox = new QCheckBox(animTab);
        animOnceBox->setObjectName(QStringLiteral("animOnceBox"));

        gridLayout_5->addWidget(animOnceBox, 4, 4, 1, 1);

        horizontalSpacer_26 = new QSpacerItem(20, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_26, 4, 5, 1, 1);

        animButton = new QRadioButton(animTab);
        animButton->setObjectName(QStringLiteral("animButton"));
        sizePolicy1.setHeightForWidth(animButton->sizePolicy().hasHeightForWidth());
        animButton->setSizePolicy(sizePolicy1);

        gridLayout_5->addWidget(animButton, 0, 1, 1, 2);

        horizontalSpacer_23 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_23, 4, 1, 1, 1);

        tabWidget->addTab(animTab, QString());
        actionTab = new QWidget();
        actionTab->setObjectName(QStringLiteral("actionTab"));
        sizePolicy.setHeightForWidth(actionTab->sizePolicy().hasHeightForWidth());
        actionTab->setSizePolicy(sizePolicy);
        gridLayout_3 = new QGridLayout(actionTab);
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        gridLayout_3->setContentsMargins(-1, -1, -1, 0);
        horizontalSpacer_5 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_5, 1, 0, 1, 1);

        modeButton = new QRadioButton(actionTab);
        modeButton->setObjectName(QStringLiteral("modeButton"));
        modeButton->setAutoExclusive(false);

        gridLayout_3->addWidget(modeButton, 0, 0, 1, 2);

        modeWrapBox = new QCheckBox(actionTab);
        modeWrapBox->setObjectName(QStringLiteral("modeWrapBox"));
        modeWrapBox->setChecked(true);

        gridLayout_3->addWidget(modeWrapBox, 1, 3, 1, 1);

        lightWrapBox = new QCheckBox(actionTab);
        lightWrapBox->setObjectName(QStringLiteral("lightWrapBox"));
        lightWrapBox->setChecked(true);

        gridLayout_3->addWidget(lightWrapBox, 4, 3, 1, 1);

        verticalSpacer_7 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_3->addItem(verticalSpacer_7, 2, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_3->addItem(verticalSpacer_6, 5, 1, 1, 1);

        lockButton = new QRadioButton(actionTab);
        lockButton->setObjectName(QStringLiteral("lockButton"));
        lockButton->setAutoExclusive(false);

        gridLayout_3->addWidget(lockButton, 6, 0, 1, 2);

        verticalSpacer_5 = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout_3->addItem(verticalSpacer_5, 8, 1, 1, 1);

        lightBox = new QComboBox(actionTab);
```

```
        lightBox->setObjectName(QStringLiteral("lightBox"));
        sizePolicy1.setHeightForWidth(lightBox->sizePolicy().hasHeightForWidth());
        lightBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(lightBox, 4, 1, 1, 1);

        lockBox = new QComboBox(actionTab);
        lockBox->setObjectName(QStringLiteral("lockBox"));
        sizePolicy1.setHeightForWidth(lockBox->sizePolicy().hasHeightForWidth());
        lockBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(lockBox, 7, 1, 1, 1);

        lightButton = new QRadioButton(actionTab);
        lightButton->setObjectName(QStringLiteral("lightButton"));
        lightButton->setAutoExclusive(false);

        gridLayout_3->addWidget(lightButton, 3, 0, 1, 2);

        modeBox = new QComboBox(actionTab);
        modeBox->setObjectName(QStringLiteral("modeBox"));
        sizePolicy1.setHeightForWidth(modeBox->sizePolicy().hasHeightForWidth());
        modeBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(modeBox, 1, 1, 1, 1);

        horizontalSpacer_8 = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_8, 1, 2, 1, 1);

        horizontalSpacer_10 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_10, 7, 3, 1, 1);

        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_7, 1, 4, 1, 1);

        horizontalSpacer_6 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_6, 1, 5, 1, 1);

        tabWidget->addTab(actionTab, QString());
        programTab = new QWidget();
        programTab->setObjectName(QStringLiteral("programTab"));
        gridLayout_4 = new QGridLayout(programTab);
        gridLayout_4->setObjectName(QStringLiteral("gridLayout_4"));
        verticalSpacer = new QSpacerItem(20, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_4->addItem(verticalSpacer, 2, 1, 1, 1);

        horizontalSpacer = new QSpacerItem(5, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer, 1, 0, 1, 1);

        programKpButton = new QCheckBox(programTab);
        programKpButton->setObjectName(QStringLiteral("programKpButton"));

        gridLayout_4->addWidget(programKpButton, 0, 0, 1, 2);

        programKpBox = new QLineEdit(programTab);
        programKpBox->setObjectName(QStringLiteral("programKpBox"));

        gridLayout_4->addWidget(programKpBox, 1, 1, 1, 1);

        horizontalSpacer_11 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_11, 0, 2, 1, 2);

        horizontalSpacer_13 = new QSpacerItem(20, 20, QSizePolicy::Fixed, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_13, 1, 2, 1, 1);

        programKrBox = new QLineEdit(programTab);
        programKrBox->setObjectName(QStringLiteral("programKrBox"));

        gridLayout_4->addWidget(programKrBox, 4, 1, 1, 1);

        programKrButton = new QCheckBox(programTab);
        programKrButton->setObjectName(QStringLiteral("programKrButton"));
```

```

        gridLayout_4->addWidget(programKrButton, 3, 0, 1, 2);

        horizontalSpacer_12 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        gridLayout_4->addItem(horizontalSpacer_12, 0, 4, 1, 1);

        programKpExtra = new QWidget(programTab);
        programKpExtra->setObjectName(QStringLiteral("programKpExtra"));
        horizontalLayout_2 = new QHBoxLayout(programKpExtra);
        horizontalLayout_2->setSpacing(12);
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        horizontalLayout_2->setContentsMargins(0, 0, 0, 0);
        programKpSIBox = new QCheckBox(programKpExtra);
        programKpSIBox->setObjectName(QStringLiteral("programKpSIBox"));

        horizontalLayout_2->addWidget(programKpSIBox);

        programKpModeBox = new QComboBox(programKpExtra);
        programKpModeBox->setObjectName(QStringLiteral("programKpModeBox"));

        horizontalLayout_2->addWidget(programKpModeBox);

        horizontalSpacer_15 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer_15);


        gridLayout_4->addWidget(programKpExtra, 1, 3, 1, 2);

        programKrExtra = new QWidget(programTab);
        programKrExtra->setObjectName(QStringLiteral("programKrExtra"));
        horizontalLayout_3 = new QHBoxLayout(programKrExtra);
        horizontalLayout_3->setSpacing(12);
        horizontalLayout_3->setObjectName(QStringLiteral("horizontalLayout_3"));
        horizontalLayout_3->setContentsMargins(0, 0, 0, 0);
        programKrSIBox = new QCheckBox(programKrExtra);
        programKrSIBox->setObjectName(QStringLiteral("programKrSIBox"));

        horizontalLayout_3->addWidget(programKrSIBox);

        programKrModeBox = new QComboBox(programKrExtra);
        programKrModeBox->setObjectName(QStringLiteral("programKrModeBox"));

        horizontalLayout_3->addWidget(programKrModeBox);

        horizontalSpacer_16 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_3->addItem(horizontalSpacer_16);


        gridLayout_4->addWidget(programKrExtra, 4, 3, 1, 2);

        progTipLabel = new QLabel(programTab);
        progTipLabel->setObjectName(QStringLiteral("progTipLabel"));
        QSizePolicy sizePolicy3(QSizePolicy::Preferred, QSizePolicy::Expanding);
        sizePolicy3.setHorizontalStretch(0);
        sizePolicy3.setVerticalStretch(0);
        sizePolicy3.setHeightForWidth(progTipLabel->sizePolicy().hasHeightForWidth());
        progTipLabel->setSizePolicy(sizePolicy3);
        progTipLabel->setTextInteractionFlags(Qt::LinksAccessibleByMouse|Qt::TextSelectableByMouse);

        gridLayout_4->addWidget(progTipLabel, 5, 1, 1, 4);

        tabWidget->addTab(programTab, QString());
        macroTab = new QWidget();
        macroTab->setObjectName(QStringLiteral("macroTab"));
        layoutWidget1 = new QWidget(macroTab);
        layoutWidget1->setObjectName(QStringLiteral("layoutWidget1"));
        layoutWidget1->setGeometry(QRect(40, 12, 241, 171));
        gridLayout_8 = new QGridLayout(layoutWidget1);
        gridLayout_8->setObjectName(QStringLiteral("gridLayout_8"));
        gridLayout_8->setContentsMargins(0, 0, 0, 0);
        groupBox_2 = new QGroupBox(layoutWidget1);
        groupBox_2->setObjectName(QStringLiteral("groupBox_2"));

        gridLayout_8->addWidget(groupBox_2, 0, 0, 1, 1);

        pteMacroBox = new QPlainTextEdit(layoutWidget1);
        pteMacroBox->setObjectName(QStringLiteral("pteMacroBox"));
        pteMacroBox->setFocusPolicy(Qt::WheelFocus);
        pteMacroBox->setTabChangesFocus(true);

```

```
        gridLayout_8->addWidget(pteMacroBox, 1, 0, 1, 1);

        pteMacroComment = new QPlainTextEdit(macroTab);
        pteMacroComment->setObjectName(QStringLiteral("pteMacroComment"));
        pteMacroComment->setEnabled(true);
        pteMacroComment->setGeometry(QRect(420, 20, 311, 31));
        pteMacroComment->setFocusPolicy(Qt::WheelFocus);
        pteMacroComment->setContextMenuPolicy(Qt::NoContextMenu);
        pteMacroComment->setAcceptDrops(true);
        pteMacroComment->setToolTipDuration(1);
        pteMacroComment->setInputMethodHints(Qt::ImhNone);
        pteMacroComment->setVerticalScrollBarPolicy(Qt::ScrollBarAlwaysOff);
        pteMacroComment->setTabChangesFocus(true);
        pteMacroComment->setUndoRedoEnabled(true);
        pteMacroComment->setReadOnly(false);
        pteMacroComment->setTabStopWidth(1);
        pteMacroText = new QPlainTextEdit(macroTab);
        pteMacroText->setObjectName(QStringLiteral("pteMacroText"));
        pteMacroText->setGeometry(QRect(420, 60, 311, 61));
        pteMacroText->setFocusPolicy(Qt::StrongFocus);
        pteMacroText->setContextMenuPolicy(Qt::NoContextMenu);
        pteMacroText->setAcceptDrops(false);
        pteMacroText->setInputMethodHints(Qt::ImhNoAutoUppercase);
        pteMacroText->setUndoRedoEnabled(false);
        pteMacroText->setReadOnly(false);
        pteMacroText->setTabStopWidth(1);
        layoutWidget = new QWidget(macroTab);
        layoutWidget->setObjectName(QStringLiteral("layoutWidget"));
        layoutWidget->setGeometry(QRect(300, 20, 119, 81));
        verticalLayout_2 = new QVBoxLayout(layoutWidget);
        verticalLayout_2->setObjectName(QStringLiteral("verticalLayout_2"));
        verticalLayout_2->setContentsMargins(0, 0, 0, 0);
        groupBox_3 = new QGroupBox(layoutWidget);
        groupBox_3->setObjectName(QStringLiteral("groupBox_3"));

        verticalLayout_2->addWidget(groupBox_3);

        groupBox_4 = new QGroupBox(layoutWidget);
        groupBox_4->setObjectName(QStringLiteral("groupBox_4"));

        verticalLayout_2->addWidget(groupBox_4);

        layoutWidget_2 = new QWidget(macroTab);
        layoutWidget_2->setObjectName(QStringLiteral("layoutWidget_2"));
        layoutWidget_2->setGeometry(QRect(300, 160, 436, 30));
        gridLayout_10 = new QGridLayout(layoutWidget_2);
        gridLayout_10->setObjectName(QStringLiteral("gridLayout_10"));
        gridLayout_10->setContentsMargins(0, 0, 0, 0);
        groupBox = new QGroupBox(layoutWidget_2);
        groupBox->setObjectName(QStringLiteral("groupBox"));

        gridLayout_10->addWidget(groupBox, 0, 0, 1, 1);

        btnStopMacro = new QPushButton(layoutWidget_2);
        btnStopMacro->setObjectName(QStringLiteral("btnStopMacro"));
        btnStopMacro->setEnabled(false);

        gridLayout_10->addWidget(btnStopMacro, 0, 2, 1, 1);

        btnStartMacro = new QPushButton(layoutWidget_2);
        btnStartMacro->setObjectName(QStringLiteral("btnStartMacro"));

        gridLayout_10->addWidget(btnStartMacro, 0, 1, 1, 1);

        btnClearMacro = new QPushButton(layoutWidget_2);
        btnClearMacro->setObjectName(QStringLiteral("btnClearMacro"));

        gridLayout_10->addWidget(btnClearMacro, 0, 3, 1, 1);

        lbl_macro = new QLabel(macroTab);
        lbl_macro->setObjectName(QStringLiteral("lbl_macro"));
        lbl_macro->setGeometry(QRect(300, 130, 431, 27));
        tabWidget->addTab(macroTab, QString());
        pteMacroComment->raise();
        layoutWidget1->raise();
        layoutWidget->raise();
        pteMacroText->raise();
        layoutWidget_2->raise();
        lbl_macro->raise();

        verticalLayout->addWidget(tabWidget);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        horizontalSpacer_14 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

```

```
        horizontalLayout->addItem(horizontalSpacer_14);

        unbindButton = new QPushButton(RebindWidget);
        unbindButton->setObjectName(QStringLiteral("unbindButton"));

        horizontalLayout->addWidget(unbindButton);

        resetButton = new QPushButton(RebindWidget);
        resetButton->setObjectName(QStringLiteral("resetButton"));

        horizontalLayout->addWidget(resetButton);

        cancelButton = new QPushButton(RebindWidget);
        cancelButton->setObjectName(QStringLiteral("cancelButton"));

        horizontalLayout->addWidget(cancelButton);

        applyButton = new QPushButton(RebindWidget);
        applyButton->setObjectName(QStringLiteral("applyButton"));

        horizontalLayout->addWidget(applyButton);


        verticalLayout->addLayout(horizontalLayout);

        QWidget::setTabOrder(tabWidget, pteMacroComment);
        QWidget::setTabOrder(pteMacroComment, pteMacroBox);
        QWidget::setTabOrder(pteMacroBox, dpiButton);
        QWidget::setTabOrder(dpiButton, mb2Box);
        QWidget::setTabOrder(mb2Box, btnStartMacro);
        QWidget::setTabOrder(btnStartMacro, fnBox);
        QWidget::setTabOrder(fnBox, dpiCustYBox);
        QWidget::setTabOrder(dpiCustYBox, dpiBox);
        QWidget::setTabOrder(dpiBox, applyButton);
        QWidget::setTabOrder(applyButton, mbBox);
        QWidget::setTabOrder(mbBox, cancelButton);
        QWidget::setTabOrder(cancelButton, wheelBox);
        QWidget::setTabOrder(wheelBox, btnStopMacro);
        QWidget::setTabOrder(btnStopMacro, mbButton);
        QWidget::setTabOrder(mbButton, dpiCustXBox);
        QWidget::setTabOrder(dpiCustXBox, btnClearMacro);
        QWidget::setTabOrder(btnClearMacro, wheelButton);
        QWidget::setTabOrder(wheelButton, mb2Button);
        QWidget::setTabOrder(mb2Button, animBox);
        QWidget::setTabOrder(animBox, animKrBox);
        QWidget::setTabOrder(animKrBox, animOnceBox);
        QWidget::setTabOrder(animOnceBox, animButton);
        QWidget::setTabOrder(animButton, modeButton);
        QWidget::setTabOrder(modeButton, modeWrapBox);
        QWidget::setTabOrder(modeWrapBox, lightWrapBox);
        QWidget::setTabOrder(lightWrapBox, lockButton);
        QWidget::setTabOrder(lockButton, lightBox);
        QWidget::setTabOrder(lightBox, resetButton);
        QWidget::setTabOrder(resetButton, lockBox);
        QWidget::setTabOrder(lockBox, lightButton);
        QWidget::setTabOrder(lightButton, modeBox);
        QWidget::setTabOrder(modeBox, unbindButton);
        QWidget::setTabOrder(unbindButton, programKpButton);
        QWidget::setTabOrder(programKpButton, programKpBox);
        QWidget::setTabOrder(programKpBox, programKrBox);
        QWidget::setTabOrder(programKrBox, programKrButton);
        QWidget::setTabOrder(programKrButton, programKpSIBox);
        QWidget::setTabOrder(programKpSIBox, programKpModeBox);
        QWidget::setTabOrder(programKpModeBox, programKrSIBox);
        QWidget::setTabOrder(programKrSIBox, programKrModeBox);
        QWidget::setTabOrder(programKrModeBox, typingBox);
        QWidget::setTabOrder(typingBox, numBox);
        QWidget::setTabOrder(numBox, pteMacroText);
        QWidget::setTabOrder(pteMacroText, typingButton);
        QWidget::setTabOrder(typingButton, mediaButton);
        QWidget::setTabOrder(mediaButton, modBox);
        QWidget::setTabOrder(modBox, modButton);
        QWidget::setTabOrder(modButton, fnButton);
        QWidget::setTabOrder(fnButton, mediaBox);
        QWidget::setTabOrder(mediaBox, numButton);

        retranslateUi(RebindWidget);
        QObject::connect(cancelButton, SIGNAL(clicked()), pteMacroBox, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroBox, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroText, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), pteMacroComment, SLOT(clear()));
        QObject::connect(btnClearMacro, SIGNAL(clicked()), btnStopMacro, SLOT(animateClick()));
```

```

        tabWidget->setCurrentIndex(0);
        applyButton->setDefault(true);


        QMetaObject::connectSlotsByName(RebindWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.100.3 Field Documentation

12.100.3.1 QWidget* Ui_RebindWidget::actionTab

Definition at line 92 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.2 QComboBox* Ui_RebindWidget::animBox

Definition at line 84 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_animBox_currentIndexChanged(), RebindWidget::on_animButton_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.3 QRadioButton* Ui_RebindWidget::animButton

Definition at line 90 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_animBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.4 QCheckBox* Ui_RebindWidget::animKrBox

Definition at line 87 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.5 QCheckBox∗ Ui_RebindWidget::animOnceBox

Definition at line 88 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.6 QWidget∗ Ui_RebindWidget::animTab

Definition at line 81 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.7 QPushButton∗ Ui_RebindWidget::applyButton

Definition at line 155 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), retranslateUi(), and setupUi().

12.100.3.8 QPushButton∗ Ui_RebindWidget::btnClearMacro

Definition at line 148 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.9 QPushButton∗ Ui_RebindWidget::btnStartMacro

Definition at line 147 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), retranslateUi(), and setupUi().

12.100.3.10 QPushButton∗ Ui_RebindWidget::btnStopMacro

Definition at line 146 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), retranslateUi(), and setupUi().

12.100.3.11 QPushButton∗ Ui_RebindWidget::cancelButton

Definition at line 154 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.12 QComboBox∗ Ui_RebindWidget::dpiBox

Definition at line 68 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget::on_dpiButton_clicked(), retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.13 QRadioButton∗ Ui_RebindWidget::dpiButton

Definition at line 62 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_dpiBox_currentIndexChanged(), retranslateUi(), RebindWidget::setBind(), and setupUi().

12.100.3.14 QLabel* Ui_RebindWidget::dpiCustLabel

Definition at line 78 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_dpiBox_currentIndexChanged(), retranslateUi(), RebindWidget::setBind(), and setupUi().

12.100.3.15 QSpinBox* Ui_RebindWidget::dpiCustXBox

Definition at line 73 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget::setBind(), RebindWidget::setSelection(), and setupUi().

12.100.3.16 QSpinBox* Ui_RebindWidget::dpiCustYBox

Definition at line 69 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_dpiBox_currentIndexChanged(), RebindWidget::setBind(), RebindWidget::setSelection(), and setupUi().

12.100.3.17 QLabel* Ui_RebindWidget::dpiWarning

Definition at line 74 of file ui_rebindwidget.h.

Referenced by retranslateUi(), RebindWidget::setBind(), and setupUi().

12.100.3.18 QComboBox* Ui_RebindWidget::fnBox

Definition at line 44 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_fnBox_currentIndexChanged(), RebindWidget::on_fnButton_clicked(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.19 QRadioButton* Ui_RebindWidget::fnButton

Definition at line 56 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_fnBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.20 QGridLayout* Ui_RebindWidget::gridLayout

Definition at line 61 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.21 QGridLayout* Ui_RebindWidget::gridLayout_10

Definition at line 144 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.22 QGridLayout* Ui_RebindWidget::gridLayout_2

Definition at line 41 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.23 QGridLayout* Ui_RebindWidget::gridLayout_3

Definition at line 93 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.24 QGridLayout* Ui_RebindWidget::gridLayout_4

Definition at line 111 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.25 QGridLayout* Ui_RebindWidget::gridLayout_5

Definition at line 82 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.26 QGridLayout* Ui_RebindWidget::gridLayout_8

Definition at line 134 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.27 QGroupBox* Ui_RebindWidget::groupBox

Definition at line 145 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.28 QGroupBox* Ui_RebindWidget::groupBox_2

Definition at line 135 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.29 QGroupBox* Ui_RebindWidget::groupBox_3

Definition at line 141 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.30 QGroupBox* Ui_RebindWidget::groupBox_4

Definition at line 142 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.31 QHBoxLayout* Ui_RebindWidget::horizontalLayout

Definition at line 150 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.32 QHBoxLayout* Ui_RebindWidget::horizontalLayout_2

Definition at line 122 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.33 QHBoxLayout* Ui_RebindWidget::horizontalLayout_3

Definition at line 127 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.34 QSpacerItem* Ui_RebindWidget::horizontalSpacer

Definition at line 113 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.35 QSpacerItem* Ui_RebindWidget::horizontalSpacer_10

Definition at line 107 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.36 QSpacerItem* Ui_RebindWidget::horizontalSpacer_11

Definition at line 116 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.37 QSpacerItem* Ui_RebindWidget::horizontalSpacer_12

Definition at line 120 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.38 QSpacerItem* Ui_RebindWidget::horizontalSpacer_13

Definition at line 117 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.39 QSpacerItem* Ui_RebindWidget::horizontalSpacer_14

Definition at line 151 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.40 QSpacerItem* Ui_RebindWidget::horizontalSpacer_15

Definition at line 125 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.41 QSpacerItem* Ui_RebindWidget::horizontalSpacer_16

Definition at line 130 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.42 QSpacerItem* Ui_RebindWidget::horizontalSpacer_17

Definition at line 59 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.43 QSpacerItem* Ui_RebindWidget::horizontalSpacer_18

Definition at line 65 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.44 QSpacerItem* Ui_RebindWidget::horizontalSpacer_19

Definition at line 79 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.45 QSpacerItem* Ui_RebindWidget::horizontalSpacer_2

Definition at line 47 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.46 QSpacerItem* Ui_RebindWidget::horizontalSpacer_20

Definition at line 66 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.47 QSpacerItem* Ui_RebindWidget::horizontalSpacer_21

Definition at line 80 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.48 QSpacerItem* Ui_RebindWidget::horizontalSpacer_22

Definition at line 76 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.49 QSpacerItem* Ui_RebindWidget::horizontalSpacer_23

Definition at line 91 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.50 QSpacerItem* Ui_RebindWidget::horizontalSpacer_24

Definition at line 85 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.51 QSpacerItem* Ui_RebindWidget::horizontalSpacer_25

Definition at line 86 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.52 QSpacerItem* Ui_RebindWidget::horizontalSpacer_26

Definition at line 89 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.53 QSpacerItem* Ui_RebindWidget::horizontalSpacer_3

Definition at line 50 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.54 QSpacerItem* Ui_RebindWidget::horizontalSpacer_4

Definition at line 54 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.55 QSpacerItem* Ui_RebindWidget::horizontalSpacer_5

Definition at line 94 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.56 QSpacerItem* Ui_RebindWidget::horizontalSpacer_6

Definition at line 109 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.57 QSpacerItem* Ui_RebindWidget::horizontalSpacer_7

Definition at line 108 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.58 QSpacerItem* Ui_RebindWidget::horizontalSpacer_8

Definition at line 106 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.59 QSpacerItem* Ui_RebindWidget::horizontalSpacer_9

Definition at line 53 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.60 QWidget* Ui_RebindWidget::keyTab

Definition at line 40 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.61 QWidget* Ui_RebindWidget::layoutWidget

Definition at line 139 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.62 QWidget* Ui_RebindWidget::layoutWidget1

Definition at line 133 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.63 QWidget* Ui_RebindWidget::layoutWidget_2

Definition at line 143 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.64 QLabel* Ui_RebindWidget::lbl_macro

Definition at line 149 of file ui_rebindwidget.h.

Referenced by RebindWidget::helpStatus(), retranslateUi(), and setupUi().

12.100.3.65 QComboBox* Ui_RebindWidget::lightBox

Definition at line 102 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lightBox_currentIndexChanged(), RebindWidget::on_lightButton_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.66 QRadioButton* Ui_RebindWidget::lightButton

Definition at line 104 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_lightBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.67 QCheckBox* Ui_RebindWidget::lightWrapBox

Definition at line 97 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lightBox_currentIndexChanged(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.68 QComboBox* Ui_RebindWidget::lockBox

Definition at line 103 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_lockBox_currentIndexChanged(), RebindWidget::on_lockButton_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.69 QRadioButton* Ui_RebindWidget::lockButton

Definition at line 100 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_lockBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.70 QWidget* Ui_RebindWidget::macroTab

Definition at line 132 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.71 QComboBox* Ui_RebindWidget::mb2Box

Definition at line 67 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mb2Box_currentIndexChanged(), RebindWidget::on_mb2Button_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.72 QRadioButton* Ui_RebindWidget::mb2Button

Definition at line 77 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mb2Box_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.73 QComboBox* Ui_RebindWidget::mbBox

Definition at line 70 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mbBox_currentIndexChanged(), RebindWidget::on_mbButton_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.74 QRadioButton* Ui_RebindWidget::mbButton

Definition at line 72 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mbBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.75 QComboBox∗ Ui_RebindWidget::mediaBox

Definition at line 57 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_mediaBox_currentIndexChanged(), RebindWidget::on_mediaButton_clicked(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.76 QRadioButton∗ Ui_RebindWidget::mediaButton

Definition at line 51 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_mediaBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.77 QComboBox∗ Ui_RebindWidget::modBox

Definition at line 49 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modBox_currentIndexChanged(), RebindWidget::on_modButton_clicked(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.78 QRadioButton∗ Ui_RebindWidget::modButton

Definition at line 55 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_modBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.79 QComboBox∗ Ui_RebindWidget::modeBox

Definition at line 105 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modeBox_currentIndexChanged(), RebindWidget::on_modeButton_clicked(), retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.80 QRadioButton∗ Ui_RebindWidget::modeButton

Definition at line 95 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_modeBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.81 QCheckBox∗ Ui_RebindWidget::modeWrapBox

Definition at line 96 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_modeBox_currentIndexChanged(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.82 QWidget∗ Ui_RebindWidget::mouseTab

Definition at line 60 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.83 QComboBox∗ Ui_RebindWidget::numBox

Definition at line 42 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_numBox_currentIndexChanged(), RebindWidget::on_numButton_clicked(), RebindWidget::RebindWidget(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.84 QRadioButton∗ Ui_RebindWidget::numButton

Definition at line 58 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_numBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.85 QLineEdit∗ Ui_RebindWidget::programKpBox

Definition at line 115 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKpBox_textChanged(), RebindWidget::on_programKpButton_clicked(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.86 QCheckBox∗ Ui_RebindWidget::programKpButton

Definition at line 114 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKpBox_textChanged(), retranslateUi(), RebindWidget::setBox(), and setupUi().

12.100.3.87 QWidget∗ Ui_RebindWidget::programKpExtra

Definition at line 121 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKpBox_textChanged(), RebindWidget::RebindWidget(), and setupUi().

12.100.3.88 QComboBox∗ Ui_RebindWidget::programKpModeBox

Definition at line 124 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKpSIBox_clicked(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.89 QCheckBox∗ Ui_RebindWidget::programKpSIBox

Definition at line 123 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.90 QLineEdit∗ Ui_RebindWidget::programKrBox

Definition at line 118 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKrBox_textChanged(), RebindWidget::on_programKrButton_clicked(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.91 QCheckBox* Ui_RebindWidget::programKrButton

Definition at line 119 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKrBox_textChanged(), retranslateUi(), RebindWidget::setBox(), and setupUi().

12.100.3.92 QWidget* Ui_RebindWidget::programKrExtra

Definition at line 126 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_programKrBox_textChanged(), RebindWidget::RebindWidget(), and setupUi().

12.100.3.93 QComboBox* Ui_RebindWidget::programKrModeBox

Definition at line 129 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_programKrSIBox_clicked(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.94 QCheckBox* Ui_RebindWidget::programKrSIBox

Definition at line 128 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.95 QWidget* Ui_RebindWidget::programTab

Definition at line 110 of file ui_rebindwidget.h.

Referenced by retranslateUi(), and setupUi().

12.100.3.96 QLabel* Ui_RebindWidget::progTipLabel

Definition at line 131 of file ui_rebindwidget.h.

Referenced by RebindWidget::RebindWidget(), retranslateUi(), and setupUi().

12.100.3.97 QPlainTextEdit* Ui_RebindWidget::pteMacroBox

Definition at line 136 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::convertMacroBox(), RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_pteMacroBox_textChanged(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.98 QPlainTextEdit* Ui_RebindWidget::pteMacroComment

Definition at line 137 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.99 QPlainTextEdit* Ui_RebindWidget::pteMacroText

Definition at line 138 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_btnStartMacro_clicked(), retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.100 QPushButton* Ui_RebindWidget::resetButton

Definition at line 153 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), retranslateUi(), and setupUi().

12.100.3.101 QTabWidget* Ui_RebindWidget::tabWidget

Definition at line 39 of file ui_rebindwidget.h.

Referenced by retranslateUi(), RebindWidget::setSelection(), and setupUi().

12.100.3.102 QComboBox* Ui_RebindWidget::typingBox

Definition at line 43 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_typingBox_currentIndexChanged(), RebindWidget::on_typingButton_clicked(), retranslateUi(), RebindWidget::setBind(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.103 QRadioButton* Ui_RebindWidget::typingButton

Definition at line 48 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_typingBox_currentIndexChanged(), retranslateUi(), and setupUi().

12.100.3.104 QPushButton* Ui_RebindWidget::unbindButton

Definition at line 152 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_btnStartMacro_clicked(), RebindWidget::on_btnStopMacro_clicked(), retranslateUi(), and setupUi().

12.100.3.105 QVBoxLayout* Ui_RebindWidget::verticalLayout

Definition at line 38 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.106 QVBoxLayout* Ui_RebindWidget::verticalLayout_2

Definition at line 140 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.107 QSpacerItem* Ui_RebindWidget::verticalSpacer

Definition at line 112 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.108 QSpacerItem* Ui_RebindWidget::verticalSpacer_10

Definition at line 45 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.109 QSpacerItem* Ui_RebindWidget::verticalSpacer_11

Definition at line 83 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.110 QSpacerItem* Ui_RebindWidget::verticalSpacer_2

Definition at line 63 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.111 QSpacerItem* Ui_RebindWidget::verticalSpacer_3

Definition at line 46 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.112 QSpacerItem* Ui_RebindWidget::verticalSpacer_4

Definition at line 52 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.113 QSpacerItem* Ui_RebindWidget::verticalSpacer_5

Definition at line 101 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.114 QSpacerItem* Ui_RebindWidget::verticalSpacer_6

Definition at line 99 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.115 QSpacerItem* Ui_RebindWidget::verticalSpacer_7

Definition at line 98 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.116 QSpacerItem* Ui_RebindWidget::verticalSpacer_8

Definition at line 64 of file ui_rebindwidget.h.

Referenced by setupUi().

12.100.3.117 QComboBox* Ui_RebindWidget::wheelBox

Definition at line 71 of file ui_rebindwidget.h.

Referenced by RebindWidget::applyChanges(), RebindWidget::on_wheelBox_currentIndexChanged(), RebindWidget::on_wheelButton_clicked(), retranslateUi(), RebindWidget::setBox(), RebindWidget::setSelection(), and setupUi().

12.100.3.118 QRadioButton* Ui_RebindWidget::wheelButton

Definition at line 75 of file ui_rebindwidget.h.

Referenced by RebindWidget::on_wheelBox_currentIndexChanged(), retranslateUi(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_rebindwidget.h

12.101 Ui_SettingsWidget Class Reference

```
#include <src/ckb/ui_settingswidget.h>
```

Inheritance diagram for Ui_SettingsWidget:

Collaboration diagram for Ui_SettingsWidget:

Public Member Functions

- void setupUi (QWidget ∗SettingsWidget)
- void retranslateUi (QWidget ∗SettingsWidget)

Data Fields

- QGridLayout ∗ gridLayout
- QLabel ∗ label_2
- QLabel ∗ label
- QLabel ∗ label_6
- QGridLayout ∗ gridLayout_5
- QSpacerItem ∗ horizontalSpacer_7
- QLabel ∗ devicesLabel
- QLabel ∗ label_5
- QComboBox ∗ layoutBox
- QSpacerItem ∗ verticalSpacer_10
- QHBoxLayout ∗ horizontalLayout_2
- QLabel ∗ label_3
- QSpacerItem ∗ horizontalSpacer
- QPushButton ∗ pushButton
- QSpacerItem ∗ verticalSpacer
- QSpacerItem ∗ verticalSpacer_8
- QCheckBox ∗ loginItemBox
- QSpacerItem ∗ verticalSpacer_6
- QCheckBox ∗ autoFWBox
- QFrame ∗ line_2
- QLabel ∗ label_8
- QGridLayout ∗ gridLayout_3
- QLabel ∗ shiftLabel
- QLabel ∗ capsLabel
- QSpacerItem ∗ horizontalSpacer_10
- QComboBox ∗ capsBox
- QLabel ∗ ctrlLabel

- QSpacerItem * horizontalSpacer_9
- QComboBox * ctrlBox
- QComboBox * shiftBox
- QLabel * winLabel
- QComboBox * winBox
- QComboBox * altBox
- QLabel * altLabel
- QFrame * line
- QSpacerItem * verticalSpacer_3
- QSpacerItem * verticalSpacer_5
- QFrame * line_3
- QSpacerItem * verticalSpacer_4
- QSpacerItem * verticalSpacer_2
- QLabel * versionLabel
- QHBoxLayout * horizontalLayout
- QPushButton * extraButton
- QSpacerItem * horizontalSpacer_2
- QSpacerItem * verticalSpacer_7

12.101.1 Detailed Description

Definition at line 29 of file ui_settingswidget.h.

12.101.2 Member Function Documentation

12.101.2.1 void Ui_SettingsWidget::retranslateUi (QWidget * *SettingsWidget*) [inline]

Definition at line 347 of file ui_settingswidget.h.

References altLabel, autoFWBox, capsLabel, ctrlLabel, devicesLabel, extraButton, label, label_2, label_3, label_5, label_6, label_8, loginItemBox, pushButton, shiftLabel, versionLabel, and winLabel.

Referenced by setupUi().

```
    {
        SettingsWidget->setWindowTitle(QApplication::translate("SettingsWidget", "Form", Q_NULLPTR));
        label_2->setText(QApplication::translate("SettingsWidget", "\302\251 2014-2016 <a href=\"
    https://github.com/ccMSC/\" style=\"text-decoration:none;\">ccMSC</a>.<br/>\302\251 2017 <a href=\"
    https://github.com/mattanger/ckb-next/graphs/contributors\" style=\"text-decoration:none;\">The ckb-next development
     team</a>.", Q_NULLPTR));
        label->setText(QApplication::translate("SettingsWidget", "Modifier keys", Q_NULLPTR));
        label_6->setText(QApplication::translate("SettingsWidget", "Application", Q_NULLPTR));
        devicesLabel->setText(QApplication::translate("SettingsWidget", "No devices connected",
     Q_NULLPTR));
        label_5->setText(QApplication::translate("SettingsWidget", "Keyboard layout:", Q_NULLPTR));
        label_3->setText(QApplication::translate("SettingsWidget", "<a href=\"
    https://github.com/mattanger/ckb-next\" style=\"text-decoration:none;\">https://github.com/mattanger/ckb-next</a>", Q_NU
        pushButton->setText(QApplication::translate("SettingsWidget", "Quit", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        loginItemBox->setToolTip(QApplication::translate("SettingsWidget", "ckb-next will be
     started when you log in to your computer.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        loginItemBox->setText(QApplication::translate("SettingsWidget", "Start ckb-next at
     login", Q_NULLPTR));
#ifndef QT_NO_TOOLTIP
        autoFWBox->setToolTip(QApplication::translate("SettingsWidget", "You will be notified when
     new firmware versions are available. You'll have the option to install them immediately or wait until
     later.", Q_NULLPTR));
#endif // QT_NO_TOOLTIP
        autoFWBox->setText(QApplication::translate("SettingsWidget", "Check for new firmware
     automatically", Q_NULLPTR));
        label_8->setText(QApplication::translate("SettingsWidget", "These will override the keyboard
     profile. See \"Binding\" tab for more settings.", Q_NULLPTR));
        shiftLabel->setText(QApplication::translate("SettingsWidget", "Shift:", Q_NULLPTR));
        capsLabel->setText(QApplication::translate("SettingsWidget", "Caps Lock:", Q_NULLPTR));
        ctrlLabel->setText(QApplication::translate("SettingsWidget", "Ctrl:", Q_NULLPTR));
        winLabel->setText(QApplication::translate("SettingsWidget", "Windows:", Q_NULLPTR));
```

```
        altLabel->setText(QApplication::translate("SettingsWidget", "Alt:", Q_NULLPTR));
        versionLabel->setText(QApplication::translate("SettingsWidget", "ckb-next", Q_NULLPTR))
    ;
        extraButton->setText(QApplication::translate("SettingsWidget", "More settings",
    Q_NULLPTR));
    } // retranslateUi
```

Here is the caller graph for this function:

12.101.2.2 void Ui_SettingsWidget::setupUi (QWidget * *SettingsWidget*) [inline]

Definition at line 78 of file ui_settingswidget.h.

References altBox, altLabel, autoFWBox, capsBox, capsLabel, ctrlBox, ctrlLabel, devicesLabel, extraButton, gridLayout, gridLayout_3, gridLayout_5, horizontalLayout, horizontalLayout_2, horizontalSpacer, horizontalSpacer_10, horizontalSpacer_2, horizontalSpacer_7, horizontalSpacer_9, label, label_2, label_3, label_5, label_6, label_8, layoutBox, line, line_2, line_3, loginItemBox, pushButton, retranslateUi(), shiftBox, shiftLabel, versionLabel, verticalSpacer, verticalSpacer_10, verticalSpacer_2, verticalSpacer_3, verticalSpacer_4, verticalSpacer_5, verticalSpacer_6, verticalSpacer_7, verticalSpacer_8, winBox, and winLabel.

Referenced by SettingsWidget::SettingsWidget().

```
    {
        if (SettingsWidget->objectName().isEmpty())
            SettingsWidget->setObjectName(QStringLiteral("SettingsWidget"));
        SettingsWidget->resize(827, 654);
        gridLayout = new QGridLayout(SettingsWidget);
        gridLayout->setObjectName(QStringLiteral("gridLayout"));
        label_2 = new QLabel(SettingsWidget);
        label_2->setObjectName(QStringLiteral("label_2"));
        label_2->setOpenExternalLinks(true);
        label_2->setAlignment(Qt::AlignLeading|Qt::AlignLeft|Qt::AlignVCenter);

        gridLayout->addWidget(label_2, 20, 0, 1, 2);

        label = new QLabel(SettingsWidget);
        label->setObjectName(QStringLiteral("label"));
        QFont font;
        font.setBold(true);
        font.setWeight(75);
        label->setFont(font);

        gridLayout->addWidget(label, 6, 0, 1, 2);

        label_6 = new QLabel(SettingsWidget);
        label_6->setObjectName(QStringLiteral("label_6"));
        label_6->setFont(font);

        gridLayout->addWidget(label_6, 12, 0, 1, 2);

        gridLayout_5 = new QGridLayout();
        gridLayout_5->setObjectName(QStringLiteral("gridLayout_5"));
        horizontalSpacer_7 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
    QSizePolicy::Minimum);

        gridLayout_5->addItem(horizontalSpacer_7, 2, 2, 1, 1);

        devicesLabel = new QLabel(SettingsWidget);
        devicesLabel->setObjectName(QStringLiteral("devicesLabel"));

        gridLayout_5->addWidget(devicesLabel, 0, 0, 1, 3);

        label_5 = new QLabel(SettingsWidget);
        label_5->setObjectName(QStringLiteral("label_5"));

```

```
        gridLayout_5->addWidget(label_5, 2, 0, 1, 1);

        layoutBox = new QComboBox(SettingsWidget);
        layoutBox->setObjectName(QStringLiteral("layoutBox"));

        gridLayout_5->addWidget(layoutBox, 2, 1, 1, 1);

        verticalSpacer_10 = new QSpacerItem(20, 6, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout_5->addItem(verticalSpacer_10, 1, 0, 1, 1);


        gridLayout->addLayout(gridLayout_5, 4, 1, 1, 1);

        horizontalLayout_2 = new QHBoxLayout();
        horizontalLayout_2->setObjectName(QStringLiteral("horizontalLayout_2"));
        label_3 = new QLabel(SettingsWidget);
        label_3->setObjectName(QStringLiteral("label_3"));
        label_3->setOpenExternalLinks(true);

        horizontalLayout_2->addWidget(label_3);

        horizontalSpacer = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout_2->addItem(horizontalSpacer);

        pushButton = new QPushButton(SettingsWidget);
        pushButton->setObjectName(QStringLiteral("pushButton"));
        pushButton->setFlat(false);

        horizontalLayout_2->addWidget(pushButton);


        gridLayout->addLayout(horizontalLayout_2, 21, 0, 1, 2);

        verticalSpacer = new QSpacerItem(20, 40, QSizePolicy::Minimum, QSizePolicy::Expanding);

        gridLayout->addItem(verticalSpacer, 19, 0, 1, 2);

        verticalSpacer_8 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_8, 16, 0, 1, 1);

        loginItemBox = new QCheckBox(SettingsWidget);
        loginItemBox->setObjectName(QStringLiteral("loginItemBox"));

        gridLayout->addWidget(loginItemBox, 16, 1, 1, 1);

        verticalSpacer_6 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_6, 15, 0, 1, 1);

        autoFWBox = new QCheckBox(SettingsWidget);
        autoFWBox->setObjectName(QStringLiteral("autoFWBox"));
        autoFWBox->setChecked(true);

        gridLayout->addWidget(autoFWBox, 15, 1, 1, 1);

        line_2 = new QFrame(SettingsWidget);
        line_2->setObjectName(QStringLiteral("line_2"));
        line_2->setFrameShape(QFrame::HLine);
        line_2->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_2, 13, 0, 1, 2);

        label_8 = new QLabel(SettingsWidget);
        label_8->setObjectName(QStringLiteral("label_8"));
        QFont font1;
        font1.setItalic(true);
        label_8->setFont(font1);

        gridLayout->addWidget(label_8, 8, 1, 1, 1);

        gridLayout_3 = new QGridLayout();
        gridLayout_3->setObjectName(QStringLiteral("gridLayout_3"));
        shiftLabel = new QLabel(SettingsWidget);
        shiftLabel->setObjectName(QStringLiteral("shiftLabel"));
        QSizePolicy sizePolicy(QSizePolicy::Expanding, QSizePolicy::Preferred);
        sizePolicy.setHorizontalStretch(0);
        sizePolicy.setVerticalStretch(0);
        sizePolicy.setHeightForWidth(shiftLabel->sizePolicy().hasHeightForWidth());
        shiftLabel->setSizePolicy(sizePolicy);
```

```
        shiftLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(shiftLabel, 0, 3, 1, 1);

        capsLabel = new QLabel(SettingsWidget);
        capsLabel->setObjectName(QStringLiteral("capsLabel"));
        capsLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(capsLabel, 0, 1, 1, 1);

        horizontalSpacer_10 = new QSpacerItem(0, 0, QSizePolicy::Fixed,
QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_10, 0, 0, 1, 1);

        capsBox = new QComboBox(SettingsWidget);
        capsBox->setObjectName(QStringLiteral("capsBox"));
        QSizePolicy sizePolicy1(QSizePolicy::Expanding, QSizePolicy::Fixed);
        sizePolicy1.setHorizontalStretch(0);
        sizePolicy1.setVerticalStretch(0);
        sizePolicy1.setHeightForWidth(capsBox->sizePolicy().hasHeightForWidth());
        capsBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(capsBox, 0, 2, 1, 1);

        ctrlLabel = new QLabel(SettingsWidget);
        ctrlLabel->setObjectName(QStringLiteral("ctrlLabel"));
        ctrlLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(ctrlLabel, 1, 1, 1, 1);

        horizontalSpacer_9 = new QSpacerItem(40, 20, QSizePolicy::Expanding,
QSizePolicy::Minimum);

        gridLayout_3->addItem(horizontalSpacer_9, 1, 7, 1, 1);

        ctrlBox = new QComboBox(SettingsWidget);
        ctrlBox->setObjectName(QStringLiteral("ctrlBox"));

        gridLayout_3->addWidget(ctrlBox, 1, 2, 1, 1);

        shiftBox = new QComboBox(SettingsWidget);
        shiftBox->setObjectName(QStringLiteral("shiftBox"));
        sizePolicy1.setHeightForWidth(shiftBox->sizePolicy().hasHeightForWidth());
        shiftBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(shiftBox, 0, 4, 1, 1);

        winLabel = new QLabel(SettingsWidget);
        winLabel->setObjectName(QStringLiteral("winLabel"));
        sizePolicy.setHeightForWidth(winLabel->sizePolicy().hasHeightForWidth());
        winLabel->setSizePolicy(sizePolicy);
        winLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(winLabel, 1, 3, 1, 1);

        winBox = new QComboBox(SettingsWidget);
        winBox->setObjectName(QStringLiteral("winBox"));
        sizePolicy1.setHeightForWidth(winBox->sizePolicy().hasHeightForWidth());
        winBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(winBox, 1, 4, 1, 1);

        altBox = new QComboBox(SettingsWidget);
        altBox->setObjectName(QStringLiteral("altBox"));
        sizePolicy1.setHeightForWidth(altBox->sizePolicy().hasHeightForWidth());
        altBox->setSizePolicy(sizePolicy1);

        gridLayout_3->addWidget(altBox, 1, 6, 1, 1);

        altLabel = new QLabel(SettingsWidget);
        altLabel->setObjectName(QStringLiteral("altLabel"));
        sizePolicy.setHeightForWidth(altLabel->sizePolicy().hasHeightForWidth());
        altLabel->setSizePolicy(sizePolicy);
        altLabel->setAlignment(Qt::AlignRight|Qt::AlignTrailing|Qt::AlignVCenter);

        gridLayout_3->addWidget(altLabel, 1, 5, 1, 1);


        gridLayout->addLayout(gridLayout_3, 10, 1, 1, 1);

        line = new QFrame(SettingsWidget);
        line->setObjectName(QStringLiteral("line"));
        line->setFrameShape(QFrame::HLine);
        line->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line, 1, 0, 1, 2);
```

```

        verticalSpacer_3 = new QSpacerItem(0, 5, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_3, 2, 1, 1, 1);

        verticalSpacer_5 = new QSpacerItem(20, 12, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_5, 11, 1, 1, 1);

        line_3 = new QFrame(SettingsWidget);
        line_3->setObjectName(QStringLiteral("line_3"));
        QSizePolicy sizePolicy2(QSizePolicy::Minimum, QSizePolicy::Fixed);
        sizePolicy2.setHorizontalStretch(0);
        sizePolicy2.setVerticalStretch(0);
        sizePolicy2.setHeightForWidth(line_3->sizePolicy().hasHeightForWidth());
        line_3->setSizePolicy(sizePolicy2);
        line_3->setFrameShape(QFrame::HLine);
        line_3->setFrameShadow(QFrame::Sunken);

        gridLayout->addWidget(line_3, 7, 0, 1, 2);

        verticalSpacer_4 = new QSpacerItem(20, 6, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_4, 9, 1, 1, 1);

        verticalSpacer_2 = new QSpacerItem(20, 12, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_2, 5, 1, 1, 1);

        versionLabel = new QLabel(SettingsWidget);
        versionLabel->setObjectName(QStringLiteral("versionLabel"));
        versionLabel->setFont(font);

        gridLayout->addWidget(versionLabel, 0, 0, 1, 2);

        horizontalLayout = new QHBoxLayout();
        horizontalLayout->setObjectName(QStringLiteral("horizontalLayout"));
        extraButton = new QPushButton(SettingsWidget);
        extraButton->setObjectName(QStringLiteral("extraButton"));

        horizontalLayout->addWidget(extraButton);

        horizontalSpacer_2 = new QSpacerItem(40, 20, QSizePolicy::Expanding, QSizePolicy::Minimum);

        horizontalLayout->addItem(horizontalSpacer_2);


        gridLayout->addLayout(horizontalLayout, 17, 1, 1, 1);

        verticalSpacer_7 = new QSpacerItem(0, 28, QSizePolicy::Minimum, QSizePolicy::Fixed);

        gridLayout->addItem(verticalSpacer_7, 17, 0, 1, 1);


        retranslateUi(SettingsWidget);

        QMetaObject::connectSlotsByName(SettingsWidget);
    } // setupUi
```

Here is the call graph for this function:

Here is the caller graph for this function:

12.101.3 Field Documentation

12.101.3.1 QComboBox* Ui_SettingsWidget::altBox

Definition at line 64 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::updateModifiers().

12.101.3.2 QLabel* Ui_SettingsWidget::altLabel

Definition at line 65 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.3 QCheckBox* Ui_SettingsWidget::autoFWBox

Definition at line 50 of file ui_settingswidget.h.

Referenced by retranslateUi(), SettingsWidget::SettingsWidget(), and setupUi().

12.101.3.4 QComboBox* Ui_SettingsWidget::capsBox

Definition at line 57 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::updateModifiers().

12.101.3.5 QLabel* Ui_SettingsWidget::capsLabel

Definition at line 55 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.6 QComboBox* Ui_SettingsWidget::ctrlBox

Definition at line 60 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::updateModifiers().

12.101.3.7 QLabel* Ui_SettingsWidget::ctrlLabel

Definition at line 58 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.8 QLabel* Ui_SettingsWidget::devicesLabel

Definition at line 38 of file ui_settingswidget.h.

Referenced by retranslateUi(), SettingsWidget::setStatus(), and setupUi().

12.101.3.9 QPushButton* Ui_SettingsWidget::extraButton

Definition at line 74 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.10 QGridLayout* Ui_SettingsWidget::gridLayout

Definition at line 32 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.11 QGridLayout* Ui_SettingsWidget::gridLayout_3

Definition at line 53 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.12 QGridLayout* Ui_SettingsWidget::gridLayout_5

Definition at line 36 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.13 QHBoxLayout* Ui_SettingsWidget::horizontalLayout

Definition at line 73 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.14 QHBoxLayout* Ui_SettingsWidget::horizontalLayout_2

Definition at line 42 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.15 QSpacerItem* Ui_SettingsWidget::horizontalSpacer

Definition at line 44 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.16 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_10

Definition at line 56 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.17 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_2

Definition at line 75 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.18 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_7

Definition at line 37 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.19 QSpacerItem* Ui_SettingsWidget::horizontalSpacer_9

Definition at line 59 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.20 QLabel* Ui_SettingsWidget::label

Definition at line 34 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.21 QLabel* Ui_SettingsWidget::label_2

Definition at line 33 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.22 QLabel* Ui_SettingsWidget::label_3

Definition at line 43 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.23 QLabel* Ui_SettingsWidget::label_5

Definition at line 39 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.24 QLabel* Ui_SettingsWidget::label_6

Definition at line 35 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.25 QLabel* Ui_SettingsWidget::label_8

Definition at line 52 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.26 QComboBox* Ui_SettingsWidget::layoutBox

Definition at line 40 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::showLayoutDialog().

12.101.3.27 QFrame* Ui_SettingsWidget::line

Definition at line 66 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.28 QFrame* Ui_SettingsWidget::line_2

Definition at line 51 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.29 QFrame* Ui_SettingsWidget::line_3

Definition at line 69 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.30 QCheckBox* Ui_SettingsWidget::loginItemBox

Definition at line 48 of file ui_settingswidget.h.

Referenced by retranslateUi(), SettingsWidget::SettingsWidget(), and setupUi().

12.101.3.31 QPushButton* Ui_SettingsWidget::pushButton

Definition at line 45 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.32 QComboBox* Ui_SettingsWidget::shiftBox

Definition at line 61 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::updateModifiers().

12.101.3.33 QLabel* Ui_SettingsWidget::shiftLabel

Definition at line 54 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

12.101.3.34 QLabel* Ui_SettingsWidget::versionLabel

Definition at line 72 of file ui_settingswidget.h.

Referenced by retranslateUi(), setupUi(), and SettingsWidget::setVersion().

12.101.3.35 QSpacerItem* Ui_SettingsWidget::verticalSpacer

Definition at line 46 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.36 QSpacerItem* Ui_SettingsWidget::verticalSpacer_10

Definition at line 41 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.37 QSpacerItem* Ui_SettingsWidget::verticalSpacer_2

Definition at line 71 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.38 QSpacerItem* Ui_SettingsWidget::verticalSpacer_3

Definition at line 67 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.39 QSpacerItem* Ui_SettingsWidget::verticalSpacer_4

Definition at line 70 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.40 QSpacerItem* Ui_SettingsWidget::verticalSpacer_5

Definition at line 68 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.41 QSpacerItem* Ui_SettingsWidget::verticalSpacer_6

Definition at line 49 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.42 QSpacerItem* Ui_SettingsWidget::verticalSpacer_7

Definition at line 76 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.43 QSpacerItem* Ui_SettingsWidget::verticalSpacer_8

Definition at line 47 of file ui_settingswidget.h.

Referenced by setupUi().

12.101.3.44 QComboBox* Ui_SettingsWidget::winBox

Definition at line 63 of file ui_settingswidget.h.

Referenced by SettingsWidget::SettingsWidget(), setupUi(), and SettingsWidget::updateModifiers().

12.101.3.45 QLabel* Ui_SettingsWidget::winLabel

Definition at line 62 of file ui_settingswidget.h.

Referenced by retranslateUi(), and setupUi().

The documentation for this class was generated from the following file:

- src/ckb/ui_settingswidget.h

12.102 UsbId Struct Reference

```
#include <src/ckb/kbmode.h>
```

Collaboration diagram for UsbId:

Public Member Functions

- UsbId (const QString &_guid, quint32 _modified)

- UsbId (const QString &_guid, const QString &_modified)
- UsbId ()
- QString guidString () const
- void guidString (const QString &newGuid)
- QString modifiedString () const
- void modifiedString (const QString &newModified)
- QString hwModifiedString () const
- void hwModifiedString (const QString &newModified)
- void newGuid ()
- void newModified ()

Data Fields

- QUuid guid
- quint32 modified
- quint32 hwModified

12.102.1 Detailed Description

Definition at line 11 of file kbmode.h.

12.102.2 Constructor & Destructor Documentation

12.102.2.1 UsbId::UsbId (const QString & *_guid*, quint32 *_modified*) [inline]

Definition at line 16 of file kbmode.h.

```
16 : guid(_guid), modified(_modified), hwModified(_modified) {}
```

12.102.2.2 UsbId::UsbId (const QString & *_guid*, const QString & *_modified*) [inline]

Definition at line 17 of file kbmode.h.

```
17 : guid(_guid), modified(_modified.toUInt(0, 16)), hwModified(
      modified) {}
```

12.102.2.3 UsbId::UsbId ( ) [inline]

Definition at line 18 of file kbmode.h.

```
18 : guid(QUuid::createUuid()),modified(0) {}
```

12.102.3 Member Function Documentation

12.102.3.1 QString UsbId::guidString ( ) const [inline]

Definition at line 20 of file kbmode.h.

References guid.

Referenced by Kb::hwSave(), KbProfile::save(), KbMode::save(), Kb::save(), and Kb::writeProfileHeader().

```
20 { return guid.toString().toUpper(); }
```

Here is the caller graph for this function:

12.102.3.2 void UsbId::guidString (const QString & *newGuid*) [inline]

Definition at line 21 of file kbmode.h.

References guid, and newGuid().

```
21 { guid = newGuid; }
```

Here is the call graph for this function:

12.102.3.3 QString UsbId::hwModifiedString ( ) const [inline]

Definition at line 24 of file kbmode.h.

References hwModified.

Referenced by KbMode::KbMode(), KbProfile::KbProfile(), Kb::readNotify(), KbProfile::save(), and KbMode::save().

```
24 { return QString::number(hwModified, 16); }
```

Here is the caller graph for this function:

12.102.3.4 void UsbId::hwModifiedString (const QString & *newModified*) [inline]

Definition at line 25 of file kbmode.h.

References hwModified.

```
25 { hwModified = newModified.toUInt(0, 16); }
```

12.102.3.5 QString UsbId::modifiedString ( ) const [inline]

Definition at line 22 of file kbmode.h.

References modified.

Referenced by Kb::hwSave(), KbProfile::KbProfile(), Kb::readNotify(), KbProfile::save(), KbMode::save(), and Kb::writeProfileHeader().

```
22 { return QString::number(modified, 16); }
```

Here is the caller graph for this function:

12.102.3.6 void UsbId::modifiedString (const QString & *newModified*) [inline]

Definition at line 23 of file kbmode.h.

References modified.

```
23 { modified = newModified.toUInt(0, 16); }
```

12.102.3.7 void UsbId::newGuid ( ) [inline]

Definition at line 28 of file kbmode.h.

References guid.

Referenced by guidString().

```
28 { guid = QUuid::createUuid(); }
```

Here is the caller graph for this function:

12.102.3.8 void UsbId::newModified ( ) [inline]

Definition at line 29 of file kbmode.h.

References modified.

Referenced by KbProfile::save(), and KbMode::save().

```
29 { quint32 newMod; do { newMod = qrand(); } while(newMod == modified);
     modified = newMod; }
```

Here is the caller graph for this function:

12.102.4 Field Documentation

12.102.4.1 QUuid UsbId::guid

Definition at line 12 of file kbmode.h.

Referenced by KbProfile::find(), Kb::find(), guidString(), KbMode::KbMode(), KbProfile::KbProfile(), newGuid(), KbWidget::on_modesList_customContextMenuRequested(), KbWidget::on_modesList_itemChanged(), KbWidget::on_modesList_itemClicked(), KbProfileDialog::on_profileList_customContextMenuRequested(), KbProfileDialog::on_profileList_itemChanged(), KbProfileDialog::on_profileList_itemClicked(), KbWidget::profileChanged(), Kb::readNotify(), and KbProfileDialog::repopulate().

12.102.4.2 quint32 UsbId::hwModified

Definition at line 14 of file kbmode.h.

Referenced by hwModifiedString(), Kb::hwSave(), KbMode::KbMode(), and KbProfile::KbProfile().

12.102.4.3 quint32 UsbId::modified

Definition at line 13 of file kbmode.h.

Referenced by Kb::hwSave(), KbMode::KbMode(), KbProfile::KbProfile(), modifiedString(), and newModified().

The documentation for this struct was generated from the following file:

- src/ckb/kbmode.h

Chapter 13

File Documentation

13.1 BUILD.md File Reference

13.2 DAEMON.md File Reference

13.3 README.md File Reference

13.4 ROADMAP.md File Reference

13.5 src/ckb/animadddialog.cpp File Reference

```
#include "animadddialog.h"
#include "ui_animadddialog.h"
```

Include dependency graph for animadddialog.cpp:

13.6 src/ckb/animadddialog.h File Reference

```
#include <QDialog>
#include "animscript.h"
#include "kblight.h"
```

Include dependency graph for animadddialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class AnimAddDialog

Namespaces

- Ui

13.7 src/ckb/animscript.cpp File Reference

```
#include <cmath>
#include <QApplication>
#include <QDateTime>
#include <QDebug>
#include <QDir>
#include <QUrl>
#include "animscript.h"
```

Include dependency graph for animscript.cpp:

Functions

- QString urlParam (const QString &param)

Variables

- static const double ONE_DAY = 24. ∗ 60. ∗ 60.

13.7.1 Function Documentation

13.7.1.1 QString urlParam (const QString & *param*) [inline]

Definition at line 71 of file animscript.cpp.

Referenced by AnimScript::load().

```
71                                                  {
72      return QUrl::fromPercentEncoding(param.trimmed().toLatin1()).trimmed();
73  }
```

Here is the caller graph for this function:

13.7.2 Variable Documentation

13.7.2.1 const double ONE_DAY = 24. ∗ 60. ∗ 60. [static]

Definition at line 75 of file animscript.cpp.

Referenced by AnimScript::load().

13.8 src/ckb/animscript.h File Reference

```
#include <QHash>
#include <QObject>
#include <QMap>
#include <QProcess>
#include <QUuid>
#include <QVariant>
#include "keymap.h"
#include "colormap.h"
```

Include dependency graph for animscript.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class AnimScript
- struct AnimScript::Param

13.8.1 Data Structure Documentation

13.8.1.1 struct AnimScript::Param

Definition at line 21 of file animscript.h.

Collaboration diagram for AnimScript::Param:

Data Fields

	Type	

Data Fields

QVariant	defaultValue	
QVariant	maximum	
QVariant	minimum	
QString	name	
QString	postfix	
QString	prefix	
Type	type	

13.9 src/ckb/animsettingdialog.cpp File Reference

```
#include <cstdio>
#include <QDial>
#include <QDoubleSpinBox>
#include <QLineEdit>
#include <QComboBox>
#include "animsettingdialog.h"
#include "ui_animsettingdialog.h"
#include "colorbutton.h"
#include "gradientbutton.h"
```

Include dependency graph for animsettingdialog.cpp:

Functions

- static int angleFlip (int angle)

13.9.1 Function Documentation

13.9.1.1 static int angleFlip (int *angle*) [inline],[static]

Definition at line 12 of file animsettingdialog.cpp.

Referenced by AnimSettingDialog::angleDialChanged(), AnimSettingDialog::angleSpinnerChanged(), AnimSettingDialog::AnimSettingDialog(), and AnimSettingDialog::updateParam().

```
12                                          {
13     if(angle <= 180)
14         return 180 - angle;
15     else
16        return 360 - (angle - 180);
17 }
```

Here is the caller graph for this function:

13.10 src/ckb/animsettingdialog.h File Reference

```
#include <QCheckBox>
#include <QDialog>
#include <QFrame>
#include <QSignalMapper>
#include <QSpinBox>
#include "kbanim.h"
```

Include dependency graph for animsettingdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class AnimSettingDialog

Namespaces

- Ui

13.11 src/ckb/autorun.cpp File Reference

```
#include <QApplication>
#include <QDir>
#include <QSettings>
#include <QStandardPaths>
#include "autorun.h"
#include "ckbsettings.h"
```

Include dependency graph for autorun.cpp:

Variables

- static const QString settingPath = "Program/DidLoginItem"

13.11.1 Variable Documentation

13.11.1.1 const QString settingPath = "Program/DidLoginItem" [static]

Definition at line 18 of file autorun.cpp.

13.12 src/ckb/autorun.h File Reference

`#include <QObject>`
Include dependency graph for autorun.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class AutoRun

13.13 src/ckb/ckb-anim.h File Reference

```
#include <ctype.h>
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
```

Include dependency graph for ckb-anim.h:

Data Structures

- struct ckb_key
- struct ckb_runctx
- struct ckb_gradient

Macros

- #define M_PI 3.14159265358979323846
- #define TRUE 1

- #define FALSE 0
- #define CKB_DOWN 1
- #define CKB_UP 0
- #define CKB_CONTAINER(macro) do { macro } while(0)
- #define CKB_GUID(guid) CKB_CONTAINER(printf("guid "); printurl(guid); printf("\n");)
- #define CKB_NAME(name) CKB_CONTAINER(printf("name "); printurl(name); printf("\n");)
- #define CKB_VERSION(version) CKB_CONTAINER(printf("version "); printurl(version); printf("\n");)
- #define CKB_COPYRIGHT(year, author) CKB_CONTAINER(printf("author "); printurl(author); printf("\nyear %s\n", year);)
- #define CKB_LICENSE(license) CKB_CONTAINER(printf("license "); printurl(license); printf("\n");)
- #define CKB_DESCRIPTION(description) CKB_CONTAINER(printf("description "); printurl(description); printf("\n");)
- #define CKB_PARAM(type, name, prefix, postfix, extra) CKB_CONTAINER(printf("param %s %s ", type, name); printurl(prefix); printf(" "); printurl(postfix); printf(" "); extra; printf("\n");)
- #define CKB_PARAM_LONG(name, prefix, postfix, default, min, max) CKB_PARAM("long", name, prefix, postfix, printf("%ld %ld %ld", (long)(default), (long)(min), (long)(max)))
- #define CKB_PARAM_DOUBLE(name, prefix, postfix, default, min, max) CKB_PARAM("double", name, prefix, postfix, printf("%lf %lf %lf", (double)(default), (double)(min), (double)(max)))
- #define CKB_PARAM_BOOL(name, text, default) CKB_PARAM("bool", name, text, "", printf((default) ? "1" : "0"))
- #define CKB_PARAM_RGB(name, prefix, postfix, r, g, b) CKB_PARAM("rgb", name, prefix, postfix, printf("%02x%02x%02x", (unsigned char)(r), (unsigned char)(g), (unsigned char)(b)))
- #define CKB_PARAM_ARGB(name, prefix, postfix, a, r, g, b) CKB_PARAM("argb", name, prefix, postfix, printf("%02x%02x%02x%02x", (unsigned char)(a), (unsigned char)(r), (unsigned char)(g), (unsigned char)(b)))
- #define CKB_PARAM_GRADIENT(name, prefix, postfix, default) CKB_PARAM("gradient", name, prefix, postfix, printurl(default))
- #define CKB_PARAM_AGRADIENT(name, prefix, postfix, default) CKB_PARAM("agradient", name, prefix, postfix, printurl(default))
- #define CKB_PARAM_ANGLE(name, prefix, postfix, default) CKB_PARAM("angle", name, prefix, postfix, printf("%ld", (long)(default)))
- #define CKB_PARAM_STRING(name, prefix, postfix, default) CKB_PARAM("string", name, prefix, postfix, printurl(default))
- #define CKB_PARAM_LABEL(name, text) CKB_PARAM("label", name, text, "",)
- #define CKB_PRESET_START(name) CKB_CONTAINER(printf("preset "); printurl(name);)
- #define CKB_PRESET_PARAM(name, value) CKB_CONTAINER(printf(" %s=", name); printurl(value);)
- #define CKB_PRESET_END CKB_CONTAINER(printf("\n");)
- #define CKB_KP_NONE "none"
- #define CKB_KP_NAME "name"
- #define CKB_KP_POSITION "position"
- #define CKB_KPMODE(mode) CKB_CONTAINER(printf("kpmode %s\n", mode);)
- #define CKB_TIME_DURATION "duration"
- #define CKB_TIME_ABSOLUTE "absolute"
- #define CKB_TIMEMODE(mode) CKB_CONTAINER(printf("time %s\n", mode);)
- #define CKB_REPEAT(enable) CKB_CONTAINER(printf("repeat %s\n", (enable) ? "on" : "off");)
- #define CKB_PREEMPT(enable) CKB_CONTAINER(printf("preempt %s\n", (enable) ? "on" : "off");)
- #define CKB_LIVEPARAMS(enable) CKB_CONTAINER(printf("parammode %s\n", (enable) ? "live" : "static");)
- #define CKB_PARSE_LONG(param_name, value_ptr) if(!strcmp(name, param_name) && sscanf(value, "%ld", value_ptr) == 1)
- #define CKB_PARSE_DOUBLE(param_name, value_ptr) if(!strcmp(name, param_name) && sscanf(value, "%lf", value_ptr) == 1)
- #define CKB_PARSE_BOOL(param_name, value_ptr) if(!strcmp(name, param_name) && sscanf(value, "%u", value_ptr) == 1)
- #define CKB_PARSE_RGB(param_name, r_ptr, g_ptr, b_ptr) if(!strcmp(name, param_name) && sscanf(value, "%2hhx%2hhx%2hhx", r_ptr, g_ptr, b_ptr) == 3)

- #define CKB_PARSE_ARGB(param_name, a_ptr, r_ptr, g_ptr, b_ptr) if(!strcmp(name, param_name) && sscanf(value, "%2hhx%2hhx%2hhx%2hhx", a_ptr, r_ptr, g_ptr, b_ptr) == 4)
- #define CKB_PARSE_GRADIENT(param_name, gradient_ptr) if(!strcmp(name, param_name) && ckb_scan_grad(value, gradient_ptr, 0))
- #define CKB_PARSE_AGRADIENT(param_name, gradient_ptr) if(!strcmp(name, param_name) && ckb_scan_grad(value, gradient_ptr, 1))
- #define CKB_PARSE_ANGLE(param_name, value_ptr) if(!strcmp(name, param_name) && sscanf(value, "%ld", value_ptr) == 1)
- #define CKB_PARSE_STRING(param_name) if(!strcmp(name, param_name))
- #define CKB_REAL_ANGLE(angle) fmod((-(angle) + 90.) ∗ M_PI / 180. + M_PI ∗ 2., M_PI ∗ 2.)
- #define CKB_KEYNAME_MAX 12
- #define CKB_KEYCLEAR(context) CKB_CONTAINER(ckb_key∗ key = context->keys; unsigned count = context->keycount; unsigned i = 0; for(; i < count; i++) key[i].a = key[i].r = key[i].g = key[i].b = 0;)
- #define CKB_GRAD_MAX 100
- #define CKB_MAX_WORD (4 ∗ 1024)

Functions

- int ckb_scan_grad (const char ∗string, ckb_gradient ∗gradient, int alpha)
- void ckb_grad_color (float ∗a, float ∗r, float ∗g, float ∗b, const ckb_gradient ∗grad, float pos)
- void ckb_alpha_blend (ckb_key ∗key, float a, float r, float g, float b)
- void printurl (const char ∗src)
- void urldecode (char ∗dst, const char ∗src)
- void ckb_getline (char word1[(4 ∗1024)], char word2[(4 ∗1024)], char word3[(4 ∗1024)])
- void ckb_info ()
- void ckb_init (ckb_runctx ∗context)
- void ckb_parameter (ckb_runctx ∗, const char ∗, const char ∗)
- void ckb_keypress (ckb_runctx ∗, ckb_key ∗, int, int, int)
- void ckb_start (ckb_runctx ∗, int)
- void ckb_time (ckb_runctx ∗, double)
- int ckb_frame (ckb_runctx ∗)
- void ckb_read_params (ckb_runctx ∗ctx)
- int main (int argc, char ∗argv[])

13.13.1 Data Structure Documentation

13.13.1.1 struct ckb_key

Definition at line 131 of file ckb-anim.h.

Collaboration diagram for ckb_key:

Data Fields

unsigned char	a	
unsigned char	b	
unsigned char	g	
char	name[12]	
unsigned char	r	
int	x	
int	y	

13.13.1.2 struct ckb_runctx

Definition at line 138 of file ckb-anim.h.

Collaboration diagram for ckb_runctx:

Data Fields

unsigned	height	
unsigned	keycount	
ckb_key *	keys	
unsigned	width	

13.13.1.3 struct ckb_gradient

Definition at line 152 of file ckb-anim.h.

Collaboration diagram for ckb_gradient:

Data Fields

unsigned char	a[100]	
unsigned char	b[100]	
unsigned char	g[100]	
int	ptcount	
char	pts[100]	
unsigned char	r[100]	

13.13.2 Macro Definition Documentation

13.13.2.1 #define CKB_CONTAINER(*macro*) do { macro } while(0)

Definition at line 57 of file ckb-anim.h.

13.13.2.2 #define CKB_COPYRIGHT(*year, author*) CKB_CONTAINER(printf("author "); printurl(author); printf("\nyear %s\n", year);)

Definition at line 66 of file ckb-anim.h.

13.13.2.3 #define CKB_DESCRIPTION(*description*) CKB_CONTAINER(printf("description "); printurl(description); printf("\n");)

Definition at line 70 of file ckb-anim.h.

13.13.2.4 #define CKB_DOWN 1

Definition at line 52 of file ckb-anim.h.

13.13.2.5 #define CKB_GRAD_MAX 100

Definition at line 151 of file ckb-anim.h.

13.13.2.6 #define CKB_GUID(*guid*) CKB_CONTAINER(printf("guid "); printurl(guid); printf("\n");)

Definition at line 60 of file ckb-anim.h.

13.13.2.7 #define CKB_KEYCLEAR(*context*) CKB_CONTAINER(ckb_key∗ key = context->keys; unsigned count = context->keycount; unsigned i = 0; for(; i < count; i++) key[i].a = key[i].r = key[i].g = key[i].b = 0;)

Definition at line 148 of file ckb-anim.h.

13.13.2.8 #define CKB_KEYNAME_MAX 12

Definition at line 130 of file ckb-anim.h.

Referenced by main().

13.13.2.9 #define CKB_KP_NAME "name"

Definition at line 91 of file ckb-anim.h.

13.13.2.10 #define CKB_KP_NONE "none"

Definition at line 90 of file ckb-anim.h.

13.13.2.11 #define CKB_KP_POSITION "position"

Definition at line 92 of file ckb-anim.h.

13.13.2.12 #define CKB_KPMODE(*mode*) CKB_CONTAINER(printf("kpmode %s\n", mode);)

Definition at line 93 of file ckb-anim.h.

13.13.2.13 #define CKB_LICENSE(*license*) CKB_CONTAINER(printf("license "); printurl(license); printf("\n");)

Definition at line 68 of file ckb-anim.h.

13.13.2.14 #define CKB_LIVEPARAMS(*enable*) CKB_CONTAINER(printf("parammode %s\n", (enable) ? "live" : "static");)

Definition at line 104 of file ckb-anim.h.

13.13.2.15 #define CKB_MAX_WORD (4 ∗ 1024)

Definition at line 238 of file ckb-anim.h.

Referenced by ckb_read_params(), and main().

13.13.2.16 #define CKB_NAME(*name*) CKB_CONTAINER(printf("name "); printurl(name); printf("\n");)

Definition at line 62 of file ckb-anim.h.

13.13.2.17 #define CKB_PARAM(*type, name, prefix, postfix, extra*) CKB_CONTAINER(printf("param %s %s ", type, name); printurl(prefix); printf(" "); printurl(postfix); printf(" "); extra; printf("\n");)

Definition at line 73 of file ckb-anim.h.

13.13.2.18 #define CKB_PARAM_AGRADIENT(*name, prefix, postfix, default*) CKB_PARAM("agradient", name, prefix, postfix, printurl(default))

Definition at line 80 of file ckb-anim.h.

13.13.2.19 #define CKB_PARAM_ANGLE(*name, prefix, postfix, default*) CKB_PARAM("angle", name, prefix, postfix, printf("%ld", (long)(default)))

Definition at line 81 of file ckb-anim.h.

13.13.2.20 #define CKB_PARAM_ARGB(*name, prefix, postfix, a, r, g, b*) CKB_PARAM("argb", name, prefix, postfix, printf("%02x%02x%02x%02x", (unsigned char)(a), (unsigned char)(r), (unsigned char)(g), (unsigned char)(b)))

Definition at line 78 of file ckb-anim.h.

13.13.2.21 #define CKB_PARAM_BOOL(*name, text, default*) CKB_PARAM("bool", name, text, "", printf((default) ? "1" : "0"))

Definition at line 76 of file ckb-anim.h.

13.13.2.22 #define CKB_PARAM_DOUBLE(*name, prefix, postfix, default, min, max*) CKB_PARAM("double", name, prefix, postfix, printf("%lf %lf %lf", (double)(default), (double)(min), (double)(max)))

Definition at line 75 of file ckb-anim.h.

13.13.2.23 #define CKB_PARAM_GRADIENT(*name, prefix, postfix, default*) CKB_PARAM("gradient", name, prefix, postfix, printurl(default))

Definition at line 79 of file ckb-anim.h.

13.13.2.24 #define CKB_PARAM_LABEL(*name, text*) CKB_PARAM("label", name, text, "",)

Definition at line 83 of file ckb-anim.h.

13.13.2.25 #define CKB_PARAM_LONG(*name, prefix, postfix, default, min, max*) CKB_PARAM("long", name, prefix, postfix, printf("%ld %ld %ld", (long)(default), (long)(min), (long)(max)))

Definition at line 74 of file ckb-anim.h.

13.13.2.26 #define CKB_PARAM_RGB(*name, prefix, postfix, r, g, b*) CKB_PARAM("rgb", name, prefix, postfix, printf("%02x%02x%02x", (unsigned char)(r), (unsigned char)(g), (unsigned char)(b)))

Definition at line 77 of file ckb-anim.h.

13.13.2.27 #define CKB_PARAM_STRING(*name, prefix, postfix, default*) CKB_PARAM("string", name, prefix, postfix, printurl(default))

Definition at line 82 of file ckb-anim.h.

13.13.2.28 #define CKB_PARSE_AGRADIENT(*param_name, gradient_ptr*) if(!strcmp(name, param_name) && ckb_scan_grad(value, gradient_ptr, 1))

Definition at line 121 of file ckb-anim.h.

13.13.2.29 #define CKB_PARSE_ANGLE(*param_name, value_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%ld", value_ptr) == 1)

Definition at line 122 of file ckb-anim.h.

13.13.2.30 #define CKB_PARSE_ARGB(*param_name, a_ptr, r_ptr, g_ptr, b_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%2hhx%2hhx%2hhx%2hhx", a_ptr, r_ptr, g_ptr, b_ptr) == 4)

Definition at line 119 of file ckb-anim.h.

13.13.2.31 #define CKB_PARSE_BOOL(*param_name, value_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%u", value_ptr) == 1)

Definition at line 117 of file ckb-anim.h.

13.13.2.32 #define CKB_PARSE_DOUBLE(*param_name, value_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%lf", value_ptr) == 1)

Definition at line 116 of file ckb-anim.h.

13.13.2.33 #define CKB_PARSE_GRADIENT(*param_name, gradient_ptr*) if(!strcmp(name, param_name) && ckb_scan_grad(value, gradient_ptr, 0))

Definition at line 120 of file ckb-anim.h.

13.13.2.34 #define CKB_PARSE_LONG(*param_name, value_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%ld", value_ptr) == 1)

Definition at line 115 of file ckb-anim.h.

13.13.2.35 #define CKB_PARSE_RGB(*param_name, r_ptr, g_ptr, b_ptr*) if(!strcmp(name, param_name) && sscanf(value, "%2hhx%2hhx%2hhx", r_ptr, g_ptr, b_ptr) == 3)

Definition at line 118 of file ckb-anim.h.

13.13.2.36 #define CKB_PARSE_STRING(*param_name*) if(!strcmp(name, param_name))

Definition at line 123 of file ckb-anim.h.

13.13.2.37 #define CKB_PREEMPT(*enable*) CKB_CONTAINER(printf("preempt %s\n", (enable) ? "on" : "off");)

Definition at line 102 of file ckb-anim.h.

13.13.2.38 #define CKB_PRESET_END CKB_CONTAINER(printf("\n");)

Definition at line 87 of file ckb-anim.h.

13.13.2.39 #define CKB_PRESET_PARAM(*name, value*) CKB_CONTAINER(printf(" %s=", name); printurl(value);)

Definition at line 86 of file ckb-anim.h.

13.13.2.40 #define CKB_PRESET_START(*name*) CKB_CONTAINER(printf("preset "); printurl(name);)

Definition at line 85 of file ckb-anim.h.

13.13.2.41 #define CKB_REAL_ANGLE(*angle*) fmod((-(angle) + 90.) ∗ M_PI / 180. + M_PI ∗ 2., M_PI ∗ 2.)

Definition at line 127 of file ckb-anim.h.

13.13.2.42 #define CKB_REPEAT(*enable*) CKB_CONTAINER(printf("repeat %s\n", (enable) ? "on" : "off");)

Definition at line 99 of file ckb-anim.h.

13.13.2.43 #define CKB_TIME_ABSOLUTE "absolute"

Definition at line 96 of file ckb-anim.h.

13.13.2.44 #define CKB_TIME_DURATION "duration"

Definition at line 95 of file ckb-anim.h.

13.13.2.45 #define CKB_TIMEMODE(*mode*) CKB_CONTAINER(printf("time %s\n", mode);)

Definition at line 97 of file ckb-anim.h.

13.13.2.46 #define CKB_UP 0

Definition at line 53 of file ckb-anim.h.

13.13.2.47 #define CKB_VERSION(*version*) CKB_CONTAINER(printf("version "); printurl(version); printf("\n");)

Definition at line 64 of file ckb-anim.h.

13.13.2.48 #define FALSE 0

Definition at line 49 of file ckb-anim.h.

13.13.2.49 #define M_PI 3.14159265358979323846

Definition at line 42 of file ckb-anim.h.

13.13.2.50 #define TRUE 1

Definition at line 46 of file ckb-anim.h.

13.13.3 Function Documentation

13.13.3.1 void ckb_alpha_blend (ckb_key * *key*, float *a*, float *r*, float *g*, float *b*)

Definition at line 283 of file ckb-anim.h.

References ckb_key::a, ckb_key::b, ckb_key::g, and ckb_key::r.

```
283                                                                     {
284     a /= 255.f;
285     float ka = key->a / 255.f;
286     float a2 = a + (1.f - a) * ka;
287     if(a2 == 0.f){
288         key->a = key->r = key->g = key->b = 0;
289         return;
290     }
291     key->a = round(a2 * 255.f);
292     key->r = round((r * a + key->r * ka * (1.f - a)) / a2);
293     key->g = round((g * a + key->g * ka * (1.f - a)) / a2);
294     key->b = round((b * a + key->b * ka * (1.f - a)) / a2);
295 }
```

13.13.3.2 int ckb_frame (ckb_runctx *)

Referenced by main().

Here is the caller graph for this function:

13.13.3.3 void ckb_getline (char *word1[(4 * 1024)]*, char *word2[(4 * 1024)]*, char *word3[(4 * 1024)]*)

Definition at line 239 of file ckb-anim.h.

References urldecode().

Referenced by ckb_read_params(), and main().

```
{
    char line[CKB_MAX_WORD * 3 + 3];
    fgets(line, sizeof(line), stdin);
    word1[0] = word1[1] = word1[2] = 0;
    int res = sscanf(line, "%s %s %s", word1, word2, word3);
    if(res >= 1)
        urldecode(word1, word1);
    if(res >= 2)
        urldecode(word2, word2);
    if(res >= 3)
        urldecode(word3, word3);
    line[strlen(line) - 1] = 0;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.13.3.4 void ckb_grad_color (float * *a*, float * *r*, float * *g*, float * *b*, const ckb_gradient * *grad*, float *pos*)

Definition at line 254 of file ckb-anim.h.

References ckb_gradient::a, ckb_gradient::b, ckb_gradient::g, ckb_gradient::ptcount, ckb_gradient::pts, and ckb_-gradient::r.

```
{
    // Find the points surrounding this position
    int count = grad->ptcount;
    if(count == 0){
        *a = *r = *g = *b = 0.f;
        return;
    }
    int i = 1;
    for(; i < count; i++){
        if(grad->pts[i] >= pos)
            break;
    }
    // Get color by linear interpolation. Premultiply the alpha value so that it returns the expected color
    // (i.e. stops with zero opacity won't contribute to color)
    float distance = grad->pts[i] - grad->pts[i - 1];
    float dx = (pos - grad->pts[i - 1]) / distance;
    float a1 = grad->a[i] / 255., a2 = grad->a[i - 1] / 255.;
    float a3 = *a = a1 * dx + a2 * (1.f - dx);
    if(a3 == 0.){
```

```
        *a = *r = *g = *b = 0.f;
        return;
    }
    *a *= 255.f;
    *r = (grad->r[i] * a1 * dx + grad->r[i - 1] * a2 * (1.f - dx)) / a3;
    *g = (grad->g[i] * a1 * dx + grad->g[i - 1] * a2 * (1.f - dx)) / a3;
    *b = (grad->b[i] * a1 * dx + grad->b[i - 1] * a2 * (1.f - dx)) / a3;
}
```

13.13.3.5 void ckb_info ( )

Referenced by main().

Here is the caller graph for this function:

13.13.3.6 void ckb_init (ckb_runctx * *context*)

Referenced by main().

Here is the caller graph for this function:

13.13.3.7 void ckb_keypress (ckb_runctx *, ckb_key *, int, int, int)

Referenced by main().

Here is the caller graph for this function:

13.13.3.8 void ckb_parameter (ckb_runctx * , const char * , const char *)

Referenced by ckb_read_params().

Here is the caller graph for this function:

13.13.3.9 void ckb_read_params (ckb_runctx * *ctx*)

Definition at line 349 of file ckb-anim.h.

References ckb_getline(), CKB_MAX_WORD, and ckb_parameter().

Referenced by main().

```
349                                     {
350     char cmd[CKB_MAX_WORD], param[CKB_MAX_WORD], value[
      CKB_MAX_WORD];
351     do {
352         ckb_getline(cmd, param, value);
353         if(!*cmd){
354             printf("Error [ckb-main]: Reached EOF reading parameters");
355             return;
356         }
357         if(!strcmp(cmd, "end") && !strcmp(param, "params"))
358             break;
359         if(strcmp(cmd, "param"))
360             continue;
361         ckb_parameter(ctx, param, value);
362     } while(1);
363 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.13.3.10 int ckb_scan_grad (const char * *string*, ckb_gradient * *gradient*, int *alpha*)

Definition at line 298 of file ckb-anim.h.

References ckb_gradient::a, ckb_gradient::b, ckb_gradient::g, ckb_gradient::ptcount, ckb_gradient::pts, and ckb_-gradient::r.

```
298                                                                                 {
299     char pos = -1;
300     unsigned char a = 255, r, g, b;
301     int count = 0;
302     while(1){
303         int scanned = 0;
304         char newpos;
305         if(sscanf(string, "%hhd:%2hhx%2hhx%2hhx%2hhx%n", &newpos, &a, &r, &g, &b, &scanned) != 5)
306             break;
307         string += scanned;
308         // Don't allow stops out-of-order or past 100
309         if(newpos <= pos || newpos > 100)
310             return 0;
311         pos = newpos;
312         if(!alpha)
313             a = 255;
314         gradient->pts[count] = pos;
315         gradient->a[count] = a;
316         gradient->r[count] = r;
317         gradient->g[count] = g;
318         gradient->b[count] = b;
319         count++;
320     }
321     if(count == 0){
322         // If nothing was read, try a single ARGB constant.
323         if(sscanf(string, "%2hhx%2hhx%2hhx%2hhx", &a, &r, &g, &b) != 4)
324             return 0;
325         count = 2;
326         gradient->pts[0] = 0;
327         gradient->pts[1] = 100;
328         gradient->a[0] = a;
329         gradient->a[1] = 0;
330         gradient->r[0] = gradient->r[1] = r;
331         gradient->g[0] = gradient->g[1] = g;
332         gradient->b[0] = gradient->b[1] = b;
333     }
334     if(count < 2)
335         return 0;
336     gradient->ptcount = count;
337     return 1;
338 }
```

13.13.3.11 void ckb_start (ckb_runctx * , int)

Referenced by main().

Here is the caller graph for this function:

13.13.3.12 void ckb_time (ckb_runctx *, double)

Referenced by main().

Here is the caller graph for this function:

13.13.3.13 int main (int *argc*, char * *argv[]*)

Definition at line 365 of file ckb-anim.h.

References ckb_key::a, ckb_key::b, ckb_frame(), ckb_getline(), ckb_info(), ckb_init(), CKB_KEYNAME_MAX, ckb_keypress(), CKB_MAX_WORD, ckb_read_params(), ckb_start(), ckb_time(), ckb_key::g, ckb_runctx::height, ckb_runctx::keycount, ckb_runctx::keys, ckb_key::name, ckb_key::r, ckb_runctx::width, ckb_key::x, and ckb_key::y.

```
365                                 {
366     if(argc == 2){
367         if(!strcmp(argv[1], "--ckb-info")){
368             ckb_info();
369             fflush(stdout);
370             return 0;
371         } else if(!strcmp(argv[1], "--ckb-run")){
372             ckb_runctx ctx;
373             // Read the keymap lines
374             char cmd[CKB_MAX_WORD], param[CKB_MAX_WORD], value[
    CKB_MAX_WORD];
375             // Skip anything up until "begin keymap"
376             do {
377                 ckb_getline(cmd, param, value);
378                 if(!*cmd){
379                     // If end-of-file is reached, abort
380                     printf("Error [ckb-main]: Reached EOF looking for \"begin keymap\"");
381                     return -2;
382                 }
383             } while(strcmp(cmd, "begin") || strcmp(param, "keymap"));
384             ckb_getline(cmd, param, value);
385             unsigned keycount;
386             if(strcmp(cmd, "keycount") || sscanf(param, "%u", &keycount) != 1 || keycount == 0){
387                 // If keycount isn't the next line, something is wrong
388                 printf("Error [ckb-main]: \"begin keymap\" not followed with \"keycount\"");
389                 return -3;
390             }
391             ctx.keys = (ckb_key*)calloc(keycount, sizeof(ckb_key));
```

```
        ctx.keycount = keycount;
        unsigned max_x = 0, max_y = 0;
        unsigned i = 0;
        for(; i < ctx.keycount; i++){
            ckb_getline(cmd, param, value);
            unsigned x, y;
            if(strcmp(cmd, "key") || !*param || !sscanf(value, "%u,%u", &x, &y)){
                i--;
                continue;
            }
            ckb_key* key = ctx.keys + i;
            strncpy(key->name, param, CKB_KEYNAME_MAX);
            key->x = x;
            key->y = y;
            if(x > max_x)
                max_x = x;
            if(y > max_y)
                max_y = y;
        }
        ctx.width = max_x + 1;
        ctx.height = max_y + 1;
        // Skip anything else until "end keymap"
        do {
            ckb_getline(cmd, param, value);
            if(!*cmd){
                printf("Error [ckb-main]: Reached EOF looking for \"end keymap\"");
                return -2;
            }
        } while(strcmp(cmd, "end") || strcmp(param, "keymap"));
        // Run init function
        ckb_init(&ctx);
        // Skip anything else until "begin params"
        do {
            ckb_getline(cmd, param, value);
            if(!*cmd){
                printf("Error [ckb-main]: Reached EOF looking for \"begin params\"");
                return -2;
            }
        } while(strcmp(cmd, "begin") || strcmp(param, "params"));
        // Parse parameters
        ckb_read_params(&ctx);
        // Skip anything else until "begin run"
        do {
            ckb_getline(cmd, param, value);
            if(!*cmd){
                printf("Error [ckb-main]: Reached EOF looking for \"begin run\"");
                return -2;
            }
        } while(strcmp(cmd, "begin") || strcmp(param, "run"));
        // Run the main loop
        printf("begin run\n");
        fflush(stdout);
        while(1){
            ckb_getline(cmd, param, value);
            if(!*cmd || (!strcmp(cmd, "end") && !strcmp(param, "run")))
                break;
            // Parse input
            if(!strcmp(cmd, "start"))
                ckb_start(&ctx, 1);
            else if(!strcmp(cmd, "stop"))
                ckb_start(&ctx, 0);
            else if(!strcmp(cmd, "begin") && !strcmp(param, "params"))
                ckb_read_params(&ctx);
            else if(!strcmp(cmd, "key")){
                int x, y;
                if(sscanf(param, "%d,%d", &x, &y) == 2){
                    // Find a key with this position
                    ckb_key* key = 0;
                    for(i = 0; i < keycount; i++){
                        if(ctx.keys[i].x == x && ctx.keys[i].y == y){
                            key = ctx.keys + i;
                            break;
                        }
                    }
                    if(key)
                        ckb_keypress(&ctx, key, key->x, key->y, !strcmp(value, "down"));
                    else
                        ckb_keypress(&ctx, 0, x, y, !strcmp(value, "down"));
                } else {
                    // Find a key with this name
                    ckb_key* key = 0;
                    for(i = 0; i < keycount; i++){
                        if(!strcmp(ctx.keys[i].name, param)){
                            key = ctx.keys + i;
                            break;
                        }
                    }
```

```
                        if(key)
                            ckb_keypress(&ctx, key, key->x, key->y, !strcmp(value, "down"));
                    }
                } else if(!strcmp(cmd, "frame")){
                    int end = ckb_frame(&ctx);
                    // Output the frame
                    printf("begin frame\n");
                    for(i = 0; i < ctx.keycount; i++){
                        ckb_key* key = ctx.keys + i;
                        printf("argb %s %02hhx%02hhx%02hhx%02hhx\n", key->name, key->
    a, key->r, key->g, key->b);
                    }
                    printf("end frame\n");
                    if(end)
                        break;
                    fflush(stdout);
                } else {
                    double delta = 0.;
                    if(!strcmp(cmd, "time") && sscanf(param, "%lf", &delta) == 1)
                        ckb_time(&ctx, delta);
                }
            }
            printf("end run\n");
            fflush(stdout);
            free(ctx.keys);
            return 0;
        }
    }
    printf("This program must be run from within ckb\n");
    return -1;
}
```

Here is the call graph for this function:

13.13.3.14 void printurl (const char * *src*)

Definition at line 178 of file ckb-anim.h.

```
178                                 {
179     char out[strlen(src) * 3 + 1];
180     char* dst = out;
181     char s;
182     while((s = *src++)){
```

```
        if(s <= ',' || s == '/' ||
                (s >= ':' && s <= '@') ||
                s == '[' || s == ']' ||
                s >= 0x7F){
            char a = s >> 4, b = s & 0xF;
            if(a >= 10)
                a += 'A' - 10;
            else
                a += '0';
            if(b >= 10)
                b += 'A' - 10;
            else
                b += '0';
            dst[0] = '%';
            dst[1] = a;
            dst[2] = b;
            dst += 3;
        } else
            *dst++ = s;
    }
    *dst = '\0';
    printf("%s", out);
}
```

13.13.3.15 void urldecode (char * *dst*, const char * *src*)

Definition at line 208 of file ckb-anim.h.

Referenced by ckb_getline().

```
                                        {
    char a, b;
    char s;
    while((s = *src)){
        if((s == '%') &&
                ((a = src[1]) && (b = src[2])) &&
                (isxdigit(a) && isxdigit(b))){
            if(a >= 'a')
                a -= 'a'-'A';
            if(a >= 'A')
                a -= 'A' - 10;
            else
                a -= '0';
            if(b >= 'a')
                b -= 'a'-'A';
            if(b >= 'A')
                b -= 'A' - 10;
            else
                b -= '0';
            *dst++ = 16*a + b;
            src += 3;
        } else {
            *dst++ = s;
            src++;
        }
    }
    *dst = '\0';
}
```

Here is the caller graph for this function:

13.14 src/ckb/ckbsettings.cpp File Reference

```
#include "ckbsettings.h"
#include "ckbsettingswriter.h"
#include <QThread>
#include <QMutex>
#include <QDebug>
```

Include dependency graph for ckbsettings.cpp:

Macros

- #define lockMutex QMutexLocker locker(backing == _globalSettings ? &settingsMutex : 0)
- #define lockMutexStatic QMutexLocker locker(&settingsMutex)
- #define lockMutexStatic2 QMutexLocker locker2(&settingsMutex)
- #define lockMutexCache QMutexLocker locker(&settingsCacheMutex)

Functions

- QAtomicInt cacheWritesInProgress (0)
- QMutex settingsMutex (QMutex::Recursive)
- QMutex settingsCacheMutex (QMutex::Recursive)
- static QSettings * globalSettings ()

Variables

- static QSettings * _globalSettings = 0
- static QThread * globalThread = 0
- static QMap< QString, QVariant > globalCache

13.14.1 Macro Definition Documentation

13.14.1.1 #define lockMutex QMutexLocker locker(backing == _globalSettings ? &settingsMutex : 0)

Definition at line 15 of file ckbsettings.cpp.

Referenced by CkbSettings::childGroups(), CkbSettings::childKeys(), CkbSettings::contains(), and CkbSettings::value().

13.14.1.2 #define lockMutexCache QMutexLocker locker(&settingsCacheMutex)

Definition at line 18 of file ckbsettings.cpp.

Referenced by CkbSettings::get(), CkbSettings::set(), and CkbSettings::setValue().

13.14.1.3 #define lockMutexStatic QMutexLocker locker(&settingsMutex)

Definition at line 16 of file ckbsettings.cpp.

Referenced by globalSettings(), and CkbSettings::set().

13.14.1.4 #define lockMutexStatic2 QMutexLocker locker2(&settingsMutex)

Definition at line 17 of file ckbsettings.cpp.

Referenced by CkbSettings::get().

13.14.2 Function Documentation

13.14.2.1 QAtomicInt cacheWritesInProgress (0)

Referenced by CkbSettings::cleanUp(), and CkbSettings::isBusy().

Here is the caller graph for this function:

13.14.2.2 static QSettings* globalSettings ( ) [static]

Definition at line 27 of file ckbsettings.cpp.

References _globalSettings, and lockMutexStatic.

Referenced by CkbSettings::get(), and CkbSettings::set().

```
27                                  {
28     if(!_globalSettings){
29         lockMutexStatic;
30         if(!(volatile QSettings*)_globalSettings){   // Check again after locking mutex in
       case another thread created the object
31             // Put the settings object in a separate thread so that it won't lock up the GUI when it syncs
32             globalThread = new QThread;
33             globalThread->start();
34             _globalSettings = new QSettings;
35             qInfo() << "Path  to settings is" << _globalSettings->fileName();
36             _globalSettings->moveToThread(globalThread);
37         }
38     }
39     return _globalSettings;
40 }
```

Here is the caller graph for this function:

13.14.2.3 QMutex settingsCacheMutex (QMutex::Recursive)

13.14.2.4 QMutex settingsMutex (QMutex::Recursive)

13.14.3 Variable Documentation

13.14.3.1 QSettings* _globalSettings = 0 [static]

Definition at line 8 of file ckbsettings.cpp.

Referenced by CkbSettings::cleanUp(), and globalSettings().

13.14.3.2 QMap<QString, QVariant> globalCache [static]

Definition at line 12 of file ckbsettings.cpp.

Referenced by CkbSettings::get(), CkbSettings::set(), and CkbSettings::setValue().

13.14.3.3 QThread* globalThread = 0 [static]

Definition at line 9 of file ckbsettings.cpp.

Referenced by CkbSettings::cleanUp().

13.15 src/ckb/ckbsettings.h File Reference

```
#include <QSettings>
```

```
#include <QStringList>
#include <QMap>
#include <QVariant>
```

Include dependency graph for ckbsettings.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class CkbSettings
- class SGroup

13.16 src/ckb/ckbsettingswriter.cpp File Reference

```
#include "ckbsettingswriter.h"
#include <QMutex>
```

Include dependency graph for ckbsettingswriter.cpp:

Macros

- #define lockMutex QMutexLocker locker(backing == _globalSettings ? &mutex : 0)
- #define lockMutexStatic QMutexLocker locker(&settingsMutex)
- #define lockMutexStatic2 QMutexLocker locker2(&settingsMutex)
- #define lockMutexCache QMutexLocker locker(&settingsCacheMutex)

Variables

- QAtomicInt cacheWritesInProgress
- QMutex settingsMutex
- QMutex settingsCacheMutex

13.16.1 Macro Definition Documentation

13.16.1.1 #define lockMutex QMutexLocker locker(backing == _globalSettings ? &mutex : 0)

Definition at line 7 of file ckbsettingswriter.cpp.

13.16.1.2 #define lockMutexCache QMutexLocker locker(&settingsCacheMutex)

Definition at line 10 of file ckbsettingswriter.cpp.

13.16.1.3 #define lockMutexStatic QMutexLocker locker(&settingsMutex)

Definition at line 8 of file ckbsettingswriter.cpp.

Referenced by CkbSettingsWriter::run().

13.16.1.4 #define lockMutexStatic2 QMutexLocker locker2(&settingsMutex)

Definition at line 9 of file ckbsettingswriter.cpp.

13.16.2 Variable Documentation

13.16.2.1 QAtomicInt cacheWritesInProgress

Referenced by CkbSettingsWriter::CkbSettingsWriter(), and CkbSettingsWriter::~CkbSettingsWriter().

13.16.2.2 QMutex settingsCacheMutex

13.16.2.3 QMutex settingsMutex

13.17 src/ckb/ckbsettingswriter.h File Reference

```
#include <QObject>
#include <QMap>
#include <QSettings>
#include <QStringList>
```

Include dependency graph for ckbsettingswriter.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class CkbSettingsWriter

13.18 src/ckb/colorbutton.cpp File Reference

```
#include "colorbutton.h"
```

```
#include <QColorDialog>
#include <QPainter>
```

Include dependency graph for colorbutton.cpp:

13.19 src/ckb/colorbutton.h File Reference

```
#include <QPushButton>
```

Include dependency graph for colorbutton.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class ColorButton

13.20 src/ckb/colormap.cpp File Reference

`#include "colormap.h"`
Include dependency graph for colormap.cpp:

Functions

- static int qs_strcmp (const void ∗lhs, const void ∗rhs)

13.20.1 Function Documentation

13.20.1.1 static int qs_strcmp (const void ∗ *lhs*, const void ∗ *rhs*) [static]

Definition at line 49 of file colormap.cpp.

Referenced by ColorMap::colorForName(), and ColorMap::init().

```
49                                                  {
50     return strcmp(*(const char**)lhs, *(const char**)rhs);
51 }
```

Here is the caller graph for this function:

13.21 src/ckb/colormap.h File Reference

```
#include <QHash>
#include <QRgb>
#include "keymap.h"
```

Include dependency graph for colormap.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class ColorMap

Typedefs

- typedef QHash< QString, QRgb > QColorMap
- typedef QHashIterator< QString, QRgb > QColorMapIterator
- typedef QMutableHashIterator < QString, QRgb > QMutableColorMapIterator

13.21.1 Typedef Documentation

13.21.1.1 typedef QHash<QString, QRgb> QColorMap

Definition at line 9 of file colormap.h.

13.21.1.2 typedef QHashIterator<QString, QRgb> QColorMapIterator

Definition at line 10 of file colormap.h.

13.21.1.3 typedef QMutableHashIterator<QString, QRgb> QMutableColorMapIterator

Definition at line 11 of file colormap.h.

13.22 src/ckb/extrasettingswidget.cpp File Reference

```
#include "extrasettingswidget.h"
#include "ui_extrasettingswidget.h"
#include "kb.h"
#include "mainwindow.h"
#include "ckbsettings.h"
```

Include dependency graph for extrasettingswidget.cpp:

Variables

- static int lastSharedDimming = -2

13.22.1 Variable Documentation

13.22.1.1 int lastSharedDimming = -2 [static]

Definition at line 8 of file extrasettingswidget.cpp.

Referenced by ExtraSettingsWidget::ExtraSettingsWidget(), and ExtraSettingsWidget::pollUpdates().

13.23 src/ckb/extrasettingswidget.h File Reference

```
#include <QDialog>
```

Include dependency graph for extrasettingswidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class ExtraSettingsWidget

Namespaces

- Ui

13.24 src/ckb/fwupgradedialog.cpp File Reference

```
#include <QDir>
```

```
#include <QMessageBox>
#include "fwupgradedialog.h"
#include "kbfirmware.h"
#include "ui_fwupgradedialog.h"
```

Include dependency graph for fwupgradedialog.cpp:

Data Structures

- struct KbId

Functions

- static const int DIALOG_HEIGHT_MAX (240)
- static float verifyFw (const QByteArray &blob, const QString &features)

Variables

- static KbId ids []
- static const int DIALOG_WIDTH = 420
- static const int DIALOG_HEIGHT_MIN = 200

13.24.1 Data Structure Documentation

13.24.1.1 struct KbId

Definition at line 8 of file fwupgradedialog.cpp.

Collaboration diagram for KbId:

Data Fields

const char *	feature	
short	product	
short	vendor	

13.24.2 Function Documentation

13.24.2.1 static const int DIALOG_HEIGHT_MAX (240) [static]

Referenced by FwUpgradeDialog::exec().

Here is the caller graph for this function:

13.24.2.2 static float verifyFw (const QByteArray & *blob*, const QString & *features*) [static]

Definition at line 85 of file fwupgradedialog.cpp.

References ids.

Referenced by FwUpgradeDialog::exec().

```
85                                                                  {
86     if(blob.length() < 0x0108)
87         return 0.f;
88     const char* bData = blob.data();
89     // Make sure it matches this device based on the vendor and product IDs embedded in the blob
90     bool match = false;
```

```
    for(uint i = 0; i < sizeof(ids)/sizeof(KbId); i++){
        if(!memcmp(&ids[i].vendor, bData + 0x102, 2) && !memcmp(&ids[i].product, bData + 0x104, 2)
                && features.startsWith(ids[i].feature, Qt::CaseInsensitive)){
            match = true;
            break;
        }
    }
    if(!match)
        return 0.f;
    // Copy the version from the blob
    short version;
    memcpy(&version, bData + 0x106, 2);
    // Un-hexify it
    return QString::number(version, 16).toFloat() / 100.f;
}
```

Here is the caller graph for this function:

13.24.3 Variable Documentation

13.24.3.1 const int DIALOG_HEIGHT_MIN = 200 [static]

Definition at line 29 of file fwupgradedialog.cpp.

Referenced by FwUpgradeDialog::FwUpgradeDialog(), and FwUpgradeDialog::on_actionButton_clicked().

13.24.3.2 const int DIALOG_WIDTH = 420 [static]

Definition at line 28 of file fwupgradedialog.cpp.

Referenced by FwUpgradeDialog::exec(), FwUpgradeDialog::FwUpgradeDialog(), and FwUpgradeDialog::on_actionButton_clicked().

13.24.3.3 KbId ids[] [static]

Initial value:

```
= {

    { 0x1b1c, 0x1b17, "corsair k65 rgb" },
    { 0x1b1c, 0x1b13, "corsair k70 rgb" },
    { 0x1b1c, 0x1b11, "corsair k95 rgb" },
    { 0x1b1c, 0x1b15, "corsair strafe monochrome" },
    { 0x1b1c, 0x1b20, "corsair strafe rgb" },

    { 0x1b1c, 0x1b12, "corsair m65 rgb" },
    { 0x1b1c, 0x1b1e, "corsair scimitar rgb" },

    { 0x1b1c, 0x1b32, "corsair sabre optical rgb" }
}
```

Definition at line 14 of file fwupgradedialog.cpp.

Referenced by verifyFw().

13.25 src/ckb/fwupgradedialog.h File Reference

```
#include <QCloseEvent>
```

```
#include <QDialog>
#include <QEventLoop>
#include "kb.h"
```

Include dependency graph for fwupgradedialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class FwUpgradeDialog

Namespaces

- Ui

13.26 src/ckb/gradientbutton.cpp File Reference

```
#include <cmath>
#include <cstdio>
#include <QPainter>
#include "gradientbutton.h"
#include "gradientdialog.h"
```

Include dependency graph for gradientbutton.cpp:

13.27 src/ckb/gradientbutton.h File Reference

```
#include <QPushButton>
```

Include dependency graph for gradientbutton.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class GradientButton

13.28 src/ckb/gradientdialog.cpp File Reference

```
#include <cmath>
#include <QMessageBox>
#include <QPainter>
#include <QSettings>
#include "ckbsettings.h"
#include "gradientdialog.h"
#include "ui_gradientdialog.h"
```

Include dependency graph for gradientdialog.cpp:

Variables

- static const QString prefsPath = "Stored Gradients"

13.28.1 Variable Documentation

13.28.1.1 const QString prefsPath = "Stored Gradients" [static]

Definition at line 9 of file gradientdialog.cpp.

Referenced by GradientDialog::GradientDialog(), and GradientDialog::~GradientDialog().

13.29 src/ckb/gradientdialog.h File Reference

```
#include <QDialog>
#include <QListWidgetItem>
#include <QMap>
```

Include dependency graph for gradientdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class GradientDialog
- struct GradientDialog::Preset

Namespaces

- Ui

13.30 src/ckb/gradientdialogwidget.cpp File Reference

```
#include <cmath>
#include <QPainter>
#include <QPropertyAnimation>
#include "gradientdialogwidget.h"
```

Include dependency graph for gradientdialogwidget.cpp:

13.31 src/ckb/gradientdialogwidget.h File Reference

```
#include <QWidget>
#include <QMouseEvent>
#include <QPaintEvent>
```

Include dependency graph for gradientdialogwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class GradientDialogWidget

13.32 src/ckb/kb.cpp File Reference

```
#include <fcntl.h>
#include <QSet>
#include <QUrl>
#include <QMutex>
#include <QDateTime>
#include "kb.h"
#include "kbmanager.h"
```

Include dependency graph for kb.cpp:

Variables

- static QSet< Kb * > activeDevices
- static QSet< QString > notifyPaths
- static QMutex notifyPathMutex

13.32.1 Variable Documentation

13.32.1.1 QSet<Kb*> activeDevices [static]

Definition at line 10 of file kb.cpp.

Referenced by Kb::dither(), Kb::frameRate(), Kb::Kb(), Kb::layout(), Kb::macroDelay(), Kb::mouseAccel(), Kb::scrollSpeed(), and Kb::~Kb().

13.32.1.2 QMutex notifyPathMutex [static]

Definition at line 13 of file kb.cpp.

Referenced by Kb::Kb(), and Kb::run().

13.32.1.3 QSet<QString> notifyPaths [static]

Definition at line 12 of file kb.cpp.

Referenced by Kb::Kb(), Kb::run(), and Kb::~Kb().

13.33 src/ckb/kb.h File Reference

```
#include <QObject>
#include <QFile>
#include <QThread>
#include "kbprofile.h"
```

Include dependency graph for kb.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Kb

13.34 src/ckb/kbanim.cpp File Reference

```
#include <cmath>
#include <QDateTime>
#include <QMetaEnum>
#include <QDebug>
#include "ckbsettings.h"
#include "kbanim.h"
```

Include dependency graph for kbanim.cpp:

Typedefs

- typedef float(∗ blendFunc)(float, float)

Functions

- static float blendNormal (float bg, float fg)
- static float blendAdd (float bg, float fg)
- static float blendSubtract (float bg, float fg)
- static float blendMultiply (float bg, float fg)
- static float blendDivide (float bg, float fg)

Variables

- static blendFunc functions [5] = { blendNormal, blendAdd, blendSubtract, blendMultiply, blendDivide }

13.34.1 Typedef Documentation

13.34.1.1 typedef float(∗ blendFunc)(float, float)

Definition at line 362 of file kbanim.cpp.

13.34.2 Function Documentation

13.34.2.1 static float blendAdd (float *bg*, float *fg*) [static]

Definition at line 337 of file kbanim.cpp.

```
337                                         {
338     float res = bg + fg;
339     if(res > 1.f)
340         res = 1.f;
341     return res;
342 }
```

13.34.2.2 static float blendDivide (float *bg*, float *fg*) [static]

Definition at line 355 of file kbanim.cpp.

```
355                                         {
356     float res = bg / fg;
357     if(res > 1.f)
358         res = 1.f;
359     return res;
360 }
```

13.34.2.3 static float blendMultiply (float *bg*, float *fg*) [static]

Definition at line 351 of file kbanim.cpp.

```
351                                         {
352     return bg * fg;
353 }
```

13.34.2.4 static float blendNormal (float *bg*, float *fg*) [static]

Definition at line 333 of file kbanim.cpp.

```
333                                                 {
334     return fg;
335 }
```

13.34.2.5 static float blendSubtract (float *bg*, float *fg*) [static]

Definition at line 344 of file kbanim.cpp.

```
344                                                 {
345     float res = bg - fg;
346     if(res < 0.f)
347         res = 0.f;
348     return res;
349 }
```

13.34.3 Variable Documentation

13.34.3.1 blendFunc functions[5] = { blendNormal, blendAdd, blendSubtract, blendMultiply, blendDivide } [static]

Definition at line 363 of file kbanim.cpp.

Referenced by KbAnim::blend().

13.35 src/ckb/kbanim.h File Reference

```
#include <QObject>
#include "ckbsettings.h"
#include "animscript.h"
#include "keymap.h"
```

Include dependency graph for kbanim.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbAnim

13.36 src/ckb/kbanimwidget.cpp File Reference

```
#include <QDateTime>
#include <QMenu>
#include "animsettingdialog.h"
#include "kbanimwidget.h"
#include "ui_kbanimwidget.h"
```

Include dependency graph for kbanimwidget.cpp:

13.37 src/ckb/kbanimwidget.h File Reference

```
#include <QListWidgetItem>
#include <QTimer>
#include <QWidget>
#include "animscript.h"
#include "kbanim.h"
#include "kblight.h"
```

Include dependency graph for kbanimwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbAnimWidget

Namespaces

- Ui

13.38 src/ckb/kbbind.cpp File Reference

```
#include <QDateTime>
#include <QUrl>
#include "ckbsettings.h"
#include "kbbind.h"
#include "kbmode.h"
#include "kb.h"
#include "qdebug.h"
```

Include dependency graph for kbbind.cpp:

13.39 src/ckb/kbbind.h File Reference

```
#include <QFile>
#include <QHash>
#include <QObject>
#include <QProcess>
#include "ckbsettings.h"
#include "keymap.h"
#include "keyaction.h"
```

Include dependency graph for kbbind.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbBind

13.40 src/ckb/kbbindwidget.cpp File Reference

```
#include <QMessageBox>
#include "kbbindwidget.h"
#include "modeselectdialog.h"
#include "rebindwidget.h"
#include "ui_kbbindwidget.h"
```

Include dependency graph for kbbindwidget.cpp:

13.41 src/ckb/kbbindwidget.h File Reference

```
#include <QWidget>
#include "kbbind.h"
#include "kbprofile.h"
```

Include dependency graph for kbbindwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbBindWidget

Namespaces

- Ui

13.42 src/ckb/kbfirmware.cpp File Reference

```
#include "kbfirmware.h"
#include "kbmanager.h"
#include "quazip/quazip.h"
#include "quazip/quazipfile.h"
#include <QDateTime>
#include <QDebug>
```

Include dependency graph for kbfirmware.cpp:

Functions

- static QString tableName (const QString &features)

Variables

- static const quint64 AUTO_CHECK_TIME = 60 ∗ 60 ∗ 1000

13.42.1 Function Documentation

13.42.1.1 static QString tableName (const QString & *features*) [static]

Definition at line 153 of file kbfirmware.cpp.

Referenced by KbFirmware::_fileForBoard(), and KbFirmware::_latestForBoard().

```
153                                                 {
154     QStringList components = features.split(" ");
155     if(components.length() < 2)
156         return "";
157     // First two components are vendor and model
158     QString vendorModel = components[0].toUpper() + "-" + components[1].toUpper();
159     // Add "RGB" on RGB boards
160     if(features.contains("rgb") && !features.contains("monochrome"))
161         vendorModel += "RGB";
162     return vendorModel;
163 }
```

Here is the caller graph for this function:

13.42.2 Variable Documentation

13.42.2.1 const quint64 AUTO_CHECK_TIME = 60 ∗ 60 ∗ 1000 [static]

Definition at line 9 of file kbfirmware.cpp.

Referenced by KbFirmware::_checkUpdates().

13.43 src/ckb/kbfirmware.h File Reference

```
#include "kb.h"
#include <QObject>
#include <QtNetwork/QtNetwork>
```

Include dependency graph for kbfirmware.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbFirmware
- struct KbFirmware::FW

13.44 src/ckb/kblight.cpp File Reference

```
#include <cmath>
#include <QDateTime>
#include <QSet>
#include "kblight.h"
#include "kbmode.h"
```

Include dependency graph for kblight.cpp:

Functions

- static float sToL (float srgb)
- static float lToS (float linear)
- QRgb monoRgb (float r, float g, float b)

Variables

- static int _shareDimming = -1
- static QSet< KbLight * > activeLights

13.44.1 Function Documentation

13.44.1.1 static float lToS (float *linear*) [static]

Definition at line 277 of file kblight.cpp.

Referenced by KbLight::frameUpdate(), and monoRgb().

```
277                                 {
278     if(linear <= 0.0031308f)
279         return 12.92f * linear * 255.f;
280     return (1.055f * pow(linear, 1.f / 2.4f) - 0.055f) * 255.f;
281 }
```

Here is the caller graph for this function:

13.44.1.2 QRgb monoRgb (float *r*, float *g*, float *b*)

Definition at line 284 of file kblight.cpp.

References lToS(), and sToL().

Referenced by KbLight::base(), KbLight::frameUpdate(), and KeyWidget::paintEvent().

```
284                                         {
285     // It's important to use a linear colorspace for this, otherwise the colors will appear inconsistent
286     // Note that although we could use linear space for alpha blending or the animation blending functions,
        we don't.
287     // The reason for this is that photo manipulation programs don't do it either, so even though the
        result would technically be more correct,
288     // it would look wrong to most people.
289     r = sToL(r);
290     g = sToL(g);
291     b = sToL(b);
292     int value = round(lToS((r + g + b) / 3.f));
293     return qRgb(value, value, value);
294 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.44.1.3 static float sToL (float *srgb*) [static]

Definition at line 270 of file kblight.cpp.

Referenced by KbLight::frameUpdate(), and monoRgb().

```
270                                 {
271     srgb /= 255.f;
272     if(srgb <= 0.04045f)
273         return srgb / 12.92f;
274     return pow((srgb + 0.055f) / 1.055f, 2.4f);
275 }
```

Here is the caller graph for this function:

13.44.2 Variable Documentation

13.44.2.1 int _shareDimming = -1 [static]

Definition at line 7 of file kblight.cpp.

Referenced by KbLight::dimming(), KbLight::open(), and KbLight::shareDimming().

13.44.2.2 QSet<KbLight*> activeLights [static]

Definition at line 8 of file kblight.cpp.

Referenced by KbLight::close(), KbLight::open(), KbLight::shareDimming(), and KbLight::~KbLight().

13.45 src/ckb/kblight.h File Reference

```
#include <QFile>
#include <QObject>
#include <QSet>
#include <QSettings>
#include "animscript.h"
#include "kbanim.h"
#include "keymap.h"
#include "colormap.h"
```

Include dependency graph for kblight.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbLight

13.46 src/ckb/kblightwidget.cpp File Reference

```
#include "animadddialog.h"
#include "ckbsettings.h"
#include "kblightwidget.h"
#include "ui_kblightwidget.h"
```

Include dependency graph for kblightwidget.cpp:

13.47 src/ckb/kblightwidget.h File Reference

```
#include <QWidget>
#include <QColor>
#include <QFile>
#include <QResizeEvent>
#include "kblight.h"
#include "keywidget.h"
```

Include dependency graph for kblightwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbLightWidget

Namespaces

- Ui

13.48 src/ckb/kbmanager.cpp File Reference

`#include "kbmanager.h"`
Include dependency graph for kbmanager.cpp:

Variables

- QString devpath = "/dev/input/ckb%1"

13.48.1 Variable Documentation

13.48.1.1 QString devpath = "/dev/input/ckb%1"

Definition at line 4 of file kbmanager.cpp.

Referenced by KbManager::scanKeyboards().

13.49 src/ckb/kbmanager.h File Reference

```
#include <QObject>
#include <QTimer>
#include <cmath>
#include <QSet>
#include "kb.h"
```

Include dependency graph for kbmanager.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbManager

Macros

- #define DAEMON_UNAVAILABLE_STR "<unavailable>"

13.49.1 Macro Definition Documentation

13.49.1.1 #define DAEMON_UNAVAILABLE_STR "<unavailable>"

Definition at line 12 of file kbmanager.h.

Referenced by KbManager::ckbDaemonVersionF(), KbManager::scanKeyboards(), and MainWindow::updateVersion().

13.50 src/ckb/kbmode.cpp File Reference

```
#include "kbmode.h"
#include "kb.h"
```

Include dependency graph for kbmode.cpp:

13.51 src/ckb/kbmode.h File Reference

```
#include <QObject>
#include "kblight.h"
#include "kbbind.h"
#include "kbperf.h"
```

Include dependency graph for kbmode.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct UsbId
- class KbMode

13.52 src/ckb/kbperf.cpp File Reference

```
#include "kbperf.h"
#include "kbmode.h"
#include "kb.h"
#include "media.h"
#include <cmath>
```

Include dependency graph for kbperf.cpp:

Macros

- #define map_last(map) ((map).last())

13.52.1 Macro Definition Documentation

13.52.1.1 #define map_last(*map*) ((map).last())

Definition at line 8 of file kbperf.cpp.

Referenced by KbPerf::popDpi().

13.53 src/ckb/kbperf.h File Reference

```
#include <QFile>
```

```
#include <QMap>
#include <QPoint>
#include "ckbsettings.h"
#include "keymap.h"
```

Include dependency graph for kbperf.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbPerf

13.54 src/ckb/kbprofile.cpp File Reference

```
#include "kbprofile.h"
#include "kb.h"
```

Include dependency graph for kbprofile.cpp:

13.55 src/ckb/kbprofile.h File Reference

```
#include <QList>
#include <QObject>
#include <QSettings>
#include <QString>
#include <QUuid>
#include "kbmode.h"
```

Include dependency graph for kbprofile.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbProfile

13.56 src/ckb/kbprofiledialog.cpp File Reference

```
#include <QMenu>
#include "kbprofiledialog.h"
#include "ui_kbprofiledialog.h"
```

Include dependency graph for kbprofiledialog.cpp:

13.57 src/ckb/kbprofiledialog.h File Reference

```
#include <QDialog>
#include "kbwidget.h"
```

Include dependency graph for kbprofiledialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbProfileDialog

Namespaces

- Ui

13.58 src/ckb/kbwidget.cpp File Reference

```
#include <cmath>
#include <QFileDialog>
#include <QMenu>
#include <QMessageBox>
#include <QUrl>
#include "ckbsettings.h"
#include "fwupgradedialog.h"
#include "kbfirmware.h"
#include "kbwidget.h"
#include "kblightwidget.h"
#include "kbprofiledialog.h"
#include "ui_kbwidget.h"
#include "ui_kblightwidget.h"
```

Include dependency graph for kbwidget.cpp:

13.59 src/ckb/kbwidget.h File Reference

```
#include <QFile>
#include <QListWidgetItem>
#include <QWidget>
#include "kb.h"
```

Include dependency graph for kbwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KbWidget

Namespaces

- Ui

13.60 src/ckb/keyaction.cpp File Reference

```
#include <qdebug.h>
#include "keyaction.h"
#include "kb.h"
#include "kbanim.h"
#include "kbprofile.h"
#include <QDateTime>
#include <QUrl>
#include <cstring>
#include <cstdio>
```

Include dependency graph for keyaction.cpp:

Variables

- static const int ANIM_ONCE = 0x1
- static const int ANIM_KRSTOP = 0x2

13.60.1 Variable Documentation

13.60.1.1 const int ANIM_KRSTOP = 0x2 [static]

Definition at line 173 of file keyaction.cpp.

Referenced by KeyAction::animAction(), and KeyAction::animInfo().

13.60.1.2 const int ANIM_ONCE = 0x1 [static]

Definition at line 173 of file keyaction.cpp.

Referenced by KeyAction::animAction(), and KeyAction::animInfo().

13.61 src/ckb/keyaction.h File Reference

```
#include <QObject>
#include <QProcess>
#include "keymap.h"
```

Include dependency graph for keyaction.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KeyAction

13.62 src/ckb/keymap.cpp File Reference

```
#include <clocale>
#include <QMap>
#include "keymap.h"
```

Include dependency graph for keymap.cpp:

Data Structures

- struct KeyPatch

Macros

- #define NS 12, 12
- #define KEYCOUNT_K95 (sizeof(K95Keys) / sizeof(Key))
- #define ANSI_ENTER_X 199
- #define ANSI_ENTER_Y 51
- #define ANSI_ENTER_W 26
- #define ANSI_ENTER_H 12
- #define ANSI_LSHIFT_X 45
- #define ANSI_LSHIFT_W 26
- #define PATCH_COUNT(patch) (sizeof(patch) / sizeof(KeyPatch))
- #define patch(map, patches) _patch(map, patches, PATCH_COUNT(patches))
- #define K95_WIDTH 298
- #define K95_HEIGHT 76
- #define K70_X_START 38
- #define K70_WIDTH (K95_WIDTH - K70_X_START)
- #define K70_HEIGHT K95_HEIGHT
- #define K65_WIDTH 209
- #define K65_HEIGHT K70_HEIGHT
- #define K65_TOP_COUNT (sizeof(K65TopRow) / sizeof(Key))
- #define KSTRAFE_X_START 12
- #define KSTRAFE_WIDTH (K70_WIDTH + (KSTRAFE_X_START * 2))
- #define KSTRAFE_HEIGHT K95_HEIGHT
- #define KEYCOUNT_M65 (sizeof(M65Keys) / sizeof(Key))

- #define M65_WIDTH 52
- #define M65_HEIGHT 67
- #define KEYCOUNT_SABRE (sizeof(SabreKeys) / sizeof(Key))
- #define SABRE_WIDTH M65_WIDTH
- #define SABRE_HEIGHT M65_HEIGHT
- #define KEYCOUNT_SCIM (sizeof(ScimKeys) / sizeof(Key))
- #define SCIM_WIDTH M65_WIDTH
- #define SCIM_HEIGHT M65_HEIGHT
- #define N_MODELS KeyMap::_MODEL_MAX
- #define N_LAYOUTS KeyMap::_LAYOUT_MAX

Functions

- static void _patch (QHash< QString, Key > &map, const KeyPatch *patches, int patchCount)
- static void patchISO (QHash< QString, Key > &map)
- static void patchANSI (QHash< QString, Key > &map)
- static QHash< QString, Key > getMap (KeyMap::Model model, KeyMap::Layout layout)

Variables

- static const Key K95Keys []
- static const KeyPatch patchDK []
- static const KeyPatch patchEU []
- static const KeyPatch patchFR []
- static const KeyPatch patchDE []
- static const KeyPatch patchIT []
- static const KeyPatch patchNO []
- static const KeyPatch patchMX []
- static const KeyPatch patchES []
- static const KeyPatch patchSE []
- static const KeyPatch patchDvorak []
- static const Key K65TopRow []
- static const Key KStrafeKeys []
- static const Key M65Keys []
- static const Key SabreKeys []
- static const Key ScimKeys []
- static QHash< QString, Key > K95BaseMap
- static QHash< QString, Key > standardMaps [KeyMap::_MODEL_MAX][KeyMap::_LAYOUT_MAX]

13.62.1 Data Structure Documentation

13.62.1.1 struct KeyPatch

Definition at line 30 of file keymap.cpp.

Collaboration diagram for KeyPatch:

Data Fields

const char *	_friendlyName	
const char *	_storageName	
const char *	name	

13.62.2 Macro Definition Documentation

13.62.2.1 #define ANSI_ENTER_H 12

Definition at line 25 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.2 #define ANSI_ENTER_W 26

Definition at line 24 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.3 #define ANSI_ENTER_X 199

Definition at line 22 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.4 #define ANSI_ENTER_Y 51

Definition at line 23 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.5 #define ANSI_LSHIFT_W 26

Definition at line 27 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.6 #define ANSI_LSHIFT_X 45

Definition at line 26 of file keymap.cpp.

Referenced by patchANSI().

13.62.2.7 #define K65_HEIGHT K70_HEIGHT

Definition at line 143 of file keymap.cpp.

13.62.2.8 #define K65_TOP_COUNT (sizeof(K65TopRow) / sizeof(Key))

Definition at line 148 of file keymap.cpp.

Referenced by getMap().

13.62.2.9 #define K65_WIDTH 209

Definition at line 142 of file keymap.cpp.

Referenced by getMap(), and KeyMap::modelWidth().

13.62.2.10 #define K70_HEIGHT K95_HEIGHT

Definition at line 139 of file keymap.cpp.

13.62.2.11 #define K70_WIDTH (K95_WIDTH - K70_X_START)

Definition at line 138 of file keymap.cpp.

Referenced by KeyMap::modelWidth().

13.62.2.12 #define K70_X_START 38

Definition at line 137 of file keymap.cpp.

Referenced by getMap().

13.62.2.13 #define K95_HEIGHT 76

Definition at line 134 of file keymap.cpp.

Referenced by KeyMap::modelHeight().

13.62.2.14 #define K95_WIDTH 298

Definition at line 133 of file keymap.cpp.

Referenced by KeyMap::modelWidth().

13.62.2.15 #define KEYCOUNT_K95 (sizeof(K95Keys) / sizeof(Key))

Definition at line 19 of file keymap.cpp.

Referenced by getMap().

13.62.2.16 #define KEYCOUNT_M65 (sizeof(M65Keys) / sizeof(Key))

Definition at line 170 of file keymap.cpp.

Referenced by getMap().

13.62.2.17 #define KEYCOUNT_SABRE (sizeof(SabreKeys) / sizeof(Key))

Definition at line 183 of file keymap.cpp.

Referenced by getMap().

13.62.2.18 #define KEYCOUNT_SCIM (sizeof(ScimKeys) / sizeof(Key))

Definition at line 200 of file keymap.cpp.

Referenced by getMap().

13.62.2.19 #define KSTRAFE_HEIGHT K95_HEIGHT

Definition at line 153 of file keymap.cpp.

13.62.2.20 #define KSTRAFE_WIDTH (K70_WIDTH + (KSTRAFE_X_START * 2))

Definition at line 152 of file keymap.cpp.

Referenced by KeyMap::modelWidth().

13.62.2.21 #define KSTRAFE_X_START 12

Definition at line 151 of file keymap.cpp.

Referenced by getMap().

13.62.2.22 #define M65_HEIGHT 67

Definition at line 173 of file keymap.cpp.

Referenced by KeyMap::modelHeight().

13.62.2.23 #define M65_WIDTH 52

Definition at line 172 of file keymap.cpp.

Referenced by KeyMap::modelWidth().

13.62.2.24 #define N_LAYOUTS KeyMap::_LAYOUT_MAX

Definition at line 207 of file keymap.cpp.

Referenced by getMap().

13.62.2.25 #define N_MODELS KeyMap::_MODEL_MAX

Definition at line 206 of file keymap.cpp.

Referenced by getMap().

13.62.2.26 #define NS 12, 12

Definition at line 6 of file keymap.cpp.

13.62.2.27 #define patch(*map, patches*) _patch(map, patches, PATCH_COUNT(patches))

Definition at line 106 of file keymap.cpp.

Referenced by getMap().

13.62.2.28 #define PATCH_COUNT(patch) (sizeof(patch) / sizeof(KeyPatch))

Definition at line 105 of file keymap.cpp.

13.62.2.29 #define SABRE_HEIGHT M65_HEIGHT

Definition at line 186 of file keymap.cpp.

13.62.2.30 #define SABRE_WIDTH M65_WIDTH

Definition at line 185 of file keymap.cpp.

13.62.2.31 #define SCIM_HEIGHT M65_HEIGHT

Definition at line 203 of file keymap.cpp.

13.62.2.32 #define SCIM_WIDTH M65_WIDTH

Definition at line 202 of file keymap.cpp.

13.62.3 Function Documentation

13.62.3.1 static void _patch (QHash< QString, Key > & *map,* const KeyPatch * *patches,* int *patchCount*) [static]

Definition at line 107 of file keymap.cpp.

References Key::_friendlyName, and Key::_storageName.

```
107                                                                                                {
108     for(const KeyPatch* p = patches; p < patches + patchCount; p++){
109         Key& key = map[p->name];
110         key._storageName = p->_storageName;
```

```
        key._friendlyName = p->_friendlyName;
    }
}
```

13.62.3.2 static QHash<QString, Key> getMap (KeyMap::Model *model*, KeyMap::Layout *layout*) [static]

Definition at line 210 of file keymap.cpp.

References KeyMap::DE, KeyMap::DK, KeyMap::ES, KeyMap::EU, KeyMap::EU_DVORAK, KeyMap::FR, KeyMap::GB_DVORAK, Key::height, KeyMap::isISO(), KeyMap::IT, KeyMap::K65, K65_TOP_COUNT, K65_WIDTH, KeyMap::K70, K70_X_START, KeyMap::K95, K95BaseMap, KEYCOUNT_K95, KEYCOUNT_M65, KEYCOUNT_SABRE, KEYCOUNT_SCIM, KSTRAFE_X_START, KeyMap::M65, KeyMap::MX, N_LAYOUTS, N_MODELS, KeyMap::NO, patch, patchANSI(), patchISO(), KeyMap::SABRE, KeyMap::SCIMITAR, KeyMap::SE, standardMaps, KeyMap::STRAFE, KeyMap::US_DVORAK, Key::width, Key::x, and Key::y.

```
210                                                                                 {
211     if(model < 0 || layout < 0 || model >= N_MODELS || layout >=
    N_LAYOUTS)
212         return QHash<QString, Key>();
213     // Return the map if it's already filled out
214     QHash<QString, Key>& map = standardMaps[model][layout];
215     if(!map.empty())
216         return map;
217     // Otherwise, create it
218     switch(model){
219     case KeyMap::K95:{
220         // The K95 maps serve as bases for all the other keyboards
221         // Fetch the master map, or create it if not yet done
222         if(K95BaseMap.empty()){
223             for(const Key* key = K95Keys; key < K95Keys +
    KEYCOUNT_K95; key++)
224                 K95BaseMap[key->name] = *key;
225         }
226         map = K95BaseMap;
227         // Patch the map for the layout
228         switch(layout){
229         case KeyMap::DK:
230             patch(map, patchDK);
231             break;
232         case KeyMap::EU_DVORAK:
233             patch(map, patchDvorak);    // fall through
234         case KeyMap::EU:
235             patch(map, patchEU);
236             break;
237         case KeyMap::GB_DVORAK:
238         case KeyMap::US_DVORAK:
239             patch(map, patchDvorak);
240             break;
241         case KeyMap::FR:
242             patch(map, patchFR);
243             break;
244         case KeyMap::DE:
245             patch(map, patchDE);
246             break;
247         case KeyMap::IT:
248             patch(map, patchIT);
249             break;
250         case KeyMap::NO:
251             patch(map, patchNO);
252             break;
253         case KeyMap::MX:
254             patch(map, patchMX);
255             break;
256         case KeyMap::ES:
257             patch(map, patchES);
258             break;
259         case KeyMap::SE:
260             patch(map, patchSE);
261             break;
262         default:;
263             // English QWERTY - no patch needed
264         }
265         if(KeyMap::isISO(layout))
266             patchISO(map);
267         else
268             patchANSI(map);
269         // Done! return the map
270         break;
271     }
```

```
    case KeyMap::K70:{
        // The K70 maps are based on the K95 maps. However all the keys are shifted left and the G keys are removed
        map = getMap(KeyMap::K95, layout);
        QMutableHashIterator<QString, Key> i(map);
        while(i.hasNext()){
            i.next();
            // Move key to left. Remove it if it fell off the edge
            if((i.value().x -= K70_X_START) < 0)
                i.remove();
        }
        // Remove the M buttons as well
        map.remove("mr");
        map.remove("m1");
        map.remove("m2");
        map.remove("m3");
        // Done!
        break;
    }
    case KeyMap::K65:{
        // The K65 maps additionally remove the numpad and have a modified top row
        map = getMap(KeyMap::K70, layout);
        QMutableHashIterator<QString, Key> i(map);
        while(i.hasNext()){
            i.next();
            if(i.value().x >= K65_WIDTH)
                i.remove();
        }
        for(const Key* key = K65TopRow; key < K65TopRow + K65_TOP_COUNT; key++)
            map[key->name] = *key;
        // Done!
        break;
    }
    case KeyMap::STRAFE:{
        // The Strafe RGB maps are based on the K70 map minus the media keys
        map = getMap(KeyMap::K70, layout);
        //move light and lock right
        map["light"].x=285 - K70_X_START;
        //map["light"].hasLed=false;
        map["lock"].x=297 - K70_X_START;
        //map["lock"].hasLed=false;
        // move everything right to make the space for the left sidelight
        QMutableHashIterator<QString, Key> i(map);
        while(i.hasNext()){
            i.next();
            i.value().x += KSTRAFE_X_START;
        }
        // Add Strafe lights and keys
        map["lsidel"] = KStrafeKeys[0];
        map["rsidel"] = KStrafeKeys[1];
        map["logo"] = KStrafeKeys[2];
        map["fn"] = KStrafeKeys[3];
        map.remove("rwin");
        // remove media controls
        map.remove("mute");
        map.remove("volup");
        map.remove("voldn");
        map.remove("stop");
        map.remove("prev");
        map.remove("play");
        map.remove("next");
        // Done!
        break;
    }
    case KeyMap::M65:{
        // M65 isn't a keyboard; all mouse maps are unique.
        for(const Key* key = M65Keys; key < M65Keys + KEYCOUNT_M65; key++){
            // Keyboard keys are written from the center because that's where the LEDs are, but the mouse buttons are odd shapes so they're
            // written from the upper left
            Key translatedKey = *key;
            translatedKey.x += translatedKey.width / 2;
            translatedKey.y += translatedKey.height / 2;
            map[key->name] = translatedKey;
        }
        // Mice also have no layout patches - no other changes necessary
        break;
    }
    case KeyMap::SABRE:{
        // Scimitar mouse
        for(const Key* key = SabreKeys; key < SabreKeys + KEYCOUNT_SABRE; key++){
            // Like the M65, the keys are upper-left justified
            Key translatedKey = *key;
            translatedKey.x += translatedKey.width / 2;
```

```
            translatedKey.y += translatedKey.height / 2;
            map[key->name] = translatedKey;
        }
        break;
    }
    case KeyMap::SCIMITAR:{
        // Scimitar mouse
        for(const Key* key = ScimKeys; key < ScimKeys +
    KEYCOUNT_SCIM; key++){
            Key translatedKey = *key;
            translatedKey.x += translatedKey.width / 2;
            translatedKey.y += translatedKey.height / 2;
            map[key->name] = translatedKey;
        }
        break;
    }
    default:;    // <- stop GCC from complaining
    }
    // Map is finished, return result
    return map;
}
```

Here is the call graph for this function:

13.62.3.3 static void patchANSI (QHash< QString, Key > & *map*) [static]

Definition at line 119 of file keymap.cpp.

References ANSI_ENTER_H, ANSI_ENTER_W, ANSI_ENTER_X, ANSI_ENTER_Y, ANSI_LSHIFT_W, ANSI_LSHIFT_X, Key::height, Key::width, Key::x, and Key::y.

Referenced by getMap().

```
{
    map.remove("bslash_iso");
    map.remove("hash");
    Key& enter = map["enter"];
    enter.x = ANSI_ENTER_X;
    enter.y = ANSI_ENTER_Y;
    enter.width = ANSI_ENTER_W;
    enter.height = ANSI_ENTER_H;
    Key& lshift = map["lshift"];
    lshift.x = ANSI_LSHIFT_X;
    lshift.width = ANSI_LSHIFT_W;
}
```

Here is the caller graph for this function:

13.62.3.4 static void patchISO (QHash< QString, Key > & *map*) [static]

Definition at line 116 of file keymap.cpp.

Referenced by getMap().

```
116                                                 {
117     map.remove("bslash");
118 }
```

Here is the caller graph for this function:

13.62.4 Variable Documentation

13.62.4.1 const Key K65TopRow[] [static]

Initial value:

```
= {
    {0, "Brightness", "light", 164 -  38 , 0, 12, 12, true, true}, {0, "Mute", "mute", 176 -  38 , 0, 12,
      12, true, true}, {0, "Volume Down", "voldn", 192 -  38 , 0, 14, 8, true, true}, {0, "Volume Up", "volup", 205
       -  38 , 0, 14, 8, true, true}, {0, "Windows Lock", "lock", 222 -  38 , 0, 12, 12, true, true}
}
```

Definition at line 145 of file keymap.cpp.

13.62.4.2 QHash<QString, Key> K95BaseMap [static]

Definition at line 208 of file keymap.cpp.

Referenced by getMap().

13.62.4.3 const Key K95Keys[] [static]

Initial value:

```
= {
    {0, 0, "mr", 38, 0,  12, 12 , true, true}, {0, 0, "m1", 50, 0,  12, 12 , true, true}, {0, 0, "m2", 62,
      0,  12, 12 , true, true}, {0, 0, "m3", 74, 0,  12, 12 , true, true}, {0, "Brightness", "light", 222, 0,  12,
       12 , true, true}, {0, "Windows Lock", "lock", 234, 0,  12, 12 , true, true}, {0, "Mute", "mute", 273, 0, 13
      , 8, true, true}, {0, "Volume Up", "volup", 290, -2, 18, 6, false, true}, {0, "Volume down", "voldn", 290, 2
      , 18, 6, false, true},
    {0, 0, "g1", 0, 14,  12, 12 , true, true}, {0, 0, "g2", 11, 14,  12, 12 , true, true}, {0, 0, "g3", 22,
       14,  12, 12 , true, true}, {0, "Esc", "esc", 38, 14,  12, 12 , true, true}, {0, 0, "f1", 58, 14,  12, 12 ,
      true, true}, {0, 0, "f2", 70, 14,  12, 12 , true, true}, {0, 0, "f3", 82, 14,  12, 12 , true, true}, {0, 0,
      "f4", 94, 14,  12, 12 , true, true}, {0, 0, "f5", 114, 14,  12, 12 , true, true}, {0, 0, "f6", 126, 14,  12,
       12 , true, true}, {0, 0, "f7", 138, 14,  12, 12 , true, true}, {0, 0, "f8", 150, 14,  12, 12 , true, true},
       {0, 0, "f9", 170, 14,  12, 12 , true, true}, {0, 0, "f10", 182, 14,  12, 12 , true, true}, {0, 0, "f11",
      194, 14,  12, 12 , true, true}, {0, 0, "f12", 206, 14,  12, 12 , true, true}, {0, "Print Screen\nSysRq", "
      prtscn", 222, 14,  12, 12 , true, true}, {0, "Scroll Lock", "scroll", 234, 14,  12, 12 , true, true}, {0, "Pause
      \nBreak", "pause", 246, 14,  12, 12 , true, true}, {0, "Stop", "stop", 262, 14, 12, 8, true, true}, {0, "
      Previous", "prev", 273, 14, 13, 8, true, true}, {0, "Play/Pause", "play", 285, 14, 13, 8, true, true}, {0, "
      Next", "next", 296, 14, 12, 8, true, true},
    {0, 0, "g4", 0, 25,  12, 12 , true, true}, {0, 0, "g5", 11, 25,  12, 12 , true, true}, {0, 0, "g6", 22,
       25,  12, 12 , true, true}, {0, "`", "grave", 38, 27,  12, 12 , true, true}, {0, 0, "1", 50, 27,  12, 12 ,
      true, true}, {0, 0, "2", 62, 27,  12, 12 , true, true}, {0, 0, "3", 74, 27,  12, 12 , true, true}, {0, 0, "4"
      , 86, 27,  12, 12 , true, true}, {0, 0, "5", 98, 27,  12, 12 , true, true}, {0, 0, "6", 110, 27,  12, 12 ,
      true, true}, {0, 0, "7", 122, 27,  12, 12 , true, true}, {0, 0, "8", 134, 27,  12, 12 , true, true}, {0, 0, "
      9", 146, 27,  12, 12 , true, true}, {0, 0, "0", 158, 27,  12, 12 , true, true}, {0, "-", "minus", 170, 27,
      12, 12 , true, true}, {0, "=", "equal", 182, 27,  12, 12 , true, true}, {0, "Backspace", "bspace", 200, 27,
      24, 12, true, true}, {0, "Insert", "ins", 222, 27,  12, 12 , true, true}, {0, "Home", "home", 234, 27,  12,
      12 , true, true}, {0, "Page Up", "pgup", 246, 27,  12, 12 , true, true}, {0, "Num Lock", "numlock", 261, 27,
        12, 12 , true, true}, {0, "NumPad /", "numslash", 273, 27,  12, 12 , true, true}, {0, "NumPad *", "numstar
      ", 285, 27,  12, 12 , true, true}, {0, "NumPad -", "numminus", 297, 27,  12, 12 , true, true},
    {0, 0, "g7", 0, 39,  12, 12 , true, true}, {0, 0, "g8", 11, 39,  12, 12 , true, true}, {0, 0, "g9", 22,
       39,  12, 12 , true, true}, {0, "Tab", "tab", 41, 39, 18, 12, true, true}, {0, 0, "q", 56, 39,  12, 12 ,
      true, true}, {0, 0, "w", 68, 39,  12, 12 , true, true}, {0, 0, "e", 80, 39,  12, 12 , true, true}, {0, 0, "r",
      92, 39,  12, 12 , true, true}, {0, 0, "t", 104, 39,  12, 12 , true, true}, {0, 0, "y", 116, 39,  12, 12 ,
      true, true}, {0, 0, "u", 128, 39,  12, 12 , true, true}, {0, 0, "i", 140, 39,  12, 12 , true, true}, {0, 0, "o
      ", 152, 39,  12, 12 , true, true}, {0, 0, "p", 164, 39,  12, 12 , true, true}, {0, "[", "lbrace", 176, 39,
      12, 12 , true, true}, {0, "]", "rbrace", 188, 39,  12, 12 , true, true}, {0, "\\", "bslash", 203, 39, 18, 12
      , true, true}, {0, "Enter", "enter", 203, 39, 18, 24, true, true}, {0, "Delete", "del", 222, 39,  12, 12 ,
      true, true}, {0, "End", "end", 234, 39,  12, 12 , true, true}, {0, "Page Down", "pgdn", 246, 39,  12, 12 ,
      true, true}, {0, "NumPad 7", "num7", 261, 39,  12, 12 , true, true}, {0, "NumPad 8", "num8", 273, 39,  12, 12
      , true, true}, {0, "NumPad 9", "num9", 285, 39,  12, 12 , true, true}, {0, "NumPad +", "numplus", 297, 45,
      12, 24, true, true},
    {0, 0, "g10", 0, 50,  12, 12 , true, true}, {0, 0, "g11", 11, 50,  12, 12 , true, true}, {0, 0, "g12",
      22, 50,  12, 12 , true, true}, {0, "Caps Lock", "caps", 42, 51, 20, 12, true, true}, {0, 0, "a", 59, 51,  12
      , 12 , true, true}, {0, 0, "s", 71, 51,  12, 12 , true, true}, {0, 0, "d", 83, 51,  12, 12 , true, true}, {0
      , 0, "f", 95, 51,  12, 12 , true, true}, {0, 0, "g", 107, 51,  12, 12 , true, true}, {0, 0, "h", 119, 51,
      12, 12 , true, true}, {0, 0, "j", 131, 51,  12, 12 , true, true}, {0, 0, "k", 143, 51,  12, 12 , true, true},
       {0, 0, "l", 155, 51,  12, 12 , true, true}, {0, ";", "colon", 167, 51,  12, 12 , true, true}, {0, "'", "
      quote", 179, 51,  12, 12 , true, true}, {0, "#", "hash", 191, 51,  12, 12 , true, true}, {0, "NumPad 4", "num4"
      , 261, 51,  12, 12 , true, true}, {0, "NumPad 5", "num5", 273, 51,  12, 12 , true, true}, {0, "NumPad 6", "
      num6", 285, 51,  12, 12 , true, true},
    {0, 0, "g13", 0, 64,  12, 12 , true, true}, {0, 0, "g14", 11, 64,  12, 12 , true, true}, {0, 0, "g15",
      22, 64,  12, 12 , true, true}, {0, "Left Shift", "lshift", 39, 63, 14, 12, true, true}, {"bslash", "\\", "
      bslash_iso", 53, 63,  12, 12 , true, true}, {0, 0, "z", 65, 63,  12, 12 , true, true}, {0, 0, "x", 77, 63,  12
      , 12 , true, true}, {0, 0, "c", 89, 63,  12, 12 , true, true}, {0, 0, "v", 101, 63,  12, 12 , true, true}, {
      0, 0, "b", 113, 63,  12, 12 , true, true}, {0, 0, "n", 125, 63,  12, 12 , true, true}, {0, 0, "m", 137, 63,
       12, 12 , true, true}, {0, ",", "comma", 149, 63,  12, 12 , true, true}, {0, ".", "dot", 161, 63,  12, 12 ,
      true, true}, {0, "/", "slash", 173, 63,  12, 12 , true, true}, {0, "Right Shift", "rshift", 196, 63, 32, 12,
       true, true}, {0, "Up", "up", 234, 63,  12, 12 , true, true}, {0, "NumPad 1", "num1", 261, 63,  12, 12 ,
      true, true}, {0, "NumPad 2", "num2", 273, 63,  12, 12 , true, true}, {0, "NumPad 3", "num3", 285, 63,  12, 12 ,
       true, true}, {0, "NumPad Enter", "numenter", 297, 69, 12, 24, true, true},
    {0, 0, "g16", 0, 75,  12, 12 , true, true}, {0, 0, "g17", 11, 75,  12, 12 , true, true}, {0, 0, "g18",
      22, 75,  12, 12 , true, true}, {0, "Left Ctrl", "lctrl", 40, 75, 16, 12, true, true}, {0, "Left Windows", "
      lwin", 54, 75,  12, 12 , true, true}, {0, "Left Alt", "lalt", 67, 75, 14, 12, true, true}, {0, "Space", "
      space", 116, 75, 84, 12, true, true}, {0, "Right Alt", "ralt", 165, 75, 14, 12, true, true}, {0, "Right Windows"
      , "rwin", 178, 75,  12, 12 , true, true}, {0, "Menu", "rmenu", 190, 75,  12, 12 , true, true}, {0, "Right
       Ctrl", "rctrl", 204, 75, 16, 12, true, true}, {0, "Left", "left", 222, 75,  12, 12 , true, true}, {0, "Down",
      "down", 234, 75,  12, 12 , true, true}, {0, "Right", "right", 246, 75,  12, 12 , true, true}, {0, "NumPad 0"
      , "num0", 267, 75, 24, 12, true, true}, {0, "NumPad .", "numdot", 285, 75,  12, 12 , true, true}
}
```

Definition at line 10 of file keymap.cpp.

13.62.4.4 const Key KStrafeKeys[] [static]

Initial value:

```
= {
```

```
    {0, "Sidelight", "lsidel", 0,   76  /2,  12 ,   76  , true, false},
    {0, "Sidelight", "rsidel",  ( ( 298  -  38 )  + ( 12  * 2)) ,   76  /2,  12 ,   76  , true, false},
    {0, "Logo", "logo",  12 , 0,  12, 12 , true, false},
    {0, "Function", "fn", 152, 75,  12, 12 , true, true}
}
```

Definition at line 155 of file keymap.cpp.

13.62.4.5 const Key M65Keys[] [static]

Initial value:

```
= {
    {0, "Left Mouse", "mouse1", 8, 0, 14, 32, false, true}, {0, "Right Mouse", "mouse2", 30, 0, 14, 32,
      false, true}, {0, "Middle Mouse", "mouse3", 22, 8, 8, 7, false, true},
    {0, "Wheel Up", "wheelup", 22, 4, 8, 5, false, true}, {0, "Wheel Down", "wheeldn", 22, 14, 8, 5, false,
       true}, {0, "Wheel Light", "front", 22, 15, 8, 8, true, false},
    {0, "DPI Up", "dpiup", 22, 19, 8, 6, false, true}, {0, "DPI Light", "dpi", 22, 24, 8, 8, true, false},
      {0, "DPI Down", "dpidn", 22, 31, 8, 6, false, true},
    {0, "Forward", "mouse5", 5, 24, 5, 9, false, true}, {0, "Back", "mouse4", 5, 33, 5, 10, false, true}, {
      0, "Sniper", "sniper", 0, 25, 5, 15, false, true},
    {0, "Logo", "back", 14, 55, 24, 12, true, false}
}
```

Definition at line 163 of file keymap.cpp.

13.62.4.6 const KeyPatch patchDE[] [static]

Initial value:

```
= {
    {"caret", "^", "grave"}, {"ss", "ß", "minus"}, {"grave", "´", "equal"},
    {"z", "Z", "y"}, {"ue", "Ü", "lbrace"}, {"plus", "+", "rbrace"},
    {"oe", "Ö", "colon"}, {"ae", "Ä", "quote"},
    {"angle", "<", "bslash_iso"}, {"y", "Y", "z"}, {"minus", "-", "slash"}
}
```

Definition at line 55 of file keymap.cpp.

13.62.4.7 const KeyPatch patchDK[] [static]

Initial value:

```
= {
    {0, "§", "grave"}, {0, "+", "minus"}, {0, "´", "equal"},
    {0, "Å", "lbrace"}, {0, "¨", "rbrace"},
    {0, "Æ", "colon"}, {0, "Ø", "quote"}, {0, "’", "hash"},
    {0, "<", "bslash_iso"}, {0, "-", "slash"},
}
```

Definition at line 36 of file keymap.cpp.

13.62.4.8 const KeyPatch patchDvorak[] [static]

Initial value:

```
= {
    {0, "[", "minus"}, {0, "]", "equal"},
    {0, "′", "q"}, {0, ",", "w"}, {0, ".", "e"}, {0, "P", "r"}, {0, "Y", "t"}, {0, "F", "y"}, {0, "G", "u"}
      , {0, "C", "i"}, {0, "R", "o"}, {0, "L", "p"}, {0, "/", "lbrace"}, {0, "=", "rbrace"},
    {0, "O", "s"}, {0, "E", "d"}, {0, "U", "f"}, {0, "I", "g"}, {0, "D", "h"}, {0, "H", "j"}, {0, "T", "k"}
      , {0, "N", "l"}, {0, "S", "colon"}, {0, "-", "quote"},
    {0, ";", "z"}, {0, "Q", "x"}, {0, "J", "c"}, {0, "K", "v"}, {0, "X", "b"}, {0, "B", "n"}, {0, "W", "
      comma"}, {0, "V", "dot"}, {0, "Z", "slash"},
}
```

Definition at line 97 of file keymap.cpp.

13.62.4.9 const KeyPatch patchES[] [static]

Initial value:

```
= {
    {"oa", "°", "grave"}, {"quote", "´", "minus"}, {"lexclam", "¡", "equal"},
    {"grave", "`", "lbrace"}, {"plus", "+", "rbrace"},
    {"nn", "Ñ", "colon"}, {"accent", "´", "quote"}, {"cc", "Ç", "hash"},
    {"angle", "<", "bslash_iso"}, {"minus", "-", "slash"},
}
```

Definition at line 83 of file keymap.cpp.

13.62.4.10 const KeyPatch patchEU[] [static]

Initial value:

```
= {
    {0, "\\ (R)", "hash"},
    {0, "\\ (L)", "bslash_iso"}
}
```

Definition at line 43 of file keymap.cpp.

13.62.4.11 const KeyPatch patchFR[] [static]

Initial value:

```
= {
    {"sup2", "²", "grave"}, {0, "&", "1"}, {0, "É", "2"}, {0, "\"", "3"}, {0, "´", "4"}, {0, "(", "5"}, {0,
      "-", "6"}, {0, "È", "7"}, {0, "_", "8"}, {0, "Ç", "9"}, {0, "À", "0"}, {"rparen", ")", "minus"},
    {"a", "A", "q"}, {"z", "Z", "w"}, {"caret", "^", "lbrace"}, {"dollar", "$", "rbrace"},
    {"q", "Q", "a"}, {"m", "M", "colon"}, {"percent", "Ù", "quote"}, {"star", "*", "hash"},
    {"angle", "<", "bslash_iso"}, {"w", "W", "z"}, {"comma", ",", "m"}, {"semicolon", ";", "comma"}, {"
      colon", ":", "dot"}, {"exclam", "!", "slash"},
}
```

Definition at line 48 of file keymap.cpp.

13.62.4.12 const KeyPatch patchIT[] [static]

Initial value:

```
= {
    {0, "\\", "grave"}, {0, "´", "minus"}, {0, "Ì", "equal"},
    {0, "È", "lbrace"}, {0, "+", "rbrace"},
    {0, "Ò", "colon"}, {0, "À", "quote"}, {0, "Ù", "hash"},
    {0, "<", "bslash_iso"}, {0, "-", "slash"},
}
```

Definition at line 62 of file keymap.cpp.

13.62.4.13 const KeyPatch patchMX[] [static]

Initial value:

```
= {
    {0, "|", "grave"}, {0, "´", "minus"}, {0, "¿", "equal"},
    {0, "´", "lbrace"}, {0, "+", "rbrace"},
    {0, "Ñ", "colon"}, {0, "{", "quote"}, {0, "}", "hash"},
    {0, "<", "bslash_iso"}, {0, "-", "slash"},
}
```

Definition at line 76 of file keymap.cpp.

13.62.4.14 const KeyPatch patchNO[] [static]

Initial value:

```
= {
    {0, "§", "grave"}, {0, "+", "minus"}, {0, "´", "equal"},
    {0, "Å", "lbrace"}, {0, "¨", "rbrace"},
    {0, "Ø", "colon"}, {0, "Æ", "quote"}, {0, "’", "hash"},
    {0, "<", "bslash_iso"}, {0, "-", "slash"},
}
```

Definition at line 69 of file keymap.cpp.

13.62.4.15 const KeyPatch patchSE[] [static]

Initial value:

```
= {
    {"section", "§", "grave"}, {"plus", "+", "minus"}, {"grave", "´", "equal"},
    {"aa", "Å", "lbrace"}, {"umlaut", "¨", "rbrace"},
    {"oe", "Ö", "colon"}, {"ae", "Ä", "quote"}, {"quote", "’", "hash"},
    {"angle", "<", "bslash_iso"}, {"minus", "-", "slash"},
}
```

Definition at line 90 of file keymap.cpp.

13.62.4.16 const Key SabreKeys[] [static]

Initial value:

```
= {
    {0, "Left Mouse", "mouse1", 8, 0, 14, 32, false, true}, {0, "Right Mouse", "mouse2", 30, 0, 14, 32,
      false, true}, {0, "Middle Mouse", "mouse3", 22, 9, 8, 7, false, true}, {0, "Front light", "front", 8, -2, 14, 8
      , true, false },
    {0, "Wheel Up", "wheelup", 22, 5, 8, 5, false, true}, {0, "Wheel Down", "wheeldn", 22, 15, 8, 5, false,
       true}, {0, "Wheel Light", "wheel", 22, 5, 8, 15, true, false}, {0, "Extra button", "thumb1", 22, 20, 8, 18,
       false, true},
    {0, "DPI Up", "dpiup", 5, 3, 5, 7, false, true}, {0, "DPI Down", "dpidn", 5, 10, 5, 7, false, true}, {0
      , "DPI Light", "dpi", 5, 4, 5, 12, true, false},
    {0, "Forward", "mouse5", 5, 24, 5, 9, false, true}, {0, "Back", "mouse4", 5, 33, 5, 10, false, true},
    {0, "Logo", "back", 14, 50, 24, 12, true, false}
}
```

Definition at line 176 of file keymap.cpp.

13.62.4.17 const Key ScimKeys[] [static]

Initial value:

```
= {
    {0, "Left Mouse", "mouse1", 8, 0, 14, 32, false, true}, {0, "Right Mouse", "mouse2", 30, 0, 12, 32,
      false, true}, {0, "Middle Mouse", "mouse3", 22, 9, 8, 6, false, true}, {0, "Front light", "front", 30, 0, 12, 8
      , true, false },
    {0, "Wheel Up", "wheelup", 22, 3, 8, 6, false, true}, {0, "Wheel Down", "wheeldn", 22, 14, 8, 6, false,
       true}, {0, "Wheel Light", "wheel", 22, 3, 8, 17, true, false},
    {0, "DPI Up", "dpiup", 22, 19, 8, 9, false, true}, {0, "DPI Light", "dpi", 1, 12, 8, 4, true, false}, {
      0, "DPI Down", "dpidn", 22, 28, 8, 9, false, true},
    {0, "Thumb light", "thumb", 0, 21, 10, 24, true, false},
    {0, "1", "thumb1", -13, 18, 7, 7, false, true}, {0, "2", "thumb2", -6, 18, 7, 7, false, true}, {0, "3",
       "thumb3", 1, 18, 7, 7, false, true},
    {0, "4", "thumb4", -13, 25, 7, 7, false, true}, {0, "5", "thumb5", -6, 25, 7, 7, false, true}, {0, "6",
       "thumb6", 1, 25, 7, 7, false, true},
    {0, "7", "thumb7", -13, 32, 7, 7, false, true}, {0, "8", "thumb8", -6, 32, 7, 7, false, true}, {0, "9",
       "thumb9", 1, 32, 7, 7, false, true},
    {0, "10", "thumb10", -13, 39, 7, 7, false, true}, {0, "11", "thumb11", -6, 39, 7, 7, false, true}, {0,
      "12", "thumb12", 1, 39, 7, 7, false, true},
    {0, "Logo", "back", 14, 50, 24, 16, true, false}
}
```

Definition at line 189 of file keymap.cpp.

13.62.4.18 QHash<QString, Key> standardMaps[KeyMap::_MODEL_MAX][KeyMap::_LAYOUT_MAX] [static]

Definition at line 209 of file keymap.cpp.

Referenced by getMap().

13.63 src/ckb/keymap.h File Reference

```
#include <QColor>
#include <QHash>
```

Include dependency graph for keymap.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct Key
- class KeyMap

13.64 src/ckb/keywidget.cpp File Reference

```
#include <cmath>
#include <QGraphicsDropShadowEffect>
#include <QGraphicsPixmapItem>
#include <QGraphicsScene>
#include <QPainter>
#include "keywidget.h"
#include "keyaction.h"
#include "kbbind.h"
```

Include dependency graph for keywidget.cpp:

Functions

- QRgb monoRgb (float r, float g, float b)

Variables

- static const int KEY_SIZE = 12
- static QImage ∗ m65Overlay = 0
- static QImage ∗ sabOverlay = 0
- static QImage ∗ scimOverlay = 0

13.64.1 Function Documentation

13.64.1.1 QRgb monoRgb (float *r*, float *g*, float *b*)

Definition at line 284 of file kblight.cpp.

References lToS(), and sToL().

Referenced by KbLight::base(), KbLight::frameUpdate(), and KeyWidget::paintEvent().

```
284                                         {
285     // It's important to use a linear colorspace for this, otherwise the colors will appear inconsistent
286     // Note that although we could use linear space for alpha blending or the animation blending functions,
        we don't.
287     // The reason for this is that photo manipulation programs don't do it either, so even though the
        result would technically be more correct,
288     // it would look wrong to most people.
289     r = sToL(r);
290     g = sToL(g);
291     b = sToL(b);
292     int value = round(lToS((r + g + b) / 3.f));
293     return qRgb(value, value, value);
294 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.64.2 Variable Documentation

13.64.2.1 const int KEY_SIZE = 12 [static]

Definition at line 10 of file keywidget.cpp.

Referenced by KeyWidget::drawInfo(), and KeyWidget::map().

13.64.2.2 QImage* m65Overlay = 0 [static]

Definition at line 12 of file keywidget.cpp.

Referenced by KeyWidget::paintEvent().

13.64.2.3 QImage * sabOverlay = 0 [static]

Definition at line 12 of file keywidget.cpp.

Referenced by KeyWidget::paintEvent().

13.64.2.4 QImage * scimOverlay = 0 [static]

Definition at line 12 of file keywidget.cpp.

Referenced by KeyWidget::paintEvent().

13.65 src/ckb/keywidget.h File Reference

```
#include <QBitArray>
#include <QMouseEvent>
#include <QPaintEvent>
#include <QWidget>
#include "keymap.h"
#include "colormap.h"
```

Include dependency graph for keywidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KeyWidget

13.66 src/ckb/kperfwidget.cpp File Reference

```
#include "kperfwidget.h"
#include "ui_kperfwidget.h"
#include "modeselectdialog.h"
#include <cmath>
```

Include dependency graph for kperfwidget.cpp:

13.67 src/ckb/kperfwidget.h File Reference

```
#include <QWidget>
#include <QCheckBox>
#include <QComboBox>
#include <QSignalMapper>
#include "kbperf.h"
#include "kbprofile.h"
#include "colorbutton.h"
```

Include dependency graph for kperfwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class KPerfWidget
- struct KPerfWidget::IndicatorUi

Namespaces

- Ui

13.67.1 Data Structure Documentation

13.67.1.1 struct KPerfWidget::IndicatorUi

Definition at line 48 of file kperfwidget.h.

Collaboration diagram for KPerfWidget::IndicatorUi:

Data Fields

ColorButton *	color1	
ColorButton *	color2	
ColorButton *	color3	

QCheckBox *	enable	
QComboBox *	hwEnable	

13.68 src/ckb/layoutdialog.cpp File Reference

```
#include "layoutdialog.h"
#include "kb.h"
#include "ui_layoutdialog.h"
```

Include dependency graph for layoutdialog.cpp:

13.69 src/ckb/layoutdialog.h File Reference

```
#include <QDialog>
#include "keymap.h"
```

Include dependency graph for layoutdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class LayoutDialog

Namespaces

- Ui

13.70 src/ckb/macroreader.cpp File Reference

```
#include <qdebug.h>
#include "macroreader.h"
```

Include dependency graph for macroreader.cpp:

13.71 src/ckb/macroreader.h File Reference

```
#include <QObject>
#include <QFile>
#include <QThread>
#include <QPlainTextEdit>
```

Include dependency graph for macroreader.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class MacroReaderThread

  The MacroReaderThread class is responsible for reading Macro Key Values. It is created as a separate thread (worker thread) for reading macro commands from an fresh opened notify channel. Standard notify channel for macro definitions is number 2.
- class MacroReader

  The MacroReader class creates a worker thread object. It does a connect do delayed deletion of thread local variables in the case the worker thread terminates.

13.72 src/ckb/main.cpp File Reference

```
#include "mainwindow.h"
#include <QApplication>
#include <QDateTime>
#include <QSharedMemory>
#include <QCommandLineParser>
#include <cstring>
#include <unistd.h>
#include <signal.h>
#include <errno.h>
```

Include dependency graph for main.cpp:

Macros

- #define SHMEM_SIZE 128 ∗ 1024
- #define SHMEM_SIZE_V015 16

Enumerations

- enum CommandLineParseResults { CommandLineOK, CommandLineError, CommandLineVersionRequested, CommandLineHelpRequested, CommandLineClose, CommandLineBackground }

Functions

- QSharedMemory appShare ("ckb")
- CommandLineParseResults parseCommandLine (QCommandLineParser &parser, QString ∗errorMessage)

  parseCommandLine - Setup options and parse command line arguments.
- static bool pidActive (const QStringList &lines)
- static bool isRunning (const char ∗command)
- int main (int argc, char ∗argv[])

13.72.1 Macro Definition Documentation

13.72.1.1 #define SHMEM_SIZE 128 ∗ 1024

Definition at line 20 of file main.cpp.

Referenced by isRunning().

13.72.1.2 #define SHMEM_SIZE_V015 16

Definition at line 21 of file main.cpp.

Referenced by isRunning().

13.72.2 Enumeration Type Documentation

13.72.2.1 enum CommandLineParseResults

Enumerator

CommandLineOK

CommandLineError

CommandLineVersionRequested

CommandLineHelpRequested

CommandLineClose

CommandLineBackground

Definition at line 24 of file main.cpp.

```
24                                {
25     CommandLineOK,
26     CommandLineError,
27     CommandLineVersionRequested,
28     CommandLineHelpRequested,
29     CommandLineClose,
30     CommandLineBackground
31 };
```

13.72.3 Function Documentation

13.72.3.1 QSharedMemory appShare ("ckb")

Referenced by isRunning().

Here is the caller graph for this function:

13.72.3.2 static bool isRunning (const char * *command*) [static]

Definition at line 109 of file main.cpp.

References appShare(), pidActive(), SHMEM_SIZE, and SHMEM_SIZE_V015.

Referenced by main().

```
109                                         {
110     // Try to create shared memory (if successful, application was not already running)
111     if(!appShare.create(SHMEM_SIZE) || !appShare.lock()){
112         // Lock existing shared memory
113         if(!appShare.attach() || !appShare.lock())
114             return true;
115         bool running = false;
116         if(appShare.size() == SHMEM_SIZE_V015){
117             // Old shmem - no PID listed so assume the process is running, and print the command directly
        to the buffer
118             if(command){
119                 void* data = appShare.data();
```

```
                snprintf((char*)data, SHMEM_SIZE_V015, "%s", command);
            }
            running = true;
        } else {
            // New shmem. Scan the contents of the shared memory for a PID
            QStringList lines = QString((const char*)appShare.constData()).split("\n");
            if(pidActive(lines)){
                running = true;
                // Append the command
                if(command){
                    lines.append(QString("Option ") + command);
                    QByteArray newMem = lines.join("\n").left(SHMEM_SIZE).toLatin1();
                    // Copy the NUL byte as well as the string
                    memcpy(appShare.data(), newMem.constData(), newMem.length() + 1);
                }
            }
        }
        if(running){
            appShare.unlock();
            return true;
        }
    }
    // Not already running. Initialize the shared memory with our PID
    snprintf((char*)appShare.data(), appShare.size(), "PID %ld", (long)getpid());
    appShare.unlock();
    return false;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.72.3.3 int main (int *argc*, char * *argv[]*)

Definition at line 148 of file main.cpp.

References CommandLineBackground, CommandLineClose, CommandLineError, CommandLineHelpRequested, CommandLineOK, CommandLineVersionRequested, disableAppNap(), isRunning(), and parseCommandLine().

```
148                                 {
149     // Setup main application
150     QApplication a(argc, argv);
```

```

    // Setup names and versions
    QCoreApplication::setOrganizationName("ckb");
    QCoreApplication::setApplicationVersion(CKB_VERSION_STR);
    QCoreApplication::setApplicationName("ckb");

    // Setup argument parser
    QCommandLineParser parser;
    QString errorMessage;
    parser.setApplicationDescription("Open Source Corsair Input Device Driver for Linux and OSX.");
    bool background = 0;

    // Although the daemon runs as root, the GUI needn't and shouldn't be, as it has the potential to corrupt settings data.
    if(getuid() == 0){
        printf("The ckb GUI should not be run as root.\n");
        return 0;
    }

    // Seed the RNG for UsbIds
    qsrand(QDateTime::currentMSecsSinceEpoch());
#ifdef Q_OS_MACX
    disableAppNap();
#endif
#if QT_VERSION >= QT_VERSION_CHECK(5, 3, 0)
    // Enable HiDPI support
    qApp->setAttribute(Qt::AA_UseHighDpiPixmaps);
#endif

    // Parse arguments
    switch (parseCommandLine(parser, &errorMessage)) {
    case CommandLineOK:
        // If launched with no argument
        break;
    case CommandLineError:
        fputs(qPrintable(errorMessage), stderr);
        fputs("\n\n", stderr);
        fputs(qPrintable(parser.helpText()), stderr);
        return 1;
    case CommandLineVersionRequested:
        // If launched with --version, print version info and then quit
        printf("%s %s\n", qPrintable(QCoreApplication::applicationName()),
               qPrintable(QCoreApplication::applicationVersion()));
        return 0;
    case CommandLineHelpRequested:
        // If launched with --help, print help and then quit
        parser.showHelp();
        return 0;
    case CommandLineClose:
        // If launched with --close, kill existing app
        if (isRunning("Close"))
            printf("Asking existing instance to close.\n");
        else
            printf("ckb is not running.\n");
        return 0;
    case CommandLineBackground:
        // If launched with --background, launch in background
        background = 1;
        break;
    }

    // Launch in background if requested, or if re-launching a previous session
    if(qApp->isSessionRestored())
            background = 1;
    if(isRunning(background ? 0 : "Open")){
        printf("ckb is already running. Exiting.\n");
        return 0;
    }
    MainWindow w;
    if(!background)
        w.show();

    return a.exec();
}
```

Here is the call graph for this function:

13.72.3.4 CommandLineParseResults parseCommandLine (QCommandLineParser & *parser*, QString * *errorMessage*)

Parameters

parser	parser instance to use for parse the arguments
errorMessage	argument parse error message

Returns

integer, representing the requested argument

Definition at line 41 of file main.cpp.

References CommandLineBackground, CommandLineClose, CommandLineError, CommandLineHelpRequested, CommandLineOK, and CommandLineVersionRequested.

Referenced by main().

```
41                                                                                                  {
42     // setup parser to interpret -abc as -a -b -c
43     parser.setSingleDashWordOptionMode(QCommandLineParser::ParseAsCompactedShortOptions);
44
45     /* add command line options */
46     // add -v, --version
47     const QCommandLineOption versionOption = parser.addVersionOption();
48     // add -h, --help (/? on windows)
49     const QCommandLineOption helpOption = parser.addHelpOption();
50     // add -b, --background
51     const QCommandLineOption backgroundOption(QStringList() << "b" << "background",
52                                               "Starts in background, without displaying the main window.");
53     parser.addOption(backgroundOption);
54     // add -c, --close
55     const QCommandLineOption closeOption(QStringList() << "c" << "close",
56                                          "Causes already running instance (if any) to exit.");
57     parser.addOption(closeOption);
58
59     /* parse arguments */
60     if (!parser.parse(QCoreApplication::arguments())) {
61         // set error, if there already are some
62         *errorMessage = parser.errorText();
63         return CommandLineError;
64     }
65
66     /* return requested operation/setup */
67     if (parser.isSet(versionOption)) {
68         // print version and exit
69         return CommandLineVersionRequested;
70     }
71
72     if (parser.isSet(helpOption)) {
```

```
        // print help and exit
        return CommandLineHelpRequested;
    }

    if (parser.isSet(backgroundOption)) {
        // open application in background
        return CommandLineBackground;
    }

    if (parser.isSet(closeOption)) {
        // close already running application instances, if any
        return CommandLineClose;
    }

    /* no explicit argument was passed */
    return CommandLineOK;
};
```

Here is the caller graph for this function:

13.72.3.5 static bool pidActive (const QStringList & *lines*) [static]

Definition at line 92 of file main.cpp.

Referenced by isRunning().

```
92                                                  {
93     foreach(const QString& line, lines){
94         if(line.startsWith("PID ")){
95             bool ok;
96             pid_t pid;
97             // Valid PID found?
98             if((pid = line.split(" ")[1].toLong(&ok)) > 0 && ok){
99                 // kill -0 does nothing to the application, but checks if it's running
100                 return (kill(pid, 0) == 0 || errno != ESRCH);
101             }
102         }
103     }
104     // If the PID wasn't listed in the shmem, assume it is running
105     return true;
106 }
```

Here is the caller graph for this function:

13.73 src/ckb/mainwindow.cpp File Reference

```
#include "ckbsettings.h"
#include "kbmanager.h"
#include "kbfirmware.h"
#include "mainwindow.h"
#include "ui_mainwindow.h"
#include <cstdlib>
#include <QSharedMemory>
#include <QShortcut>
#include <QMessageBox>
#include <QMenuBar>
#include <unistd.h>
```

Include dependency graph for mainwindow.cpp:

Variables

- QSharedMemory appShare
- static const QString configLabel = "Settings"

13.73.1 Variable Documentation

13.73.1.1 QSharedMemory appShare

Referenced by MainWindow::timerTick().

13.73.1.2 const QString configLabel = "Settings" [static]

Definition at line 15 of file mainwindow.cpp.

Referenced by MainWindow::MainWindow().

13.74 src/ckb/mainwindow.h File Reference

```
#include <QCloseEvent>
#include <QMainWindow>
#include <QMenu>
#include <QSystemTrayIcon>
#include <QTimer>
#include "kbwidget.h"
#include "settingswidget.h"
```

Include dependency graph for mainwindow.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class MainWindow

Namespaces

- Ui

13.75 src/ckb/media.h File Reference

This graph shows which files directly or indirectly include this file:

Macros

- #define EXTERN_C extern
- #define ENUM_C(name) typedef enum
- #define ENUM_END_C(name) name

Enumerations

- enum muteState { UNKNOWN = -1, UNMUTED, MUTED }

Functions

- muteState getMuteState ()

13.75.1 Macro Definition Documentation

13.75.1.1 #define ENUM_C(*name*) typedef enum

Definition at line 13 of file media.h.

13.75.1.2 #define ENUM_END_C(*name*) name

Definition at line 14 of file media.h.

13.75.1.3 #define EXTERN_C extern

Definition at line 12 of file media.h.

13.75.2 Enumeration Type Documentation

13.75.2.1 enum muteState

Enumerator

UNKNOWN

UNMUTED

MUTED

Definition at line 19 of file media.h.

```
19                  {
20     UNKNOWN = -1,
21     UNMUTED,
22     MUTED
23 } ENUM_END_C(muteState);
```

13.75.3 Function Documentation

13.75.3.1 muteState getMuteState ( )

Definition at line 9 of file media_linux.cpp.

References MUTED, muteProcess, UNKNOWN, and UNMUTED.

Referenced by KbPerf::applyIndicators().

```
{
    // Get default sink mute state from pulseaudio
    static muteState lastKnown = UNKNOWN;
    static quint64 lastTime = 0;
    // Instead of running a command to check the state and waiting for it to finish, run the command now but wait to check it until the next frame
    // (locking up the GUI thread is bad)
    if(lastTime > 0 && muteProcess.state() == QProcess::NotRunning){
        if(muteProcess.exitCode() != 0)
            lastKnown = UNKNOWN;
        QString output = muteProcess.readLine().trimmed();
        if(output == "yes")
            lastKnown = MUTED;
        else if(output == "no")
            lastKnown = UNMUTED;
    }
    quint64 time = QDateTime::currentMSecsSinceEpoch();
    if(time - lastTime < 33)
        // Don't run it than 30 times per second
        return lastKnown;
    lastTime = time;
    if(muteProcess.state() == QProcess::NotRunning)
        // Shamelessly taken from pulseaudio-ctl
        muteProcess.start("sh", QStringList() << "-c" << "pacmd list-sinks|grep -A 15 '*index'|awk '/muted:/{ print $2 }'");
    return lastKnown;
}
```

Here is the caller graph for this function:

13.76 src/ckb/media_linux.cpp File Reference

```
#include <QDateTime>
#include <QProcess>
#include "media.h"
```

Include dependency graph for media_linux.cpp:

Functions

- muteState getMuteState ()

Variables

- static QProcess muteProcess

13.76.1 Function Documentation

13.76.1.1 muteState getMuteState ( )

Definition at line 9 of file media_linux.cpp.

References MUTED, muteProcess, UNKNOWN, and UNMUTED.

```
9                           {
10      // Get default sink mute state from pulseaudio
11      static muteState lastKnown = UNKNOWN;
12      static quint64 lastTime = 0;
13      // Instead of running a command to check the state and waiting for it to finish, run the command now
        but wait to check it until the next frame
14      // (locking up the GUI thread is bad)
15      if(lastTime > 0 && muteProcess.state() == QProcess::NotRunning){
16          if(muteProcess.exitCode() != 0)
17              lastKnown = UNKNOWN;
18          QString output = muteProcess.readLine().trimmed();
19          if(output == "yes")
20              lastKnown = MUTED;
21          else if(output == "no")
22              lastKnown = UNMUTED;
23      }
24      quint64 time = QDateTime::currentMSecsSinceEpoch();
25      if(time - lastTime < 33)
26          // Don't run it than 30 times per second
27          return lastKnown;
28      lastTime = time;
29      if(muteProcess.state() == QProcess::NotRunning)
30          // Shamelessly taken from pulseaudio-ctl
31          muteProcess.start("sh", QStringList() << "-c" << "pacmd list-sinks|grep -A 15 '*
        index'|awk '/muted:/{ print $2 }'");
32      return lastKnown;
33  }
```

13.76.2 Variable Documentation

13.76.2.1 QProcess muteProcess [static]

Definition at line 7 of file media_linux.cpp.

Referenced by getMuteState().

13.77 src/ckb/media_mac.m File Reference

```
#import <AudioToolbox/AudioServices.h>
#import <Foundation/Foundation.h>
#include "media.h"
```

Include dependency graph for media_mac.m:

Functions

- muteState getMuteState ()
- void disableAppNap ()

13.77.1 Function Documentation

13.77.1.1 void disableAppNap ( )

Definition at line 34 of file media_mac.m.

Referenced by main().

```
34                      {
35      [[NSProcessInfo processInfo] beginActivityWithOptions:NSActivityUserInitiatedAllowingIdleSystemSleep
        reason:@"Keyboard animation"];
36 }
```

Here is the caller graph for this function:

13.77.1.2 muteState getMuteState ( )

Definition at line 5 of file media_mac.m.

References MUTED, UNKNOWN, and UNMUTED.

Referenced by KbPerf::applyIndicators().

```
5                       {
6     // Get the system's default audio device
7     AudioObjectPropertyAddress propertyAddress = {
8         kAudioHardwarePropertyDefaultOutputDevice,
9         kAudioObjectPropertyScopeGlobal,
10         kAudioObjectPropertyElementMaster
```

```
    };
    AudioDeviceID deviceID = 0;
    UInt32 dataSize = sizeof(deviceID);
    if(AudioHardwareServiceGetPropertyData(kAudioObjectSystemObject, &propertyAddress, 0, NULL, &dataSize, &deviceID)
            != kAudioHardwareNoError){
        return UNKNOWN;
    }
    // Grab the mute property
    AudioObjectPropertyAddress propertyAddress2 = {
        kAudioDevicePropertyMute,
        kAudioDevicePropertyScopeOutput,
        kAudioObjectPropertyElementMaster
    };
    if(!AudioHardwareServiceHasProperty(deviceID, &propertyAddress2))
        return UNKNOWN;
    bool state = 0;
    dataSize = sizeof(state);
    if(AudioHardwareServiceGetPropertyData(deviceID, &propertyAddress2, 0, NULL, &dataSize, &state)
            != kAudioHardwareNoError)
        return UNKNOWN;
    return state ? MUTED : UNMUTED;
}
```

Here is the caller graph for this function:

13.78 src/ckb/modeselectdialog.cpp File Reference

```
#include "modeselectdialog.h"
#include "ui_modeselectdialog.h"
```

Include dependency graph for modeselectdialog.cpp:

13.79 src/ckb/modeselectdialog.h File Reference

```
#include <QDialog>
#include "kbmode.h"
```

Include dependency graph for modeselectdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class ModeSelectDialog

Namespaces

- Ui

13.80 src/ckb/mperfwidget.cpp File Reference

```
#include "mperfwidget.h"
#include "ui_mperfwidget.h"
#include "modeselectdialog.h"
#include <cmath>
```

Include dependency graph for mperfwidget.cpp:

Macros

- #define SET_START if(isSetting) return; isSetting = true

- #define SET_END isSetting = false

Functions

- int dpiExp (int value, int min, int max)
- int dpiLog (int value, int min, int max)
- int dpiRound (int value)

Variables

- static const QString xyLinkPath = "UI/DPI/UnlinkXY"
- static const double DPI_BASE = (double)KbPerf::DPI_MAX / (double)KbPerf::DPI_MIN

13.80.1 Macro Definition Documentation

13.80.1.1 #define SET_END isSetting = false

Definition at line 126 of file mperfwidget.cpp.

Referenced by MPerfWidget::boxXChanged(), MPerfWidget::boxYChanged(), MPerfWidget::sliderXMoved(), and MPerfWidget::sliderYMoved().

13.80.1.2 #define SET_START if(isSetting) return; isSetting = true

Definition at line 125 of file mperfwidget.cpp.

Referenced by MPerfWidget::boxXChanged(), MPerfWidget::boxYChanged(), MPerfWidget::sliderXMoved(), and MPerfWidget::sliderYMoved().

13.80.2 Function Documentation

13.80.2.1 int dpiExp (int *value*, int *min*, int *max*) [inline]

Definition at line 105 of file mperfwidget.cpp.

References DPI_BASE, and KbPerf::DPI_MIN.

Referenced by MPerfWidget::sliderXMoved(), and MPerfWidget::sliderYMoved().

```
105                                                 {
106     double val = (value - min) / (double)(max - min);
107     val = pow(DPI_BASE, val);
108     return round(KbPerf::DPI_MIN * val);
109 }
```

Here is the caller graph for this function:

13.80.2.2 int dpiLog (int *value*, int *min*, int *max*) [inline]

Definition at line 111 of file mperfwidget.cpp.

References DPI_BASE, and KbPerf::DPI_MIN.

Referenced by MPerfWidget::boxXChanged(), and MPerfWidget::boxYChanged().

```
111                                                 {
112     double val = value / (double)KbPerf::DPI_MIN;
113     val = log(val) / log(DPI_BASE);
114     return round(val * (max - min) + min);
115 }
```

Here is the caller graph for this function:

13.80.2.3 int dpiRound (int *value*) [inline]

Definition at line 117 of file mperfwidget.cpp.

Referenced by MPerfWidget::sliderXMoved(), and MPerfWidget::sliderYMoved().

```
117                                 {
118     if(value > 1000)
119         return round(value / 100.) * 100;
120     else
121         return round(value / 50.) * 50;
122 }
```

Here is the caller graph for this function:

13.80.3 Variable Documentation

13.80.3.1 const double DPI_BASE = (double)KbPerf::DPI_MAX / (double)KbPerf::DPI_MIN [static]

Definition at line 103 of file mperfwidget.cpp.

Referenced by dpiExp(), and dpiLog().

13.80.3.2 const QString xyLinkPath = "UI/DPI/UnlinkXY" [static]

Definition at line 6 of file mperfwidget.cpp.

Referenced by MPerfWidget::on_xyBox_clicked().

13.81 src/ckb/mperfwidget.h File Reference

```
#include <QWidget>
#include <QSlider>
#include <QSpinBox>
#include <QCheckBox>
#include <QRadioButton>
#include <QSignalMapper>
#include "kbperf.h"
#include "kbprofile.h"
#include "colorbutton.h"
```

Include dependency graph for mperfwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class MPerfWidget
- struct MPerfWidget::DpiUi

Namespaces

- Ui

13.81.1 Data Structure Documentation

13.81.1.1 struct MPerfWidget::DpiUi

Definition at line 37 of file mperfwidget.h.

Collaboration diagram for MPerfWidget::DpiUi:

Data Fields

QCheckBox *	enableCheck	
ColorButton *	indicator	
QSpinBox *	xBox	

QSlider *	xSlider	
QSpinBox *	yBox	
QSlider *	ySlider	

13.82 src/ckb/quazip/crypt.h File Reference

`#include "quazip_global.h"`
Include dependency graph for crypt.h:

This graph shows which files directly or indirectly include this file:

Macros

- #define CRC32(c, b) ((*(pcrc_32_tab+(((int)(c) ^ (b)) & 0xff))) ^ ((c) >> 8))
- #define zdecode(pkeys, pcrc_32_tab, c) (update_keys(pkeys,pcrc_32_tab,c ^= decrypt_byte(pkeys,pcrc_32_tab)))
- #define zencode(pkeys, pcrc_32_tab, c, t) (t=decrypt_byte(pkeys,pcrc_32_tab), update_keys(pkeys,pcrc_32_tab,c), t^(c))

Functions

- static int decrypt_byte (unsigned long ∗pkeys, const z_crc_t FAR ∗pcrc_32_tab)
- static int update_keys (unsigned long ∗pkeys, const z_crc_t FAR ∗pcrc_32_tab, int c)
- static void init_keys (const char ∗passwd, unsigned long ∗pkeys, const z_crc_t FAR ∗pcrc_32_tab)

13.82.1 Macro Definition Documentation

13.82.1.1 #define CRC32(*c, b*) ((∗(pcrc_32_tab+(((int)(c) ^ (b)) & 0xff))) ^ ((c) >> 8))

Definition at line 32 of file crypt.h.

Referenced by update_keys().

13.82.1.2 #define zdecode(*pkeys, pcrc_32_tab, c*) (update_keys(pkeys,pcrc_32_tab,c ^= decrypt_byte(pkeys,pcrc_32_tab)))

Definition at line 79 of file crypt.h.

Referenced by unzOpenCurrentFile3(), and unzReadCurrentFile().

13.82.1.3 #define zencode(*pkeys, pcrc_32_tab, c, t*) (t=decrypt_byte(pkeys,pcrc_32_tab), update_keys(pkeys,pcrc_32_tab,c), t^(c))

Definition at line 82 of file crypt.h.

Referenced by zip64FlushWriteBuffer().

13.82.2 Function Documentation

13.82.2.1 static int decrypt_byte (unsigned long ∗ *pkeys*, const z_crc_t FAR ∗ *pcrc_32_tab*) [static]

Definition at line 37 of file crypt.h.

```
{
    //(void) pcrc_32_tab; /* avoid "unused parameter" warning */
    unsigned temp;  /* POTENTIAL BUG:  temp*(temp^1) may overflow in an
                     * unpredictable manner on 16-bit systems; not a problem
                     * with any known compiler so far, though */

    temp = ((unsigned)(*(pkeys+2)) & 0xffff) | 2;
    return (int)(((temp * (temp ^ 1)) >> 8) & 0xff);
}
```

13.82.2.2 static void init_keys (const char ∗ *passwd*, unsigned long ∗ *pkeys*, const z_crc_t FAR ∗ *pcrc_32_tab*) [static]

Definition at line 68 of file crypt.h.

References update_keys().

Referenced by unzOpenCurrentFile3().

```
{
    *(pkeys+0) = 305419896L;
    *(pkeys+1) = 591751049L;
    *(pkeys+2) = 878082192L;
    while (*passwd != '\0') {
        update_keys(pkeys,pcrc_32_tab,(int)*passwd);
        passwd++;
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.82.2.3 static int update_keys (unsigned long * *pkeys*, const z_crc_t FAR * *pcrc_32_tab*, int *c*) [static]

Definition at line 51 of file crypt.h.

References CRC32.

Referenced by init_keys().

```
52 {
53     (*(pkeys+0)) = CRC32((*(pkeys+0)), c);
54     (*(pkeys+1)) += (*(pkeys+0)) & 0xff;
55     (*(pkeys+1)) = (*(pkeys+1)) * 134775813L + 1;
56     {
57       register int keyshift = (int)((*(pkeys+1)) >> 24);
58       (*(pkeys+2)) = CRC32((*(pkeys+2)), keyshift);
59     }
60     return c;
61 }
```

Here is the caller graph for this function:

13.83 src/ckb/quazip/ioapi.h File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include "zlib.h"
```

Include dependency graph for ioapi.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct zlib_filefunc_def_s
- struct zlib_filefunc64_def_s
- struct zlib_filefunc64_32_def_s

Macros

- #define __USE_FILE_OFFSET64
- #define __USE_LARGEFILE64
- #define _LARGEFILE64_SOURCE
- #define _FILE_OFFSET_BIT 64
- #define OF _Z_OF
- #define ZLIB_FILEFUNC_SEEK_CUR (1)
- #define ZLIB_FILEFUNC_SEEK_END (2)
- #define ZLIB_FILEFUNC_SEEK_SET (0)
- #define ZLIB_FILEFUNC_MODE_READ (1)
- #define ZLIB_FILEFUNC_MODE_WRITE (2)
- #define ZLIB_FILEFUNC_MODE_READWRITEFILTER (3)
- #define ZLIB_FILEFUNC_MODE_EXISTING (4)
- #define ZLIB_FILEFUNC_MODE_CREATE (8)
- #define ZCALLBACK
- #define ZREAD64(filefunc, filestream, buf, size) ((∗((filefunc).zfile_func64.zread_file)) ((filefunc).zfile_func64.opaque,filestream,buf,size))
- #define ZWRITE64(filefunc, filestream, buf, size) ((∗((filefunc).zfile_func64.zwrite_file)) ((filefunc).zfile_func64.opaque,filestream,buf,size))
- #define ZCLOSE64(filefunc, filestream) ((∗((filefunc).zfile_func64.zclose_file)) ((filefunc).zfile_func64.opaque,filestream))
- #define ZFAKECLOSE64(filefunc, filestream) ((∗((filefunc).zfile_func64.zfakeclose_file)) ((filefunc).zfile_func64.opaque,filestream))
- #define ZERROR64(filefunc, filestream) ((∗((filefunc).zfile_func64.zerror_file)) ((filefunc).zfile_func64.opaque,filestream))
- #define ZOPEN64(filefunc, filename, mode) (call_zopen64((&(filefunc)),(filename),(mode)))
- #define ZTELL64(filefunc, filestream) (call_ztell64((&(filefunc)),(filestream)))
- #define ZSEEK64(filefunc, filestream, pos, mode) (call_zseek64((&(filefunc)),(filestream),(pos),(mode)))

Typedefs

- typedef unsigned long long int ZPOS64_T
- typedef voidpf open_file_func _Z_OF ((voidpf opaque, voidpf file, int mode))

  Addition for GDAL : START.
- typedef struct zlib_filefunc_def_s zlib_filefunc_def
- typedef struct zlib_filefunc64_def_s zlib_filefunc64_def
- typedef struct zlib_filefunc64_32_def_s zlib_filefunc64_32_def

Functions

- void fill_qiodevice64_filefunc _Z_OF ((zlib_filefunc64_def ∗pzlib_filefunc_def))
- void fill_qiodevice_filefunc _Z_OF ((zlib_filefunc_def ∗pzlib_filefunc_def))
- voidpf call_zopen64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf file, int mode))
- int call_zseek64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream, ZPOS64_T offset, int origin))

- ZPOS64_T call_ztell64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream))
- void fill_zlib_filefunc64_32_def_from_filefunc32 (zlib_filefunc64_32_def ∗p_filefunc64_32, const zlib_filefunc_def ∗p_filefunc32)

13.83.1 Data Structure Documentation

13.83.1.1 struct zlib_filefunc_def_s

Definition at line 143 of file ioapi.h.

Collaboration diagram for zlib_filefunc_def_s:

Data Fields

voidpf	opaque	
close_file_func	zclose_file	
testerror_file_-func	zerror_file	
open_file_func	zopen_file	
read_file_func	zread_file	
seek_file_func	zseek_file	
tell_file_func	ztell_file	
write_file_func	zwrite_file	

13.83.1.2 struct zlib_filefunc64_def_s

Definition at line 159 of file ioapi.h.

Collaboration diagram for zlib_filefunc64_def_s:

Data Fields

voidpf	opaque	
close_file_func	zclose_file	
testerror_file_-func	zerror_file	
close_file_func	zfakeclose_file	
open64_file_-func	zopen64_file	
read_file_func	zread_file	
seek64_file_func	zseek64_file	
tell64_file_func	ztell64_file	
write_file_func	zwrite_file	

13.83.1.3 struct zlib_filefunc64_32_def_s

Definition at line 176 of file ioapi.h.

Collaboration diagram for zlib_filefunc64_32_def_s:

Data Fields

zlib_filefunc64_-def	zfile_func64	
open_file_func	zopen32_file	
seek_file_func	zseek32_file	
tell_file_func	ztell32_file	

13.83.2 Macro Definition Documentation

13.83.2.1 #define __USE_FILE_OFFSET64

Definition at line 32 of file ioapi.h.

13.83.2.2 #define __USE_LARGEFILE64

Definition at line 35 of file ioapi.h.

13.83.2.3 #define _FILE_OFFSET_BIT 64

Definition at line 41 of file ioapi.h.

13.83.2.4 #define _LARGEFILE64_SOURCE

Definition at line 38 of file ioapi.h.

13.83.2.5 #define OF _Z_OF

Definition at line 106 of file ioapi.h.

13.83.2.6 #define ZCALLBACK

Definition at line 125 of file ioapi.h.

13.83.2.7 #define ZCLOSE64(*filefunc, filestream*) ((∗((filefunc).zfile_func64.zclose_file)) ((filefunc).zfile_func64.opaque,filestream))

Definition at line 189 of file ioapi.h.

Referenced by LoadCentralDirectoryRecord(), unzClose(), unzOpenInternal(), zipClose(), and zipOpen3().

13.83.2.8 #define ZERROR64(*filefunc, filestream*) ((∗((filefunc).zfile_func64.zerror_file)) ((filefunc).zfile_func64.opaque,filestream))

Definition at line 191 of file ioapi.h.

Referenced by unz64local_getByte(), and zip64local_getByte().

13.83.2.9 #define ZFAKECLOSE64(*filefunc, filestream*) ((∗((filefunc).zfile_func64.zfakeclose_file)) ((filefunc).zfile_func64.opaque,filestream))

Definition at line 190 of file ioapi.h.

Referenced by LoadCentralDirectoryRecord(), unzClose(), unzOpenInternal(), zipClose(), and zipOpen3().

13.83.2.10 #define ZLIB_FILEFUNC_MODE_CREATE (8)

Definition at line 118 of file ioapi.h.

Referenced by qiodevice_open_file_func(), and zipOpen3().

13.83.2.11 #define ZLIB_FILEFUNC_MODE_EXISTING (4)

Definition at line 117 of file ioapi.h.

Referenced by qiodevice_open_file_func(), unzOpenInternal(), and zipOpen3().

13.83.2.12 #define ZLIB_FILEFUNC_MODE_READ (1)

Definition at line 113 of file ioapi.h.

Referenced by qiodevice_open_file_func(), unzOpenInternal(), and zipOpen3().

13.83.2.13 #define ZLIB_FILEFUNC_MODE_READWRITEFILTER (3)

Definition at line 115 of file ioapi.h.

Referenced by qiodevice_open_file_func().

13.83.2.14 #define ZLIB_FILEFUNC_MODE_WRITE (2)

Definition at line 114 of file ioapi.h.

Referenced by zipOpen3().

13.83.2.15 #define ZLIB_FILEFUNC_SEEK_CUR (1)

Definition at line 109 of file ioapi.h.

Referenced by qiodevice64_seek_file_func(), qiodevice_seek_file_func(), and unz64local_GetCurrentFileInfoInternal().

13.83.2.16 #define ZLIB_FILEFUNC_SEEK_END (2)

Definition at line 110 of file ioapi.h.

Referenced by qiodevice64_seek_file_func(), qiodevice_seek_file_func(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), zip64local_SearchCentralDir(), and zip64local_SearchCentralDir64().

13.83.2.17 #define ZLIB_FILEFUNC_SEEK_SET (0)

Definition at line 111 of file ioapi.h.

Referenced by LoadCentralDirectoryRecord(), qiodevice64_seek_file_func(), qiodevice_seek_file_func(), unz64local_CheckCurrentFileCoherencyHeader(), unz64local_GetCurrentFileInfoInternal(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), unzGetGlobalComment(), unzGetLocalExtrafield(), unzOpenInternal(), unzReadCurrentFile(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), and zipCloseFileInZipRaw64().

13.83.2.18 #define ZOPEN64(*filefunc, filename, mode*) (call_zopen64((&(filefunc)),(filename),(mode)))

Definition at line 199 of file ioapi.h.

Referenced by unzOpenInternal(), and zipOpen3().

13.83.2.19 #define ZREAD64(*filefunc, filestream, buf, size*) ((∗((filefunc).zfile_func64.zread_file)) ((filefunc).zfile_func64.opaque,filestream,buf,size))

Definition at line 185 of file ioapi.h.

Referenced by LoadCentralDirectoryRecord(), unz64local_getByte(), unz64local_GetCurrentFileInfoInternal(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), unzGetGlobalComment(), unzGetLocalExtrafield(), unzOpenCurrentFile3(), unzReadCurrentFile(), zip64local_getByte(), zip64local_SearchCentralDir(), and zip64local_SearchCentralDir64().

13.83.2.20 #define ZSEEK64(*filefunc, filestream, pos, mode*) (call_zseek64((&(filefunc)),(filestream),(pos),(mode)))

Definition at line 201 of file ioapi.h.

Referenced by LoadCentralDirectoryRecord(), unz64local_CheckCurrentFileCoherencyHeader(), unz64local_GetCurrentFileInfoInternal(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), unzGetGlobalComment(), unzGetLocalExtrafield(), unzOpenCurrentFile3(), unzOpenInternal(), unzReadCurrentFile(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), zipCloseFileInZipRaw64(), and zipOpen3().

13.83.2.21 #define ZTELL64(*filefunc, filestream*) (call_ztell64((&(filefunc)),(filestream)))

Definition at line 200 of file ioapi.h.

Referenced by unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), Write_LocalFileHeader(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), zipClose(), zipCloseFileInZipRaw64(), zipOpen3(), and zipOpenNewFileInZip4_64().

13.83.2.22 #define ZWRITE64(*filefunc, filestream, buf, size*) ((∗((filefunc).zfile_func64.zwrite_file)) ((filefunc).zfile_func64.opaque,filestream,buf,size))

Definition at line 186 of file ioapi.h.

Referenced by Write_GlobalComment(), Write_LocalFileHeader(), zip64FlushWriteBuffer(), zip64local_putValue(), zipClose(), and zipOpenNewFileInZip4_64().

13.83.3 Typedef Documentation

13.83.3.1 zipFile ZEXPORT zipOpen64 _Z_OF ((voidpf opaque, voidpf file, int mode))

Addition for GDAL : END.

Definition at line 132 of file ioapi.h.

13.83.3.2 typedef struct zlib_filefunc64_32_def_s zlib_filefunc64_32_def

13.83.3.3 typedef struct zlib_filefunc64_def_s zlib_filefunc64_def

13.83.3.4 typedef struct zlib_filefunc_def_s zlib_filefunc_def

13.83.3.5 typedef unsigned long long int ZPOS64_T

Definition at line 94 of file ioapi.h.

13.83.4 Function Documentation

13.83.4.1 void fill_qiodevice64_filefunc _Z_OF ((zlib_filefunc64_def ∗pzlib_filefunc_def))

13.83.4.2 void fill_qiodevice_filefunc _Z_OF ((zlib_filefunc_def ∗pzlib_filefunc_def))

13.83.4.3 voidpf call_zopen64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf file, int mode))

13.83.4.4 int call_zseek64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream, ZPOS64_T offset, int origin))

13.83.4.5 ZPOS64_T call_ztell64 _Z_OF ((const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream))

13.83.4.6 void fill_zlib_filefunc64_32_def_from_filefunc32 (zlib_filefunc64_32_def * *p_filefunc64_32*, const zlib_filefunc_def * *p_filefunc32*)

Definition at line 346 of file qioapi.cpp.

References zlib_filefunc_def_s::opaque, zlib_filefunc64_def_s::opaque, zlib_filefunc_def_s::zclose_file, zlib_filefunc64_def_s::zclose_file, zlib_filefunc_def_s::zerror_file, zlib_filefunc64_def_s::zerror_file, zlib_filefunc64_def_s::zfakeclose_file, zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_32_def_s::zopen32_file, zlib_filefunc64_def_s::zopen64_file, zlib_filefunc_def_s::zopen_file, zlib_filefunc_def_s::zread_file, zlib_filefunc64_def_s::zread_file, zlib_filefunc64_32_def_s::zseek32_file, zlib_filefunc64_def_s::zseek64_file, zlib_filefunc_def_s::zseek_file, zlib_filefunc64_32_def_s::ztell32_file, zlib_filefunc64_def_s::ztell64_file, zlib_filefunc_def_s::ztell_file, zlib_filefunc_def_s::zwrite_file, and zlib_filefunc64_def_s::zwrite_file.

Referenced by unzOpen2(), and zipOpen2().

```
347 {
348     p_filefunc64_32->zfile_func64.zopen64_file = NULL;
349     p_filefunc64_32->zopen32_file = p_filefunc32->zopen_file;
350     p_filefunc64_32->zfile_func64.zerror_file = p_filefunc32->
    zerror_file;
351     p_filefunc64_32->zfile_func64.zread_file = p_filefunc32->
    zread_file;
352     p_filefunc64_32->zfile_func64.zwrite_file = p_filefunc32->
    zwrite_file;
353     p_filefunc64_32->zfile_func64.ztell64_file = NULL;
354     p_filefunc64_32->zfile_func64.zseek64_file = NULL;
355     p_filefunc64_32->zfile_func64.zclose_file = p_filefunc32->
    zclose_file;
356     p_filefunc64_32->zfile_func64.zerror_file = p_filefunc32->
    zerror_file;
357     p_filefunc64_32->zfile_func64.opaque = p_filefunc32->
    opaque;
358     p_filefunc64_32->zfile_func64.zfakeclose_file = NULL;
359     p_filefunc64_32->zseek32_file = p_filefunc32->zseek_file;
360     p_filefunc64_32->ztell32_file = p_filefunc32->ztell_file;
361 }
```

Here is the caller graph for this function:

13.84 src/ckb/quazip/JlCompress.cpp File Reference

```
#include "JlCompress.h"
#include <QDebug>
```

Include dependency graph for JlCompress.cpp:

Functions

- static bool copyData (QIODevice &inFile, QIODevice &outFile)

13.84.1 Function Documentation

13.84.1.1 static bool copyData (QIODevice & *inFile*, QIODevice & *outFile*) [static]

Definition at line 29 of file JlCompress.cpp.

Referenced by JlCompress::compressFile(), and JlCompress::extractFile().

```
{
    while (!inFile.atEnd()) {
        char buf[4096];
        qint64 readLen = inFile.read(buf, 4096);
        if (readLen <= 0)
            return false;
        if (outFile.write(buf, readLen) != readLen)
            return false;
    }
    return true;
}
```

Here is the caller graph for this function:

13.85 src/ckb/quazip/JICompress.h File Reference

```
#include "quazip.h"
#include "quazipfile.h"
#include "quazipfileinfo.h"
#include <QString>
#include <QDir>
#include <QFileInfo>
#include <QFile>
```

Include dependency graph for JICompress.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class JICompress

  Utility class for typical operations.

13.86 src/ckb/quazip/qioapi.cpp File Reference

```
#include <stdio.h>
```

```
#include <stdlib.h>
#include <string.h>
#include "zlib.h"
#include "ioapi.h"
#include "quazip_global.h"
#include <QIODevice>
```

Include dependency graph for qioapi.cpp:

Data Structures

- struct QIODevice_descriptor

Macros

- #define SEEK_CUR 1
- #define SEEK_END 2
- #define SEEK_SET 0

Functions

- voidpf call_zopen64 (const zlib_filefunc64_32_def ∗pfilefunc, voidpf file, int mode)
- int call_zseek64 (const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream, ZPOS64_T offset, int origin)
- ZPOS64_T call_ztell64 (const zlib_filefunc64_32_def ∗pfilefunc, voidpf filestream)
- voidpf qiodevice_open_file_func (voidpf opaque, voidpf file, int mode)
- uLong qiodevice_read_file_func (voidpf opaque, voidpf stream, void ∗buf, uLong size)
- uLong qiodevice_write_file_func (voidpf opaque, voidpf stream, const void ∗buf, uLong size)
- uLong qiodevice_tell_file_func (voidpf opaque, voidpf stream)
- ZPOS64_T qiodevice64_tell_file_func (voidpf opaque, voidpf stream)
- int qiodevice_seek_file_func (voidpf, voidpf stream, uLong offset, int origin)
- int qiodevice64_seek_file_func (voidpf, voidpf stream, ZPOS64_T offset, int origin)
- int qiodevice_close_file_func (voidpf opaque, voidpf stream)
- int qiodevice_fakeclose_file_func (voidpf opaque, voidpf)
- int qiodevice_error_file_func (voidpf, voidpf)
- void fill_qiodevice_filefunc (zlib_filefunc_def ∗pzlib_filefunc_def)
- void fill_qiodevice64_filefunc (zlib_filefunc64_def ∗pzlib_filefunc_def)
- void fill_zlib_filefunc64_32_def_from_filefunc32 (zlib_filefunc64_32_def ∗p_filefunc64_32, const zlib_-filefunc_def ∗p_filefunc32)

13.86.1 Macro Definition Documentation

13.86.1.1 #define SEEK_CUR 1

Definition at line 29 of file qioapi.cpp.

13.86.1.2 #define SEEK_END 2

Definition at line 33 of file qioapi.cpp.

13.86.1.3 #define SEEK_SET 0

Definition at line 37 of file qioapi.cpp.

Referenced by unzOpenCurrentFile3().

13.86.2 Function Documentation

13.86.2.1 voidpf call_zopen64 (const zlib_filefunc64_32_def * *pfilefunc,* voidpf *file,* int *mode*)

Definition at line 40 of file qioapi.cpp.

References zlib_filefunc64_def_s::opaque, zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_32_def_s::zopen32_file, and zlib_filefunc64_def_s::zopen64_file.

```
{
    if (pfilefunc->zfile_func64.zopen64_file != NULL)
        return (*(pfilefunc->zfile_func64.zopen64_file)) (pfilefunc->zfile_func64.opaque,file,mode);
    else
    {
        return (*(pfilefunc->zopen32_file))(pfilefunc->zfile_func64.opaque,file,mode);
    }
}
```

13.86.2.2 int call_zseek64 (const zlib_filefunc64_32_def * *pfilefunc,* voidpf *filestream,* ZPOS64_T *offset,* int *origin*)

Definition at line 50 of file qioapi.cpp.

References zlib_filefunc64_def_s::opaque, zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_32_def_s::zseek32_file, and zlib_filefunc64_def_s::zseek64_file.

```
{
    if (pfilefunc->zfile_func64.zseek64_file != NULL)
        return (*(pfilefunc->zfile_func64.zseek64_file)) (pfilefunc->zfile_func64.opaque,filestream,offset,origin);
    else
    {
        uLong offsetTruncated = (uLong)offset;
        if (offsetTruncated != offset)
            return -1;
        else
            return (*(pfilefunc->zseek32_file))(pfilefunc->zfile_func64.opaque,filestream,offsetTruncated,origin);
    }
}
```

13.86.2.3 ZPOS64_T call_ztell64 (const zlib_filefunc64_32_def * *pfilefunc,* voidpf *filestream*)

Definition at line 64 of file qioapi.cpp.

References zlib_filefunc64_def_s::opaque, zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_def_s::zseek64_file, zlib_filefunc64_32_def_s::ztell32_file, and zlib_filefunc64_def_s::ztell64_file.

```
{
    if (pfilefunc->zfile_func64.zseek64_file != NULL)
        return (*(pfilefunc->zfile_func64.ztell64_file)) (pfilefunc->zfile_func64.opaque,filestream);
    else
    {
        uLong tell_uLong = (*(pfilefunc->ztell32_file))(pfilefunc->zfile_func64.opaque,filestream);
        if ((tell_uLong) == ((uLong)-1))
            return (ZPOS64_T)-1;
        else
            return tell_uLong;
    }
}
```

13.86.2.4 void fill_qiodevice64_filefunc (zlib_filefunc64_def * *pzlib_filefunc_def*)

Definition at line 331 of file qioapi.cpp.

References zlib_filefunc64_def_s::opaque, qiodevice64_seek_file_func(), qiodevice64_tell_file_func(), qiodevice_close_file_func(), qiodevice_error_file_func(), qiodevice_fakeclose_file_func(), qiodevice_open_file_func(), qiodevice_read_file_func(), qiodevice_write_file_func(), zlib_filefunc64_def_s::zclose_file, zlib_filefunc64_def_s::zerror_file, zlib_filefunc64_def_s::zfakeclose_file, zlib_filefunc64_def_s::zopen64_file, zlib_filefunc64_def_s::zread_file, zlib_filefunc64_def_s::zseek64_file, zlib_filefunc64_def_s::ztell64_file, and zlib_filefunc64_def_s::zwrite_file.

Referenced by unzOpenInternal(), and zipOpen3().

```
{
    // Open functions are the same for Qt.
    pzlib_filefunc_def->zopen64_file = qiodevice_open_file_func;
    pzlib_filefunc_def->zread_file = qiodevice_read_file_func;
    pzlib_filefunc_def->zwrite_file = qiodevice_write_file_func;
    pzlib_filefunc_def->ztell64_file = qiodevice64_tell_file_func;
    pzlib_filefunc_def->zseek64_file = qiodevice64_seek_file_func;
    pzlib_filefunc_def->zclose_file = qiodevice_close_file_func;
    pzlib_filefunc_def->zerror_file = qiodevice_error_file_func;
    pzlib_filefunc_def->opaque = new QIODevice_descriptor;
    pzlib_filefunc_def->zfakeclose_file = qiodevice_fakeclose_file_func;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.86.2.5 void fill_qiodevice_filefunc (zlib_filefunc_def * *pzlib_filefunc_def*)

Definition at line 318 of file qioapi.cpp.

References zlib_filefunc_def_s::opaque, qiodevice_close_file_func(), qiodevice_error_file_func(), qiodevice_open_file_func(), qiodevice_read_file_func(), qiodevice_seek_file_func(), qiodevice_tell_file_func(), qiodevice_write_file_func(), zlib_filefunc_def_s::zclose_file, zlib_filefunc_def_s::zerror_file, zlib_filefunc_def_s::zopen_file, zlib_filefunc_def_s::zread_file, zlib_filefunc_def_s::zseek_file, zlib_filefunc_def_s::ztell_file, and zlib_filefunc_def_s::zwrite_file.

```
320 {
```

```
    pzlib_filefunc_def->zopen_file = qiodevice_open_file_func;
    pzlib_filefunc_def->zread_file = qiodevice_read_file_func;
    pzlib_filefunc_def->zwrite_file = qiodevice_write_file_func;
    pzlib_filefunc_def->ztell_file = qiodevice_tell_file_func;
    pzlib_filefunc_def->zseek_file = qiodevice_seek_file_func;
    pzlib_filefunc_def->zclose_file = qiodevice_close_file_func;
    pzlib_filefunc_def->zerror_file = qiodevice_error_file_func;
    pzlib_filefunc_def->opaque = new QIODevice_descriptor;
}
```

Here is the call graph for this function:

13.86.2.6 void fill_zlib_filefunc64_32_def_from_filefunc32 (zlib_filefunc64_32_def * *p_filefunc64_32*, const zlib_filefunc_def * *p_filefunc32*)

Definition at line 346 of file qioapi.cpp.

References zlib_filefunc_def_s::opaque, zlib_filefunc64_def_s::opaque, zlib_filefunc_def_s::zclose_file, zlib_filefunc64_def_s::zclose_file, zlib_filefunc_def_s::zerror_file, zlib_filefunc64_def_s::zerror_file, zlib_filefunc64_def_s::zfakeclose_file, zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_32_def_s::zopen32_file, zlib_filefunc64_def_s::zopen64_file, zlib_filefunc_def_s::zopen_file, zlib_filefunc_def_s::zread_file, zlib_filefunc64_def_s::zread_file, zlib_filefunc64_32_def_s::zseek32_file, zlib_filefunc64_def_s::zseek64_file, zlib_filefunc_def_s::zseek_file, zlib_filefunc64_32_def_s::ztell32_file, zlib_filefunc64_def_s::ztell64_file, zlib_filefunc_def_s::ztell_file, zlib_filefunc_def_s::zwrite_file, and zlib_filefunc64_def_s::zwrite_file.

Referenced by unzOpen2(), and zipOpen2().

```
{
    p_filefunc64_32->zfile_func64.zopen64_file = NULL;
    p_filefunc64_32->zopen32_file = p_filefunc32->zopen_file;
    p_filefunc64_32->zfile_func64.zerror_file = p_filefunc32->
  zerror_file;
    p_filefunc64_32->zfile_func64.zread_file = p_filefunc32->
```

```
    zread_file;
    p_filefunc64_32->zfile_func64.zwrite_file = p_filefunc32->zwrite_file;
    p_filefunc64_32->zfile_func64.ztell64_file = NULL;
    p_filefunc64_32->zfile_func64.zseek64_file = NULL;
    p_filefunc64_32->zfile_func64.zclose_file = p_filefunc32->zclose_file;
    p_filefunc64_32->zfile_func64.zerror_file = p_filefunc32->zerror_file;
    p_filefunc64_32->zfile_func64.opaque = p_filefunc32->opaque;
    p_filefunc64_32->zfile_func64.zfakeclose_file = NULL;
    p_filefunc64_32->zseek32_file = p_filefunc32->zseek_file;
    p_filefunc64_32->ztell32_file = p_filefunc32->ztell_file;
}
```

Here is the caller graph for this function:

13.86.2.7 int qiodevice64_seek_file_func (voidpf , voidpf *stream*, ZPOS64_T *offset*, int *origin*)

Definition at line 244 of file qioapi.cpp.

References ZLIB_FILEFUNC_SEEK_CUR, ZLIB_FILEFUNC_SEEK_END, and ZLIB_FILEFUNC_SEEK_SET.

Referenced by fill_qiodevice64_filefunc().

```
{
    QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
    if (iodevice->isSequential()) {
        if (origin == ZLIB_FILEFUNC_SEEK_END
                && offset == 0) {
            // sequential devices are always at end (needed in mdAppend)
            return 0;
        } else {
            qWarning("qiodevice_seek_file_func() called for sequential device");
            return -1;
        }
    }
    qint64 qiodevice_seek_result=0;
    int ret;
    switch (origin)
    {
    case ZLIB_FILEFUNC_SEEK_CUR :
        qiodevice_seek_result = ((QIODevice*)stream)->pos() + offset;
        break;
    case ZLIB_FILEFUNC_SEEK_END :
        qiodevice_seek_result = ((QIODevice*)stream)->size() - offset;
        break;
    case ZLIB_FILEFUNC_SEEK_SET :
        qiodevice_seek_result = offset;
        break;
    default:
        return -1;
    }
    ret = !iodevice->seek(qiodevice_seek_result);
    return ret;
}
```

Here is the caller graph for this function:

13.86.2.8 ZPOS64_T qiodevice64_tell_file_func (voidpf *opaque*, voidpf *stream*)

Definition at line 192 of file qioapi.cpp.

References QIODevice_descriptor::pos.

Referenced by fill_qiodevice64_filefunc().

```
195 {
196     QIODevice_descriptor *d = reinterpret_cast<
    QIODevice_descriptor*>(opaque);
197     QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
198     qint64 ret;
199     if (iodevice->isSequential()) {
200         ret = d->pos;
201     } else {
202         ret = iodevice->pos();
203     }
204     return static_cast<ZPOS64_T>(ret);
205 }
```

Here is the caller graph for this function:

13.86.2.9 int qiodevice_close_file_func (voidpf *opaque*, voidpf *stream*)

Definition at line 281 of file qioapi.cpp.

Referenced by fill_qiodevice64_filefunc(), and fill_qiodevice_filefunc().

```
284 {
285     QIODevice_descriptor *d = reinterpret_cast<
    QIODevice_descriptor*>(opaque);
286     delete d;
287     QIODevice *device = reinterpret_cast<QIODevice*>(stream);
288 #ifdef QUAZIP_QSAVEFILE_BUG_WORKAROUND
289     // QSaveFile terribly breaks the is-a idiom:
290     // it IS a QIODevice, but it is NOT compatible with it: close() is private
291     QSaveFile *file = qobject_cast<QSaveFile*>(device);
292     if (file != NULL) {
293         // We have to call the ugly commit() instead:
294         return file->commit() ? 0 : -1;
295     }
```

```
#endif
    device->close();
    return 0;
}
```

Here is the caller graph for this function:

13.86.2.10 int qiodevice_error_file_func (voidpf , voidpf)

Definition at line 310 of file qioapi.cpp.

Referenced by fill_qiodevice64_filefunc(), and fill_qiodevice_filefunc().

```
{
    // can't check for error due to the QIODevice API limitation
    return 0;
}
```

Here is the caller graph for this function:

13.86.2.11 int qiodevice_fakeclose_file_func (voidpf *opaque*, voidpf)

Definition at line 301 of file qioapi.cpp.

Referenced by fill_qiodevice64_filefunc().

```
{
    QIODevice_descriptor *d = reinterpret_cast<
  QIODevice_descriptor*>(opaque);
    delete d;
    return 0;
}
```

Here is the caller graph for this function:

13.86.2.12 voidpf qiodevice_open_file_func (voidpf *opaque,* voidpf *file,* int *mode*)

Definition at line 86 of file qioapi.cpp.

References QIODevice_descriptor::pos, ZLIB_FILEFUNC_MODE_CREATE, ZLIB_FILEFUNC_MODE_EXISTING, ZLIB_FILEFUNC_MODE_READ, and ZLIB_FILEFUNC_MODE_READWRITEFILTER.

Referenced by fill_qiodevice64_filefunc(), and fill_qiodevice_filefunc().

```
{
    QIODevice_descriptor *d = reinterpret_cast<QIODevice_descriptor*>(opaque);
    QIODevice *iodevice = reinterpret_cast<QIODevice*>(file);
    QIODevice::OpenMode desiredMode;
    if ((mode & ZLIB_FILEFUNC_MODE_READWRITEFILTER)==ZLIB_FILEFUNC_MODE_READ)
        desiredMode = QIODevice::ReadOnly;
    else if (mode & ZLIB_FILEFUNC_MODE_EXISTING)
        desiredMode = QIODevice::ReadWrite;
    else if (mode & ZLIB_FILEFUNC_MODE_CREATE)
        desiredMode = QIODevice::WriteOnly;
    if (iodevice->isOpen()) {
        if ((iodevice->openMode() & desiredMode) == desiredMode) {
            if (desiredMode != QIODevice::WriteOnly
                    && iodevice->isSequential()) {
                // We can use sequential devices only for writing.
                delete d;
                return NULL;
            } else {
                if ((desiredMode & QIODevice::WriteOnly) != 0) {
                    // open for writing, need to seek existing device
                    if (!iodevice->isSequential()) {
                        iodevice->seek(0);
                    } else {
                        d->pos = iodevice->pos();
                    }
                }
            }
            return iodevice;
        } else {
            delete d;
            return NULL;
        }
    }
    iodevice->open(desiredMode);
    if (iodevice->isOpen()) {
        if (desiredMode != QIODevice::WriteOnly && iodevice->isSequential()) {
            // We can use sequential devices only for writing.
            iodevice->close();
            delete d;
            return NULL;
        } else {
            return iodevice;
        }
    } else {
        delete d;
        return NULL;
    }
}
```

Here is the caller graph for this function:

13.86.2.13 uLong qiodevice_read_file_func (voidpf *opaque,* voidpf *stream,* void ∗ *buf,* uLong *size*)

Definition at line 140 of file qioapi.cpp.

References QIODevice_descriptor::pos.

Referenced by fill_qiodevice64_filefunc(), and fill_qiodevice_filefunc().

```
145 {
146     QIODevice_descriptor *d = reinterpret_cast<
    QIODevice_descriptor*>(opaque);
147     QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
148     qint64 ret64 = iodevice->read((char*)buf,size);
149     uLong ret;
150     ret = (uLong) ret64;
151     if (ret64 != -1) {
152         d->pos += ret64;
153     }
154     return ret;
155 }
```

Here is the caller graph for this function:

13.86.2.14 int qiodevice_seek_file_func (voidpf , voidpf *stream,* uLong *offset,* int *origin*)

Definition at line 207 of file qioapi.cpp.

References ZLIB_FILEFUNC_SEEK_CUR, ZLIB_FILEFUNC_SEEK_END, and ZLIB_FILEFUNC_SEEK_SET.

Referenced by fill_qiodevice_filefunc().

```
212 {
213     QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
214     if (iodevice->isSequential()) {
215         if (origin == ZLIB_FILEFUNC_SEEK_END
216                 && offset == 0) {
217             // sequential devices are always at end (needed in mdAppend)
218             return 0;
219         } else {
220             qWarning("qiodevice_seek_file_func() called for sequential device");
221             return -1;
```

```
        }
    }
    uLong qiodevice_seek_result=0;
    int ret;
    switch (origin)
    {
    case ZLIB_FILEFUNC_SEEK_CUR :
        qiodevice_seek_result = ((QIODevice*)stream)->pos() + offset;
        break;
    case ZLIB_FILEFUNC_SEEK_END :
        qiodevice_seek_result = ((QIODevice*)stream)->size() - offset;
        break;
    case ZLIB_FILEFUNC_SEEK_SET :
        qiodevice_seek_result = offset;
        break;
    default:
        return -1;
    }
    ret = !iodevice->seek(qiodevice_seek_result);
    return ret;
}
```

Here is the caller graph for this function:

13.86.2.15 uLong qiodevice_tell_file_func (voidpf *opaque*, voidpf *stream*)

Definition at line 175 of file qioapi.cpp.

References QIODevice_descriptor::pos.

Referenced by fill_qiodevice_filefunc().

```
{
    QIODevice_descriptor *d = reinterpret_cast<
  QIODevice_descriptor*>(opaque);
    QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
    uLong ret;
    qint64 ret64;
    if (iodevice->isSequential()) {
        ret64 = d->pos;
    } else {
        ret64 = iodevice->pos();
    }
    ret = static_cast<uLong>(ret64);
    return ret;
}
```

Here is the caller graph for this function:

13.86.2.16 uLong qiodevice_write_file_func (voidpf *opaque*, voidpf *stream*, const void ∗ *buf*, uLong *size*)

Definition at line 158 of file qioapi.cpp.

References QIODevice_descriptor::pos.

Referenced by fill_qiodevice64_filefunc(), and fill_qiodevice_filefunc().

```
{
    QIODevice_descriptor *d = reinterpret_cast<QIODevice_descriptor*>(opaque);
    QIODevice *iodevice = reinterpret_cast<QIODevice*>(stream);
    uLong ret;
    qint64 ret64 = iodevice->write((char*)buf,size);
    if (ret64 != -1) {
        d->pos += ret64;
    }
    ret = (uLong) ret64;
    return ret;
}
```

Here is the caller graph for this function:

13.87 src/ckb/quazip/quaadler32.cpp File Reference

```
#include "quaadler32.h"
#include "zlib.h"
```

Include dependency graph for quaadler32.cpp:

13.88 src/ckb/quazip/quaadler32.h File Reference

```
#include <QByteArray>
#include "quachecksum32.h"
```

Include dependency graph for quaadler32.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaAdler32

  Adler32 checksum.

13.89 src/ckb/quazip/quachecksum32.h File Reference

```
#include <QByteArray>
#include "quazip_global.h"
```

Include dependency graph for quachecksum32.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaChecksum32

  Checksum interface.

13.90 src/ckb/quazip/quacrc32.cpp File Reference

```
#include "quacrc32.h"
#include "zlib.h"
```

Include dependency graph for quacrc32.cpp:

13.91 src/ckb/quazip/quacrc32.h File Reference

```
#include "quachecksum32.h"
```

Include dependency graph for quacrc32.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaCrc32

  CRC32 checksum.

13.92 src/ckb/quazip/quagzipfile.cpp File Reference

```
#include <QFile>
#include "quagzipfile.h"
```

Include dependency graph for quagzipfile.cpp:

13.93 src/ckb/quazip/quagzipfile.h File Reference

```
#include <QIODevice>
#include "quazip_global.h"
#include <zlib.h>
```

Include dependency graph for quagzipfile.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaGzipFile

  GZIP file.

13.94 src/ckb/quazip/quaziodevice.cpp File Reference

`#include "quaziodevice.h"`

Include dependency graph for quaziodevice.cpp:

Macros

- #define QUAZIO_INBUFSIZE 4096

- #define QUAZIO_OUTBUFSIZE 4096

13.94.1 Macro Definition Documentation

13.94.1.1 #define QUAZIO_INBUFSIZE 4096

Definition at line 27 of file quaziodevice.cpp.

Referenced by QuaZIODevice::readData().

13.94.1.2 #define QUAZIO_OUTBUFSIZE 4096

Definition at line 28 of file quaziodevice.cpp.

Referenced by QuaZIODevice::flush(), and QuaZIODevice::writeData().

13.95 src/ckb/quazip/quaziodevice.h File Reference

```
#include <QIODevice>
#include "quazip_global.h"
#include <zlib.h>
```

Include dependency graph for quaziodevice.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaZIODevice

  A class to compress/decompress QIODevice.

13.96 src/ckb/quazip/quazip.cpp File Reference

```
#include <QFile>
#include <QFlags>
#include <QHash>
#include "quazip.h"
```

Include dependency graph for quazip.cpp:

Data Structures

- class QuaZipPrivate

  All the internal stuff for the QuaZip class.

Functions

- template<typename TFileInfo >
  TFileInfo QuaZip_getFileInfo (QuaZip *zip, bool *ok)

- template<>
  QuaZipFileInfo QuaZip_getFileInfo (QuaZip *zip, bool *ok)
- template<>
  QuaZipFileInfo64 QuaZip_getFileInfo (QuaZip *zip, bool *ok)
- template<>
  QString QuaZip_getFileInfo (QuaZip *zip, bool *ok)

13.96.1 Function Documentation

13.96.1.1 template<typename TFileInfo > TFileInfo QuaZip_getFileInfo (QuaZip * *zip*, bool * *ok*)

Definition at line 663 of file quazip.cpp.

References QuaZip::getCurrentFileInfo(), and QuaZip::getCurrentFileName().

```
664 {
665     QuaZipFileInfo info;
666     *ok = zip->getCurrentFileInfo(&info);
667     return info;
668 }
```

Here is the call graph for this function:

13.96.1.2 template<> QuaZipFileInfo QuaZip_getFileInfo (QuaZip * *zip*, bool * *ok*)

Definition at line 663 of file quazip.cpp.

References QuaZip::getCurrentFileInfo().

```
664 {
665     QuaZipFileInfo info;
666     *ok = zip->getCurrentFileInfo(&info);
667     return info;
668 }
```

Here is the call graph for this function:

13.96.1.3 template<> QuaZipFileInfo64 QuaZip_getFileInfo (QuaZip * *zip*, bool * *ok*)

Definition at line 671 of file quazip.cpp.

References QuaZip::getCurrentFileInfo().

```
672 {
673     QuaZipFileInfo64 info;
674     *ok = zip->getCurrentFileInfo(&info);
675     return info;
676 }
```

Here is the call graph for this function:

13.96.1.4 template<> QString QuaZip_getFileInfo (QuaZip * *zip*, bool * *ok*)

Definition at line 679 of file quazip.cpp.

References QuaZip::getCurrentFileName().

```
680 {
681     QString name = zip->getCurrentFileName();
682     *ok = !name.isEmpty();
683     return name;
684 }
```

Here is the call graph for this function:

13.97 src/ckb/quazip/quazip.h File Reference

```
#include <QString>
#include <QStringList>
#include <QTextCodec>
#include "zip.h"
#include "unzip.h"
#include "quazip_global.h"
#include "quazipfileinfo.h"
```

Include dependency graph for quazip.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaZip

  ZIP archive.

Macros

- #define UNZ_OPENERROR -1000

13.97.1 Macro Definition Documentation

13.97.1.1 #define UNZ_OPENERROR -1000

Definition at line 41 of file quazip.h.

Referenced by QuaZip::open().

13.98 src/ckb/quazip/quazip_global.h File Reference

```
#include <QtCore/qglobal.h>
```

Include dependency graph for quazip_global.h:

This graph shows which files directly or indirectly include this file:

Macros

- #define QUAZIP_EXPORT Q_DECL_IMPORT

  This is automatically defined when building a static library, but when including QuaZip sources directly into a project, QUAZIP_STATIC should be defined explicitly to avoid possible troubles with unnecessary importing/exporting.
- #define UNUSED
- #define QUAZIP_EXTRA_NTFS_MAGIC 0x000Au
- #define QUAZIP_EXTRA_NTFS_TIME_MAGIC 0x0001u

13.98.1 Macro Definition Documentation

13.98.1.1 #define QUAZIP_EXPORT Q_DECL_IMPORT

When building a DLL with MSVC, QUAZIP_BUILD must be defined. qglobal.h takes care of defining Q_DECL_∗ correctly for msvc/gcc.

Definition at line 46 of file quazip_global.h.

13.98.1.2 #define QUAZIP_EXTRA_NTFS_MAGIC 0x000Au

Definition at line 56 of file quazip_global.h.

Referenced by getNTFSTime(), and setNTFSTime().

13.98.1.3 #define QUAZIP_EXTRA_NTFS_TIME_MAGIC 0x0001u

Definition at line 57 of file quazip_global.h.

Referenced by getNTFSTime(), and setNTFSTime().

13.98.1.4 #define UNUSED

Definition at line 53 of file quazip_global.h.

13.99 src/ckb/quazip/quazipdir.cpp File Reference

```
#include "quazipdir.h"
#include <QSet>
#include <QSharedData>
```

Include dependency graph for quazipdir.cpp:

Functions

- QuaZipFileInfo64 QuaZipDir_getFileInfo (QuaZip *zip, bool *ok, const QString &relativeName, bool isReal)
- static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > &from, QList< QuaZipFileInfo64 > &to)
- static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > &from, QStringList &to)
- static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > &from, QList< QuaZipFileInfo > &to)

13.99.1 Function Documentation

13.99.1.1 static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > & *from*, QList< QuaZipFileInfo64 > & *to*) [static]

Definition at line 188 of file quazipdir.cpp.

```
{
    to = from;
}
```

13.99.1.2 static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > & *from*, QStringList & *to*) [static]

Definition at line 194 of file quazipdir.cpp.

```
{
    to.clear();
    for (QList<QuaZipFileInfo64>::const_iterator i = from.constBegin();
            i != from.constEnd();
            ++i) {
        to.append(i->name);
    }
}
```

13.99.1.3 static void QuaZipDir_convertInfoList (const QList< QuaZipFileInfo64 > & *from*, QList< QuaZipFileInfo > & *to*) [static]

Definition at line 205 of file quazipdir.cpp.

```
{
    to.clear();
    for (QList<QuaZipFileInfo64>::const_iterator i = from.constBegin();
            i != from.constEnd();
            ++i) {
        QuaZipFileInfo info32;
        i->toQuaZipFileInfo(info32);
        to.append(info32);
    }
}
```

13.99.1.4 QuaZipFileInfo64 QuaZipDir_getFileInfo (QuaZip * *zip*, bool * *ok*, const QString & *relativeName*, bool *isReal*)

Definition at line 165 of file quazipdir.cpp.

References QuaZipFileInfo64::compressedSize, QuaZipFileInfo64::crc, QuaZipFileInfo64::diskNumberStart, QuaZipFileInfo64::externalAttr, QuaZipFileInfo64::flags, QuaZip::getCurrentFileInfo(), QuaZipFileInfo64::internalAttr, QuaZipFileInfo64::method, QuaZipFileInfo64::name, QuaZipFileInfo64::uncompressedSize, QuaZipFileInfo64::versionCreated, and QuaZipFileInfo64::versionNeeded.

```
{
    QuaZipFileInfo64 info;
    if (isReal) {
        *ok = zip->getCurrentFileInfo(&info);
    } else {
        *ok = true;
        info.compressedSize = 0;
        info.crc = 0;
        info.diskNumberStart = 0;
        info.externalAttr = 0;
        info.flags = 0;
        info.internalAttr = 0;
        info.method = 0;
        info.uncompressedSize = 0;
        info.versionCreated = info.versionNeeded = 0;
    }
    info.name = relativeName;
    return info;
}
```

Here is the call graph for this function:

13.100 src/ckb/quazip/quazipdir.h File Reference

```
#include "quazip.h"
#include "quazipfileinfo.h"
#include <QDir>
#include <QList>
#include <QSharedDataPointer>
```

Include dependency graph for quazipdir.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaZipDir

  Provides ZIP archive navigation.

13.101 src/ckb/quazip/quazipfile.cpp File Reference

```
#include "quazipfile.h"
```

Include dependency graph for quazipfile.cpp:

Data Structures

- class QuaZipFilePrivate

  The implementation class for QuaZip.

13.102 src/ckb/quazip/quazipfile.h File Reference

```
#include <QIODevice>
#include "quazip_global.h"
#include "quazip.h"
#include "quazipnewinfo.h"
```

Include dependency graph for quazipfile.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class QuaZipFile

  A file inside ZIP archive.

13.103 src/ckb/quazip/quazipfileinfo.cpp File Reference

`#include "quazipfileinfo.h"`
Include dependency graph for quazipfileinfo.cpp:

Functions

- static QFile::Permissions permissionsFromExternalAttr (quint32 externalAttr)
- static QDateTime getNTFSTime (const QByteArray &extra, int position, int *fineTicks)

13.103.1 Function Documentation

13.103.1.1 static QDateTime getNTFSTime (const QByteArray & *extra*, int *position*, int * *fineTicks*) [static]

Definition at line 92 of file quazipfileinfo.cpp.

References QUAZIP_EXTRA_NTFS_MAGIC, and QUAZIP_EXTRA_NTFS_TIME_MAGIC.

Referenced by QuaZipFileInfo64::getNTFSaTime(), QuaZipFileInfo64::getNTFScTime(), and QuaZipFileInfo64::getNTFSmTime().

```
{
    QDateTime dateTime;
    for (int i = 0; i <= extra.size() - 4; ) {
        unsigned type = static_cast<unsigned>(static_cast<unsigned char>(
                                                extra.at(i)))
                | (static_cast<unsigned>(static_cast<unsigned char>(
                                                 extra.at(i + 1))) << 8);
        i += 2;
        unsigned length = static_cast<unsigned>(static_cast<unsigned char>(
                                                 extra.at(i)))
                 | (static_cast<unsigned>(static_cast<unsigned char>(
                                                 extra.at(i + 1))) << 8);
        i += 2;
        if (type == QUAZIP_EXTRA_NTFS_MAGIC && length >= 32) {
            i += 4; // reserved
            while (i <= extra.size() - 4) {
                unsigned tag = static_cast<unsigned>(
                            static_cast<unsigned char>(extra.at(i)))
                        | (static_cast<unsigned>(
                                static_cast<unsigned char>(extra.at(i + 1)))
                            << 8);
                i += 2;
                int tagsize = static_cast<unsigned>(
                            static_cast<unsigned char>(extra.at(i)))
                        | (static_cast<unsigned>(
                                static_cast<unsigned char>(extra.at(i + 1)))
                            << 8);
                i += 2;
                if (tag == QUAZIP_EXTRA_NTFS_TIME_MAGIC
                        && tagsize >= position + 8) {
                    i += position;
                    quint64 mtime = static_cast<quint64>(
                                 static_cast<unsigned char>(extra.at(i)))
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 1))) << 8)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 2))) << 16)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 3))) << 24)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 4))) << 32)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 5))) << 40)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 6))) << 48)
                        | (static_cast<quint64>(static_cast<unsigned char>(
                                                extra.at(i + 7))) << 56);
                    // the NTFS time is measured from 1601 for whatever reason
                    QDateTime base(QDate(1601, 1, 1), QTime(0, 0), Qt::UTC);
                    dateTime = base.addMSecs(mtime / 10000);
                    if (fineTicks != NULL) {
                        *fineTicks = static_cast<int>(mtime % 10000);
                    }
                    i += tagsize - position;
                } else {
                    i += tagsize;
                }

            }
        } else {
            i += length;
        }
    }
    if (fineTicks != NULL && dateTime.isNull()) {
        *fineTicks = 0;
    }
    return dateTime;
}
```

Here is the caller graph for this function:

13.103.1.2 static QFile::Permissions permissionsFromExternalAttr (quint32 *externalAttr*) [static]

Definition at line 27 of file quazipfileinfo.cpp.

Referenced by QuaZipFileInfo::getPermissions(), and QuaZipFileInfo64::getPermissions().

```
27                                                                          {
28     quint32 uPerm = (externalAttr & 0xFFFF0000u) >> 16;
29     QFile::Permissions perm = 0;
30     if ((uPerm & 0400) != 0)
31         perm |= QFile::ReadOwner;
32     if ((uPerm & 0200) != 0)
33         perm |= QFile::WriteOwner;
34     if ((uPerm & 0100) != 0)
35         perm |= QFile::ExeOwner;
36     if ((uPerm & 0040) != 0)
37         perm |= QFile::ReadGroup;
38     if ((uPerm & 0020) != 0)
39         perm |= QFile::WriteGroup;
40     if ((uPerm & 0010) != 0)
41         perm |= QFile::ExeGroup;
42     if ((uPerm & 0004) != 0)
43         perm |= QFile::ReadOther;
44     if ((uPerm & 0002) != 0)
45         perm |= QFile::WriteOther;
46     if ((uPerm & 0001) != 0)
47         perm |= QFile::ExeOther;
48     return perm;
49
50 }
```

Here is the caller graph for this function:

13.104 src/ckb/quazip/quazipfileinfo.h File Reference

```
#include <QByteArray>
```

```
#include <QDateTime>
#include <QFile>
#include "quazip_global.h"
```

Include dependency graph for quazipfileinfo.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct QuaZipFileInfo

  Information about a file inside archive.

- struct QuaZipFileInfo64

  Information about a file inside archive (with zip64 support).

13.105 src/ckb/quazip/quazipnewinfo.cpp File Reference

```
#include <QFileInfo>
#include "quazipnewinfo.h"
#include <string.h>
```

Include dependency graph for quazipnewinfo.cpp:

Functions

- static void QuaZipNewInfo_setPermissions (QuaZipNewInfo *info, QFile::Permissions perm, bool isDir)
- template<typename FileInfo >
  void QuaZipNewInfo_init (QuaZipNewInfo &self, const FileInfo &existing)
- static void setNTFSTime (QByteArray &extra, const QDateTime &time, int position, int fineTicks)

13.105.1 Function Documentation

13.105.1.1 template<typename FileInfo > void QuaZipNewInfo_init (QuaZipNewInfo & *self*, const FileInfo & *existing*)

Definition at line 57 of file quazipnewinfo.cpp.

Referenced by QuaZipNewInfo::QuaZipNewInfo().

```
{
    self.name = existing.name;
    self.dateTime = existing.dateTime;
    self.internalAttr = existing.internalAttr;
    self.externalAttr = existing.externalAttr;
    self.comment = existing.comment;
    self.extraLocal = existing.extra;
    self.extraGlobal = existing.extra;
    self.uncompressedSize = existing.uncompressedSize;
}
```

Here is the caller graph for this function:

13.105.1.2 static void QuaZipNewInfo_setPermissions (QuaZipNewInfo * *info*, QFile::Permissions *perm*, bool *isDir*) [static]

Definition at line 31 of file quazipnewinfo.cpp.

References QuaZipNewInfo::externalAttr.

Referenced by QuaZipNewInfo::QuaZipNewInfo(), QuaZipNewInfo::setFilePermissions(), and QuaZipNewInfo::setPermissions().

```
{
    quint32 uPerm = isDir ? 0040000 : 0100000;
    if ((perm & QFile::ReadOwner) != 0)
        uPerm |= 0400;
    if ((perm & QFile::WriteOwner) != 0)
        uPerm |= 0200;
    if ((perm & QFile::ExeOwner) != 0)
        uPerm |= 0100;
    if ((perm & QFile::ReadGroup) != 0)
        uPerm |= 0040;
    if ((perm & QFile::WriteGroup) != 0)
        uPerm |= 0020;
    if ((perm & QFile::ExeGroup) != 0)
        uPerm |= 0010;
    if ((perm & QFile::ReadOther) != 0)
        uPerm |= 0004;
    if ((perm & QFile::WriteOther) != 0)
        uPerm |= 0002;
    if ((perm & QFile::ExeOther) != 0)
        uPerm |= 0001;
    info->externalAttr = (info->externalAttr & ~0xFFFF0000u) | (uPerm << 16);
}
```

Here is the caller graph for this function:

13.105.1.3 static void setNTFSTime (QByteArray & *extra*, const QDateTime & *time*, int *position*, int *fineTicks*) [static]

Definition at line 131 of file quazipnewinfo.cpp.

References QUAZIP_EXTRA_NTFS_MAGIC, and QUAZIP_EXTRA_NTFS_TIME_MAGIC.

Referenced by QuaZipNewInfo::setFileNTFSaTime(), QuaZipNewInfo::setFileNTFScTime(), and QuaZipNewInfo::setFileNTFSmTime().

```
                                        {
    int ntfsPos = -1, timesPos = -1;
    unsigned ntfsLength = 0, ntfsTimesLength = 0;
    for (int i = 0; i <= extra.size() - 4; ) {
        unsigned type = static_cast<unsigned>(static_cast<unsigned char>(
                                                extra.at(i)))
                | (static_cast<unsigned>(static_cast<unsigned char>(
                                                extra.at(i + 1))) << 8);
        i += 2;
        unsigned length = static_cast<unsigned>(static_cast<unsigned char>(
                                                extra.at(i)))
                | (static_cast<unsigned>(static_cast<unsigned char>(
                                                extra.at(i + 1))) << 8);
        i += 2;
        if (type == QUAZIP_EXTRA_NTFS_MAGIC) {
            ntfsPos = i - 4; // the beginning of the NTFS record
            ntfsLength = length;
            if (length <= 4) {
                break; // no times in the NTFS record
            }
            i += 4; // reserved
            while (i <= extra.size() - 4) {
                unsigned tag = static_cast<unsigned>(
                            static_cast<unsigned char>(extra.at(i)))
                        | (static_cast<unsigned>(
                                static_cast<unsigned char>(extra.at(i + 1)))
                            << 8);
                i += 2;
                unsigned tagsize = static_cast<unsigned>(
                            static_cast<unsigned char>(extra.at(i)))
                        | (static_cast<unsigned>(
                                static_cast<unsigned char>(extra.at(i + 1)))
                            << 8);
                i += 2;
                if (tag == QUAZIP_EXTRA_NTFS_TIME_MAGIC) {
                    timesPos = i - 4; // the beginning of the NTFS times tag
                    ntfsTimesLength = tagsize;
                    break;
                } else {
                    i += tagsize;
                }
            }
            break; // I ain't going to search for yet another NTFS record!
        } else {
            i += length;
        }
    }
    if (ntfsPos == -1) {
        // No NTFS record, need to create one.
        ntfsPos = extra.size();
        ntfsLength = 32;
        extra.resize(extra.size() + 4 + ntfsLength);
        // the NTFS record header
        extra[ntfsPos] = static_cast<char>(QUAZIP_EXTRA_NTFS_MAGIC);
        extra[ntfsPos + 1] = static_cast<char>(QUAZIP_EXTRA_NTFS_MAGIC >> 8);
        extra[ntfsPos + 2] = 32; // the 2-byte size in LittleEndian
        extra[ntfsPos + 3] = 0;
        // zero the record
        memset(extra.data() + ntfsPos + 4, 0, 32);
        timesPos = ntfsPos + 8;
        // now set the tag data
        extra[timesPos] = static_cast<char>(QUAZIP_EXTRA_NTFS_TIME_MAGIC);
        extra[timesPos + 1] = static_cast<char>(QUAZIP_EXTRA_NTFS_TIME_MAGIC
                                                >> 8);
        // the size:
        extra[timesPos + 2] = 24;
        extra[timesPos + 3] = 0;
        ntfsTimesLength = 24;
    }
    if (timesPos == -1) {
        // No time tag in the NTFS record, need to add one.
        timesPos = ntfsPos + 4 + ntfsLength;
        extra.resize(extra.size() + 28);
        // Now we need to move the rest of the field
        // (possibly zero bytes, but memmove() is OK with that).
        // 0 ......... ntfsPos .. ntfsPos + 4   ... timesPos
        // <some data> <header>   <NTFS record>     <need-to-move data>    <end>
        memmove(extra.data() + timesPos + 28, extra.data() + timesPos,
                extra.size() - 28 - timesPos);
        ntfsLength += 28;
        // now set the tag data
```

```
        extra[timesPos] = static_cast<char>(QUAZIP_EXTRA_NTFS_TIME_MAGIC);
        extra[timesPos + 1] = static_cast<char>(QUAZIP_EXTRA_NTFS_TIME_MAGIC
                                                >> 8);
        // the size:
        extra[timesPos + 2] = 24;
        extra[timesPos + 3] = 0;
        // zero the record
        memset(extra.data() + timesPos + 4, 0, 24);
        ntfsTimesLength = 24;
    }
    if (ntfsTimesLength < 24) {
        // Broken times field. OK, this is really unlikely, but just in case...
        size_t timesEnd = timesPos + 4 + ntfsTimesLength;
        extra.resize(extra.size() + (24 - ntfsTimesLength));
        // Move it!
        // 0 ......... timesPos .... timesPos + 4 .. timesEnd
        // <some data> <time header> <broken times> <need-to-move data> <end>
        memmove(extra.data() + timesEnd + (24 - ntfsTimesLength),
                extra.data() + timesEnd,
                extra.size() - (24 - ntfsTimesLength) - timesEnd);
        // Now we have to increase the NTFS record and time tag lengths.
        ntfsLength += (24 - ntfsTimesLength);
        ntfsTimesLength = 24;
        extra[ntfsPos + 2] = static_cast<char>(ntfsLength);
        extra[ntfsPos + 3] = static_cast<char>(ntfsLength >> 8);
        extra[timesPos + 2] = static_cast<char>(ntfsTimesLength);
        extra[timesPos + 3] = static_cast<char>(ntfsTimesLength >> 8);
    }
    QDateTime base(QDate(1601, 1, 1), QTime(0, 0), Qt::UTC);
#if (QT_VERSION >= 0x040700)
    quint64 ticks = base.msecsTo(time) * 10000 + fineTicks;
#else
    QDateTime utc = time.toUTC();
    quint64 ticks = (static_cast<qint64>(base.date().daysTo(utc.date()))
            * Q_INT64_C(86400000)
            + static_cast<qint64>(base.time().msecsTo(utc.time())))
        * Q_INT64_C(10000) + fineTicks;
#endif
    extra[timesPos + 4 + position] = static_cast<char>(ticks);
    extra[timesPos + 5 + position] = static_cast<char>(ticks >> 8);
    extra[timesPos + 6 + position] = static_cast<char>(ticks >> 16);
    extra[timesPos + 7 + position] = static_cast<char>(ticks >> 24);
    extra[timesPos + 8 + position] = static_cast<char>(ticks >> 32);
    extra[timesPos + 9 + position] = static_cast<char>(ticks >> 40);
    extra[timesPos + 10 + position] = static_cast<char>(ticks >> 48);
    extra[timesPos + 11 + position] = static_cast<char>(ticks >> 56);
}
```

Here is the caller graph for this function:

13.106 src/ckb/quazip/quazipnewinfo.h File Reference

```
#include <QDateTime>
#include <QFile>
#include <QString>
#include "quazip_global.h"
#include "quazipfileinfo.h"
```

Include dependency graph for quazipnewinfo.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct QuaZipNewInfo

  Information about a file to be created.

13.107 src/ckb/quazip/unzip.c File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include "zlib.h"
#include "unzip.h"
#include <errno.h>
#include "crypt.h"
```

Include dependency graph for unzip.c:

Data Structures

- struct unz_file_info64_internal_s
- struct file_in_zip64_read_info_s
- struct unz64_s

Macros

- #define local static
- #define CASESENSITIVITYDEFAULT_NO
- #define UNZ_BUFSIZE (16384)
- #define UNZ_MAXFILENAMEINZIP (256)
- #define ALLOC(size) (malloc(size))
- #define TRYFREE(p) {if (p) free(p);}
- #define SIZECENTRALDIRITEM (0x2e)
- #define SIZEZIPLOCALHEADER (0x1e)
- #define CASESENSITIVITYDEFAULTVALUE 2
- #define STRCMPCASENOSENTIVEFUNCTION strcmpcasenosensitive_internal
- #define BUFREADCOMMENT (0x400)

Typedefs

- typedef uLongf z_crc_t
- typedef struct unz_file_info64_internal_s unz_file_info64_internal

Functions

- static int unz64local_getByte _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi))
- static int unz64local_getByte (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi)
- static int unz64local_getShort _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX))

- static int unz64local_getShort (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)
- static int unz64local_getLong (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)
- static int unz64local_getLong64 _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX))
- static int unz64local_getLong64 (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX)
- static int strcmpcasenosensitive_internal (const char *fileName1, const char *fileName2)
- int ZEXPORT unzStringFileNameCompare (const char *fileName1, const char *fileName2, int iCaseSensitivity)
- static ZPOS64_T unz64local_SearchCentralDir _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream))
- static ZPOS64_T unz64local_SearchCentralDir (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)
- static ZPOS64_T unz64local_SearchCentralDir64 (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)
- unzFile unzOpenInternal (voidpf file, zlib_filefunc64_32_def *pzlib_filefunc64_32_def, int is64bitOpenFunction, unsigned flags)
- unzFile ZEXPORT unzOpen2 (voidpf file, zlib_filefunc_def *pzlib_filefunc32_def)
- unzFile ZEXPORT unzOpen2_64 (voidpf file, zlib_filefunc64_def *pzlib_filefunc_def)
- unzFile ZEXPORT unzOpen (voidpf file)
- unzFile ZEXPORT unzOpen64 (voidpf file)
- int ZEXPORT unzClose (unzFile file)
- int ZEXPORT unzGetGlobalInfo64 (unzFile file, unz_global_info64 *pglobal_info)
- int ZEXPORT unzGetGlobalInfo (unzFile file, unz_global_info *pglobal_info32)
- static void unz64local_DosDateToTmuDate (ZPOS64_T ulDosDate, tm_unz *ptm)
- static int unz64local_GetCurrentFileInfoInternal _Z_OF ((unzFile file, unz_file_info64 *pfile_info, unz_file_info64_internal *pfile_info_internal, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize))
- static int unz64local_GetCurrentFileInfoInternal (unzFile file, unz_file_info64 *pfile_info, unz_file_info64_internal *pfile_info_internal, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize)
- int ZEXPORT unzGetCurrentFileInfo64 (unzFile file, unz_file_info64 *pfile_info, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize)
- int ZEXPORT unzGetCurrentFileInfo (unzFile file, unz_file_info *pfile_info, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize)
- int ZEXPORT unzGoToFirstFile (unzFile file)
- int ZEXPORT unzGoToNextFile (unzFile file)
- int ZEXPORT unzLocateFile (unzFile file, const char *szFileName, int iCaseSensitivity)
- int ZEXPORT unzGetFilePos64 (unzFile file, unz64_file_pos *file_pos)
- int ZEXPORT unzGetFilePos (unzFile file, unz_file_pos *file_pos)
- int ZEXPORT unzGoToFilePos64 (unzFile file, const unz64_file_pos *file_pos)
- int ZEXPORT unzGoToFilePos (unzFile file, unz_file_pos *file_pos)
- static int unz64local_CheckCurrentFileCoherencyHeader (unz64_s *s, uInt *piSizeVar, ZPOS64_T *poffset_local_extrafield, uInt *psize_local_extrafield)
- int ZEXPORT unzOpenCurrentFile3 (unzFile file, int *method, int *level, int raw, const char *password)
- int ZEXPORT unzOpenCurrentFile (unzFile file)
- int ZEXPORT unzOpenCurrentFilePassword (unzFile file, const char *password)
- int ZEXPORT unzOpenCurrentFile2 (unzFile file, int *method, int *level, int raw)
- ZPOS64_T ZEXPORT unzGetCurrentFileZStreamPos64 (unzFile file)

  Addition for GDAL : START.
- int ZEXPORT unzReadCurrentFile (unzFile file, voidp buf, unsigned len)

Addition for GDAL : END.

- z_off_t ZEXPORT unztell (unzFile file)
- ZPOS64_T ZEXPORT unztell64 (unzFile file)
- int ZEXPORT unzeof (unzFile file)
- int ZEXPORT unzGetLocalExtrafield (unzFile file, voidp buf, unsigned len)
- int ZEXPORT unzCloseCurrentFile (unzFile file)
- int ZEXPORT unzGetGlobalComment (unzFile file, char *szComment, uLong uSizeBuf)
- ZPOS64_T ZEXPORT unzGetOffset64 (unzFile file)
- uLong ZEXPORT unzGetOffset (unzFile file)
- int ZEXPORT unzSetOffset64 (unzFile file, ZPOS64_T pos)
- int ZEXPORT unzSetOffset (unzFile file, uLong pos)
- int ZEXPORT unzSetFlags (unzFile file, unsigned flags)
- int ZEXPORT unzClearFlags (unzFile file, unsigned flags)

Variables

- const char unz_copyright []

13.107.1 Data Structure Documentation

13.107.1.1 struct unz_file_info64_internal_s

Definition at line 128 of file unzip.c.

Collaboration diagram for unz_file_info64_internal_s:

Data Fields

ZPOS64_T	offset_curfile	

13.107.1.2 struct file_in_zip64_read_info_s

Definition at line 136 of file unzip.c.

Collaboration diagram for file_in_zip64_read_info_s:

Data Fields

ZPOS64_T	byte_before_the_zipfile	
uLong	compression_method	
uLong	crc32	
uLong	crc32_wait	
voidpf	filestream	
ZPOS64_T	offset_local_extrafield	
ZPOS64_T	pos_in_zipfile	
ZPOS64_T	pos_local_extrafield	
int	raw	
char *	read_buffer	
ZPOS64_T	rest_read_compressed	
ZPOS64_T	rest_read_uncompressed	
uInt	size_local_extrafield	
z_stream	stream	
uLong	stream_initialised	
ZPOS64_T	total_out_64	
zlib_filefunc64_32_def	z_filefunc	

13.107.1.3 struct unz64_s

Definition at line 167 of file unzip.c.

Collaboration diagram for unz64_s:

Data Fields

ZPOS64_T	byte_before_the_zipfile	
ZPOS64_T	central_pos	
unz_file_info64	cur_file_info	
unz_file_info64_internal	cur_file_info_internal	
ZPOS64_T	current_file_ok	
int	encrypted	
voidpf	filestream	
unsigned	flags	
unz_global_info64	gi	
int	is64bitOpenFunction	
int	isZip64	
unsigned long	keys[3]	
ZPOS64_T	num_file	
ZPOS64_T	offset_central_dir	
const z_crc_t FAR *	pcrc_32_tab	
file_in_zip64_read_info_s *	pfile_in_zip_read	
ZPOS64_T	pos_in_central_dir	
ZPOS64_T	size_central_dir	
zlib_filefunc64_32_def	z_filefunc	

13.107.2 Macro Definition Documentation

13.107.2.1 #define ALLOC(*size*) (malloc(size))

Definition at line 114 of file unzip.c.

Referenced by unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), unzOpenCurrentFile3(), and

unzOpenInternal().

13.107.2.2 #define BUFREADCOMMENT (0x400)

Definition at line 408 of file unzip.c.

Referenced by unz64local_SearchCentralDir(), and unz64local_SearchCentralDir64().

13.107.2.3 #define CASESENSITIVITYDEFAULT_NO

Definition at line 100 of file unzip.c.

13.107.2.4 #define CASESENSITIVITYDEFAULTVALUE 2

Definition at line 375 of file unzip.c.

Referenced by unzStringFileNameCompare().

13.107.2.5 #define local static

Definition at line 93 of file unzip.c.

13.107.2.6 #define SIZECENTRALDIRITEM (0x2e)

Definition at line 120 of file unzip.c.

Referenced by unzGoToNextFile().

13.107.2.7 #define SIZEZIPLOCALHEADER (0x1e)

Definition at line 121 of file unzip.c.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), and unzOpenCurrentFile3().

13.107.2.8 #define STRCMPCASENOSENTIVEFUNCTION strcmpcasenosensitive_internal

Definition at line 381 of file unzip.c.

Referenced by unzStringFileNameCompare().

13.107.2.9 #define TRYFREE(*p*) {if (p) free(p);}

Definition at line 117 of file unzip.c.

Referenced by unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), unzClose(), unzCloseCurrentFile(), and unzOpenCurrentFile3().

13.107.2.10 #define UNZ_BUFSIZE (16384)

Definition at line 106 of file unzip.c.

Referenced by unzOpenCurrentFile3(), and unzReadCurrentFile().

13.107.2.11 #define UNZ_MAXFILENAMEINZIP (256)

Definition at line 110 of file unzip.c.

Referenced by unzLocateFile().

13.107.3 Typedef Documentation

13.107.3.1 typedef struct unz_file_info64_internal_s unz_file_info64_internal

13.107.3.2 typedef uLongf z_crc_t

Definition at line 76 of file unzip.c.

13.107.4 Function Documentation

13.107.4.1 static int unz64local_getByte _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi)) [static]

13.107.4.2 static int unz64local_getShort _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)) [static]

13.107.4.3 static int unz64local_getLong64 _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX)) [static]

13.107.4.4 static ZPOS64_T unz64local_SearchCentralDir _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)) [static]

13.107.4.5 static int unz64local_GetCurrentFileInfoInternal _Z_OF ((unzFile file, unz_file_info64 *pfile_info, unz_file_info64_internal *pfile_info_internal, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize)) [static]

13.107.4.6 static int strcmpcasenosensitive_internal (const char * *fileName1*, const char * *fileName2*) [static]

Definition at line 352 of file unzip.c.

```
{
    for (;;)
    {
        char c1=*(fileName1++);
        char c2=*(fileName2++);
        if ((c1>='a') && (c1<='z'))
            c1 -= 0x20;
        if ((c2>='a') && (c2<='z'))
            c2 -= 0x20;
        if (c1=='\0')
            return ((c2=='\0') ? 0 : -1);
        if (c2=='\0')
            return 1;
        if (c1<c2)
            return -1;
        if (c1>c2)
            return 1;
    }
}
```

13.107.4.7 static int unz64local_CheckCurrentFileCoherencyHeader (unz64_s * *s*, uInt * *piSizeVar*, ZPOS64_T * *poffset_local_extrafield*, uInt * *psize_local_extrafield*) [static]

Definition at line 1393 of file unzip.c.

References unz64_s::byte_before_the_zipfile, unz_file_info64_s::compressed_size, unz_file_info64_s::compression_method, unz_file_info64_s::crc, unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::filestream, unz_file_info64_internal_s::offset_curfile, unz_file_info64_s::size_filename, SIZEZIPLOCALHEADER, unz_file_info64_s::uncompressed_size, unz64local_getLong(), unz64local_getShort(), UNZ_BADZIPFILE, UNZ_ERRNO, UNZ_OK, Z_BZIP2ED, unz64_s::z_filefunc, ZLIB_FILEFUNC_SEEK_SET, and ZSEEK64.

Referenced by unzOpenCurrentFile3().

```
{
    uLong uMagic,uData,uFlags;
    uLong size_filename;
    uLong size_extra_field;
    int err=UNZ_OK;

    *piSizeVar = 0;
    *poffset_local_extrafield = 0;
    *psize_local_extrafield = 0;

    if (ZSEEK64(s->z_filefunc, s->filestream,s->cur_file_info_internal.offset_curfile +
                                s->byte_before_the_zipfile, ZLIB_FILEFUNC_SEEK_SET)!=0)
        return UNZ_ERRNO;


    if (err==UNZ_OK)
    {
        if (unz64local_getLong(&s->z_filefunc, s->filestream,&uMagic) != UNZ_OK)
            err=UNZ_ERRNO;
        else if (uMagic!=0x04034b50)
            err=UNZ_BADZIPFILE;
    }

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&uData) != UNZ_OK)
        err=UNZ_ERRNO;
/*
    else if ((err==UNZ_OK) && (uData!=s->cur_file_info.wVersion))
        err=UNZ_BADZIPFILE;
*/
    if (unz64local_getShort(&s->z_filefunc, s->filestream,&uFlags) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&uData) != UNZ_OK)
        err=UNZ_ERRNO;
    else if ((err==UNZ_OK) && (uData!=s->cur_file_info.compression_method))
        err=UNZ_BADZIPFILE;

    if ((err==UNZ_OK) && (s->cur_file_info.compression_method!=0) &&
/* #ifdef HAVE_BZIP2 */
                        (s->cur_file_info.compression_method!=Z_BZIP2ED) &&
/* #endif */
                        (s->cur_file_info.compression_method!=Z_DEFLATED))
        err=UNZ_BADZIPFILE;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&uData) != UNZ_OK) /* date/time */
        err=UNZ_ERRNO;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&uData) != UNZ_OK) /* crc */
        err=UNZ_ERRNO;
    else if ((err==UNZ_OK) && (uData!=s->cur_file_info.crc) && ((uFlags & 8)==0))
        err=UNZ_BADZIPFILE;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&uData) != UNZ_OK) /* size compr */
        err=UNZ_ERRNO;
    else if (uData != 0xFFFFFFFF && (err==UNZ_OK) && (uData!=s->cur_file_info.compressed_size) && ((uFlags & 8)==0))
        err=UNZ_BADZIPFILE;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&uData) != UNZ_OK) /* size uncompr */
        err=UNZ_ERRNO;
    else if (uData != 0xFFFFFFFF && (err==UNZ_OK) && (uData!=s->cur_file_info.uncompressed_size) && ((uFlags & 8)==0))
        err=UNZ_BADZIPFILE;

    if (unz64local_getShort(&s->z_filefunc, s->
```

```
    filestream,&size_filename) != UNZ_OK)
        err=UNZ_ERRNO;
    else if ((err==UNZ_OK) && (size_filename!=s->cur_file_info.size_filename))
        err=UNZ_BADZIPFILE;

    *piSizeVar += (uInt)size_filename;

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&size_extra_field) != UNZ_OK)
        err=UNZ_ERRNO;
    *poffset_local_extrafield= s->cur_file_info_internal.offset_curfile +
                                    SIZEZIPLOCALHEADER + size_filename;
    *psize_local_extrafield = (uInt)size_extra_field;

    *piSizeVar += (uInt)size_extra_field;

    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.8 static void unz64local_DosDateToTmuDate (ZPOS64_T *ulDosDate*, tm_unz * *ptm*) [static]

Definition at line 862 of file unzip.c.

References tm_unz_s::tm_hour, tm_unz_s::tm_mday, tm_unz_s::tm_min, tm_unz_s::tm_mon, tm_unz_s::tm_sec, and tm_unz_s::tm_year.

Referenced by unz64local_GetCurrentFileInfoInternal().

```
{
    ZPOS64_T uDate;
    uDate = (ZPOS64_T)(ulDosDate>>16);
    ptm->tm_mday = (uInt)(uDate&0x1f) ;
    ptm->tm_mon =  (uInt)((((uDate)&0x1E0)/0x20)-1) ;
    ptm->tm_year = (uInt)(((uDate&0x0FE00)/0x0200)+1980) ;

    ptm->tm_hour = (uInt) ((ulDosDate &0xF800)/0x800);
    ptm->tm_min =  (uInt) ((ulDosDate&0x7E0)/0x20) ;
```

```
    ptm->tm_sec =  (uInt) (2*(ulDosDate&0x1f)) ;
}
```

Here is the caller graph for this function:

13.107.4.9 static int unz64local_getByte (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* int * *pi*) [static]

Definition at line 215 of file unzip.c.

References UNZ_EOF, UNZ_ERRNO, UNZ_OK, ZERROR64, and ZREAD64.

Referenced by unz64local_getLong(), unz64local_getLong64(), and unz64local_getShort().

```
{
    unsigned char c;
    int err = (int)ZREAD64(*pzlib_filefunc_def,filestream,&c,1);
    if (err==1)
    {
        *pi = (int)c;
        return UNZ_OK;
    }
    else
    {
        if (ZERROR64(*pzlib_filefunc_def,filestream))
            return UNZ_ERRNO;
        else
            return UNZ_EOF;
    }
}
```

Here is the caller graph for this function:

13.107.4.10 static int unz64local_GetCurrentFileInfoInternal (unzFile *file*, unz_file_info64 * *pfile_info*, unz_file_info64_internal * *pfile_info_internal*, char * *szFileName*, uLong *fileNameBufferSize*, void * *extraField*, uLong *extraFieldBufferSize*, char * *szComment*, uLong *commentBufferSize*) [static]

Definition at line 889 of file unzip.c.

References unz64_s::byte_before_the_zipfile, unz_file_info64_s::compressed_size, unz_file_info64_s::compression_method, unz_file_info64_s::crc, unz_file_info64_s::disk_num_start, unz_file_info64_s::dosDate, unz_file_info64_s::external_fa, unz64_s::filestream, unz_file_info64_s::flag, unz_file_info64_s::internal_fa, unz_file_info64_internal_s::offset_curfile, unz64_s::pos_in_central_dir, unz_file_info64_s::size_file_comment, unz_file_info64_s::size_file_extra, unz_file_info64_s::size_filename, unz_file_info64_s::tmu_date, unz_file_info64_s::uncompressed_size, unz64local_DosDateToTmuDate(), unz64local_getLong(), unz64local_getLong64(), unz64local_getShort(), UNZ_BADZIPFILE, UNZ_ERRNO, UNZ_OK, UNZ_PARAMERROR, unz_file_info64_s::version, unz_file_info64_s::version_needed, unz64_s::z_filefunc, ZLIB_FILEFUNC_SEEK_CUR, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, and ZSEEK64.

Referenced by unzGetCurrentFileInfo(), unzGetCurrentFileInfo64(), unzGoToFilePos64(), unzGoToFirstFile(), unzGoToNextFile(), and unzSetOffset64().

```
{
    unz64_s* s;
    unz_file_info64 file_info;
    unz_file_info64_internal file_info_internal;
    int err=UNZ_OK;
    uLong uMagic;
    ZPOS64_T llSeek=0;
    uLong uL;

    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    if (ZSEEK64(s->z_filefunc, s->filestream,
              s->pos_in_central_dir+s->byte_before_the_zipfile,
              ZLIB_FILEFUNC_SEEK_SET)!=0)
        err=UNZ_ERRNO;


    /* we check the magic */
    if (err==UNZ_OK)
    {
        if (unz64local_getLong(&s->z_filefunc, s->filestream,&uMagic) != UNZ_OK)
            err=UNZ_ERRNO;
        else if (uMagic!=0x02014b50)
            err=UNZ_BADZIPFILE;
    }

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.version) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.version_needed) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.flag) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.compression_method) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&file_info.dosDate) != UNZ_OK)
        err=UNZ_ERRNO;

    unz64local_DosDateToTmuDate(file_info.dosDate,&file_info.tmu_date);

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&file_info.crc) != UNZ_OK)
        err=UNZ_ERRNO;

    if (unz64local_getLong(&s->z_filefunc, s->filestream,&uL) != UNZ_OK)
        err=UNZ_ERRNO;
    file_info.compressed_size = uL;

    if (unz64local_getLong(&s->z_filefunc, s->
```

```
filestream,&uL) != UNZ_OK)
        err=UNZ_ERRNO;
  file_info.uncompressed_size = uL;

  if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.size_filename) != UNZ_OK)
        err=UNZ_ERRNO;

  if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.size_file_extra) != UNZ_OK)
        err=UNZ_ERRNO;

  if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.size_file_comment) != UNZ_OK)
        err=UNZ_ERRNO;

  if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.disk_num_start) != UNZ_OK)
        err=UNZ_ERRNO;

  if (unz64local_getShort(&s->z_filefunc, s->filestream,&file_info.internal_fa) != UNZ_OK)
        err=UNZ_ERRNO;

  if (unz64local_getLong(&s->z_filefunc, s->filestream,&file_info.external_fa) != UNZ_OK)
        err=UNZ_ERRNO;

                /* relative offset of local header */
  if (unz64local_getLong(&s->z_filefunc, s->filestream,&uL) != UNZ_OK)
        err=UNZ_ERRNO;
  file_info_internal.offset_curfile = uL;

  llSeek+=file_info.size_filename;
  if ((err==UNZ_OK) && (szFileName!=NULL))
  {
      uLong uSizeRead ;
      if (file_info.size_filename<fileNameBufferSize)
      {
          *(szFileName+file_info.size_filename)='\0';
          uSizeRead = file_info.size_filename;
      }
      else
          uSizeRead = fileNameBufferSize;

      if ((file_info.size_filename>0) && (fileNameBufferSize>0))
          if (ZREAD64(s->z_filefunc, s->filestream,szFileName,uSizeRead)!=uSizeRead)
              err=UNZ_ERRNO;
      llSeek -= uSizeRead;
  }

  /* Read extrafield */
  if ((err==UNZ_OK) && (extraField!=NULL))
  {
      ZPOS64_T uSizeRead ;
      if (file_info.size_file_extra<extraFieldBufferSize)
          uSizeRead = file_info.size_file_extra;
       else
          uSizeRead = extraFieldBufferSize;

       if (llSeek!=0)
       {
          if (ZSEEK64(s->z_filefunc, s->filestream,llSeek,ZLIB_FILEFUNC_SEEK_CUR)==0)
              llSeek=0;
          else
              err=UNZ_ERRNO;
       }

       if ((file_info.size_file_extra>0) && (extraFieldBufferSize>0))
          if (ZREAD64(s->z_filefunc, s->filestream,extraField,(uLong)uSizeRead)!=uSizeRead)
              err=UNZ_ERRNO;

       llSeek += file_info.size_file_extra - (uLong)uSizeRead;
    }
    else
       llSeek += file_info.size_file_extra;


    if ((err==UNZ_OK) && (file_info.size_file_extra != 0))
    {
                                uLong acc = 0;

       /* since lSeek now points to after the extra field we need to move back */
```

```
        llSeek -= file_info.size_file_extra;

        if (llSeek!=0)
        {
            if (ZSEEK64(s->z_filefunc, s->filestream,llSeek,
ZLIB_FILEFUNC_SEEK_CUR)==0)
                llSeek=0;
            else
                err=UNZ_ERRNO;
        }

        while(acc < file_info.size_file_extra)
        {
            uLong headerId;
                                                uLong dataSize;

            if (unz64local_getShort(&s->z_filefunc, s->
filestream,&headerId) != UNZ_OK)
                err=UNZ_ERRNO;

            if (unz64local_getShort(&s->z_filefunc, s->
filestream,&dataSize) != UNZ_OK)
                err=UNZ_ERRNO;

            /* ZIP64 extra fields */
            if (headerId == 0x0001)
            {
                uLong uL;

                if(file_info.uncompressed_size == (ZPOS64_T)0xFFFFFFFFu)
                {
                    if (unz64local_getLong64(&s->z_filefunc, s->
filestream,&file_info.uncompressed_size) != UNZ_OK)
                        err=UNZ_ERRNO;
                }

                if(file_info.compressed_size == (ZPOS64_T)0xFFFFFFFFu)
                {
                    if (unz64local_getLong64(&s->z_filefunc, s->
filestream,&file_info.compressed_size) != UNZ_OK)
                        err=UNZ_ERRNO;
                }

                if(file_info_internal.offset_curfile == (ZPOS64_T)0xFFFFFFFFu)
                {
                    /* Relative Header offset */
                    if (unz64local_getLong64(&s->z_filefunc, s->
filestream,&file_info_internal.offset_curfile) != UNZ_OK)
                        err=UNZ_ERRNO;
                }

                if(file_info.disk_num_start == 0xFFFFFFFFu)
                {
                    /* Disk Start Number */
                    if (unz64local_getLong(&s->z_filefunc, s->
filestream,&uL) != UNZ_OK)
                        err=UNZ_ERRNO;
                }

            }
            else
            {
                if (ZSEEK64(s->z_filefunc, s->filestream,dataSize,
ZLIB_FILEFUNC_SEEK_CUR)!=0)
                    err=UNZ_ERRNO;
            }

            acc += 2 + 2 + dataSize;
        }
    }

    if ((err==UNZ_OK) && (szComment!=NULL))
    {
        uLong uSizeRead ;
        if (file_info.size_file_comment<commentBufferSize)
        {
            *(szComment+file_info.size_file_comment)='\0';
            uSizeRead = file_info.size_file_comment;
        }
        else
            uSizeRead = commentBufferSize;

        if (llSeek!=0)
        {
            if (ZSEEK64(s->z_filefunc, s->filestream,llSeek,
ZLIB_FILEFUNC_SEEK_CUR)==0)
                llSeek=0;
```

```
            else
                err=UNZ_ERRNO;
        }

        if ((file_info.size_file_comment>0) && (commentBufferSize>0))
            if (ZREAD64(s->z_filefunc, s->filestream,szComment,uSizeRead)!=
    uSizeRead)
                err=UNZ_ERRNO;
        llSeek+=file_info.size_file_comment - uSizeRead;
    }
    else
        llSeek+=file_info.size_file_comment;


    if ((err==UNZ_OK) && (pfile_info!=NULL))
        *pfile_info=file_info;

    if ((err==UNZ_OK) && (pfile_info_internal!=NULL))
        *pfile_info_internal=file_info_internal;

    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.11 static int unz64local_getLong (const zlib_filefunc64_32_def * *pzlib_filefunc_def*, voidpf *filestream*, uLong * *pX*) [static]

Definition at line 269 of file unzip.c.

References unz64local_getByte(), and UNZ_OK.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), unz64local_GetCurrentFileInfoInternal(), unz64local_SearchCentralDir64(), and unzOpenInternal().

```
272 {
273     uLong x ;
```

```
    int i = 0;
    int err;

    err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x = (uLong)i;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((uLong)i)<<8;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((uLong)i)<<16;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x += ((uLong)i)<<24;

    if (err==UNZ_OK)
        *pX = x;
    else
        *pX = 0;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.12 static int unz64local_getLong64 (const zlib_filefunc64_32_def * *pzlib_filefunc_def*, voidpf *filestream*, ZPOS64_T * *pX*) [static]

Definition at line 305 of file unzip.c.

References unz64local_getByte(), and UNZ_OK.

Referenced by unz64local_GetCurrentFileInfoInternal(), unz64local_SearchCentralDir64(), and unzOpenInternal().

```
{
    ZPOS64_T x ;
    int i = 0;
    int err;

    err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x = (ZPOS64_T)i;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<8;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<16;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<24;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<32;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<40;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<48;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((ZPOS64_T)i)<<56;

    if (err==UNZ_OK)
        *pX = x;
    else
        *pX = 0;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.13 static int unz64local_getShort (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* uLong * *pX*) [static]

Definition at line 242 of file unzip.c.

References unz64local_getByte(), and UNZ_OK.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), unz64local_GetCurrentFileInfoInternal(), and unzOpenInternal().

```
{
    uLong x ;
    int i = 0;
    int err;

    err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x = (uLong)i;

    if (err==UNZ_OK)
        err = unz64local_getByte(pzlib_filefunc_def,filestream,&i);
    x |= ((uLong)i)<<8;

    if (err==UNZ_OK)
        *pX = x;
    else
        *pX = 0;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.14 static ZPOS64_T unz64local_SearchCentralDir (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream*) [static]

Definition at line 416 of file unzip.c.

References ALLOC, BUFREADCOMMENT, TRYFREE, ZLIB_FILEFUNC_SEEK_END, ZLIB_FILEFUNC_SEEK_-SET, ZREAD64, ZSEEK64, and ZTELL64.

Referenced by unzOpenInternal().

```
{
    unsigned char* buf;
    ZPOS64_T uSizeFile;
    ZPOS64_T uBackRead;
    ZPOS64_T uMaxBack=0xffff; /* maximum size of global comment */
    ZPOS64_T uPosFound=0;

    if (ZSEEK64(*pzlib_filefunc_def,filestream,0,ZLIB_FILEFUNC_SEEK_END) != 0)
        return 0;


    uSizeFile = ZTELL64(*pzlib_filefunc_def,filestream);

    if (uMaxBack>uSizeFile)
        uMaxBack = uSizeFile;

    buf = (unsigned char*)ALLOC(BUFREADCOMMENT+4);
    if (buf==NULL)
        return 0;

    uBackRead = 4;
    while (uBackRead<uMaxBack)
    {
        uLong uReadSize;
        ZPOS64_T uReadPos ;
        int i;
        if (uBackRead+BUFREADCOMMENT>uMaxBack)
            uBackRead = uMaxBack;
        else
            uBackRead+=BUFREADCOMMENT;
        uReadPos = uSizeFile-uBackRead ;

        uReadSize = ((BUFREADCOMMENT+4) < (uSizeFile-uReadPos)) ?
                     (BUFREADCOMMENT+4) : (uLong)(uSizeFile-uReadPos);
        if (ZSEEK64(*pzlib_filefunc_def,filestream,uReadPos,
    ZLIB_FILEFUNC_SEEK_SET)!=0)
            break;

        if (ZREAD64(*pzlib_filefunc_def,filestream,buf,uReadSize)!=uReadSize)
            break;

        for (i=(int)uReadSize-3; (i--)>0;)
            if (((*(buf+i))==0x50) && ((*(buf+i+1))==0x4b) &&
                ((*(buf+i+2))==0x05) && ((*(buf+i+3))==0x06))
            {
                uPosFound = uReadPos+i;
                break;
            }

        if (uPosFound!=0)
            break;
    }
    TRYFREE(buf);
    return uPosFound;
}
```

Here is the caller graph for this function:

13.107.4.15 static ZPOS64_T unz64local_SearchCentralDir64 (const zlib_filefunc64_32_def * *pzlib_filefunc_def*, voidpf *filestream*) [static]

Definition at line 481 of file unzip.c.

References ALLOC, BUFREADCOMMENT, TRYFREE, unz64local_getLong(), unz64local_getLong64(), UNZ_OK, ZLIB_FILEFUNC_SEEK_END, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, ZSEEK64, and ZTELL64.

Referenced by unzOpenInternal().

```
483 {
484     unsigned char* buf;
485     ZPOS64_T uSizeFile;
486     ZPOS64_T uBackRead;
487     ZPOS64_T uMaxBack=0xffff; /* maximum size of global comment */
488     ZPOS64_T uPosFound=0;
489     uLong uL;
490                 ZPOS64_T relativeOffset;
491
492     if (ZSEEK64(*pzlib_filefunc_def,filestream,0,ZLIB_FILEFUNC_SEEK_END) != 0)
493         return 0;
494
495
496     uSizeFile = ZTELL64(*pzlib_filefunc_def,filestream);
497
498     if (uMaxBack>uSizeFile)
499         uMaxBack = uSizeFile;
500
501     buf = (unsigned char*)ALLOC(BUFREADCOMMENT+4);
502     if (buf==NULL)
503         return 0;
504
505     uBackRead = 4;
506     while (uBackRead<uMaxBack)
507     {
508         uLong uReadSize;
509         ZPOS64_T uReadPos;
510         int i;
511         if (uBackRead+BUFREADCOMMENT>uMaxBack)
512             uBackRead = uMaxBack;
513         else
514             uBackRead+=BUFREADCOMMENT;
515         uReadPos = uSizeFile-uBackRead ;
516
517         uReadSize = ((BUFREADCOMMENT+4) < (uSizeFile-uReadPos)) ?
518                       (BUFREADCOMMENT+4) : (uLong)(uSizeFile-uReadPos);
519         if (ZSEEK64(*pzlib_filefunc_def,filestream,uReadPos,
    ZLIB_FILEFUNC_SEEK_SET)!=0)
520             break;
521
522         if (ZREAD64(*pzlib_filefunc_def,filestream,buf,uReadSize)!=uReadSize)
523             break;
524
525         for (i=(int)uReadSize-3; (i--)>0;)
526             if (((*(buf+i))==0x50) && ((*(buf+i+1))==0x4b) &&
527                 ((*(buf+i+2))==0x06) && ((*(buf+i+3))==0x07))
528             {
529                 uPosFound = uReadPos+i;
530                 break;
531             }
532
533         if (uPosFound!=0)
534             break;
535     }
536     TRYFREE(buf);
537     if (uPosFound == 0)
538         return 0;
539
540     /* Zip64 end of central directory locator */
541     if (ZSEEK64(*pzlib_filefunc_def,filestream, uPosFound,
    ZLIB_FILEFUNC_SEEK_SET)!=0)
542         return 0;
543
544     /* the signature, already checked */
545     if (unz64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
    UNZ_OK)
546         return 0;
547
548     /* number of the disk with the start of the zip64 end of  central directory */
549     if (unz64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
    UNZ_OK)
550         return 0;
551     if (uL != 0)
552         return 0;
```

```
    /* relative offset of the zip64 end of central directory record */
    if (unz64local_getLong64(pzlib_filefunc_def,filestream,&relativeOffset)!=UNZ_OK)
        return 0;

    /* total number of disks */
    if (unz64local_getLong(pzlib_filefunc_def,filestream,&uL)!=UNZ_OK)
        return 0;
    if (uL != 1)
        return 0;

    /* Goto end of central directory record */
    if (ZSEEK64(*pzlib_filefunc_def,filestream, relativeOffset,ZLIB_FILEFUNC_SEEK_SET)!=0)
        return 0;

     /* the signature */
    if (unz64local_getLong(pzlib_filefunc_def,filestream,&uL)!=UNZ_OK)
        return 0;

    if (uL != 0x06064b50)
        return 0;

    return relativeOffset;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.16 int ZEXPORT unzClearFlags (unzFile *file*, unsigned *flags*)

Definition at line 2147 of file unzip.c.

References unz64_s::flags, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::open().

```
{
    unz64_s* s;
    if (file == NULL)
        return UNZ_PARAMERROR;
    s = (unz64_s*)file;
    s->flags &= ~flags;
    return UNZ_OK;
}
```

Here is the caller graph for this function:

13.107.4.17 int ZEXPORT unzClose (unzFile *file*)

Definition at line 815 of file unzip.c.

References unz64_s::filestream, unz64_s::flags, unz64_s::pfile_in_zip_read, TRYFREE, UNZ_AUTO_CLOSE, UNZ_OK, UNZ_PARAMERROR, unzCloseCurrentFile(), unz64_s::z_filefunc, ZCLOSE64, and ZFAKECLOSE64.

Referenced by QuaZip::close(), and QuaZip::open().

```
{
    unz64_s* s;
    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;

    if (s->pfile_in_zip_read!=NULL)
        unzCloseCurrentFile(file);

    if ((s->flags & UNZ_AUTO_CLOSE) != 0)
        ZCLOSE64(s->z_filefunc, s->filestream);
    else
        ZFAKECLOSE64(s->z_filefunc, s->filestream);
    TRYFREE(s);
    return UNZ_OK;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.18 int ZEXPORT unzCloseCurrentFile (unzFile *file*)

Definition at line 2012 of file unzip.c.

References file_in_zip64_read_info_s::crc32, file_in_zip64_read_info_s::crc32_wait, unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::raw, file_in_zip64_read_info_s::read_buffer, file_in_zip64_read_info_s::rest_read_uncompressed, file_in_zip64_read_info_s::stream, file_in_zip64_read_info_s::stream_initialised, TRYFREE, UNZ_CRCERROR, UNZ_OK, UNZ_PARAMERROR, and Z_BZIP2ED.

Referenced by QuaZipFile::close(), unzClose(), and unzOpenCurrentFile3().

```
2013 {
2014     int err=UNZ_OK;
2015
2016     unz64_s* s;
2017     file_in_zip64_read_info_s* pfile_in_zip_read_info;
2018     if (file==NULL)
2019         return UNZ_PARAMERROR;
2020     s=(unz64_s*)file;
2021     pfile_in_zip_read_info=s->pfile_in_zip_read;
2022
2023     if (pfile_in_zip_read_info==NULL)
2024         return UNZ_PARAMERROR;
2025
2026
2027     if ((pfile_in_zip_read_info->rest_read_uncompressed == 0) &&
2028         (!pfile_in_zip_read_info->raw))
2029     {
2030         if (pfile_in_zip_read_info->crc32 != pfile_in_zip_read_info->
      crc32_wait)
2031             err=UNZ_CRCERROR;
2032     }
2033
2034
2035     TRYFREE(pfile_in_zip_read_info->read_buffer);
2036     pfile_in_zip_read_info->read_buffer = NULL;
2037     if (pfile_in_zip_read_info->stream_initialised == Z_DEFLATED)
2038         inflateEnd(&pfile_in_zip_read_info->stream);
2039 #ifdef HAVE_BZIP2
2040     else if (pfile_in_zip_read_info->stream_initialised ==
      Z_BZIP2ED)
2041         BZ2_bzDecompressEnd(&pfile_in_zip_read_info->bstream);
2042 #endif
2043
2044
2045     pfile_in_zip_read_info->stream_initialised = 0;
2046     TRYFREE(pfile_in_zip_read_info);
2047
2048     s->pfile_in_zip_read=NULL;
2049
2050     return err;
2051 }
```

Here is the caller graph for this function:

13.107.4.19 int ZEXPORT unzeof (unzFile *file*)

Definition at line 1932 of file unzip.c.

References unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::rest_read_uncompressed, and UNZ_PARAMERROR.

Referenced by QuaZipFile::atEnd().

```
1933 {
1934     unz64_s* s;
1935     file_in_zip64_read_info_s* pfile_in_zip_read_info;
1936     if (file==NULL)
1937         return UNZ_PARAMERROR;
1938     s=(unz64_s*)file;
1939     pfile_in_zip_read_info=s->pfile_in_zip_read;
1940
1941     if (pfile_in_zip_read_info==NULL)
1942         return UNZ_PARAMERROR;
1943
1944     if (pfile_in_zip_read_info->rest_read_uncompressed == 0)
1945         return 1;
1946     else
1947         return 0;
1948 }
```

Here is the caller graph for this function:

13.107.4.20 int ZEXPORT unzGetCurrentFileInfo (unzFile *file*, unz_file_info * *pfile_info*, char * *szFileName*, uLong *fileNameBufferSize*, void * *extraField*, uLong *extraFieldBufferSize*, char * *szComment*, uLong *commentBufferSize*)

Definition at line 1146 of file unzip.c.

References unz_file_info64_s::compressed_size, unz_file_info_s::compressed_size, unz_file_info64_s::compression_method, unz_file_info_s::compression_method, unz_file_info64_s::crc, unz_file_info_s::crc, unz_file_info64_s::disk_num_start, unz_file_info_s::disk_num_start, unz_file_info64_s::dosDate, unz_file_info_s::dosDate,

unz_file_info64_s::external_fa, unz_file_info_s::external_fa, unz_file_info64_s::flag, unz_file_info_s::flag, unz_file_info64_s::internal_fa, unz_file_info_s::internal_fa, unz_file_info64_s::size_file_comment, unz_file_info_s::size_file_comment, unz_file_info64_s::size_file_extra, unz_file_info_s::size_file_extra, unz_file_info64_s::size_filename, unz_file_info_s::size_filename, unz_file_info64_s::tmu_date, unz_file_info_s::tmu_date, unz_file_info64_s::uncompressed_size, unz_file_info_s::uncompressed_size, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, unz_file_info64_s::version, unz_file_info_s::version, unz_file_info64_s::version_needed, and unz_file_info_s::version_needed.

```
1151 {
1152     int err;
1153     unz_file_info64 file_info64;
1154     err = unz64local_GetCurrentFileInfoInternal(file,&file_info64,NULL
     ,
1155                                                 szFileName,fileNameBufferSize,
1156                                                 extraField,extraFieldBufferSize,
1157                                                 szComment,commentBufferSize);
1158     if (err==UNZ_OK && pfile_info != NULL)
1159     {
1160         pfile_info->version = file_info64.version;
1161         pfile_info->version_needed = file_info64.version_needed;
1162         pfile_info->flag = file_info64.flag;
1163         pfile_info->compression_method = file_info64.
     compression_method;
1164         pfile_info->dosDate = file_info64.dosDate;
1165         pfile_info->crc = file_info64.crc;
1166
1167         pfile_info->size_filename = file_info64.size_filename;
1168         pfile_info->size_file_extra = file_info64.size_file_extra;
1169         pfile_info->size_file_comment = file_info64.
     size_file_comment;
1170
1171         pfile_info->disk_num_start = file_info64.disk_num_start;
1172         pfile_info->internal_fa = file_info64.internal_fa;
1173         pfile_info->external_fa = file_info64.external_fa;
1174
1175         pfile_info->tmu_date = file_info64.tmu_date,
1176
1177
1178         pfile_info->compressed_size = (uLong)file_info64.
     compressed_size;
1179         pfile_info->uncompressed_size = (uLong)file_info64.
     uncompressed_size;
1180
1181     }
1182     return err;
1183 }
```

Here is the call graph for this function:

13.107.4.21 int ZEXPORT unzGetCurrentFileInfo64 (unzFile *file*, unz_file_info64 * *pfile_info*, char * *szFileName*, uLong *fileNameBufferSize*, void * *extraField*, uLong *extraFieldBufferSize*, char * *szComment*, uLong *commentBufferSize*)

Definition at line 1134 of file unzip.c.

References unz64local_GetCurrentFileInfoInternal().

Referenced by QuaZipFile::csize(), QuaZip::getCurrentFileInfo(), QuaZip::getCurrentFileName(), unzLocateFile(), and QuaZipFile::usize().

```
{
    return unz64local_GetCurrentFileInfoInternal(file,pfile_info,NULL,
                                                 szFileName,fileNameBufferSize,
                                                 extraField,extraFieldBufferSize,
                                                 szComment,commentBufferSize);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.22 ZPOS64_T ZEXPORT unzGetCurrentFileZStreamPos64 (unzFile *file*)

Definition at line 1666 of file unzip.c.

References file_in_zip64_read_info_s::byte_before_the_zipfile, unz64_s::pfile_in_zip_read, and file_in_zip64_read_info_s::pos_in_zipfile.

```
{
    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    s=(unz64_s*)file;
    if (file==NULL)
        return 0; /*UNZ_PARAMERROR; */
    pfile_in_zip_read_info=s->pfile_in_zip_read;
    if (pfile_in_zip_read_info==NULL)
        return 0; /*UNZ_PARAMERROR; */
    return pfile_in_zip_read_info->pos_in_zipfile +
                         pfile_in_zip_read_info->byte_before_the_zipfile;
}
```

13.107.4.23 int ZEXPORT unzGetFilePos (unzFile *file*, unz_file_pos * *file_pos*)

Definition at line 1334 of file unzip.c.

References unz_file_pos_s::num_of_file, unz64_file_pos_s::num_of_file, unz_file_pos_s::pos_in_zip_directory, unz64_file_pos_s::pos_in_zip_directory, UNZ_OK, and unzGetFilePos64().

```
{
    unz64_file_pos file_pos64;
    int err = unzGetFilePos64(file,&file_pos64);
    if (err==UNZ_OK)
    {
```

```
        file_pos->pos_in_zip_directory = (uLong)file_pos64.pos_in_zip_directory;
        file_pos->num_of_file = (uLong)file_pos64.num_of_file;
    }
    return err;
}
```

Here is the call graph for this function:

13.107.4.24 int ZEXPORT unzGetFilePos64 (unzFile *file*, unz64_file_pos * *file_pos*)

Definition at line 1318 of file unzip.c.

References unz64_s::current_file_ok, unz64_s::num_file, unz64_file_pos_s::num_of_file, unz64_s::pos_in_central_dir, unz64_file_pos_s::pos_in_zip_directory, UNZ_END_OF_LIST_OF_FILE, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZipPrivate::addCurrentFileToDirectoryMap(), and unzGetFilePos().

```
{
    unz64_s* s;

    if (file==NULL || file_pos==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    if (!s->current_file_ok)
        return UNZ_END_OF_LIST_OF_FILE;

    file_pos->pos_in_zip_directory  = s->pos_in_central_dir;
    file_pos->num_of_file           = s->num_file;

    return UNZ_OK;
}
```

Here is the caller graph for this function:

13.107.4.25 int ZEXPORT unzGetGlobalComment (unzFile *file*, char * *szComment*, uLong *uSizeBuf*)

Definition at line 2059 of file unzip.c.

References unz64_s::central_pos, unz64_s::filestream, unz64_s::gi, unz_global_info64_s::size_comment, UNZ_ERRNO, UNZ_PARAMERROR, unz64_s::z_filefunc, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, and ZSEEK64.

Referenced by QuaZip::getComment().

```
{
    unz64_s* s;
    uLong uReadThis ;
    if (file==NULL)
        return (int)UNZ_PARAMERROR;
    s=(unz64_s*)file;

    uReadThis = uSizeBuf;
    if (uReadThis>s->gi.size_comment)
        uReadThis = s->gi.size_comment;

    if (ZSEEK64(s->z_filefunc,s->filestream,s->central_pos+22,ZLIB_FILEFUNC_SEEK_SET)!=0)
        return UNZ_ERRNO;

    if (uReadThis>0)
    {
      *szComment='\0';
      if (ZREAD64(s->z_filefunc,s->filestream,szComment,uReadThis)!=uReadThis)
        return UNZ_ERRNO;
    }

    if ((szComment != NULL) && (uSizeBuf > s->gi.size_comment))
        *(szComment+s->gi.size_comment)='\0';
    return (int)uReadThis;
}
```

Here is the caller graph for this function:

13.107.4.26 int ZEXPORT unzGetGlobalInfo (unzFile *file*, unz_global_info * *pglobal_info32*)

Definition at line 848 of file unzip.c.

References unz64_s::gi, unz_global_info64_s::number_entry, unz_global_info_s::number_entry, unz_global_-info64_s::size_comment, unz_global_info_s::size_comment, UNZ_OK, and UNZ_PARAMERROR.

```
{
    unz64_s* s;
    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    /* to do : check if number_entry is not truncated */
    pglobal_info32->number_entry = (uLong)s->gi.number_entry;
    pglobal_info32->size_comment = s->gi.size_comment;
    return UNZ_OK;
}
```

13.107.4.27 int ZEXPORT unzGetGlobalInfo64 (unzFile *file*, unz_global_info64 * *pglobal_info*)

Definition at line 838 of file unzip.c.

References unz64_s::gi, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::getComment(), and QuaZip::getEntriesCount().

```
{
    unz64_s* s;
    if (file==NULL)
```

```
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    *pglobal_info=s->gi;
    return UNZ_OK;
}
```

Here is the caller graph for this function:

13.107.4.28 int ZEXPORT unzGetLocalExtrafield (unzFile *file*, voidp *buf*, unsigned *len*)

Definition at line 1964 of file unzip.c.

References file_in_zip64_read_info_s::filestream, file_in_zip64_read_info_s::offset_local_extrafield, unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::pos_local_extrafield, file_in_zip64_read_info_s::size_local_extrafield, UNZ_ERRNO, UNZ_PARAMERROR, file_in_zip64_read_info_s::z_filefunc, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, and ZSEEK64.

```
{
    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    uInt read_now;
    ZPOS64_T size_to_read;

    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    pfile_in_zip_read_info=s->pfile_in_zip_read;

    if (pfile_in_zip_read_info==NULL)
        return UNZ_PARAMERROR;

    size_to_read = (pfile_in_zip_read_info->size_local_extrafield -
                pfile_in_zip_read_info->pos_local_extrafield);

    if (buf==NULL)
        return (int)size_to_read;

    if (len>size_to_read)
        read_now = (uInt)size_to_read;
    else
        read_now = (uInt)len ;

    if (read_now==0)
        return 0;

    if (ZSEEK64(pfile_in_zip_read_info->z_filefunc,
              pfile_in_zip_read_info->filestream,
              pfile_in_zip_read_info->offset_local_extrafield +
              pfile_in_zip_read_info->pos_local_extrafield,
              ZLIB_FILEFUNC_SEEK_SET)!=0)
        return UNZ_ERRNO;

    if (ZREAD64(pfile_in_zip_read_info->z_filefunc,
              pfile_in_zip_read_info->filestream,
              buf,read_now)!=read_now)
        return UNZ_ERRNO;

    return (int)read_now;
}
```

13.107.4.29 uLong ZEXPORT unzGetOffset (unzFile *file*)

Definition at line 2102 of file unzip.c.

References unzGetOffset64().

```
{
    ZPOS64_T offset64;

    if (file==NULL)
          return 0; /*UNZ_PARAMERROR; */
    offset64 = unzGetOffset64(file);
    return (uLong)offset64;
}
```

Here is the call graph for this function:

13.107.4.30 ZPOS64_T ZEXPORT unzGetOffset64 (unzFile *file*)

Definition at line 2087 of file unzip.c.

References unz64_s::current_file_ok, unz64_s::gi, unz64_s::num_file, unz_global_info64_s::number_entry, and unz64_s::pos_in_central_dir.

Referenced by unzGetOffset().

```
{
    unz64_s* s;

    if (file==NULL)
          return 0; /*UNZ_PARAMERROR; */
    s=(unz64_s*)file;
    if (!s->current_file_ok)
      return 0;
    if (s->gi.number_entry != 0 && s->gi.number_entry != 0xffff)
      if (s->num_file==s->gi.number_entry)
         return 0;
    return s->pos_in_central_dir;
}
```

Here is the caller graph for this function:

13.107.4.31 int ZEXPORT unzGoToFilePos (unzFile *file*, unz_file_pos * *file_pos*)

Definition at line 1370 of file unzip.c.

References unz_file_pos_s::num_of_file, unz64_file_pos_s::num_of_file, unz_file_pos_s::pos_in_zip_directory, unz64_file_pos_s::pos_in_zip_directory, UNZ_PARAMERROR, and unzGoToFilePos64().

```
{
    unz64_file_pos file_pos64;
    if (file_pos == NULL)
        return UNZ_PARAMERROR;

    file_pos64.pos_in_zip_directory = file_pos->pos_in_zip_directory;
    file_pos64.num_of_file = file_pos->num_of_file;
    return unzGoToFilePos64(file,&file_pos64);
}
```

Here is the call graph for this function:

13.107.4.32 int ZEXPORT unzGoToFilePos64 (unzFile *file*, const unz64_file_pos * *file_pos*)

Definition at line 1348 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::num_file, unz64_file_pos_s::num_of_file, unz64_s::pos_in_central_dir, unz64_file_pos_s::pos_in_zip_directory, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZipPrivate::goToFirstUnmappedFile(), QuaZip::setCurrentFile(), and unzGoToFilePos().

```
{
    unz64_s* s;
    int err;

    if (file==NULL || file_pos==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;

    /* jump to the right spot */
    s->pos_in_central_dir = file_pos->pos_in_zip_directory;
    s->num_file           = file_pos->num_of_file;

    /* set the current file */
    err = unz64local_GetCurrentFileInfoInternal(file,&s->cur_file_info,
                                                &s->cur_file_info_internal,
                                                NULL,0,NULL,0,NULL,0);
    /* return results */
    s->current_file_ok = (err == UNZ_OK);
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.33 int ZEXPORT unzGoToFirstFile (unzFile *file*)

Definition at line 1188 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::num_file, unz64_s::offset_central_dir, unz64_s::pos_in_central_dir, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::goToFirstFile(), QuaZipPrivate::goToFirstUnmappedFile(), unzLocateFile(), and unzOpenInternal().

```
{
    int err=UNZ_OK;
    unz64_s* s;
    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    s->pos_in_central_dir=s->offset_central_dir;
    s->num_file=0;
    err=unz64local_GetCurrentFileInfoInternal(file,&s->cur_file_info,
                                              &s->cur_file_info_internal,
                                              NULL,0,NULL,0,NULL,0);
    s->current_file_ok = (err == UNZ_OK);
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.34 int ZEXPORT unzGoToNextFile (unzFile *file*)

Definition at line 1209 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::gi, unz64_s::num_file, unz_global_info64_s::number_entry, unz64_s::pos_in_central_dir, unz_file_info64_s::size_file_comment, unz_file_info64_s::size_file_extra, unz_file_info64_s::size_filename, SIZECENTRALDIRITEM, unz64local_GetCurrentFileInfoInternal(), UNZ_END_OF_LIST_OF_FILE, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZipPrivate::goToFirstUnmappedFile(), QuaZip::goToNextFile(), and unzLocateFile().

```
1210 {
1211     unz64_s* s;
1212     int err;
1213
1214     if (file==NULL)
1215         return UNZ_PARAMERROR;
1216     s=(unz64_s*)file;
1217     if (!s->current_file_ok)
1218         return UNZ_END_OF_LIST_OF_FILE;
1219     if (s->gi.number_entry != 0xffff)    /* 2^16 files overflow hack */
1220       if (s->num_file+1==s->gi.number_entry)
1221         return UNZ_END_OF_LIST_OF_FILE;
1222
1223     s->pos_in_central_dir += SIZECENTRALDIRITEM + s->
     cur_file_info.size_filename +
1224             s->cur_file_info.size_file_extra + s->
     cur_file_info.size_file_comment ;
1225     s->num_file++;
1226     err = unz64local_GetCurrentFileInfoInternal(file,&s->
     cur_file_info,
1227                                                 &s->cur_file_info_internal,
1228                                                 NULL,0,NULL,0,NULL,0);
1229     s->current_file_ok = (err == UNZ_OK);
1230     return err;
1231 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.35 int ZEXPORT unzLocateFile (unzFile *file*, const char * *szFileName*, int *iCaseSensitivity*)

Definition at line 1242 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::num_file, unz64_s::pos_in_central_dir, UNZ_END_OF_LIST_OF_FILE, UNZ_MAXFILENAMEINZIP, UNZ_OK, UNZ_PARAMERROR, unzGetCurrentFileInfo64(), unzGoToFirstFile(), unzGoToNextFile(), and unzStringFileNameCompare().

```
{
    unz64_s* s;
    int err;

    /* We remember the 'current' position in the file so that we can jump
     * back there if we fail.
     */
    unz_file_info64 cur_file_infoSaved;
    unz_file_info64_internal cur_file_info_internalSaved;
    ZPOS64_T num_fileSaved;
    ZPOS64_T pos_in_central_dirSaved;


    if (file==NULL)
        return UNZ_PARAMERROR;

    if (strlen(szFileName)>=UNZ_MAXFILENAMEINZIP)
        return UNZ_PARAMERROR;

    s=(unz64_s*)file;
    if (!s->current_file_ok)
        return UNZ_END_OF_LIST_OF_FILE;

    /* Save the current state */
    num_fileSaved = s->num_file;
    pos_in_central_dirSaved = s->pos_in_central_dir;
    cur_file_infoSaved = s->cur_file_info;
    cur_file_info_internalSaved = s->cur_file_info_internal;

    err = unzGoToFirstFile(file);

    while (err == UNZ_OK)
    {
        char szCurrentFileName[UNZ_MAXFILENAMEINZIP+1];
        err = unzGetCurrentFileInfo64(file,NULL,
                                      szCurrentFileName,sizeof(szCurrentFileName)-1,
                                      NULL,0,NULL,0);
        if (err == UNZ_OK)
        {
            if (unzStringFileNameCompare(szCurrentFileName,
                                         szFileName,iCaseSensitivity)==0)
                return UNZ_OK;
            err = unzGoToNextFile(file);
        }
    }

    /* We failed, so restore the state of the 'current file' to where we
     * were.
     */
    s->num_file = num_fileSaved ;
    s->pos_in_central_dir = pos_in_central_dirSaved ;
    s->cur_file_info = cur_file_infoSaved;
    s->cur_file_info_internal = cur_file_info_internalSaved;
    return err;
}
```

Here is the call graph for this function:

13.107.4.36 unzFile ZEXPORT unzOpen (voidpf *file*)

Definition at line 800 of file unzip.c.

References UNZ_DEFAULT_FLAGS, and unzOpenInternal().

```
801 {
802     return unzOpenInternal(file, NULL, 0, UNZ_DEFAULT_FLAGS);
803 }
```

Here is the call graph for this function:

13.107.4.37 unzFile ZEXPORT unzOpen2 (voidpf *file*, zlib_filefunc_def * *pzlib_filefunc32_def*)

Definition at line 772 of file unzip.c.

References fill_zlib_filefunc64_32_def_from_filefunc32(), UNZ_DEFAULT_FLAGS, and unzOpenInternal().

Referenced by QuaZip::open().

```
774 {
775     if (pzlib_filefunc32_def != NULL)
776     {
777         zlib_filefunc64_32_def zlib_filefunc64_32_def_fill;
778         fill_zlib_filefunc64_32_def_from_filefunc32(&
```

```
zlib_filefunc64_32_def_fill,pzlib_filefunc32_def);
        return unzOpenInternal(file, &zlib_filefunc64_32_def_fill, 0,
UNZ_DEFAULT_FLAGS);
    }
    else
        return unzOpenInternal(file, NULL, 0, UNZ_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.38 unzFile ZEXPORT unzOpen2_64 (voidpf *file*, zlib_filefunc64_def * *pzlib_filefunc_def*)

Definition at line 785 of file unzip.c.

References UNZ_DEFAULT_FLAGS, unzOpenInternal(), zlib_filefunc64_32_def_s::zfile_func64, zlib_filefunc64_-32_def_s::zseek32_file, and zlib_filefunc64_32_def_s::ztell32_file.

```
{
    if (pzlib_filefunc_def != NULL)
    {
        zlib_filefunc64_32_def zlib_filefunc64_32_def_fill;
        zlib_filefunc64_32_def_fill.zfile_func64 = *pzlib_filefunc_def;
        zlib_filefunc64_32_def_fill.ztell32_file = NULL;
        zlib_filefunc64_32_def_fill.zseek32_file = NULL;
        return unzOpenInternal(file, &zlib_filefunc64_32_def_fill, 1,
UNZ_DEFAULT_FLAGS);
    }
    else
```

```
        return unzOpenInternal(file, NULL, 1, UNZ_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

13.107.4.39 unzFile ZEXPORT unzOpen64 (voidpf *file*)

Definition at line 805 of file unzip.c.

References UNZ_DEFAULT_FLAGS, and unzOpenInternal().

```
{
    return unzOpenInternal(file, NULL, 1, UNZ_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

13.107.4.40 int ZEXPORT unzOpenCurrentFile (unzFile *file*)

Definition at line 1649 of file unzip.c.

References unzOpenCurrentFile3().

```
1650 {
1651     return unzOpenCurrentFile3(file, NULL, NULL, 0, NULL);
1652 }
```

Here is the call graph for this function:

13.107.4.41 int ZEXPORT unzOpenCurrentFile2 (unzFile *file*, int * *method*, int * *level*, int *raw*)

Definition at line 1659 of file unzip.c.

References unzOpenCurrentFile3().

```
1660 {
1661     return unzOpenCurrentFile3(file, method, level, raw, NULL);
1662 }
```

Here is the call graph for this function:

13.107.4.42 int ZEXPORT unzOpenCurrentFile3 (unzFile *file*, int * *method*, int * *level*, int *raw*, const char * *password*)

Definition at line 1480 of file unzip.c.

References ALLOC, file_in_zip64_read_info_s::byte_before_the_zipfile, unz64_s::byte_before_the_zipfile, unz_file_info64_s::compressed_size, unz_file_info64_s::compression_method, file_in_zip64_read_info_s::compression_method, unz_file_info64_s::crc, file_in_zip64_read_info_s::crc32, file_in_zip64_read_info_s::crc32_wait, unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::encrypted, file_in_zip64_read_info_s::filestream, unz64_s::filestream, unz_file_info64_s::flag, init_keys(), unz64_s::keys, unz_file_info64_internal_s::offset_curfile, file_in_zip64_read_info_s::offset_local_extrafield, unz64_s::pcrc_32_tab, unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::pos_in_zipfile, file_in_zip64_read_info_s::pos_local_extrafield, file_in_zip64_read_info_s::raw, file_in_zip64_read_info_s::read_buffer, file_in_zip64_read_info_s::rest_read_compressed, file_in_zip64_read_info_s::rest_read_uncompressed, SEEK_SET, file_in_zip64_read_info_s::size_local_extrafield,

SIZEZIPLOCALHEADER, file_in_zip64_read_info_s::stream, file_in_zip64_read_info_s::stream_initialised, file_in_zip64_read_info_s::total_out_64, TRYFREE, unz_file_info64_s::uncompressed_size, unz64local_CheckCurrentFileCoherencyHeader(), UNZ_BADZIPFILE, UNZ_BUFSIZE, UNZ_INTERNALERROR, UNZ_OK, UNZ_PARAMERROR, unzCloseCurrentFile(), Z_BZIP2ED, file_in_zip64_read_info_s::z_filefunc, unz64_s::z_filefunc, zdecode, ZREAD64, and ZSEEK64.

Referenced by QuaZipFile::open(), unzOpenCurrentFile(), unzOpenCurrentFile2(), and unzOpenCurrentFilePassword().

```
{
    int err=UNZ_OK;
    uInt iSizeVar;
    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    ZPOS64_T offset_local_extrafield;  /* offset of the local extra field */
    uInt  size_local_extrafield;    /* size of the local extra field */
#    ifndef NOUNCRYPT
    char source[12];
#    else
    if (password != NULL)
        return UNZ_PARAMERROR;
#    endif

    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    if (!s->current_file_ok)
        return UNZ_PARAMERROR;

    if (s->pfile_in_zip_read != NULL)
        unzCloseCurrentFile(file);

    if (unz64local_CheckCurrentFileCoherencyHeader(s,&iSizeVar, &offset_local_extrafield,&size_local_extrafield)!=UNZ_OK)
        return UNZ_BADZIPFILE;

    pfile_in_zip_read_info = (file_in_zip64_read_info_s*)ALLOC(sizeof(file_in_zip64_read_info_s));
    if (pfile_in_zip_read_info==NULL)
        return UNZ_INTERNALERROR;

    pfile_in_zip_read_info->read_buffer=(char*)ALLOC(UNZ_BUFSIZE);
    pfile_in_zip_read_info->offset_local_extrafield = offset_local_extrafield;
    pfile_in_zip_read_info->size_local_extrafield = size_local_extrafield;
    pfile_in_zip_read_info->pos_local_extrafield=0;
    pfile_in_zip_read_info->raw=raw;

    if (pfile_in_zip_read_info->read_buffer==NULL)
    {
        TRYFREE(pfile_in_zip_read_info);
        return UNZ_INTERNALERROR;
    }

    pfile_in_zip_read_info->stream_initialised=0;

    if (method!=NULL)
        *method = (int)s->cur_file_info.compression_method;

    if (level!=NULL)
    {
        *level = 6;
        switch (s->cur_file_info.flag & 0x06)
        {
          case 6 : *level = 1; break;
          case 4 : *level = 2; break;
          case 2 : *level = 9; break;
        }
    }

    if ((s->cur_file_info.compression_method!=0) &&
/* #ifdef HAVE_BZIP2 */
        (s->cur_file_info.compression_method!=Z_BZIP2ED) &&
/* #endif */
        (s->cur_file_info.compression_method!=Z_DEFLATED))

        err=UNZ_BADZIPFILE;

    pfile_in_zip_read_info->crc32_wait=s->cur_file_info.crc;
    pfile_in_zip_read_info->crc32=0;
    pfile_in_zip_read_info->total_out_64=0;
    pfile_in_zip_read_info->compression_method = s->cur_file_info.compression_method;
```

```
    pfile_in_zip_read_info->filestream=s->filestream;
    pfile_in_zip_read_info->z_filefunc=s->z_filefunc;
    pfile_in_zip_read_info->byte_before_the_zipfile=s->byte_before_the_zipfile;

    pfile_in_zip_read_info->stream.total_out = 0;

    if ((s->cur_file_info.compression_method==Z_BZIP2ED) && (!raw))
    {
#ifdef HAVE_BZIP2
      pfile_in_zip_read_info->bstream.bzalloc = (void *(*) (void *, int, int))0;
      pfile_in_zip_read_info->bstream.bzfree = (free_func)0;
      pfile_in_zip_read_info->bstream.opaque = (voidpf)0;
      pfile_in_zip_read_info->bstream.state = (voidpf)0;

      pfile_in_zip_read_info->stream.zalloc = (alloc_func)0;
      pfile_in_zip_read_info->stream.zfree = (free_func)0;
      pfile_in_zip_read_info->stream.opaque = (voidpf)0;
      pfile_in_zip_read_info->stream.next_in = (voidpf)0;
      pfile_in_zip_read_info->stream.avail_in = 0;

      err=BZ2_bzDecompressInit(&pfile_in_zip_read_info->bstream, 0, 0);
      if (err == Z_OK)
        pfile_in_zip_read_info->stream_initialised=Z_BZIP2ED;
      else
      {
        TRYFREE(pfile_in_zip_read_info);
        return err;
      }
#else
      pfile_in_zip_read_info->raw=1;
#endif
    }
    else if ((s->cur_file_info.compression_method==Z_DEFLATED) && (!raw))
    {
      pfile_in_zip_read_info->stream.zalloc = (alloc_func)0;
      pfile_in_zip_read_info->stream.zfree = (free_func)0;
      pfile_in_zip_read_info->stream.opaque = (voidpf)0;
      pfile_in_zip_read_info->stream.next_in = 0;
      pfile_in_zip_read_info->stream.avail_in = 0;

      err=inflateInit2(&pfile_in_zip_read_info->stream, -MAX_WBITS);
      if (err == Z_OK)
        pfile_in_zip_read_info->stream_initialised=Z_DEFLATED;
      else
      {
        TRYFREE(pfile_in_zip_read_info);
        return err;
      }
        /* windowBits is passed < 0 to tell that there is no zlib header.
         * Note that in this case inflate *requires* an extra "dummy" byte
         * after the compressed stream in order to complete decompression and
         * return Z_STREAM_END.
         * In unzip, i don't wait absolutely Z_STREAM_END because I known the
         * size of both compressed and uncompressed data
         */
    }
    pfile_in_zip_read_info->rest_read_compressed =
            s->cur_file_info.compressed_size ;
    pfile_in_zip_read_info->rest_read_uncompressed =
            s->cur_file_info.uncompressed_size ;


    pfile_in_zip_read_info->pos_in_zipfile =
            s->cur_file_info_internal.offset_curfile + SIZEZIPLOCALHEADER +
              iSizeVar;

    pfile_in_zip_read_info->stream.avail_in = (uInt)0;

    s->pfile_in_zip_read = pfile_in_zip_read_info;
                s->encrypted = 0;

#    ifndef NOUNCRYPT
    if (password != NULL)
    {
        int i;
        s->pcrc_32_tab = get_crc_table();
        init_keys(password,s->keys,s->pcrc_32_tab);
        if (ZSEEK64(s->z_filefunc, s->filestream,
                  s->pfile_in_zip_read->pos_in_zipfile +
                     s->pfile_in_zip_read->byte_before_the_zipfile,
                  SEEK_SET)!=0)
            return UNZ_INTERNALERROR;
        if(ZREAD64(s->z_filefunc, s->filestream,source, 12)<12)
```

```
            return UNZ_INTERNALERROR;

        for (i = 0; i<12; i++)
            zdecode(s->keys,s->pcrc_32_tab,source[i]);

        s->pfile_in_zip_read->pos_in_zipfile+=12;
        s->encrypted=1;
    }
#    endif


    return UNZ_OK;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.43 int ZEXPORT unzOpenCurrentFilePassword (unzFile *file*, const char * *password*)

Definition at line 1654 of file unzip.c.

References unzOpenCurrentFile3().

```
{
    return unzOpenCurrentFile3(file, NULL, NULL, 0, password);
}
```

Here is the call graph for this function:

13.107.4.44 unzFile unzOpenInternal (voidpf *file*, zlib_filefunc64_32_def * *pzlib_filefunc64_32_def*, int *is64bitOpenFunction*, unsigned *flags*)

Definition at line 587 of file unzip.c.

References ALLOC, unz64_s::byte_before_the_zipfile, unz64_s::central_pos, unz64_s::encrypted, unz64_s::filestream, fill_qiodevice64_filefunc(), unz64_s::flags, unz64_s::gi, unz64_s::is64bitOpenFunction, unz64_s::isZip64, unz_global_info64_s::number_entry, unz64_s::offset_central_dir, unz64_s::pfile_in_zip_read, unz64_s::size_central_dir, unz_global_info64_s::size_comment, unz64local_getLong(), unz64local_getLong64(), unz64local_getShort(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), UNZ_AUTO_CLOSE, UNZ_BADZIPFILE, unz_copyright, UNZ_ERRNO, UNZ_OK, unzGoToFirstFile(), unz64_s::z_filefunc, ZCLOSE64, ZFAKECLOSE64, zlib_filefunc64_32_def_s::zfile_func64, ZLIB_FILEFUNC_MODE_EXISTING, ZLIB_FILEFUNC_MODE_READ, ZLIB_FILEFUNC_SEEK_SET, ZOPEN64, zlib_filefunc64_32_def_s::zseek32_file, ZSEEK64, and zlib_filefunc64_32_def_s::ztell32_file.

Referenced by QuaZip::open(), unzOpen(), unzOpen2(), unzOpen2_64(), and unzOpen64().

```
{
    unz64_s us;
    unz64_s *s;
    ZPOS64_T central_pos;
    uLong   uL;

    uLong number_disk;          /* number of the current dist, used for
                                   spaning ZIP, unsupported, always 0*/
    uLong number_disk_with_CD;  /* number the the disk with central dir, used
                                   for spaning ZIP, unsupported, always 0*/
    ZPOS64_T number_entry_CD;      /* total number of entries in
                                   the central dir
                                   (same than number_entry on nospan) */

    int err=UNZ_OK;

    if (unz_copyright[0]!=' ')
        return NULL;

    us.flags = flags;
    us.z_filefunc.zseek32_file = NULL;
    us.z_filefunc.ztell32_file = NULL;
    if (pzlib_filefunc64_32_def==NULL)
        fill_qiodevice64_filefunc(&us.z_filefunc.
zfile_func64);
    else
        us.z_filefunc = *pzlib_filefunc64_32_def;
    us.is64bitOpenFunction = is64bitOpenFunction;



    us.filestream = ZOPEN64(us.z_filefunc,
                                                file,
                                                ZLIB_FILEFUNC_MODE_READ |
                                                ZLIB_FILEFUNC_MODE_EXISTING);
    if (us.filestream==NULL)
        return NULL;

    central_pos = unz64local_SearchCentralDir64(&us.
z_filefunc,us.filestream);
    if (central_pos)
    {
        uLong uS;
        ZPOS64_T uL64;

```

```
        us.isZip64 = 1;

        if (ZSEEK64(us.z_filefunc, us.filestream,
                                    central_pos,ZLIB_FILEFUNC_SEEK_SET)!=0)
        err=UNZ_ERRNO;

        /* the signature, already checked */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* size of zip64 end of central directory record */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&uL64)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* version made by */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uS)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* version needed to extract */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uS)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of this disk */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&number_disk)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of the disk with the start of the central directory */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&number_disk_with_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central directory on this disk */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.gi.number_entry)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central directory */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&number_entry_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        if ((number_entry_CD!=us.gi.number_entry) ||
            (number_disk_with_CD!=0) ||
            (number_disk!=0))
            err=UNZ_BADZIPFILE;

        /* size of the central directory */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.size_central_dir)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* offset of start of central directory with respect to the
          starting disk number */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.offset_central_dir)!=UNZ_OK)
            err=UNZ_ERRNO;

        us.gi.size_comment = 0;
    }
    else
    {
        central_pos = unz64local_SearchCentralDir(&us.z_filefunc,us.filestream);
        if (central_pos==0)
            err=UNZ_ERRNO;

        us.isZip64 = 0;

        if (ZSEEK64(us.z_filefunc, us.filestream,
                                    central_pos,ZLIB_FILEFUNC_SEEK_SET)!=0)
            err=UNZ_ERRNO;

        /* the signature, already checked */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of this disk */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&number_disk)!=UNZ_OK)
            err=UNZ_ERRNO;

```

```
        /* number of the disk with the start of the central directory */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&number_disk_with_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central dir on this disk */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.gi.number_entry = uL;

        /* total number of entries in the central dir */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        number_entry_CD = uL;

        if ((number_entry_CD!=us.gi.number_entry) ||
            (number_disk_with_CD!=0) ||
            (number_disk!=0))
            err=UNZ_BADZIPFILE;

        /* size of the central directory */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.size_central_dir = uL;

        /* offset of start of central directory with respect to the
            starting disk number */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.offset_central_dir = uL;

        /* zipfile comment length */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&us.gi.size_comment)!=UNZ_OK)
            err=UNZ_ERRNO;
    }

    if ((central_pos<us.offset_central_dir+us.size_central_dir) &&
        (err==UNZ_OK))
        err=UNZ_BADZIPFILE;

    if (err!=UNZ_OK)
    {
        if ((us.flags & UNZ_AUTO_CLOSE) != 0)
            ZCLOSE64(us.z_filefunc, us.filestream);
        else
            ZFAKECLOSE64(us.z_filefunc, us.filestream);
        return NULL;
    }

    us.byte_before_the_zipfile = central_pos -
                            (us.offset_central_dir+us.size_central_dir);
    us.central_pos = central_pos;
    us.pfile_in_zip_read = NULL;
    us.encrypted = 0;


    s=(unz64_s*)ALLOC(sizeof(unz64_s));
    if( s != NULL)
    {
        *s=us;
        unzGoToFirstFile((unzFile)s);
    }
    return (unzFile)s;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.45 int ZEXPORT unzReadCurrentFile (unzFile *file*, voidp *buf*, unsigned *len*)

Definition at line 1692 of file unzip.c.

References file_in_zip64_read_info_s::byte_before_the_zipfile, file_in_zip64_read_info_s::compression_method, file_in_zip64_read_info_s::crc32, unz64_s::encrypted, file_in_zip64_read_info_s::filestream, unz64_s::keys, unz64_s::pcrc_32_tab, unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::pos_in_zipfile, file_in_zip64_read_info_s::raw, file_in_zip64_read_info_s::read_buffer, file_in_zip64_read_info_s::rest_read_compressed, file_in_zip64_read_info_s::rest_read_uncompressed, file_in_zip64_read_info_s::stream, file_in_zip64_read_info_s::total_out_64, UNZ_BUFSIZE, UNZ_END_OF_LIST_OF_FILE, UNZ_EOF, UNZ_ERRNO, UNZ_OK, UNZ_PARAMERROR, Z_BZIP2ED, file_in_zip64_read_info_s::z_filefunc, zdecode, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, and ZSEEK64.

Referenced by QuaZipFile::readData().

```
{
    int err=UNZ_OK;
    uInt iRead = 0;
    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    if (file==NULL)
```

```
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    pfile_in_zip_read_info=s->pfile_in_zip_read;

    if (pfile_in_zip_read_info==NULL)
        return UNZ_PARAMERROR;


    if (pfile_in_zip_read_info->read_buffer == NULL)
        return UNZ_END_OF_LIST_OF_FILE;
    if (len==0)
        return 0;

    pfile_in_zip_read_info->stream.next_out = (Bytef*)buf;

    pfile_in_zip_read_info->stream.avail_out = (uInt)len;

    if ((len>pfile_in_zip_read_info->rest_read_uncompressed) &&
        (!(pfile_in_zip_read_info->raw)))
        pfile_in_zip_read_info->stream.avail_out =
            (uInt)pfile_in_zip_read_info->rest_read_uncompressed;

    if ((len>pfile_in_zip_read_info->rest_read_compressed+
           pfile_in_zip_read_info->stream.avail_in) &&
         (pfile_in_zip_read_info->raw))
        pfile_in_zip_read_info->stream.avail_out =
            (uInt)pfile_in_zip_read_info->rest_read_compressed+
            pfile_in_zip_read_info->stream.avail_in;

    while (pfile_in_zip_read_info->stream.avail_out>0)
    {
        if ((pfile_in_zip_read_info->stream.avail_in==0) &&
            (pfile_in_zip_read_info->rest_read_compressed>0))
        {
            uInt uReadThis = UNZ_BUFSIZE;
            if (pfile_in_zip_read_info->rest_read_compressed<uReadThis)
                uReadThis = (uInt)pfile_in_zip_read_info->rest_read_compressed;
            if (uReadThis == 0)
                return UNZ_EOF;
            if (ZSEEK64(pfile_in_zip_read_info->z_filefunc,
                      pfile_in_zip_read_info->filestream,
                      pfile_in_zip_read_info->pos_in_zipfile +
                         pfile_in_zip_read_info->byte_before_the_zipfile,
                         ZLIB_FILEFUNC_SEEK_SET)!=0)
                return UNZ_ERRNO;
            if (ZREAD64(pfile_in_zip_read_info->z_filefunc,
                      pfile_in_zip_read_info->filestream,
                      pfile_in_zip_read_info->read_buffer,
                      uReadThis)!=uReadThis)
                return UNZ_ERRNO;


#            ifndef NOUNCRYPT
            if(s->encrypted)
            {
                uInt i;
                for(i=0;i<uReadThis;i++)
                  pfile_in_zip_read_info->read_buffer[i] =
                      zdecode(s->keys,s->pcrc_32_tab,
                              pfile_in_zip_read_info->read_buffer[i]);
            }
#            endif


            pfile_in_zip_read_info->pos_in_zipfile += uReadThis;

            pfile_in_zip_read_info->rest_read_compressed-=uReadThis;

            pfile_in_zip_read_info->stream.next_in =
                (Bytef*)pfile_in_zip_read_info->read_buffer;
            pfile_in_zip_read_info->stream.avail_in = (uInt)uReadThis;
        }

        if ((pfile_in_zip_read_info->compression_method==0) || (pfile_in_zip_read_info->
raw))
        {
            uInt uDoCopy,i ;

            if ((pfile_in_zip_read_info->stream.avail_in == 0) &&
                (pfile_in_zip_read_info->rest_read_compressed == 0))
                return (iRead==0) ? UNZ_EOF : iRead;

            if (pfile_in_zip_read_info->stream.avail_out <
                            pfile_in_zip_read_info->stream.avail_in)
                uDoCopy = pfile_in_zip_read_info->stream.avail_out ;
            else
                uDoCopy = pfile_in_zip_read_info->stream.avail_in ;
```

```

            for (i=0;i<uDoCopy;i++)
                *(pfile_in_zip_read_info->stream.next_out+i) =
                        *(pfile_in_zip_read_info->stream.next_in+i);

            pfile_in_zip_read_info->total_out_64 = pfile_in_zip_read_info->total_out_64 + uDoCopy;

            pfile_in_zip_read_info->crc32 = crc32(pfile_in_zip_read_info->crc32,
                                    pfile_in_zip_read_info->stream.next_out,
                                    uDoCopy);
            pfile_in_zip_read_info->rest_read_uncompressed-=uDoCopy;
            pfile_in_zip_read_info->stream.avail_in -= uDoCopy;
            pfile_in_zip_read_info->stream.avail_out -= uDoCopy;
            pfile_in_zip_read_info->stream.next_out += uDoCopy;
            pfile_in_zip_read_info->stream.next_in += uDoCopy;
            pfile_in_zip_read_info->stream.total_out += uDoCopy;
            iRead += uDoCopy;
        }
        else if (pfile_in_zip_read_info->compression_method==Z_BZIP2ED)
        {
#ifdef HAVE_BZIP2
            uLong uTotalOutBefore,uTotalOutAfter;
            const Bytef *bufBefore;
            uLong uOutThis;

            pfile_in_zip_read_info->bstream.next_in        = (char*)pfile_in_zip_read_info->stream.next_in;
            pfile_in_zip_read_info->bstream.avail_in       = pfile_in_zip_read_info->stream.avail_in;
            pfile_in_zip_read_info->bstream.total_in_lo32  = pfile_in_zip_read_info->stream.total_in;
            pfile_in_zip_read_info->bstream.total_in_hi32  = 0;
            pfile_in_zip_read_info->bstream.next_out       = (char*)pfile_in_zip_read_info->stream.next_out;
            pfile_in_zip_read_info->bstream.avail_out      = pfile_in_zip_read_info->stream.avail_out;
            pfile_in_zip_read_info->bstream.total_out_lo32 = pfile_in_zip_read_info->stream.total_out;
            pfile_in_zip_read_info->bstream.total_out_hi32 = 0;

            uTotalOutBefore = pfile_in_zip_read_info->bstream.total_out_lo32;
            bufBefore = (const Bytef *)pfile_in_zip_read_info->bstream.next_out;

            err=BZ2_bzDecompress(&pfile_in_zip_read_info->bstream);

            uTotalOutAfter = pfile_in_zip_read_info->bstream.total_out_lo32;
            uOutThis = uTotalOutAfter-uTotalOutBefore;

            pfile_in_zip_read_info->total_out_64 = pfile_in_zip_read_info->total_out_64 + uOutThis;

            pfile_in_zip_read_info->crc32 = crc32(pfile_in_zip_read_info->crc32,bufBefore, (uInt)(uOutThis));
            pfile_in_zip_read_info->rest_read_uncompressed -= uOutThis;
            iRead += (uInt)(uTotalOutAfter - uTotalOutBefore);

            pfile_in_zip_read_info->stream.next_in   = (Bytef*)pfile_in_zip_read_info->bstream.next_in;
            pfile_in_zip_read_info->stream.avail_in  = pfile_in_zip_read_info->bstream.avail_in;
            pfile_in_zip_read_info->stream.total_in  = pfile_in_zip_read_info->bstream.total_in_lo32;
            pfile_in_zip_read_info->stream.next_out  = (Bytef*)pfile_in_zip_read_info->bstream.next_out;
            pfile_in_zip_read_info->stream.avail_out = pfile_in_zip_read_info->bstream.avail_out;
            pfile_in_zip_read_info->stream.total_out = pfile_in_zip_read_info->bstream.total_out_lo32;

            if (err==BZ_STREAM_END)
              return (iRead==0) ? UNZ_EOF : iRead;
            if (err!=BZ_OK)
              break;
#endif
        } /* end Z_BZIP2ED */
        else
        {
            ZPOS64_T uTotalOutBefore,uTotalOutAfter;
            const Bytef *bufBefore;
            ZPOS64_T uOutThis;
            int flush=Z_SYNC_FLUSH;

            uTotalOutBefore = pfile_in_zip_read_info->stream.total_out;
            bufBefore = pfile_in_zip_read_info->stream.next_out;

            /*
            if ((pfile_in_zip_read_info->rest_read_uncompressed ==
```

```
                    pfile_in_zip_read_info->stream.avail_out) &&
                (pfile_in_zip_read_info->rest_read_compressed == 0))
                flush = Z_FINISH;
            */
            err=inflate(&pfile_in_zip_read_info->stream,flush);

            if ((err>=0) && (pfile_in_zip_read_info->stream.msg!=NULL))
              err = Z_DATA_ERROR;

            uTotalOutAfter = pfile_in_zip_read_info->stream.total_out;
            uOutThis = uTotalOutAfter-uTotalOutBefore;

            pfile_in_zip_read_info->total_out_64 = pfile_in_zip_read_info->
    total_out_64 + uOutThis;

            pfile_in_zip_read_info->crc32 =
                crc32(pfile_in_zip_read_info->crc32,bufBefore,
                        (uInt)(uOutThis));

            pfile_in_zip_read_info->rest_read_uncompressed -=
                uOutThis;

            iRead += (uInt)(uTotalOutAfter - uTotalOutBefore);

            if (err==Z_STREAM_END)
                return (iRead==0) ? UNZ_EOF : iRead;
            if (err!=Z_OK)
                break;
        }
    }

    if (err==Z_OK)
        return iRead;
    return err;
}
```

Here is the caller graph for this function:

13.107.4.46 int ZEXPORT unzSetFlags (unzFile *file*, unsigned *flags*)

Definition at line 2136 of file unzip.c.

References unz64_s::flags, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::open().

```
{
    unz64_s* s;
    if (file == NULL)
        return UNZ_PARAMERROR;
    s = (unz64_s*)file;
    s->flags |= flags;
    return UNZ_OK;
}
```

Here is the caller graph for this function:

13.107.4.47 int ZEXPORT unzSetOffset (unzFile *file*, uLong *pos*)

Definition at line 2130 of file unzip.c.

References unzSetOffset64().

```
2131 {
2132     return unzSetOffset64(file,pos);
2133 }
```

Here is the call graph for this function:

13.107.4.48 int ZEXPORT unzSetOffset64 (unzFile *file*, ZPOS64_T *pos*)

Definition at line 2112 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::gi, unz64_s::num_file, unz_global_info64_s::number_entry, unz64_s::pos_in_central_dir, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, and UNZ_PARAMERROR.

Referenced by unzSetOffset().

```
2113 {
2114     unz64_s* s;
2115     int err;
2116
2117     if (file==NULL)
2118         return UNZ_PARAMERROR;
2119     s=(unz64_s*)file;
2120
2121     s->pos_in_central_dir = pos;
2122     s->num_file = s->gi.number_entry;       /* hack */
2123     err = unz64local_GetCurrentFileInfoInternal(file,&s->
      cur_file_info,
2124                                                 &s->cur_file_info_internal,
2125                                                 NULL,0,NULL,0,NULL,0);
2126     s->current_file_ok = (err == UNZ_OK);
2127     return err;
2128 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.107.4.49 int ZEXPORT unzStringFileNameCompare (const char * *fileName1*, const char * *fileName2*, int *iCaseSensitivity*)

Definition at line 393 of file unzip.c.

References CASESENSITIVITYDEFAULTVALUE, and STRCMPCASENOSENTIVEFUNCTION.

Referenced by unzLocateFile().

```
{
    if (iCaseSensitivity==0)
        iCaseSensitivity=CASESENSITIVITYDEFAULTVALUE;

    if (iCaseSensitivity==1)
        return strcmp(fileName1,fileName2);

    return STRCMPCASENOSENTIVEFUNCTION(fileName1,fileName2);
}
```

Here is the caller graph for this function:

13.107.4.50 z_off_t ZEXPORT unztell (unzFile *file*)

Definition at line 1897 of file unzip.c.

References unz64_s::pfile_in_zip_read, file_in_zip64_read_info_s::stream, and UNZ_PARAMERROR.

Referenced by QuaZipFile::pos().

```
{
    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    if (file==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    pfile_in_zip_read_info=s->pfile_in_zip_read;

    if (pfile_in_zip_read_info==NULL)
        return UNZ_PARAMERROR;

    return (z_off_t)pfile_in_zip_read_info->stream.total_out;
}
```

Here is the caller graph for this function:

13.107.4.51 ZPOS64_T ZEXPORT unztell64 (unzFile *file*)

Definition at line 1912 of file unzip.c.

References unz64_s::pfile_in_zip_read, and file_in_zip64_read_info_s::total_out_64.

```
{

    unz64_s* s;
    file_in_zip64_read_info_s* pfile_in_zip_read_info;
    if (file==NULL)
        return (ZPOS64_T)-1;
    s=(unz64_s*)file;
    pfile_in_zip_read_info=s->pfile_in_zip_read;

    if (pfile_in_zip_read_info==NULL)
        return (ZPOS64_T)-1;

    return pfile_in_zip_read_info->total_out_64;
}
```

13.107.5 Variable Documentation

13.107.5.1 const char unz_copyright[ ]

Initial value:

```
=
   " unzip 1.01 Copyright 1998-2004 Gilles Vollant - http://www.winimage.com/zLibDll"
```

Definition at line 124 of file unzip.c.

Referenced by unzOpenInternal().

13.108 src/ckb/quazip/unzip.h File Reference

```
#include "zlib.h"
#include "ioapi.h"
```

Include dependency graph for unzip.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct tm_unz_s
- struct unz_global_info64_s
- struct unz_global_info_s
- struct unz_file_info64_s
- struct unz_file_info_s
- struct unz_file_pos_s
- struct unz64_file_pos_s

Macros

- #define Z_BZIP2ED 12

- #define UNZ_OK (0)
- #define UNZ_END_OF_LIST_OF_FILE (-100)
- #define UNZ_ERRNO (Z_ERRNO)
- #define UNZ_EOF (0)
- #define UNZ_PARAMERROR (-102)
- #define UNZ_BADZIPFILE (-103)
- #define UNZ_INTERNALERROR (-104)
- #define UNZ_CRCERROR (-105)
- #define UNZ_AUTO_CLOSE 0x01u
- #define UNZ_DEFAULT_FLAGS UNZ_AUTO_CLOSE

Typedefs

- typedef voidp unzFile
- typedef struct tm_unz_s tm_unz
- typedef struct unz_global_info64_s unz_global_info64
- typedef struct unz_global_info_s unz_global_info
- typedef struct unz_file_info64_s unz_file_info64
- typedef struct unz_file_info_s unz_file_info
- typedef struct unz_file_pos_s unz_file_pos
- typedef struct unz64_file_pos_s unz64_file_pos

Functions

- int ZEXPORT unzStringFileNameCompare _Z_OF ((const char ∗fileName1, const char ∗fileName2, int iCaseSensitivity))
- unzFile ZEXPORT unzOpen _Z_OF ((voidpf file))
- unzFile ZEXPORT unzOpen2 _Z_OF ((voidpf file, zlib_filefunc_def ∗pzlib_filefunc_def))
- unzFile ZEXPORT unzOpen2_64 _Z_OF ((voidpf file, zlib_filefunc64_def ∗pzlib_filefunc_def))
- unzFile unzOpenInternal (voidpf file, zlib_filefunc64_32_def ∗pzlib_filefunc64_32_def, int is64bitOpenFunction, unsigned flags)
- int ZEXPORT unzClose _Z_OF ((unzFile file))

  Addition for GDAL : START.
- int ZEXPORT unzGetGlobalInfo _Z_OF ((unzFile file, unz_global_info ∗pglobal_info))
- int ZEXPORT unzGetGlobalInfo64 _Z_OF ((unzFile file, unz_global_info64 ∗pglobal_info))
- int ZEXPORT unzGetGlobalComment _Z_OF ((unzFile file, char ∗szComment, uLong uSizeBuf))
- int ZEXPORT unzLocateFile _Z_OF ((unzFile file, const char ∗szFileName, int iCaseSensitivity))
- int ZEXPORT unzGetFilePos (unzFile file, unz_file_pos ∗file_pos)
- int ZEXPORT unzGoToFilePos (unzFile file, unz_file_pos ∗file_pos)
- int ZEXPORT unzGetFilePos64 (unzFile file, unz64_file_pos ∗file_pos)
- int ZEXPORT unzGoToFilePos64 (unzFile file, const unz64_file_pos ∗file_pos)
- int ZEXPORT unzGetCurrentFileInfo64 _Z_OF ((unzFile file, unz_file_info64 ∗pfile_info, char ∗szFileName, uLong fileNameBufferSize, void ∗extraField, uLong extraFieldBufferSize, char ∗szComment, uLong commentBufferSize))
- int ZEXPORT unzGetCurrentFileInfo _Z_OF ((unzFile file, unz_file_info ∗pfile_info, char ∗szFileName, uLong fileNameBufferSize, void ∗extraField, uLong extraFieldBufferSize, char ∗szComment, uLong commentBufferSize))
- int ZEXPORT unzOpenCurrentFilePassword _Z_OF ((unzFile file, const char ∗password))
- int ZEXPORT unzOpenCurrentFile2 _Z_OF ((unzFile file, int ∗method, int ∗level, int raw))
- int ZEXPORT unzOpenCurrentFile3 _Z_OF ((unzFile file, int ∗method, int ∗level, int raw, const char ∗password))
- int ZEXPORT unzReadCurrentFile _Z_OF ((unzFile file, voidp buf, unsigned len))
- ZPOS64_T ZEXPORT unzGetOffset64 (unzFile file)

- uLong ZEXPORT unzGetOffset (unzFile file)
- int ZEXPORT unzSetOffset64 (unzFile file, ZPOS64_T pos)
- int ZEXPORT unzSetOffset (unzFile file, uLong pos)
- int ZEXPORT unzSetFlags (unzFile file, unsigned flags)
- int ZEXPORT unzClearFlags (unzFile file, unsigned flags)

13.108.1 Data Structure Documentation

13.108.1.1 struct tm_unz_s

Definition at line 92 of file unzip.h.

Collaboration diagram for tm_unz_s:

Data Fields

uInt	tm_hour	
uInt	tm_mday	
uInt	tm_min	
uInt	tm_mon	
uInt	tm_sec	
uInt	tm_year	

13.108.1.2 struct unz_global_info64_s

Definition at line 104 of file unzip.h.

Collaboration diagram for unz_global_info64_s:

Data Fields

ZPOS64_T	number_entry	
uLong	size_comment	

13.108.1.3 struct unz_global_info_s

Definition at line 111 of file unzip.h.

Collaboration diagram for unz_global_info_s:

Data Fields

uLong	number_entry	
uLong	size_comment	

13.108.1.4 struct unz_file_info64_s

Definition at line 119 of file unzip.h.

Collaboration diagram for unz_file_info64_s:

Data Fields

ZPOS64_T	compressed_-size	

uLong	compression_-method	
uLong	crc	
uLong	disk_num_start	
uLong	dosDate	
uLong	external_fa	
uLong	flag	
uLong	internal_fa	
uLong	size_file_-comment	
uLong	size_file_extra	
uLong	size_filename	
tm_unz	tmu_date	
ZPOS64_T	uncompressed_-size	
uLong	version	
uLong	version_needed	

13.108.1.5 struct unz_file_info_s

Definition at line 140 of file unzip.h.

Collaboration diagram for unz_file_info_s:

Data Fields

uLong	compressed_-size	

uLong	compression_-method	
uLong	crc	
uLong	disk_num_start	
uLong	dosDate	
uLong	external_fa	
uLong	flag	
uLong	internal_fa	
uLong	size_file_-comment	
uLong	size_file_extra	
uLong	size_filename	
tm_unz	tmu_date	
uLong	uncompressed_-size	
uLong	version	
uLong	version_needed	

13.108.1.6 struct unz_file_pos_s

Definition at line 278 of file unzip.h.

Collaboration diagram for unz_file_pos_s:

Data Fields

uLong	num_of_file	
uLong	pos_in_zip_-directory	

13.108.1.7 struct unz64_file_pos_s

Definition at line 292 of file unzip.h.

Collaboration diagram for unz64_file_pos_s:

Data Fields

ZPOS64_T	num_of_file	
ZPOS64_T	pos_in_zip_-directory	

13.108.2 Macro Definition Documentation

13.108.2.1 #define UNZ_AUTO_CLOSE 0x01u

Definition at line 88 of file unzip.h.

Referenced by QuaZip::open(), unzClose(), and unzOpenInternal().

13.108.2.2 #define UNZ_BADZIPFILE (-103)

Definition at line 84 of file unzip.h.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), unz64local_GetCurrentFileInfoInternal(), unzOpenCurrentFile3(), and unzOpenInternal().

13.108.2.3 #define UNZ_CRCERROR (-105)

Definition at line 86 of file unzip.h.

Referenced by unzCloseCurrentFile().

13.108.2.4 #define UNZ_DEFAULT_FLAGS UNZ_AUTO_CLOSE

Definition at line 89 of file unzip.h.

Referenced by unzOpen(), unzOpen2(), unzOpen2_64(), and unzOpen64().

13.108.2.5 #define UNZ_END_OF_LIST_OF_FILE (-100)

Definition at line 80 of file unzip.h.

Referenced by QuaZipPrivate::goToFirstUnmappedFile(), QuaZip::goToNextFile(), unzGetFilePos64(), unzGoToNextFile(), unzLocateFile(), and unzReadCurrentFile().

13.108.2.6 #define UNZ_EOF (0)

Definition at line 82 of file unzip.h.

Referenced by unz64local_getByte(), and unzReadCurrentFile().

13.108.2.7 #define UNZ_ERRNO (Z_ERRNO)

Definition at line 81 of file unzip.h.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), unz64local_getByte(), unz64local_GetCurrentFileInfoInternal(), unzGetGlobalComment(), unzGetLocalExtrafield(), unzOpenInternal(), and unzReadCurrentFile().

13.108.2.8 #define UNZ_INTERNALERROR (-104)

Definition at line 85 of file unzip.h.

Referenced by unzOpenCurrentFile3().

13.108.2.9 #define UNZ_OK (0)

Definition at line 79 of file unzip.h.

Referenced by QuaZip::close(), QuaZipFile::close(), JlCompress::compressFile(), QuaZipFile::csize(), JlCompress::extractFile(), QuaZipFile::getActualFileName(), QuaZip::getComment(), QuaZip::getCurrentFileInfo(), QuaZip::getCurrentFileName(), QuaZip::getEntriesCount(), QuaZipFile::getFileInfo(), QuaZipPrivate::getFileInfoList(), QuaZip::goToFirstFile(), QuaZipPrivate::goToFirstUnmappedFile(), QuaZip::goToNextFile(), QuaZip::open(), QuaZipFile::open(), QuaZipFile::readData(), QuaZipFilePrivate::resetZipError(), QuaZip::setCurrentFile(), QuaZipFilePrivate::setZipError(), unz64local_CheckCurrentFileCoherencyHeader(), unz64local_getByte(), unz64local_GetCurrentFileInfoInternal(), unz64local_getLong(), unz64local_getLong64(), unz64local_getShort(), unz64local_SearchCentralDir64(), unzClearFlags(), unzClose(), unzCloseCurrentFile(), unzGetCurrentFileInfo(), unzGetFilePos(), unzGetFilePos64(), unzGetGlobalInfo(), unzGetGlobalInfo64(), unzGoToFilePos64(), unzGoToFirstFile(), unzGoToNextFile(), unzLocateFile(), unzOpenCurrentFile3(), unzOpenInternal(), unzReadCurrentFile(), unzSetFlags(), unzSetOffset64(), and QuaZipFile::usize().

13.108.2.10 #define UNZ_PARAMERROR (-102)

Definition at line 83 of file unzip.h.

Referenced by QuaZip::setCurrentFile(), unz64local_GetCurrentFileInfoInternal(), unzClearFlags(), unzClose(), unzCloseCurrentFile(), unzeof(), unzGetFilePos64(), unzGetGlobalComment(), unzGetGlobalInfo(), unzGetGlobalInfo64(), unzGetLocalExtrafield(), unzGoToFilePos(), unzGoToFilePos64(), unzGoToFirstFile(), unzGoToNextFile(), unzLocateFile(), unzOpenCurrentFile3(), unzReadCurrentFile(), unzSetFlags(), unzSetOffset64(), and unztell().

13.108.2.11 #define Z_BZIP2ED 12

Definition at line 67 of file unzip.h.

Referenced by unz64local_CheckCurrentFileCoherencyHeader(), unzCloseCurrentFile(), unzOpenCurrentFile3(), unzReadCurrentFile(), zip64FlushWriteBuffer(), zipCloseFileInZipRaw64(), zipOpenNewFileInZip4_64(), and zipWriteInFileInZip().

13.108.3 Typedef Documentation

13.108.3.1 typedef struct tm_unz_s tm_unz

13.108.3.2 typedef struct unz64_file_pos_s unz64_file_pos

13.108.3.3 typedef struct unz_file_info_s unz_file_info

13.108.3.4 typedef struct unz_file_info64_s unz_file_info64

13.108.3.5 typedef struct unz_file_pos_s unz_file_pos

13.108.3.6 typedef struct unz_global_info_s unz_global_info

13.108.3.7 typedef struct unz_global_info64_s unz_global_info64

13.108.3.8 typedef voidp unzFile

Definition at line 75 of file unzip.h.

13.108.4 Function Documentation

13.108.4.1 int ZEXPORT unzStringFileNameCompare _Z_OF ((const char *fileName1, const char *fileName2, int iCaseSensitivity))

13.108.4.2 unzFile ZEXPORT unzOpen _Z_OF ((voidpf file))

13.108.4.3 unzFile ZEXPORT unzOpen2 _Z_OF ((voidpf file, zlib_filefunc_def *pzlib_filefunc_def))

13.108.4.4 unzFile ZEXPORT unzOpen2_64 _Z_OF ((voidpf file, zlib_filefunc64_def *pzlib_filefunc_def))

13.108.4.5 int ZEXPORT unzClose _Z_OF ((unzFile file))

Addition for GDAL : END.

13.108.4.6 int ZEXPORT unzGetGlobalInfo _Z_OF ((unzFile file, unz_global_info *pglobal_info))

13.108.4.7 int ZEXPORT unzGetGlobalInfo64 _Z_OF ((unzFile file, unz_global_info64 *pglobal_info))

13.108.4.8 int ZEXPORT unzGetGlobalComment _Z_OF ((unzFile file, char *szComment, uLong uSizeBuf))

13.108.4.9 int ZEXPORT unzLocateFile _Z_OF ((unzFile file, const char *szFileName, int iCaseSensitivity))

13.108.4.10 int ZEXPORT unzGetCurrentFileInfo64 _Z_OF ((unzFile file, unz_file_info64 *pfile_info, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize))

13.108.4.11 int ZEXPORT unzGetCurrentFileInfo _Z_OF ((unzFile file, unz_file_info *pfile_info, char *szFileName, uLong fileNameBufferSize, void *extraField, uLong extraFieldBufferSize, char *szComment, uLong commentBufferSize))

13.108.4.12 int ZEXPORT unzOpenCurrentFilePassword _Z_OF ((unzFile file, const char *password))

13.108.4.13 int ZEXPORT unzOpenCurrentFile2 _Z_OF ((unzFile file, int *method, int *level, int raw))

13.108.4.14 int ZEXPORT unzOpenCurrentFile3 _Z_OF ((unzFile file, int *method, int *level, int raw, const char *password))

13.108.4.15 int ZEXPORT unzReadCurrentFile _Z_OF ((unzFile file, voidp buf, unsigned len))

13.108.4.16 int ZEXPORT unzClearFlags (unzFile *file*, unsigned *flags*)

Definition at line 2147 of file unzip.c.

References unz64_s::flags, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::open().

```
2148 {
2149     unz64_s* s;
2150     if (file == NULL)
2151         return UNZ_PARAMERROR;
2152     s = (unz64_s*)file;
2153     s->flags &= ~flags;
2154     return UNZ_OK;
2155 }
```

Here is the caller graph for this function:

13.108.4.17 int ZEXPORT unzGetFilePos (unzFile *file*, unz_file_pos * *file_pos*)

Definition at line 1334 of file unzip.c.

References unz_file_pos_s::num_of_file, unz64_file_pos_s::num_of_file, unz_file_pos_s::pos_in_zip_directory, unz64_file_pos_s::pos_in_zip_directory, UNZ_OK, and unzGetFilePos64().

```
1337 {
1338     unz64_file_pos file_pos64;
1339     int err = unzGetFilePos64(file,&file_pos64);
1340     if (err==UNZ_OK)
1341     {
1342         file_pos->pos_in_zip_directory = (uLong)file_pos64.
      pos_in_zip_directory;
1343         file_pos->num_of_file = (uLong)file_pos64.num_of_file;
1344     }
1345     return err;
1346 }
```

Here is the call graph for this function:

13.108.4.18 int ZEXPORT unzGetFilePos64 (unzFile *file*, unz64_file_pos * *file_pos*)

Definition at line 1318 of file unzip.c.

References unz64_s::current_file_ok, unz64_s::num_file, unz64_file_pos_s::num_of_file, unz64_s::pos_in_central_dir, unz64_file_pos_s::pos_in_zip_directory, UNZ_END_OF_LIST_OF_FILE, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZipPrivate::addCurrentFileToDirectoryMap(), and unzGetFilePos().

```
{
    unz64_s* s;

    if (file==NULL || file_pos==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;
    if (!s->current_file_ok)
        return UNZ_END_OF_LIST_OF_FILE;

    file_pos->pos_in_zip_directory  = s->pos_in_central_dir;
    file_pos->num_of_file           = s->num_file;

    return UNZ_OK;
}
```

Here is the caller graph for this function:

13.108.4.19 uLong ZEXPORT unzGetOffset (unzFile *file*)

Definition at line 2102 of file unzip.c.

References unzGetOffset64().

```
{
    ZPOS64_T offset64;

    if (file==NULL)
          return 0; /*UNZ_PARAMERROR; */
    offset64 = unzGetOffset64(file);
    return (uLong)offset64;
}
```

Here is the call graph for this function:

13.108.4.20 ZPOS64_T ZEXPORT unzGetOffset64 (unzFile *file*)

Definition at line 2087 of file unzip.c.

References unz64_s::current_file_ok, unz64_s::gi, unz64_s::num_file, unz_global_info64_s::number_entry, and unz64_s::pos_in_central_dir.

Referenced by unzGetOffset().

```
{
    unz64_s* s;

    if (file==NULL)
          return 0; /*UNZ_PARAMERROR; */
    s=(unz64_s*)file;
    if (!s->current_file_ok)
      return 0;
    if (s->gi.number_entry != 0 && s->gi.number_entry != 0xffff)
      if (s->num_file==s->gi.number_entry)
         return 0;
    return s->pos_in_central_dir;
}
```

Here is the caller graph for this function:

13.108.4.21 int ZEXPORT unzGoToFilePos (unzFile *file*, unz_file_pos * *file_pos*)

Definition at line 1370 of file unzip.c.

References unz_file_pos_s::num_of_file, unz64_file_pos_s::num_of_file, unz_file_pos_s::pos_in_zip_directory, unz64_file_pos_s::pos_in_zip_directory, UNZ_PARAMERROR, and unzGoToFilePos64().

```
{
    unz64_file_pos file_pos64;
    if (file_pos == NULL)
        return UNZ_PARAMERROR;

    file_pos64.pos_in_zip_directory = file_pos->
  pos_in_zip_directory;
    file_pos64.num_of_file = file_pos->num_of_file;
    return unzGoToFilePos64(file,&file_pos64);
}
```

Here is the call graph for this function:

13.108.4.22 int ZEXPORT unzGoToFilePos64 (unzFile *file*, const unz64_file_pos * *file_pos*)

Definition at line 1348 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::num_file, unz64_file_pos_s::num_of_file, unz64_s::pos_in_central_dir, unz64_file_pos_s::pos_in_zip_directory, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZipPrivate::goToFirstUnmappedFile(), QuaZip::setCurrentFile(), and unzGoToFilePos().

```
{
    unz64_s* s;
    int err;

    if (file==NULL || file_pos==NULL)
        return UNZ_PARAMERROR;
    s=(unz64_s*)file;

    /* jump to the right spot */
    s->pos_in_central_dir = file_pos->pos_in_zip_directory;
    s->num_file           = file_pos->num_of_file;

    /* set the current file */
    err = unz64local_GetCurrentFileInfoInternal(file,&s->cur_file_info,
                                                &s->cur_file_info_internal,
                                                NULL,0,NULL,0,NULL,0);
    /* return results */
    s->current_file_ok = (err == UNZ_OK);
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.108.4.23 unzFile unzOpenInternal (voidpf *file*, zlib_filefunc64_32_def * *pzlib_filefunc64_32_def*, int *is64bitOpenFunction*, unsigned *flags*)

Definition at line 587 of file unzip.c.

References ALLOC, unz64_s::byte_before_the_zipfile, unz64_s::central_pos, unz64_s::encrypted, unz64_s::filestream, fill_qiodevice64_filefunc(), unz64_s::flags, unz64_s::gi, unz64_s::is64bitOpenFunction, unz64_s::isZip64, unz_global_info64_s::number_entry, unz64_s::offset_central_dir, unz64_s::pfile_in_zip_read, unz64_s::size_central_dir, unz_global_info64_s::size_comment, unz64local_getLong(), unz64local_getLong64(), unz64local_getShort(), unz64local_SearchCentralDir(), unz64local_SearchCentralDir64(), UNZ_AUTO_CLOSE, UNZ_BADZIPFILE, unz_copyright, UNZ_ERRNO, UNZ_OK, unzGoToFirstFile(), unz64_s::z_filefunc, ZCLOSE64, ZFAKECLOSE64, zlib_filefunc64_32_def_s::zfile_func64, ZLIB_FILEFUNC_MODE_EXISTING, ZLIB_FILEFUNC_MODE_READ, ZLIB_FILEFUNC_SEEK_SET, ZOPEN64, zlib_filefunc64_32_def_s::zseek32_file, ZSEEK64, and zlib_filefunc64_32_def_s::ztell32_file.

Referenced by QuaZip::open(), unzOpen(), unzOpen2(), unzOpen2_64(), and unzOpen64().

```
{
    unz64_s us;
    unz64_s *s;
    ZPOS64_T central_pos;
    uLong   uL;

    uLong number_disk;          /* number of the current dist, used for
                                   spaning ZIP, unsupported, always 0*/
    uLong number_disk_with_CD;  /* number the the disk with central dir, used
                                   for spaning ZIP, unsupported, always 0*/
    ZPOS64_T number_entry_CD;      /* total number of entries in
                                   the central dir
                                   (same than number_entry on nospan) */

    int err=UNZ_OK;

    if (unz_copyright[0]!=' ')
        return NULL;

    us.flags = flags;
    us.z_filefunc.zseek32_file = NULL;
    us.z_filefunc.ztell32_file = NULL;
    if (pzlib_filefunc64_32_def==NULL)
        fill_qiodevice64_filefunc(&us.z_filefunc.zfile_func64);
    else
        us.z_filefunc = *pzlib_filefunc64_32_def;
    us.is64bitOpenFunction = is64bitOpenFunction;



    us.filestream = ZOPEN64(us.z_filefunc,
                                                file,
                                                ZLIB_FILEFUNC_MODE_READ |
                                                ZLIB_FILEFUNC_MODE_EXISTING);
    if (us.filestream==NULL)
        return NULL;

    central_pos = unz64local_SearchCentralDir64(&us.z_filefunc,us.filestream);
    if (central_pos)
    {
        uLong uS;
        ZPOS64_T uL64;

```

```
        us.isZip64 = 1;

        if (ZSEEK64(us.z_filefunc, us.filestream,
                                    central_pos,ZLIB_FILEFUNC_SEEK_SET)!=0)
        err=UNZ_ERRNO;

        /* the signature, already checked */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* size of zip64 end of central directory record */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&uL64)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* version made by */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uS)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* version needed to extract */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uS)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of this disk */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&number_disk)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of the disk with the start of the central directory */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&number_disk_with_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central directory on this disk */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.gi.number_entry)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central directory */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&number_entry_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        if ((number_entry_CD!=us.gi.number_entry) ||
            (number_disk_with_CD!=0) ||
            (number_disk!=0))
            err=UNZ_BADZIPFILE;

        /* size of the central directory */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.size_central_dir)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* offset of start of central directory with respect to the
          starting disk number */
        if (unz64local_getLong64(&us.z_filefunc, us.filestream,&us.offset_central_dir)!=UNZ_OK)
            err=UNZ_ERRNO;

        us.gi.size_comment = 0;
    }
    else
    {
        central_pos = unz64local_SearchCentralDir(&us.z_filefunc,us.filestream);
        if (central_pos==0)
            err=UNZ_ERRNO;

        us.isZip64 = 0;

        if (ZSEEK64(us.z_filefunc, us.filestream,
                                    central_pos,ZLIB_FILEFUNC_SEEK_SET)!=0)
            err=UNZ_ERRNO;

        /* the signature, already checked */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* number of this disk */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&number_disk)!=UNZ_OK)
            err=UNZ_ERRNO;

```

```
        /* number of the disk with the start of the central directory */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&number_disk_with_CD)!=UNZ_OK)
            err=UNZ_ERRNO;

        /* total number of entries in the central dir on this disk */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.gi.number_entry = uL;

        /* total number of entries in the central dir */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        number_entry_CD = uL;

        if ((number_entry_CD!=us.gi.number_entry) ||
            (number_disk_with_CD!=0) ||
            (number_disk!=0))
            err=UNZ_BADZIPFILE;

        /* size of the central directory */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.size_central_dir = uL;

        /* offset of start of central directory with respect to the
            starting disk number */
        if (unz64local_getLong(&us.z_filefunc, us.filestream,&uL)!=UNZ_OK)
            err=UNZ_ERRNO;
        us.offset_central_dir = uL;

        /* zipfile comment length */
        if (unz64local_getShort(&us.z_filefunc, us.filestream,&us.gi.size_comment)!=UNZ_OK)
            err=UNZ_ERRNO;
    }

    if ((central_pos<us.offset_central_dir+us.size_central_dir) &&
        (err==UNZ_OK))
        err=UNZ_BADZIPFILE;

    if (err!=UNZ_OK)
    {
        if ((us.flags & UNZ_AUTO_CLOSE) != 0)
            ZCLOSE64(us.z_filefunc, us.filestream);
        else
            ZFAKECLOSE64(us.z_filefunc, us.filestream);
        return NULL;
    }

    us.byte_before_the_zipfile = central_pos -
                            (us.offset_central_dir+us.size_central_dir);
    us.central_pos = central_pos;
    us.pfile_in_zip_read = NULL;
    us.encrypted = 0;


    s=(unz64_s*)ALLOC(sizeof(unz64_s));
    if( s != NULL)
    {
        *s=us;
        unzGoToFirstFile((unzFile)s);
    }
    return (unzFile)s;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.108.4.24 int ZEXPORT unzSetFlags (unzFile *file*, unsigned *flags*)

Definition at line 2136 of file unzip.c.

References unz64_s::flags, UNZ_OK, and UNZ_PARAMERROR.

Referenced by QuaZip::open().

```
2137 {
2138     unz64_s* s;
2139     if (file == NULL)
2140         return UNZ_PARAMERROR;
2141     s = (unz64_s*)file;
2142     s->flags |= flags;
2143     return UNZ_OK;
2144 }
```

Here is the caller graph for this function:

13.108.4.25 int ZEXPORT unzSetOffset (unzFile *file*, uLong *pos*)

Definition at line 2130 of file unzip.c.

References unzSetOffset64().

```
2131 {
2132     return unzSetOffset64(file,pos);
2133 }
```

Here is the call graph for this function:

13.108.4.26 int ZEXPORT unzSetOffset64 (unzFile *file*, ZPOS64_T *pos*)

Definition at line 2112 of file unzip.c.

References unz64_s::cur_file_info, unz64_s::cur_file_info_internal, unz64_s::current_file_ok, unz64_s::gi, unz64_s::num_file, unz_global_info64_s::number_entry, unz64_s::pos_in_central_dir, unz64local_GetCurrentFileInfoInternal(), UNZ_OK, and UNZ_PARAMERROR.

Referenced by unzSetOffset().

```
2113 {
2114     unz64_s* s;
2115     int err;
2116
2117     if (file==NULL)
2118         return UNZ_PARAMERROR;
2119     s=(unz64_s*)file;
2120
2121     s->pos_in_central_dir = pos;
2122     s->num_file = s->gi.number_entry;       /* hack */
2123     err = unz64local_GetCurrentFileInfoInternal(file,&s->
      cur_file_info,
2124                                                 &s->cur_file_info_internal,
2125                                                 NULL,0,NULL,0,NULL,0);
2126     s->current_file_ok = (err == UNZ_OK);
2127     return err;
2128 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109 src/ckb/quazip/zip.c File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include "zlib.h"
#include "zip.h"
#include <errno.h>
#include "crypt.h"
```

Include dependency graph for zip.c:

Data Structures

- struct linkedlist_datablock_internal_s
- struct linkedlist_data_s
- struct curfile64_info
- struct zip64_internal

Macros

- #define local static
- #define VERSIONMADEBY (0x031e) /∗ best for standard pkware crypt ∗/
- #define Z_BUFSIZE (64∗1024) /∗ (16384) ∗/
- #define Z_MAXFILENAMEINZIP (256)
- #define ALLOC(size) (malloc(size))
- #define TRYFREE(p) {if (p) free(p);}
- #define MAKEULONG64(a, b) ((ZPOS64_T)(((unsigned long)(a)) | ((ZPOS64_T)((unsigned long)(b))) << 32))
- #define SEEK_CUR 1
- #define SEEK_END 2
- #define SEEK_SET 0
- #define SIZEDATA_INDATABLOCK (4096-(4∗4))
- #define LOCALHEADERMAGIC (0x04034b50)
- #define DESCRIPTORHEADERMAGIC (0x08074b50)
- #define CENTRALHEADERMAGIC (0x02014b50)
- #define ENDHEADERMAGIC (0x06054b50)
- #define ZIP64ENDHEADERMAGIC (0x6064b50)
- #define ZIP64ENDLOCHEADERMAGIC (0x7064b50)
- #define FLAG_LOCALHEADER_OFFSET (0x06)
- #define CRC_LOCALHEADER_OFFSET (0x0e)
- #define SIZECENTRALHEADER (0x2e) /∗ 46 ∗/
- #define INCLUDECRYPTINGCODE_IFCRYPTALLOWED
- #define BUFREADCOMMENT (0x400)

Typedefs

- typedef uLongf z_crc_t
- typedef struct linkedlist_datablock_internal_s linkedlist_datablock_internal
- typedef struct linkedlist_data_s linkedlist_data

Functions

- static linkedlist_datablock_internal ∗ allocate_new_datablock ()
- static void free_datablock (linkedlist_datablock_internal ∗ldi)
- static void init_linkedlist (linkedlist_data ∗ll)
- static void free_linkedlist (linkedlist_data ∗ll)
- static int add_data_in_datablock (linkedlist_data ∗ll, const void ∗buf, uLong len)
- static int zip64local_putValue _Z_OF ((const zlib_filefunc64_32_def ∗pzlib_filefunc_def, voidpf filestream, ZPOS64_T x, int nbByte))
- static int zip64local_putValue (const zlib_filefunc64_32_def ∗pzlib_filefunc_def, voidpf filestream, ZPOS64_T x, int nbByte)
- static void zip64local_putValue_inmemory _Z_OF ((void ∗dest, ZPOS64_T x, int nbByte))

- static void zip64local_putValue_inmemory (void *dest, ZPOS64_T x, int nbByte)
- static uLong zip64local_TmzDateToDosDate (const tm_zip *ptm)
- static int zip64local_getByte _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi))
- static int zip64local_getByte (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi)
- static int zip64local_getShort _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX))
- static int zip64local_getShort (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)
- static int zip64local_getLong (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)
- static int zip64local_getLong64 _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX))
- static int zip64local_getLong64 (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX)
- static ZPOS64_T zip64local_SearchCentralDir _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream))
- static ZPOS64_T zip64local_SearchCentralDir (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)
- static ZPOS64_T zip64local_SearchCentralDir64 (const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)
- int LoadCentralDirectoryRecord (zip64_internal *pziinit)
- zipFile ZEXPORT zipOpen3 (voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc64_32_def *pzlib_filefunc64_32_def, unsigned flags)
- zipFile ZEXPORT zipOpen2 (voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc_def *pzlib_filefunc32_def)
- zipFile ZEXPORT zipOpen2_64 (voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc64_def *pzlib_filefunc_def)
- zipFile ZEXPORT zipOpen (voidpf file, int append)
- zipFile ZEXPORT zipOpen64 (voidpf file, int append)
- int Write_LocalFileHeader (zip64_internal *zi, const char *filename, uInt size_extrafield_local, const void *extrafield_local, uLong version_to_extract)
- int ZEXPORT zipOpenNewFileInZip4_64 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase, int zip64)
- int ZEXPORT zipOpenNewFileInZip4 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase)
- int ZEXPORT zipOpenNewFileInZip3 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting)
- int ZEXPORT zipOpenNewFileInZip3_64 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, int zip64)
- int ZEXPORT zipOpenNewFileInZip2 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw)
- int ZEXPORT zipOpenNewFileInZip2_64 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int zip64)
- int ZEXPORT zipOpenNewFileInZip64 (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int zip64)

- int ZEXPORT zipOpenNewFileInZip (zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level)
- static int zip64FlushWriteBuffer (zip64_internal *zi)
- int ZEXPORT zipWriteInFileInZip (zipFile file, const void *buf, unsigned int len)
- int ZEXPORT zipCloseFileInZipRaw (zipFile file, uLong uncompressed_size, uLong crc32)
- int ZEXPORT zipCloseFileInZipRaw64 (zipFile file, ZPOS64_T uncompressed_size, uLong crc32)
- int ZEXPORT zipCloseFileInZip (zipFile file)
- int Write_Zip64EndOfCentralDirectoryLocator (zip64_internal *zi, ZPOS64_T zip64eocd_pos_inzip)
- int Write_Zip64EndOfCentralDirectoryRecord (zip64_internal *zi, uLong size_centraldir, ZPOS64_T centraldir_pos_inzip)
- int Write_EndOfCentralDirectoryRecord (zip64_internal *zi, uLong size_centraldir, ZPOS64_T centraldir_pos_inzip)
- int Write_GlobalComment (zip64_internal *zi, const char *global_comment)
- int ZEXPORT zipClose (zipFile file, const char *global_comment)
- int ZEXPORT zipRemoveExtraInfoBlock (char *pData, int *dataLen, short sHeader)
- int ZEXPORT zipSetFlags (zipFile file, unsigned flags)
- int ZEXPORT zipClearFlags (zipFile file, unsigned flags)

Variables

- const char zip_copyright [] =" zip 1.01 Copyright 1998-2004 Gilles Vollant - http://www.winimage.com/zLibDll"

13.109.1 Data Structure Documentation

13.109.1.1 struct linkedlist_datablock_internal_s

Definition at line 121 of file zip.c.

Collaboration diagram for linkedlist_datablock_internal_s:

Data Fields

uLong	avail_in_this_-block	
unsigned char	data[(4096-(4 ∗4))]	
uLong	filled_in_this_-block	
struct linkedlist_-datablock_-internal_s ∗	next_datablock	
uLong	unused	

13.109.1.2 struct linkedlist_data_s

Definition at line 130 of file zip.c.

Collaboration diagram for linkedlist_data_s:

Data Fields

linkedlist_-datablock_-internal *	first_block	
linkedlist_-datablock_-internal *	last_block	

13.109.1.3 struct curfile64_info

Definition at line 137 of file zip.c.

Collaboration diagram for curfile64_info:

Data Fields

Byte	buffered_-data[(64 *1024)]	
char *	central_header	
uLong	crc32	
int	crypt_header_-size	
uLong	dosDate	
int	encrypt	
uLong	flag	
unsigned long	keys[3]	
int	method	
const z_crc_t FAR *	pcrc_32_tab	
uInt	pos_in_buffered-_data	
ZPOS64_T	pos_local_-header	
ZPOS64_T	pos_-zip64extrainfo	

int	raw	
uLong	size_central-Extra	
uLong	size_central-ExtraFree	
uLong	size_-centralheader	
z_stream	stream	
int	stream_-initialised	
ZPOS64_T	total-Compressed-Data	
ZPOS64_T	total-Uncompressed-Data	
int	zip64	

13.109.1.4 struct zip64_internal

Definition at line 172 of file zip.c.

Collaboration diagram for zip64_internal:

Data Fields

ZPOS64_T	add_position_-when_writting_-offset	
ZPOS64_T	begin_pos	
linkedlist_data	central_dir	
curfile64_info	ci	
voidpf	filestream	
unsigned	flags	
char ∗	globalcomment	
int	in_opened_file_-inzip	
ZPOS64_T	number_entry	
zlib_filefunc64_-32_def	z_filefunc	

13.109.2 Macro Definition Documentation

13.109.2.1 #define ALLOC(*size*) (malloc(size))

Definition at line 68 of file zip.c.

Referenced by allocate_new_datablock(), LoadCentralDirectoryRecord(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), zipOpen3(), zipOpenNewFileInZip4_64(), and zipRemoveExtraInfoBlock().

13.109.2.2 #define BUFREADCOMMENT (0x400)

Definition at line 481 of file zip.c.

Referenced by zip64local_SearchCentralDir(), and zip64local_SearchCentralDir64().

13.109.2.3 #define CENTRALHEADERMAGIC (0x02014b50)

Definition at line 111 of file zip.c.

Referenced by zipOpenNewFileInZip4_64().

13.109.2.4 #define CRC_LOCALHEADER_OFFSET (0x0e)

Definition at line 117 of file zip.c.

13.109.2.5 #define DESCRIPTORHEADERMAGIC (0x08074b50)

Definition at line 110 of file zip.c.

Referenced by zipCloseFileInZipRaw64().

13.109.2.6 #define ENDHEADERMAGIC (0x06054b50)

Definition at line 112 of file zip.c.

Referenced by Write_EndOfCentralDirectoryRecord().

13.109.2.7 #define FLAG_LOCALHEADER_OFFSET (0x06)

Definition at line 116 of file zip.c.

13.109.2.8 #define INCLUDECRYPTINGCODE_IFCRYPTALLOWED

Definition at line 194 of file zip.c.

13.109.2.9 #define local static

Definition at line 51 of file zip.c.

13.109.2.10 #define LOCALHEADERMAGIC (0x04034b50)

Definition at line 109 of file zip.c.

Referenced by Write_LocalFileHeader().

13.109.2.11 #define MAKEULONG64(a, b) ((ZPOS64_T)(((unsigned long)(a)) | ((ZPOS64_T)((unsigned long)(b))) << 32))

Definition at line 83 of file zip.c.

13.109.2.12 #define SEEK_CUR 1

Definition at line 86 of file zip.c.

13.109.2.13 #define SEEK_END 2

Definition at line 90 of file zip.c.

Referenced by zipOpen3().

13.109.2.14 #define SEEK_SET 0

Definition at line 94 of file zip.c.

13.109.2.15 #define SIZECENTRALHEADER (0x2e) /* 46 */

Definition at line 119 of file zip.c.

Referenced by zipOpenNewFileInZip4_64().

13.109.2.16 #define SIZEDATA_INDATABLOCK (4096-(4*4))

Definition at line 107 of file zip.c.

Referenced by allocate_new_datablock(), and LoadCentralDirectoryRecord().

13.109.2.17 #define TRYFREE(p) {if (p) free(p);}

Definition at line 71 of file zip.c.

Referenced by free_datablock(), LoadCentralDirectoryRecord(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), zipClose(), zipOpen3(), and zipRemoveExtraInfoBlock().

13.109.2.18 #define VERSIONMADEBY (0x031e) /* best for standard pkware crypt */

Definition at line 56 of file zip.c.

Referenced by zipOpenNewFileInZip(), zipOpenNewFileInZip2(), zipOpenNewFileInZip2_64(), zipOpenNewFileInZip3(), zipOpenNewFileInZip3_64(), and zipOpenNewFileInZip64().

13.109.2.19 #define Z_BUFSIZE (64*1024) /* (16384) */

Definition at line 60 of file zip.c.

Referenced by zipCloseFileInZipRaw64(), zipOpenNewFileInZip4_64(), and zipWriteInFileInZip().

13.109.2.20 #define Z_MAXFILENAMEINZIP (256)

Definition at line 64 of file zip.c.

13.109.2.21 #define ZIP64ENDHEADERMAGIC (0x6064b50)

Definition at line 113 of file zip.c.

Referenced by Write_Zip64EndOfCentralDirectoryRecord().

13.109.2.22 #define ZIP64ENDLOCHEADERMAGIC (0x7064b50)

Definition at line 114 of file zip.c.

Referenced by Write_Zip64EndOfCentralDirectoryLocator().

13.109.3 Typedef Documentation

13.109.3.1 typedef struct linkedlist_data_s linkedlist_data

13.109.3.2 typedef struct linkedlist_datablock_internal_s linkedlist_datablock_internal

13.109.3.3 typedef uLongf z_crc_t

Definition at line 34 of file zip.c.

13.109.4 Function Documentation

13.109.4.1 static int zip64local_putValue _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T x, int nbByte)) [static]

13.109.4.2 static void zip64local_putValue_inmemory _Z_OF ((void *dest, ZPOS64_T x, int nbByte)) [static]

13.109.4.3 static int zip64local_getByte _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, int *pi)) [static]

13.109.4.4 static int zip64local_getShort _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, uLong *pX)) [static]

13.109.4.5 static int zip64local_getLong64 _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream, ZPOS64_T *pX)) [static]

13.109.4.6 static ZPOS64_T zip64local_SearchCentralDir _Z_OF ((const zlib_filefunc64_32_def *pzlib_filefunc_def, voidpf filestream)) [static]

13.109.4.7 static int add_data_in_datablock (linkedlist_data * *ll*, const void * *buf*, uLong *len*) [static]

Definition at line 234 of file zip.c.

References allocate_new_datablock(), linkedlist_datablock_internal_s::avail_in_this_block, linkedlist_datablock_internal_s::data, linkedlist_datablock_internal_s::filled_in_this_block, linkedlist_data_s::first_block, linkedlist_data_s::last_block, linkedlist_datablock_internal_s::next_datablock, ZIP_INTERNALERROR, and ZIP_OK.

Referenced by LoadCentralDirectoryRecord(), and zipCloseFileInZipRaw64().

```
{
    linkedlist_datablock_internal* ldi;
    const unsigned char* from_copy;

    if (ll==NULL)
        return ZIP_INTERNALERROR;

    if (ll->last_block == NULL)
    {
```

```
        ll->first_block = ll->last_block = allocate_new_datablock();
        if (ll->first_block == NULL)
            return ZIP_INTERNALERROR;
    }

    ldi = ll->last_block;
    from_copy = (unsigned char*)buf;

    while (len>0)
    {
        uInt copy_this;
        uInt i;
        unsigned char* to_copy;

        if (ldi->avail_in_this_block==0)
        {
            ldi->next_datablock = allocate_new_datablock();
            if (ldi->next_datablock == NULL)
                return ZIP_INTERNALERROR;
            ldi = ldi->next_datablock ;
            ll->last_block = ldi;
        }

        if (ldi->avail_in_this_block < len)
            copy_this = (uInt)ldi->avail_in_this_block;
        else
            copy_this = (uInt)len;

        to_copy = &(ldi->data[ldi->filled_in_this_block]);

        for (i=0;i<copy_this;i++)
            *(to_copy+i)=*(from_copy+i);

        ldi->filled_in_this_block += copy_this;
        ldi->avail_in_this_block -= copy_this;
        from_copy += copy_this ;
        len -= copy_this;
    }
    return ZIP_OK;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.8 static linkedlist_datablock_internal* allocate_new_datablock ( ) [static]

Definition at line 198 of file zip.c.

References ALLOC, linkedlist_datablock_internal_s::avail_in_this_block, linkedlist_datablock_internal_s::filled_in_-this_block, linkedlist_datablock_internal_s::next_datablock, and SIZEDATA_INDATABLOCK.

Referenced by add_data_in_datablock().

```
{
    linkedlist_datablock_internal* ldi;
    ldi = (linkedlist_datablock_internal*)
                ALLOC(sizeof(linkedlist_datablock_internal));
    if (ldi!=NULL)
    {
        ldi->next_datablock = NULL ;
        ldi->filled_in_this_block = 0 ;
        ldi->avail_in_this_block = SIZEDATA_INDATABLOCK ;
    }
    return ldi;
}
```

Here is the caller graph for this function:

13.109.4.9 static void free_datablock (linkedlist_datablock_internal * *ldi*) [static]

Definition at line 212 of file zip.c.

References linkedlist_datablock_internal_s::next_datablock, and TRYFREE.

Referenced by free_linkedlist().

```
{
    while (ldi!=NULL)
    {
        linkedlist_datablock_internal* ldinext = ldi->
next_datablock;
        TRYFREE(ldi);
        ldi = ldinext;
    }
}
```

Here is the caller graph for this function:

13.109.4.10 static void free_linkedlist (linkedlist_data * ll) [static]

Definition at line 227 of file zip.c.

References linkedlist_data_s::first_block, free_datablock(), and linkedlist_data_s::last_block.

Referenced by zipClose().

```
228 {
229     free_datablock(ll->first_block);
230     ll->first_block = ll->last_block = NULL;
231 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.11 static void init_linkedlist (linkedlist_data * ll) [static]

Definition at line 222 of file zip.c.

References linkedlist_data_s::first_block, and linkedlist_data_s::last_block.

Referenced by zipOpen3().

```
223 {
224     ll->first_block = ll->last_block = NULL;
225 }
```

Here is the caller graph for this function:

13.109.4.12 int LoadCentralDirectoryRecord (zip64_internal * *pziinit*)

Definition at line 649 of file zip.c.

References add_data_in_datablock(), zip64_internal::add_position_when_writting_offset, ALLOC, zip64_internal::begin_pos, zip64_internal::central_dir, zip64_internal::filestream, zip64_internal::flags, zip64_internal::globalcomment, zip64_internal::number_entry, SIZEDATA_INDATABLOCK, TRYFREE, zip64_internal::z_filefunc, ZCLOSE64, ZFAKECLOSE64, zip64local_getLong(), zip64local_getLong64(), zip64local_getShort(), zip64local_SearchCentralDir(), zip64local_SearchCentralDir64(), ZIP_AUTO_CLOSE, ZIP_BADZIPFILE, ZIP_ERRNO, ZIP_OK, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, and ZSEEK64.

Referenced by zipOpen3().

```
650 {
651   int err=ZIP_OK;
652   ZPOS64_T byte_before_the_zipfile;/* byte before the zipfile, (>0 for sfx)*/
653
654   ZPOS64_T size_central_dir;     /* size of the central directory  */
655   ZPOS64_T offset_central_dir;   /* offset of start of central directory */
656   ZPOS64_T central_pos;
657   uLong uL;
658
659   uLong number_disk;          /* number of the current dist, used for
660                               spaning ZIP, unsupported, always 0*/
661   uLong number_disk_with_CD;  /* number the the disk with central dir, used
662                               for spaning ZIP, unsupported, always 0*/
663   ZPOS64_T number_entry;
664   ZPOS64_T number_entry_CD;      /* total number of entries in
665                                 the central dir
666                                 (same than number_entry on nospan) */
667   uLong VersionMadeBy;
668   uLong VersionNeeded;
669   uLong size_comment;
670
671   int hasZIP64Record = 0;
672
673   /* check first if we find a ZIP64 record */
674   central_pos = zip64local_SearchCentralDir64(&pziinit->
      z_filefunc,pziinit->filestream);
675   if(central_pos > 0)
676   {
677     hasZIP64Record = 1;
678   }
679   else if(central_pos == 0)
680   {
681     central_pos = zip64local_SearchCentralDir(&pziinit->
      z_filefunc,pziinit->filestream);
682   }
683
684 /* disable to allow appending to empty ZIP archive
685        if (central_pos==0)
686            err=ZIP_ERRNO;
687 */
688
689   if(hasZIP64Record)
690   {
691     ZPOS64_T sizeEndOfCentralDirectory;
692     if (ZSEEK64(pziinit->z_filefunc, pziinit->filestream, central_pos,
      ZLIB_FILEFUNC_SEEK_SET) != 0)
693       err=ZIP_ERRNO;
694
695     /* the signature, already checked */
```

```
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream,&uL)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* size of zip64 end of central directory record */
    if (zip64local_getLong64(&pziinit->z_filefunc, pziinit->filestream, &sizeEndOfCentralDirectory)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* version made by */
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream, &VersionMadeBy)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* version needed to extract */
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream, &VersionNeeded)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* number of this disk */
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream,&number_disk)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* number of the disk with the start of the central directory */
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream,&number_disk_with_CD)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* total number of entries in the central directory on this disk */
    if (zip64local_getLong64(&pziinit->z_filefunc, pziinit->filestream, &number_entry)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* total number of entries in the central directory */
    if (zip64local_getLong64(&pziinit->z_filefunc, pziinit->filestream,&number_entry_CD)!=ZIP_OK)
      err=ZIP_ERRNO;

    if ((number_entry_CD!=number_entry) || (number_disk_with_CD!=0) || (number_disk!=0))
      err=ZIP_BADZIPFILE;

    /* size of the central directory */
    if (zip64local_getLong64(&pziinit->z_filefunc, pziinit->filestream,&size_central_dir)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* offset of start of central directory with respect to the
    starting disk number */
    if (zip64local_getLong64(&pziinit->z_filefunc, pziinit->filestream,&offset_central_dir)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* TODO.. */
    /* read the comment from the standard central header. */
    size_comment = 0;
  }
  else
  {
    /* Read End of central Directory info */
    if (ZSEEK64(pziinit->z_filefunc, pziinit->filestream, central_pos, ZLIB_FILEFUNC_SEEK_SET)!=0)
      err=ZIP_ERRNO;

    /* the signature, already checked */
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream,&uL)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* number of this disk */
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream,&number_disk)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* number of the disk with the start of the central directory */
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream,&number_disk_with_CD)!=ZIP_OK)
      err=ZIP_ERRNO;

    /* total number of entries in the central dir on this disk */
    number_entry = 0;
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream, &uL)!=ZIP_OK)
      err=ZIP_ERRNO;
    else
      number_entry = uL;

```

```
    /* total number of entries in the central dir */
    number_entry_CD = 0;
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream, &uL)!=ZIP_OK)
        err=ZIP_ERRNO;
    else
        number_entry_CD = uL;

    if ((number_entry_CD!=number_entry) || (number_disk_with_CD!=0) || (number_disk!=0))
        err=ZIP_BADZIPFILE;

    /* size of the central directory */
    size_central_dir = 0;
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream, &uL)!=ZIP_OK)
        err=ZIP_ERRNO;
    else
        size_central_dir = uL;

    /* offset of start of central directory with respect to the starting disk number */
    offset_central_dir = 0;
    if (zip64local_getLong(&pziinit->z_filefunc, pziinit->filestream, &uL)!=ZIP_OK)
        err=ZIP_ERRNO;
    else
        offset_central_dir = uL;


    /* zipfile global comment length */
    if (zip64local_getShort(&pziinit->z_filefunc, pziinit->filestream, &size_comment)!=ZIP_OK)
        err=ZIP_ERRNO;
  }

  if ((central_pos<offset_central_dir+size_central_dir) &&
     (err==ZIP_OK))
    err=ZIP_BADZIPFILE;

  if (err!=ZIP_OK)
  {
      if ((pziinit->flags & ZIP_AUTO_CLOSE) != 0) {
        ZCLOSE64(pziinit->z_filefunc, pziinit->filestream);
      } else {
        ZFAKECLOSE64(pziinit->z_filefunc, pziinit->filestream);
      }
    return ZIP_ERRNO;
  }

  if (size_comment>0)
  {
    pziinit->globalcomment = (char*)ALLOC(size_comment+1);
    if (pziinit->globalcomment)
    {
      size_comment = ZREAD64(pziinit->z_filefunc, pziinit->filestream, pziinit->globalcomment,size_comment);
      pziinit->globalcomment[size_comment]=0;
    }
  }

  byte_before_the_zipfile = central_pos - (offset_central_dir+size_central_dir);
  pziinit->add_position_when_writting_offset = byte_before_the_zipfile;

  {
    ZPOS64_T size_central_dir_to_read = size_central_dir;
    size_t buf_size = SIZEDATA_INDATABLOCK;
    void* buf_read = (void*)ALLOC(buf_size);
    if (ZSEEK64(pziinit->z_filefunc, pziinit->filestream, offset_central_dir + byte_before_the_zipfile, ZLIB_FILEFUNC_SEEK_SET) != 0)
        err=ZIP_ERRNO;

    while ((size_central_dir_to_read>0) && (err==ZIP_OK))
    {
      ZPOS64_T read_this = SIZEDATA_INDATABLOCK;
      if (read_this > size_central_dir_to_read)
        read_this = size_central_dir_to_read;

      if (ZREAD64(pziinit->z_filefunc, pziinit->filestream,buf_read,(uLong)read_this) != read_this)
        err=ZIP_ERRNO;

      if (err==ZIP_OK)
        err = add_data_in_datablock(&pziinit->central_dir,buf_read, (uLong)read_this);

      size_central_dir_to_read-=read_this;
    }
```

```
    TRYFREE(buf_read);
  }
  pziinit->begin_pos = byte_before_the_zipfile;
  pziinit->number_entry = number_entry_CD;

  if (ZSEEK64(pziinit->z_filefunc, pziinit->filestream, offset_central_dir+
  byte_before_the_zipfile,ZLIB_FILEFUNC_SEEK_SET) != 0)
    err=ZIP_ERRNO;

  return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.13 int Write_EndOfCentralDirectoryRecord (zip64_internal * *zi*, uLong *size_centraldir*, ZPOS64_T *centraldir_pos_inzip*)

Definition at line 1876 of file zip.c.

References zip64_internal::add_position_when_writting_offset, ENDHEADERMAGIC, zip64_internal::filestream, zip64_internal::number_entry, zip64_internal::z_filefunc, zip64local_putValue(), and ZIP_OK.

Referenced by zipClose().

```
{
  int err = ZIP_OK;

  /*signature*/
  err = zip64local_putValue(&zi->z_filefunc,zi->
filestream,(uLong)ENDHEADERMAGIC,4);

  if (err==ZIP_OK) /* number of this disk */
    err = zip64local_putValue(&zi->z_filefunc,zi->
filestream,(uLong)0,2);

  if (err==ZIP_OK) /* number of the disk with the start of the central directory */
    err = zip64local_putValue(&zi->z_filefunc,zi->
filestream,(uLong)0,2);

  if (err==ZIP_OK) /* total number of entries in the central dir on this disk */
```

```
  {
    {
      if(zi->number_entry >= 0xFFFF)
        err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0xffff,2); /* use value in ZIP64 record */
      else
        err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)zi->number_entry,2);
    }
  }

  if (err==ZIP_OK) /* total number of entries in the central dir */
  {
    if(zi->number_entry >= 0xFFFF)
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0xffff,2); /* use value in ZIP64 record */
    else
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)zi->number_entry,2);
  }

  if (err==ZIP_OK) /* size of the central directory */
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)size_centraldir,4);

  if (err==ZIP_OK) /* offset of start of central directory with respect to the starting disk number */
  {
    ZPOS64_T pos = centraldir_pos_inzip - zi->add_position_when_writting_offset;
    if(pos >= 0xffffffff)
    {
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream, (uLong)0xffffffff,4);
    }
    else
                  err = zip64local_putValue(&zi->z_filefunc,zi->filestream, (uLong)(centraldir_pos_inzip - zi->add_position_when_writting_offset),4);
  }

   return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.14 int Write_GlobalComment (zip64_internal * *zi*, const char * *global_comment*)

Definition at line 1924 of file zip.c.

References zip64_internal::filestream, zip64_internal::z_filefunc, zip64local_putValue(), ZIP_ERRNO, ZIP_OK, and ZWRITE64.

Referenced by zipClose().

```
{
  int err = ZIP_OK;
  uInt size_global_comment = 0;

  if(global_comment != NULL)
    size_global_comment = (uInt)strlen(global_comment);

  err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)size_global_comment,2);

  if (err == ZIP_OK && size_global_comment > 0)
  {
    if (ZWRITE64(zi->z_filefunc,zi->filestream, global_comment, size_global_comment) != size_global_comment)
      err = ZIP_ERRNO;
  }
  return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.15 int Write_LocalFileHeader (zip64_internal * *zi*, const char * *filename*, uInt *size_extrafield_local*, const void * *extrafield_local*, uLong *version_to_extract*)

Definition at line 977 of file zip.c.

References zip64_internal::ci, curfile64_info::dosDate, zip64_internal::filestream, curfile64_info::flag, LOCALHEADERMAGIC, curfile64_info::method, curfile64_info::pos_zip64extrainfo, zip64_internal::z_filefunc, curfile64_info::zip64, zip64local_putValue(), ZIP_ERRNO, ZIP_OK, ZTELL64, and ZWRITE64.

Referenced by zipOpenNewFileInZip4_64().

```
{
  /* write the local header */
  int err;
  uInt size_filename = (uInt)strlen(filename);
  uInt size_extrafield = size_extrafield_local;

  err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)LOCALHEADERMAGIC, 4);

  if (err==ZIP_OK)
  {
    if(zi->ci.zip64)
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)45,2);/* version needed to extract */
    else
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)version_to_extract,2);
  }

  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)zi->ci.flag,2);

  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)zi->ci.method,2);

  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)zi->ci.dosDate,4);

  /* CRC / Compressed size / Uncompressed size will be filled in later and rewritten later */
  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4); /* crc 32, unknown */
  if (err==ZIP_OK)
  {
    if(zi->ci.zip64)
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0xFFFFFFFF,4); /* compressed size, unknown */
    else
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4); /* compressed size, unknown */
  }
  if (err==ZIP_OK)
  {
    if(zi->ci.zip64)
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0xFFFFFFFF,4); /* uncompressed size, unknown */
    else
      err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4); /* uncompressed size, unknown */
  }

  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)size_filename,2);

  if(zi->ci.zip64)
  {
    size_extrafield += 20;
  }

  if (err==ZIP_OK)
    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)size_extrafield,2);

  if ((err==ZIP_OK) && (size_filename > 0))
  {
    if (ZWRITE64(zi->z_filefunc,zi->filestream,filename,size_filename)!=size_filename)
      err = ZIP_ERRNO;
  }

  if ((err==ZIP_OK) && (size_extrafield_local > 0))
  {
    if (ZWRITE64(zi->z_filefunc, zi->filestream, extrafield_local, size_extrafield_local) != size_extrafield_local)
      err = ZIP_ERRNO;
  }


  if ((err==ZIP_OK) && (zi->ci.zip64))
  {
      /* write the Zip64 extended info */
      short HeaderID = 1;
      short DataSize = 16;
```

```
        ZPOS64_T CompressedSize = 0;
        ZPOS64_T UncompressedSize = 0;

        /* Remember position of Zip64 extended info for the local file header. (needed when we update size after done with file) */
        zi->ci.pos_zip64extrainfo = ZTELL64(zi->z_filefunc,zi->filestream);

        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, (short)HeaderID,2);
        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, (short)DataSize,2);

        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, (ZPOS64_T)UncompressedSize,8);
        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, (ZPOS64_T)CompressedSize,8);
    }

    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.16 int Write_Zip64EndOfCentralDirectoryLocator (zip64_internal * *zi*, ZPOS64_T *zip64eocd_pos_inzip*)

Definition at line 1815 of file zip.c.

References zip64_internal::add_position_when_writting_offset, zip64_internal::filestream, zip64_internal::z_filefunc, ZIP64ENDLOCHEADERMAGIC, zip64local_putValue(), and ZIP_OK.

Referenced by zipClose().

```
{
  int err = ZIP_OK;
```

```
 ZPOS64_T pos = zip64eocd_pos_inzip - zi->add_position_when_writting_offset;

 err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)ZIP64ENDLOCHEADERMAGIC,4);

 /*num disks*/
   if (err==ZIP_OK) /* number of the disk with the start of the central directory */
     err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4);

 /*relative offset*/
   if (err==ZIP_OK) /* Relative offset to the Zip64EndOfCentralDirectory */
     err = zip64local_putValue(&zi->z_filefunc,zi->filestream, pos,8);

 /*total disks*/ /* Do not support spawning of disk so always say 1 here*/
   if (err==ZIP_OK) /* number of the disk with the start of the central directory */
     err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)1,4);

   return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.17 int Write_Zip64EndOfCentralDirectoryRecord (zip64_internal * *zi*, uLong *size_centraldir*, ZPOS64_T *centraldir_pos_inzip*)

Definition at line 1837 of file zip.c.

References zip64_internal::add_position_when_writting_offset, zip64_internal::filestream, zip64_internal::number_entry, zip64_internal::z_filefunc, ZIP64ENDHEADERMAGIC, zip64local_putValue(), and ZIP_OK.

Referenced by zipClose().

```
{
  int err = ZIP_OK;

  uLong Zip64DataSize = 44;

  err = zip64local_putValue(&zi->z_filefunc,zi->
```

```
    filestream,(uLong)ZIP64ENDHEADERMAGIC,4);

 if (err==ZIP_OK) /* size of this 'zip64 end of central directory' */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(ZPOS64_T)Zip64DataSize,8); /* why ZPOS64_T of this ? */

 if (err==ZIP_OK) /* version made by */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)45,2);

 if (err==ZIP_OK) /* version needed */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)45,2);

 if (err==ZIP_OK) /* number of this disk */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4);

 if (err==ZIP_OK) /* number of the disk with the start of the central directory */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)0,4);

 if (err==ZIP_OK) /* total number of entries in the central dir on this disk */
   err = zip64local_putValue(&zi->z_filefunc, zi->filestream, zi->number_entry, 8);

 if (err==ZIP_OK) /* total number of entries in the central dir */
   err = zip64local_putValue(&zi->z_filefunc, zi->filestream, zi->number_entry, 8);

 if (err==ZIP_OK) /* size of the central directory */
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(ZPOS64_T)size_centraldir,8);

 if (err==ZIP_OK) /* offset of start of central directory with respect to the starting disk number */
 {
   ZPOS64_T pos = centraldir_pos_inzip - zi->add_position_when_writting_offset;
   err = zip64local_putValue(&zi->z_filefunc,zi->filestream, (ZPOS64_T)pos,8);
 }
 return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.18 static int zip64FlushWriteBuffer (zip64_internal * *zi*) [static]

Definition at line 1403 of file zip.c.

References curfile64_info::buffered_data, zip64_internal::ci, curfile64_info::encrypt, zip64_internal::filestream, curfile64_info::keys, curfile64_info::method, curfile64_info::pcrc_32_tab, curfile64_info::pos_in_buffered_data, curfile64_info::stream, curfile64_info::totalCompressedData, curfile64_info::totalUncompressedData, Z_BZIP2ED, zip64_internal::z_filefunc, zencode, ZIP_ERRNO, ZIP_OK, and ZWRITE64.

Referenced by zipCloseFileInZipRaw64(), and zipWriteInFileInZip().

```
{
    int err=ZIP_OK;

    if (zi->ci.encrypt != 0)
    {
#ifndef NOCRYPT
        uInt i;
        int t;
        for (i=0;i<zi->ci.pos_in_buffered_data;i++)
            zi->ci.buffered_data[i] = zencode(zi->ci.keys, zi->ci.pcrc_32_tab, zi->ci.buffered_data[i],t);
#endif
    }

    if (ZWRITE64(zi->z_filefunc,zi->filestream,zi->ci.buffered_data,zi->ci.pos_in_buffered_data) != zi->ci.pos_in_buffered_data)
      err = ZIP_ERRNO;

    zi->ci.totalCompressedData += zi->ci.pos_in_buffered_data;

#ifdef HAVE_BZIP2
    if(zi->ci.method == Z_BZIP2ED)
    {
      zi->ci.totalUncompressedData += zi->ci.bstream.total_in_lo32;
      zi->ci.bstream.total_in_lo32 = 0;
      zi->ci.bstream.total_in_hi32 = 0;
    }
    else
#endif
    {
      zi->ci.totalUncompressedData += zi->ci.stream.total_in;
      zi->ci.stream.total_in = 0;
    }


    zi->ci.pos_in_buffered_data = 0;

    return err;
}
```

Here is the caller graph for this function:

13.109.4.19 static int zip64local_getByte (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* int * *pi*) [static]

Definition at line 358 of file zip.c.

References ZERROR64, ZIP_EOF, ZIP_ERRNO, ZIP_OK, and ZREAD64.

Referenced by zip64local_getLong(), zip64local_getLong64(), and zip64local_getShort().

```
{
    unsigned char c;
    int err = (int)ZREAD64(*pzlib_filefunc_def,filestream,&c,1);
    if (err==1)
    {
        *pi = (int)c;
        return ZIP_OK;
    }
    else
    {
        if (ZERROR64(*pzlib_filefunc_def,filestream))
            return ZIP_ERRNO;
        else
            return ZIP_EOF;
    }
}
```

Here is the caller graph for this function:

13.109.4.20 static int zip64local_getLong (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* uLong * *pX*) [static]

Definition at line 404 of file zip.c.

References zip64local_getByte(), and ZIP_OK.

Referenced by LoadCentralDirectoryRecord(), and zip64local_SearchCentralDir64().

```
{
    uLong x ;
    int i = 0;
    int err;

    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x = (uLong)i;

    if (err==ZIP_OK)
        err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x += ((uLong)i)<<8;

    if (err==ZIP_OK)
        err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x += ((uLong)i)<<16;

    if (err==ZIP_OK)
        err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x += ((uLong)i)<<24;

    if (err==ZIP_OK)
        *pX = x;
    else
        *pX = 0;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.21 static int zip64local_getLong64 (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* ZPOS64_T * *pX*) [static]

Definition at line 435 of file zip.c.

References zip64local_getByte(), and ZIP_OK.

Referenced by LoadCentralDirectoryRecord(), and zip64local_SearchCentralDir64().

```
{
  ZPOS64_T x;
  int i = 0;
  int err;

  err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x = (ZPOS64_T)i;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<8;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<16;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<24;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<32;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<40;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<48;

  if (err==ZIP_OK)
    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
  x += ((ZPOS64_T)i)<<56;

  if (err==ZIP_OK)
    *pX = x;
```

```
  else
    *pX = 0;

  return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.22 static int zip64local_getShort (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* uLong * *pX*) [static]

Definition at line 382 of file zip.c.

References zip64local_getByte(), and ZIP_OK.

Referenced by LoadCentralDirectoryRecord().

```
{
    uLong x ;
    int i = 0;
    int err;

    err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x = (uLong)i;

    if (err==ZIP_OK)
        err = zip64local_getByte(pzlib_filefunc_def,filestream,&i);
    x += ((uLong)i)<<8;

    if (err==ZIP_OK)
        *pX = x;
    else
        *pX = 0;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.23 static int zip64local_putValue (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream,* ZPOS64_T *x,* int *nbByte*) [static]

Definition at line 296 of file zip.c.

References ZIP_ERRNO, ZIP_OK, and ZWRITE64.

Referenced by Write_EndOfCentralDirectoryRecord(), Write_GlobalComment(), Write_LocalFileHeader(), Write_Zip64EndOfCentralDirectoryLocator(), Write_Zip64EndOfCentralDirectoryRecord(), and zipCloseFileInZipRaw64().

```
{
    unsigned char buf[8];
    int n;
    for (n = 0; n < nbByte; n++)
    {
        buf[n] = (unsigned char)(x & 0xff);
        x >>= 8;
    }
    if (x != 0)
      {     /* data overflow - hack for ZIP64 (X Roche) */
      for (n = 0; n < nbByte; n++)
        {
          buf[n] = 0xff;
        }
      }

    if (ZWRITE64(*pzlib_filefunc_def,filestream,buf,nbByte)!=(uLong)nbByte)
        return ZIP_ERRNO;
    else
        return ZIP_OK;
}
```

Here is the caller graph for this function:

13.109.4.24 static void zip64local_putValue_inmemory (void * *dest*, ZPOS64_T *x*, int *nbByte*) [static]

Definition at line 320 of file zip.c.

Referenced by zipCloseFileInZipRaw64(), and zipOpenNewFileInZip4_64().

```
{
    unsigned char* buf=(unsigned char*)dest;
    int n;
    for (n = 0; n < nbByte; n++) {
        buf[n] = (unsigned char)(x & 0xff);
        x >>= 8;
    }

    if (x != 0)
    {     /* data overflow - hack for ZIP64 */
       for (n = 0; n < nbByte; n++)
       {
          buf[n] = 0xff;
       }
    }
}
```

Here is the caller graph for this function:

13.109.4.25 static ZPOS64_T zip64local_SearchCentralDir (const zlib_filefunc64_32_def * *pzlib_filefunc_def*, voidpf *filestream*) [static]

Definition at line 489 of file zip.c.

References ALLOC, BUFREADCOMMENT, TRYFREE, ZLIB_FILEFUNC_SEEK_END, ZLIB_FILEFUNC_SEEK_-SET, ZREAD64, ZSEEK64, and ZTELL64.

Referenced by LoadCentralDirectoryRecord().

```
{
  unsigned char* buf;
  ZPOS64_T uSizeFile;
```

```
  ZPOS64_T uBackRead;
  ZPOS64_T uMaxBack=0xffff; /* maximum size of global comment */
  ZPOS64_T uPosFound=0;

  if (ZSEEK64(*pzlib_filefunc_def,filestream,0,ZLIB_FILEFUNC_SEEK_END) != 0)
    return 0;


  uSizeFile = ZTELL64(*pzlib_filefunc_def,filestream);

  if (uMaxBack>uSizeFile)
    uMaxBack = uSizeFile;

  buf = (unsigned char*)ALLOC(BUFREADCOMMENT+4);
  if (buf==NULL)
    return 0;

  uBackRead = 4;
  while (uBackRead<uMaxBack)
  {
    uLong uReadSize;
    ZPOS64_T uReadPos ;
    int i;
    if (uBackRead+BUFREADCOMMENT>uMaxBack)
      uBackRead = uMaxBack;
    else
      uBackRead+=BUFREADCOMMENT;
    uReadPos = uSizeFile-uBackRead ;

    uReadSize = ((BUFREADCOMMENT+4) < (uSizeFile-uReadPos)) ?
      (BUFREADCOMMENT+4) : (uLong)(uSizeFile-uReadPos);
    if (ZSEEK64(*pzlib_filefunc_def,filestream,uReadPos,
  ZLIB_FILEFUNC_SEEK_SET)!=0)
      break;

    if (ZREAD64(*pzlib_filefunc_def,filestream,buf,uReadSize)!=uReadSize)
      break;

    for (i=(int)uReadSize-3; (i--)>0;)
      if (((*(buf+i))==0x50) && ((*(buf+i+1))==0x4b) &&
        ((*(buf+i+2))==0x05) && ((*(buf+i+3))==0x06))
      {
        uPosFound = uReadPos+i;
        break;
      }

    if (uPosFound!=0)
      break;
  }
  TRYFREE(buf);
  return uPosFound;
}
```

Here is the caller graph for this function:

13.109.4.26 static ZPOS64_T zip64local_SearchCentralDir64 (const zlib_filefunc64_32_def * *pzlib_filefunc_def,* voidpf *filestream*) [static]

Definition at line 551 of file zip.c.

References ALLOC, BUFREADCOMMENT, TRYFREE, zip64local_getLong(), zip64local_getLong64(), ZIP_OK, ZLIB_FILEFUNC_SEEK_END, ZLIB_FILEFUNC_SEEK_SET, ZREAD64, ZSEEK64, and ZTELL64.

Referenced by LoadCentralDirectoryRecord().

```
552 {
```

```
unsigned char* buf;
ZPOS64_T uSizeFile;
ZPOS64_T uBackRead;
ZPOS64_T uMaxBack=0xffff; /* maximum size of global comment */
ZPOS64_T uPosFound=0;
uLong uL;
ZPOS64_T relativeOffset;

if (ZSEEK64(*pzlib_filefunc_def,filestream,0,ZLIB_FILEFUNC_SEEK_END) != 0)
  return 0;

uSizeFile = ZTELL64(*pzlib_filefunc_def,filestream);

if (uMaxBack>uSizeFile)
  uMaxBack = uSizeFile;

buf = (unsigned char*)ALLOC(BUFREADCOMMENT+4);
if (buf==NULL)
  return 0;

uBackRead = 4;
while (uBackRead<uMaxBack)
{
  uLong uReadSize;
  ZPOS64_T uReadPos;
  int i;
  if (uBackRead+BUFREADCOMMENT>uMaxBack)
    uBackRead = uMaxBack;
  else
    uBackRead+=BUFREADCOMMENT;
  uReadPos = uSizeFile-uBackRead ;

  uReadSize = ((BUFREADCOMMENT+4) < (uSizeFile-uReadPos)) ?
    (BUFREADCOMMENT+4) : (uLong)(uSizeFile-uReadPos);
  if (ZSEEK64(*pzlib_filefunc_def,filestream,uReadPos,
ZLIB_FILEFUNC_SEEK_SET)!=0)
    break;

  if (ZREAD64(*pzlib_filefunc_def,filestream,buf,uReadSize)!=uReadSize)
    break;

  for (i=(int)uReadSize-3; (i--)>0;)
  {
    /* Signature "0x07064b50" Zip64 end of central directory locater */
    if (((*(buf+i))==0x50) && ((*(buf+i+1))==0x4b) && ((*(buf+i+2))==0x06) && ((*(buf+i+3))==0x07))
    {
      uPosFound = uReadPos+i;
      break;
    }
  }

    if (uPosFound!=0)
      break;
}

TRYFREE(buf);
if (uPosFound == 0)
  return 0;

/* Zip64 end of central directory locator */
if (ZSEEK64(*pzlib_filefunc_def,filestream, uPosFound,
ZLIB_FILEFUNC_SEEK_SET)!=0)
  return 0;

/* the signature, already checked */
if (zip64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
ZIP_OK)
  return 0;

/* number of the disk with the start of the zip64 end of  central directory */
if (zip64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
ZIP_OK)
  return 0;
if (uL != 0)
  return 0;

/* relative offset of the zip64 end of central directory record */
if (zip64local_getLong64(pzlib_filefunc_def,filestream,&relativeOffset)!=
ZIP_OK)
  return 0;

/* total number of disks */
if (zip64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
ZIP_OK)
  return 0;
if (uL != 1)
  return 0;
```

```
  /* Goto Zip64 end of central directory record */
  if (ZSEEK64(*pzlib_filefunc_def,filestream, relativeOffset,
  ZLIB_FILEFUNC_SEEK_SET)!=0)
    return 0;

  /* the signature */
  if (zip64local_getLong(pzlib_filefunc_def,filestream,&uL)!=
  ZIP_OK)
    return 0;

  if (uL != 0x06064b50) /* signature of 'Zip64 end of central directory' */
    return 0;

  return relativeOffset;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.27 static uLong zip64local_TmzDateToDosDate (const tm_zip * *ptm*) [static]

Definition at line 341 of file zip.c.

References tm_zip_s::tm_hour, tm_zip_s::tm_mday, tm_zip_s::tm_min, tm_zip_s::tm_mon, tm_zip_s::tm_sec, and tm_zip_s::tm_year.

Referenced by zipOpenNewFileInZip4_64().

```
{
    uLong year = (uLong)ptm->tm_year;
    if (year>=1980)
        year-=1980;
    else if (year>=80)
        year-=80;
    return
      (uLong) (((ptm->tm_mday) + (32 * (ptm->tm_mon+1)) + (512 * year)) << 16) |
        ((ptm->tm_sec/2) + (32* ptm->tm_min) + (2048 * (uLong)ptm->
  tm_hour));
}
```

Here is the caller graph for this function:

13.109.4.28 int ZEXPORT zipClearFlags (zipFile *file*, unsigned *flags*)

Definition at line 2091 of file zip.c.

References zip64_internal::flags, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, and ZIP_WRITE_DATA_DESCRIPTOR.

Referenced by QuaZipFile::open().

```
{
    zip64_internal* zi;
    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;
    zi->flags &= ~flags;
    // If the data descriptor is not written, we can't use a non-seekable output.
    if ((zi->flags & ZIP_WRITE_DATA_DESCRIPTOR) == 0) {
        zi->flags &= ~ZIP_SEQUENTIAL;
    }
    return ZIP_OK;
}
```

Here is the caller graph for this function:

13.109.4.29 int ZEXPORT zipClose (zipFile *file*, const char * *global_comment*)

Definition at line 1942 of file zip.c.

References zip64_internal::add_position_when_writting_offset, zip64_internal::central_dir, linkedlist_datablock_internal_s::data, zip64_internal::filestream, linkedlist_datablock_internal_s::filled_in_this_block, linkedlist_data_s::first_block, zip64_internal::flags, free_linkedlist(), zip64_internal::globalcomment, zip64_internal::in_opened_file_inzip, linkedlist_datablock_internal_s::next_datablock, zip64_internal::number_entry, TRYFREE, Write_EndOf-

CentralDirectoryRecord(), Write_GlobalComment(), Write_Zip64EndOfCentralDirectoryLocator(), Write_Zip64EndOfCentralDirectoryRecord(), zip64_internal::z_filefunc, ZCLOSE64, ZFAKECLOSE64, ZIP_AUTO_CLOSE, ZIP_ERRNO, ZIP_OK, ZIP_PARAMERROR, zipCloseFileInZip(), ZTELL64, and ZWRITE64.

Referenced by QuaZip::close(), and QuaZip::open().

```
{
    zip64_internal* zi;
    int err = 0;
    uLong size_centraldir = 0;
    ZPOS64_T centraldir_pos_inzip;
    ZPOS64_T pos;

    if (file == NULL)
        return ZIP_PARAMERROR;

    zi = (zip64_internal*)file;

    if (zi->in_opened_file_inzip == 1)
    {
        err = zipCloseFileInZip (file);
    }

#ifndef NO_ADDFILEINEXISTINGZIP
    if (global_comment==NULL)
        global_comment = zi->globalcomment;
#endif

    centraldir_pos_inzip = ZTELL64(zi->z_filefunc,zi->filestream);

    if (err==ZIP_OK)
    {
        linkedlist_datablock_internal* ldi = zi->central_dir.first_block;
        while (ldi!=NULL)
        {
            if ((err==ZIP_OK) && (ldi->filled_in_this_block>0))
            {
                if (ZWRITE64(zi->z_filefunc,zi->filestream, ldi->data, ldi->filled_in_this_block) != ldi->filled_in_this_block)
                    err = ZIP_ERRNO;
            }

            size_centraldir += ldi->filled_in_this_block;
            ldi = ldi->next_datablock;
        }
    }
    free_linkedlist(&(zi->central_dir));

    pos = centraldir_pos_inzip - zi->add_position_when_writting_offset;
    if(pos >= 0xffffffff || zi->number_entry > 0xFFFF)
    {
      ZPOS64_T Zip64EOCDpos = ZTELL64(zi->z_filefunc,zi->filestream);
      Write_Zip64EndOfCentralDirectoryRecord(zi, size_centraldir, centraldir_pos_inzip);

      Write_Zip64EndOfCentralDirectoryLocator(zi, Zip64EOCDpos);
    }

    if (err==ZIP_OK)
      err = Write_EndOfCentralDirectoryRecord(zi, size_centraldir, centraldir_pos_inzip);

    if(err == ZIP_OK)
      err = Write_GlobalComment(zi, global_comment);

    if ((zi->flags & ZIP_AUTO_CLOSE) != 0) {
        if (ZCLOSE64(zi->z_filefunc,zi->filestream) != 0) {
            if (err == ZIP_OK)
                err = ZIP_ERRNO;
        }
    } else {
        if (ZFAKECLOSE64(zi->z_filefunc,zi->filestream) != 0) {
            if (err == ZIP_OK)
                err = ZIP_ERRNO;
        }
    }

#ifndef NO_ADDFILEINEXISTINGZIP
    TRYFREE(zi->globalcomment);
#endif
    TRYFREE(zi);

```

```
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.30 int ZEXPORT zipCloseFileInZip (zipFile *file*)

Definition at line 1810 of file zip.c.

References zipCloseFileInZipRaw().

Referenced by QuaZipFile::close(), zipClose(), and zipOpenNewFileInZip4_64().

```
{
    return zipCloseFileInZipRaw (file,0,0);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.31 int ZEXPORT zipCloseFileInZipRaw (zipFile *file,* uLong *uncompressed_size,* uLong *crc32*)

Definition at line 1549 of file zip.c.

References zipCloseFileInZipRaw64().

Referenced by zipCloseFileInZip().

```
1550 {
1551     return zipCloseFileInZipRaw64 (file, uncompressed_size, crc32);
1552 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.32 int ZEXPORT zipCloseFileInZipRaw64 (zipFile *file*, ZPOS64_T *uncompressed_size*, uLong *crc32*)

Definition at line 1554 of file zip.c.

References add_data_in_datablock(), curfile64_info::buffered_data, zip64_internal::central_dir, curfile64_info::central_header, zip64_internal::ci, curfile64_info::crc32, curfile64_info::crypt_header_size, DESCRIPTORHEADERMAGIC, zip64_internal::filestream, curfile64_info::flag, zip64_internal::flags, zip64_internal::in_opened_file_inzip, curfile64_info::method, zip64_internal::number_entry, curfile64_info::pos_in_buffered_data, curfile64_info::pos_local_header, curfile64_info::pos_zip64extrainfo, curfile64_info::raw, curfile64_info::size_centralExtra, curfile64_info::size_centralExtraFree, curfile64_info::size_centralheader, curfile64_info::stream, curfile64_info::stream_initialised, curfile64_info::totalCompressedData, curfile64_info::totalUncompressedData, Z_BUFSIZE, Z_BZIP2ED, zip64_internal::z_filefunc, curfile64_info::zip64, zip64FlushWriteBuffer(), zip64local_putValue(), zip64local_putValue_inmemory(), ZIP_BADZIPFILE, ZIP_ERRNO, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, ZLIB_FILEFUNC_SEEK_SET, ZSEEK64, and ZTELL64.

Referenced by QuaZipFile::close(), and zipCloseFileInZipRaw().

```
{
    zip64_internal* zi;
    ZPOS64_T compressed_size;
    uLong invalidValue = 0xffffffff;
    short datasize = 0;
    int err=ZIP_OK;

    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;

    if (zi->in_opened_file_inzip == 0)
        return ZIP_PARAMERROR;
    zi->ci.stream.avail_in = 0;

    if ((zi->ci.method == Z_DEFLATED) && (!zi->ci.raw))
                {
                        while (err==ZIP_OK)
                        {
                                uLong uTotalOutBefore;
                                if (zi->ci.stream.avail_out == 0)
                                {
                                        if (zip64FlushWriteBuffer(zi) == ZIP_ERRNO)
                                                err = ZIP_ERRNO;
                                        zi->ci.stream.avail_out = (uInt)Z_BUFSIZE;
                                        zi->ci.stream.next_out = zi->ci.buffered_data;
                                }
                                uTotalOutBefore = zi->ci.stream.total_out;
                                err=deflate(&zi->ci.stream,  Z_FINISH);
                                zi->ci.pos_in_buffered_data += (uInt)(zi->ci.stream.total_out - uTotalOutBefore) ;
                        }
                }
    else if ((zi->ci.method == Z_BZIP2ED) && (!zi->ci.raw))
    {
#ifdef HAVE_BZIP2
      err = BZ_FINISH_OK;
      while (err==BZ_FINISH_OK)
      {
        uLong uTotalOutBefore;
        if (zi->ci.bstream.avail_out == 0)
        {
          if (zip64FlushWriteBuffer(zi) == ZIP_ERRNO)
            err = ZIP_ERRNO;
          zi->ci.bstream.avail_out = (uInt)Z_BUFSIZE;
          zi->ci.bstream.next_out = (char*)zi->ci.buffered_data;
        }
        uTotalOutBefore = zi->ci.bstream.total_out_lo32;
        err=BZ2_bzCompress(&zi->ci.bstream,  BZ_FINISH);
        if(err == BZ_STREAM_END)
          err = Z_STREAM_END;

        zi->ci.pos_in_buffered_data += (uInt)(zi->ci.bstream.total_out_lo32 - uTotalOutBefore);
      }

      if(err == BZ_FINISH_OK)
        err = ZIP_OK;
#endif
    }

```

```
    if (err==Z_STREAM_END)
        err=ZIP_OK; /* this is normal */

    if ((zi->ci.pos_in_buffered_data>0) && (err==ZIP_OK))
                {
        if (zip64FlushWriteBuffer(zi)==ZIP_ERRNO)
            err = ZIP_ERRNO;
                }

    if ((zi->ci.method == Z_DEFLATED) && (!zi->ci.raw))
    {
        int tmp_err = deflateEnd(&zi->ci.stream);
        if (err == ZIP_OK)
            err = tmp_err;
        zi->ci.stream_initialised = 0;
    }
#ifdef HAVE_BZIP2
    else if((zi->ci.method == Z_BZIP2ED) && (!zi->ci.raw))
    {
      int tmperr = BZ2_bzCompressEnd(&zi->ci.bstream);
                        if (err==ZIP_OK)
                                err = tmperr;
                        zi->ci.stream_initialised = 0;
    }
#endif

    if (!zi->ci.raw)
    {
        crc32 = (uLong)zi->ci.crc32;
        uncompressed_size = zi->ci.totalUncompressedData;
    }
    compressed_size = zi->ci.totalCompressedData;

#    ifndef NOCRYPT
    compressed_size += zi->ci.crypt_header_size;
#    endif

    /* update Current Item crc and sizes, */
    if(compressed_size >= 0xffffffff || uncompressed_size >= 0xffffffff || zi->ci.pos_local_header >= 0xffffffff)
    {
      /*version Made by*/
      zip64local_putValue_inmemory(zi->ci.central_header+4,(uLong)45,2);
      /*version needed*/
      zip64local_putValue_inmemory(zi->ci.central_header+6,(uLong)45,2);

    }

    zip64local_putValue_inmemory(zi->ci.central_header+16,crc32,4); /*crc*/


    if(compressed_size >= 0xffffffff)
      zip64local_putValue_inmemory(zi->ci.central_header+20, invalidValue,4); /*compr size*/
    else
      zip64local_putValue_inmemory(zi->ci.central_header+20, compressed_size,4); /*compr size*/

    /* set internal file attributes field */
    if (zi->ci.stream.data_type == Z_ASCII)
        zip64local_putValue_inmemory(zi->ci.central_header+36,(uLong)Z_ASCII,2);

    if(uncompressed_size >= 0xffffffff)
      zip64local_putValue_inmemory(zi->ci.central_header+24, invalidValue,4); /*uncompr size*/
    else
      zip64local_putValue_inmemory(zi->ci.central_header+24, uncompressed_size,4); /*uncompr size*/

    /* Add ZIP64 extra info field for uncompressed size */
    if(uncompressed_size >= 0xffffffff)
      datasize += 8;

    /* Add ZIP64 extra info field for compressed size */
    if(compressed_size >= 0xffffffff)
      datasize += 8;

    /* Add ZIP64 extra info field for relative offset to local file header of current file */
    if(zi->ci.pos_local_header >= 0xffffffff)
      datasize += 8;

    if(datasize > 0)
    {
```

```
      char* p = NULL;

      if((uLong)(datasize + 4) > zi->ci.size_centralExtraFree)
      {
        /* we can not write more data to the buffer that we have room for. */
        return ZIP_BADZIPFILE;
      }

      p = zi->ci.central_header + zi->ci.size_centralheader;

      /* Add Extra Information Header for 'ZIP64 information' */
      zip64local_putValue_inmemory(p, 0x0001, 2); /* HeaderID */
      p += 2;
      zip64local_putValue_inmemory(p, datasize, 2); /* DataSize */
      p += 2;

      if(uncompressed_size >= 0xffffffff)
      {
        zip64local_putValue_inmemory(p, uncompressed_size, 8);
        p += 8;
      }

      if(compressed_size >= 0xffffffff)
      {
        zip64local_putValue_inmemory(p, compressed_size, 8);
        p += 8;
      }

      if(zi->ci.pos_local_header >= 0xffffffff)
      {
        zip64local_putValue_inmemory(p, zi->ci.pos_local_header, 8);
        p += 8;
      }

      /* Update how much extra free space we got in the memory buffer */
      /* and increase the centralheader size so the new ZIP64 fields are included */
      /* ( 4 below is the size of HeaderID and DataSize field ) */
      zi->ci.size_centralExtraFree -= datasize + 4;
      zi->ci.size_centralheader += datasize + 4;

      /* Update the extra info size field */
      zi->ci.size_centralExtra += datasize + 4;
      zip64local_putValue_inmemory(zi->ci.central_header+30,(uLong)zi->ci.size_centralExtra,2);
    }

    if (err==ZIP_OK)
        err = add_data_in_datablock(&zi->central_dir, zi->ci.central_header, (uLong)zi->ci.size_centralheader);

    free(zi->ci.central_header);

    if (err==ZIP_OK)
    {
        if ((zi->flags & ZIP_SEQUENTIAL) == 0) {
            /* Update the LocalFileHeader with the new values. */

            ZPOS64_T cur_pos_inzip = ZTELL64(zi->z_filefunc,zi->filestream);

            if (ZSEEK64(zi->z_filefunc,zi->filestream, zi->ci.pos_local_header + 14,ZLIB_FILEFUNC_SEEK_SET)!=0)
                err = ZIP_ERRNO;

            if (err==ZIP_OK)
                err = zip64local_putValue(&zi->z_filefunc,zi->filestream,crc32,4); /* crc 32, unknown */

            if(uncompressed_size >= 0xffffffff || compressed_size >= 0xffffffff)
            {
                if(zi->ci.pos_zip64extrainfo > 0)
                {
                    /* Update the size in the ZIP64 extended field. */
                    if (ZSEEK64(zi->z_filefunc,zi->filestream, zi->ci.pos_zip64extrainfo + 4,ZLIB_FILEFUNC_SEEK_SET)!=0)
                        err = ZIP_ERRNO;

                    if (err==ZIP_OK) /* compressed size, unknown */
                        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, uncompressed_size, 8);

                    if (err==ZIP_OK) /* uncompressed size, unknown */
                        err = zip64local_putValue(&zi->z_filefunc, zi->filestream, compressed_size, 8);
                }
            }
```

```
            else
            {
                if (err==ZIP_OK) /* compressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,compressed_size,4);

                if (err==ZIP_OK) /* uncompressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,uncompressed_size,4);
            }

            if (ZSEEK64(zi->z_filefunc,zi->filestream, cur_pos_inzip, ZLIB_FILEFUNC_SEEK_SET)!=0)
                err = ZIP_ERRNO;
        }

        if ((zi->ci.flag & 8) != 0) {
            /* Write local Descriptor after file data */
            if (err==ZIP_OK)
                err = zip64local_putValue(&zi->z_filefunc,zi->filestream,(uLong)DESCRIPTORHEADERMAGIC,4);
            if (err==ZIP_OK)
                err = zip64local_putValue(&zi->z_filefunc,zi->filestream,crc32,4); /* crc 32, unknown */
            if (zi->ci.zip64) {
                if (err==ZIP_OK) /* compressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,compressed_size,8);

                if (err==ZIP_OK) /* uncompressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,uncompressed_size,8);
            } else {
                if (err==ZIP_OK) /* compressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,compressed_size,4);
                if (err==ZIP_OK) /* uncompressed size, unknown */
                    err = zip64local_putValue(&zi->z_filefunc,zi->filestream,uncompressed_size,4);
            }
        }
    }

    zi->number_entry ++;
    zi->in_opened_file_inzip = 0;

    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.33 zipFile ZEXPORT zipOpen (voidpf *file*, int *append*)

Definition at line 967 of file zip.c.

References ZIP_DEFAULT_FLAGS, and zipOpen3().

```
968 {
969     return zipOpen3(file,append,NULL,NULL, ZIP_DEFAULT_FLAGS);
970 }
```

Here is the call graph for this function:

13.109.4.34 zipFile ZEXPORT zipOpen2 (voidpf *file*, int *append*, zipcharpc * *globalcomment*, zlib_filefunc_def * *pzlib_filefunc32_def*)

Definition at line 939 of file zip.c.

References fill_zlib_filefunc64_32_def_from_filefunc32(), ZIP_DEFAULT_FLAGS, and zipOpen3().

Referenced by QuaZip::open().

```
{
    if (pzlib_filefunc32_def != NULL)
    {
        zlib_filefunc64_32_def zlib_filefunc64_32_def_fill;
        fill_zlib_filefunc64_32_def_from_filefunc32(&zlib_filefunc64_32_def_fill,pzlib_filefunc32_def);
        return zipOpen3(file, append, globalcomment, &zlib_filefunc64_32_def_fill, ZIP_DEFAULT_FLAGS);
    }
    else
        return zipOpen3(file, append, globalcomment, NULL, ZIP_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.35 zipFile ZEXPORT zipOpen2_64 (voidpf *file*, int *append*, zipcharpc * *globalcomment*, zlib_filefunc64_def * *pzlib_filefunc_def*)

Definition at line 951 of file zip.c.

References zlib_filefunc64_32_def_s::zfile_func64, ZIP_DEFAULT_FLAGS, zipOpen3(), zlib_filefunc64_32_def_s::zseek32_file, and zlib_filefunc64_32_def_s::ztell32_file.

```
{
    if (pzlib_filefunc_def != NULL)
    {
```

```
        zlib_filefunc64_32_def zlib_filefunc64_32_def_fill;
        zlib_filefunc64_32_def_fill.zfile_func64 = *pzlib_filefunc_def;
        zlib_filefunc64_32_def_fill.ztell32_file = NULL;
        zlib_filefunc64_32_def_fill.zseek32_file = NULL;
        return zipOpen3(file, append, globalcomment, &zlib_filefunc64_32_def_fill,
    ZIP_DEFAULT_FLAGS);
    }
    else
        return zipOpen3(file, append, globalcomment, NULL,
    ZIP_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

13.109.4.36 zipFile ZEXPORT zipOpen3 (voidpf *file*, int *append*, zipcharpc * *globalcomment*, zlib_filefunc64_32_def * *pzlib_filefunc64_32_def*, unsigned *flags*)

Definition at line 862 of file zip.c.

References zip64_internal::add_position_when_writting_offset, ALLOC, APPEND_STATUS_ADDINZIP, APPEND_STATUS_CREATE, APPEND_STATUS_CREATEAFTER, zip64_internal::begin_pos, zip64_internal::central_dir, zip64_internal::ci, zip64_internal::filestream, fill_qiodevice64_filefunc(), zip64_internal::flags, zip64_internal::globalcomment, zip64_internal::in_opened_file_inzip, init_linkedlist(), LoadCentralDirectoryRecord(), zip64_internal::number_entry, SEEK_END, curfile64_info::stream_initialised, TRYFREE, zip64_internal::z_filefunc, ZCLOSE64, ZFAKECLOSE64, zlib_filefunc64_32_def_s::zfile_func64, ZIP_AUTO_CLOSE, ZIP_OK, ZLIB_FILEFUNC_MODE_CREATE, ZLIB_FILEFUNC_MODE_EXISTING, ZLIB_FILEFUNC_MODE_READ, ZLIB_FILEFUNC_MODE_WRITE, ZOPEN64, zlib_filefunc64_32_def_s::zseek32_file, ZSEEK64, zlib_filefunc64_32_def_s::ztell32_file, and ZTELL64.

Referenced by QuaZip::open(), zipOpen(), zipOpen2(), zipOpen2_64(), and zipOpen64().

```
{
    zip64_internal ziinit;
    zip64_internal* zi;
    int err=ZIP_OK;

    ziinit.flags = flags;
    ziinit.z_filefunc.zseek32_file = NULL;
    ziinit.z_filefunc.ztell32_file = NULL;
    if (pzlib_filefunc64_32_def==NULL)
        fill_qiodevice64_filefunc(&ziinit.z_filefunc.
    zfile_func64);
```

```
    else
        ziinit.z_filefunc = *pzlib_filefunc64_32_def;

    ziinit.filestream = ZOPEN64(ziinit.z_filefunc,
                    file,
                    (append == APPEND_STATUS_CREATE) ?
                    (ZLIB_FILEFUNC_MODE_READ | ZLIB_FILEFUNC_MODE_WRITE | ZLIB_FILEFUNC_MODE_CREATE) :
                      (ZLIB_FILEFUNC_MODE_READ | ZLIB_FILEFUNC_MODE_WRITE | ZLIB_FILEFUNC_MODE_EXISTING));

    if (ziinit.filestream == NULL)
        return NULL;

    if (append == APPEND_STATUS_CREATEAFTER)
        ZSEEK64(ziinit.z_filefunc,ziinit.filestream,0,SEEK_END);

    ziinit.begin_pos = ZTELL64(ziinit.z_filefunc,ziinit.filestream);
    ziinit.in_opened_file_inzip = 0;
    ziinit.ci.stream_initialised = 0;
    ziinit.number_entry = 0;
    ziinit.add_position_when_writting_offset = 0;
    init_linkedlist(&(ziinit.central_dir));



    zi = (zip64_internal*)ALLOC(sizeof(zip64_internal));
    if (zi==NULL)
    {
        if ((ziinit.flags & ZIP_AUTO_CLOSE) != 0) {
            ZCLOSE64(ziinit.z_filefunc,ziinit.filestream);
        } else {
            ZFAKECLOSE64(ziinit.z_filefunc,ziinit.filestream);
        }
        return NULL;
    }

    /* now we add file in a zipfile */
#    ifndef NO_ADDFILEINEXISTINGZIP
    ziinit.globalcomment = NULL;
    if (append == APPEND_STATUS_ADDINZIP)
    {
      /* Read and Cache Central Directory Records */
      err = LoadCentralDirectoryRecord(&ziinit);
    }

    if (globalcomment)
    {
      *globalcomment = ziinit.globalcomment;
    }
#    endif /* !NO_ADDFILEINEXISTINGZIP*/

    if (err != ZIP_OK)
    {
#    ifndef NO_ADDFILEINEXISTINGZIP
        TRYFREE(ziinit.globalcomment);
#    endif /* !NO_ADDFILEINEXISTINGZIP*/
        TRYFREE(zi);
        return NULL;
    }
    else
    {
        *zi = ziinit;
        return (zipFile)zi;
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.37 zipFile ZEXPORT zipOpen64 (voidpf *file*, int *append*)

Definition at line 972 of file zip.c.

References ZIP_DEFAULT_FLAGS, and zipOpen3().

```
{
    return zipOpen3(file,append,NULL,NULL, ZIP_DEFAULT_FLAGS);
}
```

Here is the call graph for this function:

13.109.4.38 int ZEXPORT zipOpenNewFileInZip (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*)

Definition at line 1390 of file zip.c.

References DEF_MEM_LEVEL, VERSIONMADEBY, and zipOpenNewFileInZip4_64().

```
1394 {
1395     return zipOpenNewFileInZip4_64 (file, filename, zipfi,
1396                                     extrafield_local, size_extrafield_local,
1397                                     extrafield_global, size_extrafield_global,
1398                                     comment, method, level, 0,
1399                                     -MAX_WBITS, DEF_MEM_LEVEL, Z_DEFAULT_STRATEGY,
1400                                     NULL, 0, VERSIONMADEBY, 0, 0);
1401 }
```

Here is the call graph for this function:

13.109.4.39 int ZEXPORT zipOpenNewFileInZip2 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*)

Definition at line 1351 of file zip.c.

References DEF_MEM_LEVEL, VERSIONMADEBY, and zipOpenNewFileInZip4_64().

```
{
    return zipOpenNewFileInZip4_64 (file, filename, zipfi,
                                    extrafield_local, size_extrafield_local,
                                    extrafield_global, size_extrafield_global,
                                    comment, method, level, raw,
                                    -MAX_WBITS, DEF_MEM_LEVEL, Z_DEFAULT_STRATEGY,
                                    NULL, 0, VERSIONMADEBY, 0, 0);
}
```

Here is the call graph for this function:

13.109.4.40 int ZEXPORT zipOpenNewFileInZip2_64 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*, int *zip64*)

Definition at line 1364 of file zip.c.

References DEF_MEM_LEVEL, VERSIONMADEBY, and zipOpenNewFileInZip4_64().

```
{
    return zipOpenNewFileInZip4_64 (file, filename, zipfi,
                                    extrafield_local, size_extrafield_local,
                                    extrafield_global, size_extrafield_global,
                                    comment, method, level, raw,
                                    -MAX_WBITS, DEF_MEM_LEVEL, Z_DEFAULT_STRATEGY,
                                    NULL, 0, VERSIONMADEBY, 0, zip64);
}
```

Here is the call graph for this function:

13.109.4.41 int ZEXPORT zipOpenNewFileInZip3 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*, int *windowBits*, int *memLevel*, int *strategy*, const char * *password*, uLong *crcForCrypting*)

Definition at line 1321 of file zip.c.

References VERSIONMADEBY, and zipOpenNewFileInZip4_64().

```
{
    return zipOpenNewFileInZip4_64 (file, filename, zipfi,
                                    extrafield_local, size_extrafield_local,
                                    extrafield_global, size_extrafield_global,
                                    comment, method, level, raw,
                                    windowBits, memLevel, strategy,
                                    password, crcForCrypting, VERSIONMADEBY, 0, 0);
}
```

Here is the call graph for this function:

13.109.4.42 int ZEXPORT zipOpenNewFileInZip3_64 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*, int *windowBits*, int *memLevel*, int *strategy*, const char * *password*, uLong *crcForCrypting*, int *zip64*)

Definition at line 1336 of file zip.c.

References VERSIONMADEBY, and zipOpenNewFileInZip4_64().

Referenced by QuaZipFile::open().

```
1342 {
1343     return zipOpenNewFileInZip4_64 (file, filename, zipfi,
1344                                 extrafield_local, size_extrafield_local,
1345                                 extrafield_global, size_extrafield_global,
1346                                 comment, method, level, raw,
1347                                 windowBits, memLevel, strategy,
1348                                 password, crcForCrypting, VERSIONMADEBY, 0, zip64);
1349 }
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.43 int ZEXPORT zipOpenNewFileInZip4 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*, int *windowBits*, int *memLevel*, int *strategy*, const char * *password*, uLong *crcForCrypting*, uLong *versionMadeBy*, uLong *flagBase*)

Definition at line 1305 of file zip.c.

References zipOpenNewFileInZip4_64().

```
{
    return zipOpenNewFileInZip4_64 (file, filename, zipfi,
                                    extrafield_local, size_extrafield_local,
                                    extrafield_global, size_extrafield_global,
                                    comment, method, level, raw,
                                    windowBits, memLevel, strategy,
                                    password, crcForCrypting, versionMadeBy, flagBase, 0);
}
```

Here is the call graph for this function:

13.109.4.44 int ZEXPORT zipOpenNewFileInZip4_64 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *raw*, int *windowBits*, int *memLevel*, int *strategy*, const char * *password*, uLong *crcForCrypting*, uLong *versionMadeBy*, uLong *flagBase*, int *zip64*)

Definition at line 1077 of file zip.c.

References zip64_internal::add_position_when_writting_offset, ALLOC, curfile64_info::buffered_data, curfile64_info::central_header, CENTRALHEADERMAGIC, zip64_internal::ci, curfile64_info::crc32, curfile64_info::crypt_header_size, zip_fileinfo::dosDate, curfile64_info::dosDate, curfile64_info::encrypt, zip_fileinfo::external_fa, zip64_internal::filestream, curfile64_info::flag, zip64_internal::flags, zip64_internal::in_opened_file_inzip, zip_fileinfo::internal_fa, curfile64_info::keys, curfile64_info::method, curfile64_info::pcrc_32_tab, curfile64_info::pos_in_buffered_data, curfile64_info::pos_local_header, curfile64_info::pos_zip64extrainfo, curfile64_info::raw, curfile64_info::size_centralExtra, curfile64_info::size_centralExtraFree, curfile64_info::size_centralheader, SIZECENTRALHEADER, curfile64_info::stream, curfile64_info::stream_initialised, zip_fileinfo::tmz_date, curfile64_info::totalCompressedData, curfile64_info::totalUncompressedData, Write_LocalFileHeader(), Z_BUFSIZE, Z_BZIP2ED, zip64_internal::z_filefunc, curfile64_info::zip64, zip64local_putValue_inmemory(), zip64local_TmzDateToDosDate(), ZIP_ERRNO, ZIP_INTERNALERROR, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, ZIP_WRITE_DATA_DESCRIPTOR, zipCloseFileInZip(), ZTELL64, and ZWRITE64.

Referenced by zipOpenNewFileInZip(), zipOpenNewFileInZip2(), zipOpenNewFileInZip2_64(), zipOpenNewFileInZip3(), zipOpenNewFileInZip3_64(), zipOpenNewFileInZip4(), and zipOpenNewFileInZip64().

```
{
    zip64_internal* zi;
    uInt size_filename;
    uInt size_comment;
    uInt i;
    int err = ZIP_OK;
    uLong version_to_extract;

#    ifdef NOCRYPT
    if (password != NULL)
        return ZIP_PARAMERROR;
#    endif

    if (file == NULL)
        return ZIP_PARAMERROR;

#ifdef HAVE_BZIP2
    if ((method!=0) && (method!=Z_DEFLATED) && (method!=Z_BZIP2ED))
      return ZIP_PARAMERROR;
#else
    if ((method!=0) && (method!=Z_DEFLATED))
      return ZIP_PARAMERROR;
#endif
```

```

    zi = (zip64_internal*)file;

    if (zi->in_opened_file_inzip == 1)
    {
        err = zipCloseFileInZip (file);
        if (err != ZIP_OK)
            return err;
    }

    if (method == 0
            && (level == 0 || (zi->flags & ZIP_WRITE_DATA_DESCRIPTOR) == 0)
            && (zi->flags & ZIP_SEQUENTIAL) == 0)
    {
        version_to_extract = 10;
    }
    else
    {
        version_to_extract = 20;
    }

    if (filename==NULL)
        filename="-";

    if (comment==NULL)
        size_comment = 0;
    else
        size_comment = (uInt)strlen(comment);

    size_filename = (uInt)strlen(filename);

    if (zipfi == NULL)
        zi->ci.dosDate = 0;
    else
    {
        if (zipfi->dosDate != 0)
            zi->ci.dosDate = zipfi->dosDate;
        else
          zi->ci.dosDate = zip64local_TmzDateToDosDate(&zipfi->tmz_date);
    }

    zi->ci.flag = flagBase;
    if ((level==8) || (level==9))
      zi->ci.flag |= 2;
    if (level==2)
      zi->ci.flag |= 4;
    if (level==1)
      zi->ci.flag |= 6;
    if (password != NULL)
      zi->ci.flag |= 1;
    if (version_to_extract >= 20
            && ((zi->flags & ZIP_WRITE_DATA_DESCRIPTOR) != 0
                || (zi->flags & ZIP_SEQUENTIAL) != 0))
      zi->ci.flag |= 8;

    zi->ci.crc32 = 0;
    zi->ci.method = method;
    zi->ci.encrypt = 0;
    zi->ci.stream_initialised = 0;
    zi->ci.pos_in_buffered_data = 0;
    zi->ci.raw = raw;
    zi->ci.pos_local_header = ZTELL64(zi->z_filefunc,zi->filestream);

    zi->ci.size_centralheader = SIZECENTRALHEADER + size_filename + size_extrafield_global + size_comment;
    zi->ci.size_centralExtraFree = 32; /* Extra space we have reserved in case we need to add ZIP64 extra info data */

    zi->ci.central_header = (char*)ALLOC((uInt)zi->ci.size_centralheader + zi->ci.size_centralExtraFree);

    zi->ci.size_centralExtra = size_extrafield_global;
    zip64local_putValue_inmemory(zi->ci.central_header,(uLong)CENTRALHEADERMAGIC,4);
    /* version info */
    zip64local_putValue_inmemory(zi->ci.central_header+4,(uLong)versionMadeBy,2);
    zip64local_putValue_inmemory(zi->ci.central_header+6,(uLong)version_to_extract,2);
    zip64local_putValue_inmemory(zi->ci.central_header+8,(uLong)zi->ci.flag,2);
    zip64local_putValue_inmemory(zi->ci.central_header+10,(uLong)zi->ci.method,2);
    zip64local_putValue_inmemory(zi->ci.central_header+12,(uLong)zi->ci.dosDate,4);
```

```
    zip64local_putValue_inmemory(zi->ci.central_header+16,(uLong)0,4); /*crc*/
    zip64local_putValue_inmemory(zi->ci.central_header+20,(uLong)0,4); /*compr size*/
    zip64local_putValue_inmemory(zi->ci.central_header+24,(uLong)0,4); /*uncompr size*/
    zip64local_putValue_inmemory(zi->ci.central_header+28,(uLong)size_filename,2);
    zip64local_putValue_inmemory(zi->ci.central_header+30,(uLong)size_extrafield_global,2);
    zip64local_putValue_inmemory(zi->ci.central_header+32,(uLong)size_comment,2);
    zip64local_putValue_inmemory(zi->ci.central_header+34,(uLong)0,2); /*disk nm start*/

    if (zipfi==NULL)
        zip64local_putValue_inmemory(zi->ci.central_header+36,(uLong)0,2);
    else
        zip64local_putValue_inmemory(zi->ci.central_header+36,(uLong)zipfi->internal_fa,2);

    if (zipfi==NULL)
        zip64local_putValue_inmemory(zi->ci.central_header+38,(uLong)0,4);
    else
        zip64local_putValue_inmemory(zi->ci.central_header+38,(uLong)zipfi->external_fa,4);

    if(zi->ci.pos_local_header >= 0xffffffff)
      zip64local_putValue_inmemory(zi->ci.central_header+42,(uLong)0xffffffff,4);
    else
      zip64local_putValue_inmemory(zi->ci.central_header+42,(uLong)zi->ci.pos_local_header - zi->add_position_when_writting_offset,4);

    for (i=0;i<size_filename;i++)
        *(zi->ci.central_header+SIZECENTRALHEADER+i) = *(filename+i);

    for (i=0;i<size_extrafield_global;i++)
        *(zi->ci.central_header+SIZECENTRALHEADER+size_filename+i) =
              *(((const char*)extrafield_global)+i);

    for (i=0;i<size_comment;i++)
        *(zi->ci.central_header+SIZECENTRALHEADER+size_filename+
              size_extrafield_global+i) = *(comment+i);
    if (zi->ci.central_header == NULL)
        return ZIP_INTERNALERROR;

    zi->ci.zip64 = zip64;
    zi->ci.totalCompressedData = 0;
    zi->ci.totalUncompressedData = 0;
    zi->ci.pos_zip64extrainfo = 0;

    err = Write_LocalFileHeader(zi, filename, size_extrafield_local,
                                extrafield_local, version_to_extract);

#ifdef HAVE_BZIP2
    zi->ci.bstream.avail_in = (uInt)0;
    zi->ci.bstream.avail_out = (uInt)Z_BUFSIZE;
    zi->ci.bstream.next_out = (char*)zi->ci.buffered_data;
    zi->ci.bstream.total_in_hi32 = 0;
    zi->ci.bstream.total_in_lo32 = 0;
    zi->ci.bstream.total_out_hi32 = 0;
    zi->ci.bstream.total_out_lo32 = 0;
#endif

    zi->ci.stream.avail_in = (uInt)0;
    zi->ci.stream.avail_out = (uInt)Z_BUFSIZE;
    zi->ci.stream.next_out = zi->ci.buffered_data;
    zi->ci.stream.total_in = 0;
    zi->ci.stream.total_out = 0;
    zi->ci.stream.data_type = Z_BINARY;

#ifdef HAVE_BZIP2
    if ((err==ZIP_OK) && (zi->ci.method == Z_DEFLATED || zi->ci.method == Z_BZIP2ED) && (!zi->ci.raw))
#else
    if ((err==ZIP_OK) && (zi->ci.method == Z_DEFLATED) && (!zi->ci.raw))
#endif
    {
        if(zi->ci.method == Z_DEFLATED)
        {
          zi->ci.stream.zalloc = (alloc_func)0;
          zi->ci.stream.zfree = (free_func)0;
```

```
            zi->ci.stream.opaque = (voidpf)0;

            if (windowBits>0)
                windowBits = -windowBits;

            err = deflateInit2(&zi->ci.stream, level, Z_DEFLATED, windowBits, memLevel, strategy);

            if (err==Z_OK)
                zi->ci.stream_initialised = Z_DEFLATED;
        }
        else if(zi->ci.method == Z_BZIP2ED)
        {
#ifdef HAVE_BZIP2
            /* Init BZip stuff here */
            zi->ci.bstream.bzalloc = 0;
            zi->ci.bstream.bzfree = 0;
            zi->ci.bstream.opaque = (voidpf)0;

            err = BZ2_bzCompressInit(&zi->ci.bstream, level, 0,35);
            if(err == BZ_OK)
              zi->ci.stream_initialised = Z_BZIP2ED;
#endif
        }

    }

#    ifndef NOCRYPT
    zi->ci.crypt_header_size = 0;
    if ((err==Z_OK) && (password != NULL))
    {
        unsigned char bufHead[RAND_HEAD_LEN];
        unsigned int sizeHead;
        zi->ci.encrypt = 1;
        zi->ci.pcrc_32_tab = get_crc_table();
        /*init_keys(password,zi->ci.keys,zi->ci.pcrc_32_tab);*/
        if (crcForCrypting == 0) {
            crcForCrypting = (uLong)zi->ci.dosDate << 16; /* ATTANTION! Without this row, you don't unpack your password protected archive in other app. */
        }
        sizeHead=crypthead(password,bufHead,RAND_HEAD_LEN,zi->ci.keys,zi->ci.pcrc_32_tab,crcForCrypting);
        zi->ci.crypt_header_size = sizeHead;

        if (ZWRITE64(zi->z_filefunc,zi->filestream,bufHead,sizeHead) != sizeHead)
                err = ZIP_ERRNO;
    }
#    endif

    if (err==Z_OK)
        zi->in_opened_file_inzip = 1;
    return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.4.45 int ZEXPORT zipOpenNewFileInZip64 (zipFile *file*, const char * *filename*, const zip_fileinfo * *zipfi*, const void * *extrafield_local*, uInt *size_extrafield_local*, const void * *extrafield_global*, uInt *size_extrafield_global*, const char * *comment*, int *method*, int *level*, int *zip64*)

Definition at line 1377 of file zip.c.

References DEF_MEM_LEVEL, VERSIONMADEBY, and zipOpenNewFileInZip4_64().

```
{
    return zipOpenNewFileInZip4_64 (file, filename, zipfi,
                                    extrafield_local, size_extrafield_local,
                                    extrafield_global, size_extrafield_global,
                                    comment, method, level, 0,
                                    -MAX_WBITS, DEF_MEM_LEVEL, Z_DEFAULT_STRATEGY,
                                    NULL, 0, VERSIONMADEBY, 0, zip64);
}
```

Here is the call graph for this function:

13.109.4.46 int ZEXPORT zipRemoveExtraInfoBlock (char * *pData*, int * *dataLen*, short *sHeader*)

Definition at line 2019 of file zip.c.

References ALLOC, TRYFREE, ZIP_ERRNO, ZIP_OK, and ZIP_PARAMERROR.

```
{
  char* p = pData;
  int size = 0;
```

```
  char* pNewHeader;
  char* pTmp;
  short header;
  short dataSize;

  int retVal = ZIP_OK;

  if(pData == NULL || *dataLen < 4)
    return ZIP_PARAMERROR;

  pNewHeader = (char*)ALLOC(*dataLen);
  pTmp = pNewHeader;

  while(p < (pData + *dataLen))
  {
    header = *(short*)p;
    dataSize = *(((short*)p)+1);

    if( header == sHeader ) /* Header found. */
    {
      p += dataSize + 4; /* skip it. do not copy to temp buffer */
    }
    else
    {
      /* Extra Info block should not be removed, So copy it to the temp buffer. */
      memcpy(pTmp, p, dataSize + 4);
      p += dataSize + 4;
      size += dataSize + 4;
    }

  }

  if(size < *dataLen)
  {
    /* clean old extra info block. */
    memset(pData,0, *dataLen);

    /* copy the new extra info block over the old */
    if(size > 0)
      memcpy(pData, pNewHeader, size);

    /* set the new extra info size */
    *dataLen = size;

    retVal = ZIP_OK;
  }
  else
    retVal = ZIP_ERRNO;

  TRYFREE(pNewHeader);

  return retVal;
}
```

13.109.4.47 int ZEXPORT zipSetFlags (zipFile *file*, unsigned *flags*)

Definition at line 2077 of file zip.c.

References zip64_internal::flags, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, and ZIP_WRITE_DATA_DESCRIPTOR.

Referenced by QuaZip::open(), and QuaZipFile::open().

```
{
    zip64_internal* zi;
    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;
    zi->flags |= flags;
    // If the output is non-seekable, the data descriptor is needed.
    if ((zi->flags & ZIP_SEQUENTIAL) != 0) {
        zi->flags |= ZIP_WRITE_DATA_DESCRIPTOR;
    }
    return ZIP_OK;
}
```

Here is the caller graph for this function:

13.109.4.48 int ZEXPORT zipWriteInFileInZip (zipFile *file*, const void * *buf*, unsigned int *len*)

Definition at line 1442 of file zip.c.

References curfile64_info::buffered_data, zip64_internal::ci, curfile64_info::crc32, zip64_internal::in_opened_file_inzip, curfile64_info::method, curfile64_info::pos_in_buffered_data, curfile64_info::raw, curfile64_info::stream, Z_BUFSIZE, Z_BZIP2ED, zip64FlushWriteBuffer(), ZIP_ERRNO, ZIP_OK, and ZIP_PARAMERROR.

Referenced by QuaZipFile::writeData().

```
{
    zip64_internal* zi;
    int err=ZIP_OK;

    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;

    if (zi->in_opened_file_inzip == 0)
        return ZIP_PARAMERROR;

    zi->ci.crc32 = crc32(zi->ci.crc32,buf,(uInt)len);

#ifdef HAVE_BZIP2
    if(zi->ci.method == Z_BZIP2ED && (!zi->ci.raw))
    {
      zi->ci.bstream.next_in = (void*)buf;
      zi->ci.bstream.avail_in = len;
      err = BZ_RUN_OK;

      while ((err==BZ_RUN_OK) && (zi->ci.bstream.avail_in>0))
      {
        if (zi->ci.bstream.avail_out == 0)
        {
          if (zip64FlushWriteBuffer(zi) == ZIP_ERRNO)
            err = ZIP_ERRNO;
          zi->ci.bstream.avail_out = (uInt)Z_BUFSIZE;
          zi->ci.bstream.next_out = (char*)zi->ci.buffered_data;
        }


        if(err != BZ_RUN_OK)
          break;

        if ((zi->ci.method == Z_BZIP2ED) && (!zi->ci.raw))
        {
          uLong uTotalOutBefore_lo = zi->ci.bstream.total_out_lo32;
/*          uLong uTotalOutBefore_hi = zi->ci.bstream.total_out_hi32; */
          err=BZ2_bzCompress(&zi->ci.bstream,  BZ_RUN);

          zi->ci.pos_in_buffered_data += (uInt)(zi->ci.bstream.total_out_lo32 - uTotalOutBefore_lo) ;
        }
      }

      if(err == BZ_RUN_OK)
        err = ZIP_OK;
    }
    else
#endif
    {
      zi->ci.stream.next_in = (Bytef*)buf;
```

```
    zi->ci.stream.avail_in = len;

    while ((err==ZIP_OK) && (zi->ci.stream.avail_in>0))
    {
        if (zi->ci.stream.avail_out == 0)
        {
            if (zip64FlushWriteBuffer(zi) == ZIP_ERRNO)
                err = ZIP_ERRNO;
            zi->ci.stream.avail_out = (uInt)Z_BUFSIZE;
            zi->ci.stream.next_out = zi->ci.buffered_data;
        }


        if(err != ZIP_OK)
            break;

        if ((zi->ci.method == Z_DEFLATED) && (!zi->ci.raw))
        {
            uLong uTotalOutBefore = zi->ci.stream.total_out;
            err=deflate(&zi->ci.stream,  Z_NO_FLUSH);
            if(uTotalOutBefore > zi->ci.stream.total_out)
            {
              int bBreak = 0;
              bBreak++;
            }

            zi->ci.pos_in_buffered_data += (uInt)(zi->ci.stream.total_out - uTotalOutBefore) ;
        }
        else
        {
            uInt copy_this,i;
            if (zi->ci.stream.avail_in < zi->ci.stream.avail_out)
                copy_this = zi->ci.stream.avail_in;
            else
                copy_this = zi->ci.stream.avail_out;

            for (i = 0; i < copy_this; i++)
                *(((char*)zi->ci.stream.next_out)+i) =
                    *(((const char*)zi->ci.stream.next_in)+i);
            {
                zi->ci.stream.avail_in -= copy_this;
                zi->ci.stream.avail_out-= copy_this;
                zi->ci.stream.next_in+= copy_this;
                zi->ci.stream.next_out+= copy_this;
                zi->ci.stream.total_in+= copy_this;
                zi->ci.stream.total_out+= copy_this;
                zi->ci.pos_in_buffered_data += copy_this;
            }
        }
    }/* while(...) */
  }

  return err;
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.109.5 Variable Documentation

13.109.5.1 const char zip_copyright[] =" zip 1.01 Copyright 1998-2004 Gilles Vollant - http://www.winimage.com/zLibDll"

Definition at line 104 of file zip.c.

13.110 src/ckb/quazip/zip.h File Reference

```
#include "zlib.h"
#include "ioapi.h"
```

Include dependency graph for zip.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- struct tm_zip_s
- struct zip_fileinfo

Macros

- #define Z_BZIP2ED 12
- #define ZIP_OK (0)
- #define ZIP_EOF (0)
- #define ZIP_ERRNO (Z_ERRNO)
- #define ZIP_PARAMERROR (-102)
- #define ZIP_BADZIPFILE (-103)
- #define ZIP_INTERNALERROR (-104)
- #define ZIP_WRITE_DATA_DESCRIPTOR 0x8u
- #define ZIP_AUTO_CLOSE 0x1u
- #define ZIP_SEQUENTIAL 0x2u
- #define ZIP_DEFAULT_FLAGS (ZIP_AUTO_CLOSE | ZIP_WRITE_DATA_DESCRIPTOR)
- #define DEF_MEM_LEVEL MAX_MEM_LEVEL
- #define APPEND_STATUS_CREATE (0)
- #define APPEND_STATUS_CREATEAFTER (1)
- #define APPEND_STATUS_ADDINZIP (2)

Typedefs

- typedef voidp zipFile
- typedef struct tm_zip_s tm_zip
- typedef const char * zipcharpc

Functions

- zipFile ZEXPORT zipOpen _Z_OF ((voidpf file, int append))
- zipFile ZEXPORT zipOpen2 _Z_OF ((voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc_def *pzlib_filefunc_def))
- zipFile ZEXPORT zipOpen2_64 _Z_OF ((voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc64_def *pzlib_filefunc_def))
- zipFile ZEXPORT zipOpen3 (voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc64_32_def *pzlib_filefunc64_32_def, unsigned flags)

- int ZEXPORT zipOpenNewFileInZip _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level))
- int ZEXPORT zipOpenNewFileInZip64 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_-global, const char *comment, int method, int level, int zip64))
- int ZEXPORT zipOpenNewFileInZip2 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_-global, const char *comment, int method, int level, int raw))
- int ZEXPORT zipOpenNewFileInZip2_64 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_-global, const char *comment, int method, int level, int raw, int zip64))
- int ZEXPORT zipOpenNewFileInZip3 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting))
- int ZEXPORT zipOpenNewFileInZip3_64 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_-global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, int zip64))
- int ZEXPORT zipOpenNewFileInZip4 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase))
- int ZEXPORT zipOpenNewFileInZip4_64 _Z_OF ((zipFile file, const char *filename, const zip_fileinfo *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_-global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase, int zip64))
- int ZEXPORT zipWriteInFileInZip _Z_OF ((zipFile file, const void *buf, unsigned len))
- int ZEXPORT zipCloseFileInZip _Z_OF ((zipFile file))
- int ZEXPORT zipCloseFileInZipRaw _Z_OF ((zipFile file, uLong uncompressed_size, uLong crc32))
- int ZEXPORT zipCloseFileInZipRaw64 _Z_OF ((zipFile file, ZPOS64_T uncompressed_size, uLong crc32))
- int ZEXPORT zipClose _Z_OF ((zipFile file, const char *global_comment))
- int ZEXPORT zipRemoveExtraInfoBlock _Z_OF ((char *pData, int *dataLen, short sHeader))
- int ZEXPORT zipSetFlags (zipFile file, unsigned flags)
- int ZEXPORT zipClearFlags (zipFile file, unsigned flags)

13.110.1 Data Structure Documentation

13.110.1.1 struct tm_zip_s

Definition at line 100 of file zip.h.

Collaboration diagram for tm_zip_s:

Data Fields

uInt	tm_hour	
uInt	tm_mday	
uInt	tm_min	
uInt	tm_mon	
uInt	tm_sec	
uInt	tm_year	

13.110.1.2 struct zip_fileinfo

Definition at line 110 of file zip.h.

Collaboration diagram for zip_fileinfo:

Data Fields

uLong	dosDate	
uLong	external_fa	
uLong	internal_fa	
tm_zip	tmz_date	

13.110.2 Macro Definition Documentation

13.110.2.1 #define APPEND_STATUS_ADDINZIP (2)

Definition at line 125 of file zip.h.

Referenced by QuaZip::open(), and zipOpen3().

13.110.2.2 #define APPEND_STATUS_CREATE (0)

Definition at line 123 of file zip.h.

Referenced by QuaZip::open(), and zipOpen3().

13.110.2.3 #define APPEND_STATUS_CREATEAFTER (1)

Definition at line 124 of file zip.h.

Referenced by QuaZip::open(), and zipOpen3().

13.110.2.4 #define DEF_MEM_LEVEL MAX_MEM_LEVEL

Definition at line 94 of file zip.h.

Referenced by zipOpenNewFileInZip(), zipOpenNewFileInZip2(), zipOpenNewFileInZip2_64(), and zipOpenNewFileInZip64().

13.110.2.5 #define Z_BZIP2ED 12

Definition at line 67 of file zip.h.

13.110.2.6 #define ZIP_AUTO_CLOSE 0x1u

Definition at line 86 of file zip.h.

Referenced by LoadCentralDirectoryRecord(), QuaZip::open(), zipClose(), and zipOpen3().

13.110.2.7 #define ZIP_BADZIPFILE (-103)

Definition at line 82 of file zip.h.

Referenced by LoadCentralDirectoryRecord(), and zipCloseFileInZipRaw64().

13.110.2.8 #define ZIP_DEFAULT_FLAGS (ZIP_AUTO_CLOSE | ZIP_WRITE_DATA_DESCRIPTOR)

Definition at line 88 of file zip.h.

Referenced by zipOpen(), zipOpen2(), zipOpen2_64(), and zipOpen64().

13.110.2.9 #define ZIP_EOF (0)

Definition at line 79 of file zip.h.

Referenced by zip64local_getByte().

13.110.2.10 #define ZIP_ERRNO (Z_ERRNO)

Definition at line 80 of file zip.h.

Referenced by LoadCentralDirectoryRecord(), Write_GlobalComment(), Write_LocalFileHeader(), zip64FlushWriteBuffer(), zip64local_getByte(), zip64local_putValue(), zipClose(), zipCloseFileInZipRaw64(), zipOpenNewFileInZip4_64(), zipRemoveExtraInfoBlock(), and zipWriteInFileInZip().

13.110.2.11 #define ZIP_INTERNALERROR (-104)

Definition at line 83 of file zip.h.

Referenced by add_data_in_datablock(), and zipOpenNewFileInZip4_64().

13.110.2.12 #define ZIP_OK (0)

Definition at line 78 of file zip.h.

Referenced by add_data_in_datablock(), LoadCentralDirectoryRecord(), Write_EndOfCentralDirectoryRecord(), Write_GlobalComment(), Write_LocalFileHeader(), Write_Zip64EndOfCentralDirectoryLocator(), Write_Zip64EndOfCentralDirectoryRecord(), QuaZipFile::writeData(), zip64FlushWriteBuffer(), zip64local_getByte(), zip64local_getLong(), zip64local_getLong64(), zip64local_getShort(), zip64local_putValue(), zip64local_SearchCentralDir64(), zipClearFlags(), zipClose(), zipCloseFileInZipRaw64(), zipOpen3(), zipOpenNewFileInZip4_64(), zipRemoveExtraInfoBlock(), zipSetFlags(), and zipWriteInFileInZip().

13.110.2.13 #define ZIP_PARAMERROR (-102)

Definition at line 81 of file zip.h.

Referenced by zipClearFlags(), zipClose(), zipCloseFileInZipRaw64(), zipOpenNewFileInZip4_64(), zipRemoveExtraInfoBlock(), zipSetFlags(), and zipWriteInFileInZip().

13.110.2.14 #define ZIP_SEQUENTIAL 0x2u

Definition at line 87 of file zip.h.

Referenced by QuaZip::open(), zipClearFlags(), zipCloseFileInZipRaw64(), zipOpenNewFileInZip4_64(), and zipSetFlags().

13.110.2.15 #define ZIP_WRITE_DATA_DESCRIPTOR 0x8u

Definition at line 85 of file zip.h.

Referenced by QuaZip::open(), QuaZipFile::open(), zipClearFlags(), zipOpenNewFileInZip4_64(), and zipSetFlags().

13.110.3 Typedef Documentation

13.110.3.1 typedef struct tm_zip_s tm_zip

13.110.3.2 typedef const char* zipcharpc

Definition at line 120 of file zip.h.

13.110.3.3 typedef voidp zipFile

Definition at line 75 of file zip.h.

13.110.4 Function Documentation

13.110.4.1 zipFile ZEXPORT zipOpen _Z_OF ((voidpf file, int append))

13.110.4.2 zipFile ZEXPORT zipOpen2 _Z_OF ((voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc_def *pzlib_filefunc_def))

13.110.4.3 zipFile ZEXPORT zipOpen2_64 _Z_OF ((voidpf file, int append, zipcharpc *globalcomment, zlib_filefunc64_def *pzlib_filefunc_def))

13.110.4.4 int ZEXPORT **zipOpenNewFileInZip _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level))

13.110.4.5 int ZEXPORT **zipOpenNewFileInZip64 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int zip64))

13.110.4.6 int ZEXPORT **zipOpenNewFileInZip2 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw))

13.110.4.7 int ZEXPORT **zipOpenNewFileInZip2_64 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int zip64))

13.110.4.8 int ZEXPORT **zipOpenNewFileInZip3 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting))

13.110.4.9 int ZEXPORT **zipOpenNewFileInZip3_64 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, int zip64))

13.110.4.10 int ZEXPORT **zipOpenNewFileInZip4 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase))

13.110.4.11 int ZEXPORT **zipOpenNewFileInZip4_64 _Z_OF** ((**zipFile** file, const char *filename, const **zip_fileinfo** *zipfi, const void *extrafield_local, uInt size_extrafield_local, const void *extrafield_global, uInt size_extrafield_global, const char *comment, int method, int level, int raw, int windowBits, int memLevel, int strategy, const char *password, uLong crcForCrypting, uLong versionMadeBy, uLong flagBase, int zip64))

13.110.4.12 int ZEXPORT **zipWriteInFileInZip _Z_OF** ((**zipFile** file, const void *buf, unsigned len))

13.110.4.13 int ZEXPORT **zipCloseFileInZip _Z_OF** ((**zipFile** file))

13.110.4.14 int ZEXPORT **zipCloseFileInZipRaw _Z_OF** ((**zipFile** file, uLong uncompressed_size, uLong crc32))

13.110.4.15 int ZEXPORT **zipCloseFileInZipRaw64 _Z_OF** ((**zipFile** file, **ZPOS64_T** uncompressed_size, uLong crc32))

13.110.4.16 int ZEXPORT **zipClose _Z_OF** ((**zipFile** file, const char *global_comment))

13.110.4.17 int ZEXPORT **zipRemoveExtraInfoBlock _Z_OF** ((char *pData, int *dataLen, short sHeader))

13.110.4.18 int ZEXPORT zipClearFlags (**zipFile** *file,* unsigned *flags*)

Definition at line 2091 of file zip.c.

References zip64_internal::flags, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, and ZIP_WRITE_DATA_DESCRIPTOR.

Referenced by QuaZipFile::open().

```
2092 {
2093     zip64_internal* zi;
```

```
    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;
    zi->flags &= ~flags;
    // If the data descriptor is not written, we can't use a non-seekable output.
    if ((zi->flags & ZIP_WRITE_DATA_DESCRIPTOR) == 0) {
        zi->flags &= ~ZIP_SEQUENTIAL;
    }
    return ZIP_OK;
}
```

Here is the caller graph for this function:

13.110.4.19 zipFile ZEXPORT zipOpen3 (voidpf *file*, int *append*, zipcharpc * *globalcomment*, zlib_filefunc64_32_def * *pzlib_filefunc64_32_def*, unsigned *flags*)

Definition at line 862 of file zip.c.

References zip64_internal::add_position_when_writting_offset, ALLOC, APPEND_STATUS_ADDINZIP, APPEND_STATUS_CREATE, APPEND_STATUS_CREATEAFTER, zip64_internal::begin_pos, zip64_internal::central_dir, zip64_internal::ci, zip64_internal::filestream, fill_qiodevice64_filefunc(), zip64_internal::flags, zip64_internal::globalcomment, zip64_internal::in_opened_file_inzip, init_linkedlist(), LoadCentralDirectoryRecord(), zip64_internal::number_entry, SEEK_END, curfile64_info::stream_initialised, TRYFREE, zip64_internal::z_filefunc, ZCLOSE64, ZFAKECLOSE64, zlib_filefunc64_32_def_s::zfile_func64, ZIP_AUTO_CLOSE, ZIP_OK, ZLIB_FILEFUNC_MODE_CREATE, ZLIB_FILEFUNC_MODE_EXISTING, ZLIB_FILEFUNC_MODE_READ, ZLIB_FILEFUNC_MODE_WRITE, ZOPEN64, zlib_filefunc64_32_def_s::zseek32_file, ZSEEK64, zlib_filefunc64_32_def_s::ztell32_file, and ZTELL64.

Referenced by QuaZip::open(), zipOpen(), zipOpen2(), zipOpen2_64(), and zipOpen64().

```
{
    zip64_internal ziinit;
    zip64_internal* zi;
    int err=ZIP_OK;

    ziinit.flags = flags;
    ziinit.z_filefunc.zseek32_file = NULL;
    ziinit.z_filefunc.ztell32_file = NULL;
    if (pzlib_filefunc64_32_def==NULL)
        fill_qiodevice64_filefunc(&ziinit.z_filefunc.zfile_func64);
    else
        ziinit.z_filefunc = *pzlib_filefunc64_32_def;

    ziinit.filestream = ZOPEN64(ziinit.z_filefunc,
                    file,
                    (append == APPEND_STATUS_CREATE) ?
                    (ZLIB_FILEFUNC_MODE_READ | ZLIB_FILEFUNC_MODE_WRITE | ZLIB_FILEFUNC_MODE_CREATE) :
                      (ZLIB_FILEFUNC_MODE_READ | ZLIB_FILEFUNC_MODE_WRITE | ZLIB_FILEFUNC_MODE_EXISTING))
    ;

    if (ziinit.filestream == NULL)
        return NULL;

    if (append == APPEND_STATUS_CREATEAFTER)
        ZSEEK64(ziinit.z_filefunc,ziinit.filestream,0,SEEK_END);

```

```
    ziinit.begin_pos = ZTELL64(ziinit.z_filefunc,ziinit.filestream);
    ziinit.in_opened_file_inzip = 0;
    ziinit.ci.stream_initialised = 0;
    ziinit.number_entry = 0;
    ziinit.add_position_when_writting_offset = 0;
    init_linkedlist(&(ziinit.central_dir));



    zi = (zip64_internal*)ALLOC(sizeof(zip64_internal));
    if (zi==NULL)
    {
        if ((ziinit.flags & ZIP_AUTO_CLOSE) != 0) {
            ZCLOSE64(ziinit.z_filefunc,ziinit.filestream);
        } else {
            ZFAKECLOSE64(ziinit.z_filefunc,ziinit.filestream);
        }
        return NULL;
    }

    /* now we add file in a zipfile */
#    ifndef NO_ADDFILEINEXISTINGZIP
    ziinit.globalcomment = NULL;
    if (append == APPEND_STATUS_ADDINZIP)
    {
      /* Read and Cache Central Directory Records */
      err = LoadCentralDirectoryRecord(&ziinit);
    }

    if (globalcomment)
    {
      *globalcomment = ziinit.globalcomment;
    }
#    endif /* !NO_ADDFILEINEXISTINGZIP*/

    if (err != ZIP_OK)
    {
#    ifndef NO_ADDFILEINEXISTINGZIP
        TRYFREE(ziinit.globalcomment);
#    endif /* !NO_ADDFILEINEXISTINGZIP*/
        TRYFREE(zi);
        return NULL;
    }
    else
    {
        *zi = ziinit;
        return (zipFile)zi;
    }
}
```

Here is the call graph for this function:

Here is the caller graph for this function:

13.110.4.20 int ZEXPORT zipSetFlags (zipFile *file*, unsigned *flags*)

Definition at line 2077 of file zip.c.

References zip64_internal::flags, ZIP_OK, ZIP_PARAMERROR, ZIP_SEQUENTIAL, and ZIP_WRITE_DATA_DESCRIPTOR.

Referenced by QuaZip::open(), and QuaZipFile::open().

```
{
    zip64_internal* zi;
    if (file == NULL)
        return ZIP_PARAMERROR;
    zi = (zip64_internal*)file;
    zi->flags |= flags;
    // If the output is non-seekable, the data descriptor is needed.
    if ((zi->flags & ZIP_SEQUENTIAL) != 0) {
        zi->flags |= ZIP_WRITE_DATA_DESCRIPTOR;
    }
    return ZIP_OK;
}
```

Here is the caller graph for this function:

13.111 src/ckb/rebindwidget.cpp File Reference

```
#include <QStandardPaths>
#include "rebindwidget.h"
#include "ui_rebindwidget.h"
#include <qdebug.h>
```

Include dependency graph for rebindwidget.cpp:

Variables

- static const int DPI_OFFSET = -KeyAction::DPI_UP + 1
- static const int DPI_CUST_IDX = KeyAction::DPI_CUSTOM + DPI_OFFSET

13.111.1 Variable Documentation

13.111.1.1 const int DPI_CUST_IDX = KeyAction::DPI_CUSTOM + DPI_OFFSET [static]

Definition at line 7 of file rebindwidget.cpp.

Referenced by RebindWidget::on_dpiBox_currentIndexChanged().

13.111.1.2 const int DPI_OFFSET = -KeyAction::DPI_UP + 1 [static]

Definition at line 6 of file rebindwidget.cpp.

Referenced by RebindWidget::applyChanges(), and RebindWidget::setSelection().

13.112 src/ckb/rebindwidget.h File Reference

```
#include <QWidget>
#include "kbbind.h"
#include "kbprofile.h"
#include "macroreader.h"
```

Include dependency graph for rebindwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class RebindWidget

Namespaces

- Ui

13.113 src/ckb/release/moc_animadddialog.cpp File Reference

```
#include "../animadddialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_animadddialog.cpp:

Data Structures

- struct qt_meta_stringdata_AnimAddDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_AnimAddDialog_t qt_meta_stringdata_AnimAddDialog
- static const uint qt_meta_data_AnimAddDialog []

13.113.1 Data Structure Documentation

13.113.1.1 struct qt_meta_stringdata_AnimAddDialog_t

Definition at line 21 of file moc_animadddialog.cpp.

Collaboration diagram for qt_meta_stringdata_AnimAddDialog_t:

Data Fields

QByteArrayData	data[7]	
char	stringdata0[95]	

13.113.2 Macro Definition Documentation

13.113.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_AnimAddDialog_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_animadddialog.cpp.

13.113.3 Variable Documentation

13.113.3.1 const uint qt_meta_data_AnimAddDialog[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        3,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
       0,
       0,


       1,    1,   29,    2, 0x08 ,
       4,    1,   32,    2, 0x08 ,
       5,    1,   35,    2, 0x08 ,


    QMetaType::Void, QMetaType::Int,    3,
    QMetaType::Void, QMetaType::Int,    3,
    QMetaType::Void, QMetaType::Bool,    6,

       0
}
```

Definition at line 47 of file moc_animadddialog.cpp.

13.113.3.2 const qt_meta_stringdata_AnimAddDialog_t qt_meta_stringdata_AnimAddDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  14    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  35    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  36    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 22 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  42    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  65    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimAddDialog_t, stringdata0) +  87    -  6  * sizeof(
      QByteArrayData))   )

    },
    "AnimAddDialog\0on_animBox_activated\0\0"
    "index\0on_presetBox_activated\0"
    "on_previewBox_clicked\0checked"
}
```

Definition at line 30 of file moc_animadddialog.cpp.

13.114 src/ckb/release/moc_animscript.cpp File Reference

```
#include "../animscript.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_animscript.cpp:

Data Structures

- struct qt_meta_stringdata_AnimScript_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_AnimScript_t qt_meta_stringdata_AnimScript
- static const uint qt_meta_data_AnimScript [ ]

13.114.1 Data Structure Documentation

13.114.1.1 struct qt_meta_stringdata_AnimScript_t

Definition at line 21 of file moc_animscript.cpp.

Collaboration diagram for qt_meta_stringdata_AnimScript_t:

Data Fields

QByteArrayData	data[3]	
char	stringdata0[24]	

13.114.2 Macro Definition Documentation

13.114.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_AnimScript_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_animscript.cpp.

13.114.3 Variable Documentation

13.114.3.1 const uint qt_meta_data_AnimScript[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        1,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
```

```
        0,

        1,    0,   19,    2, 0x08 ,

    QMetaType::Void,

        0
}
```

Definition at line 41 of file moc_animscript.cpp.

13.114.3.2 const qt_meta_stringdata_AnimScript_t qt_meta_stringdata_AnimScript [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimScript_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimScript_t, stringdata0) +  11    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimScript_t, stringdata0) +  23    -  2  * sizeof(
      QByteArrayData))   )

    },
    "AnimScript\0readProcess\0"
}
```

Definition at line 30 of file moc_animscript.cpp.

13.115 src/ckb/release/moc_animsettingdialog.cpp File Reference

```
#include "../animsettingdialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_animsettingdialog.cpp:

Data Structures

- struct qt_meta_stringdata_AnimSettingDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_AnimSettingDialog_t qt_meta_stringdata_AnimSettingDialog
- static const uint qt_meta_data_AnimSettingDialog []

13.115.1 Data Structure Documentation

13.115.1.1 struct qt_meta_stringdata_AnimSettingDialog_t

Definition at line 21 of file moc_animsettingdialog.cpp.

Collaboration diagram for qt_meta_stringdata_AnimSettingDialog_t:

Data Fields

QByteArrayData	data[15]	
char	stringdata0[246]	

13.115.2 Macro Definition Documentation

13.115.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_AnimSettingDialog_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_animsettingdialog.cpp.

13.115.3 Variable Documentation

13.115.3.1 const uint qt_meta_data_AnimSettingDialog[] [static]

Definition at line 60 of file moc_animsettingdialog.cpp.

13.115.3.2 const qt_meta_stringdata_AnimSettingDialog_t qt_meta_stringdata_AnimSettingDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 17 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  18    -  1  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  30    -  2  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  31    -  3  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  40    -  4  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  52    -  5  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  69    -  6  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  74    -  7  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  94    -  8  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 24 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  106    -  9
      * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  131    -  10
       * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 25 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  136    -  11
       * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 26 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  162    -  12
       * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 27 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  189    -  13
       * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 28 ,   qptrdiff(offsetof(
      qt_meta_stringdata_AnimSettingDialog_t, stringdata0) +  217    -  14
       * sizeof(QByteArrayData))   )

    },
    "AnimSettingDialog\0newDuration\0\0duration\0"
    "updateStops\0angleDialChanged\0name\0"
    "angleSpinnerChanged\0updateParam\0"
    "on_delayBox_valueChanged\0arg1\0"
    "on_repeatBox_valueChanged\0"
    "on_kpDelayBox_valueChanged\0"
    "on_kpRepeatBox_valueChanged\0"
    "on_kpReleaseBox_stateChanged"
}
```

Definition at line 30 of file moc_animsettingdialog.cpp.

13.116 src/ckb/release/moc_ckbsettingswriter.cpp File Reference

```
#include "../ckbsettingswriter.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_ckbsettingswriter.cpp:

Data Structures

- struct qt_meta_stringdata_CkbSettingsWriter_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_CkbSettingsWriter_t qt_meta_stringdata_CkbSettingsWriter
- static const uint qt_meta_data_CkbSettingsWriter []

13.116.1 Data Structure Documentation

13.116.1.1 struct qt_meta_stringdata_CkbSettingsWriter_t

Definition at line 21 of file moc_ckbsettingswriter.cpp.

Collaboration diagram for qt_meta_stringdata_CkbSettingsWriter_t:

Data Fields

QByteArrayData	data[3]	
char	stringdata0[23]	

13.116.2 Macro Definition Documentation

13.116.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_CkbSettingsWriter_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_ckbsettingswriter.cpp.

13.116.3 Variable Documentation

13.116.3.1 const uint qt_meta_data_CkbSettingsWriter[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        1,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        0,


        1,    0,   19,    2, 0x0a ,


    QMetaType::Void,

        0
}
```

Definition at line 41 of file moc_ckbsettingswriter.cpp.

13.116.3.2 const qt_meta_stringdata_CkbSettingsWriter_t qt_meta_stringdata_CkbSettingsWriter [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 17 ,   qptrdiff(offsetof(
      qt_meta_stringdata_CkbSettingsWriter_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 3 ,   qptrdiff(offsetof(
      qt_meta_stringdata_CkbSettingsWriter_t, stringdata0) +  18    -  1  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_CkbSettingsWriter_t, stringdata0) +  22    -  2  *
       sizeof(QByteArrayData))   )

    },
    "CkbSettingsWriter\0run\0"
}
```

Definition at line 30 of file moc_ckbsettingswriter.cpp.

13.117 src/ckb/release/moc_colorbutton.cpp File Reference

```
#include "../colorbutton.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_colorbutton.cpp:

Data Structures

- struct qt_meta_stringdata_ColorButton_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_ColorButton_t qt_meta_stringdata_ColorButton
- static const uint qt_meta_data_ColorButton []

13.117.1 Data Structure Documentation

13.117.1.1 struct qt_meta_stringdata_ColorButton_t

Definition at line 21 of file moc_colorbutton.cpp.

Collaboration diagram for qt_meta_stringdata_ColorButton_t:

Data Fields

QByteArrayData	data[5]	
char	stringdata0[45]	

13.117.2 Macro Definition Documentation

13.117.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_ColorButton_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_colorbutton.cpp.

13.117.3 Variable Documentation

13.117.3.1 const uint qt_meta_data_ColorButton[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        2,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
        1,


        1,    1,   24,    2, 0x06 ,


        4,    0,   27,    2, 0x08 ,


    QMetaType::Void, QMetaType::QColor,    3,


    QMetaType::Void,

        0
}
```

Definition at line 44 of file moc_colorbutton.cpp.

13.117.3.2 const qt_meta_stringdata_ColorButton_t qt_meta_stringdata_ColorButton [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ColorButton_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ColorButton_t, stringdata0) +  12    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ColorButton_t, stringdata0) +  25    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ColorButton_t, stringdata0) +  26    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ColorButton_t, stringdata0) +  35    -  4  * sizeof(
      QByteArrayData))   )

    },
    "ColorButton\0colorChanged\0\0newColor\0"
    "pickColor"
}
```

Definition at line 30 of file moc_colorbutton.cpp.

13.118 src/ckb/release/moc_extrasettingswidget.cpp File Reference

```
#include "../extrasettingswidget.h"
```

```
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_extrasettingswidget.cpp:

Data Structures

- struct qt_meta_stringdata_ExtraSettingsWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_ExtraSettingsWidget_t qt_meta_stringdata_ExtraSettingsWidget
- static const uint qt_meta_data_ExtraSettingsWidget []

13.118.1 Data Structure Documentation

13.118.1.1 struct qt_meta_stringdata_ExtraSettingsWidget_t

Definition at line 21 of file moc_extrasettingswidget.cpp.

Collaboration diagram for qt_meta_stringdata_ExtraSettingsWidget_t:

Data Fields

QByteArrayData	data[13]	
char	stringdata0[236]	

13.118.2 Macro Definition Documentation

13.118.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_ExtraSettingsWidget_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_extrasettingswidget.cpp.

13.118.3 Variable Documentation

13.118.3.1 const uint qt_meta_data_ExtraSettingsWidget[] [static]

Definition at line 57 of file moc_extrasettingswidget.cpp.

13.118.3.2 const qt_meta_stringdata_ExtraSettingsWidget_t qt_meta_stringdata_ExtraSettingsWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
```

```
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  0    -  0
        * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 18 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  20    -
      1  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  39    -
      2  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  40    -
      3  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 24 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  48    -
      4  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 25 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  73    -
      5  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 22 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  99    -
      6  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  122    -
       7  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  127    -
       8  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  148    -
       9  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  169    -
       10  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 25 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  190    -
       11  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ExtraSettingsWidget_t, stringdata0) +  216    -
       12  * sizeof(QByteArrayData))   )

    },
    "ExtraSettingsWidget\0on_trayBox_clicked\0"
    "\0checked\0on_brightnessBox_clicked\0"
    "on_animScanButton_clicked\0"
    "on_fpsBox_valueChanged\0arg1\0"
    "on_ditherBox_clicked\0on_mAccelBox_clicked\0"
    "on_sAccelBox_clicked\0on_sSpeedBox_valueChanged\0"
    "on_delayBox_clicked"
}
```

Definition at line 30 of file moc_extrasettingswidget.cpp.

13.119 src/ckb/release/moc_fwupgradedialog.cpp File Reference

```
#include "../fwupgradedialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_fwupgradedialog.cpp:

Data Structures

- struct qt_meta_stringdata_FwUpgradeDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_FwUpgradeDialog_t qt_meta_stringdata_FwUpgradeDialog
- static const uint qt_meta_data_FwUpgradeDialog [ ]

13.119.1 Data Structure Documentation

13.119.1.1 struct qt_meta_stringdata_FwUpgradeDialog_t

Definition at line 21 of file moc_fwupgradedialog.cpp.

Collaboration diagram for qt_meta_stringdata_FwUpgradeDialog_t:

Data Fields

QByteArrayData	data[10]	
char	stringdata0[133]	

13.119.2 Macro Definition Documentation

13.119.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_FwUpgradeDialog_t, stringdata0
      ) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_fwupgradedialog.cpp.

13.119.3 Variable Documentation

13.119.3.1 const uint qt_meta_data_FwUpgradeDialog[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        5,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        0,


        1,    2,   39,    2, 0x08 ,
        5,    1,   44,    2, 0x08 ,
        7,    0,   47,    2, 0x08 ,
        8,    0,   48,    2, 0x08 ,
        9,    0,   49,    2, 0x08 ,


    QMetaType::Void, QMetaType::Int, QMetaType::Int,    3,    4,
    QMetaType::Void, QMetaType::Bool,    6,
    QMetaType::Void,
    QMetaType::Void,
    QMetaType::Void,

        0
}
```

Definition at line 51 of file moc_fwupgradedialog.cpp.

13.119.3.2 const qt_meta_stringdata_FwUpgradeDialog_t qt_meta_stringdata_FwUpgradeDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  16    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  33    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  34    -  3  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  42    -  4  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  48    -  5  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  65    -  6  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  75    -  7  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  85    -  8  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_FwUpgradeDialog_t, stringdata0) +  109    -  9  *
      sizeof(QByteArrayData))   )

    },
    "FwUpgradeDialog\0fwUpdateProgress\0\0"
    "current\0total\0fwUpdateFinished\0succeeded\0"
    "removeDev\0on_cancelButton_clicked\0"
    "on_actionButton_clicked"
}
```

Definition at line 30 of file moc_fwupgradedialog.cpp.

13.120 src/ckb/release/moc_gradientbutton.cpp File Reference

```
#include "../gradientbutton.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_gradientbutton.cpp:

Data Structures

- struct qt_meta_stringdata_GradientButton_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_GradientButton_t qt_meta_stringdata_GradientButton
- static const uint qt_meta_data_GradientButton []

13.120.1 Data Structure Documentation

13.120.1.1 struct qt_meta_stringdata_GradientButton_t

Definition at line 21 of file moc_gradientbutton.cpp.

Collaboration diagram for qt_meta_stringdata_GradientButton_t:

Data Fields

QByteArrayData	data[4]	
char	stringdata0[45]	

13.120.2 Macro Definition Documentation

13.120.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_GradientButton_t, stringdata0)
      + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_gradientbutton.cpp.

13.120.3 Variable Documentation

13.120.3.1 const uint qt_meta_data_GradientButton[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        2,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        1,

        1,    0,   24,    2, 0x06 ,

        3,    0,   25,    2, 0x08 ,

    QMetaType::Void,

    QMetaType::Void,

        0
}
```

Definition at line 43 of file moc_gradientbutton.cpp.

13.120.3.2 const qt_meta_stringdata_GradientButton_t qt_meta_stringdata_GradientButton [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientButton_t, stringdata0) +  0    -  0  * sizeof
      (QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientButton_t, stringdata0) +  15    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientButton_t, stringdata0) +  31    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientButton_t, stringdata0) +  32    -  3  *
      sizeof(QByteArrayData))   )

    },
    "GradientButton\0gradientChanged\0\0"
    "pickGradient"
}
```

Definition at line 30 of file moc_gradientbutton.cpp.

13.121 src/ckb/release/moc_gradientdialog.cpp File Reference

```
#include "../gradientdialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_gradientdialog.cpp:

Data Structures

- struct qt_meta_stringdata_GradientDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_GradientDialog_t qt_meta_stringdata_GradientDialog
- static const uint qt_meta_data_GradientDialog []

13.121.1 Data Structure Documentation

13.121.1.1 struct qt_meta_stringdata_GradientDialog_t

Definition at line 21 of file moc_gradientdialog.cpp.

Collaboration diagram for qt_meta_stringdata_GradientDialog_t:

Data Fields

QByteArrayData	data[17]	
char	stringdata0[266]	

13.121.2 Macro Definition Documentation

13.121.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_GradientDialog_t, stringdata0)
      + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_gradientdialog.cpp.

13.121.3 Variable Documentation

13.121.3.1 const uint qt_meta_data_GradientDialog[] [static]

Definition at line 62 of file moc_gradientdialog.cpp.

13.121.3.2 const qt_meta_stringdata_GradientDialog_t qt_meta_stringdata_GradientDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  0    -  0  * sizeof
      (QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  15    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  30    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  31    -  3  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  37    -  4  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  49    -  5  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  58    -  6  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 32 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  71    -  7  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  104    -  8  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  121    -  9  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  129    -  10  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 24 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  138    -  11  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  163    -  12  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  168    -  13  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  190    -  14  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  214    -  15  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 27 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialog_t, stringdata0) +  238    -  16  *
      sizeof(QByteArrayData))   )

    },
    "GradientDialog\0currentChanged\0\0color\0"
    "spontaneous\0position\0colorChanged\0"
    "on_presetList_currentItemChanged\0"
    "QListWidgetItem*\0current\0previous\0"
```

```
    "on_presetName_textEdited\0arg1\0"
    "on_presetSave_clicked\0on_presetDelete_clicked\0"
    "on_stopPos_valueChanged\0"
    "on_stopOpacity_valueChanged"
}
```

Definition at line 30 of file moc_gradientdialog.cpp.

13.122 src/ckb/release/moc_gradientdialogwidget.cpp File Reference

```
#include "../gradientdialogwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_gradientdialogwidget.cpp:

Data Structures

- struct qt_meta_stringdata_GradientDialogWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_GradientDialogWidget_t qt_meta_stringdata_GradientDialogWidget
- static const uint qt_meta_data_GradientDialogWidget []

13.122.1 Data Structure Documentation

13.122.1.1 struct qt_meta_stringdata_GradientDialogWidget_t

Definition at line 21 of file moc_gradientdialogwidget.cpp.

Collaboration diagram for qt_meta_stringdata_GradientDialogWidget_t:

Data Fields

QByteArrayData	data[6]	
char	stringdata0[64]	

13.122.2 Macro Definition Documentation

13.122.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_GradientDialogWidget_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_gradientdialogwidget.cpp.

13.122.3 Variable Documentation

13.122.3.1 const uint qt_meta_data_GradientDialogWidget[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        1,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        1,


        1,    3,   19,    2, 0x06 ,


    QMetaType::Void, QMetaType::QColor, QMetaType::Bool, QMetaType::Int,    3,    4,    5,

        0
}
```

Definition at line 45 of file moc_gradientdialogwidget.cpp.

13.122.3.2 const qt_meta_stringdata_GradientDialogWidget_t qt_meta_stringdata_GradientDialogWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  0    -
       0  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  21    -
        1  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  36    -
        2  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  37    -
        3  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  43    -
        4  * sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_GradientDialogWidget_t, stringdata0) +  55    -
        5  * sizeof(QByteArrayData))   )

    },
    "GradientDialogWidget\0currentChanged\0"
    "\0color\0spontaneous\0position"
}
```

Definition at line 30 of file moc_gradientdialogwidget.cpp.

13.123 src/ckb/release/moc_kb.cpp File Reference

```
#include "../kb.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kb.cpp:

Data Structures

- struct qt_meta_stringdata_Kb_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_Kb_t qt_meta_stringdata_Kb
- static const uint qt_meta_data_Kb [ ]

13.123.1 Data Structure Documentation

13.123.1.1 struct qt_meta_stringdata_Kb_t

Definition at line 21 of file moc_kb.cpp.

Collaboration diagram for qt_meta_stringdata_Kb_t:

Data Fields

QByteArrayData	data[20]	
char	stringdata0[214]	

13.123.2 Macro Definition Documentation

13.123.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_Kb_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kb.cpp.

13.123.3 Variable Documentation

13.123.3.1 const uint qt_meta_data_Kb[] [static]

Definition at line 63 of file moc_kb.cpp.

13.123.3.2 const qt_meta_stringdata_Kb_t qt_meta_stringdata_Kb [static]

Definition at line 30 of file moc_kb.cpp.

13.124 src/ckb/release/moc_kbanim.cpp File Reference

```
#include "../kbanim.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbanim.cpp:

Data Structures

- struct qt_meta_stringdata_KbAnim_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbAnim_t qt_meta_stringdata_KbAnim
- static const uint qt_meta_data_KbAnim [ ]

13.124.1 Data Structure Documentation

13.124.1.1 struct qt_meta_stringdata_KbAnim_t

Definition at line 21 of file moc_kbanim.cpp.

Collaboration diagram for qt_meta_stringdata_KbAnim_t:

Data Fields

QByteArrayData	data[7]	
char	stringdata0[48]	

13.124.2 Macro Definition Documentation

13.124.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbAnim_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbanim.cpp.

13.124.3 Variable Documentation

13.124.3.1 const uint qt_meta_data_KbAnim[] [static]

Initial value:

```
= {

        7,
        0,
        0,     0,
        0,     0,
        0,     0,
        1,    14,
        0,     0,
        0,
```

```
        0,

        1, 0x0,    5,   18,

        2, uint(KbAnim::Normal),
        3, uint(KbAnim::Add),
        4, uint(KbAnim::Subtract),
        5, uint(KbAnim::Multiply),
        6, uint(KbAnim::Divide),

        0
}
```

Definition at line 46 of file moc_kbanim.cpp.

13.124.3.2 const qt_meta_stringdata_KbAnim_t qt_meta_stringdata_KbAnim [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  0    -  0  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  7    -  1  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  12    -  2  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 3 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  19    -  3  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  23    -  4  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  32    -  5  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbAnim_t, stringdata0) +  41    -  6  * sizeof(QByteArrayData
      ))   )

    },
    "KbAnim\0Mode\0Normal\0Add\0Subtract\0"
    "Multiply\0Divide"
}
```

Definition at line 30 of file moc_kbanim.cpp.

13.125 src/ckb/release/moc_kbanimwidget.cpp File Reference

```
#include "../kbanimwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbanimwidget.cpp:

Data Structures

- struct qt_meta_stringdata_KbAnimWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbAnimWidget_t qt_meta_stringdata_KbAnimWidget
- static const uint qt_meta_data_KbAnimWidget []

13.125.1 Data Structure Documentation

13.125.1.1 struct qt_meta_stringdata_KbAnimWidget_t

Definition at line 21 of file moc_kbanimwidget.cpp.

Collaboration diagram for qt_meta_stringdata_KbAnimWidget_t:

Data Fields

QByteArrayData	data[25]	
char	stringdata0[383]	

13.125.2 Macro Definition Documentation

13.125.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbAnimWidget_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbanimwidget.cpp.

13.125.3 Variable Documentation

13.125.3.1 const uint qt_meta_data_KbAnimWidget[] [static]

Definition at line 74 of file moc_kbanimwidget.cpp.

13.125.3.2 const qt_meta_stringdata_KbAnimWidget_t qt_meta_stringdata_KbAnimWidget [static]

Definition at line 30 of file moc_kbanimwidget.cpp.

13.126 src/ckb/release/moc_kbbind.cpp File Reference

```
#include "../kbbind.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbbind.cpp:

Data Structures

- struct qt_meta_stringdata_KbBind_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbBind_t qt_meta_stringdata_KbBind
- static const uint qt_meta_data_KbBind []

13.126.1 Data Structure Documentation

13.126.1.1 struct qt_meta_stringdata_KbBind_t

Definition at line 21 of file moc_kbbind.cpp.

Collaboration diagram for qt_meta_stringdata_KbBind_t:

Data Fields

QByteArrayData	data[8]	
char	stringdata0[56]	

13.126.2 Macro Definition Documentation

13.126.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbBind_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbbind.cpp.

13.126.3 Variable Documentation

13.126.3.1 const uint qt_meta_data_KbBind[] [static]

Definition at line 47 of file moc_kbbind.cpp.

13.126.3.2 const qt_meta_stringdata_KbBind_t qt_meta_stringdata_KbBind [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  0    -  0  * sizeof(QByteArrayData)
```

```
      )    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  7    -  1  * sizeof(QByteArrayData)
      )    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  15    -  2  * sizeof(QByteArrayData
      ))    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  16    -  3  * sizeof(QByteArrayData
      ))    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  30    -  4  * sizeof(QByteArrayData
      ))    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  38    -  5  * sizeof(QByteArrayData
      ))    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 3 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  47    -  6  * sizeof(QByteArrayData
      ))    ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBind_t, stringdata0) +  51    -  7  * sizeof(QByteArrayData
      ))    )

    },
    "KbBind\0didLoad\0\0layoutChanged\0updated\0"
    "keyEvent\0key\0down"
}
```

Definition at line 30 of file moc_kbbind.cpp.

13.127 src/ckb/release/moc_kbbindwidget.cpp File Reference

```
#include "../kbbindwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbbindwidget.cpp:

Data Structures

- struct qt_meta_stringdata_KbBindWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbBindWidget_t qt_meta_stringdata_KbBindWidget
- static const uint qt_meta_data_KbBindWidget []

13.127.1 Data Structure Documentation

13.127.1.1 struct qt_meta_stringdata_KbBindWidget_t

Definition at line 21 of file moc_kbbindwidget.cpp.

Collaboration diagram for qt_meta_stringdata_KbBindWidget_t:

Data Fields

QByteArrayData	data[9]	
char	stringdata0[120]	

13.127.2 Macro Definition Documentation

13.127.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbBindWidget_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbbindwidget.cpp.

13.127.3 Variable Documentation

13.127.3.1 const uint qt_meta_data_KbBindWidget[] [static]

Definition at line 49 of file moc_kbbindwidget.cpp.

13.127.3.2 const qt_meta_stringdata_KbBindWidget_t qt_meta_stringdata_KbBindWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  13    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  24    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  25    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  35    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  48    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  58    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 22 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  75    -  7  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbBindWidget_t, stringdata0) +  98    -  8  * sizeof(
      QByteArrayData))   )

    },
    "KbBindWidget\0updateBind\0\0newLayout\0"
    "newSelection\0selection\0updateSelDisplay\0"
    "on_resetButton_clicked\0on_copyButton_clicked"
}
```

Definition at line 30 of file moc_kbbindwidget.cpp.

13.128 src/ckb/release/moc_kbfirmware.cpp File Reference

```
#include "../kbfirmware.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbfirmware.cpp:

Data Structures

- struct qt_meta_stringdata_KbFirmware_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbFirmware_t qt_meta_stringdata_KbFirmware
- static const uint qt_meta_data_KbFirmware [ ]

13.128.1 Data Structure Documentation

13.128.1.1 struct qt_meta_stringdata_KbFirmware_t

Definition at line 21 of file moc_kbfirmware.cpp.

Collaboration diagram for qt_meta_stringdata_KbFirmware_t:

Data Fields

QByteArrayData	data[7]	
char	stringdata0[77]	

13.128.2 Macro Definition Documentation

13.128.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbFirmware_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbfirmware.cpp.

13.128.3 Variable Documentation

13.128.3.1 const uint qt_meta_data_KbFirmware[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        3,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
```

```
        1,

        1,    0,   29,    2, 0x06 ,

        3,    1,   30,    2, 0x08 ,
        6,    0,   33,    2, 0x08 ,

    QMetaType::Void,

    QMetaType::Void, 0x80000000 | 4,    5,
    QMetaType::Void,

        0
}
```

Definition at line 46 of file moc_kbfirmware.cpp.

13.128.3.2 const qt_meta_stringdata_KbFirmware_t qt_meta_stringdata_KbFirmware [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  11    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  22    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  23    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  39    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  54    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbFirmware_t, stringdata0) +  60    -  6  * sizeof(
      QByteArrayData))   )

    },
    "KbFirmware\0downloaded\0\0processDownload\0"
    "QNetworkReply*\0reply\0downloadFinished"
}
```

Definition at line 30 of file moc_kbfirmware.cpp.

13.129 src/ckb/release/moc_kblight.cpp File Reference

```
#include "../kblight.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
#include <QtCore/QSet>
```

Include dependency graph for moc_kblight.cpp:

Data Structures

- struct qt_meta_stringdata_KbLight_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbLight_t qt_meta_stringdata_KbLight
- static const uint qt_meta_data_KbLight []

13.129.1 Data Structure Documentation

13.129.1.1 struct qt_meta_stringdata_KbLight_t

Definition at line 22 of file moc_kblight.cpp.

Collaboration diagram for qt_meta_stringdata_KbLight_t:

Data Fields

QByteArrayData	data[9]	
char	stringdata0[92]	

13.129.2 Macro Definition Documentation

13.129.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbLight_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 26 of file moc_kblight.cpp.

13.129.3 Variable Documentation

13.129.3.1 const uint qt_meta_data_KbLight[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        3,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
```

```
       3,


       1,    0,   29,    2, 0x06 ,
       3,    0,   30,    2, 0x06 ,
       4,    2,   31,    2, 0x06 ,


    QMetaType::Void,
    QMetaType::Void,
    QMetaType::Void, 0x80000000 | 5, 0x80000000 | 7,    6,    8,

       0
}
```

Definition at line 50 of file moc_kblight.cpp.

13.129.3.2 const qt_meta_stringdata_KbLight_t qt_meta_stringdata_KbLight [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  8    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  16    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  17    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  25    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  40    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  49    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  64    -  7  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbLight_t, stringdata0) +  78    -  8  * sizeof(
      QByteArrayData))   )

    },
    "KbLight\0didLoad\0\0updated\0frameDisplayed\0"
    "ColorMap\0animatedColors\0QSet<QString>\0"
    "indicatorList"
}
```

Definition at line 31 of file moc_kblight.cpp.

13.130 src/ckb/release/moc_kblightwidget.cpp File Reference

```
#include "../kblightwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kblightwidget.cpp:

Data Structures

- struct qt_meta_stringdata_KbLightWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbLightWidget_t qt_meta_stringdata_KbLightWidget
- static const uint qt_meta_data_KbLightWidget [ ]

13.130.1 Data Structure Documentation

13.130.1.1 struct qt_meta_stringdata_KbLightWidget_t

Definition at line 21 of file moc_kblightwidget.cpp.

Collaboration diagram for qt_meta_stringdata_KbLightWidget_t:

Data Fields

QByteArrayData	data[19]	
char	stringdata0[240]	

13.130.2 Macro Definition Documentation

13.130.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbLightWidget_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kblightwidget.cpp.

13.130.3 Variable Documentation

13.130.3.1 const uint qt_meta_data_KbLightWidget[] [static]

Definition at line 63 of file moc_kblightwidget.cpp.

13.130.3.2 const qt_meta_stringdata_KbLightWidget_t qt_meta_stringdata_KbLightWidget [static]

Definition at line 30 of file moc_kblightwidget.cpp.

13.131 src/ckb/release/moc_kbmanager.cpp File Reference

```
#include "../kbmanager.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbmanager.cpp:

Data Structures

- struct qt_meta_stringdata_KbManager_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbManager_t qt_meta_stringdata_KbManager
- static const uint qt_meta_data_KbManager []

13.131.1 Data Structure Documentation

13.131.1.1 struct qt_meta_stringdata_KbManager_t

Definition at line 21 of file moc_kbmanager.cpp.

Collaboration diagram for qt_meta_stringdata_KbManager_t:

Data Fields

QByteArrayData	data[8]	
char	stringdata0[78]	

13.131.2 Macro Definition Documentation

13.131.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbManager_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbmanager.cpp.

13.131.3 Variable Documentation

13.131.3.1 const uint qt_meta_data_KbManager[] [static]

Definition at line 48 of file moc_kbmanager.cpp.

13.131.3.2 const qt_meta_stringdata_KbManager_t qt_meta_stringdata_KbManager [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  0    -  0  * sizeof(
```

```
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  10    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  22    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 3 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  23    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  27    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  34    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  49    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbManager_t, stringdata0) +  64    -  7  * sizeof(
      QByteArrayData))   )

    },
    "KbManager\0kbConnected\0\0Kb*\0device\0"
    "kbDisconnected\0versionUpdated\0"
    "scanKeyboards"
}
```

Definition at line 30 of file moc_kbmanager.cpp.

13.132 src/ckb/release/moc_kbmode.cpp File Reference

```
#include "../kbmode.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbmode.cpp:

Data Structures

- struct qt_meta_stringdata_KbMode_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbMode_t qt_meta_stringdata_KbMode
- static const uint qt_meta_data_KbMode []

13.132.1 Data Structure Documentation

13.132.1.1 struct qt_meta_stringdata_KbMode_t

Definition at line 21 of file moc_kbmode.cpp.

Collaboration diagram for qt_meta_stringdata_KbMode_t:

Data Fields

QByteArrayData	data[4]	
char	stringdata0[25]	

13.132.2 Macro Definition Documentation

13.132.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbMode_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbmode.cpp.

13.132.3 Variable Documentation

13.132.3.1 const uint qt_meta_data_KbMode[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        2,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
        1,


        1,    0,   24,    2, 0x06 ,


        3,    0,   25,    2, 0x08 ,


    QMetaType::Void,


    QMetaType::Void,

        0
}
```

Definition at line 42 of file moc_kbmode.cpp.

13.132.3.2 const qt_meta_stringdata_KbMode_t qt_meta_stringdata_KbMode [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbMode_t, stringdata0) +  0    -  0  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbMode_t, stringdata0) +  7    -  1  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbMode_t, stringdata0) +  15    -  2  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbMode_t, stringdata0) +  16    -  3  * sizeof(QByteArrayData
      ))   )

    },
    "KbMode\0updated\0\0doUpdate"
}
```

Definition at line 30 of file moc_kbmode.cpp.

13.133 src/ckb/release/moc_kbperf.cpp File Reference

```
#include "../kbperf.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbperf.cpp:

Data Structures

- struct qt_meta_stringdata_KbPerf_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbPerf_t qt_meta_stringdata_KbPerf
- static const uint qt_meta_data_KbPerf [ ]

13.133.1 Data Structure Documentation

13.133.1.1 struct qt_meta_stringdata_KbPerf_t

Definition at line 21 of file moc_kbperf.cpp.

Collaboration diagram for qt_meta_stringdata_KbPerf_t:

Data Fields

QByteArrayData	data[4]	
char	stringdata0[32]	

13.133.2 Macro Definition Documentation

13.133.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbPerf_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbperf.cpp.

13.133.3 Variable Documentation

13.133.3.1 const uint qt_meta_data_KbPerf[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        2,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
```

```
        2,


        1,    0,   24,    2, 0x06 ,
        3,    0,   25,    2, 0x06 ,


    QMetaType::Void,
    QMetaType::Void,

        0
}
```

Definition at line 42 of file moc_kbperf.cpp.

13.133.3.2 const qt_meta_stringdata_KbPerf_t qt_meta_stringdata_KbPerf [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbPerf_t, stringdata0) +  0    -  0  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbPerf_t, stringdata0) +  7    -  1  * sizeof(QByteArrayData)
      )   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbPerf_t, stringdata0) +  15    -  2  * sizeof(QByteArrayData
      ))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbPerf_t, stringdata0) +  16    -  3  * sizeof(QByteArrayData
      ))   )

    },
    "KbPerf\0didLoad\0\0settingsUpdated"
}
```

Definition at line 30 of file moc_kbperf.cpp.

13.134 src/ckb/release/moc_kbprofile.cpp File Reference

```
#include "../kbprofile.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbprofile.cpp:

Data Structures

- struct qt_meta_stringdata_KbProfile_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbProfile_t qt_meta_stringdata_KbProfile
- static const uint qt_meta_data_KbProfile [ ]

13.134.1 Data Structure Documentation

13.134.1.1 struct qt_meta_stringdata_KbProfile_t

Definition at line 21 of file moc_kbprofile.cpp.

Collaboration diagram for qt_meta_stringdata_KbProfile_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[10]	

13.134.2 Macro Definition Documentation

13.134.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbProfile_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbprofile.cpp.

13.134.3 Variable Documentation

13.134.3.1 const uint qt_meta_data_KbProfile[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,
        0,

        0
}
```

Definition at line 39 of file moc_kbprofile.cpp.

13.134.3.2 const qt_meta_stringdata_KbProfile_t qt_meta_stringdata_KbProfile [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfile_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "KbProfile"
}
```

Definition at line 30 of file moc_kbprofile.cpp.

13.135 src/ckb/release/moc_kbprofiledialog.cpp File Reference

```
#include "../kbprofiledialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbprofiledialog.cpp:

Data Structures

- struct qt_meta_stringdata_KbProfileDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbProfileDialog_t qt_meta_stringdata_KbProfileDialog
- static const uint qt_meta_data_KbProfileDialog []

13.135.1 Data Structure Documentation

13.135.1.1 struct qt_meta_stringdata_KbProfileDialog_t

Definition at line 21 of file moc_kbprofiledialog.cpp.

Collaboration diagram for qt_meta_stringdata_KbProfileDialog_t:

Data Fields

QByteArrayData	data[12]	
char	stringdata0[212]	

13.135.2 Macro Definition Documentation

13.135.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbProfileDialog_t, stringdata0
      ) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbprofiledialog.cpp.

13.135.3 Variable Documentation

13.135.3.1 const uint qt_meta_data_KbProfileDialog[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        5,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
       0,
       0,


       1,    0,   39,    2, 0x08 ,
       3,    2,   40,    2, 0x08 ,
       7,    1,   45,    2, 0x08 ,
       9,    1,   48,    2, 0x08 ,
      10,    1,   51,    2, 0x08 ,


    QMetaType::Void,
    QMetaType::Void, 0x80000000 | 4, 0x80000000 | 4,    5,    6,
    QMetaType::Void, 0x80000000 | 4,    8,
    QMetaType::Void, 0x80000000 | 4,    8,
    QMetaType::Void, QMetaType::QPoint,   11,

       0
}
```

Definition at line 56 of file moc_kbprofiledialog.cpp.

13.135.3.2 const qt_meta_stringdata_KbProfileDialog_t qt_meta_stringdata_KbProfileDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  16    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  38    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 33 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  39    -  3  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  73    -  4  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  90    -  5  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  98    -  6  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 26 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  107    -  7  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  134    -  8  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 26 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  139    -  9  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 41 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  166    -  10  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 3 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KbProfileDialog_t, stringdata0) +  208    -  11  *
      sizeof(QByteArrayData))   )

    },
    "KbProfileDialog\0profileList_reordered\0"
    "\0on_profileList_currentItemChanged\0"
    "QListWidgetItem*\0current\0previous\0"
    "on_profileList_itemClicked\0item\0"
    "on_profileList_itemChanged\0"
    "on_profileList_customContextMenuRequested\0"
    "pos"
}
```

Definition at line 30 of file moc_kbprofiledialog.cpp.

13.136 src/ckb/release/moc_kbwidget.cpp File Reference

```
#include "../kbwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kbwidget.cpp:

Data Structures

- struct qt_meta_stringdata_KbWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KbWidget_t qt_meta_stringdata_KbWidget
- static const uint qt_meta_data_KbWidget []

13.136.1 Data Structure Documentation

13.136.1.1 struct qt_meta_stringdata_KbWidget_t

Definition at line 21 of file moc_kbwidget.cpp.

Collaboration diagram for qt_meta_stringdata_KbWidget_t:

Data Fields

QByteArrayData	data[29]	
char	stringdata0[442]	

13.136.2 Macro Definition Documentation

13.136.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KbWidget_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kbwidget.cpp.

13.136.3 Variable Documentation

13.136.3.1 const uint qt_meta_data_KbWidget[] [static]

Definition at line 80 of file moc_kbwidget.cpp.

13.136.3.2 const qt_meta_stringdata_KbWidget_t qt_meta_stringdata_KbWidget [static]

Definition at line 30 of file moc_kbwidget.cpp.

13.137 src/ckb/release/moc_keyaction.cpp File Reference

```
#include "../keyaction.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_keyaction.cpp:

Data Structures

- struct qt_meta_stringdata_KeyAction_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KeyAction_t qt_meta_stringdata_KeyAction
- static const uint qt_meta_data_KeyAction [ ]

13.137.1 Data Structure Documentation

13.137.1.1 struct qt_meta_stringdata_KeyAction_t

Definition at line 21 of file moc_keyaction.cpp.

Collaboration diagram for qt_meta_stringdata_KeyAction_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[10]	

13.137.2 Macro Definition Documentation

13.137.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KeyAction_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_keyaction.cpp.

13.137.3 Variable Documentation

13.137.3.1 const uint qt_meta_data_KeyAction[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,
```

```
        0,

        0
}
```

Definition at line 39 of file moc_keyaction.cpp.

13.137.3.2 const qt_meta_stringdata_KeyAction_t qt_meta_stringdata_KeyAction [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyAction_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "KeyAction"
}
```

Definition at line 30 of file moc_keyaction.cpp.

13.138 src/ckb/release/moc_keywidget.cpp File Reference

```
#include "../keywidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
#include <QtCore/QSet>
```

Include dependency graph for moc_keywidget.cpp:

Data Structures

- struct qt_meta_stringdata_KeyWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KeyWidget_t qt_meta_stringdata_KeyWidget
- static const uint qt_meta_data_KeyWidget []

13.138.1 Data Structure Documentation

13.138.1.1 struct qt_meta_stringdata_KeyWidget_t

Definition at line 22 of file moc_keywidget.cpp.

Collaboration diagram for qt_meta_stringdata_KeyWidget_t:

Data Fields

QByteArrayData	data[10]	
char	stringdata0[118]	

13.138.2 Macro Definition Documentation

13.138.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KeyWidget_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 26 of file moc_keywidget.cpp.

13.138.3 Variable Documentation

13.138.3.1 const uint qt_meta_data_KeyWidget[] [static]

Definition at line 52 of file moc_keywidget.cpp.

13.138.3.2 const qt_meta_stringdata_KeyWidget_t qt_meta_stringdata_KeyWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  10    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  27    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  28    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  37    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 15 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  54    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 8 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  70    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  79    -  7  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  93    -  8  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KeyWidget_t, stringdata0) +  107    -  9  * sizeof(
      QByteArrayData))   )

    },
    "KeyWidget\0selectionChanged\0\0selected\0"
    "sidelightToggled\0displayColorMap\0"
    "ColorMap\0newDisplayMap\0QSet<QString>\0"
    "indicators"
}
```

Definition at line 31 of file moc_keywidget.cpp.

13.139 src/ckb/release/moc_kperfwidget.cpp File Reference

```
#include "../kperfwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_kperfwidget.cpp:

Data Structures

- struct qt_meta_stringdata_KPerfWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_KPerfWidget_t qt_meta_stringdata_KPerfWidget
- static const uint qt_meta_data_KPerfWidget []

13.139.1 Data Structure Documentation

13.139.1.1 struct qt_meta_stringdata_KPerfWidget_t

Definition at line 21 of file moc_kperfwidget.cpp.

Collaboration diagram for qt_meta_stringdata_KPerfWidget_t:

Data Fields

QByteArrayData	data[7]	
char	stringdata0[85]	

13.139.2 Macro Definition Documentation

13.139.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_KPerfWidget_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_kperfwidget.cpp.

13.139.3 Variable Documentation

13.139.3.1 const uint qt_meta_data_KPerfWidget[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        3,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
       0,
       0,


       1,    1,   29,    2, 0x08 ,
       4,    1,   32,    2, 0x08 ,
       6,    0,   35,    2, 0x08 ,


    QMetaType::Void, QMetaType::Int,    3,
    QMetaType::Void, QMetaType::Int,    5,
    QMetaType::Void,

       0
}
```

Definition at line 47 of file moc_kperfwidget.cpp.

13.139.3.2 const qt_meta_stringdata_KPerfWidget_t qt_meta_stringdata_KPerfWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  12    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  22    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  23    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 28 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  29    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  58    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_KPerfWidget_t, stringdata0) +  63    -  6  * sizeof(
      QByteArrayData))   )

    },
    "KPerfWidget\0uiUpdated\0\0index\0"
    "on_intensityBox_valueChanged\0arg1\0"
    "on_copyButton_clicked"
}
```

Definition at line 30 of file moc_kperfwidget.cpp.

13.140 src/ckb/release/moc_layoutdialog.cpp File Reference

```
#include "../layoutdialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_layoutdialog.cpp:

Data Structures

- struct qt_meta_stringdata_LayoutDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_LayoutDialog_t qt_meta_stringdata_LayoutDialog
- static const uint qt_meta_data_LayoutDialog []

13.140.1 Data Structure Documentation

13.140.1.1 struct qt_meta_stringdata_LayoutDialog_t

Definition at line 21 of file moc_layoutdialog.cpp.

Collaboration diagram for qt_meta_stringdata_LayoutDialog_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[13]	

13.140.2 Macro Definition Documentation

13.140.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_LayoutDialog_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_layoutdialog.cpp.

13.140.3 Variable Documentation

13.140.3.1 const uint qt_meta_data_LayoutDialog[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        0,

        0
}
```

Definition at line 39 of file moc_layoutdialog.cpp.

13.140.3.2 const qt_meta_stringdata_LayoutDialog_t qt_meta_stringdata_LayoutDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_LayoutDialog_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "LayoutDialog"
}
```

Definition at line 30 of file moc_layoutdialog.cpp.

13.141 src/ckb/release/moc_macroreader.cpp File Reference

```
#include "../macroreader.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_macroreader.cpp:

Data Structures

- struct qt_meta_stringdata_MacroReaderThread_t
- struct qt_meta_stringdata_MacroReader_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)
- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_MacroReaderThread_t qt_meta_stringdata_MacroReaderThread
- static const uint qt_meta_data_MacroReaderThread []
- static const qt_meta_stringdata_MacroReader_t qt_meta_stringdata_MacroReader
- static const uint qt_meta_data_MacroReader []

13.141.1 Data Structure Documentation

13.141.1.1 struct qt_meta_stringdata_MacroReaderThread_t

Definition at line 21 of file moc_macroreader.cpp.

Collaboration diagram for qt_meta_stringdata_MacroReaderThread_t:

Data Fields

QByteArrayData	data[4]	
char	stringdata0[34]	

13.141.1.2 struct qt_meta_stringdata_MacroReader_t

Definition at line 111 of file moc_macroreader.cpp.

Collaboration diagram for qt_meta_stringdata_MacroReader_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[12]	

13.141.2 Macro Definition Documentation

13.141.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_MacroReaderThread_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 115 of file moc_macroreader.cpp.

13.141.2.2 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_MacroReader_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 115 of file moc_macroreader.cpp.

13.141.3 Variable Documentation

13.141.3.1 const uint qt_meta_data_MacroReader[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,
        0,

        0
}
```

Definition at line 129 of file moc_macroreader.cpp.

13.141.3.2 const uint qt_meta_data_MacroReaderThread[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        1,   14,
        0,    0,
        0,    0,
        0,    0,
        0,
        0,


        1,    1,   19,    2, 0x08 ,


    QMetaType::Void, QMetaType::QString,    3,

        0
}
```

Definition at line 42 of file moc_macroreader.cpp.

13.141.3.3 const qt_meta_stringdata_MacroReader_t qt_meta_stringdata_MacroReader [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MacroReader_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "MacroReader"
}
```

Definition at line 120 of file moc_macroreader.cpp.

13.141.3.4 const qt_meta_stringdata_MacroReaderThread_t qt_meta_stringdata_MacroReaderThread [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 17 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MacroReaderThread_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MacroReaderThread_t, stringdata0) +  18    -  1  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MacroReaderThread_t, stringdata0) +  28    -  2  *
       sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MacroReaderThread_t, stringdata0) +  29    -  3  *
       sizeof(QByteArrayData))   )

    },
    "MacroReaderThread\0readMacro\0\0line"
}
```

Definition at line 30 of file moc_macroreader.cpp.

13.142 src/ckb/release/moc_mainwindow.cpp File Reference

```
#include "../mainwindow.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_mainwindow.cpp:

Data Structures

- struct qt_meta_stringdata_MainWindow_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_MainWindow_t qt_meta_stringdata_MainWindow
- static const uint qt_meta_data_MainWindow []

13.142.1 Data Structure Documentation

13.142.1.1 struct qt_meta_stringdata_MainWindow_t

Definition at line 21 of file moc_mainwindow.cpp.

Collaboration diagram for qt_meta_stringdata_MainWindow_t:

Data Fields

QByteArrayData	data[22]	
char	stringdata0[253]	

13.142.2 Macro Definition Documentation

13.142.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_MainWindow_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_mainwindow.cpp.

13.142.3 Variable Documentation

13.142.3.1 const uint qt_meta_data_MainWindow[] [static]

Definition at line 66 of file moc_mainwindow.cpp.

13.142.3.2 const qt_meta_stringdata_MainWindow_t qt_meta_stringdata_MainWindow [static]

Definition at line 30 of file moc_mainwindow.cpp.

13.143 src/ckb/release/moc_modeselectdialog.cpp File Reference

```
#include "../modeselectdialog.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_modeselectdialog.cpp:

Data Structures

- struct qt_meta_stringdata_ModeSelectDialog_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_ModeSelectDialog_t qt_meta_stringdata_ModeSelectDialog
- static const uint qt_meta_data_ModeSelectDialog [ ]

13.143.1 Data Structure Documentation

13.143.1.1 struct qt_meta_stringdata_ModeSelectDialog_t

Definition at line 21 of file moc_modeselectdialog.cpp.

Collaboration diagram for qt_meta_stringdata_ModeSelectDialog_t:

Data Fields

QByteArrayData	data[4]	
char	stringdata0[67]	

13.143.2 Macro Definition Documentation

13.143.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_ModeSelectDialog_t,
      stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_modeselectdialog.cpp.

13.143.3 Variable Documentation

13.143.3.1 const uint qt_meta_data_ModeSelectDialog[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        2,   14,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        0,


        1,    0,   24,    2, 0x08 ,
        3,    0,   25,    2, 0x08 ,


    QMetaType::Void,
    QMetaType::Void,

        0
}
```

Definition at line 43 of file moc_modeselectdialog.cpp.

13.143.3.2 const qt_meta_stringdata_ModeSelectDialog_t qt_meta_stringdata_ModeSelectDialog [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ModeSelectDialog_t, stringdata0) +  0    -  0  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ModeSelectDialog_t, stringdata0) +  17    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ModeSelectDialog_t, stringdata0) +  41    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 24 ,   qptrdiff(offsetof(
      qt_meta_stringdata_ModeSelectDialog_t, stringdata0) +  42    -  3  *
      sizeof(QByteArrayData))   )

    },
    "ModeSelectDialog\0on_selAllButton_clicked\0"
    "\0on_selNoneButton_clicked"
}
```

Definition at line 30 of file moc_modeselectdialog.cpp.

13.144 src/ckb/release/moc_mperfwidget.cpp File Reference

```
#include "../mperfwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_mperfwidget.cpp:

Data Structures

- struct qt_meta_stringdata_MPerfWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_MPerfWidget_t qt_meta_stringdata_MPerfWidget
- static const uint qt_meta_data_MPerfWidget []

13.144.1 Data Structure Documentation

13.144.1.1 struct qt_meta_stringdata_MPerfWidget_t

Definition at line 21 of file moc_mperfwidget.cpp.

Collaboration diagram for qt_meta_stringdata_MPerfWidget_t:

Data Fields

QByteArrayData	data[18]	
char	stringdata0[249]	

13.144.2 Macro Definition Documentation

13.144.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_MPerfWidget_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_mperfwidget.cpp.

13.144.3 Variable Documentation

13.144.3.1 const uint qt_meta_data_MPerfWidget[] [static]

Definition at line 62 of file moc_mperfwidget.cpp.

13.144.3.2 const qt_meta_stringdata_MPerfWidget_t qt_meta_stringdata_MPerfWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  12    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  25    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  26    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  32    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  45    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  58    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  71    -  7  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  83    -  8  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 13 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  95    -  9  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  109    -  10  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  126    -  11  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  134    -  12  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  154    -  13  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  174    -  14  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  198    -  15  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  220    -  16  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_MPerfWidget_t, stringdata0) +  244    -  17  * sizeof(
      QByteArrayData))   )

    },
    "MPerfWidget\0colorClicked\0\0index\0"
    "colorChanged\0sliderXMoved\0sliderYMoved\0"
    "boxXChanged\0boxYChanged\0enableChanged\0"
    "on_xyBox_clicked\0checked\0on_indicBox_clicked\0"
    "on_aSnapBox_clicked\0on_lHeightBox_activated\0"
    "on_copyButton_clicked\0on_spinBox_valueChanged\0"
    "arg1"
}
```

Definition at line 30 of file moc_mperfwidget.cpp.

13.145 src/ckb/release/moc_quagzipfile.cpp File Reference

```
#include "../quazip/quagzipfile.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_quagzipfile.cpp:

Data Structures

- struct qt_meta_stringdata_QuaGzipFile_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_QuaGzipFile_t qt_meta_stringdata_QuaGzipFile
- static const uint qt_meta_data_QuaGzipFile []

13.145.1 Data Structure Documentation

13.145.1.1 struct qt_meta_stringdata_QuaGzipFile_t

Definition at line 21 of file moc_quagzipfile.cpp.

Collaboration diagram for qt_meta_stringdata_QuaGzipFile_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[12]	

13.145.2 Macro Definition Documentation

13.145.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_QuaGzipFile_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_quagzipfile.cpp.

13.145.3 Variable Documentation

13.145.3.1 const uint qt_meta_data_QuaGzipFile[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
```

```
        0,
        0,

        0
}
```

Definition at line 39 of file moc_quagzipfile.cpp.

13.145.3.2 const qt_meta_stringdata_QuaGzipFile_t qt_meta_stringdata_QuaGzipFile [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
      qt_meta_stringdata_QuaGzipFile_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "QuaGzipFile"
}
```

Definition at line 30 of file moc_quagzipfile.cpp.

13.146 src/ckb/release/moc_quaziodevice.cpp File Reference

```
#include "../quazip/quaziodevice.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_quaziodevice.cpp:

Data Structures

- struct qt_meta_stringdata_QuaZIODevice_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_QuaZIODevice_t qt_meta_stringdata_QuaZIODevice
- static const uint qt_meta_data_QuaZIODevice []

13.146.1 Data Structure Documentation

13.146.1.1 struct qt_meta_stringdata_QuaZIODevice_t

Definition at line 21 of file moc_quaziodevice.cpp.

Collaboration diagram for qt_meta_stringdata_QuaZIODevice_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[13]	

13.146.2 Macro Definition Documentation

13.146.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_QuaZIODevice_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_quaziodevice.cpp.

13.146.3 Variable Documentation

13.146.3.1 const uint qt_meta_data_QuaZIODevice[] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,
        0,

        0
}
```

Definition at line 39 of file moc_quaziodevice.cpp.

13.146.3.2 const qt_meta_stringdata_QuaZIODevice_t qt_meta_stringdata_QuaZIODevice [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_QuaZIODevice_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "QuaZIODevice"
}
```

Definition at line 30 of file moc_quaziodevice.cpp.

13.147 src/ckb/release/moc_quazipfile.cpp File Reference

```
#include "../quazip/quazipfile.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_quazipfile.cpp:

Data Structures

- struct qt_meta_stringdata_QuaZipFile_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_QuaZipFile_t qt_meta_stringdata_QuaZipFile
- static const uint qt_meta_data_QuaZipFile []

13.147.1 Data Structure Documentation

13.147.1.1 struct qt_meta_stringdata_QuaZipFile_t

Definition at line 21 of file moc_quazipfile.cpp.

Collaboration diagram for qt_meta_stringdata_QuaZipFile_t:

Data Fields

QByteArrayData	data[1]	
char	stringdata0[11]	

13.147.2 Macro Definition Documentation

13.147.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_QuaZipFile_t, stringdata0) + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_quazipfile.cpp.

13.147.3 Variable Documentation

13.147.3.1 const uint qt_meta_data_QuaZipFile[ ] [static]

Initial value:

```
= {

        7,
        0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,    0,
        0,
        0,

        0
}
```

Definition at line 39 of file moc_quazipfile.cpp.

13.147.3.2 const qt_meta_stringdata_QuaZipFile_t qt_meta_stringdata_QuaZipFile [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 10 ,   qptrdiff(offsetof(
      qt_meta_stringdata_QuaZipFile_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   )

    },
    "QuaZipFile"
}
```

Definition at line 30 of file moc_quazipfile.cpp.

13.148 src/ckb/release/moc_rebindwidget.cpp File Reference

```
#include "../rebindwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_rebindwidget.cpp:

Data Structures

- struct qt_meta_stringdata_RebindWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_RebindWidget_t qt_meta_stringdata_RebindWidget
- static const uint qt_meta_data_RebindWidget []

13.148.1 Data Structure Documentation

13.148.1.1 struct qt_meta_stringdata_RebindWidget_t

Definition at line 21 of file moc_rebindwidget.cpp.

Collaboration diagram for qt_meta_stringdata_RebindWidget_t:

Data Fields

QByteArrayData	data[48]	
char	stringdata0[1100]	

13.148.2 Macro Definition Documentation

13.148.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_RebindWidget_t, stringdata0) +
      ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_rebindwidget.cpp.

13.148.3 Variable Documentation

13.148.3.1 const uint qt_meta_data_RebindWidget[] [static]

Definition at line 118 of file moc_rebindwidget.cpp.

13.148.3.2 const qt_meta_stringdata_RebindWidget_t qt_meta_stringdata_RebindWidget [static]

Definition at line 30 of file moc_rebindwidget.cpp.

13.149 src/ckb/release/moc_rlistwidget.cpp File Reference

```
#include "../rlistwidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_rlistwidget.cpp:

Data Structures

- struct qt_meta_stringdata_RListWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_RListWidget_t qt_meta_stringdata_RListWidget
- static const uint qt_meta_data_RListWidget []

13.149.1 Data Structure Documentation

13.149.1.1 struct qt_meta_stringdata_RListWidget_t

Definition at line 21 of file moc_rlistwidget.cpp.

Collaboration diagram for qt_meta_stringdata_RListWidget_t:

Data Fields

QByteArrayData	data[8]	
char	stringdata0[71]	

13.149.2 Macro Definition Documentation

13.149.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_RListWidget_t, stringdata0) + ofs
      \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_rlistwidget.cpp.

13.149.3 Variable Documentation

13.149.3.1 const uint qt_meta_data_RListWidget[] [static]

Definition at line 47 of file moc_rlistwidget.cpp.

13.149.3.2 const qt_meta_stringdata_RListWidget_t qt_meta_stringdata_RListWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 11 ,   qptrdiff(offsetof(
```

```
      qt_meta_stringdata_RListWidget_t, stringdata0) +  0    -  0  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 12 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  12    -  1  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  25    -  2  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 9 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  26    -  3  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  36    -  4  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  42    -  5  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 4 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  59    -  6  * sizeof(
      QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 6 ,   qptrdiff(offsetof(
      qt_meta_stringdata_RListWidget_t, stringdata0) +  64    -  7  * sizeof(
      QByteArrayData))   )

    },
    "RListWidget\0orderChanged\0\0timerTick\0"
    "enter\0QListWidgetItem*\0item\0change"
}
```

Definition at line 30 of file moc_rlistwidget.cpp.

13.150 src/ckb/release/moc_settingswidget.cpp File Reference

```
#include "../settingswidget.h"
#include <QtCore/qbytearray.h>
#include <QtCore/qmetatype.h>
```

Include dependency graph for moc_settingswidget.cpp:

Data Structures

- struct qt_meta_stringdata_SettingsWidget_t

Macros

- #define QT_MOC_LITERAL(idx, ofs, len)

Variables

- static const qt_meta_stringdata_SettingsWidget_t qt_meta_stringdata_SettingsWidget
- static const uint qt_meta_data_SettingsWidget []

13.150.1 Data Structure Documentation

13.150.1.1 struct qt_meta_stringdata_SettingsWidget_t

Definition at line 21 of file moc_settingswidget.cpp.

Collaboration diagram for qt_meta_stringdata_SettingsWidget_t:

Data Fields

QByteArrayData	data[15]	
char	stringdata0[264]	

13.150.2 Macro Definition Documentation

13.150.2.1 #define QT_MOC_LITERAL(*idx, ofs, len*)

Value:

```
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET(len, \
    qptrdiff(offsetof(qt_meta_stringdata_SettingsWidget_t, stringdata0)
      + ofs \
        - idx * sizeof(QByteArrayData)) \
    )
```

Definition at line 25 of file moc_settingswidget.cpp.

13.150.3 Variable Documentation

13.150.3.1 const uint qt_meta_data_SettingsWidget[] [static]

Definition at line 59 of file moc_settingswidget.cpp.

13.150.3.2 const qt_meta_stringdata_SettingsWidget_t qt_meta_stringdata_SettingsWidget [static]

Initial value:

```
= {
    {
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 14 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  0    -  0  * sizeof
      (QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  15    -  1  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 0 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  37    -  2  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  38    -  3  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 5 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  59    -  4  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 21 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  65    -  5  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  87    -  6  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  108    -  7  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 19 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  128    -  8  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 20 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  148    -  9  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 7 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  169    -  10  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 23 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  177    -  11  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 22 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  201    -  12  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 16 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  224    -  13  *
      sizeof(QByteArrayData))   ),
Q_STATIC_BYTE_ARRAY_DATA_HEADER_INITIALIZER_WITH_OFFSET( 22 ,   qptrdiff(offsetof(
      qt_meta_stringdata_SettingsWidget_t, stringdata0) +  241    -  14  *
      sizeof(QByteArrayData))   )

    },
    "SettingsWidget\0on_pushButton_clicked\0"
    "\0on_capsBox_activated\0index\0"
    "on_shiftBox_activated\0on_ctrlBox_activated\0"
    "on_altBox_activated\0on_winBox_activated\0"
    "on_autoFWBox_clicked\0checked\0"
    "on_loginItemBox_clicked\0on_layoutBox_activated\0"
    "showLayoutDialog\0on_extraButton_clicked"
}
```

Definition at line 30 of file moc_settingswidget.cpp.

13.151 src/ckb/release/qrc_binary.cpp File Reference

Macros

- #define QT_RCC_PREPEND_NAMESPACE(name) name
- #define QT_RCC_MANGLE_NAMESPACE(name) name

Functions

- bool qRegisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- bool qUnregisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- int qInitResources_binary ()
- int qCleanupResources_binary ()

Variables

- static const unsigned char qt_resource_data []
- static const unsigned char qt_resource_name []
- static const unsigned char qt_resource_struct []

13.151.1 Macro Definition Documentation

13.151.1.1 #define QT_RCC_MANGLE_NAMESPACE(*name*) name

Definition at line 147 of file qrc_binary.cpp.

13.151.1.2 #define QT_RCC_PREPEND_NAMESPACE(*name*) name

Definition at line 146 of file qrc_binary.cpp.

Referenced by qCleanupResources_binary(), and qInitResources_binary().

13.151.2 Function Documentation

13.151.2.1 int qCleanupResources_binary ( )

Definition at line 171 of file qrc_binary.cpp.

References QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, qt_resource_struct, and qUnregisterResourceData().

```
{
    QT_RCC_PREPEND_NAMESPACE(qUnregisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name,
    qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.151.2.2 int qInitResources_binary ( )

Definition at line 163 of file qrc_binary.cpp.

References qRegisterResourceData(), QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, and qt_resource_struct.

```
{
    QT_RCC_PREPEND_NAMESPACE(qRegisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name, qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.151.2.3 bool qRegisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qInitResources_binary().

Here is the caller graph for this function:

13.151.2.4 bool qUnregisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qCleanupResources_binary().

Here is the caller graph for this function:

13.151.3 Variable Documentation

13.151.3.1 const unsigned char qt_resource_data[] [static]

Definition at line 9 of file qrc_binary.cpp.

Referenced by qCleanupResources_binary(), and qInitResources_binary().

13.151.3.2 const unsigned char qt_resource_name[] [static]

Initial value:

```
= {

  0x0,0x3,
  0x0,0x0,0x68,0xfe,
  0x0,0x62,
  0x0,0x69,0x0,0x6e,

  0x0,0x10,
  0x9,0x4b,0x25,0x27,
  0x0,0x63,
  0x0,0x6b,0x0,0x62,0x0,0x2d,0x0,0x6e,0x0,0x65,0x0,0x78,0x0,0x74,0x0,0x2d,0x0,0x6b,0x0,0x65,0x0,0x79,0x0,
      0x2e,0x0,0x67,0x0,0x70,0x0,0x67,

}
```

Definition at line 114 of file qrc_binary.cpp.

Referenced by qCleanupResources_binary(), and qInitResources_binary().

13.151.3.3 const unsigned char qt_resource_struct[] [static]

Initial value:

```
= {

  0x0,0x0,0x0,0x0,0x0,0x2,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0x1,

  0x0,0x0,0x0,0x0,0x0,0x2,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0x2,

  0x0,0x0,0x0,0xc,0x0,0x0,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0x0,

}
```

Definition at line 128 of file qrc_binary.cpp.

Referenced by qCleanupResources_binary(), and qInitResources_binary().

13.152 src/ckb/release/qrc_image.cpp File Reference

Macros

- #define QT_RCC_PREPEND_NAMESPACE(name) name
- #define QT_RCC_MANGLE_NAMESPACE(name) name

Functions

- bool qRegisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- bool qUnregisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- int qInitResources_image ()
- int qCleanupResources_image ()

Variables

- static const unsigned char qt_resource_data []
- static const unsigned char qt_resource_name []
- static const unsigned char qt_resource_struct []

13.152.1 Macro Definition Documentation

13.152.1.1 #define QT_RCC_MANGLE_NAMESPACE(*name*) name

Definition at line 9796 of file qrc_image.cpp.

13.152.1.2 #define QT_RCC_PREPEND_NAMESPACE(*name*) name

Definition at line 9795 of file qrc_image.cpp.

Referenced by qCleanupResources_image(), and qInitResources_image().

13.152.2 Function Documentation

13.152.2.1 int qCleanupResources_image ( )

Definition at line 9820 of file qrc_image.cpp.

References QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, qt_resource_struct, and qUnregisterResourceData().

```
{
    QT_RCC_PREPEND_NAMESPACE(qUnregisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name,
    qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.152.2.2 int qInitResources_image ( )

Definition at line 9812 of file qrc_image.cpp.

References qRegisterResourceData(), QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, and qt_resource_struct.

```
{
    QT_RCC_PREPEND_NAMESPACE(qRegisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name,
    qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.152.2.3 bool qRegisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qInitResources_image().

Here is the caller graph for this function:

13.152.2.4 bool qUnregisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qCleanupResources_image().

Here is the caller graph for this function:

13.152.3 Variable Documentation

13.152.3.1 const unsigned char qt_resource_data[] [static]

Definition at line 9 of file qrc_image.cpp.

Referenced by qCleanupResources_image(), and qInitResources_image().

13.152.3.2 const unsigned char qt_resource_name[] [static]

Definition at line 9659 of file qrc_image.cpp.

Referenced by qCleanupResources_image(), and qInitResources_image().

13.152.3.3 const unsigned char qt_resource_struct[] [static]

Definition at line 9749 of file qrc_image.cpp.

Referenced by qCleanupResources_image(), and qInitResources_image().

13.153 src/ckb/release/qrc_text.cpp File Reference

Macros

- #define QT_RCC_PREPEND_NAMESPACE(name) name
- #define QT_RCC_MANGLE_NAMESPACE(name) name

Functions

- bool qRegisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- bool qUnregisterResourceData (int, const unsigned char ∗, const unsigned char ∗, const unsigned char ∗)
- int qInitResources_text ()
- int qCleanupResources_text ()

Variables

- static const unsigned char qt_resource_data []
- static const unsigned char qt_resource_name []
- static const unsigned char qt_resource_struct []

13.153.1 Macro Definition Documentation

13.153.1.1 #define QT_RCC_MANGLE_NAMESPACE(*name*) name

Definition at line 350 of file qrc_text.cpp.

13.153.1.2 #define QT_RCC_PREPEND_NAMESPACE(*name*) name

Definition at line 349 of file qrc_text.cpp.

Referenced by qCleanupResources_text(), and qInitResources_text().

13.153.2 Function Documentation

13.153.2.1 int qCleanupResources_text ( )

Definition at line 374 of file qrc_text.cpp.

References QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, qt_resource_struct, and qUnregisterResourceData().

```
{
    QT_RCC_PREPEND_NAMESPACE(qUnregisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name,
    qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.153.2.2 int qInitResources_text ( )

Definition at line 366 of file qrc_text.cpp.

References qRegisterResourceData(), QT_RCC_PREPEND_NAMESPACE, qt_resource_data, qt_resource_name, and qt_resource_struct.

```
{
    QT_RCC_PREPEND_NAMESPACE(qRegisterResourceData)
        (0x01, qt_resource_struct, qt_resource_name,
    qt_resource_data);
    return 1;
}
```

Here is the call graph for this function:

13.153.2.3 bool qRegisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qInitResources_text().

Here is the caller graph for this function:

13.153.2.4 bool qUnregisterResourceData (int , const unsigned char * , const unsigned char * , const unsigned char *)

Referenced by qCleanupResources_text().

Here is the caller graph for this function:

13.153.3 Variable Documentation

13.153.3.1 const unsigned char qt_resource_data[] [static]

Definition at line 9 of file qrc_text.cpp.

Referenced by qCleanupResources_text(), and qInitResources_text().

13.153.3.2 const unsigned char qt_resource_name[] [static]

Initial value:

```
= {

  0x0,0x3,
  0x0,0x0,0x7b,0xf4,
  0x0,0x74,
  0x0,0x78,0x0,0x74,

  0x0,0xb,
  0xa,0x1e,0x1,0xe0,
  0x0,0x63,
  0x0,0x6b,0x0,0x62,0x0,0x2e,0x0,0x64,0x0,0x65,0x0,0x73,0x0,0x6b,0x0,0x74,0x0,0x6f,0x0,0x70,

  0x0,0x10,
  0xe,0xac,0xaf,0x46,
  0x0,0x64,
  0x0,0x65,0x0,0x6d,0x0,0x6f,0x0,0x70,0x0,0x72,0x0,0x6f,0x0,0x66,0x0,0x69,0x0,0x6c,0x0,0x65,0x0,0x2e,0x0,
      0x63,0x0,0x6f,0x0,0x6e,0x0,0x66,

  0x0,0x11,
  0x0,0xd4,0x25,0xa4,
  0x0,0x63,
  0x0,0x6f,0x0,0x6d,0x0,0x2e,0x0,0x63,0x0,0x6b,0x0,0x62,0x0,0x2e,0x0,0x63,0x0,0x6b,0x0,0x62,0x0,0x2e,0x0,
      0x70,0x0,0x6c,0x0,0x69,0x0,0x73,0x0,0x74,


}
```

Definition at line 302 of file qrc_text.cpp.

Referenced by qCleanupResources_text(), and qInitResources_text().

13.153.3.3 const unsigned char qt_resource_struct[] [static]

Initial value:

```
= {

  0x0,0x0,0x0,0x0,0x0,0x2,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0x1,
```

```
  0x0,0x0,0x0,0x0,0x0,0x2,0x0,0x0,0x0,0x3,0x0,0x0,0x0,0x2,
  0x0,0x0,0x0,0x4e,0x0,0x0,0x0,0x0,0x0,0x1,0x0,0x0,0xf,0x74,
  0x0,0x0,0x0,0xc,0x0,0x0,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0x0,
  0x0,0x0,0x0,0x28,0x0,0x1,0x0,0x0,0x0,0x1,0x0,0x0,0x0,0xc6,
}
```

Definition at line 327 of file qrc_text.cpp.

Referenced by qCleanupResources_text(), and qInitResources_text().

13.154 src/ckb/rlistwidget.cpp File Reference

```
#include <QUuid>
#include "rlistwidget.h"
```

Include dependency graph for rlistwidget.cpp:

13.155 src/ckb/rlistwidget.h File Reference

```
#include <QListWidget>
#include <QTimer>
```

Include dependency graph for rlistwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class RListWidget

13.156 src/ckb/settingswidget.cpp File Reference

```
#include <QTimer>
#include "animscript.h"
#include "autorun.h"
#include "ckbsettings.h"
#include "kb.h"
#include "layoutdialog.h"
#include "settingswidget.h"
#include "ui_settingswidget.h"
```

Include dependency graph for settingswidget.cpp:

Functions

- static QString right (const QString &left)

Variables

- QString devpath
- static QStringList modKeys
- static QStringList modNames

13.156.1 Function Documentation

13.156.1.1 static QString right (const QString & *left*) [inline],[static]

Definition at line 118 of file settingswidget.cpp.

Referenced by GradientDialogWidget::mouseMoveEvent(), and SettingsWidget::updateModifiers().

```
118                                                 {
119     if(left[0] != 'l')
120         return left;
121     return "r" + left.mid(1);
122 }
```

Here is the caller graph for this function:

13.156.2 Variable Documentation

13.156.2.1 QString devpath

Definition at line 4 of file kbmanager.cpp.

Referenced by KbManager::scanKeyboards().

13.156.2.2 QStringList modKeys [static]

Definition at line 13 of file settingswidget.cpp.

Referenced by SettingsWidget::SettingsWidget(), and SettingsWidget::updateModifiers().

13.156.2.3 QStringList modNames [static]

Definition at line 13 of file settingswidget.cpp.

Referenced by SettingsWidget::SettingsWidget().

13.157 src/ckb/settingswidget.h File Reference

```
#include <QWidget>
#include "extrasettingswidget.h"
```

Include dependency graph for settingswidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class SettingsWidget

Namespaces

- Ui

13.158 src/ckb/ui_animadddialog.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QSpacerItem>
```

Include dependency graph for ui_animadddialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_AnimAddDialog
- class Ui::AnimAddDialog

Namespaces

- Ui

13.159 src/ckb/ui_animsettingdialog.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QDoubleSpinBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QLineEdit>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QTabWidget>
#include <QtWidgets/QWidget>
```

Include dependency graph for ui_animsettingdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_AnimSettingDialog
- class Ui::AnimSettingDialog

Namespaces

- Ui

13.160 src/ckb/ui_extrasettingswidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QSpinBox>
#include <QtWidgets/QWidget>
```

Include dependency graph for ui_extrasettingswidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_ExtraSettingsWidget
- class Ui::ExtraSettingsWidget

Namespaces

- Ui

13.161 src/ckb/ui_fwupgradedialog.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QDialog>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QProgressBar>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
```

Include dependency graph for ui_fwupgradedialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_FwUpgradeDialog
- class Ui::FwUpgradeDialog

Namespaces

- Ui

13.162 src/ckb/ui_gradientdialog.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QGroupBox>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QLineEdit>
#include <QtWidgets/QListWidget>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QSpinBox>
#include "colorbutton.h"
#include "gradientdialogwidget.h"
```

Include dependency graph for ui_gradientdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_GradientDialog
- class Ui::GradientDialog

Namespaces

- Ui

13.163 src/ckb/ui_kbanimwidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QDoubleSpinBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QLineEdit>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QStackedWidget>
#include <QtWidgets/QVBoxLayout>
#include <QtWidgets/QWidget>
#include "rlistwidget.h"
```

Include dependency graph for ui_kbanimwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KbAnimWidget
- class Ui::KbAnimWidget

Namespaces

- Ui

13.164 src/ckb/ui_kbbindwidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QVBoxLayout>
#include <QtWidgets/QWidget>
#include "keywidget.h"
#include "rebindwidget.h"
```

Include dependency graph for ui_kbbindwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KbBindWidget
- class Ui::KbBindWidget

Namespaces

- Ui

13.165 src/ckb/ui_kblightwidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QVBoxLayout>
#include <QtWidgets/QWidget>
#include "colorbutton.h"
#include "kbanimwidget.h"
#include "keywidget.h"
```

Include dependency graph for ui_kblightwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KbLightWidget
- class Ui::KbLightWidget

Namespaces

- Ui

13.166 src/ckb/ui_kbprofiledialog.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QSpacerItem>
#include "rlistwidget.h"
```

Include dependency graph for ui_kbprofiledialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KbProfileDialog
- class Ui::KbProfileDialog

Namespaces

- Ui

13.167 src/ckb/ui_kbwidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QTabWidget>
#include <QtWidgets/QWidget>
#include <kblightwidget.h>
#include "kbbindwidget.h"
#include "kperfwidget.h"
#include "mperfwidget.h"
#include "rlistwidget.h"
```

Include dependency graph for ui_kbwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KbWidget
- class Ui::KbWidget

Namespaces

- Ui

13.168 src/ckb/ui_kperfwidget.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QSpinBox>
#include <QtWidgets/QWidget>
#include <colorbutton.h>
```

Include dependency graph for ui_kperfwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_KPerfWidget
- class Ui::KPerfWidget

Namespaces

- Ui

13.169 src/ckb/ui_layoutdialog.h File Reference

```
#include <QtCore/QVariant>
```

```
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QSpacerItem>
```

Include dependency graph for ui_layoutdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_LayoutDialog
- class Ui::LayoutDialog

Namespaces

- Ui

13.170 src/ckb/ui_mainwindow.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QMainWindow>
#include <QtWidgets/QTabWidget>
#include <QtWidgets/QWidget>
```

Include dependency graph for ui_mainwindow.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_MainWindow
- class Ui::MainWindow

Namespaces

- Ui

13.171 src/ckb/ui_modeselectdialog.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QDialog>
#include <QtWidgets/QDialogButtonBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QListWidget>
#include <QtWidgets/QPushButton>
```

Include dependency graph for ui_modeselectdialog.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_ModeSelectDialog
- class Ui::ModeSelectDialog

Namespaces

- Ui

13.172 src/ckb/ui_mperfwidget.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSlider>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QSpinBox>
#include <QtWidgets/QVBoxLayout>
#include <QtWidgets/QWidget>
#include <colorbutton.h>
```

Include dependency graph for ui_mperfwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_MPerfWidget
- class Ui::MPerfWidget

Namespaces

- Ui

13.173 src/ckb/ui_rebindwidget.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QGroupBox>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QLineEdit>
#include <QtWidgets/QPlainTextEdit>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QRadioButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QSpinBox>
#include <QtWidgets/QTabWidget>
#include <QtWidgets/QVBoxLayout>
#include <QtWidgets/QWidget>
```

Include dependency graph for ui_rebindwidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_RebindWidget
- class Ui::RebindWidget

Namespaces

- Ui

13.174 src/ckb/ui_settingswidget.h File Reference

```
#include <QtCore/QVariant>
#include <QtWidgets/QAction>
#include <QtWidgets/QApplication>
#include <QtWidgets/QButtonGroup>
#include <QtWidgets/QCheckBox>
#include <QtWidgets/QComboBox>
#include <QtWidgets/QFrame>
#include <QtWidgets/QGridLayout>
#include <QtWidgets/QHBoxLayout>
#include <QtWidgets/QHeaderView>
#include <QtWidgets/QLabel>
#include <QtWidgets/QPushButton>
#include <QtWidgets/QSpacerItem>
#include <QtWidgets/QWidget>
```

Include dependency graph for ui_settingswidget.h:

This graph shows which files directly or indirectly include this file:

Data Structures

- class Ui_SettingsWidget
- class Ui::SettingsWidget

Namespaces

- Ui

Index

~AnimAddDialog
AnimAddDialog, 43
~AnimScript
AnimScript, 57
~AnimSettingDialog
AnimSettingDialog, 105
~CkbSettings
CkbSettings, 125
~CkbSettingsWriter
CkbSettingsWriter, 138
~ColorMap
ColorMap, 150
~ExtraSettingsWidget
ExtraSettingsWidget, 173
~FwUpgradeDialog
FwUpgradeDialog, 182
~GradientDialog
GradientDialog, 212
~KPerfWidget
KPerfWidget, 700
~Kb
Kb, 260
~KbAnimWidget
KbAnimWidget, 345
~KbBindWidget
KbBindWidget, 399
~KbFirmware
KbFirmware, 410
~KbLight
KbLight, 424
~KbLightWidget
KbLightWidget, 459
~KbMode
KbMode, 487
~KbProfileDialog
KbProfileDialog, 550
~KbWidget
KbWidget, 566
~KeyAction
KeyAction, 602
~LayoutDialog
LayoutDialog, 713
~MPerfWidget
MPerfWidget, 774
~MacroReader
MacroReader, 717
~MainWindow
MainWindow, 730
~ModeSelectDialog
ModeSelectDialog, 747
~QuaGzipFile
QuaGzipFile, 809
~QuaZIODevice
QuaZIODevice, 815
~QuaZip
QuaZip, 824
~QuaZipDir
QuaZipDir, 855
~QuaZipFile
QuaZipFile, 875
~QuaZipFilePrivate
QuaZipFilePrivate, 906
~RebindWidget
RebindWidget, 961
~SGroup
SGroup, 1020
~SettingsWidget
SettingsWidget, 998
_LAYOUT_MAX
KeyMap, 630
_MODEL_MAX
KeyMap, 631
_FILE_OFFSET_BIT
ioapi.h, 1317
_LARGEFILE64_SOURCE
ioapi.h, 1318
_Z_OF
ioapi.h, 1320
unzip.c, 1368
unzip.h, 1422, 1423
zip.c, 1441
zip.h, 1494, 1495
__USE_FILE_OFFSET64
ioapi.h, 1317
__USE_LARGEFILE64
ioapi.h, 1317
_alpha
ColorButton, 148
GradientButton, 200
_angleSnap
KbPerf, 527
_anim
AnimSettingDialog, 116
_animList
KbLight, 446
_animMap
KbLight, 446
_backing

CkbSettingsWriter, 139
_bigIcons
ColorButton, 148
_bind
KbBind, 388
KbMode, 495
_bindMap
KeyWidget, 671
_checkUpdates
KbFirmware, 410
_color
ColorButton, 148
_colorBuffer
AnimScript, 81
_colorMap
KbLight, 447
KeyWidget, 671
_colors
AnimScript, 81
ColorMap, 157
GradientDialogWidget, 236
_count
ColorMap, 157
_curDpi
KbPerf, 502
_current
GradientDialogWidget, 236
_currentMode
Kb, 301
KbProfile, 547
_currentProfile
Kb, 301
_daemonVersion
KbManager, 481
_delay
Kb, 301
_devParent
KbBind, 388
_devices
KbManager, 481
_dimming
KbLight, 447
_displayColorMap
KeyWidget, 672
_dither
Kb, 301
_dpiIndicator
KbPerf, 527
_eventTimer
KbManager, 481
_fileForBoard
KbFirmware, 411
_frameRate
Kb, 301
_friendlyName
Key, 596
_globalRemap
KbBind, 388
_globalSettings
ckbsettings.cpp, 1228
_guiVersion
KbManager, 481
_guid
KbAnim, 330
_hwProfile
Kb, 301
_iOpacity
KbPerf, 527
_id
KbMode, 495
KbProfile, 547
_indicatorList
KbLight, 447
_indicatorMap
KbLight, 447
_indicators
KeyWidget, 672
_info
AnimScript, 81
_isActive
KbAnim, 330
_isActiveKp
KbAnim, 330
_kbManager
KbManager, 482
_keyMap
KbProfile, 547
_keyNames
ColorMap, 157
_keys
AnimAddDialog, 46
AnimScript, 81
KbAnim, 330
KeyMap, 650
_latestForBoard
KbFirmware, 412
_layout
Kb, 302
_liftHeight
KbPerf, 527
_light
AnimAddDialog, 46
KbMode, 495
_map
AnimScript, 81
KbAnim, 330
KbBind, 388
KbLight, 447
_mapCount
ColorMap, 157
_mode
KbAnim, 330
_modeList
ModeSelectDialog, 748
_model
Kb, 302

_modes
KbProfile, 547
_monochrome
KeyWidget, 672
_mouseAccel
Kb, 302
_name
KbAnim, 330
KbMode, 495
KbProfile, 547
_needsMapRefresh
KbLight, 447
_needsSave
Kb, 302
KbAnim, 330
KbBind, 388
KbLight, 447
KbMode, 495
KbPerf, 527
KbProfile, 547
_needsUpdate
KbBind, 388
KbPerf, 528
_opacity
KbAnim, 331
_paramValues
AnimScript, 81
_parameters
KbAnim, 331
_patch
keymap.cpp, 1275
_path
AnimScript, 81
_perf
KbMode, 495
_presetValues
AnimScript, 82
_presets
AnimScript, 81
_previewAnim
KbLight, 447
_profiles
Kb, 302
_qColorMap
KbLight, 447
_removals
CkbSettingsWriter, 139
_rgbMode
KeyWidget, 672
_scanTimer
KbManager, 482
_script
KbAnim, 331
_scriptGuid
KbAnim, 331
_scriptName
KbAnim, 331
_scrollSpeed
Kb, 302
_setLabel
ColorButton, 148
_settings
SGroup, 1020
_shareDimming
kblight.cpp, 1258
_start
KbLight, 448
_stops
GradientButton, 200
GradientDialogWidget, 236
_storageName
Key, 596
_tempParameters
KbAnim, 331
_updates
CkbSettingsWriter, 139
_value
KeyAction, 624
_winLock
KbBind, 388
_xyLink
MPerfWidget, 784

ADD
KeyWidget, 654
ALWAYS_OFF
KPerfWidget, 698
ALWAYS_ON
KPerfWidget, 698
aCopyLabel
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1069
ALLOC
unzip.c, 1366
zip.c, 1438
aMissingLabel
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1069
aMissingPage
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1069
ANIM_KRSTOP
keyaction.cpp, 1269
ANIM_ONCE
keyaction.cpp, 1269
ANSI_ENTER_H
keymap.cpp, 1272
ANSI_ENTER_W
keymap.cpp, 1272
ANSI_ENTER_X
keymap.cpp, 1272
ANSI_ENTER_Y
keymap.cpp, 1272
ANSI_LSHIFT_W
keymap.cpp, 1272
ANSI_LSHIFT_X
keymap.cpp, 1273

aNameLabel
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1069
APPEND_STATUS_CREATE
zip.h, 1492
aSnapBox
Ui::MPerfWidget, 760
Ui_MPerfWidget, 1144
AUTO_CHECK_TIME
kbfirmware.cpp, 1254
aVerLabel
Ui::KbAnimWidget, 339
Ui_KbAnimWidget, 1070
action
KbBind, 364
actionAbout
Ui::MainWindow, 725
Ui_MainWindow, 1128
actionButton
Ui::FwUpgradeDialog, 192
Ui_FwUpgradeDialog, 1054
actionExit
Ui::MainWindow, 725
Ui_MainWindow, 1128
actionTab
Ui::RebindWidget, 942
Ui_RebindWidget, 1167
activeDevices
kb.cpp, 1245
activeLights
kblight.cpp, 1258
Add
KbAnim, 308
add_data_in_datablock
zip.c, 1441
addAnim
KbAnimWidget, 345
KbLight, 424
addCurrentFileToDirectoryMap
QuaZipPrivate, 920
addDevice
MainWindow, 731
addNewModeItem
KbWidget, 566
addNewProfileItem
KbProfileDialog, 550
addPreset
GradientDialog, 212
adjustDisplay
KeyAction, 602
advance
AnimScript, 58
alloc
ColorMap, 151
allocate_new_datablock
zip.c, 1442
allowAlpha
ColorButton, 142, 143
altBox
Ui::SettingsWidget, 1013
Ui_SettingsWidget, 1188
altLabel
Ui::SettingsWidget, 1013
Ui_SettingsWidget, 1188
angleDialChanged
AnimSettingDialog, 105
angleDialMapper
AnimSettingDialog, 116
angleFlip
animsettingdialog.cpp, 1204
angleSnap
KbPerf, 502, 503
angleSpinnerChanged
AnimSettingDialog, 106
angleSpinnerMapper
AnimSettingDialog, 116
angleSpinners
AnimSettingDialog, 116
AnimScript::Param, 56, 1202
animAction
KeyAction, 603
AnimAddDialog, 41
~AnimAddDialog, 43
_keys, 46
_light, 46
AnimAddDialog, 42
AnimAddDialog, 42
chosenPreset, 43
chosenScript, 44
on_animBox_activated, 44
on_presetBox_activated, 45
on_previewBox_clicked, 46
scripts, 46
showPreview, 46
ui, 47
animBox
Ui::AnimAddDialog, 50
Ui::RebindWidget, 942
Ui_AnimAddDialog, 1024
Ui_RebindWidget, 1167
animButton
Ui::KbLightWidget, 454
Ui::RebindWidget, 942
Ui_KbLightWidget, 1084
Ui_RebindWidget, 1167
animChanged
KbAnimWidget, 346
animCountLabel
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1045
animInfo
KeyAction, 604
animKeypress
KbLight, 424
animKrBox
Ui::RebindWidget, 942

Ui_RebindWidget, 1167
AnimList
KbLight, 423
animList
KbLight, 425, 426
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1069
animName
Ui::AnimSettingDialog, 91
Ui_AnimSettingDialog, 1032
animOnceBox
Ui::RebindWidget, 942
Ui_RebindWidget, 1167
animPage
Ui::KbAnimWidget, 338
Ui_KbAnimWidget, 1070
animPathLabel
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1045
animScanButton
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1046
AnimScript, 52
~AnimScript, 57
_colorBuffer, 81
_colors, 81
_info, 81
_keys, 81
_map, 81
_paramValues, 81
_path, 81
_presetValues, 82
_presets, 81
advance, 58
AnimScript, 57
AnimScript, 57
author, 58
begin, 59
colors, 60
copy, 60
copyright, 61
count, 61
description, 62
durationMsec, 82
end, 62
firstFrame, 82
frame, 63
guid, 64
hasFrame, 64
hasKeypress, 65
hasParam, 65
inFrame, 82
init, 66
initialized, 82
KP_NAME, 82
KP_NONE, 82
KP_POSITION, 82
keypress, 67
lastFrame, 82
license, 68
list, 68
load, 69
minX, 83
minY, 83
name, 72
param, 72
paramIterator, 74
parameters, 73
path, 74
preset, 74
PresetValue, 57
presets, 75
printParams, 75
process, 83
readAnyFrame, 83
readFrame, 83
readProcess, 76
repeatMsec, 83
retrigger, 77
scan, 78
scripts, 83
setDuration, 78
stop, 79
stopped, 83
version, 80
year, 80
AnimSettingDialog, 97
~AnimSettingDialog, 105
_anim, 116
angleDialChanged, 105
angleDialMapper, 116
angleSpinnerChanged, 106
angleSpinnerMapper, 116
angleSpinners, 116
AnimSettingDialog, 100
AnimSettingDialog, 100
hLine, 107
hasRepeat, 117
kpStopCheck, 117
lastDuration, 117
name, 108
newDuration, 108
on_delayBox_valueChanged, 109
on_kpDelayBox_valueChanged, 110
on_kpReleaseBox_stateChanged, 110
on_kpRepeatBox_valueChanged, 111
on_repeatBox_valueChanged, 111
settingWidgets, 117
stopCheck, 117
ui, 117
updateMapper, 117
updateParam, 112
updateStops, 115
animTab
Ui::RebindWidget, 943
Ui_RebindWidget, 1168

animWidget
Ui::KbLightWidget, 454
Ui_KbLightWidget, 1085
animation
KeyWidget, 672
animations
KbAnimWidget, 359
animscript.cpp
ONE_DAY, 1201
urlParam, 1201
animsettingdialog.cpp
angleFlip, 1204
appShare
main.cpp, 1294
mainwindow.cpp, 1299
append
KbProfile, 535
appendProfile
Kb, 263
applyButton
Ui::RebindWidget, 943
Ui_RebindWidget, 1168
applyChanges
RebindWidget, 961
applyIndicators
KbPerf, 503
atEnd
QuaZipFile, 875
author
AnimScript, 58
autoClose
QuaZipPrivate, 924
autoFWBox
Ui::SettingsWidget, 1013
Ui_SettingsWidget, 1188
AutoRun, 118
available, 118
disable, 119
enable, 119
isEnabled, 120
once, 121
autoSave
Kb, 263
autorun.cpp
settingPath, 1206
available
AutoRun, 118

BOTH
KPerfWidget, 698
BUFREADCOMMENT
unzip.c, 1367
zip.c, 1439
BUILD.md, 1199
backing
CkbSettings, 136
base
KbLight, 426
begin
AnimScript, 59
beginGroup
CkbSettings, 125
bgButton
Ui::KbLightWidget, 454
Ui_KbLightWidget, 1085
bigIcons
ColorButton, 143, 144
bind
KbBindWidget, 407
KbMode, 487
KbPerf, 504
RebindWidget, 986
bindAction
KbBind, 364
BindMap
KeyWidget, 653
bindMap
KeyWidget, 654
bindTab
Ui::KbWidget, 590
Ui_KbWidget, 1097
bindWidget
Ui::KbWidget, 590
Ui_KbWidget, 1097
blend
KbAnim, 311
blendAdd
kbanim.cpp, 1247
blendBox
Ui::KbAnimWidget, 339
Ui_KbAnimWidget, 1070
blendDivide
kbanim.cpp, 1247
blendFunc
kbanim.cpp, 1247
blendMultiply
kbanim.cpp, 1247
blendNormal
kbanim.cpp, 1247
blendSubtract
kbanim.cpp, 1248
blob
FwUpgradeDialog, 187
boxXChanged
MPerfWidget, 774
boxXMapper
MPerfWidget, 784
boxYChanged
MPerfWidget, 775
boxYMapper
MPerfWidget, 784
brightnessBox
Ui::ExtraSettingsWidget, 165
Ui::KbLightWidget, 454
Ui_ExtraSettingsWidget, 1046
Ui_KbLightWidget, 1085
btnClearMacro

Ui::RebindWidget, 943
Ui_RebindWidget, 1168
btnStartMacro
Ui::RebindWidget, 943
Ui_RebindWidget, 1168
btnStopMacro
Ui::RebindWidget, 943
Ui_RebindWidget, 1168
builtIn
GradientDialog::Preset, 787
buttonBox
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 91
Ui::ExtraSettingsWidget, 165
Ui::GradientDialog, 205
Ui::KbProfileDialog, 561
Ui::LayoutDialog, 710
Ui::ModeSelectDialog, 744
Ui_AnimAddDialog, 1024
Ui_AnimSettingDialog, 1032
Ui_ExtraSettingsWidget, 1046
Ui_GradientDialog, 1061
Ui_KbProfileDialog, 1090
Ui_LayoutDialog, 1124
Ui_ModeSelectDialog, 1132
buttonMapper1
MPerfWidget, 784
buttonMapper2
MPerfWidget, 784
byPosition
KeyMap, 632
bytesAvailable
QuaZipFile, 876

CAPS
KbPerf, 500
CENTRALHEADERMAGIC
zip.c, 1439
CKB_CONTAINER
ckb-anim.h, 1212
CKB_COPYRIGHT
ckb-anim.h, 1212
CKB_DESCRIPTION
ckb-anim.h, 1212
CKB_DOWN
ckb-anim.h, 1212
CKB_GRAD_MAX
ckb-anim.h, 1212
CKB_GUID
ckb-anim.h, 1213
CKB_KEYCLEAR
ckb-anim.h, 1213
CKB_KEYNAME_MAX
ckb-anim.h, 1213
CKB_KP_NAME
ckb-anim.h, 1213
CKB_KP_NONE
ckb-anim.h, 1213
CKB_KP_POSITION
ckb-anim.h, 1213
CKB_KPMODE
ckb-anim.h, 1213
CKB_LICENSE
ckb-anim.h, 1213
CKB_LIVEPARAMS
ckb-anim.h, 1213
CKB_MAX_WORD
ckb-anim.h, 1213
CKB_NAME
ckb-anim.h, 1213
CKB_PARAM
ckb-anim.h, 1214
CKB_PARAM_AGRADIENT
ckb-anim.h, 1214
CKB_PARAM_ANGLE
ckb-anim.h, 1214
CKB_PARAM_ARGB
ckb-anim.h, 1214
CKB_PARAM_BOOL
ckb-anim.h, 1214
CKB_PARAM_DOUBLE
ckb-anim.h, 1214
CKB_PARAM_GRADIENT
ckb-anim.h, 1214
CKB_PARAM_LABEL
ckb-anim.h, 1214
CKB_PARAM_LONG
ckb-anim.h, 1214
CKB_PARAM_RGB
ckb-anim.h, 1214
CKB_PARAM_STRING
ckb-anim.h, 1215
CKB_PARSE_AGRADIENT
ckb-anim.h, 1215
CKB_PARSE_ANGLE
ckb-anim.h, 1215
CKB_PARSE_ARGB
ckb-anim.h, 1215
CKB_PARSE_BOOL
ckb-anim.h, 1215
CKB_PARSE_DOUBLE
ckb-anim.h, 1215
CKB_PARSE_GRADIENT
ckb-anim.h, 1215
CKB_PARSE_LONG
ckb-anim.h, 1215
CKB_PARSE_RGB
ckb-anim.h, 1215
CKB_PARSE_STRING
ckb-anim.h, 1215
CKB_PREEMPT
ckb-anim.h, 1216
CKB_PRESET_END
ckb-anim.h, 1216
CKB_PRESET_PARAM
ckb-anim.h, 1216
CKB_PRESET_START

ckb-anim.h, 1216
CKB_REAL_ANGLE
ckb-anim.h, 1216
CKB_REPEAT
ckb-anim.h, 1216
CKB_TIME_ABSOLUTE
ckb-anim.h, 1216
CKB_TIME_DURATION
ckb-anim.h, 1216
CKB_TIMEMODE
ckb-anim.h, 1216
CKB_UP
ckb-anim.h, 1216
CKB_VERSION
ckb-anim.h, 1216
CRC32
crypt.h, 1312
cacheWritesInProgress
ckbsettings.cpp, 1227
ckbsettingswriter.cpp, 1231
calculate
QuaAdler32, 798
QuaChecksum32, 801
QuaCrc32, 804
call_zopen64
qioapi.cpp, 1325
call_zseek64
qioapi.cpp, 1325
call_ztell64
qioapi.cpp, 1325
cancelButton
Ui::FwUpgradeDialog, 192
Ui::RebindWidget, 943
Ui_FwUpgradeDialog, 1055
Ui_RebindWidget, 1168
capsBox
Ui::KPerfWidget, 685
Ui::SettingsWidget, 1013
Ui_KPerfWidget, 1111
Ui_SettingsWidget, 1188
capsColorOff
Ui::KPerfWidget, 685
Ui_KPerfWidget, 1111
capsColorOn
Ui::KPerfWidget, 685
Ui_KPerfWidget, 1112
capsLabel
Ui::SettingsWidget, 1013
Ui_SettingsWidget, 1188
CaseSensitivity
QuaZip, 823
caseSensitivity
QuaZipDir, 856
QuaZipFilePrivate, 907
catchUp
KbAnim, 312
cd
QuaZipDir, 856
cdUp
QuaZipDir, 858
centralWidget
Ui::MainWindow, 725
Ui_MainWindow, 1128
change
RListWidget, 991
changeAnim
KbLightWidget, 460
changeAnimKeys
KbLightWidget, 460
changeColor
KbLightWidget, 461
checkFwUpdates
MainWindow, 731
checkUpdates
KbFirmware, 413
checksum
QuaAdler32, 799
QuaCrc32, 805
childGroups
CkbSettings, 125
childKeys
CkbSettings, 126
chosenPreset
AnimAddDialog, 43
chosenScript
AnimAddDialog, 44
ckb-anim.h
CKB_CONTAINER, 1212
CKB_COPYRIGHT, 1212
CKB_DESCRIPTION, 1212
CKB_DOWN, 1212
CKB_GRAD_MAX, 1212
CKB_GUID, 1213
CKB_KEYCLEAR, 1213
CKB_KEYNAME_MAX, 1213
CKB_KP_NAME, 1213
CKB_KP_NONE, 1213
CKB_KP_POSITION, 1213
CKB_KPMODE, 1213
CKB_LICENSE, 1213
CKB_LIVEPARAMS, 1213
CKB_MAX_WORD, 1213
CKB_NAME, 1213
CKB_PARAM, 1214
CKB_PARAM_AGRADIENT, 1214
CKB_PARAM_ANGLE, 1214
CKB_PARAM_ARGB, 1214
CKB_PARAM_BOOL, 1214
CKB_PARAM_DOUBLE, 1214
CKB_PARAM_GRADIENT, 1214
CKB_PARAM_LABEL, 1214
CKB_PARAM_LONG, 1214
CKB_PARAM_RGB, 1214
CKB_PARAM_STRING, 1215
CKB_PARSE_AGRADIENT, 1215
CKB_PARSE_ANGLE, 1215

CKB_PARSE_ARGB, 1215
CKB_PARSE_BOOL, 1215
CKB_PARSE_DOUBLE, 1215
CKB_PARSE_GRADIENT, 1215
CKB_PARSE_LONG, 1215
CKB_PARSE_RGB, 1215
CKB_PARSE_STRING, 1215
CKB_PREEMPT, 1216
CKB_PRESET_END, 1216
CKB_PRESET_PARAM, 1216
CKB_PRESET_START, 1216
CKB_REAL_ANGLE, 1216
CKB_REPEAT, 1216
CKB_TIME_ABSOLUTE, 1216
CKB_TIME_DURATION, 1216
CKB_TIMEMODE, 1216
CKB_UP, 1216
CKB_VERSION, 1216
ckb_alpha_blend, 1217
ckb_frame, 1217
ckb_getline, 1217
ckb_grad_color, 1218
ckb_info, 1219
ckb_init, 1219
ckb_keypress, 1219
ckb_parameter, 1219
ckb_read_params, 1220
ckb_scan_grad, 1221
ckb_start, 1221
ckb_time, 1222
FALSE, 1216
M_PI, 1217
main, 1222
printurl, 1224
TRUE, 1217
urldecode, 1225
ckb_gradient, 1211
ckb_key, 1209
ckb_runctx, 1210
ckb_alpha_blend
ckb-anim.h, 1217
ckb_frame
ckb-anim.h, 1217
ckb_getline
ckb-anim.h, 1217
ckb_grad_color
ckb-anim.h, 1218
ckb_info
ckb-anim.h, 1219
ckb_init
ckb-anim.h, 1219
ckb_keypress
ckb-anim.h, 1219
ckb_parameter
ckb-anim.h, 1219
ckb_read_params
ckb-anim.h, 1220
ckb_scan_grad
ckb-anim.h, 1221
ckb_start
ckb-anim.h, 1221
ckb_time
ckb-anim.h, 1222
ckbDaemonVersion
KbManager, 473
ckbDaemonVersionF
KbManager, 473
ckbGuiVersion
KbManager, 474
ckbGuiVersionF
KbManager, 474
CkbSettings, 122
~CkbSettings, 125
backing, 136
beginGroup, 125
childGroups, 125
childKeys, 126
CkbSettings, 124, 125
CkbSettings, 124, 125
cleanUp, 127
contains, 128
containsGroup, 128
endGroup, 129
get, 129
groups, 136
isBusy, 130
pwd, 131, 132
remove, 133
removeCache, 137
set, 133
setValue, 134
value, 135
writeCache, 137
CkbSettingsWriter, 137
~CkbSettingsWriter, 138
_backing, 139
_removals, 139
_updates, 139
CkbSettingsWriter, 138
CkbSettingsWriter, 138
run, 139
ckbVersion
KbFirmware::FW, 179
ckbsettings.cpp
_globalSettings, 1228
cacheWritesInProgress, 1227
globalCache, 1228
globalSettings, 1227
globalThread, 1228
lockMutex, 1226
lockMutexCache, 1226
lockMutexStatic, 1227
lockMutexStatic2, 1227
settingsCacheMutex, 1228
settingsMutex, 1228
ckbsettingswriter.cpp

cacheWritesInProgress, 1231
lockMutex, 1230
lockMutexCache, 1230
lockMutexStatic, 1230
lockMutexStatic2, 1230
settingsCacheMutex, 1231
settingsMutex, 1231
cleanBlob
FwUpgradeDialog, 182
cleanUp
CkbSettings, 127
cleanup
MainWindow, 732
clear
ColorMap, 151
clearAnimation
KeyWidget, 655
clearDirectoryMap
QuaZipPrivate, 921
clearSelection
KbAnimWidget, 347
KeyWidget, 655
close
KbLight, 427
QuaGzipFile, 809
QuaZIODevice, 815
QuaZip, 825
QuaZipFile, 876
closeAction
MainWindow, 740
closeEvent
FwUpgradeDialog, 182
MainWindow, 733
cmd
Kb, 302
cmdpath
Kb, 302
color
ColorButton, 144, 145
KbLight, 428
colorAt
GradientDialogWidget, 224
ColorButton, 139
_alpha, 148
_bigIcons, 148
_color, 148
_setLabel, 148
allowAlpha, 142, 143
bigIcons, 143, 144
color, 144, 145
ColorButton, 142
colorChanged, 146
ColorButton, 142
pickColor, 146
setLabel, 146, 147
updateImage, 147
colorChanged
ColorButton, 146
GradientDialog, 213
MPerfWidget, 776
colorClicked
MPerfWidget, 777
colorForName
ColorMap, 152, 153
colorLink
MPerfWidget, 785
ColorMap, 149
~ColorMap, 150
_colors, 157
_count, 157
_keyNames, 157
_mapCount, 157
alloc, 151
clear, 151
colorForName, 152, 153
ColorMap, 150
ColorMap, 150
colors, 153, 154
count, 154
deAlloc, 154
init, 155
keyNames, 156
operator=, 156
colorMap
KbLight, 429
KeyWidget, 655, 656
colormap.cpp
qs_strcmp, 1233
colormap.h
QColorMap, 1235
QColorMapIterator, 1235
QMutableColorMapIterator, 1235
colors
AnimScript, 60
ColorMap, 153, 154
comboBox
Ui::LayoutDialog, 710
Ui_LayoutDialog, 1124
CommandLineBackground
main.cpp, 1294
CommandLineClose
main.cpp, 1294
CommandLineError
main.cpp, 1294
CommandLineHelpRequested
main.cpp, 1294
CommandLineOK
main.cpp, 1294
CommandLineVersionRequested
main.cpp, 1294
CommandLineParseResults
main.cpp, 1294
comment
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
QuaZipNewInfo, 916

QuaZipPrivate, 924
commentCodec
QuaZipPrivate, 924
commitParams
KbAnim, 314
compressDir
JlCompress, 238
compressFile
JlCompress, 239, 240
compressFiles
JlCompress, 241
compressSubDir
JlCompress, 243
compressedSize
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
configLabel
mainwindow.cpp, 1299
Constants
QuaZip, 823
contains
CkbSettings, 128
KeyMap, 632
containsGroup
CkbSettings, 128
convertCaseSensitivity
QuaZip, 826
convertMacroBox
RebindWidget, 963
copy
AnimScript, 60
copyButton
Ui::KbBindWidget, 394
Ui::KPerfWidget, 685
Ui::MPerfWidget, 760
Ui_KbBindWidget, 1077
Ui_KPerfWidget, 1112
Ui_MPerfWidget, 1144
copyData
JlCompress.cpp, 1322
copyright
AnimScript, 61
count
AnimScript, 61
ColorMap, 154
KeyMap, 633
QuaZipDir, 858
crc
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
QuaZipFilePrivate, 907
crypt.h
CRC32, 1312
decrypt_byte, 1312
init_keys, 1312
update_keys, 1313
zdecode, 1312
zencode, 1312
csDefault
QuaZip, 823
csInsensitive
QuaZip, 823
csSensitive
QuaZip, 823
csize
QuaZipFile, 877
ctrlBox
Ui::SettingsWidget, 1014
Ui_SettingsWidget, 1188
ctrlLabel
Ui::SettingsWidget, 1014
Ui_SettingsWidget, 1188
curDpi
KbPerf, 505, 506
curDpiIdx
KbPerf, 506, 507
curLabel
Ui::FwUpgradeDialog, 192
Ui_FwUpgradeDialog, 1055
curfile64_info, 1437
current
GradientDialogWidget, 225
KbAnimWidget, 359
currentBind
Kb, 263
currentChanged
GradientDialog, 213
GradientDialogWidget, 225
currentData
RListWidget, 994
currentLight
Kb, 264
currentMode
Kb, 265
KbProfile, 535, 536
KbWidget, 583
currentPerf
Kb, 265
currentPreset
GradientDialog, 220
currentProfile
Kb, 266
currentSelection
KbBindWidget, 407
KbLightWidget, 469

d
QuaGzipFile, 812
QuaZIODevice, 819
QuaZipDir, 869
DE
KeyMap, 630
DK
KeyMap, 630
DAEMON.md, 1199
DATA_ROLE
RListWidget, 994

DEF_MEM_LEVEL
zip.h, 1493
DESCRIPTORHEADERMAGIC
zip.c, 1439
DIALOG_HEIGHT_MAX
fwupgradedialog.cpp, 1238
DIALOG_HEIGHT_MIN
fwupgradedialog.cpp, 1239
DIALOG_WIDTH
fwupgradedialog.cpp, 1239
DPI_BASE
mperfwidget.cpp, 1308
DPI_COUNT
KbPerf, 528
MPerfWidget, 785
DPI_CUST_IDX
rebindwidget.cpp, 1499
DPI_CUSTOM
KeyAction, 624
DPI_DOWN
KeyAction, 624
DPI_MAX
KbPerf, 528
MPerfWidget, 785
DPI_MIN
KbPerf, 528
MPerfWidget, 785
DPI_OFFSET
rebindwidget.cpp, 1499
DPI_SNIPER
KeyAction, 624
DPI_UP
KeyAction, 625
dataDescriptorWritingEnabled
QuaZipPrivate, 924
dataForBoard
KbFirmware, 413
dateTime
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
QuaZipNewInfo, 916
deAlloc
ColorMap, 154
decrypt_byte
crypt.h, 1312
defaultAction
KbBind, 365
KeyAction, 604
defaultFileNameCodec
QuaZipPrivate, 925
delayBox
Ui::AnimSettingDialog, 91
Ui::ExtraSettingsWidget, 165
Ui_AnimSettingDialog, 1033
Ui_ExtraSettingsWidget, 1046
deleteButton
Ui::KbAnimWidget, 339
Ui_KbAnimWidget, 1070
deleteHw
Kb, 266
deletePrevious
Kb, 267
description
AnimScript, 62
devLabel
Ui::FwUpgradeDialog, 192
Ui_FwUpgradeDialog, 1055
devParent
KbBind, 366
devTab
Ui::KbWidget, 590
Ui_KbWidget, 1097
devUpdate
KbWidget, 567
device
KbProfileDialog, 556
KbWidget, 583
devices
KbManager, 475
devicesLabel
Ui::SettingsWidget, 1014
Ui_SettingsWidget, 1188
devpath
Kb, 302
kbmanager.cpp, 1261
settingswidget.cpp, 1608
didLoad
KbBind, 366
KbLight, 429
KbPerf, 507
didUpdateSelection
KbAnimWidget, 347
dimming
KbLight, 430
dirName
QuaZipDir, 859
directoryCaseInsensitive
QuaZipPrivate, 925
directoryCaseSensitive
QuaZipPrivate, 925
disable
AutoRun, 119
disableAppNap
media_mac.m, 1304
diskNumberStart
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
displayColorMap
KeyWidget, 656
dither
Kb, 267, 268
ditherBox
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1046
Divide
KbAnim, 309

doUpdate
KbMode, 487
downloadFinished
KbFirmware, 414
downloaded
KbFirmware, 414
dpi
KbPerf, 508
dpiAction
KeyAction, 605
dpiBox
Ui::RebindWidget, 943
Ui_RebindWidget, 1168
dpiButton
Ui::RebindWidget, 943
Ui_RebindWidget, 1168
dpiClr
KbPerf, 528
dpiColor
KbPerf, 509, 510
dpiCurIdx
KbPerf, 528
dpiCurX
KbPerf, 528
dpiCurY
KbPerf, 528
dpiCustLabel
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
dpiCustXBox
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
dpiCustYBox
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
dpiDown
KbPerf, 510
dpiEnabled
KbPerf, 511
dpiExp
mperfwidget.cpp, 1307
dpiIndicator
KbPerf, 511, 512
dpiInfo
KeyAction, 605
dpiLastIdx
KbPerf, 528
dpiLog
mperfwidget.cpp, 1307
dpiOn
KbPerf, 528
dpiRound
mperfwidget.cpp, 1308
dpiUp
KbPerf, 512
dpiWarning
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
dpiX
KbPerf, 529
dpiY
KbPerf, 529
dragged
RListWidget, 994
drawInfo
KeyWidget, 656
driverName
KeyAction, 606
duplicateAnim
KbAnimWidget, 348
KbLight, 431
durationMsec
AnimScript, 82

ES
KeyMap, 630
EU
KeyMap, 630
EU_DVORAK
KeyMap, 630
eBox1
Ui::MPerfWidget, 760
Ui_MPerfWidget, 1144
eBox2
Ui::MPerfWidget, 760
Ui_MPerfWidget, 1144
eBox3
Ui::MPerfWidget, 761
Ui_MPerfWidget, 1144
eBox4
Ui::MPerfWidget, 761
Ui_MPerfWidget, 1144
eBox5
Ui::MPerfWidget, 761
Ui_MPerfWidget, 1145
ENDHEADERMAGIC
zip.c, 1439
ENUM_C
media.h, 1301
ENUM_END_C
media.h, 1301
EXTERN_C
media.h, 1301
effectiveParams
KbAnim, 314
enable
AutoRun, 119
enableChanged
MPerfWidget, 777
enableMapper
MPerfWidget, 785
end
AnimScript, 62
endGroup
CkbSettings, 129
enter
RListWidget, 991

entryInfoList
QuaZipDir, 859, 860
entryInfoList64
QuaZipDir, 860, 861
entryList
QuaZipDir, 861, 862
evLoop
FwUpgradeDialog, 187
eventTimer
KbManager, 475
exec
FwUpgradeDialog, 183
exists
QuaZipDir, 862, 863
exitSuccess
FwUpgradeDialog, 187
externalAttr
QuaZipFileInfo, 895
QuaZipFileInfo64, 902
QuaZipNewInfo, 916
extra
QuaZipFileInfo, 895
QuaZipFileInfo64, 903
SettingsWidget, 1005
extraButton
Ui::SettingsWidget, 1014
Ui_SettingsWidget, 1189
extraGlobal
QuaZipNewInfo, 917
extraLocal
QuaZipNewInfo, 917
ExtraSettingsWidget, 170
~ExtraSettingsWidget, 173
ExtraSettingsWidget, 172
ExtraSettingsWidget, 172
on_animScanButton_clicked, 173
on_brightnessBox_clicked, 174
on_delayBox_clicked, 174
on_ditherBox_clicked, 174
on_fpsBox_valueChanged, 175
on_mAccelBox_clicked, 175
on_sAccelBox_clicked, 176
on_sSpeedBox_valueChanged, 176
on_trayBox_clicked, 177
pollUpdates, 177
ui, 178
extractDir
JlCompress, 246
extractFile
JlCompress, 248, 250
extractFiles
JlCompress, 251
extrasettingswidget.cpp
lastSharedDimming, 1235

FR
KeyMap, 630
FALSE
ckb-anim.h, 1216
FW
KbFirmware::FW, 179
features
Kb, 303
file_in_zip64_read_info_s, 1364
fileName
KbFirmware::FW, 179
QuaZipFilePrivate, 907
fileNameCodec
QuaZipPrivate, 925
filePath
QuaZipDir, 864
fill_qiodevice64_filefunc
qioapi.cpp, 1326
fill_qiodevice_filefunc
qioapi.cpp, 1327
fill_zlib_filefunc64_32_def_from_filefunc32
ioapi.h, 1320
qioapi.cpp, 1328
fillRect
GradientDialogWidget, 225
filter
QuaZipDir, 864
find
Kb, 268
KbProfile, 536
findAnim
KbLight, 431
findAnimIdx
KbLight, 432
firmware
Kb, 303
firstFrame
AnimScript, 82
flags
QuaZipFileInfo, 895
QuaZipFileInfo64, 903
flush
QuaGzipFile, 810
QuaZIODevice, 816
fnBox
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
fnButton
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
fnKeys
RebindWidget, 986
fps
KbManager, 475
fpsBox
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1046
fpsWarnLabel
Ui::ExtraSettingsWidget, 165
Ui_ExtraSettingsWidget, 1046
frame
AnimScript, 63

frameDisplayed
KbLight, 433
frameRate
Kb, 269
frameUpdate
Kb, 270
KbLight, 433
free_datablock
zip.c, 1443
free_linkedlist
zip.c, 1443
friendlyActionName
KbBind, 367
friendlyName
KbBind, 367
Key, 595
KeyAction, 607
KeyMap, 633
fromName
KeyMap, 634
fromStorage
KeyMap, 635
fromString
GradientButton, 196
functions
kbanim.cpp, 1248
fwLabel
Ui::KbWidget, 590
Ui_KbWidget, 1097
fwTable
KbFirmware, 418
fwTableHash
KbFirmware, 418
fwUpdButton
Ui::KbWidget, 590
Ui_KbWidget, 1097
fwUpdLabel
Ui::KbWidget, 591
Ui_KbWidget, 1097
fwUpdLayout
Ui::KbWidget, 591
Ui_KbWidget, 1098
fwUpdPath
Kb, 303
fwUpdate
Kb, 271
fwUpdateFinished
FwUpgradeDialog, 184
Kb, 272
fwUpdateProgress
FwUpgradeDialog, 185
Kb, 272
FwUpgradeDialog, 179
~FwUpgradeDialog, 182
blob, 187
cleanBlob, 182
closeEvent, 182
evLoop, 187
exec, 183
exitSuccess, 187
fwUpdateFinished, 184
fwUpdateProgress, 185
FwUpgradeDialog, 181
FwUpgradeDialog, 181
kb, 187
on_actionButton_clicked, 185
on_cancelButton_clicked, 186
removeDev, 186
saveBlob, 186
savePath, 187
ui, 188
fwVersion
KbFirmware::FW, 179
fwupgradedialog.cpp
DIALOG_HEIGHT_MAX, 1238
DIALOG_HEIGHT_MIN, 1239
DIALOG_WIDTH, 1239
ids, 1239
verifyFw, 1238

GB
KeyMap, 630
GB_DVORAK
KeyMap, 630
GUID
KbProfileDialog, 557
KbWidget, 584
get
CkbSettings, 129
getActualFileName
QuaZipFile, 878
getCaseSensitivity
QuaZipFile, 879
getComment
QuaZip, 827
getCommentCodec
QuaZip, 827
getCurrentFileInfo
QuaZip, 828, 829
getCurrentFileName
QuaZip, 830
getDefaultFileNameCodec
QuaZipPrivate, 922
getEntriesCount
QuaZip, 831
getFileInfo
QuaZipFile, 879, 880
getFileInfoList
QuaZip, 832
QuaZipPrivate, 922
getFileInfoList64
QuaZip, 832
getFileList
JlCompress, 252
getFileName
QuaGzipFile, 810
QuaZipFile, 881

getFileNameCodec
QuaZip, 833
getFileNameList
QuaZip, 833
getGradient
GradientDialog, 214
getIndicator
KbPerf, 512
getIoDevice
QuaZIODevice, 817
QuaZip, 834
getKeyMap
Kb, 273
getLayout
KeyMap, 636
getMacroNumber
Kb, 273
KbBind, 368
getMacroPath
Kb, 273
KbBind, 368
getMap
keymap.cpp, 1276
getMode
QuaZip, 834
getModel
KeyMap, 637, 638
getMuteState
media.h, 1301
media_linux.cpp, 1303
media_mac.m, 1304
getNTFSTime
quazipfileinfo.cpp, 1353
getNTFSaTime
QuaZipFileInfo64, 898
getNTFScTime
QuaZipFileInfo64, 899
getNTFSmTime
QuaZipFileInfo64, 899
getPermissions
QuaZipFileInfo, 894
QuaZipFileInfo64, 900
getUnzFile
QuaZip, 835
getZip
QuaZipFile, 881
getZipError
QuaZip, 836
QuaZipFile, 881
getZipFile
QuaZip, 837
getZipName
QuaZip, 837
QuaZipFile, 882
globalCache
ckbsettings.cpp, 1228
globalRemap
KbBind, 369
globalRemapTime
KbBind, 389
globalSettings
ckbsettings.cpp, 1227
globalThread
ckbsettings.cpp, 1228
goToFirstFile
QuaZip, 838
goToFirstUnmappedFile
QuaZipPrivate, 923
goToNextFile
QuaZip, 839
gradient
GradientDialog::Preset, 787
GradientButton, 194
_alpha, 200
_stops, 200
fromString, 196
GradientButton, 196
gradientChanged, 197
GradientButton, 196
pickGradient, 197
toString, 198
updateImage, 199
gradientChanged
GradientButton, 197
GradientDialog, 208
~GradientDialog, 212
addPreset, 212
colorChanged, 213
currentChanged, 213
currentPreset, 220
getGradient, 214
GradientDialog, 211
GradientDialog, 211
makeIcon, 215
on_presetDelete_clicked, 216
on_presetList_currentItemChanged, 216
on_presetName_textEdited, 217
on_presetSave_clicked, 217
on_stopOpacity_valueChanged, 218
on_stopPos_valueChanged, 218
presets, 220
setPreset, 218
ui, 221
updatePresets, 219
GradientDialog::Preset, 786
builtIn, 787
gradient, 787
name, 787
Preset, 787
GradientDialogWidget, 221
_colors, 236
_current, 236
_stops, 236
colorAt, 224
current, 225
currentChanged, 225

fillRect, 225
GradientDialogWidget, 224
GradientDialogWidget, 224
makeStops, 226
mouseMoveEvent, 227
mousePressEvent, 228
mouseReleaseEvent, 228
moveCurrent, 229
paintEvent, 230
selected, 236
selectedOffset, 236
selectedPos, 236
selectedStop, 231
selectionColors, 232
setCurrentColor, 232
setStops, 233
stopCount, 234
stopRect, 234
stops, 235
gradientdialog.cpp
prefsPath, 1242
gridLayout
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 91
Ui::ExtraSettingsWidget, 166
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 205
Ui::KbAnimWidget, 339
Ui::KbBindWidget, 394
Ui::KbLightWidget, 454
Ui::KbProfileDialog, 561
Ui::KbWidget, 591
Ui::KPerfWidget, 685
Ui::LayoutDialog, 710
Ui::MainWindow, 726
Ui::ModeSelectDialog, 744
Ui::MPerfWidget, 761
Ui::RebindWidget, 944
Ui::SettingsWidget, 1014
Ui_AnimAddDialog, 1024
Ui_AnimSettingDialog, 1033
Ui_ExtraSettingsWidget, 1046
Ui_FwUpgradeDialog, 1055
Ui_GradientDialog, 1061
Ui_KbAnimWidget, 1070
Ui_KbBindWidget, 1077
Ui_KbLightWidget, 1085
Ui_KbProfileDialog, 1090
Ui_KbWidget, 1098
Ui_KPerfWidget, 1112
Ui_LayoutDialog, 1124
Ui_MainWindow, 1128
Ui_ModeSelectDialog, 1132
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1169
Ui_SettingsWidget, 1189
gridLayout_10
Ui::RebindWidget, 944
Ui_RebindWidget, 1169
gridLayout_2
Ui::AnimSettingDialog, 92
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 205
Ui::KbAnimWidget, 339
Ui::KbBindWidget, 394
Ui::KbLightWidget, 454
Ui::KbWidget, 591
Ui::RebindWidget, 945
Ui_AnimSettingDialog, 1033
Ui_FwUpgradeDialog, 1055
Ui_GradientDialog, 1061
Ui_KbAnimWidget, 1070
Ui_KbBindWidget, 1077
Ui_KbLightWidget, 1085
Ui_KbWidget, 1098
Ui_RebindWidget, 1169
gridLayout_3
Ui::GradientDialog, 205
Ui::KbAnimWidget, 339
Ui::KbWidget, 591
Ui::RebindWidget, 945
Ui::SettingsWidget, 1014
Ui_GradientDialog, 1061
Ui_KbAnimWidget, 1070
Ui_KbWidget, 1098
Ui_RebindWidget, 1170
Ui_SettingsWidget, 1189
gridLayout_4
Ui::KbAnimWidget, 339
Ui::KbLightWidget, 454
Ui::KbWidget, 591
Ui::RebindWidget, 945
Ui_KbAnimWidget, 1070
Ui_KbLightWidget, 1085
Ui_KbWidget, 1098
Ui_RebindWidget, 1170
gridLayout_5
Ui::KbWidget, 591
Ui::RebindWidget, 945
Ui::SettingsWidget, 1014
Ui_KbWidget, 1098
Ui_RebindWidget, 1170
Ui_SettingsWidget, 1189
gridLayout_7
Ui::KbWidget, 591
Ui_KbWidget, 1098
gridLayout_8
Ui::RebindWidget, 945
Ui_RebindWidget, 1170
groupBox
Ui::RebindWidget, 945
Ui_RebindWidget, 1170
groupBox_2
Ui::GradientDialog, 206
Ui::RebindWidget, 945
Ui_GradientDialog, 1062

Ui_RebindWidget, 1170
groupBox_3
Ui::RebindWidget, 945
Ui_RebindWidget, 1170
groupBox_4
Ui::RebindWidget, 945
Ui_RebindWidget, 1170
groups
CkbSettings, 136
guid
AnimScript, 64
KbAnim, 315
UsbId, 1197
guidString
UsbId, 1194, 1195

HIGH
KbPerf, 499
HW_IMAX
KbPerf, 500
hLine
AnimSettingDialog, 107
HW_I_COUNT
KbPerf, 529
KPerfWidget, 705
HWMODE_MAX
Kb, 303
handleNotificationChannel
KbBind, 370
hasCurrentFile
QuaZip, 840
hasCurrentFile_f
QuaZipPrivate, 925
hasDownloaded
KbFirmware, 415
hasFrame
AnimScript, 64
hasGPG
KbFirmware, 418
hasKeypress
AnimScript, 65
hasLed
Key, 596
hasParam
AnimScript, 65
hasParameter
KbAnim, 315
hasRepeat
AnimSettingDialog, 117
hasScan
Key, 596
hasShownNewFW
KbWidget, 584
hash
KbFirmware::FW, 179
height
KbPerf, 499
Key, 596
KeyMap, 638
helpStatus
RebindWidget, 964
horizontalLayout
Ui::AnimAddDialog, 51
Ui::ExtraSettingsWidget, 166
Ui::GradientDialog, 206
Ui::KbAnimWidget, 339
Ui::KbLightWidget, 455
Ui::KPerfWidget, 685
Ui::MPerfWidget, 761
Ui::RebindWidget, 946
Ui::SettingsWidget, 1014
Ui_AnimAddDialog, 1024
Ui_ExtraSettingsWidget, 1046
Ui_GradientDialog, 1062
Ui_KbAnimWidget, 1070
Ui_KbLightWidget, 1085
Ui_KPerfWidget, 1112
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1170
Ui_SettingsWidget, 1189
horizontalLayout_2
Ui::ExtraSettingsWidget, 166
Ui::GradientDialog, 206
Ui::KbBindWidget, 394
Ui::KbLightWidget, 455
Ui::KPerfWidget, 685
Ui::MPerfWidget, 761
Ui::RebindWidget, 946
Ui::SettingsWidget, 1014
Ui_ExtraSettingsWidget, 1047
Ui_GradientDialog, 1062
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1085
Ui_KPerfWidget, 1112
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1171
Ui_SettingsWidget, 1189
horizontalLayout_3
Ui::KbLightWidget, 455
Ui::RebindWidget, 946
Ui_KbLightWidget, 1085
Ui_RebindWidget, 1171
horizontalLayout_4
Ui::MPerfWidget, 761
Ui_MPerfWidget, 1145
horizontalSpacer
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 92
Ui::ExtraSettingsWidget, 166
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 206
Ui::KbAnimWidget, 339
Ui::KbBindWidget, 394
Ui::KbProfileDialog, 561
Ui::KPerfWidget, 685
Ui::LayoutDialog, 710
Ui::MPerfWidget, 761

Ui::RebindWidget, 946
Ui::SettingsWidget, 1015
Ui_AnimAddDialog, 1024
Ui_AnimSettingDialog, 1033
Ui_ExtraSettingsWidget, 1047
Ui_FwUpgradeDialog, 1055
Ui_GradientDialog, 1062
Ui_KbAnimWidget, 1071
Ui_KbBindWidget, 1078
Ui_KbProfileDialog, 1091
Ui_KPerfWidget, 1112
Ui_LayoutDialog, 1124
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1171
Ui_SettingsWidget, 1189
horizontalSpacer_10
Ui::RebindWidget, 946
Ui::SettingsWidget, 1015
Ui_RebindWidget, 1171
Ui_SettingsWidget, 1189
horizontalSpacer_11
Ui::RebindWidget, 946
Ui_RebindWidget, 1171
horizontalSpacer_12
Ui::RebindWidget, 946
Ui_RebindWidget, 1171
horizontalSpacer_13
Ui::RebindWidget, 946
Ui_RebindWidget, 1171
horizontalSpacer_14
Ui::RebindWidget, 946
Ui_RebindWidget, 1171
horizontalSpacer_15
Ui::RebindWidget, 947
Ui_RebindWidget, 1171
horizontalSpacer_16
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_17
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_18
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_19
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_2
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 92
Ui::ExtraSettingsWidget, 166
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 206
Ui::KbAnimWidget, 340
Ui::KbBindWidget, 394
Ui::KbProfileDialog, 561
Ui::KbWidget, 591
Ui::KPerfWidget, 686
Ui::LayoutDialog, 710
Ui::MPerfWidget, 761
Ui::RebindWidget, 947
Ui::SettingsWidget, 1015
Ui_AnimAddDialog, 1024
Ui_AnimSettingDialog, 1033
Ui_ExtraSettingsWidget, 1047
Ui_FwUpgradeDialog, 1055
Ui_GradientDialog, 1062
Ui_KbAnimWidget, 1071
Ui_KbBindWidget, 1078
Ui_KbProfileDialog, 1091
Ui_KbWidget, 1098
Ui_KPerfWidget, 1112
Ui_LayoutDialog, 1124
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1172
Ui_SettingsWidget, 1189
horizontalSpacer_20
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_21
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_22
Ui::RebindWidget, 947
Ui_RebindWidget, 1172
horizontalSpacer_23
Ui::RebindWidget, 948
Ui_RebindWidget, 1172
horizontalSpacer_24
Ui::RebindWidget, 948
Ui_RebindWidget, 1173
horizontalSpacer_25
Ui::RebindWidget, 948
Ui_RebindWidget, 1173
horizontalSpacer_26
Ui::RebindWidget, 948
Ui_RebindWidget, 1173
horizontalSpacer_3
Ui::AnimSettingDialog, 92
Ui::ExtraSettingsWidget, 166
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 206
Ui::KbAnimWidget, 340
Ui::KbLightWidget, 455
Ui::KbWidget, 592
Ui::KPerfWidget, 686
Ui::MPerfWidget, 762
Ui::RebindWidget, 948
Ui_AnimSettingDialog, 1033
Ui_ExtraSettingsWidget, 1047
Ui_FwUpgradeDialog, 1055
Ui_GradientDialog, 1062
Ui_KbAnimWidget, 1071
Ui_KbLightWidget, 1085
Ui_KbWidget, 1098
Ui_KPerfWidget, 1112

Ui_MPerfWidget, 1145
Ui_RebindWidget, 1173
horizontalSpacer_4
Ui::AnimSettingDialog, 92
Ui::FwUpgradeDialog, 193
Ui::KbAnimWidget, 340
Ui::KbLightWidget, 455
Ui::KPerfWidget, 686
Ui::MPerfWidget, 762
Ui::RebindWidget, 948
Ui_AnimSettingDialog, 1033
Ui_FwUpgradeDialog, 1055
Ui_KbAnimWidget, 1071
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1112
Ui_MPerfWidget, 1145
Ui_RebindWidget, 1173
horizontalSpacer_5
Ui::AnimSettingDialog, 92
Ui::KbAnimWidget, 340
Ui::KbLightWidget, 455
Ui::KPerfWidget, 686
Ui::MPerfWidget, 762
Ui::RebindWidget, 948
Ui_AnimSettingDialog, 1033
Ui_KbAnimWidget, 1071
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1113
Ui_MPerfWidget, 1146
Ui_RebindWidget, 1173
horizontalSpacer_6
Ui::AnimSettingDialog, 92
Ui::KbLightWidget, 455
Ui::KPerfWidget, 686
Ui::MPerfWidget, 762
Ui::RebindWidget, 948
Ui_AnimSettingDialog, 1033
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1113
Ui_MPerfWidget, 1146
Ui_RebindWidget, 1173
horizontalSpacer_7
Ui::KPerfWidget, 686
Ui::MPerfWidget, 762
Ui::RebindWidget, 948
Ui::SettingsWidget, 1015
Ui_KPerfWidget, 1113
Ui_MPerfWidget, 1146
Ui_RebindWidget, 1173
Ui_SettingsWidget, 1190
horizontalSpacer_8
Ui::KPerfWidget, 686
Ui::RebindWidget, 949
Ui_KPerfWidget, 1113
Ui_RebindWidget, 1173
horizontalSpacer_9
Ui::RebindWidget, 949
Ui::SettingsWidget, 1015
Ui_RebindWidget, 1174
Ui_SettingsWidget, 1190
hwIType
KbPerf, 529
hwLoading
Kb, 303
HwMode
KPerfWidget, 698
hwModeCount
Kb, 303
hwModified
UsbId, 1197
hwModifiedString
UsbId, 1195
hwProfile
Kb, 274
hwSave
Kb, 275
hwSaveButton
Ui::KbWidget, 592
Ui_KbWidget, 1099

IT
KeyMap, 630
I_COUNT
KbPerf, 529
KPerfWidget, 705
i_hw
KbPerf, 499
KPerfWidget, 697
iButton0
Ui::MPerfWidget, 762
Ui_MPerfWidget, 1146
iButton1
Ui::MPerfWidget, 762
Ui_MPerfWidget, 1146
iButton2
Ui::MPerfWidget, 762
Ui_MPerfWidget, 1146
iButton3
Ui::MPerfWidget, 762
Ui_MPerfWidget, 1146
iButton4
Ui::MPerfWidget, 763
Ui_MPerfWidget, 1146
iButton5
Ui::MPerfWidget, 763
Ui_MPerfWidget, 1146
iButtonO
Ui::MPerfWidget, 763
Ui_MPerfWidget, 1147
iColor
KbPerf, 529
iEnable
KbPerf, 529
iOpacity
KbPerf, 513
iState
Kb, 303

iconClicked
MainWindow, 733
id
KbMode, 488
KbProfile, 537
ids
fwupgradedialog.cpp, 1239
inFrame
AnimScript, 82
indexOf
Kb, 276
KbProfile, 538
indicBox
Ui::MPerfWidget, 763
Ui_MPerfWidget, 1147
indicator
KbPerf, 500
KPerfWidget, 698
indicators
KPerfWidget, 706
infoTab
Ui::AnimSettingDialog, 92
Ui_AnimSettingDialog, 1033
infoUpdated
Kb, 277
init
AnimScript, 66
ColorMap, 155
KbManager, 476
init_keys
crypt.h, 1312
init_linkedlist
zip.c, 1444
initManager
KbFirmware, 415
initialized
AnimScript, 82
insert
KbProfile, 538
instance
KbFirmware, 418
intensityBox
Ui::KPerfWidget, 686
Ui_KPerfWidget, 1113
internal
QuaZipFilePrivate, 907
internalAttr
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
QuaZipNewInfo, 917
ioDevice
QuaZipPrivate, 925
ioapi.h
_FILE_OFFSET_BIT, 1317
_LARGEFILE64_SOURCE, 1318
_Z_OF, 1320
__USE_LARGEFILE64, 1317
fill_zlib_filefunc64_32_def_from_filefunc32, 1320
OF, 1318
ZCALLBACK, 1318
ZCLOSE64, 1318
ZERROR64, 1318
ZFAKECLOSE64, 1318
ZOPEN64, 1319
ZPOS64_T, 1320
ZREAD64, 1319
ZSEEK64, 1319
ZTELL64, 1320
ZWRITE64, 1320
zlib_filefunc64_32_def, 1320
zlib_filefunc64_def, 1320
zlib_filefunc_def, 1320
isActive
KbAnim, 316
isAnim
KeyAction, 608
isAutoClose
QuaZip, 840
isBusy
CkbSettings, 130
isDPI
KeyAction, 608
isDataDescriptorWritingEnabled
QuaZip, 840
isEnabled
AutoRun, 120
isEncrypted
QuaZipFileInfo64, 901
isISO
KbBind, 371
KeyMap, 638, 639
isKeyboard
Kb, 277
KbBind, 371
KeyMap, 639, 640
isMacro
KeyAction, 609
isMedia
KeyAction, 609
isMouse
Kb, 278
KbBind, 371
KeyAction, 609
KeyMap, 641
isNormal
KeyAction, 610
isOpen
Kb, 279
QuaZip, 841
isProgram
KeyAction, 610
isRaw
QuaZipFile, 882
isRoot
QuaZipDir, 865
isRunning

KbAnim, 316
main.cpp, 1294
isSequential
QuaGzipFile, 810
QuaZIODevice, 817
QuaZipFile, 883
isSetting
MPerfWidget, 785
isSpecial
KeyAction, 611
isStarted
KbLight, 435
isUnbound
KeyAction, 611
isValidMacro
KeyAction, 612
isZip64Enabled
QuaZip, 841

JlCompress, 237
compressDir, 238
compressFile, 239, 240
compressFiles, 241
compressSubDir, 243
extractDir, 246
extractFile, 248, 250
extractFiles, 251
getFileList, 252
removeFile, 253
JlCompress.cpp
copyData, 1322

K65
KeyMap, 630
K65_HEIGHT
keymap.cpp, 1273
K65_TOP_COUNT
keymap.cpp, 1273
K65_WIDTH
keymap.cpp, 1273
K65TopRow
keymap.cpp, 1279
K70
KeyMap, 630
K70_HEIGHT
keymap.cpp, 1273
K70_WIDTH
keymap.cpp, 1273
K70_X_START
keymap.cpp, 1273
K95
KeyMap, 630
K95_HEIGHT
keymap.cpp, 1273
K95_WIDTH
keymap.cpp, 1273
K95BaseMap
keymap.cpp, 1279
K95Keys
keymap.cpp, 1279
k95Label1
Ui::KPerfWidget, 686
Ui_KPerfWidget, 1113
k95Label2
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1113
k95Label3
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1113
k95Label4
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1113
k95Label5
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1114
k95Label6
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1114
k95Line
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1114
k95Spacer
Ui::KPerfWidget, 687
Ui_KPerfWidget, 1114
k95Widgets
KPerfWidget, 706
KPerfWidget
ALWAYS_OFF, 698
ALWAYS_ON, 698
BOTH, 698
NORMAL, 698
RGB, 698
KPerfWidget::IndicatorUi, 696, 1288
KEY_SIZE
keywidget.cpp, 1286
KEYCOUNT_K95
keymap.cpp, 1273
KEYCOUNT_M65
keymap.cpp, 1274
KEYCOUNT_SABRE
keymap.cpp, 1274
KEYCOUNT_SCIM
keymap.cpp, 1274
KP_NAME
AnimScript, 82
KP_NONE
AnimScript, 82
KP_POSITION
AnimScript, 82
kPerfTab
Ui::KbWidget, 592
Ui_KbWidget, 1099
KPerfWidget, 693
~KPerfWidget, 700
HW_I_COUNT, 705
HwMode, 698
I_COUNT, 705

i_hw, 697
indicator, 698
indicators, 706
k95Widgets, 706
KPerfWidget, 698
KPerfWidget, 698
mode2Raw, 700
on_copyButton_clicked, 701
on_intensityBox_valueChanged, 701
perf, 706
profile, 706
raw2Mode, 702
setPerf, 702
ui, 706
uiUpdated, 704
updateMapper, 706
kPerfWidget
Ui::KbWidget, 592
Ui_KbWidget, 1099
KSTRAFE_HEIGHT
keymap.cpp, 1274
KSTRAFE_WIDTH
keymap.cpp, 1274
KSTRAFE_X_START
keymap.cpp, 1274
KStrafeKeys
keymap.cpp, 1280
Kb, 255
~Kb, 260
_currentMode, 301
_currentProfile, 301
_delay, 301
_dither, 301
_frameRate, 301
_hwProfile, 301
_layout, 302
_model, 302
_mouseAccel, 302
_needsSave, 302
_profiles, 302
_scrollSpeed, 302
appendProfile, 263
autoSave, 263
cmd, 302
cmdpath, 302
currentBind, 263
currentLight, 264
currentMode, 265
currentPerf, 265
currentProfile, 266
deleteHw, 266
deletePrevious, 267
devpath, 302
dither, 267, 268
features, 303
find, 268
firmware, 303
frameRate, 269
frameUpdate, 270
fwUpdPath, 303
fwUpdate, 271
fwUpdateFinished, 272
fwUpdateProgress, 272
getKeyMap, 273
getMacroNumber, 273
getMacroPath, 273
HWMODE_MAX, 303
hwLoading, 303
hwModeCount, 303
hwProfile, 274
hwSave, 275
iState, 303
indexOf, 276
infoUpdated, 277
isKeyboard, 277
isMouse, 278
isOpen, 279
Kb, 260
KbManager, 301
lastAutoSave, 303
layout, 279
load, 280
macroDelay, 281
macroNumber, 303
macroPath, 304
matches, 282
modeChanged, 282
modeRenamed, 283
model, 282
monochrome, 304
mouseAccel, 283
needsSave, 284
newMode, 284, 285
newProfile, 285, 286
notifyNumber, 304
notifyPath, 304
pollrate, 304
prefsPath, 304
prevMode, 304
prevProfile, 304
profileAdded, 287
profileChanged, 287
profileRenamed, 287
profiles, 288
readNotify, 289
run, 293
save, 294
scrollSpeed, 295
setCurrentMode, 296, 297
setCurrentProfile, 298
updateLayout, 299
usbModel, 304
usbSerial, 305
writeProfileHeader, 300
kb
FwUpgradeDialog, 187

kb.cpp
activeDevices, 1245
notifyPathMutex, 1245
notifyPaths, 1245
KbAnim
Add, 308
Divide, 309
Multiply, 308
Normal, 308
Subtract, 308
KbFirmware
NO, 410
UNKNOWN, 410
YES, 410
KbId, 1237
KbPerf
CAPS, 500
HIGH, 499
HW_IMAX, 500
LIGHT, 500
LOCK, 500
LOW, 499
LOWMED, 499
MACRO, 500
MEDHIGH, 499
MEDIUM, 499
MODE, 500
MUTE, 500
NONE, 500
NORMAL, 500
NUM, 500
OFF, 500
ON, 500
SCROLL, 500
KbAnim, 305
_guid, 330
_isActive, 330
_isActiveKp, 330
_keys, 330
_map, 330
_mode, 330
_name, 330
_needsSave, 330
_opacity, 331
_parameters, 331
_script, 331
_scriptGuid, 331
_scriptName, 331
_tempParameters, 331
blend, 311
catchUp, 312
commitParams, 314
effectiveParams, 314
guid, 315
hasParameter, 315
isActive, 316
isRunning, 316
KbAnim, 309–311
KbAnim, 309–311
keypress, 317
keys, 318, 319
kpRepeatMsec, 331
kpRepeatTime, 331
kpStopTime, 331
map, 319, 320
Mode, 308
mode, 320
name, 320, 321
needsSave, 321
newId, 322
opacity, 322
parameter, 322, 323
reInit, 324
repeatKey, 332
repeatMsec, 332
repeatTime, 332
resetParams, 324
save, 325
script, 326
scriptName, 326
stop, 327
stopTime, 332
trigger, 328
updateParams, 329
KbAnimWidget, 342
~KbAnimWidget, 345
addAnim, 345
animChanged, 346
animations, 359
clearSelection, 347
current, 359
didUpdateSelection, 347
duplicateAnim, 348
KbAnimWidget, 344
KbAnimWidget, 344
light, 359
noReorder, 359
on_animList_currentItemChanged, 348
on_animList_customContextMenuRequested, 349
on_animList_itemChanged, 350
on_blendBox_activated, 350
on_deleteButton_clicked, 351
on_keyButton_clicked, 351
on_nameBox_textEdited, 352
on_opacityBox_valueChanged, 353
on_propertyButton_clicked, 353
refreshList, 354
reorderAnims, 355
selectedKeys, 359
setCurrent, 356
setLight, 357
setSelectedKeys, 358
ui, 359
KbBind, 360
_bind, 388
_devParent, 388

_globalRemap, 388
_map, 388
_needsSave, 388
_needsUpdate, 388
_winLock, 388
action, 364
bindAction, 364
defaultAction, 365
devParent, 366
didLoad, 366
friendlyActionName, 367
friendlyName, 367
getMacroNumber, 368
getMacroPath, 368
globalRemap, 369
globalRemapTime, 389
handleNotificationChannel, 370
isISO, 371
isKeyboard, 371
isMouse, 371
KbBind, 363
KbBind, 363
KeyAction, 388
keyEvent, 372
lastCmd, 389
lastGlobalRemapTime, 389
layoutChanged, 373
light, 374
load, 374
loadGlobalRemap, 375
map, 376, 377
modeParent, 377
needsSave, 377
noAction, 378
perf, 379
resetAction, 380
save, 381
saveGlobalRemap, 382
setAction, 383
setGlobalRemap, 384
setNeedsUpdate, 385
update, 385
updated, 387
winLock, 387
KbBindWidget, 396
~KbBindWidget, 399
bind, 407
currentSelection, 407
KbBindWidget, 399
KbBindWidget, 399
newLayout, 400
newSelection, 401
on_copyButton_clicked, 402
on_resetButton_clicked, 402
profile, 407
setBind, 403
ui, 407
updateBind, 404
updateSelDisplay, 406
kbConnected
KbManager, 477
kbDisconnected
KbManager, 477
KbFirmware, 407
~KbFirmware, 410
_checkUpdates, 410
_fileForBoard, 411
_latestForBoard, 412
checkUpdates, 413
dataForBoard, 413
downloadFinished, 414
downloaded, 414
fwTable, 418
fwTableHash, 418
hasDownloaded, 415
hasGPG, 418
initManager, 415
instance, 418
KbFirmware, 410
KbFirmware, 410
lastCheck, 418
lastFinished, 418
networkManager, 418
processDownload, 416
tableDownload, 419
versionForBoard, 417
KbFirmware::FW, 178
ckbVersion, 179
FW, 179
fileName, 179
fwVersion, 179
hash, 179
url, 179
KbLight, 419
~KbLight, 424
_animList, 446
_animMap, 446
_colorMap, 447
_dimming, 447
_indicatorList, 447
_indicatorMap, 447
_map, 447
_needsMapRefresh, 447
_needsSave, 447
_previewAnim, 447
_qColorMap, 447
_start, 448
addAnim, 424
animKeypress, 424
AnimList, 423
animList, 425, 426
base, 426
close, 427
color, 428
colorMap, 429
didLoad, 429

dimming, 430
duplicateAnim, 431
findAnim, 431
findAnimIdx, 432
frameDisplayed, 433
frameUpdate, 433
isStarted, 435
KbLight, 423
KbLight, 423
lastFrameSignal, 448
load, 435
MAX_DIM, 448
map, 437
needsSave, 438
open, 438
previewAnim, 439
printRGB, 440
rebuildBaseMap, 441
resetIndicators, 442
restartAnimation, 442
save, 443
setIndicator, 444
shareDimming, 444, 445
stopPreview, 445
updated, 446
KbLightWidget, 457
~KbLightWidget, 459
changeAnim, 460
changeAnimKeys, 460
changeColor, 461
currentSelection, 469
KbLightWidget, 459
KbLightWidget, 459
light, 469
newSelection, 462
on_animButton_clicked, 463
on_bgButton_clicked, 464
on_brightnessBox_activated, 464
on_showAnimBox_clicked, 465
setLight, 465
setMonochrome, 466
toggleSidelight, 467
ui, 469
updateLight, 468
KbManager, 470
_daemonVersion, 481
_devices, 481
_eventTimer, 481
_guiVersion, 481
_kbManager, 482
_scanTimer, 482
ckbDaemonVersion, 473
ckbDaemonVersionF, 473
ckbGuiVersion, 474
ckbGuiVersionF, 474
devices, 475
eventTimer, 475
fps, 475
init, 476
Kb, 301
kbConnected, 477
kbDisconnected, 477
KbManager, 472
kbManager, 477
KbManager, 472
parseVersionString, 478
scanKeyboards, 478
scanTimer, 480
stop, 480
versionUpdated, 481
kbManager
KbManager, 477
KbMode, 482
~KbMode, 487
_bind, 495
_id, 495
_light, 495
_name, 495
_needsSave, 495
_perf, 495
bind, 487
doUpdate, 487
id, 488
KbMode, 485, 486
KbMode, 485, 486
keyMap, 489
light, 489
name, 490
needsSave, 491
newId, 491
perf, 492
save, 492
setNeedsSave, 493
setNeedsUpdate, 494
updated, 494
KbPerf, 496
_angleSnap, 527
_curDpi, 502
_dpiIndicator, 527
_iOpacity, 527
_liftHeight, 527
_needsSave, 527
_needsUpdate, 528
angleSnap, 502, 503
applyIndicators, 503
bind, 504
curDpi, 505, 506
curDpiIdx, 506, 507
DPI_COUNT, 528
DPI_MAX, 528
DPI_MIN, 528
didLoad, 507
dpi, 508
dpiClr, 528
dpiColor, 509, 510
dpiCurIdx, 528

dpiCurX, 528
dpiCurY, 528
dpiDown, 510
dpiEnabled, 511
dpiIndicator, 511, 512
dpiLastIdx, 528
dpiOn, 528
dpiUp, 512
dpiX, 529
dpiY, 529
getIndicator, 512
HW_I_COUNT, 529
height, 499
hwIType, 529
I_COUNT, 529
i_hw, 499
iColor, 529
iEnable, 529
iOpacity, 513
indicator, 500
KbPerf, 500, 501
KbPerf, 500, 501
liftHeight, 514
light, 514
light100Color, 529
lightIndicator, 515
load, 516
modeParent, 517
muteNAColor, 529
needsSave, 518
OTHER, 530
operator=, 518
popDpi, 519
pushDpi, 519, 520
pushSniper, 521
pushedDpis, 530
runningPushIdx, 530
SNIPER, 530
save, 522
setIndicator, 523
setNeedsUpdate, 523
settingsUpdated, 524
sniperDpi, 524, 525
update, 526
KbProfile, 530
_currentMode, 547
_id, 547
_keyMap, 547
_modes, 547
_name, 547
_needsSave, 547
append, 535
currentMode, 535, 536
find, 536
id, 537
indexOf, 538
insert, 538
KbProfile, 533, 534
KbProfile, 533, 534
keyMap, 539
modeCount, 540
ModeList, 533
modes, 540, 541
move, 541
name, 542
needsSave, 542
newId, 543
removeAll, 544
save, 545
setNeedsSave, 546
setNeedsUpdate, 546
KbProfileDialog, 548
~KbProfileDialog, 550
addNewProfileItem, 550
device, 556
GUID, 557
KbProfileDialog, 550
KbProfileDialog, 550
NEW_FLAG, 557
on_profileList_currentItemChanged, 551
on_profileList_customContextMenuRequested, 551
on_profileList_itemChanged, 553
on_profileList_itemClicked, 554
profileList_reordered, 554
repopulate, 555
ui, 557
KbWidget, 562
~KbWidget, 566
addNewModeItem, 566
currentMode, 583
devUpdate, 567
device, 583
GUID, 584
hasShownNewFW, 584
KbWidget, 564
KbWidget, 564
lastAutoSave, 584
modeChanged, 567
modeIcon, 569
modeUpdate, 571
modesList_reordered, 570
NEW_FLAG, 584
name, 571
on_fwUpdButton_clicked, 571
on_hwSaveButton_clicked, 573
on_modesList_currentItemChanged, 574
on_modesList_customContextMenuRequested, 575
on_modesList_itemChanged, 576
on_modesList_itemClicked, 577
on_profileBox_activated, 578
on_tabWidget_currentChanged, 578
profileChanged, 579
showFirstTab, 580
showFwUpdate, 580

showLastTab, 581
ui, 584
updateFwButton, 581
updateProfileList, 582
kbWidgets
MainWindow, 740
kbanim.cpp
blendAdd, 1247
blendDivide, 1247
blendFunc, 1247
blendMultiply, 1247
blendNormal, 1247
blendSubtract, 1248
functions, 1248
kbfirmware.cpp
AUTO_CHECK_TIME, 1254
tableName, 1254
kblight.cpp
_shareDimming, 1258
activeLights, 1258
IToS, 1256
monoRgb, 1256
sToL, 1257
kbmanager.cpp
devpath, 1261
kbperf.cpp
map_last, 1263
Key, 594
_friendlyName, 596
_storageName, 596
friendlyName, 595
hasLed, 596
hasScan, 596
height, 596
name, 597
operator bool, 595
storageName, 596
width, 597
x, 597
y, 597
key
KeyMap, 642
KeyAction
NORMAL, 601
SPECIAL, 601
UNBOUND, 601
KeyMap
_LAYOUT_MAX, 630
_MODEL_MAX, 631
DE, 630
DK, 630
ES, 630
EU, 630
EU_DVORAK, 630
FR, 630
GB, 630
GB_DVORAK, 630
IT, 630
K65, 630
K70, 630
K95, 630
M65, 631
MX, 630
NO, 630
NO_LAYOUT, 630
NO_MODEL, 630
PL, 630
SABRE, 631
SCIMITAR, 631
SE, 630
STRAFE, 631
US, 630
US_DVORAK, 630
KeyPatch, 1271
KeyWidget
ADD, 654
NONE, 654
SET, 654
SUBTRACT, 654
TOGGLE, 654
KeyAction, 597
~KeyAction, 602
_value, 624
adjustDisplay, 602
animAction, 603
animInfo, 604
DPI_CUSTOM, 624
DPI_DOWN, 624
DPI_SNIPER, 624
DPI_UP, 625
defaultAction, 604
dpiAction, 605
dpiInfo, 605
driverName, 606
friendlyName, 607
isAnim, 608
isDPI, 608
isMacro, 609
isMedia, 609
isMouse, 609
isNormal, 610
isProgram, 610
isSpecial, 611
isUnbound, 611
isValidMacro, 612
KbBind, 388
KeyAction, 602
keyEvent, 613
keyRelease, 616
KeyAction, 602
LIGHT_DOWN, 625
LIGHT_DOWN_WRAP, 625
LIGHT_UP, 625
LIGHT_UP_WRAP, 625
LOCK_OFF, 625
LOCK_ON, 625

LOCK_TOGGLE, 625
lightAction, 616
lockAction, 617
MODE_NEXT, 625
MODE_NEXT_WRAP, 626
MODE_PREV, 626
MODE_PREV_WRAP, 626
macroAction, 617
macroContent, 618
macroDisplay, 618
macroFullLine, 619
macroLine, 620
modeAction, 621
noAction, 621
operator QString, 621
operator=, 621
PROGRAM_PR_INDEF, 626
PROGRAM_PR_KPSTOP, 626
PROGRAM_PR_KRSTOP, 626
PROGRAM_PR_MULTI, 626
PROGRAM_RE_INDEF, 626
PROGRAM_RE_KPSTOP, 627
PROGRAM_RE_MULTI, 627
preProgram, 626
programAction, 621
programInfo, 622
relProgram, 627
sniperValue, 627
specialInfo, 623
Type, 601
type, 623
value, 624
keyButton
Ui::KbAnimWidget, 340
Ui_KbAnimWidget, 1071
keyEvent
KbBind, 372
KeyAction, 613
keyHeight
KeyMap, 650
keyLayout
KeyMap, 650
KeyMap, 627
_keys, 650
byPosition, 632
contains, 632
count, 633
friendlyName, 633
fromName, 634
fromStorage, 635
getLayout, 636
getModel, 637, 638
height, 638
isISO, 638, 639
isKeyboard, 639, 640
isMouse, 641
key, 642
keyHeight, 650
keyLayout, 650
KeyMap, 631
keyModel, 650
keyWidth, 650
KeyMap, 631
keys, 642
Layout, 630
layout, 643
layoutNames, 643
locale, 644
map, 645
Model, 630
model, 645
modelHeight, 645
modelWidth, 646
name, 646
operator const QHash< QString, Key > &, 647
positions, 647
strLayout, 648
strModel, 648
toStorage, 649
width, 649
keyMap
KbMode, 489
KbProfile, 539
KeyWidget, 672
keyModel
KeyMap, 650
keyNames
ColorMap, 156
keyRelease
KeyAction, 616
keyTab
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
KeyWidget, 650
_bindMap, 671
_colorMap, 671
_displayColorMap, 672
_indicators, 672
_monochrome, 672
_rgbMode, 672
animation, 672
BindMap, 653
bindMap, 654
clearAnimation, 655
clearSelection, 655
colorMap, 655, 656
displayColorMap, 656
drawInfo, 656
keyMap, 672
KeyWidget, 654
KeyWidget, 654
map, 657, 658
monochrome, 658, 659
mouseCurrentX, 672
mouseCurrentY, 672
mouseDownMode, 672

mouseDownX, 673
mouseDownY, 673
mouseMoveEvent, 659
mousePressEvent, 660
mouseReleaseEvent, 661
newSelection, 673
paintEvent, 662
rgbMode, 667, 668
selectAll, 668
selection, 673
selectionChanged, 669
setAnimation, 669
setAnimationToSelection, 670
setSelection, 670
sidelightToggled, 671
keyWidget
Ui::KbBindWidget, 395
Ui::KbLightWidget, 455
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1086
keyWidth
KeyMap, 650
keyaction.cpp
ANIM_KRSTOP, 1269
ANIM_ONCE, 1269
keymap.cpp
_patch, 1275
ANSI_ENTER_H, 1272
ANSI_ENTER_W, 1272
ANSI_ENTER_X, 1272
ANSI_ENTER_Y, 1272
ANSI_LSHIFT_W, 1272
ANSI_LSHIFT_X, 1273
getMap, 1276
K65_HEIGHT, 1273
K65_TOP_COUNT, 1273
K65_WIDTH, 1273
K65TopRow, 1279
K70_HEIGHT, 1273
K70_WIDTH, 1273
K70_X_START, 1273
K95_HEIGHT, 1273
K95_WIDTH, 1273
K95BaseMap, 1279
K95Keys, 1279
KEYCOUNT_K95, 1273
KEYCOUNT_M65, 1274
KEYCOUNT_SABRE, 1274
KEYCOUNT_SCIM, 1274
KSTRAFE_HEIGHT, 1274
KSTRAFE_WIDTH, 1274
KSTRAFE_X_START, 1274
KStrafeKeys, 1280
M65_HEIGHT, 1274
M65_WIDTH, 1274
M65Keys, 1281
N_LAYOUTS, 1274
N_MODELS, 1275
NS, 1275
PATCH_COUNT, 1275
patch, 1275
patchANSI, 1278
patchDE, 1281
patchDK, 1281
patchDvorak, 1281
patchES, 1281
patchEU, 1282
patchFR, 1282
patchISO, 1279
patchIT, 1282
patchMX, 1282
patchNO, 1282
patchSE, 1283
SABRE_HEIGHT, 1275
SABRE_WIDTH, 1275
SCIM_HEIGHT, 1275
SCIM_WIDTH, 1275
SabreKeys, 1283
ScimKeys, 1283
standardMaps, 1283
keypress
AnimScript, 67
KbAnim, 317
keys
KbAnim, 318, 319
KeyMap, 642
keywidget.cpp
KEY_SIZE, 1286
m65Overlay, 1286
monoRgb, 1285
sabOverlay, 1286
scimOverlay, 1286
kpDelayBox
Ui::AnimSettingDialog, 92
Ui_AnimSettingDialog, 1034
kpModeStopBox
Ui::AnimSettingDialog, 93
Ui_AnimSettingDialog, 1034
kpReleaseBox
Ui::AnimSettingDialog, 93
Ui_AnimSettingDialog, 1034
kpRepeatBox
Ui::AnimSettingDialog, 93
Ui_AnimSettingDialog, 1034
kpRepeatLabel
Ui::AnimSettingDialog, 93
Ui_AnimSettingDialog, 1034
kpRepeatLabel_2
Ui::AnimSettingDialog, 93
Ui_AnimSettingDialog, 1034
kpRepeatMsec
KbAnim, 331
kpRepeatTime
KbAnim, 331
kpStopCheck
AnimSettingDialog, 117

kpStopTime
KbAnim, 331

LIGHT
KbPerf, 500
LOCK
KbPerf, 500
LOW
KbPerf, 499
LOWMED
KbPerf, 499
lHeightBox
Ui::MPerfWidget, 765
Ui_MPerfWidget, 1148
LIGHT_DOWN
KeyAction, 625
LIGHT_DOWN_WRAP
KeyAction, 625
LIGHT_UP
KeyAction, 625
LIGHT_UP_WRAP
KeyAction, 625
LOCALHEADERMAGIC
zip.c, 1439
LOCK_OFF
KeyAction, 625
LOCK_ON
KeyAction, 625
LOCK_TOGGLE
KeyAction, 625
lToS
kblight.cpp, 1256
label
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 93
Ui::ExtraSettingsWidget, 166
Ui::GradientDialog, 206
Ui::KbBindWidget, 395
Ui::KbLightWidget, 455
Ui::KPerfWidget, 687
Ui::LayoutDialog, 710
Ui::ModeSelectDialog, 744
Ui::MPerfWidget, 763
Ui::SettingsWidget, 1015
Ui_AnimAddDialog, 1025
Ui_AnimSettingDialog, 1034
Ui_ExtraSettingsWidget, 1047
Ui_GradientDialog, 1062
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1114
Ui_LayoutDialog, 1124
Ui_ModeSelectDialog, 1132
Ui_MPerfWidget, 1147
Ui_SettingsWidget, 1190
label_10
Ui::AnimSettingDialog, 93
Ui::ExtraSettingsWidget, 166
Ui::KPerfWidget, 687
Ui_AnimSettingDialog, 1034
Ui_ExtraSettingsWidget, 1047
Ui_KPerfWidget, 1114
label_11
Ui::AnimSettingDialog, 93
Ui::ExtraSettingsWidget, 166
Ui::KPerfWidget, 688
Ui::MPerfWidget, 763
Ui_AnimSettingDialog, 1034
Ui_ExtraSettingsWidget, 1047
Ui_KPerfWidget, 1114
Ui_MPerfWidget, 1147
label_12
Ui::AnimSettingDialog, 93
Ui::KPerfWidget, 688
Ui::MPerfWidget, 763
Ui_AnimSettingDialog, 1035
Ui_KPerfWidget, 1114
Ui_MPerfWidget, 1147
label_13
Ui::AnimSettingDialog, 94
Ui::MPerfWidget, 763
Ui_AnimSettingDialog, 1035
Ui_MPerfWidget, 1147
label_14
Ui::KPerfWidget, 688
Ui::MPerfWidget, 763
Ui_KPerfWidget, 1114
Ui_MPerfWidget, 1147
label_15
Ui::KPerfWidget, 688
Ui::MPerfWidget, 764
Ui_KPerfWidget, 1115
Ui_MPerfWidget, 1147
label_16
Ui::KPerfWidget, 688
Ui_KPerfWidget, 1115
label_17
Ui::KPerfWidget, 688
Ui_KPerfWidget, 1115
label_18
Ui::KPerfWidget, 688
Ui_KPerfWidget, 1115
label_19
Ui::KPerfWidget, 688
Ui_KPerfWidget, 1115
label_2
Ui::AnimAddDialog, 51
Ui::AnimSettingDialog, 94
Ui::ExtraSettingsWidget, 167
Ui::FwUpgradeDialog, 193
Ui::GradientDialog, 206
Ui::KbBindWidget, 395
Ui::KbLightWidget, 456
Ui::KPerfWidget, 688
Ui::LayoutDialog, 711
Ui::MPerfWidget, 764
Ui::SettingsWidget, 1015

Ui_AnimAddDialog, 1025
Ui_AnimSettingDialog, 1035
Ui_ExtraSettingsWidget, 1047
Ui_FwUpgradeDialog, 1056
Ui_GradientDialog, 1062
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1115
Ui_LayoutDialog, 1125
Ui_MPerfWidget, 1147
Ui_SettingsWidget, 1190
label_20
Ui::KPerfWidget, 689
Ui_KPerfWidget, 1115
label_21
Ui::KPerfWidget, 689
Ui_KPerfWidget, 1115
label_22
Ui::KPerfWidget, 689
Ui_KPerfWidget, 1115
label_23
Ui::KPerfWidget, 689
Ui_KPerfWidget, 1116
label_24
Ui::KPerfWidget, 689
Ui_KPerfWidget, 1116
label_25
Ui::MPerfWidget, 764
Ui_MPerfWidget, 1148
label_3
Ui::AnimSettingDialog, 94
Ui::ExtraSettingsWidget, 167
Ui::KbLightWidget, 456
Ui::KbWidget, 592
Ui::KPerfWidget, 689
Ui::MPerfWidget, 764
Ui::SettingsWidget, 1015
Ui_AnimSettingDialog, 1035
Ui_ExtraSettingsWidget, 1047
Ui_KbLightWidget, 1086
Ui_KbWidget, 1099
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
Ui_SettingsWidget, 1190
label_4
Ui::AnimSettingDialog, 94
Ui::FwUpgradeDialog, 193
Ui::KbWidget, 592
Ui::KPerfWidget, 689
Ui::MPerfWidget, 764
Ui_AnimSettingDialog, 1035
Ui_FwUpgradeDialog, 1056
Ui_KbWidget, 1099
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
label_5
Ui::AnimSettingDialog, 94
Ui::ExtraSettingsWidget, 167
Ui::KbAnimWidget, 340
Ui::KPerfWidget, 689
Ui::MPerfWidget, 764
Ui::SettingsWidget, 1015
Ui_AnimSettingDialog, 1035
Ui_ExtraSettingsWidget, 1048
Ui_KbAnimWidget, 1071
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
Ui_SettingsWidget, 1190
label_6
Ui::AnimSettingDialog, 94
Ui::ExtraSettingsWidget, 167
Ui::KbAnimWidget, 340
Ui::KPerfWidget, 689
Ui::MPerfWidget, 764
Ui::SettingsWidget, 1016
Ui_AnimSettingDialog, 1035
Ui_ExtraSettingsWidget, 1048
Ui_KbAnimWidget, 1071
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
Ui_SettingsWidget, 1190
label_7
Ui::AnimSettingDialog, 94
Ui::KbAnimWidget, 340
Ui::KPerfWidget, 690
Ui::MPerfWidget, 764
Ui_AnimSettingDialog, 1035
Ui_KbAnimWidget, 1071
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
label_8
Ui::AnimSettingDialog, 94
Ui::KPerfWidget, 690
Ui::MPerfWidget, 764
Ui::SettingsWidget, 1016
Ui_AnimSettingDialog, 1035
Ui_KPerfWidget, 1116
Ui_MPerfWidget, 1148
Ui_SettingsWidget, 1190
label_9
Ui::AnimSettingDialog, 94
Ui::KbWidget, 592
Ui_AnimSettingDialog, 1036
Ui_KbWidget, 1099
lastAutoSave
Kb, 303
KbWidget, 584
lastCheck
KbFirmware, 418
lastCmd
KbBind, 389
lastDuration
AnimSettingDialog, 117
lastFinished
KbFirmware, 418
lastFrame

AnimScript, 82
lastFrameSignal
KbLight, 448
lastGlobalRemapTime
KbBind, 389
lastMappedDirectoryEntry
QuaZipPrivate, 925
lastSharedDimming
extrasettingswidget.cpp, 1235
Layout
KeyMap, 630
layout
Kb, 279
KeyMap, 643
layoutBox
Ui::SettingsWidget, 1016
Ui_SettingsWidget, 1190
layoutChanged
KbBind, 373
LayoutDialog, 711
~LayoutDialog, 713
LayoutDialog, 713
LayoutDialog, 713
selected, 714
ui, 714
layoutNames
KeyMap, 643
layoutWidget
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
layoutWidget1
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
layoutWidget_2
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
lbl_macro
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
license
AnimScript, 68
liftHeight
KbPerf, 514
light
KbAnimWidget, 359
KbBind, 374
KbLightWidget, 469
KbMode, 489
KbPerf, 514
light100Color
KbPerf, 529
lightAction
KeyAction, 616
lightBox
Ui::KPerfWidget, 690
Ui::RebindWidget, 949
Ui_KPerfWidget, 1116
Ui_RebindWidget, 1174
lightButton
Ui::RebindWidget, 949
Ui_RebindWidget, 1174
lightColor1
Ui::KPerfWidget, 690
Ui_KPerfWidget, 1117
lightColor2
Ui::KPerfWidget, 690
Ui_KPerfWidget, 1117
lightColor3
Ui::KPerfWidget, 690
Ui_KPerfWidget, 1117
lightIndicator
KbPerf, 515
lightTab
Ui::KbWidget, 592
Ui_KbWidget, 1099
lightWidget
Ui::KbWidget, 592
Ui_KbWidget, 1099
lightWrapBox
Ui::RebindWidget, 950
Ui_RebindWidget, 1174
line
Ui::AnimSettingDialog, 95
Ui::ExtraSettingsWidget, 167
Ui::KbBindWidget, 395
Ui::KbLightWidget, 456
Ui::KPerfWidget, 690
Ui::MPerfWidget, 765
Ui::SettingsWidget, 1016
Ui_AnimSettingDialog, 1036
Ui_ExtraSettingsWidget, 1048
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1117
Ui_MPerfWidget, 1148
Ui_SettingsWidget, 1191
line_2
Ui::AnimSettingDialog, 95
Ui::ExtraSettingsWidget, 167
Ui::KbBindWidget, 395
Ui::KbLightWidget, 456
Ui::KPerfWidget, 690
Ui::MPerfWidget, 765
Ui::SettingsWidget, 1016
Ui_AnimSettingDialog, 1036
Ui_ExtraSettingsWidget, 1048
Ui_KbBindWidget, 1078
Ui_KbLightWidget, 1086
Ui_KPerfWidget, 1117
Ui_MPerfWidget, 1149
Ui_SettingsWidget, 1191
line_3
Ui::ExtraSettingsWidget, 167
Ui::KPerfWidget, 690
Ui::MPerfWidget, 765
Ui::SettingsWidget, 1016

Ui_ExtraSettingsWidget, 1048
Ui_KPerfWidget, 1117
Ui_MPerfWidget, 1149
Ui_SettingsWidget, 1191
linkedlist_data_s, 1436
linkedlist_datablock_internal_s, 1435
linkedlist_data
zip.c, 1441
linkedlist_datablock_internal
zip.c, 1441
list
AnimScript, 68
load
AnimScript, 69
Kb, 280
KbBind, 374
KbLight, 435
KbPerf, 516
LoadCentralDirectoryRecord
zip.c, 1445
loadGlobalRemap
KbBind, 375
local
unzip.c, 1367
zip.c, 1439
locale
KeyMap, 644
lockAction
KeyAction, 617
lockBox
Ui::KPerfWidget, 691
Ui::RebindWidget, 950
Ui_KPerfWidget, 1117
Ui_RebindWidget, 1175
lockButton
Ui::RebindWidget, 950
Ui_RebindWidget, 1175
lockColorOff
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1117
lockColorOn
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1117
lockMutex
ckbsettings.cpp, 1226
ckbsettingswriter.cpp, 1230
lockMutexCache
ckbsettings.cpp, 1226
ckbsettingswriter.cpp, 1230
lockMutexStatic
ckbsettings.cpp, 1227
ckbsettingswriter.cpp, 1230
lockMutexStatic2
ckbsettings.cpp, 1227
ckbsettingswriter.cpp, 1230
loginItemBox
Ui::SettingsWidget, 1016
Ui_SettingsWidget, 1191
M65
KeyMap, 631
M65_HEIGHT
keymap.cpp, 1274
M65_WIDTH
keymap.cpp, 1274
M65Keys
keymap.cpp, 1281
m65Overlay
keywidget.cpp, 1286
MACRO
KbPerf, 500
MAX_FILE_NAME_LENGTH
QuaZip, 823
MEDHIGH
KbPerf, 499
MEDIUM
KbPerf, 499
MODE
KbPerf, 500
MPerfWidget::DpiUi, 771, 1310
MUTE
KbPerf, 500
MUTED
media.h, 1301
MX
KeyMap, 630
M_PI
ckb-anim.h, 1217
MAKEULONG64
zip.c, 1439
MAX_DIM
KbLight, 448
mAccelBox
Ui::ExtraSettingsWidget, 167
Ui_ExtraSettingsWidget, 1048
MODE_NEXT
KeyAction, 625
MODE_NEXT_WRAP
KeyAction, 626
MODE_PREV
KeyAction, 626
MODE_PREV_WRAP
KeyAction, 626
mPerfTab
Ui::KbWidget, 593
Ui_KbWidget, 1100
MPerfWidget, 768
~MPerfWidget, 774
_xyLink, 784
boxXChanged, 774
boxXMapper, 784
boxYChanged, 775
boxYMapper, 784
buttonMapper1, 784
buttonMapper2, 784
colorChanged, 776
colorClicked, 777

colorLink, 785
DPI_COUNT, 785
DPI_MAX, 785
DPI_MIN, 785
enableChanged, 777
enableMapper, 785
isSetting, 785
MPerfWidget, 772
MPerfWidget, 772
on_aSnapBox_clicked, 778
on_copyButton_clicked, 778
on_indicBox_clicked, 779
on_lHeightBox_activated, 779
on_spinBox_valueChanged, 780
on_xyBox_clicked, 780
perf, 785
profile, 785
setPerf, 781
sliderXMapper, 785
sliderXMoved, 782
sliderYMapper, 785
sliderYMoved, 783
stages, 786
ui, 786
mPerfWidget
Ui::KbWidget, 593
Ui_KbWidget, 1100
macReader
RebindWidget, 987
macroAction
KeyAction, 617
macroBox
MacroReaderThread, 721
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1118
macroColorOff
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1118
macroColorOn
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1118
macroContent
KeyAction, 618
macroDelay
Kb, 281
macroDisplay
KeyAction, 618
macroFullLine
KeyAction, 619
macroLine
KeyAction, 620
macroNumber
Kb, 303
MacroReaderThread, 722
macroPath
Kb, 304
MacroReaderThread, 722
MacroReader, 714
~MacroReader, 717
MacroReader, 717
macroReaderThread, 718
MacroReader, 717
startWorkInAThread, 717
MacroReaderThread, 718
macroBox, 721
macroNumber, 722
macroPath, 722
MacroReaderThread, 720
macroText, 722
MacroReaderThread, 720
readMacro, 721
run, 721
macroReaderThread
MacroReader, 718
macroTab
Ui::RebindWidget, 950
Ui_RebindWidget, 1175
macroText
MacroReaderThread, 722
main
ckb-anim.h, 1222
main.cpp, 1295
main.cpp
CommandLineBackground, 1294
CommandLineClose, 1294
CommandLineError, 1294
CommandLineHelpRequested, 1294
CommandLineOK, 1294
CommandLineVersionRequested, 1294
main.cpp
appShare, 1294
CommandLineParseResults, 1294
isRunning, 1294
main, 1295
parseCommandLine, 1297
pidActive, 1298
SHMEM_SIZE, 1293
SHMEM_SIZE_V015, 1293
MainWindow, 726
~MainWindow, 730
addDevice, 731
checkFwUpdates, 731
cleanup, 732
closeAction, 740
closeEvent, 733
iconClicked, 733
kbWidgets, 740
MainWindow, 729
mainWindow, 740
MainWindow, 729
quitApp, 734
removeDevice, 735
restoreAction, 740
settingsWidget, 740
SettingsWidget, 1005
showFwUpdateNotification, 735

showWindow, 736
stateChange, 736
timerTick, 737
toggleTrayIcon, 738
trayIcon, 740
trayIconMenu, 740
ui, 740
updateVersion, 739
mainWindow
MainWindow, 740
mainwindow.cpp
appShare, 1299
configLabel, 1299
makeIcon
GradientDialog, 215
makeStops
GradientDialogWidget, 226
map
KbAnim, 319, 320
KbBind, 376, 377
KbLight, 437
KeyMap, 645
KeyWidget, 657, 658
map_last
kbperf.cpp, 1263
matches
Kb, 282
mb2Box
Ui::RebindWidget, 950
Ui_RebindWidget, 1175
mb2Button
Ui::RebindWidget, 950
Ui_RebindWidget, 1175
mbBox
Ui::RebindWidget, 950
Ui_RebindWidget, 1175
mbButton
Ui::RebindWidget, 951
Ui_RebindWidget, 1175
mdAdd
QuaZip, 823
mdAppend
QuaZip, 823
mdCreate
QuaZip, 823
mdNotOpen
QuaZip, 823
mdUnzip
QuaZip, 823
media.h
MUTED, 1301
UNKNOWN, 1301
UNMUTED, 1301
media.h
ENUM_C, 1301
ENUM_END_C, 1301
EXTERN_C, 1301
getMuteState, 1301
muteState, 1301
media_linux.cpp
getMuteState, 1303
muteProcess, 1303
media_mac.m
disableAppNap, 1304
getMuteState, 1304
mediaBox
Ui::RebindWidget, 951
Ui_RebindWidget, 1175
mediaButton
Ui::RebindWidget, 951
Ui_RebindWidget, 1176
mediaKeys
RebindWidget, 987
method
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
minX
AnimScript, 83
minY
AnimScript, 83
moc_animadddialog.cpp
QT_MOC_LITERAL, 1502
qt_meta_data_AnimAddDialog, 1502
qt_meta_stringdata_AnimAddDialog, 1503
moc_animscript.cpp
QT_MOC_LITERAL, 1505
qt_meta_data_AnimScript, 1505
qt_meta_stringdata_AnimScript, 1506
moc_animsettingdialog.cpp
QT_MOC_LITERAL, 1507
qt_meta_data_AnimSettingDialog, 1508
qt_meta_stringdata_AnimSettingDialog, 1508
moc_ckbsettingswriter.cpp
QT_MOC_LITERAL, 1510
qt_meta_data_CkbSettingsWriter, 1510
qt_meta_stringdata_CkbSettingsWriter, 1511
moc_colorbutton.cpp
QT_MOC_LITERAL, 1512
qt_meta_data_ColorButton, 1513
qt_meta_stringdata_ColorButton, 1513
moc_extrasettingswidget.cpp
QT_MOC_LITERAL, 1515
qt_meta_data_ExtraSettingsWidget, 1515
qt_meta_stringdata_ExtraSettingsWidget, 1515
moc_fwupgradedialog.cpp
QT_MOC_LITERAL, 1518
qt_meta_data_FwUpgradeDialog, 1518
qt_meta_stringdata_FwUpgradeDialog, 1519
moc_gradientbutton.cpp
QT_MOC_LITERAL, 1521
qt_meta_data_GradientButton, 1521
qt_meta_stringdata_GradientButton, 1522
moc_gradientdialog.cpp
QT_MOC_LITERAL, 1523
qt_meta_data_GradientDialog, 1524
qt_meta_stringdata_GradientDialog, 1524

moc_gradientdialogwidget.cpp
QT_MOC_LITERAL, 1526
qt_meta_data_GradientDialogWidget, 1526
qt_meta_stringdata_GradientDialogWidget, 1527
moc_kb.cpp
QT_MOC_LITERAL, 1529
qt_meta_data_Kb, 1529
qt_meta_stringdata_Kb, 1529
moc_kbanim.cpp
QT_MOC_LITERAL, 1531
qt_meta_data_KbAnim, 1531
qt_meta_stringdata_KbAnim, 1532
moc_kbanimwidget.cpp
QT_MOC_LITERAL, 1534
qt_meta_data_KbAnimWidget, 1534
qt_meta_stringdata_KbAnimWidget, 1534
moc_kbbind.cpp
QT_MOC_LITERAL, 1536
qt_meta_data_KbBind, 1536
qt_meta_stringdata_KbBind, 1536
moc_kbbindwidget.cpp
QT_MOC_LITERAL, 1538
qt_meta_data_KbBindWidget, 1539
qt_meta_stringdata_KbBindWidget, 1539
moc_kbfirmware.cpp
QT_MOC_LITERAL, 1541
qt_meta_data_KbFirmware, 1541
qt_meta_stringdata_KbFirmware, 1542
moc_kblight.cpp
QT_MOC_LITERAL, 1544
qt_meta_data_KbLight, 1544
qt_meta_stringdata_KbLight, 1545
moc_kblightwidget.cpp
QT_MOC_LITERAL, 1547
qt_meta_data_KbLightWidget, 1547
qt_meta_stringdata_KbLightWidget, 1547
moc_kbmanager.cpp
QT_MOC_LITERAL, 1549
qt_meta_data_KbManager, 1549
qt_meta_stringdata_KbManager, 1549
moc_kbmode.cpp
QT_MOC_LITERAL, 1551
qt_meta_data_KbMode, 1552
qt_meta_stringdata_KbMode, 1552
moc_kbperf.cpp
QT_MOC_LITERAL, 1554
qt_meta_data_KbPerf, 1554
qt_meta_stringdata_KbPerf, 1555
moc_kbprofile.cpp
QT_MOC_LITERAL, 1556
qt_meta_data_KbProfile, 1557
qt_meta_stringdata_KbProfile, 1557
moc_kbprofiledialog.cpp
QT_MOC_LITERAL, 1559
qt_meta_data_KbProfileDialog, 1559
qt_meta_stringdata_KbProfileDialog, 1560
moc_kbwidget.cpp
QT_MOC_LITERAL, 1562
qt_meta_data_KbWidget, 1562
qt_meta_stringdata_KbWidget, 1562
moc_keyaction.cpp
QT_MOC_LITERAL, 1564
qt_meta_data_KeyAction, 1564
qt_meta_stringdata_KeyAction, 1565
moc_keywidget.cpp
QT_MOC_LITERAL, 1566
qt_meta_data_KeyWidget, 1567
qt_meta_stringdata_KeyWidget, 1567
moc_kperfwidget.cpp
QT_MOC_LITERAL, 1569
qt_meta_data_KPerfWidget, 1569
qt_meta_stringdata_KPerfWidget, 1570
moc_layoutdialog.cpp
QT_MOC_LITERAL, 1572
qt_meta_data_LayoutDialog, 1572
qt_meta_stringdata_LayoutDialog, 1573
moc_macroreader.cpp
QT_MOC_LITERAL, 1575
qt_meta_data_MacroReader, 1575
qt_meta_data_MacroReaderThread, 1576
qt_meta_stringdata_MacroReader, 1576
qt_meta_stringdata_MacroReaderThread, 1576
moc_mainwindow.cpp
QT_MOC_LITERAL, 1578
qt_meta_data_MainWindow, 1578
qt_meta_stringdata_MainWindow, 1578
moc_modeselectdialog.cpp
QT_MOC_LITERAL, 1580
qt_meta_data_ModeSelectDialog, 1580
qt_meta_stringdata_ModeSelectDialog, 1581
moc_mperfwidget.cpp
QT_MOC_LITERAL, 1582
qt_meta_data_MPerfWidget, 1583
qt_meta_stringdata_MPerfWidget, 1583
moc_quagzipfile.cpp
QT_MOC_LITERAL, 1585
qt_meta_data_QuaGzipFile, 1585
qt_meta_stringdata_QuaGzipFile, 1586
moc_quaziodevice.cpp
QT_MOC_LITERAL, 1587
qt_meta_data_QuaZIODevice, 1588
qt_meta_stringdata_QuaZIODevice, 1588
moc_quazipfile.cpp
QT_MOC_LITERAL, 1589
qt_meta_data_QuaZipFile, 1590
qt_meta_stringdata_QuaZipFile, 1590
moc_rebindwidget.cpp
QT_MOC_LITERAL, 1592
qt_meta_data_RebindWidget, 1592
qt_meta_stringdata_RebindWidget, 1592
moc_rlistwidget.cpp
QT_MOC_LITERAL, 1594
qt_meta_data_RListWidget, 1594
qt_meta_stringdata_RListWidget, 1594
moc_settingswidget.cpp
QT_MOC_LITERAL, 1596

qt_meta_data_SettingsWidget, 1597
qt_meta_stringdata_SettingsWidget, 1597
modBox
Ui::RebindWidget, 951
Ui_RebindWidget, 1176
modButton
Ui::RebindWidget, 951
Ui_RebindWidget, 1176
modKeys
RebindWidget, 987
settingswidget.cpp, 1608
modNames
settingswidget.cpp, 1609
Mode
KbAnim, 308
QuaZip, 823
mode
KbAnim, 320
QuaZipPrivate, 925
mode2Raw
KPerfWidget, 700
modeAction
KeyAction, 621
modeBox
Ui::KPerfWidget, 691
Ui::RebindWidget, 951
Ui_KPerfWidget, 1118
Ui_RebindWidget, 1176
modeButton
Ui::RebindWidget, 951
Ui_RebindWidget, 1176
modeChanged
Kb, 282
KbWidget, 567
modeColorOff
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1118
modeColorOn
Ui::KPerfWidget, 691
Ui_KPerfWidget, 1118
modeCount
KbProfile, 540
modeIcon
KbWidget, 569
ModeList
KbProfile, 533
modeList
Ui::ModeSelectDialog, 744
Ui_ModeSelectDialog, 1132
modeParent
KbBind, 377
KbPerf, 517
modeRenamed
Kb, 283
ModeSelectDialog, 745
~ModeSelectDialog, 747
_modeList, 748
ModeSelectDialog, 747
ModeSelectDialog, 747
on_selAllButton_clicked, 747
on_selNoneButton_clicked, 747
selection, 748
ui, 748
modeUpdate
KbWidget, 571
modeWrapBox
Ui::RebindWidget, 951
Ui_RebindWidget, 1176
Model
KeyMap, 630
model
Kb, 282
KeyMap, 645
modelHeight
KeyMap, 645
modelWidth
KeyMap, 646
modes
KbProfile, 540, 541
modesList
Ui::KbWidget, 593
Ui_KbWidget, 1099
modesList_reordered
KbWidget, 570
modified
UsbId, 1197
modifiedString
UsbId, 1196
monoRgb
kblight.cpp, 1256
keywidget.cpp, 1285
monochrome
Kb, 304
KeyWidget, 658, 659
mouseAccel
Kb, 283
mouseCurrentX
KeyWidget, 672
mouseCurrentY
KeyWidget, 672
mouseDownMode
KeyWidget, 672
mouseDownX
KeyWidget, 673
mouseDownY
KeyWidget, 673
mouseExtKeys
RebindWidget, 987
mouseKeys
RebindWidget, 987
mouseMoveEvent
GradientDialogWidget, 227
KeyWidget, 659
mousePressEvent
GradientDialogWidget, 228
KeyWidget, 660

mouseReleaseEvent
GradientDialogWidget, 228
KeyWidget, 661
mouseTab
Ui::RebindWidget, 952
Ui_RebindWidget, 1176
move
KbProfile, 541
moveCurrent
GradientDialogWidget, 229
mperfwidget.cpp
DPI_BASE, 1308
dpiExp, 1307
dpiLog, 1307
dpiRound, 1308
SET_END, 1307
SET_START, 1307
xyLinkPath, 1308
Multiply
KbAnim, 308
muteBox
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1118
muteColorNA
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1118
muteColorOff
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1118
muteColorOn
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1119
muteNAColor
KbPerf, 529
muteProcess
media_linux.cpp, 1303
muteState
media.h, 1301

NO
KbFirmware, 410
KeyMap, 630
NO_LAYOUT
KeyMap, 630
NO_MODEL
KeyMap, 630
NONE
KbPerf, 500
KeyWidget, 654
NORMAL
KPerfWidget, 698
KbPerf, 500
KeyAction, 601
NUM
KbPerf, 500
N_LAYOUTS
keymap.cpp, 1274
N_MODELS
keymap.cpp, 1275
NEW_FLAG
KbProfileDialog, 557
KbWidget, 584
NS
keymap.cpp, 1275
name
AnimScript, 72
AnimSettingDialog, 108
GradientDialog::Preset, 787
KbAnim, 320, 321
KbMode, 490
KbProfile, 542
KbWidget, 571
Key, 597
KeyMap, 646
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
QuaZipNewInfo, 917
nameBox
Ui::KbAnimWidget, 340
Ui_KbAnimWidget, 1072
nameFilters
QuaZipDir, 865
needsSave
Kb, 284
KbAnim, 321
KbBind, 377
KbLight, 438
KbMode, 491
KbPerf, 518
KbProfile, 542
networkManager
KbFirmware, 418
newDuration
AnimSettingDialog, 108
newGuid
UsbId, 1196
newId
KbAnim, 322
KbMode, 491
KbProfile, 543
newLabel
Ui::FwUpgradeDialog, 193
Ui_FwUpgradeDialog, 1056
newLayout
KbBindWidget, 400
newMode
Kb, 284, 285
newModified
UsbId, 1196
newProfile
Kb, 285, 286
newSelection
KbBindWidget, 401
KbLightWidget, 462
KeyWidget, 673
noAction
KbBind, 378

KeyAction, 621
noAnimLabel
Ui::KbAnimWidget, 341
Ui_KbAnimWidget, 1072
noReorder
KbAnimWidget, 359
noSelPage
Ui::KbAnimWidget, 341
Ui_KbAnimWidget, 1072
Normal
KbAnim, 308
notifyNumber
Kb, 304
notifyPath
Kb, 304
notifyPathMutex
kb.cpp, 1245
notifyPaths
kb.cpp, 1245
numBox
Ui::KPerfWidget, 692
Ui::RebindWidget, 952
Ui_KPerfWidget, 1119
Ui_RebindWidget, 1176
numButton
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
numColorOff
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1119
numColorOn
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1119
numKeys
RebindWidget, 987

OFF
KbPerf, 500
ON
KbPerf, 500
OF
ioapi.h, 1318
ONE_DAY
animscript.cpp, 1201
OTHER
KbPerf, 530
on_aSnapBox_clicked
MPerfWidget, 778
on_actionButton_clicked
FwUpgradeDialog, 185
on_altBox_activated
SettingsWidget, 998
on_animBox_activated
AnimAddDialog, 44
on_animBox_currentIndexChanged
RebindWidget, 964
on_animButton_clicked
KbLightWidget, 463
RebindWidget, 965
on_animList_currentItemChanged
KbAnimWidget, 348
on_animList_customContextMenuRequested
KbAnimWidget, 349
on_animList_itemChanged
KbAnimWidget, 350
on_animScanButton_clicked
ExtraSettingsWidget, 173
on_applyButton_clicked
RebindWidget, 965
on_autoFWBox_clicked
SettingsWidget, 999
on_bgButton_clicked
KbLightWidget, 464
on_blendBox_activated
KbAnimWidget, 350
on_brightnessBox_activated
KbLightWidget, 464
on_brightnessBox_clicked
ExtraSettingsWidget, 174
on_btnClearMacro_clicked
RebindWidget, 965
on_btnStartMacro_clicked
RebindWidget, 966
on_btnStopMacro_clicked
RebindWidget, 966
on_cancelButton_clicked
FwUpgradeDialog, 186
RebindWidget, 967
on_capsBox_activated
SettingsWidget, 999
on_copyButton_clicked
KbBindWidget, 402
KPerfWidget, 701
MPerfWidget, 778
on_ctrlBox_activated
SettingsWidget, 999
on_delayBox_clicked
ExtraSettingsWidget, 174
on_delayBox_valueChanged
AnimSettingDialog, 109
on_deleteButton_clicked
KbAnimWidget, 351
on_ditherBox_clicked
ExtraSettingsWidget, 174
on_dpiBox_currentIndexChanged
RebindWidget, 968
on_dpiButton_clicked
RebindWidget, 969
on_extraButton_clicked
SettingsWidget, 1000
on_fnBox_currentIndexChanged
RebindWidget, 969
on_fnButton_clicked
RebindWidget, 969
on_fpsBox_valueChanged
ExtraSettingsWidget, 175
on_fwUpdButton_clicked

KbWidget, 571
on_hwSaveButton_clicked
KbWidget, 573
on_indicBox_clicked
MPerfWidget, 779
on_intensityBox_valueChanged
KPerfWidget, 701
on_keyButton_clicked
KbAnimWidget, 351
on_kpDelayBox_valueChanged
AnimSettingDialog, 110
on_kpReleaseBox_stateChanged
AnimSettingDialog, 110
on_kpRepeatBox_valueChanged
AnimSettingDialog, 111
on_lHeightBox_activated
MPerfWidget, 779
on_layoutBox_activated
SettingsWidget, 1000
on_lightBox_currentIndexChanged
RebindWidget, 969
on_lightButton_clicked
RebindWidget, 970
on_lockBox_currentIndexChanged
RebindWidget, 970
on_lockButton_clicked
RebindWidget, 970
on_loginItemBox_clicked
SettingsWidget, 1001
on_mAccelBox_clicked
ExtraSettingsWidget, 175
on_mb2Box_currentIndexChanged
RebindWidget, 971
on_mb2Button_clicked
RebindWidget, 971
on_mbBox_currentIndexChanged
RebindWidget, 971
on_mbButton_clicked
RebindWidget, 972
on_mediaBox_currentIndexChanged
RebindWidget, 972
on_mediaButton_clicked
RebindWidget, 972
on_modBox_currentIndexChanged
RebindWidget, 972
on_modButton_clicked
RebindWidget, 973
on_modeBox_currentIndexChanged
RebindWidget, 973
on_modeButton_clicked
RebindWidget, 973
on_modesList_currentItemChanged
KbWidget, 574
on_modesList_customContextMenuRequested
KbWidget, 575
on_modesList_itemChanged
KbWidget, 576
on_modesList_itemClicked
KbWidget, 577
on_nameBox_textEdited
KbAnimWidget, 352
on_numBox_currentIndexChanged
RebindWidget, 974
on_numButton_clicked
RebindWidget, 974
on_opacityBox_valueChanged
KbAnimWidget, 353
on_presetBox_activated
AnimAddDialog, 45
on_presetDelete_clicked
GradientDialog, 216
on_presetList_currentItemChanged
GradientDialog, 216
on_presetName_textEdited
GradientDialog, 217
on_presetSave_clicked
GradientDialog, 217
on_previewBox_clicked
AnimAddDialog, 46
on_profileBox_activated
KbWidget, 578
on_profileList_currentItemChanged
KbProfileDialog, 551
on_profileList_customContextMenuRequested
KbProfileDialog, 551
on_profileList_itemChanged
KbProfileDialog, 553
on_profileList_itemClicked
KbProfileDialog, 554
on_programKpBox_textChanged
RebindWidget, 974
on_programKpButton_clicked
RebindWidget, 975
on_programKpSIBox_clicked
RebindWidget, 975
on_programKrBox_textChanged
RebindWidget, 975
on_programKrButton_clicked
RebindWidget, 976
on_programKrSIBox_clicked
RebindWidget, 976
on_propertyButton_clicked
KbAnimWidget, 353
on_pteMacroBox_textChanged
RebindWidget, 976
on_pushButton_clicked
SettingsWidget, 1001
on_repeatBox_valueChanged
AnimSettingDialog, 111
on_resetButton_clicked
KbBindWidget, 402
RebindWidget, 977
on_sAccelBox_clicked
ExtraSettingsWidget, 176
on_sSpeedBox_valueChanged
ExtraSettingsWidget, 176

on_selAllButton_clicked
ModeSelectDialog, 747
on_selNoneButton_clicked
ModeSelectDialog, 747
on_shiftBox_activated
SettingsWidget, 1001
on_showAnimBox_clicked
KbLightWidget, 465
on_spinBox_valueChanged
MPerfWidget, 780
on_stopOpacity_valueChanged
GradientDialog, 218
on_stopPos_valueChanged
GradientDialog, 218
on_tabWidget_currentChanged
KbWidget, 578
on_trayBox_clicked
ExtraSettingsWidget, 177
on_typingBox_currentIndexChanged
RebindWidget, 977
on_typingButton_clicked
RebindWidget, 977
on_unbindButton_clicked
RebindWidget, 978
on_wheelBox_currentIndexChanged
RebindWidget, 978
on_wheelButton_clicked
RebindWidget, 978
on_winBox_activated
SettingsWidget, 1002
on_xyBox_clicked
MPerfWidget, 780
once
AutoRun, 121
opacity
KbAnim, 322
opacityBox
Ui::KbAnimWidget, 341
Ui_KbAnimWidget, 1072
open
KbLight, 438
QuaGzipFile, 810, 811
QuaZIODevice, 817
QuaZip, 842
QuaZipFile, 883–885
operator bool
Key, 595
operator const QHash< QString, Key > &
KeyMap, 647
operator QString
KeyAction, 621
operator=
ColorMap, 156
KbPerf, 518
KeyAction, 621
QuaGzipFile, 811
QuaZip, 845
QuaZipDir, 866
QuaZipFile, 887
operator==
QuaZipDir, 866
orderChanged
RListWidget, 992
osxLabel
Ui::ExtraSettingsWidget, 167
Ui_ExtraSettingsWidget, 1048
osxLine
Ui::ExtraSettingsWidget, 168
Ui_ExtraSettingsWidget, 1048

p
QuaZip, 852
QuaZipFile, 893
PL
KeyMap, 630
PATCH_COUNT
keymap.cpp, 1275
PROGRAM_PR_INDEF
KeyAction, 626
PROGRAM_PR_KPSTOP
KeyAction, 626
PROGRAM_PR_KRSTOP
KeyAction, 626
PROGRAM_PR_MULTI
KeyAction, 626
PROGRAM_RE_INDEF
KeyAction, 626
PROGRAM_RE_KPSTOP
KeyAction, 627
PROGRAM_RE_MULTI
KeyAction, 627
paintEvent
GradientDialogWidget, 230
KeyWidget, 662
param
AnimScript, 72
paramIterator
AnimScript, 74
parameter
KbAnim, 322, 323
parameters
AnimScript, 73
parseCommandLine
main.cpp, 1297
parseVersionString
KbManager, 478
patch
keymap.cpp, 1275
patchANSI
keymap.cpp, 1278
patchDE
keymap.cpp, 1281
patchDK
keymap.cpp, 1281
patchDvorak
keymap.cpp, 1281
patchES

keymap.cpp, 1281
patchEU
keymap.cpp, 1282
patchFR
keymap.cpp, 1282
patchISO
keymap.cpp, 1279
patchIT
keymap.cpp, 1282
patchMX
keymap.cpp, 1282
patchNO
keymap.cpp, 1282
patchSE
keymap.cpp, 1283
path
AnimScript, 74
QuaZipDir, 866
perf
KbBind, 379
KbMode, 492
KPerfWidget, 706
MPerfWidget, 785
permissionsFromExternalAttr
quazipfileinfo.cpp, 1355
pickColor
ColorButton, 146
pickGradient
GradientButton, 197
pidActive
main.cpp, 1298
pollLabel
Ui::KbWidget, 593
Ui_KbWidget, 1100
pollLabel2
Ui::KbWidget, 593
Ui_KbWidget, 1100
pollUpdates
ExtraSettingsWidget, 177
SettingsWidget, 1002
pollrate
Kb, 304
popDpi
KbPerf, 519
pos
QIODevice_descriptor, 790
QuaZipFile, 887
positions
KeyMap, 647
preProgram
KeyAction, 626
prefsPath
gradientdialog.cpp, 1242
Kb, 304
Preset
GradientDialog::Preset, 787
preset
AnimScript, 74
presetBox
Ui::AnimAddDialog, 51
Ui_AnimAddDialog, 1025
presetDelete
Ui::GradientDialog, 206
Ui_GradientDialog, 1062
presetList
Ui::GradientDialog, 207
Ui_GradientDialog, 1062
presetName
Ui::GradientDialog, 207
Ui_GradientDialog, 1063
presetSave
Ui::GradientDialog, 207
Ui_GradientDialog, 1063
PresetValue
AnimScript, 57
presets
AnimScript, 75
GradientDialog, 220
prevMode
Kb, 304
prevProfile
Kb, 304
previewAnim
KbLight, 439
previewBox
Ui::AnimAddDialog, 51
Ui_AnimAddDialog, 1025
previousItems
RListWidget, 994
printParams
AnimScript, 75
printRGB
KbLight, 440
printurl
ckb-anim.h, 1224
process
AnimScript, 83
processDownload
KbFirmware, 416
profile
KbBindWidget, 407
KPerfWidget, 706
MPerfWidget, 785
RebindWidget, 987
profileAdded
Kb, 287
profileBox
Ui::KbWidget, 593
Ui_KbWidget, 1100
profileChanged
Kb, 287
KbWidget, 579
profileList
Ui::KbProfileDialog, 561
Ui_KbProfileDialog, 1091
profileList_reordered

KbProfileDialog, 554
profileRenamed
Kb, 287
profiles
Kb, 288
progTipLabel
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
programAction
KeyAction, 621
programInfo
KeyAction, 622
programKpBox
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
programKpButton
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
programKpExtra
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
programKpModeBox
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
programKpSIBox
Ui::RebindWidget, 952
Ui_RebindWidget, 1177
programKrBox
Ui::RebindWidget, 953
Ui_RebindWidget, 1177
programKrButton
Ui::RebindWidget, 953
Ui_RebindWidget, 1177
programKrExtra
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
programKrModeBox
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
programKrSIBox
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
programTab
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
progressBar
Ui::FwUpgradeDialog, 194
Ui_FwUpgradeDialog, 1056
propertyButton
Ui::KbAnimWidget, 341
Ui_KbAnimWidget, 1072
pteMacroBox
Ui::RebindWidget, 953
Ui_RebindWidget, 1178
pteMacroComment
Ui::RebindWidget, 954
Ui_RebindWidget, 1178
pteMacroText
Ui::RebindWidget, 954
Ui_RebindWidget, 1178
pushButton
Ui::SettingsWidget, 1016
Ui_SettingsWidget, 1191
pushDpi
KbPerf, 519, 520
pushSniper
KbPerf, 521
pushedDpis
KbPerf, 530
pwd
CkbSettings, 131, 132

q
QuaZipFilePrivate, 908
QuaZipPrivate, 926
qCleanupResources_binary
qrc_binary.cpp, 1598
qCleanupResources_image
qrc_image.cpp, 1601
qCleanupResources_text
qrc_text.cpp, 1603
QColorMap
colormap.h, 1235
QColorMapIterator
colormap.h, 1235
QDialog, 788
QIODevice, 789
QIODevice_descriptor, 790
pos, 790
QIODevice_descriptor, 790
QIODevice_descriptor, 790
qInitResources_binary
qrc_binary.cpp, 1598
qInitResources_image
qrc_image.cpp, 1601
qInitResources_text
qrc_text.cpp, 1604
QListWidget, 791
QMainWindow, 792
QMutableColorMapIterator
colormap.h, 1235
QObject, 793
QPushButton, 794
qRegisterResourceData
qrc_binary.cpp, 1599
qrc_image.cpp, 1602
qrc_text.cpp, 1604
QT_MOC_LITERAL
moc_animadddialog.cpp, 1502
moc_animscript.cpp, 1505
moc_animsettingdialog.cpp, 1507
moc_ckbsettingswriter.cpp, 1510
moc_colorbutton.cpp, 1512
moc_extrasettingswidget.cpp, 1515
moc_fwupgradedialog.cpp, 1518
moc_gradientbutton.cpp, 1521
moc_gradientdialog.cpp, 1523

moc_gradientdialogwidget.cpp, 1526
moc_kb.cpp, 1529
moc_kbanim.cpp, 1531
moc_kbanimwidget.cpp, 1534
moc_kbbind.cpp, 1536
moc_kbbindwidget.cpp, 1538
moc_kbfirmware.cpp, 1541
moc_kblight.cpp, 1544
moc_kblightwidget.cpp, 1547
moc_kbmanager.cpp, 1549
moc_kbmode.cpp, 1551
moc_kbperf.cpp, 1554
moc_kbprofile.cpp, 1556
moc_kbprofiledialog.cpp, 1559
moc_kbwidget.cpp, 1562
moc_keyaction.cpp, 1564
moc_keywidget.cpp, 1566
moc_kperfwidget.cpp, 1569
moc_layoutdialog.cpp, 1572
moc_macroreader.cpp, 1575
moc_mainwindow.cpp, 1578
moc_modeselectdialog.cpp, 1580
moc_mperfwidget.cpp, 1582
moc_quagzipfile.cpp, 1585
moc_quaziodevice.cpp, 1587
moc_quazipfile.cpp, 1589
moc_rebindwidget.cpp, 1592
moc_rlistwidget.cpp, 1594
moc_settingswidget.cpp, 1596
QThread, 795
QUAZIO_INBUFSIZE
quaziodevice.cpp, 1343
QUAZIO_OUTBUFSIZE
quaziodevice.cpp, 1343
QUAZIP_EXPORT
quazip_global.h, 1348
qUnregisterResourceData
qrc_binary.cpp, 1599
qrc_image.cpp, 1602
qrc_text.cpp, 1604
QWidget, 926
qioapi.cpp
call_zopen64, 1325
call_zseek64, 1325
call_ztell64, 1325
fill_qiodevice64_filefunc, 1326
fill_qiodevice_filefunc, 1327
fill_zlib_filefunc64_32_def_from_filefunc32, 1328
qiodevice64_seek_file_func, 1329
qiodevice64_tell_file_func, 1330
qiodevice_close_file_func, 1330
qiodevice_error_file_func, 1331
qiodevice_fakeclose_file_func, 1331
qiodevice_open_file_func, 1332
qiodevice_read_file_func, 1333
qiodevice_seek_file_func, 1333
qiodevice_tell_file_func, 1334
qiodevice_write_file_func, 1334
SEEK_CUR, 1325
SEEK_END, 1325
SEEK_SET, 1325
qiodevice64_seek_file_func
qioapi.cpp, 1329
qiodevice64_tell_file_func
qioapi.cpp, 1330
qiodevice_close_file_func
qioapi.cpp, 1330
qiodevice_error_file_func
qioapi.cpp, 1331
qiodevice_fakeclose_file_func
qioapi.cpp, 1331
qiodevice_open_file_func
qioapi.cpp, 1332
qiodevice_read_file_func
qioapi.cpp, 1333
qiodevice_seek_file_func
qioapi.cpp, 1333
qiodevice_tell_file_func
qioapi.cpp, 1334
qiodevice_write_file_func
qioapi.cpp, 1334
qrc_binary.cpp
qCleanupResources_binary, 1598
qInitResources_binary, 1598
qRegisterResourceData, 1599
qUnregisterResourceData, 1599
qt_resource_data, 1600
qt_resource_name, 1600
qt_resource_struct, 1600
qrc_image.cpp
qCleanupResources_image, 1601
qInitResources_image, 1601
qRegisterResourceData, 1602
qUnregisterResourceData, 1602
qt_resource_data, 1602
qt_resource_name, 1602
qt_resource_struct, 1603
qrc_text.cpp
qCleanupResources_text, 1603
qInitResources_text, 1604
qRegisterResourceData, 1604
qUnregisterResourceData, 1604
qt_resource_data, 1605
qt_resource_name, 1605
qt_resource_struct, 1605
qs_strcmp
colormap.cpp, 1233
qt_meta_stringdata_AnimAddDialog_t, 1501
qt_meta_stringdata_AnimScript_t, 1504
qt_meta_stringdata_AnimSettingDialog_t, 1507
qt_meta_stringdata_CkbSettingsWriter_t, 1509
qt_meta_stringdata_ColorButton_t, 1512
qt_meta_stringdata_ExtraSettingsWidget_t, 1514
qt_meta_stringdata_FwUpgradeDialog_t, 1517
qt_meta_stringdata_GradientButton_t, 1520
qt_meta_stringdata_GradientDialog_t, 1523

qt_meta_stringdata_GradientDialogWidget_t, 1525
qt_meta_stringdata_KPerfWidget_t, 1568
qt_meta_stringdata_Kb_t, 1528
qt_meta_stringdata_KbAnim_t, 1530
qt_meta_stringdata_KbAnimWidget_t, 1533
qt_meta_stringdata_KbBind_t, 1535
qt_meta_stringdata_KbBindWidget_t, 1538
qt_meta_stringdata_KbFirmware_t, 1540
qt_meta_stringdata_KbLight_t, 1543
qt_meta_stringdata_KbLightWidget_t, 1546
qt_meta_stringdata_KbManager_t, 1548
qt_meta_stringdata_KbMode_t, 1551
qt_meta_stringdata_KbPerf_t, 1553
qt_meta_stringdata_KbProfile_t, 1556
qt_meta_stringdata_KbProfileDialog_t, 1558
qt_meta_stringdata_KbWidget_t, 1561
qt_meta_stringdata_KeyAction_t, 1563
qt_meta_stringdata_KeyWidget_t, 1566
qt_meta_stringdata_LayoutDialog_t, 1571
qt_meta_stringdata_MPerfWidget_t, 1582
qt_meta_stringdata_MacroReader_t, 1574
qt_meta_stringdata_MacroReaderThread_t, 1574
qt_meta_stringdata_MainWindow_t, 1578
qt_meta_stringdata_ModeSelectDialog_t, 1579
qt_meta_stringdata_QuaGzipFile_t, 1584
qt_meta_stringdata_QuaZIODevice_t, 1587
qt_meta_stringdata_QuaZipFile_t, 1589
qt_meta_stringdata_RListWidget_t, 1593
qt_meta_stringdata_RebindWidget_t, 1591
qt_meta_stringdata_SettingsWidget_t, 1596
qt_meta_data_AnimAddDialog
    moc_animadddialog.cpp, 1502
qt_meta_data_AnimScript
    moc_animscript.cpp, 1505
qt_meta_data_AnimSettingDialog
    moc_animsettingdialog.cpp, 1508
qt_meta_data_CkbSettingsWriter
    moc_ckbsettingswriter.cpp, 1510
qt_meta_data_ColorButton
    moc_colorbutton.cpp, 1513
qt_meta_data_ExtraSettingsWidget
    moc_extrasettingswidget.cpp, 1515
qt_meta_data_FwUpgradeDialog
    moc_fwupgradedialog.cpp, 1518
qt_meta_data_GradientButton
    moc_gradientbutton.cpp, 1521
qt_meta_data_GradientDialog
    moc_gradientdialog.cpp, 1524
qt_meta_data_GradientDialogWidget
    moc_gradientdialogwidget.cpp, 1526
qt_meta_data_KPerfWidget
    moc_kperfwidget.cpp, 1569
qt_meta_data_Kb
    moc_kb.cpp, 1529
qt_meta_data_KbAnim
    moc_kbanim.cpp, 1531
qt_meta_data_KbAnimWidget
    moc_kbanimwidget.cpp, 1534
qt_meta_data_KbBind
    moc_kbbind.cpp, 1536
qt_meta_data_KbBindWidget
    moc_kbbindwidget.cpp, 1539
qt_meta_data_KbFirmware
    moc_kbfirmware.cpp, 1541
qt_meta_data_KbLight
    moc_kblight.cpp, 1544
qt_meta_data_KbLightWidget
    moc_kblightwidget.cpp, 1547
qt_meta_data_KbManager
    moc_kbmanager.cpp, 1549
qt_meta_data_KbMode
    moc_kbmode.cpp, 1552
qt_meta_data_KbPerf
    moc_kbperf.cpp, 1554
qt_meta_data_KbProfile
    moc_kbprofile.cpp, 1557
qt_meta_data_KbProfileDialog
    moc_kbprofiledialog.cpp, 1559
qt_meta_data_KbWidget
    moc_kbwidget.cpp, 1562
qt_meta_data_KeyAction
    moc_keyaction.cpp, 1564
qt_meta_data_KeyWidget
    moc_keywidget.cpp, 1567
qt_meta_data_LayoutDialog
    moc_layoutdialog.cpp, 1572
qt_meta_data_MPerfWidget
    moc_mperfwidget.cpp, 1583
qt_meta_data_MacroReader
    moc_macroreader.cpp, 1575
qt_meta_data_MacroReaderThread
    moc_macroreader.cpp, 1576
qt_meta_data_MainWindow
    moc_mainwindow.cpp, 1578
qt_meta_data_ModeSelectDialog
    moc_modeselectdialog.cpp, 1580
qt_meta_data_QuaGzipFile
    moc_quagzipfile.cpp, 1585
qt_meta_data_QuaZIODevice
    moc_quaziodevice.cpp, 1588
qt_meta_data_QuaZipFile
    moc_quazipfile.cpp, 1590
qt_meta_data_RListWidget
    moc_rlistwidget.cpp, 1594
qt_meta_data_RebindWidget
    moc_rebindwidget.cpp, 1592
qt_meta_data_SettingsWidget
    moc_settingswidget.cpp, 1597
qt_meta_stringdata_AnimAddDialog
    moc_animadddialog.cpp, 1503
qt_meta_stringdata_AnimScript
    moc_animscript.cpp, 1506
qt_meta_stringdata_AnimSettingDialog
    moc_animsettingdialog.cpp, 1508
qt_meta_stringdata_CkbSettingsWriter
    moc_ckbsettingswriter.cpp, 1511

qt_meta_stringdata_ColorButton
moc_colorbutton.cpp, 1513
qt_meta_stringdata_ExtraSettingsWidget
moc_extrasettingswidget.cpp, 1515
qt_meta_stringdata_FwUpgradeDialog
moc_fwupgradedialog.cpp, 1519
qt_meta_stringdata_GradientButton
moc_gradientbutton.cpp, 1522
qt_meta_stringdata_GradientDialog
moc_gradientdialog.cpp, 1524
qt_meta_stringdata_GradientDialogWidget
moc_gradientdialogwidget.cpp, 1527
qt_meta_stringdata_KPerfWidget
moc_kperfwidget.cpp, 1570
qt_meta_stringdata_Kb
moc_kb.cpp, 1529
qt_meta_stringdata_KbAnim
moc_kbanim.cpp, 1532
qt_meta_stringdata_KbAnimWidget
moc_kbanimwidget.cpp, 1534
qt_meta_stringdata_KbBind
moc_kbbind.cpp, 1536
qt_meta_stringdata_KbBindWidget
moc_kbbindwidget.cpp, 1539
qt_meta_stringdata_KbFirmware
moc_kbfirmware.cpp, 1542
qt_meta_stringdata_KbLight
moc_kblight.cpp, 1545
qt_meta_stringdata_KbLightWidget
moc_kblightwidget.cpp, 1547
qt_meta_stringdata_KbManager
moc_kbmanager.cpp, 1549
qt_meta_stringdata_KbMode
moc_kbmode.cpp, 1552
qt_meta_stringdata_KbPerf
moc_kbperf.cpp, 1555
qt_meta_stringdata_KbProfile
moc_kbprofile.cpp, 1557
qt_meta_stringdata_KbProfileDialog
moc_kbprofiledialog.cpp, 1560
qt_meta_stringdata_KbWidget
moc_kbwidget.cpp, 1562
qt_meta_stringdata_KeyAction
moc_keyaction.cpp, 1565
qt_meta_stringdata_KeyWidget
moc_keywidget.cpp, 1567
qt_meta_stringdata_LayoutDialog
moc_layoutdialog.cpp, 1573
qt_meta_stringdata_MPerfWidget
moc_mperfwidget.cpp, 1583
qt_meta_stringdata_MacroReader
moc_macroreader.cpp, 1576
qt_meta_stringdata_MacroReaderThread
moc_macroreader.cpp, 1576
qt_meta_stringdata_MainWindow
moc_mainwindow.cpp, 1578
qt_meta_stringdata_ModeSelectDialog
moc_modeselectdialog.cpp, 1581
qt_meta_stringdata_QuaGzipFile
moc_quagzipfile.cpp, 1586
qt_meta_stringdata_QuaZIODevice
moc_quaziodevice.cpp, 1588
qt_meta_stringdata_QuaZipFile
moc_quazipfile.cpp, 1590
qt_meta_stringdata_RListWidget
moc_rlistwidget.cpp, 1594
qt_meta_stringdata_RebindWidget
moc_rebindwidget.cpp, 1592
qt_meta_stringdata_SettingsWidget
moc_settingswidget.cpp, 1597
qt_resource_data
qrc_binary.cpp, 1600
qrc_image.cpp, 1602
qrc_text.cpp, 1605
qt_resource_name
qrc_binary.cpp, 1600
qrc_image.cpp, 1602
qrc_text.cpp, 1605
qt_resource_struct
qrc_binary.cpp, 1600
qrc_image.cpp, 1603
qrc_text.cpp, 1605
QuaZip
csDefault, 823
csInsensitive, 823
csSensitive, 823
MAX_FILE_NAME_LENGTH, 823
mdAdd, 823
mdAppend, 823
mdCreate, 823
mdNotOpen, 823
mdUnzip, 823
QuaAdler32, 796
calculate, 798
checksum, 799
QuaAdler32, 798
QuaAdler32, 798
reset, 798
update, 799
value, 799
QuaChecksum32, 799
calculate, 801
reset, 801
update, 801
value, 801
QuaCrc32, 802
calculate, 804
checksum, 805
QuaCrc32, 804
QuaCrc32, 804
reset, 804
update, 805
value, 805
QuaGzipFile, 805
~QuaGzipFile, 809
close, 809

d, 812
flush, 810
getFileName, 810
isSequential, 810
open, 810, 811
operator=, 811
QuaGzipFile, 808, 809
QuaGzipFile, 808, 809
readData, 811
setFileName, 811
writeData, 811
QuaZIODevice, 812
~QuaZIODevice, 815
close, 815
d, 819
flush, 816
getIoDevice, 817
isSequential, 817
open, 817
QuaZIODevice, 815
QuaZIODevice, 815
readData, 818
writeData, 819
QuaZip, 820
~QuaZip, 824
CaseSensitivity, 823
close, 825
Constants, 823
convertCaseSensitivity, 826
getComment, 827
getCommentCodec, 827
getCurrentFileInfo, 828, 829
getCurrentFileName, 830
getEntriesCount, 831
getFileInfoList, 832
getFileInfoList64, 832
getFileNameCodec, 833
getFileNameList, 833
getIoDevice, 834
getMode, 834
getUnzFile, 835
getZipError, 836
getZipFile, 837
getZipName, 837
goToFirstFile, 838
goToNextFile, 839
hasCurrentFile, 840
isAutoClose, 840
isDataDescriptorWritingEnabled, 840
isOpen, 841
isZip64Enabled, 841
Mode, 823
open, 842
operator=, 845
p, 852
QuaZip, 824
QuaZipPrivate, 852
QuaZip, 824
QuaZipPrivate, 924
setAutoClose, 845
setComment, 846
setCommentCodec, 846
setCurrentFile, 846
setDataDescriptorWritingEnabled, 848
setDefaultFileNameCodec, 849
setFileNameCodec, 850
setIoDevice, 850
setZip64Enabled, 851
setZipName, 851
QuaZip_getFileInfo
quazip.cpp, 1345, 1346
QuaZipDir, 852
~QuaZipDir, 855
caseSensitivity, 856
cd, 856
cdUp, 858
count, 858
d, 869
dirName, 859
entryInfoList, 859, 860
entryInfoList64, 860, 861
entryList, 861, 862
exists, 862, 863
filePath, 864
filter, 864
isRoot, 865
nameFilters, 865
operator=, 866
operator==, 866
path, 866
QuaZipDir, 855
QuaZipDir, 855
relativeFilePath, 867
setCaseSensitivity, 867
setFilter, 868
setNameFilters, 868
setPath, 868
setSorting, 869
sorting, 869
QuaZipDir_convertInfoList
quazipdir.cpp, 1349, 1350
QuaZipDir_getFileInfo
quazipdir.cpp, 1350
QuaZipFile, 870
~QuaZipFile, 875
atEnd, 875
bytesAvailable, 876
close, 876
csize, 877
getActualFileName, 878
getCaseSensitivity, 879
getFileInfo, 879, 880
getFileName, 881
getZip, 881
getZipError, 881
getZipName, 882

isRaw, 882
isSequential, 883
open, 883–885
operator=, 887
p, 893
pos, 887
QuaZipFile, 873, 874
QuaZipFilePrivate, 892
QuaZipFile, 873, 874
QuaZipFilePrivate, 907
readData, 888
setFileName, 889
setZip, 889
setZipName, 890
size, 890
usize, 891
writeData, 892
QuaZipFileInfo, 893
comment, 895
compressedSize, 895
crc, 895
dateTime, 895
diskNumberStart, 895
externalAttr, 895
extra, 895
flags, 895
getPermissions, 894
internalAttr, 896
method, 896
name, 896
uncompressedSize, 896
versionCreated, 896
versionNeeded, 896
QuaZipFileInfo64, 896
comment, 902
compressedSize, 902
crc, 902
dateTime, 902
diskNumberStart, 902
externalAttr, 902
extra, 903
flags, 903
getNTFSaTime, 898
getNTFScTime, 899
getNTFSmTime, 899
getPermissions, 900
internalAttr, 903
isEncrypted, 901
method, 903
name, 903
toQuaZipFileInfo, 901
uncompressedSize, 903
versionCreated, 903
versionNeeded, 903
QuaZipFilePrivate, 904
~QuaZipFilePrivate, 906
caseSensitivity, 907
crc, 907
fileName, 907
internal, 907
q, 908
QuaZipFile, 907
QuaZipFilePrivate, 905, 906
QuaZipFile, 892
QuaZipFilePrivate, 905, 906
raw, 908
resetZipError, 906
setZipError, 906
uncompressedSize, 908
writePos, 908
zip, 908
zipError, 908
QuaZipNewInfo, 909
comment, 916
dateTime, 916
externalAttr, 916
extraGlobal, 917
extraLocal, 917
internalAttr, 917
name, 917
QuaZipNewInfo, 910, 911
QuaZipNewInfo, 910, 911
setFileDateTime, 912
setFileNTFSTimes, 915
setFileNTFSaTime, 912
setFileNTFScTime, 913
setFileNTFSmTime, 914
setFilePermissions, 915
setPermissions, 916
uncompressedSize, 917
QuaZipNewInfo_init
quazipnewinfo.cpp, 1357
QuaZipNewInfo_setPermissions
quazipnewinfo.cpp, 1358
QuaZipPrivate, 917
addCurrentFileToDirectoryMap, 920
autoClose, 924
clearDirectoryMap, 921
comment, 924
commentCodec, 924
dataDescriptorWritingEnabled, 924
defaultFileNameCodec, 925
directoryCaseInsensitive, 925
directoryCaseSensitive, 925
fileNameCodec, 925
getDefaultFileNameCodec, 922
getFileInfoList, 922
goToFirstUnmappedFile, 923
hasCurrentFile_f, 925
ioDevice, 925
lastMappedDirectoryEntry, 925
mode, 925
q, 926
QuaZip, 924
QuaZipPrivate, 919, 920
QuaZip, 852

QuaZipPrivate, 919, 920
zip64, 926
zipError, 926
zipName, 926
quaziodevice.cpp
QUAZIO_INBUFSIZE, 1343
QUAZIO_OUTBUFSIZE, 1343
quazip.cpp
QuaZip_getFileInfo, 1345, 1346
quazip.h
UNZ_OPENERROR, 1347
quazip_global.h
QUAZIP_EXPORT, 1348
UNUSED, 1349
quazipdir.cpp
QuaZipDir_convertInfoList, 1349, 1350
QuaZipDir_getFileInfo, 1350
quazipfileinfo.cpp
getNTFSTime, 1353
permissionsFromExternalAttr, 1355
quazipnewinfo.cpp
QuaZipNewInfo_init, 1357
QuaZipNewInfo_setPermissions, 1358
setNTFSTime, 1358
quitApp
MainWindow, 734

RGB
KPerfWidget, 698
README.md, 1199
RListWidget, 989
change, 991
currentData, 994
DATA_ROLE, 994
dragged, 994
enter, 991
orderChanged, 992
previousItems, 994
RListWidget, 991
reorderTimer, 994
rescanItems, 992
RListWidget, 991
timerTick, 993
ROADMAP.md, 1199
raw
QuaZipFilePrivate, 908
raw2Mode
KPerfWidget, 702
rbWidget
Ui::KbBindWidget, 395
Ui_KbBindWidget, 1078
reInit
KbAnim, 324
readAnyFrame
AnimScript, 83
readData
QuaGzipFile, 811
QuaZIODevice, 818
QuaZipFile, 888
readFrame
AnimScript, 83
readMacro
MacroReaderThread, 721
readNotify
Kb, 289
readProcess
AnimScript, 76
RebindWidget, 956
~RebindWidget, 961
applyChanges, 961
bind, 986
convertMacroBox, 963
fnKeys, 986
helpStatus, 964
macReader, 987
mediaKeys, 987
modKeys, 987
mouseExtKeys, 987
mouseKeys, 987
numKeys, 987
on_animBox_currentIndexChanged, 964
on_animButton_clicked, 965
on_applyButton_clicked, 965
on_btnClearMacro_clicked, 965
on_btnStartMacro_clicked, 966
on_btnStopMacro_clicked, 966
on_cancelButton_clicked, 967
on_dpiBox_currentIndexChanged, 968
on_dpiButton_clicked, 969
on_fnBox_currentIndexChanged, 969
on_fnButton_clicked, 969
on_lightBox_currentIndexChanged, 969
on_lightButton_clicked, 970
on_lockBox_currentIndexChanged, 970
on_lockButton_clicked, 970
on_mb2Box_currentIndexChanged, 971
on_mb2Button_clicked, 971
on_mbBox_currentIndexChanged, 971
on_mbButton_clicked, 972
on_mediaBox_currentIndexChanged, 972
on_mediaButton_clicked, 972
on_modBox_currentIndexChanged, 972
on_modButton_clicked, 973
on_modeBox_currentIndexChanged, 973
on_modeButton_clicked, 973
on_numBox_currentIndexChanged, 974
on_numButton_clicked, 974
on_programKpBox_textChanged, 974
on_programKpButton_clicked, 975
on_programKpSIBox_clicked, 975
on_programKrBox_textChanged, 975
on_programKrButton_clicked, 976
on_programKrSIBox_clicked, 976
on_pteMacroBox_textChanged, 976
on_resetButton_clicked, 977
on_typingBox_currentIndexChanged, 977
on_typingButton_clicked, 977

on_unbindButton_clicked, 978
on_wheelBox_currentIndexChanged, 978
on_wheelButton_clicked, 978
profile, 987
RebindWidget, 960
RebindWidget, 960
selection, 987
setBind, 979
setBox, 981
setSelection, 982
TAB_ANIM, 987
TAB_KB, 987
TAB_MACRO, 988
TAB_MOUSE, 988
TAB_PROGRAM, 988
TAB_SPECIAL, 988
typingKeys, 988
ui, 988
wheelKeys, 988
rebindwidget.cpp
DPI_CUST_IDX, 1499
DPI_OFFSET, 1499
rebuildBaseMap
KbLight, 441
refreshList
KbAnimWidget, 354
relProgram
KeyAction, 627
relativeFilePath
QuaZipDir, 867
remove
CkbSettings, 133
removeAll
KbProfile, 544
removeCache
CkbSettings, 137
removeDev
FwUpgradeDialog, 186
removeDevice
MainWindow, 735
removeFile
JlCompress, 253
reorderAnims
KbAnimWidget, 355
reorderTimer
RListWidget, 994
repeatBox
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
repeatKey
KbAnim, 332
repeatLabel
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
repeatLabel_2
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
repeatMsec
AnimScript, 83
KbAnim, 332
repeatTime
KbAnim, 332
repopulate
KbProfileDialog, 555
rescanItems
RListWidget, 992
reset
QuaAdler32, 798
QuaChecksum32, 801
QuaCrc32, 804
resetAction
KbBind, 380
resetButton
Ui::KbBindWidget, 395
Ui::RebindWidget, 954
Ui_KbBindWidget, 1079
Ui_RebindWidget, 1179
resetIndicators
KbLight, 442
resetParams
KbAnim, 324
resetZipError
QuaZipFilePrivate, 906
restartAnimation
KbLight, 442
restoreAction
MainWindow, 740
retranslateUi
Ui::AnimAddDialog, 48
Ui::AnimSettingDialog, 86
Ui::ExtraSettingsWidget, 160
Ui::FwUpgradeDialog, 190
Ui::GradientDialog, 202
Ui::KbAnimWidget, 334
Ui::KbBindWidget, 391
Ui::KbLightWidget, 450
Ui::KbProfileDialog, 559
Ui::KbWidget, 586
Ui::KPerfWidget, 677
Ui::LayoutDialog, 708
Ui::MainWindow, 724
Ui::ModeSelectDialog, 742
Ui::MPerfWidget, 752
Ui::RebindWidget, 930
Ui::SettingsWidget, 1008
Ui_AnimAddDialog, 1022
Ui_AnimSettingDialog, 1028
Ui_ExtraSettingsWidget, 1041
Ui_FwUpgradeDialog, 1052
Ui_GradientDialog, 1058
Ui_KbAnimWidget, 1066
Ui_KbBindWidget, 1075
Ui_KbLightWidget, 1081
Ui_KbProfileDialog, 1089
Ui_KbWidget, 1093
Ui_KPerfWidget, 1104

Ui_LayoutDialog, 1122
Ui_MainWindow, 1127
Ui_ModeSelectDialog, 1130
Ui_MPerfWidget, 1136
Ui_RebindWidget, 1156
Ui_SettingsWidget, 1183
retrigger
AnimScript, 77
rgbMode
KeyWidget, 667, 668
right
settingswidget.cpp, 1608
run
CkbSettingsWriter, 139
Kb, 293
MacroReaderThread, 721
runningPushIdx
KbPerf, 530

SABRE
KeyMap, 631
SCIMITAR
KeyMap, 631
SCROLL
KbPerf, 500
SE
KeyMap, 630
SET
KeyWidget, 654
SPECIAL
KeyAction, 601
STRAFE
KeyMap, 631
SUBTRACT
KeyWidget, 654
SABRE_HEIGHT
keymap.cpp, 1275
SABRE_WIDTH
keymap.cpp, 1275
sAccelBox
Ui::ExtraSettingsWidget, 168
Ui_ExtraSettingsWidget, 1048
sAuthorLabel
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
SCIM_HEIGHT
keymap.cpp, 1275
SCIM_WIDTH
keymap.cpp, 1275
sDescLabel
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
SEEK_CUR
qioapi.cpp, 1325
zip.c, 1440
SEEK_END
qioapi.cpp, 1325
zip.c, 1440
SEEK_SET
qioapi.cpp, 1325
zip.c, 1440
SET_END
mperfwidget.cpp, 1307
SET_START
mperfwidget.cpp, 1307
SGroup, 1018
~SGroup, 1020
_settings, 1020
SGroup, 1020
SGroup, 1020
SHMEM_SIZE
main.cpp, 1293
SHMEM_SIZE_V015
main.cpp, 1293
SIZECENTRALDIRITEM
unzip.c, 1367
SIZECENTRALHEADER
zip.c, 1440
SIZEDATA_INDATABLOCK
zip.c, 1440
SIZEZIPLOCALHEADER
unzip.c, 1367
sLicenseLabel
Ui::AnimSettingDialog, 96
Ui_AnimSettingDialog, 1037
SNIPER
KbPerf, 530
sNameLabel
Ui::AnimSettingDialog, 96
Ui_AnimSettingDialog, 1037
sSpeedBox
Ui::ExtraSettingsWidget, 168
Ui_ExtraSettingsWidget, 1049
sSpeedWidget
Ui::ExtraSettingsWidget, 168
Ui_ExtraSettingsWidget, 1049
sToL
kblight.cpp, 1257
sVerLabel
Ui::AnimSettingDialog, 96
Ui_AnimSettingDialog, 1037
sYearLabel
Ui::AnimSettingDialog, 96
Ui_AnimSettingDialog, 1037
sabOverlay
keywidget.cpp, 1286
SabreKeys
keymap.cpp, 1283
save
Kb, 294
KbAnim, 325
KbBind, 381
KbLight, 443
KbMode, 492
KbPerf, 522
KbProfile, 545
saveBlob

FwUpgradeDialog, 186
saveGlobalRemap
KbBind, 382
savePath
FwUpgradeDialog, 187
scan
AnimScript, 78
scanKeyboards
KbManager, 478
scanTimer
KbManager, 480
ScimKeys
keymap.cpp, 1283
scimOverlay
keywidget.cpp, 1286
script
KbAnim, 326
scriptName
KbAnim, 326
scripts
AnimAddDialog, 46
AnimScript, 83
scrollBox
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1119
scrollColorOff
Ui::KPerfWidget, 692
Ui_KPerfWidget, 1119
scrollColorOn
Ui::KPerfWidget, 693
Ui_KPerfWidget, 1119
scrollSpeed
Kb, 295
selAllButton
Ui::ModeSelectDialog, 744
Ui_ModeSelectDialog, 1132
selLabel
Ui::KbLightWidget, 456
Ui_KbLightWidget, 1087
selNoneButton
Ui::ModeSelectDialog, 745
Ui_ModeSelectDialog, 1133
selectAll
KeyWidget, 668
selectLabel
Ui::KbBindWidget, 395
Ui_KbBindWidget, 1079
selected
GradientDialogWidget, 236
LayoutDialog, 714
selectedKeys
KbAnimWidget, 359
selectedOffset
GradientDialogWidget, 236
selectedPos
GradientDialogWidget, 236
selectedStop
GradientDialogWidget, 231
selection
KeyWidget, 673
ModeSelectDialog, 748
RebindWidget, 987
selectionChanged
KeyWidget, 669
selectionColors
GradientDialogWidget, 232
selectionStack
Ui::KbAnimWidget, 341
Ui_KbAnimWidget, 1072
serialLabel
Ui::KbWidget, 593
Ui_KbWidget, 1100
set
CkbSettings, 133
setAction
KbBind, 383
setAnimation
KeyWidget, 669
setAnimationToSelection
KeyWidget, 670
setAutoClose
QuaZip, 845
setBind
KbBindWidget, 403
RebindWidget, 979
setBox
RebindWidget, 981
setCaseSensitivity
QuaZipDir, 867
setComment
QuaZip, 846
setCommentCodec
QuaZip, 846
setCurrent
KbAnimWidget, 356
setCurrentColor
GradientDialogWidget, 232
setCurrentFile
QuaZip, 846
setCurrentMode
Kb, 296, 297
setCurrentProfile
Kb, 298
setDataDescriptorWritingEnabled
QuaZip, 848
setDefaultFileNameCodec
QuaZip, 849
setDuration
AnimScript, 78
setFileDateTime
QuaZipNewInfo, 912
setFileNTFSTimes
QuaZipNewInfo, 915
setFileNTFSaTime
QuaZipNewInfo, 912
setFileNTFScTime

QuaZipNewInfo, 913
setFileNTFSmTime
QuaZipNewInfo, 914
setFileName
QuaGzipFile, 811
QuaZipFile, 889
setFileNameCodec
QuaZip, 850
setFilePermissions
QuaZipNewInfo, 915
setFilter
QuaZipDir, 868
setGlobalRemap
KbBind, 384
setIndicator
KbLight, 444
KbPerf, 523
setIoDevice
QuaZip, 850
setLabel
ColorButton, 146, 147
setLight
KbAnimWidget, 357
KbLightWidget, 465
setMonochrome
KbLightWidget, 466
setNTFSTime
quazipnewinfo.cpp, 1358
setNameFilters
QuaZipDir, 868
setNeedsSave
KbMode, 493
KbProfile, 546
setNeedsUpdate
KbBind, 385
KbMode, 494
KbPerf, 523
KbProfile, 546
setPath
QuaZipDir, 868
setPerf
KPerfWidget, 702
MPerfWidget, 781
setPermissions
QuaZipNewInfo, 916
setPreset
GradientDialog, 218
setSelectedKeys
KbAnimWidget, 358
setSelection
KeyWidget, 670
RebindWidget, 982
setSorting
QuaZipDir, 869
setStatus
SettingsWidget, 1002
setStops
GradientDialogWidget, 233
setValue
CkbSettings, 134
setVersion
SettingsWidget, 1003
setZip
QuaZipFile, 889
setZip64Enabled
QuaZip, 851
setZipError
QuaZipFilePrivate, 906
setZipName
QuaZip, 851
QuaZipFile, 890
settingPath
autorun.cpp, 1206
settingTab
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1037
settingWidgets
AnimSettingDialog, 117
settingsCacheMutex
ckbsettings.cpp, 1228
ckbsettingswriter.cpp, 1231
settingsGrid
Ui::AnimSettingDialog, 95
Ui_AnimSettingDialog, 1036
settingsMutex
ckbsettings.cpp, 1228
ckbsettingswriter.cpp, 1231
settingsUpdated
KbPerf, 524
SettingsWidget, 994
~SettingsWidget, 998
extra, 1005
MainWindow, 1005
on_altBox_activated, 998
on_autoFWBox_clicked, 999
on_capsBox_activated, 999
on_ctrlBox_activated, 999
on_extraButton_clicked, 1000
on_layoutBox_activated, 1000
on_loginItemBox_clicked, 1001
on_pushButton_clicked, 1001
on_shiftBox_activated, 1001
on_winBox_activated, 1002
pollUpdates, 1002
setStatus, 1002
setVersion, 1003
SettingsWidget, 997
SettingsWidget, 997
showLayoutDialog, 1003
ui, 1005
updateModifiers, 1004
settingsWidget
MainWindow, 740
settingswidget.cpp
devpath, 1608
modKeys, 1608

modNames, 1609
right, 1608
setupUi
Ui::AnimAddDialog, 49
Ui::AnimSettingDialog, 87
Ui::ExtraSettingsWidget, 161
Ui::FwUpgradeDialog, 190
Ui::GradientDialog, 203
Ui::KbAnimWidget, 335
Ui::KbBindWidget, 391
Ui::KbLightWidget, 451
Ui::KbProfileDialog, 560
Ui::KbWidget, 587
Ui::KPerfWidget, 678
Ui::LayoutDialog, 708
Ui::MainWindow, 724
Ui::ModeSelectDialog, 743
Ui::MPerfWidget, 753
Ui::RebindWidget, 933
Ui::SettingsWidget, 1009
Ui_AnimAddDialog, 1022
Ui_AnimSettingDialog, 1029
Ui_ExtraSettingsWidget, 1042
Ui_FwUpgradeDialog, 1052
Ui_GradientDialog, 1059
Ui_KbAnimWidget, 1066
Ui_KbBindWidget, 1075
Ui_KbLightWidget, 1082
Ui_KbProfileDialog, 1089
Ui_KbWidget, 1094
Ui_KPerfWidget, 1105
Ui_LayoutDialog, 1122
Ui_MainWindow, 1127
Ui_ModeSelectDialog, 1131
Ui_MPerfWidget, 1137
Ui_RebindWidget, 1158
Ui_SettingsWidget, 1184
shareDimming
KbLight, 444, 445
shiftBox
Ui::SettingsWidget, 1016
Ui_SettingsWidget, 1191
shiftLabel
Ui::SettingsWidget, 1017
Ui_SettingsWidget, 1191
showAnimBox
Ui::KbLightWidget, 456
Ui_KbLightWidget, 1087
showFirstTab
KbWidget, 580
showFwUpdate
KbWidget, 580
showFwUpdateNotification
MainWindow, 735
showLastTab
KbWidget, 581
showLayoutDialog
SettingsWidget, 1003
showPreview
AnimAddDialog, 46
showWindow
MainWindow, 736
sidelightToggled
KeyWidget, 671
size
QuaZipFile, 890
sliderXMapper
MPerfWidget, 785
sliderXMoved
MPerfWidget, 782
sliderYMapper
MPerfWidget, 785
sliderYMoved
MPerfWidget, 783
sniperDpi
KbPerf, 524, 525
sniperValue
KeyAction, 627
sorting
QuaZipDir, 869
specialInfo
KeyAction, 623
spinBox
Ui::MPerfWidget, 765
Ui_MPerfWidget, 1149
src/ckb/animadddialog.cpp, 1199
src/ckb/animadddialog.h, 1199
src/ckb/animscript.cpp, 1200
src/ckb/animscript.h, 1202
src/ckb/animsettingdialog.cpp, 1203
src/ckb/animsettingdialog.h, 1205
src/ckb/autorun.cpp, 1205
src/ckb/autorun.h, 1206
src/ckb/ckb-anim.h, 1207
src/ckb/ckbsettings.cpp, 1226
src/ckb/ckbsettings.h, 1228
src/ckb/ckbsettingswriter.cpp, 1229
src/ckb/ckbsettingswriter.h, 1231
src/ckb/colorbutton.cpp, 1231
src/ckb/colorbutton.h, 1232
src/ckb/colormap.cpp, 1233
src/ckb/colormap.h, 1234
src/ckb/extrasettingswidget.cpp, 1235
src/ckb/extrasettingswidget.h, 1236
src/ckb/fwupgradedialog.cpp, 1236
src/ckb/fwupgradedialog.h, 1239
src/ckb/gradientbutton.cpp, 1240
src/ckb/gradientbutton.h, 1241
src/ckb/gradientdialog.cpp, 1242
src/ckb/gradientdialog.h, 1242
src/ckb/gradientdialogwidget.cpp, 1243
src/ckb/gradientdialogwidget.h, 1243
src/ckb/kb.cpp, 1244
src/ckb/kb.h, 1245
src/ckb/kbanim.cpp, 1246
src/ckb/kbanim.h, 1248

src/ckb/kbanimwidget.cpp, 1249
src/ckb/kbanimwidget.h, 1249
src/ckb/kbbind.cpp, 1250
src/ckb/kbbind.h, 1251
src/ckb/kbbindwidget.cpp, 1252
src/ckb/kbbindwidget.h, 1252
src/ckb/kbfirmware.cpp, 1253
src/ckb/kbfirmware.h, 1254
src/ckb/kblight.cpp, 1255
src/ckb/kblight.h, 1258
src/ckb/kblightwidget.cpp, 1259
src/ckb/kblightwidget.h, 1259
src/ckb/kbmanager.cpp, 1260
src/ckb/kbmanager.h, 1261
src/ckb/kbmode.cpp, 1262
src/ckb/kbmode.h, 1262
src/ckb/kbperf.cpp, 1263
src/ckb/kbperf.h, 1263
src/ckb/kbprofile.cpp, 1264
src/ckb/kbprofile.h, 1265
src/ckb/kbprofiledialog.cpp, 1265
src/ckb/kbprofiledialog.h, 1266
src/ckb/kbwidget.cpp, 1267
src/ckb/kbwidget.h, 1267
src/ckb/keyaction.cpp, 1268
src/ckb/keyaction.h, 1269
src/ckb/keymap.cpp, 1270
src/ckb/keymap.h, 1284
src/ckb/keywidget.cpp, 1284
src/ckb/keywidget.h, 1286
src/ckb/kperfwidget.cpp, 1287
src/ckb/kperfwidget.h, 1288
src/ckb/layoutdialog.cpp, 1290
src/ckb/layoutdialog.h, 1290
src/ckb/macroreader.cpp, 1291
src/ckb/macroreader.h, 1291
src/ckb/main.cpp, 1292
src/ckb/mainwindow.cpp, 1299
src/ckb/mainwindow.h, 1299
src/ckb/media.h, 1300
src/ckb/media_linux.cpp, 1302
src/ckb/media_mac.m, 1303
src/ckb/modeselectdialog.cpp, 1305
src/ckb/modeselectdialog.h, 1305
src/ckb/mperfwidget.cpp, 1306
src/ckb/mperfwidget.h, 1309
src/ckb/quazip/JlCompress.cpp, 1321
src/ckb/quazip/JlCompress.h, 1323
src/ckb/quazip/crypt.h, 1311
src/ckb/quazip/ioapi.h, 1314
src/ckb/quazip/qioapi.cpp, 1323
src/ckb/quazip/quaadler32.cpp, 1335
src/ckb/quazip/quaadler32.h, 1336
src/ckb/quazip/quachecksum32.h, 1337
src/ckb/quazip/quacrc32.cpp, 1338
src/ckb/quazip/quacrc32.h, 1339
src/ckb/quazip/quagzipfile.cpp, 1340
src/ckb/quazip/quagzipfile.h, 1341
src/ckb/quazip/quaziodevice.cpp, 1342
src/ckb/quazip/quaziodevice.h, 1343
src/ckb/quazip/quazip.cpp, 1344
src/ckb/quazip/quazip.h, 1346
src/ckb/quazip/quazip_global.h, 1347
src/ckb/quazip/quazipdir.cpp, 1349
src/ckb/quazip/quazipdir.h, 1351
src/ckb/quazip/quazipfile.cpp, 1351
src/ckb/quazip/quazipfile.h, 1352
src/ckb/quazip/quazipfileinfo.cpp, 1353
src/ckb/quazip/quazipfileinfo.h, 1355
src/ckb/quazip/quazipnewinfo.cpp, 1356
src/ckb/quazip/quazipnewinfo.h, 1360
src/ckb/quazip/unzip.c, 1361
src/ckb/quazip/unzip.h, 1412
src/ckb/quazip/zip.c, 1432
src/ckb/quazip/zip.h, 1488
src/ckb/rebindwidget.cpp, 1499
src/ckb/rebindwidget.h, 1499
src/ckb/release/moc_animadddialog.cpp, 1500
src/ckb/release/moc_animscript.cpp, 1503
src/ckb/release/moc_animsettingdialog.cpp, 1506
src/ckb/release/moc_ckbsettingswriter.cpp, 1509
src/ckb/release/moc_colorbutton.cpp, 1511
src/ckb/release/moc_extrasettingswidget.cpp, 1513
src/ckb/release/moc_fwupgradedialog.cpp, 1516
src/ckb/release/moc_gradientbutton.cpp, 1519
src/ckb/release/moc_gradientdialog.cpp, 1522
src/ckb/release/moc_gradientdialogwidget.cpp, 1525
src/ckb/release/moc_kb.cpp, 1527
src/ckb/release/moc_kbanim.cpp, 1530
src/ckb/release/moc_kbanimwidget.cpp, 1532
src/ckb/release/moc_kbbind.cpp, 1535
src/ckb/release/moc_kbbindwidget.cpp, 1537
src/ckb/release/moc_kbfirmware.cpp, 1539
src/ckb/release/moc_kblight.cpp, 1542
src/ckb/release/moc_kblightwidget.cpp, 1545
src/ckb/release/moc_kbmanager.cpp, 1548
src/ckb/release/moc_kbmode.cpp, 1550
src/ckb/release/moc_kbperf.cpp, 1552
src/ckb/release/moc_kbprofile.cpp, 1555
src/ckb/release/moc_kbprofiledialog.cpp, 1557
src/ckb/release/moc_kbwidget.cpp, 1561
src/ckb/release/moc_keyaction.cpp, 1563
src/ckb/release/moc_keywidget.cpp, 1565
src/ckb/release/moc_kperfwidget.cpp, 1567
src/ckb/release/moc_layoutdialog.cpp, 1570
src/ckb/release/moc_macroreader.cpp, 1573
src/ckb/release/moc_mainwindow.cpp, 1577
src/ckb/release/moc_modeselectdialog.cpp, 1579
src/ckb/release/moc_mperfwidget.cpp, 1581
src/ckb/release/moc_quagzipfile.cpp, 1584
src/ckb/release/moc_quaziodevice.cpp, 1586
src/ckb/release/moc_quazipfile.cpp, 1588
src/ckb/release/moc_rebindwidget.cpp, 1590
src/ckb/release/moc_rlistwidget.cpp, 1593
src/ckb/release/moc_settingswidget.cpp, 1595
src/ckb/release/qrc_binary.cpp, 1597

src/ckb/release/qrc_image.cpp, 1600
src/ckb/release/qrc_text.cpp, 1603
src/ckb/rlistwidget.cpp, 1606
src/ckb/rlistwidget.h, 1606
src/ckb/settingswidget.cpp, 1607
src/ckb/settingswidget.h, 1609
src/ckb/ui_animadddialog.h, 1610
src/ckb/ui_animsettingdialog.h, 1611
src/ckb/ui_extrasettingswidget.h, 1611
src/ckb/ui_fwupgradedialog.h, 1612
src/ckb/ui_gradientdialog.h, 1613
src/ckb/ui_kbanimwidget.h, 1614
src/ckb/ui_kbbindwidget.h, 1615
src/ckb/ui_kblightwidget.h, 1616
src/ckb/ui_kbprofiledialog.h, 1617
src/ckb/ui_kbwidget.h, 1618
src/ckb/ui_kperfwidget.h, 1619
src/ckb/ui_layoutdialog.h, 1620
src/ckb/ui_mainwindow.h, 1621
src/ckb/ui_modeselectdialog.h, 1622
src/ckb/ui_mperfwidget.h, 1623
src/ckb/ui_rebindwidget.h, 1624
src/ckb/ui_settingswidget.h, 1625
stages
    MPerfWidget, 786
standardMaps
    keymap.cpp, 1283
startWorkInAThread
    MacroReader, 717
stateChange
    MainWindow, 736
statusLabel
    Ui::FwUpgradeDialog, 194
    Ui_FwUpgradeDialog, 1056
stop
    AnimScript, 79
    KbAnim, 327
    KbManager, 480
stopBox
    Ui::GradientDialog, 207
    Ui_GradientDialog, 1063
stopCheck
    AnimSettingDialog, 117
stopColor
    Ui::GradientDialog, 207
    Ui_GradientDialog, 1063
stopCount
    GradientDialogWidget, 234
stopOpacity
    Ui::GradientDialog, 207
    Ui_GradientDialog, 1063
stopPos
    Ui::GradientDialog, 207
    Ui_GradientDialog, 1063
stopPreview
    KbLight, 445
stopRect
    GradientDialogWidget, 234
stopTime
    KbAnim, 332
stopped
    AnimScript, 83
stops
    GradientDialogWidget, 235
storageName
    Key, 596
strLayout
    KeyMap, 648
strModel
    KeyMap, 648
strcmpcasenosensitive_internal
    unzip.c, 1368
Subtract
    KbAnim, 308

TOGGLE
    KeyWidget, 654
TAB_ANIM
    RebindWidget, 987
TAB_KB
    RebindWidget, 987
TAB_MACRO
    RebindWidget, 988
TAB_MOUSE
    RebindWidget, 988
TAB_PROGRAM
    RebindWidget, 988
TAB_SPECIAL
    RebindWidget, 988
TRUE
    ckb-anim.h, 1217
TRYFREE
    unzip.c, 1367
    zip.c, 1440
tabWidget
    Ui::AnimSettingDialog, 96
    Ui::KbWidget, 593
    Ui::MainWindow, 726
    Ui::RebindWidget, 954
    Ui_AnimSettingDialog, 1037
    Ui_KbWidget, 1100
    Ui_MainWindow, 1129
    Ui_RebindWidget, 1179
tableDownload
    KbFirmware, 419
tableName
    kbfirmware.cpp, 1254
timeGrid
    Ui::AnimSettingDialog, 96
    Ui_AnimSettingDialog, 1037
timeTab
    Ui::AnimSettingDialog, 96
    Ui_AnimSettingDialog, 1037
timerTick
    MainWindow, 737
    RListWidget, 993
tm_unz_s, 1414

tm_zip_s, 1490
tm_unz
unzip.h, 1422
tm_zip
zip.h, 1494
toQuaZipFileInfo
QuaZipFileInfo64, 901
toStorage
KeyMap, 649
toString
GradientButton, 198
toggleSidelight
KbLightWidget, 467
toggleTrayIcon
MainWindow, 738
trayBox
Ui::ExtraSettingsWidget, 168
Ui_ExtraSettingsWidget, 1049
trayIcon
MainWindow, 740
trayIconMenu
MainWindow, 740
trigger
KbAnim, 328
Type
KeyAction, 601
type
KeyAction, 623
typingBox
Ui::RebindWidget, 954
Ui_RebindWidget, 1179
typingButton
Ui::RebindWidget, 954
Ui_RebindWidget, 1179
typingKeys
RebindWidget, 988

UNBOUND
KeyAction, 601
UNKNOWN
KbFirmware, 410
media.h, 1301
UNMUTED
media.h, 1301
US
KeyMap, 630
US_DVORAK
KeyMap, 630
UNUSED
quazip_global.h, 1349
UNZ_AUTO_CLOSE
unzip.h, 1420
UNZ_BADZIPFILE
unzip.h, 1420
UNZ_BUFSIZE
unzip.c, 1367
UNZ_CRCERROR
unzip.h, 1420
UNZ_DEFAULT_FLAGS
unzip.h, 1420
UNZ_EOF
unzip.h, 1421
UNZ_ERRNO
unzip.h, 1421
UNZ_INTERNALERROR
unzip.h, 1421
UNZ_MAXFILENAMEINZIP
unzip.c, 1367
UNZ_OK
unzip.h, 1421
UNZ_OPENERROR
quazip.h, 1347
UNZ_PARAMERROR
unzip.h, 1421
Ui, 39
ui
AnimAddDialog, 47
AnimSettingDialog, 117
ExtraSettingsWidget, 178
FwUpgradeDialog, 188
GradientDialog, 221
KbAnimWidget, 359
KbBindWidget, 407
KbLightWidget, 469
KbProfileDialog, 557
KbWidget, 584
KPerfWidget, 706
LayoutDialog, 714
MainWindow, 740
ModeSelectDialog, 748
MPerfWidget, 786
RebindWidget, 988
SettingsWidget, 1005
Ui::AnimAddDialog, 47
animBox, 50
buttonBox, 51
gridLayout, 51
horizontalLayout, 51
horizontalSpacer, 51
horizontalSpacer_2, 51
label, 51
label_2, 51
presetBox, 51
previewBox, 51
retranslateUi, 48
setupUi, 49
verticalSpacer_2, 52
verticalSpacer_3, 52
Ui::AnimSettingDialog, 84
animName, 91
buttonBox, 91
delayBox, 91
gridLayout, 91
gridLayout_2, 92
horizontalSpacer, 92
horizontalSpacer_2, 92
horizontalSpacer_3, 92

horizontalSpacer_4, 92
horizontalSpacer_5, 92
horizontalSpacer_6, 92
infoTab, 92
kpDelayBox, 92
kpModeStopBox, 93
kpReleaseBox, 93
kpRepeatBox, 93
kpRepeatLabel, 93
kpRepeatLabel_2, 93
label, 93
label_10, 93
label_11, 93
label_12, 93
label_13, 94
label_2, 94
label_3, 94
label_4, 94
label_5, 94
label_6, 94
label_7, 94
label_8, 94
label_9, 94
line, 95
line_2, 95
repeatBox, 95
repeatLabel, 95
repeatLabel_2, 95
retranslateUi, 86
sAuthorLabel, 95
sDescLabel, 95
sLicenseLabel, 96
sNameLabel, 96
sVerLabel, 96
sYearLabel, 96
settingTab, 95
settingsGrid, 95
setupUi, 87
tabWidget, 96
timeGrid, 96
timeTab, 96
verticalSpacer, 96
verticalSpacer_2, 96
verticalSpacer_3, 97
Ui::ExtraSettingsWidget, 157
animCountLabel, 165
animPathLabel, 165
animScanButton, 165
brightnessBox, 165
buttonBox, 165
delayBox, 165
ditherBox, 165
fpsBox, 165
fpsWarnLabel, 165
gridLayout, 166
horizontalLayout, 166
horizontalLayout_2, 166
horizontalSpacer, 166
horizontalSpacer_2, 166
horizontalSpacer_3, 166
label, 166
label_10, 166
label_11, 166
label_2, 167
label_3, 167
label_5, 167
label_6, 167
line, 167
line_2, 167
line_3, 167
mAccelBox, 167
osxLabel, 167
osxLine, 168
retranslateUi, 160
sAccelBox, 168
sSpeedBox, 168
sSpeedWidget, 168
setupUi, 161
trayBox, 168
verticalSpacer, 168
verticalSpacer_10, 168
verticalSpacer_11, 168
verticalSpacer_2, 169
verticalSpacer_3, 169
verticalSpacer_4, 169
verticalSpacer_5, 169
verticalSpacer_6, 169
verticalSpacer_7, 169
verticalSpacer_8, 169
verticalSpacer_9, 169
Ui::FwUpgradeDialog, 188
actionButton, 192
cancelButton, 192
curLabel, 192
devLabel, 192
gridLayout, 193
gridLayout_2, 193
horizontalSpacer, 193
horizontalSpacer_2, 193
horizontalSpacer_3, 193
horizontalSpacer_4, 193
label_2, 193
label_4, 193
newLabel, 193
progressBar, 194
retranslateUi, 190
setupUi, 190
statusLabel, 194
Ui::GradientDialog, 200
buttonBox, 205
gridLayout, 205
gridLayout_2, 205
gridLayout_3, 205
groupBox_2, 206
horizontalLayout, 206
horizontalLayout_2, 206

horizontalSpacer, 206
horizontalSpacer_2, 206
horizontalSpacer_3, 206
label, 206
label_2, 206
presetDelete, 206
presetList, 207
presetName, 207
presetSave, 207
retranslateUi, 202
setupUi, 203
stopBox, 207
stopColor, 207
stopOpacity, 207
stopPos, 207
verticalSpacer, 207
verticalSpacer_2, 208
widget, 208
Ui::KPerfWidget, 673
capsBox, 685
capsColorOff, 685
capsColorOn, 685
copyButton, 685
gridLayout, 685
horizontalLayout, 685
horizontalLayout_2, 685
horizontalSpacer, 685
horizontalSpacer_2, 686
horizontalSpacer_3, 686
horizontalSpacer_4, 686
horizontalSpacer_5, 686
horizontalSpacer_6, 686
horizontalSpacer_7, 686
horizontalSpacer_8, 686
intensityBox, 686
k95Label1, 686
k95Label2, 687
k95Label3, 687
k95Label4, 687
k95Label5, 687
k95Label6, 687
k95Line, 687
k95Spacer, 687
label, 687
label_10, 687
label_11, 688
label_12, 688
label_14, 688
label_15, 688
label_16, 688
label_17, 688
label_18, 688
label_19, 688
label_2, 688
label_20, 689
label_21, 689
label_22, 689
label_23, 689
label_24, 689
label_3, 689
label_4, 689
label_5, 689
label_6, 689
label_7, 690
label_8, 690
lightBox, 690
lightColor1, 690
lightColor2, 690
lightColor3, 690
line, 690
line_2, 690
line_3, 690
lockBox, 691
lockColorOff, 691
lockColorOn, 691
macroBox, 691
macroColorOff, 691
macroColorOn, 691
modeBox, 691
modeColorOff, 691
modeColorOn, 691
muteBox, 692
muteColorNA, 692
muteColorOff, 692
muteColorOn, 692
numBox, 692
numColorOff, 692
numColorOn, 692
retranslateUi, 677
scrollBox, 692
scrollColorOff, 692
scrollColorOn, 693
setupUi, 678
verticalSpacer, 693
verticalSpacer_2, 693
verticalSpacer_3, 693
verticalSpacer_4, 693
Ui::KbAnimWidget, 332
aCopyLabel, 338
aMissingLabel, 338
aMissingPage, 338
aNameLabel, 338
aVerLabel, 339
animList, 338
animPage, 338
blendBox, 339
deleteButton, 339
gridLayout, 339
gridLayout_2, 339
gridLayout_3, 339
gridLayout_4, 339
horizontalLayout, 339
horizontalSpacer, 339
horizontalSpacer_2, 340
horizontalSpacer_3, 340
horizontalSpacer_4, 340

horizontalSpacer_5, 340
keyButton, 340
label_5, 340
label_6, 340
label_7, 340
nameBox, 340
noAnimLabel, 341
noSelPage, 341
opacityBox, 341
propertyButton, 341
retranslateUi, 334
selectionStack, 341
setupUi, 335
verticalLayout, 341
verticalSpacer, 341
verticalSpacer_2, 341
verticalSpacer_3, 341
Ui::KbBindWidget, 389
copyButton, 394
gridLayout, 394
gridLayout_2, 394
horizontalLayout_2, 394
horizontalSpacer, 394
horizontalSpacer_2, 394
keyWidget, 395
label, 395
label_2, 395
line, 395
line_2, 395
rbWidget, 395
resetButton, 395
retranslateUi, 391
selectLabel, 395
setupUi, 391
verticalLayout, 395
verticalSpacer, 396
widget, 396
Ui::KbLightWidget, 448
animButton, 454
animWidget, 454
bgButton, 454
brightnessBox, 454
gridLayout, 454
gridLayout_2, 454
gridLayout_4, 454
horizontalLayout, 455
horizontalLayout_2, 455
horizontalLayout_3, 455
horizontalSpacer_3, 455
horizontalSpacer_4, 455
horizontalSpacer_5, 455
horizontalSpacer_6, 455
keyWidget, 455
label, 455
label_2, 456
label_3, 456
line, 456
line_2, 456
retranslateUi, 450
selLabel, 456
setupUi, 451
showAnimBox, 456
verticalLayout, 456
verticalSpacer_2, 456
verticalSpacer_3, 456
widget, 457
Ui::KbProfileDialog, 557
buttonBox, 561
gridLayout, 561
horizontalSpacer, 561
horizontalSpacer_2, 561
profileList, 561
retranslateUi, 559
setupUi, 560
Ui::KbWidget, 584
bindTab, 590
bindWidget, 590
devTab, 590
fwLabel, 590
fwUpdButton, 590
fwUpdLabel, 591
fwUpdLayout, 591
gridLayout, 591
gridLayout_2, 591
gridLayout_3, 591
gridLayout_4, 591
gridLayout_5, 591
gridLayout_7, 591
horizontalSpacer_2, 591
horizontalSpacer_3, 592
hwSaveButton, 592
kPerfTab, 592
kPerfWidget, 592
label_3, 592
label_4, 592
label_9, 592
lightTab, 592
lightWidget, 592
mPerfTab, 593
mPerfWidget, 593
modesList, 593
pollLabel, 593
pollLabel2, 593
profileBox, 593
retranslateUi, 586
serialLabel, 593
setupUi, 587
tabWidget, 593
verticalSpacer, 593
Ui::LayoutDialog, 706
buttonBox, 710
comboBox, 710
gridLayout, 710
horizontalSpacer, 710
horizontalSpacer_2, 710
label, 710

label_2, 711
retranslateUi, 708
setupUi, 708
verticalSpacer, 711
verticalSpacer_2, 711
verticalSpacer_3, 711
verticalSpacer_4, 711
Ui::MPerfWidget, 749
aSnapBox, 760
copyButton, 760
eBox1, 760
eBox2, 760
eBox3, 761
eBox4, 761
eBox5, 761
gridLayout, 761
horizontalLayout, 761
horizontalLayout_2, 761
horizontalLayout_4, 761
horizontalSpacer, 761
horizontalSpacer_2, 761
horizontalSpacer_3, 762
horizontalSpacer_4, 762
horizontalSpacer_5, 762
horizontalSpacer_6, 762
horizontalSpacer_7, 762
iButton0, 762
iButton1, 762
iButton2, 762
iButton3, 762
iButton4, 763
iButton5, 763
iButtonO, 763
indicBox, 763
lHeightBox, 765
label, 763
label_11, 763
label_12, 763
label_13, 763
label_14, 763
label_15, 764
label_2, 764
label_25, 764
label_3, 764
label_4, 764
label_5, 764
label_6, 764
label_7, 764
label_8, 764
line, 765
line_2, 765
line_3, 765
retranslateUi, 752
setupUi, 753
spinBox, 765
verticalLayout, 765
verticalSpacer, 765
verticalSpacer_2, 765
verticalSpacer_3, 765
xBox0, 766
xBox1, 766
xBox2, 766
xBox3, 766
xBox4, 766
xBox5, 766
xSlider0, 766
xSlider1, 766
xSlider2, 766
xSlider3, 767
xSlider4, 767
xSlider5, 767
xyBox, 767
yBox0, 767
yBox1, 767
yBox2, 767
yBox3, 767
yBox4, 767
yBox5, 768
ySlider0, 768
ySlider1, 768
ySlider2, 768
ySlider3, 768
ySlider4, 768
ySlider5, 768
Ui::MainWindow, 722
actionAbout, 725
actionExit, 725
centralWidget, 725
gridLayout, 726
retranslateUi, 724
setupUi, 724
tabWidget, 726
Ui::ModeSelectDialog, 741
buttonBox, 744
gridLayout, 744
label, 744
modeList, 744
retranslateUi, 742
selAllButton, 744
selNoneButton, 745
setupUi, 743
Ui::RebindWidget, 927
actionTab, 942
animBox, 942
animButton, 942
animKrBox, 942
animOnceBox, 942
animTab, 943
applyButton, 943
btnClearMacro, 943
btnStartMacro, 943
btnStopMacro, 943
cancelButton, 943
dpiBox, 943
dpiButton, 943
dpiCustLabel, 944

dpiCustXBox, 944
dpiCustYBox, 944
dpiWarning, 944
fnBox, 944
fnButton, 944
gridLayout, 944
gridLayout_10, 944
gridLayout_2, 945
gridLayout_3, 945
gridLayout_4, 945
gridLayout_5, 945
gridLayout_8, 945
groupBox, 945
groupBox_2, 945
groupBox_3, 945
groupBox_4, 945
horizontalLayout, 946
horizontalLayout_2, 946
horizontalLayout_3, 946
horizontalSpacer, 946
horizontalSpacer_10, 946
horizontalSpacer_11, 946
horizontalSpacer_12, 946
horizontalSpacer_13, 946
horizontalSpacer_14, 946
horizontalSpacer_15, 947
horizontalSpacer_16, 947
horizontalSpacer_17, 947
horizontalSpacer_18, 947
horizontalSpacer_19, 947
horizontalSpacer_2, 947
horizontalSpacer_20, 947
horizontalSpacer_21, 947
horizontalSpacer_22, 947
horizontalSpacer_23, 948
horizontalSpacer_24, 948
horizontalSpacer_25, 948
horizontalSpacer_26, 948
horizontalSpacer_3, 948
horizontalSpacer_4, 948
horizontalSpacer_5, 948
horizontalSpacer_6, 948
horizontalSpacer_7, 948
horizontalSpacer_8, 949
horizontalSpacer_9, 949
keyTab, 949
layoutWidget, 949
layoutWidget1, 949
layoutWidget_2, 949
lbl_macro, 949
lightBox, 949
lightButton, 949
lightWrapBox, 950
lockBox, 950
lockButton, 950
macroTab, 950
mb2Box, 950
mb2Button, 950
mbBox, 950
mbButton, 951
mediaBox, 951
mediaButton, 951
modBox, 951
modButton, 951
modeBox, 951
modeButton, 951
modeWrapBox, 951
mouseTab, 952
numBox, 952
numButton, 952
progTipLabel, 953
programKpBox, 952
programKpButton, 952
programKpExtra, 952
programKpModeBox, 952
programKpSIBox, 952
programKrBox, 953
programKrButton, 953
programKrExtra, 953
programKrModeBox, 953
programKrSIBox, 953
programTab, 953
pteMacroBox, 953
pteMacroComment, 954
pteMacroText, 954
resetButton, 954
retranslateUi, 930
setupUi, 933
tabWidget, 954
typingBox, 954
typingButton, 954
unbindButton, 954
verticalLayout, 954
verticalLayout_2, 955
verticalSpacer, 955
verticalSpacer_10, 955
verticalSpacer_11, 955
verticalSpacer_2, 955
verticalSpacer_3, 955
verticalSpacer_4, 955
verticalSpacer_5, 955
verticalSpacer_6, 955
verticalSpacer_7, 956
verticalSpacer_8, 956
wheelBox, 956
wheelButton, 956
Ui::SettingsWidget, 1006
altBox, 1013
altLabel, 1013
autoFWBox, 1013
capsBox, 1013
capsLabel, 1013
ctrlBox, 1014
ctrlLabel, 1014
devicesLabel, 1014
extraButton, 1014

gridLayout, 1014
gridLayout_3, 1014
gridLayout_5, 1014
horizontalLayout, 1014
horizontalLayout_2, 1014
horizontalSpacer, 1015
horizontalSpacer_10, 1015
horizontalSpacer_2, 1015
horizontalSpacer_7, 1015
horizontalSpacer_9, 1015
label, 1015
label_2, 1015
label_3, 1015
label_5, 1015
label_6, 1016
label_8, 1016
layoutBox, 1016
line, 1016
line_2, 1016
line_3, 1016
loginItemBox, 1016
pushButton, 1016
retranslateUi, 1008
setupUi, 1009
shiftBox, 1016
shiftLabel, 1017
versionLabel, 1017
verticalSpacer, 1017
verticalSpacer_10, 1017
verticalSpacer_2, 1017
verticalSpacer_3, 1017
verticalSpacer_4, 1017
verticalSpacer_5, 1017
verticalSpacer_6, 1017
verticalSpacer_7, 1018
verticalSpacer_8, 1018
winBox, 1018
winLabel, 1018
Ui_AnimAddDialog, 1021
animBox, 1024
buttonBox, 1024
gridLayout, 1024
horizontalLayout, 1024
horizontalSpacer, 1024
horizontalSpacer_2, 1024
label, 1025
label_2, 1025
presetBox, 1025
previewBox, 1025
retranslateUi, 1022
setupUi, 1022
verticalSpacer_2, 1025
verticalSpacer_3, 1025
Ui_AnimSettingDialog, 1025
animName, 1032
buttonBox, 1032
delayBox, 1033
gridLayout, 1033
gridLayout_2, 1033
horizontalSpacer, 1033
horizontalSpacer_2, 1033
horizontalSpacer_3, 1033
horizontalSpacer_4, 1033
horizontalSpacer_5, 1033
horizontalSpacer_6, 1033
infoTab, 1033
kpDelayBox, 1034
kpModeStopBox, 1034
kpReleaseBox, 1034
kpRepeatBox, 1034
kpRepeatLabel, 1034
kpRepeatLabel_2, 1034
label, 1034
label_10, 1034
label_11, 1034
label_12, 1035
label_13, 1035
label_2, 1035
label_3, 1035
label_4, 1035
label_5, 1035
label_6, 1035
label_7, 1035
label_8, 1035
label_9, 1036
line, 1036
line_2, 1036
repeatBox, 1036
repeatLabel, 1036
repeatLabel_2, 1036
retranslateUi, 1028
sAuthorLabel, 1036
sDescLabel, 1036
sLicenseLabel, 1037
sNameLabel, 1037
sVerLabel, 1037
sYearLabel, 1037
settingTab, 1037
settingsGrid, 1036
setupUi, 1029
tabWidget, 1037
timeGrid, 1037
timeTab, 1037
verticalSpacer, 1037
verticalSpacer_2, 1038
verticalSpacer_3, 1038
Ui_ExtraSettingsWidget, 1038
animCountLabel, 1045
animPathLabel, 1045
animScanButton, 1046
brightnessBox, 1046
buttonBox, 1046
delayBox, 1046
ditherBox, 1046
fpsBox, 1046
fpsWarnLabel, 1046

gridLayout, 1046
horizontalLayout, 1046
horizontalLayout_2, 1047
horizontalSpacer, 1047
horizontalSpacer_2, 1047
horizontalSpacer_3, 1047
label, 1047
label_10, 1047
label_11, 1047
label_2, 1047
label_3, 1047
label_5, 1048
label_6, 1048
line, 1048
line_2, 1048
line_3, 1048
mAccelBox, 1048
osxLabel, 1048
osxLine, 1048
retranslateUi, 1041
sAccelBox, 1048
sSpeedBox, 1049
sSpeedWidget, 1049
setupUi, 1042
trayBox, 1049
verticalSpacer, 1049
verticalSpacer_10, 1049
verticalSpacer_11, 1049
verticalSpacer_2, 1049
verticalSpacer_3, 1049
verticalSpacer_4, 1049
verticalSpacer_5, 1050
verticalSpacer_6, 1050
verticalSpacer_7, 1050
verticalSpacer_8, 1050
verticalSpacer_9, 1050
Ui_FwUpgradeDialog, 1050
actionButton, 1054
cancelButton, 1055
curLabel, 1055
devLabel, 1055
gridLayout, 1055
gridLayout_2, 1055
horizontalSpacer, 1055
horizontalSpacer_2, 1055
horizontalSpacer_3, 1055
horizontalSpacer_4, 1055
label_2, 1056
label_4, 1056
newLabel, 1056
progressBar, 1056
retranslateUi, 1052
setupUi, 1052
statusLabel, 1056
Ui_GradientDialog, 1056
buttonBox, 1061
gridLayout, 1061
gridLayout_2, 1061
gridLayout_3, 1061
groupBox_2, 1062
horizontalLayout, 1062
horizontalLayout_2, 1062
horizontalSpacer, 1062
horizontalSpacer_2, 1062
horizontalSpacer_3, 1062
label, 1062
label_2, 1062
presetDelete, 1062
presetList, 1062
presetName, 1063
presetSave, 1063
retranslateUi, 1058
setupUi, 1059
stopBox, 1063
stopColor, 1063
stopOpacity, 1063
stopPos, 1063
verticalSpacer, 1063
verticalSpacer_2, 1063
widget, 1063
Ui_KPerfWidget, 1101
capsBox, 1111
capsColorOff, 1111
capsColorOn, 1112
copyButton, 1112
gridLayout, 1112
horizontalLayout, 1112
horizontalLayout_2, 1112
horizontalSpacer, 1112
horizontalSpacer_2, 1112
horizontalSpacer_3, 1112
horizontalSpacer_4, 1112
horizontalSpacer_5, 1113
horizontalSpacer_6, 1113
horizontalSpacer_7, 1113
horizontalSpacer_8, 1113
intensityBox, 1113
k95Label1, 1113
k95Label2, 1113
k95Label3, 1113
k95Label4, 1113
k95Label5, 1114
k95Label6, 1114
k95Line, 1114
k95Spacer, 1114
label, 1114
label_10, 1114
label_11, 1114
label_12, 1114
label_14, 1114
label_15, 1115
label_16, 1115
label_17, 1115
label_18, 1115
label_19, 1115
label_2, 1115

label_20, 1115
label_21, 1115
label_22, 1115
label_23, 1116
label_24, 1116
label_3, 1116
label_4, 1116
label_5, 1116
label_6, 1116
label_7, 1116
label_8, 1116
lightBox, 1116
lightColor1, 1117
lightColor2, 1117
lightColor3, 1117
line, 1117
line_2, 1117
line_3, 1117
lockBox, 1117
lockColorOff, 1117
lockColorOn, 1117
macroBox, 1118
macroColorOff, 1118
macroColorOn, 1118
modeBox, 1118
modeColorOff, 1118
modeColorOn, 1118
muteBox, 1118
muteColorNA, 1118
muteColorOff, 1118
muteColorOn, 1119
numBox, 1119
numColorOff, 1119
numColorOn, 1119
retranslateUi, 1104
scrollBox, 1119
scrollColorOff, 1119
scrollColorOn, 1119
setupUi, 1105
verticalSpacer, 1119
verticalSpacer_2, 1119
verticalSpacer_3, 1120
verticalSpacer_4, 1120
Ui_KbAnimWidget, 1064
aCopyLabel, 1069
aMissingLabel, 1069
aMissingPage, 1069
aNameLabel, 1069
aVerLabel, 1070
animList, 1069
animPage, 1070
blendBox, 1070
deleteButton, 1070
gridLayout, 1070
gridLayout_2, 1070
gridLayout_3, 1070
gridLayout_4, 1070
horizontalLayout, 1070
horizontalSpacer, 1071
horizontalSpacer_2, 1071
horizontalSpacer_3, 1071
horizontalSpacer_4, 1071
horizontalSpacer_5, 1071
keyButton, 1071
label_5, 1071
label_6, 1071
label_7, 1071
nameBox, 1072
noAnimLabel, 1072
noSelPage, 1072
opacityBox, 1072
propertyButton, 1072
retranslateUi, 1066
selectionStack, 1072
setupUi, 1066
verticalLayout, 1072
verticalSpacer, 1072
verticalSpacer_2, 1072
verticalSpacer_3, 1073
Ui_KbBindWidget, 1073
copyButton, 1077
gridLayout, 1077
gridLayout_2, 1077
horizontalLayout_2, 1078
horizontalSpacer, 1078
horizontalSpacer_2, 1078
keyWidget, 1078
label, 1078
label_2, 1078
line, 1078
line_2, 1078
rbWidget, 1078
resetButton, 1079
retranslateUi, 1075
selectLabel, 1079
setupUi, 1075
verticalLayout, 1079
verticalSpacer, 1079
widget, 1079
Ui_KbLightWidget, 1079
animButton, 1084
animWidget, 1085
bgButton, 1085
brightnessBox, 1085
gridLayout, 1085
gridLayout_2, 1085
gridLayout_4, 1085
horizontalLayout, 1085
horizontalLayout_2, 1085
horizontalLayout_3, 1085
horizontalSpacer_3, 1085
horizontalSpacer_4, 1086
horizontalSpacer_5, 1086
horizontalSpacer_6, 1086
keyWidget, 1086
label, 1086

label_2, 1086
label_3, 1086
line, 1086
line_2, 1086
retranslateUi, 1081
selLabel, 1087
setupUi, 1082
showAnimBox, 1087
verticalLayout, 1087
verticalSpacer_2, 1087
verticalSpacer_3, 1087
widget, 1087
Ui_KbProfileDialog, 1087
buttonBox, 1090
gridLayout, 1090
horizontalSpacer, 1091
horizontalSpacer_2, 1091
profileList, 1091
retranslateUi, 1089
setupUi, 1089
Ui_KbWidget, 1091
bindTab, 1097
bindWidget, 1097
devTab, 1097
fwLabel, 1097
fwUpdButton, 1097
fwUpdLabel, 1097
fwUpdLayout, 1098
gridLayout, 1098
gridLayout_2, 1098
gridLayout_3, 1098
gridLayout_4, 1098
gridLayout_5, 1098
gridLayout_7, 1098
horizontalSpacer_2, 1098
horizontalSpacer_3, 1098
hwSaveButton, 1099
kPerfTab, 1099
kPerfWidget, 1099
label_3, 1099
label_4, 1099
label_9, 1099
lightTab, 1099
lightWidget, 1099
mPerfTab, 1100
mPerfWidget, 1100
modesList, 1099
pollLabel, 1100
pollLabel2, 1100
profileBox, 1100
retranslateUi, 1093
serialLabel, 1100
setupUi, 1094
tabWidget, 1100
verticalSpacer, 1100
Ui_LayoutDialog, 1120
buttonBox, 1124
comboBox, 1124
gridLayout, 1124
horizontalSpacer, 1124
horizontalSpacer_2, 1124
label, 1124
label_2, 1125
retranslateUi, 1122
setupUi, 1122
verticalSpacer, 1125
verticalSpacer_2, 1125
verticalSpacer_3, 1125
verticalSpacer_4, 1125
Ui_MPerfWidget, 1133
aSnapBox, 1144
copyButton, 1144
eBox1, 1144
eBox2, 1144
eBox3, 1144
eBox4, 1144
eBox5, 1145
gridLayout, 1145
horizontalLayout, 1145
horizontalLayout_2, 1145
horizontalLayout_4, 1145
horizontalSpacer, 1145
horizontalSpacer_2, 1145
horizontalSpacer_3, 1145
horizontalSpacer_4, 1145
horizontalSpacer_5, 1146
horizontalSpacer_6, 1146
horizontalSpacer_7, 1146
iButton0, 1146
iButton1, 1146
iButton2, 1146
iButton3, 1146
iButton4, 1146
iButton5, 1146
iButtonO, 1147
indicBox, 1147
lHeightBox, 1148
label, 1147
label_11, 1147
label_12, 1147
label_13, 1147
label_14, 1147
label_15, 1147
label_2, 1147
label_25, 1148
label_3, 1148
label_4, 1148
label_5, 1148
label_6, 1148
label_7, 1148
label_8, 1148
line, 1148
line_2, 1149
line_3, 1149
retranslateUi, 1136
setupUi, 1137

spinBox, 1149
verticalLayout, 1149
verticalSpacer, 1149
verticalSpacer_2, 1149
verticalSpacer_3, 1149
xBox0, 1149
xBox1, 1149
xBox2, 1150
xBox3, 1150
xBox4, 1150
xBox5, 1150
xSlider0, 1150
xSlider1, 1150
xSlider2, 1150
xSlider3, 1150
xSlider4, 1150
xSlider5, 1151
xyBox, 1151
yBox0, 1151
yBox1, 1151
yBox2, 1151
yBox3, 1151
yBox4, 1151
yBox5, 1151
ySlider0, 1151
ySlider1, 1152
ySlider2, 1152
ySlider3, 1152
ySlider4, 1152
ySlider5, 1152
Ui_MainWindow, 1125
actionAbout, 1128
actionExit, 1128
centralWidget, 1128
gridLayout, 1128
retranslateUi, 1127
setupUi, 1127
tabWidget, 1129
Ui_ModeSelectDialog, 1129
buttonBox, 1132
gridLayout, 1132
label, 1132
modeList, 1132
retranslateUi, 1130
selAllButton, 1132
selNoneButton, 1133
setupUi, 1131
Ui_RebindWidget, 1152
actionTab, 1167
animBox, 1167
animButton, 1167
animKrBox, 1167
animOnceBox, 1167
animTab, 1168
applyButton, 1168
btnClearMacro, 1168
btnStartMacro, 1168
btnStopMacro, 1168
cancelButton, 1168
dpiBox, 1168
dpiButton, 1168
dpiCustLabel, 1169
dpiCustXBox, 1169
dpiCustYBox, 1169
dpiWarning, 1169
fnBox, 1169
fnButton, 1169
gridLayout, 1169
gridLayout_10, 1169
gridLayout_2, 1169
gridLayout_3, 1170
gridLayout_4, 1170
gridLayout_5, 1170
gridLayout_8, 1170
groupBox, 1170
groupBox_2, 1170
groupBox_3, 1170
groupBox_4, 1170
horizontalLayout, 1170
horizontalLayout_2, 1171
horizontalLayout_3, 1171
horizontalSpacer, 1171
horizontalSpacer_10, 1171
horizontalSpacer_11, 1171
horizontalSpacer_12, 1171
horizontalSpacer_13, 1171
horizontalSpacer_14, 1171
horizontalSpacer_15, 1171
horizontalSpacer_16, 1172
horizontalSpacer_17, 1172
horizontalSpacer_18, 1172
horizontalSpacer_19, 1172
horizontalSpacer_2, 1172
horizontalSpacer_20, 1172
horizontalSpacer_21, 1172
horizontalSpacer_22, 1172
horizontalSpacer_23, 1172
horizontalSpacer_24, 1173
horizontalSpacer_25, 1173
horizontalSpacer_26, 1173
horizontalSpacer_3, 1173
horizontalSpacer_4, 1173
horizontalSpacer_5, 1173
horizontalSpacer_6, 1173
horizontalSpacer_7, 1173
horizontalSpacer_8, 1173
horizontalSpacer_9, 1174
keyTab, 1174
layoutWidget, 1174
layoutWidget1, 1174
layoutWidget_2, 1174
lbl_macro, 1174
lightBox, 1174
lightButton, 1174
lightWrapBox, 1174
lockBox, 1175

lockButton, 1175
macroTab, 1175
mb2Box, 1175
mb2Button, 1175
mbBox, 1175
mbButton, 1175
mediaBox, 1175
mediaButton, 1176
modBox, 1176
modButton, 1176
modeBox, 1176
modeButton, 1176
modeWrapBox, 1176
mouseTab, 1176
numBox, 1176
numButton, 1177
progTipLabel, 1178
programKpBox, 1177
programKpButton, 1177
programKpExtra, 1177
programKpModeBox, 1177
programKpSIBox, 1177
programKrBox, 1177
programKrButton, 1177
programKrExtra, 1178
programKrModeBox, 1178
programKrSIBox, 1178
programTab, 1178
pteMacroBox, 1178
pteMacroComment, 1178
pteMacroText, 1178
resetButton, 1179
retranslateUi, 1156
setupUi, 1158
tabWidget, 1179
typingBox, 1179
typingButton, 1179
unbindButton, 1179
verticalLayout, 1179
verticalLayout_2, 1179
verticalSpacer, 1179
verticalSpacer_10, 1179
verticalSpacer_11, 1180
verticalSpacer_2, 1180
verticalSpacer_3, 1180
verticalSpacer_4, 1180
verticalSpacer_5, 1180
verticalSpacer_6, 1180
verticalSpacer_7, 1180
verticalSpacer_8, 1180
wheelBox, 1180
wheelButton, 1181
Ui_SettingsWidget, 1181
altBox, 1188
altLabel, 1188
autoFWBox, 1188
capsBox, 1188
capsLabel, 1188
ctrlBox, 1188
ctrlLabel, 1188
devicesLabel, 1188
extraButton, 1189
gridLayout, 1189
gridLayout_3, 1189
gridLayout_5, 1189
horizontalLayout, 1189
horizontalLayout_2, 1189
horizontalSpacer, 1189
horizontalSpacer_10, 1189
horizontalSpacer_2, 1189
horizontalSpacer_7, 1190
horizontalSpacer_9, 1190
label, 1190
label_2, 1190
label_3, 1190
label_5, 1190
label_6, 1190
label_8, 1190
layoutBox, 1190
line, 1191
line_2, 1191
line_3, 1191
loginItemBox, 1191
pushButton, 1191
retranslateUi, 1183
setupUi, 1184
shiftBox, 1191
shiftLabel, 1191
versionLabel, 1191
verticalSpacer, 1191
verticalSpacer_10, 1192
verticalSpacer_2, 1192
verticalSpacer_3, 1192
verticalSpacer_4, 1192
verticalSpacer_5, 1192
verticalSpacer_6, 1192
verticalSpacer_7, 1192
verticalSpacer_8, 1192
winBox, 1192
winLabel, 1193
uiUpdated
KPerfWidget, 704
unbindButton
Ui::RebindWidget, 954
Ui_RebindWidget, 1179
uncompressedSize
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
QuaZipFilePrivate, 908
QuaZipNewInfo, 917
unz64_file_pos_s, 1419
unz64_s, 1365
unz64_file_pos
unzip.h, 1422
unz64local_CheckCurrentFileCoherencyHeader
unzip.c, 1368

unz64local_DosDateToTmuDate
unzip.c, 1370
unz64local_GetCurrentFileInfoInternal
unzip.c, 1371
unz64local_SearchCentralDir
unzip.c, 1378
unz64local_SearchCentralDir64
unzip.c, 1379
unz64local_getByte
unzip.c, 1371
unz64local_getLong
unzip.c, 1375
unz64local_getLong64
unzip.c, 1376
unz64local_getShort
unzip.c, 1377
unz_file_info64_internal_s, 1364
unz_file_info64_s, 1416
unz_file_info_s, 1417
unz_file_pos_s, 1419
unz_global_info64_s, 1414
unz_global_info_s, 1415
unz_copyright
unzip.c, 1411
unz_file_info
unzip.h, 1422
unz_file_info64
unzip.h, 1422
unz_file_info64_internal
unzip.c, 1368
unz_file_pos
unzip.h, 1422
unz_global_info
unzip.h, 1422
unz_global_info64
unzip.h, 1422
unzClearFlags
unzip.c, 1381
unzip.h, 1423
unzClose
unzip.c, 1382
unzCloseCurrentFile
unzip.c, 1383
unzFile
unzip.h, 1422
unzGetCurrentFileInfo
unzip.c, 1384
unzGetCurrentFileInfo64
unzip.c, 1385
unzGetCurrentFileZStreamPos64
unzip.c, 1386
unzGetFilePos
unzip.c, 1386
unzip.h, 1423
unzGetFilePos64
unzip.c, 1387
unzip.h, 1424
unzGetGlobalComment
unzip.c, 1387
unzGetGlobalInfo
unzip.c, 1388
unzGetGlobalInfo64
unzip.c, 1388
unzGetLocalExtrafield
unzip.c, 1389
unzGetOffset
unzip.c, 1389
unzip.h, 1424
unzGetOffset64
unzip.c, 1390
unzip.h, 1425
unzGoToFilePos
unzip.c, 1390
unzip.h, 1425
unzGoToFilePos64
unzip.c, 1391
unzip.h, 1426
unzGoToFirstFile
unzip.c, 1392
unzGoToNextFile
unzip.c, 1393
unzLocateFile
unzip.c, 1394
unzOpen
unzip.c, 1395
unzOpen2
unzip.c, 1395
unzOpen2_64
unzip.c, 1396
unzOpen64
unzip.c, 1397
unzOpenCurrentFile
unzip.c, 1397
unzOpenCurrentFile2
unzip.c, 1398
unzOpenCurrentFile3
unzip.c, 1398
unzOpenCurrentFilePassword
unzip.c, 1401
unzOpenInternal
unzip.c, 1402
unzip.h, 1427
unzReadCurrentFile
unzip.c, 1405
unzSetFlags
unzip.c, 1408
unzip.h, 1430
unzSetOffset
unzip.c, 1409
unzip.h, 1431
unzSetOffset64
unzip.c, 1409
unzip.h, 1431
unzStringFileNameCompare
unzip.c, 1410
unzeof

unzip.c, 1384
unzip.c
_Z_OF, 1368
ALLOC, 1366
BUFREADCOMMENT, 1367
local, 1367
SIZECENTRALDIRITEM, 1367
SIZEZIPLOCALHEADER, 1367
strcmpcasenosensitive_internal, 1368
TRYFREE, 1367
UNZ_BUFSIZE, 1367
UNZ_MAXFILENAMEINZIP, 1367
unz64local_CheckCurrentFileCoherencyHeader, 1368
unz64local_DosDateToTmuDate, 1370
unz64local_GetCurrentFileInfoInternal, 1371
unz64local_SearchCentralDir, 1378
unz64local_SearchCentralDir64, 1379
unz64local_getByte, 1371
unz64local_getLong, 1375
unz64local_getLong64, 1376
unz64local_getShort, 1377
unz_copyright, 1411
unz_file_info64_internal, 1368
unzClearFlags, 1381
unzClose, 1382
unzCloseCurrentFile, 1383
unzGetCurrentFileInfo, 1384
unzGetCurrentFileInfo64, 1385
unzGetCurrentFileZStreamPos64, 1386
unzGetFilePos, 1386
unzGetFilePos64, 1387
unzGetGlobalComment, 1387
unzGetGlobalInfo, 1388
unzGetGlobalInfo64, 1388
unzGetLocalExtrafield, 1389
unzGetOffset, 1389
unzGetOffset64, 1390
unzGoToFilePos, 1390
unzGoToFilePos64, 1391
unzGoToFirstFile, 1392
unzGoToNextFile, 1393
unzLocateFile, 1394
unzOpen, 1395
unzOpen2, 1395
unzOpen2_64, 1396
unzOpen64, 1397
unzOpenCurrentFile, 1397
unzOpenCurrentFile2, 1398
unzOpenCurrentFile3, 1398
unzOpenCurrentFilePassword, 1401
unzOpenInternal, 1402
unzReadCurrentFile, 1405
unzSetFlags, 1408
unzSetOffset, 1409
unzSetOffset64, 1409
unzStringFileNameCompare, 1410
unzeof, 1384
unztell, 1410
unztell64, 1411
z_crc_t, 1368
unzip.h
_Z_OF, 1422, 1423
tm_unz, 1422
UNZ_AUTO_CLOSE, 1420
UNZ_BADZIPFILE, 1420
UNZ_CRCERROR, 1420
UNZ_DEFAULT_FLAGS, 1420
UNZ_EOF, 1421
UNZ_ERRNO, 1421
UNZ_INTERNALERROR, 1421
UNZ_OK, 1421
UNZ_PARAMERROR, 1421
unz64_file_pos, 1422
unz_file_info, 1422
unz_file_info64, 1422
unz_file_pos, 1422
unz_global_info, 1422
unz_global_info64, 1422
unzClearFlags, 1423
unzFile, 1422
unzGetFilePos, 1423
unzGetFilePos64, 1424
unzGetOffset, 1424
unzGetOffset64, 1425
unzGoToFilePos, 1425
unzGoToFilePos64, 1426
unzOpenInternal, 1427
unzSetFlags, 1430
unzSetOffset, 1431
unzSetOffset64, 1431
Z_BZIP2ED, 1421
unztell
unzip.c, 1410
unztell64
unzip.c, 1411
update
KbBind, 385
KbPerf, 526
QuaAdler32, 799
QuaChecksum32, 801
QuaCrc32, 805
update_keys
crypt.h, 1313
updateBind
KbBindWidget, 404
updateFwButton
KbWidget, 581
updateImage
ColorButton, 147
GradientButton, 199
updateLayout
Kb, 299
updateLight
KbLightWidget, 468
updateMapper

AnimSettingDialog, 117
KPerfWidget, 706
updateModifiers
SettingsWidget, 1004
updateParam
AnimSettingDialog, 112
updateParams
KbAnim, 329
updatePresets
GradientDialog, 219
updateProfileList
KbWidget, 582
updateSelDisplay
KbBindWidget, 406
updateStops
AnimSettingDialog, 115
updateVersion
MainWindow, 739
updated
KbBind, 387
KbLight, 446
KbMode, 494
url
KbFirmware::FW, 179
urlParam
animscript.cpp, 1201
urldecode
ckb-anim.h, 1225
UsbId, 1193
guid, 1197
guidString, 1194, 1195
hwModified, 1197
hwModifiedString, 1195
modified, 1197
modifiedString, 1196
newGuid, 1196
newModified, 1196
UsbId, 1194
UsbId, 1194
usbModel
Kb, 304
usbSerial
Kb, 305
usize
QuaZipFile, 891

VERSIONMADEBY
zip.c, 1440
value
CkbSettings, 135
KeyAction, 624
QuaAdler32, 799
QuaChecksum32, 801
QuaCrc32, 805
verifyFw
fwupgradedialog.cpp, 1238
version
AnimScript, 80
versionCreated
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
versionForBoard
KbFirmware, 417
versionLabel
Ui::SettingsWidget, 1017
Ui_SettingsWidget, 1191
versionNeeded
QuaZipFileInfo, 896
QuaZipFileInfo64, 903
versionUpdated
KbManager, 481
verticalLayout
Ui::KbAnimWidget, 341
Ui::KbBindWidget, 395
Ui::KbLightWidget, 456
Ui::MPerfWidget, 765
Ui::RebindWidget, 954
Ui_KbAnimWidget, 1072
Ui_KbBindWidget, 1079
Ui_KbLightWidget, 1087
Ui_MPerfWidget, 1149
Ui_RebindWidget, 1179
verticalLayout_2
Ui::RebindWidget, 955
Ui_RebindWidget, 1179
verticalSpacer
Ui::AnimSettingDialog, 96
Ui::ExtraSettingsWidget, 168
Ui::GradientDialog, 207
Ui::KbAnimWidget, 341
Ui::KbBindWidget, 396
Ui::KbWidget, 593
Ui::KPerfWidget, 693
Ui::LayoutDialog, 711
Ui::MPerfWidget, 765
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_AnimSettingDialog, 1037
Ui_ExtraSettingsWidget, 1049
Ui_GradientDialog, 1063
Ui_KbAnimWidget, 1072
Ui_KbBindWidget, 1079
Ui_KbWidget, 1100
Ui_KPerfWidget, 1119
Ui_LayoutDialog, 1125
Ui_MPerfWidget, 1149
Ui_RebindWidget, 1179
Ui_SettingsWidget, 1191
verticalSpacer_10
Ui::ExtraSettingsWidget, 168
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_ExtraSettingsWidget, 1049
Ui_RebindWidget, 1179
Ui_SettingsWidget, 1192
verticalSpacer_11
Ui::ExtraSettingsWidget, 168

Ui::RebindWidget, 955
Ui_ExtraSettingsWidget, 1049
Ui_RebindWidget, 1180
verticalSpacer_2
Ui::AnimAddDialog, 52
Ui::AnimSettingDialog, 96
Ui::ExtraSettingsWidget, 169
Ui::GradientDialog, 208
Ui::KbAnimWidget, 341
Ui::KbLightWidget, 456
Ui::KPerfWidget, 693
Ui::LayoutDialog, 711
Ui::MPerfWidget, 765
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_AnimAddDialog, 1025
Ui_AnimSettingDialog, 1038
Ui_ExtraSettingsWidget, 1049
Ui_GradientDialog, 1063
Ui_KbAnimWidget, 1072
Ui_KbLightWidget, 1087
Ui_KPerfWidget, 1119
Ui_LayoutDialog, 1125
Ui_MPerfWidget, 1149
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_3
Ui::AnimAddDialog, 52
Ui::AnimSettingDialog, 97
Ui::ExtraSettingsWidget, 169
Ui::KbAnimWidget, 341
Ui::KbLightWidget, 456
Ui::KPerfWidget, 693
Ui::LayoutDialog, 711
Ui::MPerfWidget, 765
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_AnimAddDialog, 1025
Ui_AnimSettingDialog, 1038
Ui_ExtraSettingsWidget, 1049
Ui_KbAnimWidget, 1073
Ui_KbLightWidget, 1087
Ui_KPerfWidget, 1120
Ui_LayoutDialog, 1125
Ui_MPerfWidget, 1149
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_4
Ui::ExtraSettingsWidget, 169
Ui::KPerfWidget, 693
Ui::LayoutDialog, 711
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_ExtraSettingsWidget, 1049
Ui_KPerfWidget, 1120
Ui_LayoutDialog, 1125
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_5
Ui::ExtraSettingsWidget, 169
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_ExtraSettingsWidget, 1050
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_6
Ui::ExtraSettingsWidget, 169
Ui::RebindWidget, 955
Ui::SettingsWidget, 1017
Ui_ExtraSettingsWidget, 1050
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_7
Ui::ExtraSettingsWidget, 169
Ui::RebindWidget, 956
Ui::SettingsWidget, 1018
Ui_ExtraSettingsWidget, 1050
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_8
Ui::ExtraSettingsWidget, 169
Ui::RebindWidget, 956
Ui::SettingsWidget, 1018
Ui_ExtraSettingsWidget, 1050
Ui_RebindWidget, 1180
Ui_SettingsWidget, 1192
verticalSpacer_9
Ui::ExtraSettingsWidget, 169
Ui_ExtraSettingsWidget, 1050

wheelBox
Ui::RebindWidget, 956
Ui_RebindWidget, 1180
wheelButton
Ui::RebindWidget, 956
Ui_RebindWidget, 1181
wheelKeys
RebindWidget, 988
widget
Ui::GradientDialog, 208
Ui::KbBindWidget, 396
Ui::KbLightWidget, 457
Ui_GradientDialog, 1063
Ui_KbBindWidget, 1079
Ui_KbLightWidget, 1087
width
Key, 597
KeyMap, 649
winBox
Ui::SettingsWidget, 1018
Ui_SettingsWidget, 1192
winLabel
Ui::SettingsWidget, 1018
Ui_SettingsWidget, 1193
winLock
KbBind, 387
Write_EndOfCentralDirectoryRecord

zip.c, 1448
Write_GlobalComment
zip.c, 1449
Write_LocalFileHeader
zip.c, 1450
Write_Zip64EndOfCentralDirectoryLocator
zip.c, 1452
Write_Zip64EndOfCentralDirectoryRecord
zip.c, 1453
writeCache
CkbSettings, 137
writeData
QuaGzipFile, 811
QuaZIODevice, 819
QuaZipFile, 892
writePos
QuaZipFilePrivate, 908
writeProfileHeader
Kb, 300

x
Key, 597
xBox0
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1149
xBox1
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1149
xBox2
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xBox3
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xBox4
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xBox5
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xSlider0
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xSlider1
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xSlider2
Ui::MPerfWidget, 766
Ui_MPerfWidget, 1150
xSlider3
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1150
xSlider4
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1150
xSlider5
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
xyBox
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
xyLinkPath
mperfwidget.cpp, 1308

y
Key, 597
YES
KbFirmware, 410
yBox0
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
yBox1
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
yBox2
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
yBox3
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
yBox4
Ui::MPerfWidget, 767
Ui_MPerfWidget, 1151
yBox5
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1151
ySlider0
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1151
ySlider1
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1152
ySlider2
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1152
ySlider3
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1152
ySlider4
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1152
ySlider5
Ui::MPerfWidget, 768
Ui_MPerfWidget, 1152
year
AnimScript, 80

Z_BUFSIZE
zip.c, 1440
Z_BZIP2ED
unzip.h, 1421
zip.h, 1493
Z_MAXFILENAMEINZIP
zip.c, 1440
z_crc_t
unzip.c, 1368
zip.c, 1441
ZCALLBACK

ioapi.h, 1318
ZCLOSE64
ioapi.h, 1318
ZERROR64
ioapi.h, 1318
ZFAKECLOSE64
ioapi.h, 1318
ZIP64ENDHEADERMAGIC
zip.c, 1440
ZIP64ENDLOCHEADERMAGIC
zip.c, 1441
ZIP_AUTO_CLOSE
zip.h, 1493
ZIP_BADZIPFILE
zip.h, 1493
ZIP_DEFAULT_FLAGS
zip.h, 1493
ZIP_EOF
zip.h, 1493
ZIP_ERRNO
zip.h, 1493
ZIP_INTERNALERROR
zip.h, 1493
ZIP_OK
zip.h, 1493
ZIP_PARAMERROR
zip.h, 1494
ZIP_SEQUENTIAL
zip.h, 1494
ZOPEN64
ioapi.h, 1319
ZPOS64_T
ioapi.h, 1320
ZREAD64
ioapi.h, 1319
ZSEEK64
ioapi.h, 1319
ZTELL64
ioapi.h, 1320
ZWRITE64
ioapi.h, 1320
zdecode
crypt.h, 1312
zencode
crypt.h, 1312
zip
QuaZipFilePrivate, 908
zip.c
_Z_OF, 1441
ALLOC, 1438
add_data_in_datablock, 1441
allocate_new_datablock, 1442
BUFREADCOMMENT, 1439
CENTRALHEADERMAGIC, 1439
DESCRIPTORHEADERMAGIC, 1439
ENDHEADERMAGIC, 1439
free_datablock, 1443
free_linkedlist, 1443
init_linkedlist, 1444
LOCALHEADERMAGIC, 1439
linkedlist_data, 1441
linkedlist_datablock_internal, 1441
LoadCentralDirectoryRecord, 1445
local, 1439
MAKEULONG64, 1439
SEEK_CUR, 1440
SEEK_END, 1440
SEEK_SET, 1440
SIZECENTRALHEADER, 1440
SIZEDATA_INDATABLOCK, 1440
TRYFREE, 1440
VERSIONMADEBY, 1440
Write_EndOfCentralDirectoryRecord, 1448
Write_GlobalComment, 1449
Write_LocalFileHeader, 1450
Write_Zip64EndOfCentralDirectoryLocator, 1452
Write_Zip64EndOfCentralDirectoryRecord, 1453
Z_BUFSIZE, 1440
Z_MAXFILENAMEINZIP, 1440
z_crc_t, 1441
ZIP64ENDHEADERMAGIC, 1440
ZIP64ENDLOCHEADERMAGIC, 1441
zip64FlushWriteBuffer, 1454
zip64local_SearchCentralDir, 1460
zip64local_SearchCentralDir64, 1461
zip64local_TmzDateToDosDate, 1463
zip64local_getByte, 1455
zip64local_getLong, 1456
zip64local_getLong64, 1457
zip64local_getShort, 1458
zip64local_putValue, 1459
zip64local_putValue_inmemory, 1460
zip_copyright, 1488
zipClearFlags, 1464
zipClose, 1464
zipCloseFileInZip, 1466
zipCloseFileInZipRaw, 1467
zipCloseFileInZipRaw64, 1467
zipOpen, 1472
zipOpen2, 1472
zipOpen2_64, 1473
zipOpen3, 1474
zipOpen64, 1476
zipOpenNewFileInZip, 1477
zipOpenNewFileInZip2, 1477
zipOpenNewFileInZip2_64, 1478
zipOpenNewFileInZip3, 1478
zipOpenNewFileInZip3_64, 1479
zipOpenNewFileInZip4, 1479
zipOpenNewFileInZip4_64, 1480
zipOpenNewFileInZip64, 1484
zipRemoveExtraInfoBlock, 1484
zipSetFlags, 1485
zipWriteInFileInZip, 1486
zip.h
_Z_OF, 1494, 1495

DEF_MEM_LEVEL, 1493
tm_zip, 1494
Z_BZIP2ED, 1493
ZIP_AUTO_CLOSE, 1493
ZIP_BADZIPFILE, 1493
ZIP_DEFAULT_FLAGS, 1493
ZIP_EOF, 1493
ZIP_ERRNO, 1493
ZIP_INTERNALERROR, 1493
ZIP_OK, 1493
ZIP_PARAMERROR, 1494
ZIP_SEQUENTIAL, 1494
zipClearFlags, 1495
zipFile, 1494
zipOpen3, 1496
zipSetFlags, 1498
zipcharpc, 1494
zip64
QuaZipPrivate, 926
zip64_internal, 1438
zip64FlushWriteBuffer
zip.c, 1454
zip64local_SearchCentralDir
zip.c, 1460
zip64local_SearchCentralDir64
zip.c, 1461
zip64local_TmzDateToDosDate
zip.c, 1463
zip64local_getByte
zip.c, 1455
zip64local_getLong
zip.c, 1456
zip64local_getLong64
zip.c, 1457
zip64local_getShort
zip.c, 1458
zip64local_putValue
zip.c, 1459
zip64local_putValue_inmemory
zip.c, 1460
zip_fileinfo, 1491
zip_copyright
zip.c, 1488
zipClearFlags
zip.c, 1464
zip.h, 1495
zipClose
zip.c, 1464
zipCloseFileInZip
zip.c, 1466
zipCloseFileInZipRaw
zip.c, 1467
zipCloseFileInZipRaw64
zip.c, 1467
zipError
QuaZipFilePrivate, 908
QuaZipPrivate, 926
zipFile
zip.h, 1494
zipName
QuaZipPrivate, 926
zipOpen
zip.c, 1472
zipOpen2
zip.c, 1472
zipOpen2_64
zip.c, 1473
zipOpen3
zip.c, 1474
zip.h, 1496
zipOpen64
zip.c, 1476
zipOpenNewFileInZip
zip.c, 1477
zipOpenNewFileInZip2
zip.c, 1477
zipOpenNewFileInZip2_64
zip.c, 1478
zipOpenNewFileInZip3
zip.c, 1478
zipOpenNewFileInZip3_64
zip.c, 1479
zipOpenNewFileInZip4
zip.c, 1479
zipOpenNewFileInZip4_64
zip.c, 1480
zipOpenNewFileInZip64
zip.c, 1484
zipRemoveExtraInfoBlock
zip.c, 1484
zipSetFlags
zip.c, 1485
zip.h, 1498
zipWriteInFileInZip
zip.c, 1486
zipcharpc
zip.h, 1494
zlib_filefunc64_32_def_s, 1317
zlib_filefunc64_def_s, 1316
zlib_filefunc_def_s, 1316
zlib_filefunc64_32_def
ioapi.h, 1320
zlib_filefunc64_def
ioapi.h, 1320
zlib_filefunc_def
ioapi.h, 1320