

**Uniwersytet Jagielloński**

---

Faculty of Physics, Astronomy and Applied Computer Science  
**Master of Science Thesis**

Sebastian Poręba

**Comparison of 3D physics engines**

Promotor:

Paweł Węgrzyn Ph.D Konsultant:

Bartosz Porębski MSc

Kraków 2013

## **OŚWIADCZENIE AUTORA PRACY**

Oświadczam, świadomy odpowiedzialności karnej za poświadczenie nieprawdy, że niniejszą pracę dyplomową wykonałem osobiście i samodzielnie, i nie korzystałem ze źródeł innych niż wymienione w pracy.

.....  
PODPIS

I would like to thank my advisors Paweł Węgrzyn and Bartek Porębski and people who advised and supported me during writing: Patrycja Bartyzel, Ibon Tolosana, Collin Hover

# Spis treści

<b>1. Introduction</b> .....	6
1.1. Influence on distribution process .....	8
1.2. Technology.....	10
<b>2. Overview of JavaScript and V8 engine architecture</b> .....	11
2.1. JIT compilation – tracking variable types.....	12
2.2. Type interference.....	14
2.3. Hidden classes .....	15
2.4. Garbage collection .....	17
<b>3. Particle system</b> .....	18
3.1. System parameters .....	19
3.2. Implementation with high memory allocation .....	20
3.3. Implementation with object pool.....	24
<b>4. Sphere collision</b> .....	26
4.1. Algorithm description .....	27
4.2. $O(N^2)$ approach .....	30
4.3. Octree-partitioned space .....	32
<b>5. Emscripten</b> .....	34
5.1. Asm.js overview.....	37
<b>6. Summary</b> .....	39
<b>A. Acknowledgements</b> .....	42
<b>B. Source code</b> .....	43
B.1. Math utilities.....	43
B.2. Particle system .....	46
B.3. Spheres collision detection .....	60
<b>References</b> .....	84

# 1. Introduction

The main objective of presented project is the implementation of parts of 3D engine in a browser environment. Parts of engine are analysed side-by-side with parallel engine compiled from C++. The objective of analysis is comparison of performance and description of possible issues related to the limited browser resources and dynamic features of JavaScript.

At the moment of writing majority of games are developed with C++ and usually DirectX. These technologies are mature and have excellent performance. Features of the language give flexibility and high-level solutions to effectively manage application (e.g. operator overloading, multiple inheritance) and allow to fine-tune internals of application to achieve best execution times. For games with high budget<sup>1</sup> C++ is an obvious choice for having the best possible result.

However, in parallel to AAA game industry casual and independent games sector is growing. In 2013 market is expected to be worth \$8.64 billions in total. Total of 2.4 billion tablets and smartphones with casual games capabilities will be reached before the end of 2013. These games are less focused on creating cutting edge graphics and physics simulations and more on overall experience and social interactions.

JavaScript is a scripting language not designed to perform high-load computations. However, at present it is the only language widely supported by all browsers. With all its advantages and quirks is the only choice available for programmers.<sup>2</sup>

While suffering from design issues, JavaScript provides a complete environment that makes development very easy for both beginner and advanced programmer. Two very important components of every application are provided out of the box – rendering system and networking in browser, designed for HTML pages to carry mainly text information are still suitable for gaming. Creation of simple 2D game is often a matter of few hundred lines of code responsible for transferring user input to positions of sprites defined in CSS. This is clearly visible during competitions like JS13kGames<sup>3</sup> where all game assets and code have to be fitted into 13kB package.

Many projects varying from server side solutions<sup>4</sup> to hardware developer boards<sup>6</sup> are taking advantage of this simplicity. From the perspective of game development, it is unlikely at the time of writing that AAA game

---

<sup>1</sup>Grand Theft Auto V, released in 2013 had a budget of \$137 millions – <http://www.gamesindustry.biz/articles/2013-02-01-gta-v-dev-costs-over-USD137-million-says-analyst>

<sup>2</sup>Currently two new languages are worked on – Dart by Google and TypeScript by MicroSoft. However, to enable cross-compilation to JavaScript, paradigm of these languages is similar and work is focused mainly on better IDE support.

<sup>3</sup><http://js13kgames.com/>

<sup>4</sup><http://nodejs.org/>

<sup>5</sup><http://googlecreativelab.github.io/coder/>

<sup>6</sup><http://www.espruino.com/>

may be created to run in browser. However, growing segments of casual, independent and social games are already targeting web as a platform.

## 1.1. Influence on distribution process

Traditionally, games are often still sold in physical boxes and some update system is always incorporated to patch any bugs appearing after initial release. Systems like Steam<sup>7</sup> are making this process easier but still suffer from necessity to install a game on hard drive.

Creating application that works in browser simplifies distribution significantly. All assets and code are downloaded each time user enters a website, so no update system is necessary – all users always play the newest version. Usually browser games are monetised differently than traditional titles. Playing basic version is usually free and earnings come from either ads or premium content. This is completely new approach, present also in MMO<sup>8</sup> games. It resulted in psychological research on leveraging compulsive behaviours to maximise profits<sup>9</sup>.

Working in browser gives access to all social network of user, so incorporation of Twitter or Facebook based features is very simple – which boosts promotion of game. It also enables, morally questionable, target of people not able to install games on company issued computer. Disallowing games in browsers is far more complicated task for administrator, similar to blocking ads or mature content.

Lastly, web is better suited to run easily on all platforms. Browser is a layer of abstraction that makes transparent for application, whether it runs on any traditional operating system, gaming console or mobile device. Of course performance and screen size should be taken under consideration, but ability to write one codebase that runs on multiple devices led already to projects that package JavaScript applications as native ones<sup>10</sup>, greatly reducing development costs for growing variety of phones and tablets.

Rysunek 1.1: Game created with ImpactJS



<sup>7</sup><http://store.steampowered.com/>


<sup>8</sup>Massive Multiplayer Online

<sup>9</sup><http://www.emcneill.com/exploitative-game-design-beyond-the-f2p-debate/>

<sup>10</sup><http://phonegap.com/>


Multiple open-source and commercial game engines are created lately. Examples worth mentioning are ImpactJS<sup>11</sup>, Turbulenz<sup>12</sup> and Isogenic Engine<sup>13</sup>.

Rysunek 1.2: Game created with Isogenic Engine



Very important and growing sector are interactive 3D arts with two major targets – music videos and commercials. They are uniquely available only in browsers as a very viral extensions of normal marketing. One of the first occurrences of this technology was video for Rome music group: "3 dreams of black"<sup>14</sup>. Project allows to move the camera while animated 3D story is rendered alongside music. After movie is over user is allowed to create 3D models that are later incorporated into experiences of other people watching. This way interactions and social element are enabled in what used to be one-way transmission of art form.

Rysunek 1.3: Screenshot from "3 dreams of black"




---

<sup>11</sup><http://impactjs.com/>

<sup>12</sup><http://biz.turbulenz.com/turbulenz>

<sup>13</sup><http://www.isogenicengine.com/>

<sup>14</sup><http://www.ro.me/>

## 1.2. Technology

Browser-based engine is implemented in JavaScript and analyzed in V8 engine. V8 is maintained by Google and is used in Google Chrome browser. Executable examples are compiled using gcc compiler and are runned on the same platform. For additional comparison Emscripten project is used to automatically generate JavaScript and measure if automated conversion may be as effective as writing code by hand.

Project is based on conference sessions and announcements authored by V8 programmers regarding performance of JavaScript applications. Analysis of available materials is a topic of Chapter 2, where internals of modern engines for dynamic languages are briefly explained.

Chapter 3 covers particles often used to simulate loosely connected systems like smoke, fire, fog, etc. It shows techniques of memory allocation and garbage collection that help improve performance. Two particle systems are presented – one with high memory allocation that is expected to cause performance issues and second one, improved by usage of object pools.

Chapter 4 is focused on sphere collision detection and reaction, with both naive solution and space partitioning using Octree. This benchmark shows application with high CPU usage and relatively simple math computations. Because of this simplicity, collision detection with spheres is almost always used as a preliminary method of eliminating collision between objects. Only if bounding spheres are colliding more complex and expensive algorithms are used to determine real state of such pair.

Systems presented in chapters 3 and 4 are not targeted to be full physics engines. They are however representative to general concepts encountered in every game.

Chapter 5 describes Emscripten, project aimed to convert complete C++ projects to JavaScript. Related library, asm.js, is presented with overview of architectural choices that lead to better performance. Generated code is compared to the one created in previous chapters and execution times of all benchmarks is compared and briefly explained.

Last chapter is summary of all achieved results. Limitations of JavaScript engines are presented alongside future possibilities for gaming industry.

Benchmarks are by no means a complete physics system and are not representing current state of the art of physics algorithms. They are aimed to resemble optimal algorithms in used methods and complexity, so that benchmarks reflect how actual engine is using memory and computing power.

## 2. Overview of JavaScript and V8 engine architecture


Historically, JavaScript was considered untyped language, meaning that values had no types attached to variables, either by programmer or compiler. All variables were of single, unified type and procedures called unboxing and boxing, performed before and after each operation on variable, ensured that it was properly used on machine code level. Complete code source was sent from server to the browser and was parsed and executed on fly. Without types attached to variables, all functions were polymorphic and unstable, since parameters may have carried any type of variable. To solve this problem source code of function was parsed each time it was called, each time generating machine code based on current parameters and variables in scope. This approach, called interpretation, is still present in JavaScript engines and used whenever variables don't match set criteria of stability described later in this chapter.

This paper uses as an engine of choice V8 Crankshaft. Choice was made because it's the only engine available at the moment which provides direct command line access, enabling precise performance measurements of code parsing and execution, without browser context and overhead. Executable file of V8 (named d8) is compiled with consideration of target platform.


## 2.1. JIT compilation – tracking variable types

As mentioned before, initially JavaScript was treated as untyped language. With release of SpiderMonkey in Firefox 3.5 in 2009 situation has changed. First Just-In-Time compiler for JavaScript, TraceMonkey, was created. Based on works of Prof. Dr. Michael Franz on TraceTrees<sup>1</sup> JIT compiler was collecting all paths that interpreter took with specific types of variables. A path could split to different methods or if statements. Whenever part of code was executed often enough, path was marked as hot and compiler optimised it for given types. If single path was traversed with different set of types compiler could generate another version of optimised code. When path turned out to be highly polymorphic optimised versions were removed and interpreter was used as a fallback. Initial reports shown speedups between 20x to 40x<sup>2</sup>. However, trace JIT turned out to be very complicated to maintain<sup>3</sup> and eventually was removed from Firefox in 2011.<sup>4</sup> At the time SpiderMonkey was already equipped with JägerMonkey, JIT engine based on method calls. Instead of collecting complete traces, only method calls are counted. This gives easy track of function parameters and variables in scope.

Rysunek 2.1: JIT compiler tracking method calls



Rysunek 2.2: JIT compiler marking one of methods as hot and recompiling



This proved to be more effective and simpler approach and now used in all JavaScript engines. In V8 Crankshaft step forward was taken and simple methods are compiled even before any statistics on data types are collected. For compiled methods source code is not stored. Instead procedure called deoptimisation is implemented. Whenever engine detects that compiled code doesn't match actual types of variables, code is

<sup>1</sup><http://www.michaelfranz.com/>

<sup>2</sup><http://arstechnica.com/information-technology/2008/08/firefox-to-get-massive-javascript-performance-boost/>

<sup>3</sup><https://hacks.mozilla.org/2010/03/improving-javascript-performance-with-jagermonkey/>

<sup>4</sup><http://blog.mozilla.org/nethercote/2011/11/23/memshrink-progress-report-week-23/>

deoptimised and either optimised again to match new, better set of variables, or kept in interpreter friendly form.

To track these changes two debug options for V8 are available: `-trace-opt` and `-trace-deopt`.

```

1 [marking Point.setX 0x2d6ecb87e568 for recompilation,
2 reason: small function, ICs with typeinfo: 1/1 (100%)]
3 [marking Point.setY 0x2d6ecb87e5b0 for recompilation,
4 reason: small function, ICs with typeinfo: 1/1 (100%)]
5
6 [optimizing: Point.setY / 2d6ecb87e5b1 - took 0.037, 0.047, 0.000 ms]
7 [optimizing: Point.setX / 2d6ecb87e569 - took 0.021, 0.038, 0.000 ms]
8
9 [marking Point 0x2d6ecb87e448 for recompilation,
10 reason: small function, ICs with typeinfo: 0/0 (100%)]
11 [marking dot 0x2d6ecb87e490 for recompilation,
12 reason: small function, ICs with typeinfo: 7/7 (100%)]
13
14 [optimizing: Point / 2d6ecb87e449 - took 0.004, 0.019, 0.000 ms]
15 [optimizing: dot / 2d6ecb87e491 - took 0.013, 0.057, 0.000 ms]
16
17 **** DEOPT: dot at bailout #2, address 0x0, frame size 0
18 [deoptimizing: begin 0x2d6ecb87e491 dot @2]
19   translating dot => node=3, height=0
20 [deoptimizing: end 0x2d6ecb87e491 dot => node=3, pc=0x98518d30ac6, state=NO_REGISTERS,
21   alignment=no padding, took 0.146 ms]
22 [removing optimized code for: dot]
```

Listing 2.1: Output from V8 debug run showing optimisation and deoptimisation

## 2.2. Type interference

V8's method of optimising code before it's run relies on type inference. Based on context of variable it's type is guessed. Generated assembler has to support cache miss – whenever inferred type turns out to be incorrect, new type is assigned and another JIT compilation runs. Types of variables are organised in a tree, where Number object may store both Float or Integer, Integer may store SMI (small int), etc.

```

1 //      Unknown
2 //      |   \-----
3 //      |           |
4 //      Primitive      Non-primitive
5 //      |   \-----  |
6 //      |           |   |
7 //      Number       String  |
8 //      /   \          |   |
9 //      Double    Integer32  |   /
10 //     |           |   /   /
11 //     |           Smi   /   /
12 //     |           |   /   _/
13 //           Uninitialized.

```

Listing 2.2: Tree of types in JavaScript


In V8 type inference is tightly connected with JIT compilation and may be tracked with the same flags: `-trace-opt` and `-trace-deopt`.

## 2.3. Hidden classes


TODO: add paragraph on dictionary mode in objects.

JavaScript is classless language. Object may have defined a prototype which behaves similar to base class in other languages. However, a property may be added to an Object or its prototype at any point in runtime. To optimise such dynamic representation engines use a concept of hidden class. Whenever an Object is created its hidden class is pointed to base, empty Object representation. Then each definition of new property makes a transition on hidden class graph, introducing hidden classes that are not yet defined, as in following example:


Rysunek 2.3: Initial shape of hidden class for Point



Rysunek 2.4: Shape of hidden class for Point after x property added




Rysunek 2.5: Shape of hidden class for Point after y property added



Based on hidden class further JIT compiler optimises methods, to generate even simpler assembly code similar to one compiled from C++. Class shape defines address offsets of Object properties. Thus, hidden class graph is actually a tree, where one class can't be reached in more than one way.

Rysunek 2.6: Two point representations based on order of declared properties



At the moment of writing type of property is not tracked in hidden classes. The only exception are primitive values (see Listing 2.2). In other words, storing an object in property results in the same hidden class regardless of hidden class of this object.

Transitions between hidden classes can be tracked in V8 using flags `-trace-generalization` tracking when variables are casted to more generic type (e.g. SMI to Integer, or Integer to Number) and `-trace-migration` (tracking when hidden classes are migrated).

```

1 // TODO: update when it lands in V8
2
3 [generalizing xQ] I:s->d (+20 maps) [xQ.Kd+919 at :719]
4 [generalizing xQ] Si:s->d (+3 maps) [xQ.Kd+1057 at :719]
5 [migrating xQ] I:s->d Si:s->d
6 [migrating xQ] I:s->d Si:s->d
  
```

Listing 2.3: Log of migration trace in V8

## 2.4. Garbage collection

Memory in JavaScript is managed automatically. Each allocation puts an object on memory heap. First generation of garbage collection traversed the whole tree and freed memory for all inaccessible objects. This type of deallocation is called mark-sweep and is causing taking a long time. Since JavaScript is single-threaded, this operation is blocking all other operations. To improve performance, especially in games, incremental scavange method of garbage collection was introduced. Engine tracks age of objects, allowing to quickly detect objects allocated temporarily (e.g. for a single frame rendered in game). When object is inaccessible, it's queued for deallocation, in chunks that don't cause long UI freezes.<sup>5</sup> <sup>6</sup>

TODO: check and extent

```

1 [1592]      34 ms: Scavenge 1.6 (18.8) -> 0.9 (18.8) MB, 0.0 ms [Runtime::PerformGC].
2 [1592]      37 ms: Scavenge 1.6 (18.8) -> 1.2 (19.8) MB, 1.0 ms [Runtime::PerformGC].
3 [1592]      40 ms: Scavenge 1.9 (19.8) -> 1.7 (19.8) MB, 1.0 ms [Runtime::PerformGC].
4 [1592]      43 ms: Scavenge 2.4 (19.8) -> 2.2 (19.8) MB, 2.0 ms [Runtime::PerformGC].
5 [1592]      49 ms: Scavenge 3.7 (19.8) -> 3.3 (20.8) MB, 3.0 ms [Runtime::PerformGC].
6 [1592]      56 ms: Scavenge 4.8 (20.8) -> 4.3 (21.8) MB, 3.0 ms [Runtime::PerformGC].
7 [1592]      74 ms: Scavenge 7.2 (21.8) -> 6.5 (23.8) MB, 6.0 ms [Runtime::PerformGC].
8 [1592]      98 ms: Scavenge 9.4 (23.8) -> 8.6 (24.8) MB, 5.0 ms [Runtime::PerformGC].
9 [1592]     194 ms: Scavenge 14.4 (24.8) -> 11.8 (25.8) MB, 23.0 ms [Runtime::PerformGC].
10 [1592]     340 ms: Scavenge 15.9 (25.8) -> 14.1 (30.8) MB, 15.0 ms
    (+ 10.0 ms in 41 steps since last GC) [Runtime::PerformGC].
11 [1592]     689 ms: Mark-sweep 18.7 (30.8) -> 14.0 (32.8) MB, 7.0 ms
12 [1592]     (+ 20.0 ms in 113 steps since start of marking, biggest step 1.0 ms)
    [StackGuard GC request] [GC in old space requested].
13 [1592]     1240 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 0.0 ms [Runtime::PerformGC].
14 [1592]     1799 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 0.0 ms [Runtime::PerformGC].
15 [1592]     2350 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 1.0 ms [Runtime::PerformGC].
16 [1592]     2902 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 1.0 ms [Runtime::PerformGC].

```

Listing 2.4: Log of garbage collection in V8

<sup>5</sup>[http://en.wikipedia.org/wiki/Cheney's\\_algorithm](http://en.wikipedia.org/wiki/Cheney's_algorithm)

<sup>6</sup>[http://en.wikipedia.org/wiki/Garbage\\_collection\\_\(computer\\_science\)](http://en.wikipedia.org/wiki/Garbage_collection_(computer_science))

### 3. Particle system

Particle system is one of most commonly used techniques to simulate smoke, fire, rain and other groups of discrete objects, usually independent from each other. System consist of defined number of emitters, producing lightweight particle objects with certain parameters. Each emitter has defined production ratio and each particle a certain lifespan, resulting in upper limit of total particles on screen. Some systems use also attraction points which enable better control over particles, using equations often similar to those of electrostatic forces. Such simulation is independent from rendering. The same particle system may be used for different effects with proper configuration.

Rysunek 3.1: Example rendering of tested particle system



### 3.1. System parameters

Tested system works on two-dimensional Cartesian plane. For purpose of performance analysis movements are calculated based only on frames rather than actual flow of time. This means that systems with different framerate will result in different visualisations, but requesting given amount of frames rendered will result in the same lifespan and total number of particles in both systems.

Emitter supports following parameters:

- position – initial position of created particles
- angle – angle counting clockwise from vector [0, 1]
- spread – parameter controlling random differences in initial angle of particles
- velocity – initial velocity of particles, in pixels per frame
- velocity spread – parameter controlling random differences in initial velocity of particles
- lifespan – initial lifespan of particles
- productionRate – amount of particles initialized in each frame

A Particle has similar properties:

- position
- velocity
- lifespan
- age – counted in frames, when higher then lifespan particle is removed from system

Source code of both implementations is attached in Appendix B.

## 3.2. Implementation with high memory allocation

Initial tested implementation has one very important property of particle emitter. Whenever new particles are created, new array of pointers is allocated and returned from emitter. System appends new particles to existing array. In each frame particle system creates new, empty array of particles and adds there only particles that are still alive. Array from previous frame and all dead particles are removed from system and deallocated. This is clearly suboptimal solution that allocates and deallocates plenty of memory in each frame. Purpose of this exercise is to show how both languages handle bad code and how big impact it has comparing to the optimal solution.

TODO: this part may need to be updated before publication. TODO: Is this accounting properly for v8 startup time? Maybe profiling ticks would be better.

```

1 $ time browser/static/d8 browser/static/particles1.js
2
3 real    0m20.619s
4 user    0m0.000s
5 sys     0m0.015s

```

Listing 3.1: Time measurement of unoptimized particle system in JavaScript

```

1 $ time runtime/static/particles1
2
3 real    0m2.606s
4 user    0m1.950s
5 sys     0m0.498s

```

Listing 3.2: Time measurement of unoptimized particle system in C++

Time measurement shows that JavaScript version is almost 8 times slower than native one. To analyse situation –prof and –log-timer-events flags may be used. Output file v8.log is parsed using available online tool.<sup>1</sup>

```

1 Statistical profiling result from null, (28293 ticks, 2631 unaccounted, 0 excluded).
2
3 [Shared libraries]:
4   ticks  total  nonlib    name
5   9577   37.3%   0.0%  D:\Dropbox\praca_magisterska\physics\browser\static\d8.exe
6   1078   4.2%   0.0%  C:\Windows\SysWOW64\ntdll.dll
7     3   0.0%   0.0%  C:\Windows\syswow64\kernel32.dll
8     2   0.0%   0.0%  C:\Windows\syswow64\KERNELBASE.dll
9
10 [JavaScript]:
11   ticks  total  nonlib    name
12   4621   18.0%  30.8%  LazyCompile: ~verifyIfAlive :463
13   2228   8.7%  14.9%  LazyCompile: ~stepParticle :460
14   1800   7.0%  12.0%  LazyCompile: ~smash.ParticleSystem.step :449
15   1018   4.0%  6.8%  Stub: CompareICStub

```

<sup>1</sup>[http://v8.googlecode.com/svn/branches/bleeding\\_edge/tools/profviz/profviz.html](http://v8.googlecode.com/svn/branches/bleeding_edge/tools/profviz/profviz.html)

```

16    949   3.7%   6.3%  Stub: LoadFieldStub {1}
17    831   3.2%   5.5%  LazyCompile: ~<anonymous> :466
18    799   3.1%   5.3%  Builtin: A builtin from the snapshot
19    770   3.0%   5.1%  Stub: CompareICStub {1}
20    739   2.9%   4.9%  Stub: CallFunctionStub
21    614   2.4%   4.1%  LazyCompile: IN native runtime.js:348
22    549   2.1%   3.7%  Stub: LoadFieldStub
23    430   1.7%   2.9%  Stub: CEntryStub
24    259   1.0%   1.7%  LazyCompile: *forEach native array.js:1188
25    246   1.0%   1.6%  LazyCompile: *verifyIfAlive :463
26    169   0.7%   1.1%  LazyCompile: *stepParticle :460
27    145   0.6%   1.0%  LazyCompile: *<anonymous> :466
28    129   0.5%   0.9%  Stub: LoadFieldStub {3}
29    127   0.5%   0.8%  LazyCompile: *smash.ParticleEmitter.getNewParticles :429
30    121   0.5%   0.8%  Stub: CompareICStub {2}
31     86   0.3%   0.6%  Stub: TranscendentalCacheStub {1}
32     79   0.3%   0.5%  Stub: ParticleSystem {1}
33     79   0.3%   0.5%  Stub: LoadFieldStub {4}
34     78   0.3%   0.5%  Stub: LoadFieldStub {2}
35     65   0.3%   0.4%  Stub: TranscendentalCacheStub
36     52   0.2%   0.3%  Stub: RecordWriteStub
37     42   0.2%   0.3%  Stub: CallFunctionStub_Args1
38     34   0.1%   0.2%  Stub: LoadFieldStub {5}
39     30   0.1%   0.2%  Stub: InterruptStub
40     14   0.1%   0.1%  LazyCompile: ~appendNewParticles :455
41      8   0.0%   0.1%  Stub: KeyedLoadElementStub
42      5   0.0%   0.0%  LazyCompile: ~forEach native array.js:1188
43      5   0.0%   0.0%  LazyCompile: *appendNewParticles :455
44      3   0.0%   0.0%  LazyCompile: *smash.Particle :389
45      3   0.0%   0.0%  Builtin: A builtin from the snapshot {1}
46      2   0.0%   0.0%  Stub: CEntryStub {1}
47      2   0.0%   0.0%  LazyCompile: ~smash.ParticleEmitter.getNewParticles :429
48      1   0.0%   0.0%  Stub: ToBooleanStub
49      1   0.0%   0.0%  Stub: FastNewClosureStub
50      1   0.0%   0.0%  Stub: CompareICStub {3}
51      1   0.0%   0.0%  Stub: CallConstructStub
52      1   0.0%   0.0%  Stub: BinaryOpStub_ADD_OverwriteRight_Smi+Number
53      1   0.0%   0.0%  LazyCompile: APPLY_PREPARE native runtime.js:432
54      1   0.0%   0.0%  LazyCompile: *random native math.js:188
55      1   0.0%   0.0%  KeyedLoadIC: {55}
56      1   0.0%   0.0%  Function: ~stepParticle :460
57
58 [C++]:
59   ticks  total  nonlib   name
60
61 [GC]:
62   ticks  total  nonlib   name
63   2067   8.1%

```

Listing 3.3: Profiler output for unoptimized particles

Methods prefixed with `~` are unoptimized, the ones prefixed with `*` are JIT compiled. As seen in profiler log, most of the time is spent in unoptimised versions of `verifyIfAlive` and `stepParticle` methods of particle system step.

```


1 smash.ParticleSystem.prototype.step = function() {
2   this.emitters.forEach(function appendNewParticles(a) {
3     this.particles.push.apply(this.particles, a.getNewParticles())
4   }, this);
5   var newParticles = [];
6   function stepParticle(a) {
7     a.step();
8   }
9   function verifyIfAlive(a) {
10     if (0 <= a.positionX && a.positionX < smash.ParticleSystem.CANVAS_WIDTH &&
11         0 <= a.positionY && a.positionY < smash.ParticleSystem.CANVAS_HEIGHT &&
12         a.age < a.lifespan) {
13       newParticles.push(a);
14     }
15   }
16   this.particles.forEach(function (a) {
17     stepParticle(a);
18     verifyIfAlive(a);
19   }, this);
20   this.particles = newParticles;
21 };

```

Listing 3.4: Annotated part of source

The same methods are also used in optimised versions, where they take significantly less ticks to run. It's clear that presented code not only allocates and deallocates too much memory, but also fails to run in optimised mode. It's visible on chart obtained from the same tool – stripe labelled `code kind in execution` shows multiple kinds of code running and is interrupted often with garbage collection cycles.

Rysunek 3.2: Chart of time used in unoptimised verion of JavaScript



Garbage collection cycles blocking execution are also visible with `--trace-gc` flag.

```
1 $ browser/static/d8 --trace-gc browser/static/particles1.js
```

```

2 [9696]      10 ms: Scavenge 1.6 (18.8) -> 0.9 (18.8) MB, 0.0 ms [Runtime::PerformGC].
3 [9696]      14 ms: Scavenge 1.6 (18.8) -> 1.3 (19.8) MB, 2.0 ms [Runtime::PerformGC].
4 (...).
5 [9696]      233 ms: Scavenge 15.0 (25.8) -> 9.7 (25.8) MB, 4.0 ms [Runtime::PerformGC].
6 [9696]      277 ms: Scavenge 15.6 (26.8) -> 10.0 (27.8) MB, 4.0 ms
7      (+ 13.0 ms in 22 steps since last GC) [Runtime::PerformGC].
8 [9696] Limited new space size due to high promotion rate: 1 MB
9 [9696]      284 ms: Mark-sweep 10.6 (27.8) -> 10.4 (28.8) MB, 6.0 ms
10     (+ 14.0 ms in 23 steps since start of marking, biggest step 1.0 ms)
11     [StackGuard GC request] [GC in old space requested].
12 [9696]      294 ms: Scavenge 11.5 (28.8) -> 11.0 (29.8) MB, 1.0 ms [Runtime::PerformGC].
13 [9696]      295 ms: Scavenge 11.9 (29.8) -> 11.6 (30.8) MB, 0.0 ms [Runtime::PerformGC].
14 (...).
15 [9696]      555 ms: Scavenge 43.4 (68.8) -> 43.4 (69.8) MB, 1.0 ms [Runtime::PerformGC].
16 [9696] Increasing marking speed to 3 due to high promotion rate
17 [9696]      564 ms: Scavenge 43.9 (69.8) -> 43.6 (69.8) MB, 1.0 ms
18      (+ 4.0 ms in 3 steps since last GC) [Runtime::PerformGC].
19 [9696]      576 ms: Scavenge 44.2 (69.8) -> 44.2 (70.8) MB, 1.0 ms
20      (+ 8.0 ms in 2 steps since last GC) [Runtime::PerformGC].
21 [9696]      581 ms: Mark-sweep 44.9 (70.8) -> 13.4 (61.8) MB, 3.0 ms
22      (+ 14.0 ms in 6 steps since start of marking, biggest step 2.0 ms)
23     [StackGuard GC request] [GC in old space requested].
24 [9696]      591 ms: Scavenge 14.3 (61.8) -> 14.1 (61.8) MB, 0.0 ms [Runtime::PerformGC].
25 (...).
```

Listing 3.5: Garbage collection in unoptimised particle system

### 3.3. Implementation with object pool

To improve performance different approach to particles allocation is used. Each particle has a flag "isDead" telling if it may be safely reused for new particle. Particle pool is kept along with a list of pointers to dead particles. This way when system reaches it's maximum congestion (around 15000 particles in given example) no new allocations occur. Creation of new particles is moved from particle emitter to particle system, to avoid allocation of new array. Emitter works now as a structure describing behaviour but not implementing one.

```

1 $ time browser/static/d8 browser/static/particles2.js
2
3 real    0m3.275s
4 user    0m0.000s
5 sys     0m0.015s

```

Listing 3.6: Time measurement of optimized particle system in JavaScript

```

1 $ time runtime/static/particles2
2
3 real    0m1.483s
4 user    0m1.387s
5 sys     0m0.000s

```

Listing 3.7: Time measurement of optimized particle system in C++

Optimised version shows overall improvement of 85% for JavaScript and 45% for C++ making JavaScript version only 2.2 times slower than native one. It's clearly visible that JavaScript is more sensitive to unwise memory management.

```

1 Statistical profiling result from null, (3780 ticks, 2 unaccounted, 0 excluded).
2
3 [Shared libraries]:
4   ticks  total  nonlib  name
5     98    2.6%   0.0%  D:\Dropbox\praca_magisterska\physics\browser\static\d8.exe
6      6    0.2%   0.0%  C:\Windows\SysWOW64\ntdll.dll
7
8 [JavaScript]:
9   ticks  total  nonlib  name
10    3476   92.0%  94.6%  LazyCompile: *f.step browser/static/particles2.js:28
11     101    2.7%   2.7%  Stub: TranscendentalCacheStub {1}
12      89    2.4%   2.4%  Stub: TranscendentalCacheStub
13       5    0.1%   0.1%  Script: ~browser/static/particles2.js
14       1    0.0%   0.0%  Stub: TranscendentalCacheStub {2}
15       1    0.0%   0.0%  Stub: BinaryOpStub_MUL_OverwriteLeft_Number+Number
16       1    0.0%   0.0%  LazyCompile: *sin native math.js:199
17       1    0.0%   0.0%  Builtin: A builtin from the snapshot
18
19 [C++]:
20   ticks  total  nonlib  name
21

```

```


22 [GC]:
23   ticks  total  nonlib   name
24      59    1.6%

```

Listing 3.8: Profiler output for optimized particles

Profiling shows that step method of particle system now runs always in optimised mode and almost no time is spent on other methods. The same is visible on profiling chart, where code kind in execution stripe shows only optimised code.

Rysunek 3.3: Chart of time used in optimised verion of JavaScript



Situation is also improved in garbage collection log.

```

1 $ browser/static/d8 --trace-gc browser/static/particles2.js
2 [8348]      10 ms: Scavenge 1.6 (18.8) -> 0.9 (18.8) MB, 1.0 ms [Runtime::PerformGC].
3 [8348]      13 ms: Scavenge 1.6 (18.8) -> 1.2 (19.8) MB, 1.0 ms [Runtime::PerformGC].
4 [8348]      16 ms: Scavenge 1.9 (19.8) -> 1.7 (19.8) MB, 1.0 ms [Runtime::PerformGC].
5 [8348]      19 ms: Scavenge 2.4 (19.8) -> 2.2 (19.8) MB, 2.0 ms [Runtime::PerformGC].
6 [8348]      25 ms: Scavenge 3.7 (19.8) -> 3.3 (20.8) MB, 3.0 ms [Runtime::PerformGC].
7 [8348]      32 ms: Scavenge 4.8 (20.8) -> 4.3 (21.8) MB, 2.0 ms [Runtime::PerformGC].
8 [8348]      50 ms: Scavenge 7.2 (21.8) -> 6.5 (23.8) MB, 5.0 ms [Runtime::PerformGC].
9 [8348]      75 ms: Scavenge 9.4 (23.8) -> 8.6 (24.8) MB, 5.0 ms [Runtime::PerformGC].
10 [8348]     173 ms: Scavenge 14.4 (24.8) -> 11.8 (25.8) MB, 24.0 ms [Runtime::PerformGC].
11 [8348]     319 ms: Scavenge 15.9 (25.8) -> 14.1 (30.8) MB, 15.0 ms
12     (+ 9.0 ms in 44 steps since last GC) [Runtime::PerformGC].
13 [8348]     669 ms: Mark-sweep 18.7 (30.8) -> 14.0 (32.8) MB, 7.0 ms
14     (+ 17.0 ms in 116 steps since start of marking, biggest step 1.0 ms)
15     [StackGuard GC request] [GC in old space requested].
16 [8348]     1229 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 0.0 ms [Runtime::PerformGC].
17 [8348]     1793 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 0.0 ms [Runtime::PerformGC].
18 [8348]     2353 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 0.0 ms [Runtime::PerformGC].
19 [8348]     2914 ms: Scavenge 21.8 (32.8) -> 14.0 (32.8) MB, 1.0 ms [Runtime::PerformGC].


```

Listing 3.9: Garbage collection in optimised particle system

## 4. Sphere collision

Spheres are the simplest of bounding shapes used in collision detection. This chapter presents tests for two versions of algorithms – naive  $O(N^2)$  approach and with partitioned space. While simpler algorithm has far greater number of collision checks per frame, it allocates almost no memory per frame. More complex method will minimise number of checks, but additional structure and steps added may influence overall execution time in unexpected way.

Rysunek 4.1: Example rendering of tested sphere collision system




## 4.1. Algorithm description

Collision detection for spheres is a trivial task. If distance between two spheres is smaller than sum of their radiiuses, spheres collide.

$$\sqrt{(S_1.x - S_2.x)^2 + (S_1.y - S_2.y)^2 + (S_1.z - S_2.z)^2} < S_1.radius + S_2.radius$$

While the equation is simple, with large number N of colliding objects complexity of this detection is  $O(N^2)$ . Methods of space partitioning are used to reduce number of checks. One used in this benchmark is Octree. Base for algorithm is a tree-like structure of bounding boxes. Whenever a box contains more than one colliding object, it's divided into eight smaller boxes, by partitioning each edge by 2. When maximum tree depth is reached, multiple objects are stored in one box. One object may be referenced from multiple boxes, when its size and position make them intersect. Each movement requires a check if object has already moved to one of neighbour boxes.

Rysunek 4.2: Octree structure. Source: <http://en.wikipedia.org/wiki/File:Octree2.svg/>



Having objects grouped in boxes reduces complexity of collision check. Since an object may collide only with objects in the same box, number of checks is much smaller. Overall complexity of Octree checks is  $O(N \log N)$ . TODO: reference for complexity.

When collision is detected, collision response is calculated. From rule of conservation of momentum:

$$m_1 * \vec{v}_1 + m_2 * \vec{v}_2 = m_1 * \vec{v}'_1 + m_2 * \vec{v}'_2$$


Meaning that change of both momentums is of equal value.

$$\begin{aligned} m_1 * \vec{v}'_1 &= m_1 * \vec{v}_1 - \Delta P \\ m_2 * \vec{v}'_2 &= m_2 * \vec{v}_2 + \Delta P \\ \vec{v}'_1 &= \vec{v}_1 - \frac{\Delta P}{m_1} \\ \vec{v}'_2 &= \vec{v}_2 + \frac{\Delta P}{m_2} \end{aligned}$$

To simplify response rotation and deformation of spheres are ignored. This does not affect performance analysis, since operations performed all tests is done in the same way.

Let

Rysunek 4.3: Example of WebGL Octree debug rendering. Available online at <http://pawlowski.it/octtree/>



$$P = |\Delta P|$$

$$N = pos_1 \hat{-} pos_2$$

Since transference of momentum occurs only along single point of contact:

$$\Delta P = P * \hat{N}$$

$$\vec{v}_1' = \vec{v}_1 - \frac{P}{m_1} * \vec{N}$$

$$\vec{v}_2' = \vec{v}_2 + \frac{P}{m_2} * \vec{N}$$

Lets split each velocity into two scalars, perpendicular and parallel value of velocity vector, and introduce  $\vec{Q}$ , similar to  $\vec{N}$ , a perpendicular normalised vector lining along exchanged momentum.

$$\vec{v}_1 = a_1 * \vec{N} + b_1 * \vec{Q}$$

$$\vec{v}_2 = a_2 * \vec{N} + b_2 * \vec{Q}$$

$$\vec{v}_1' = a'_1 * \vec{N} + b'_1 * \vec{Q}$$

$$\vec{v}_2' = a'_2 * \vec{N} + b'_2 * \vec{Q}$$

Deriving from previous equations:


$$a'_1 = a_1 - \frac{P}{m_1}$$

$$b'_1 = b_1$$

$$a'_2 = a_2 + \frac{P}{m_2}$$

$$b'_2 = b_2$$

Rysunek 4.4: Illustration for collision response



Now lets use rule of conservation of energy to solve P:

$$\begin{aligned} \frac{m_1}{2} * ||\vec{v}_1||^2 + \frac{m_2}{2} * ||\vec{v}_2||^2 &= \frac{m_1}{2} * ||\vec{v}'_1||^2 + \frac{m_2}{2} * ||\vec{v}'_2||^2 \\ \frac{m_1}{2} * (a_1^2 + b_1^2) + \frac{m_2}{2} * (a_2^2 + b_2^2) &= \frac{m_1}{2} * (a'_1^2 + b'_1^2) + \frac{m_2}{2} * (a'_2^2 + b'_2^2) \\ P &= \frac{2*m_1*m_2*(a_1-a_2)}{m_1+m_2} \end{aligned}$$

and finally, using result from conservation of momentum:


$$\begin{aligned} \vec{v}'_1 &= \vec{v}_1 - \frac{2*(a_1-a_2)}{m_1+m_2} * m_2 * \vec{N} \\ \vec{v}'_2 &= \vec{v}_2 + \frac{2*(a_1-a_2)}{m_1+m_2} * m_1 * \vec{N} \end{aligned}$$

From this result, using only dot product of velocity vectors and normalised vector  $pos_1 - pos_2$  correct response to collision is calculated. In tested scenarios mass of all spheres is equal since it doesn't affect complexity of calculations and produces less randomised results.

## 4.2. $O(N^2)$ approach


Naive approach for collision detection proves to be easy to implement in JavaScript. Since almost no memory is allocated in each frame, no garbage collection issues appear. All methods are well defined and work mostly on floats. This results in highly optimised binary code produced by compiler, as shown on 4.5.

Rysunek 4.5: Chart of time used in optimised version of JavaScript




Multiple tests with  $N=1000$  and different number of frames rendered show, that for simple mathematical task performance of JavaScript is very close to this of C++. On average, JavaScript version of benchmark runs 15% longer than C++ one.

Rysunek 4.6: Comparison of total execution time.  $N = 1000$ , varying number of frames.




Rysunek 4.7: Comparison of execution time per frame.  $N = 1000$ , varying number of frames.



### 4.3. Octree-partitioned space


Rysunek 4.8: Octree partitioned sphere collision system



Tests with Octree partitioning were executed with  $N=1000$  spheres and  $T=1000$  frames. Varying value is maximum depth of Octree, ranging from 1 to 10. Changing maximum depth reduces number of collision checks between spheres, as shown on 4.9.

Rysunek 4.9: Number of collisions in Octree


#### AVG collision checks (millions) per Octree level



For low values overall complexity of checks doesn't change significantly, since most of spheres are in one or few bounding cubes and no checks are skipped. Additional operations related to Octree are actually making this solution slower than  $O(n^2)$  approach. For depth values in optimal zone, number of collision is reduced by factor of at least 10, while keeping Octree overhead reasonable. Interesting thing happens when maximum level of Octree is very high and edge of smallest Octree cube approaches size of spheres. Number of transitions between partitioning cubes, related memory allocation and cleanups actually make this approach much slower, as shown on 4.10. Moreover, some spheres are references in more than one cube, raising again number of collision checks.

It's clearly visible that number of collision checks and run time is correlated only up to certain point. For deep Octrees number of checks doesn't improve further, but overall run time is getting longer. Performance of JavaScript in relation to C++ varies between 30% to 80% overhead. In comparison with  $O(n^2)$  approach, optimal Octree in JavaScript runs over 92% faster and C++ over 94% faster.

Rysunek 4.10: Run times in Octree system




## 5. Emscripten

JavaScript is often called an assembly language of the Web.<sup>1</sup> One could argue that since only one language is supported by browsers it could be made a compilation target similar to assembler for CPU. This statement is flawed since eventually JavaScript is translated to assembly making it only an intermediate step. Probably resemblance to ByteCode in JVM, which is compilation target of multiple languages like Java, Scala and Clojure is more in place. Nevertheless, last years showed multiple projects aimed at converting code to JavaScript. Some introduce new syntax like CoffeeScript, Dart or TypeScript while still serving the same purpose – providing human readable code that is interpreted in browser on fly. Others, that are focus of this chapter, aim to convert existing projects to run in browser.

Several new projects are connected to make this happen. First steps in conversion between languages were made with LLVM project<sup>2</sup> which currently is a collection of tools and compilers converting code to and from intermediate representation (LLVM IR). For C++ Clang<sup>3</sup> is a conversion tool.

Rysunek 5.1: Pipeline of Emscripten conversion. Source:  
<http://www.hanselman.com/blog/JavaScriptIsWebAssemblyLanguageAndThatsOK.aspx>



Code in LLVM is suitable for further conversion to language like JavaScript. This part is handled by Emscripten<sup>4</sup> project. Initially compilation target for Emscripten was plain JavaScript. With recent developments asm.js<sup>5</sup> library was created. It provides syntax built on top of JavaScript, that is strongly typed and easily translatable to assembly language. Asm.js details are explained in section 5.1.

<sup>1</sup><http://www.hanselman.com/blog/JavaScriptIsWebAssemblyLanguageAndThatsOK.aspx>

<sup>2</sup><http://llvm.org/>

<sup>3</sup><http://clang.llvm.org/>

<sup>4</sup><https://github.com/kripken/emscripten/wiki>

<sup>5</sup><http://asmjs.org/spec/latest/>

```

1 do {
2   if (a[k + 22 | 0] << 24 >> 24 == 30) {
3     h = b[k + 14 >> 1] | 0;
4     if ((h - 1 & 65535) > 1) {
5       break
6     }
7     l = c[j >> 2] | 0;
8     p = (c[1384465] | 0) + 3 | 0;
9     if (p >>> 0 < 26) {
10       s = (2293760 >>> (p >>> 0) & 1 | 0) != 0 ? 0 : -1e3
11     } else {
12       s = -1e3
13     }
14     if (!(Vq(d, l, k | 0, h << 16 >> 16, s) | 0)) {
15       break
16     }
17     g[(c[f >> 2] | 0) + (l * 112 & -1) + 56 >> 2] = +(b[k + 12 >> 1] << 16 >> 16 | 0);
18     h = (c[f >> 2] | 0) + (l * 112 & -1) + 60 | 0;
19     l = k + 28 | 0;
20     c[h >> 2] = c[l >> 2] | 0;
21     c[h + 4 >> 2] = c[l + 4 >> 2] | 0;
22     c[h + 8 >> 2] = c[l + 8 >> 2] | 0;
23     c[h + 12 >> 2] = c[l + 12 >> 2] | 0;
24     c[h + 16 >> 2] = c[l + 16 >> 2] | 0;
25     c[h + 20 >> 2] = c[l + 20 >> 2] | 0;
26     c[h + 24 >> 2] = c[l + 24 >> 2] | 0
27   }
28 } while (0);

```

Listing 5.1: Example of code using asm.js

Project, built in cooperation with Mozilla Foundation, has its own engine for Firefox – OdinMonkey, designed to run faster for this limited and well-defined syntax.

Altogether these projects resulted in multiple libraries and games converted from native version to JavaScript.

Proof-of-concept demo made in cooperation between Mozilla and Unreal is Epic Citadel HTML5 – Unreal Engine 3 technology demo<sup>6</sup> instance running in browser.<sup>7</sup> Companies claim it took only four days to complete the conversion.


Another example of successful converted project is ammo.js<sup>8</sup> – originating from Bullet physics engine. TODO: Maybe extend this part a bit, cover more on how conversion was going and what were the issues.

<sup>6</sup>[http://www.unrealengine.com/en/showcase/udk/epic\\_citadel/](http://www.unrealengine.com/en/showcase/udk/epic_citadel/)


<sup>7</sup><http://www.unrealengine.com/html5/>

<sup>8</sup><https://github.com/kripken/ammo.js/>

Rysunek 5.2: Epic Citadel screenshot



Rysunek 5.3: Ammo.js demo colliding 500 boxes at 30fps, available at  
<http://kripken.github.io/ammo.js/examples/new/ammo.html>



## 5.1. Asm.js overview

Asm.js introduces some improvements targeted to fix performance problems of JavaScript. Ahead of time compilation enforces very specific rules on coding style. Documentation<sup>9</sup> lists:

### 5.1.1. Unboxed representations of integers and floating-point numbers

In asm.js only types allowed are integers and doubles. All numbers have annotations indicating static type (see: 2.2). This way compiler doesn't have to detect possible transitions between variable types and code overall runs faster.

### 5.1.2. Absence of runtime type checks

Since asm.js works only on well-defined numbers, all function calls are monomorphic and stable. In OdinMonkey ahead-of-time compilation is able to compile them to the most optimised version without tracking method calls. In engines using JIT methods are compiled early and newer deoptimised.

### 5.1.3. Absence of garbage collection

As shown in previous chapters, garbage collection calls are often a performance bottleneck. Asm.js solves this problem by eliminating garbage collection completely. Memory is stored in short-life variables, deallocated after method exits and in global heaps, which are never resized or deallocated.

### 5.1.4. Efficient heap loads and stores

Heaps are global arrays of statically typed arrays, in JavaScript implemented as objects listed in 5.1. Size of heap doesn't change during runtime – it has to be calculated during compilation and incorrect prediction or memory leaks may result in buffer overflow. Heaps are always passed as an argument to asm.js modules. Each module may reference part of the heap and use it as long as necessary.

### 5.1.5. Summary

These solutions remove some of performance bottlenecks described in previous chapters. Code suitable to run with asm.js is almost unreadable by programmer and resembles assembly code. Asm.js is not designed to be a language used by a programmer, it is mainly a target for compilation using converters like Emscripten.

Most of optimisation used by asm.js are consistent with code that is expected by V8 engine – variables and methods are monomorphic, garbage collection is close to zero. It's worth noting that code written by hand is almost always shorter than one generated by Emscripten. Partial solution for this is built-in Google Closure Compiler used on output of Emscripten and different levels of optimisation. In tests mentioned in this work all

---

<sup>9</sup><http://asmjs.org/spec/latest/>

Tablica 5.1: Statically typed arrays in JavaScript

View Type	Element Size (Bytes)	Element Type
Uint8Array	1	intish
Int8Array	1	intish
Uint16Array	2	intish
Int16Array	2	intish
Uint32Array	4	intish
Int32Array	4	intish
Float32Array	4	doublish
Float64Array	8	doublish

solutions take 2 to 4kB compiled, while Emscripten produces over 450kB of code for each. This affects real life performance by lengthening at least transfer and parse time for code. Average parse time of 1kB of JS is believed to be up to 1ms<sup>10</sup>. Global average bandwidth was 3.1 Mbps in Q1 2013<sup>11</sup> thus transfer of each kilobyte is around 2.5ms. In total, load time of tested code is approximately 1.5 second on average bandwidth and platform. In case of larger applications and games waiting time for load may be significantly larger and should be taken under consideration.

---

<sup>10</sup><https://developers.google.com/speed/docs/best-practices/mobile>

<sup>11</sup>[http://www.akamai.com/dl/akamai/akamai\\_soti\\_q113.pdf](http://www.akamai.com/dl/akamai/akamai_soti_q113.pdf)

## 6. Summary

All four test were compiled and run times were measured on different platforms.

Unoptimised version of particle system (see: 3.2) was designed to perform a lot of memory operations. In tests it's visible that C++ handles this task best. Code generated using Emscripten benefits from static memory heap which effectively works similar to object pool introduced later and runs approximately twice as long as C++. Plain JavaScript suffers greatly from memory allocation issues and unoptimised code, resulting in 6 times slower execution than C++.

Optimised particles (see: 3.3) with object pool and low garbage collection show how improvements of algorithm result in much faster JavaScript execution. It still takes twice as long to run particle system in V8, but Emscripten version takes three times longer than C++. Additional overhead of long and complex code is clearly visible and since JS code employs the same techniques that Emscripten uses automatically, there is no improvement in related areas. It's worth mentioning that unoptimised version of C++ particle system is slightly slower than optimised JavaScript one, showing that code quality improvement that doesn't affect algorithmic complexity of algorithm may be more important than choice of environment.

Tablica 6.1: Particle tests on different platforms

Platform	Unoptimised particles			Optimised particles		
	C++	JavaScript	Emscripten	C++	JavaScript	Emscripten
Fedora 19, Intel i7 2670QM, 4GB RAM, g++ 4.8.1	3.21s	19.51s	4.85s	1.63s	4.96s	5.10s
Windows 7, Intel i7 2670QM, 4GB RAM, g++ 4.7.3, Cygwin	3.51s	20.77s	6.46s	1.71s	3.47s	5.57s

Sphere collision test is putting high load on CPU.

In  $O(n^2)$  version (see: 4.2) exactly 1 000 000 000 checks for object collisions are made. Overall execution time is surprisingly good for JavaScript with overhead of approximately 15% and 25% for Emscripten generated version. It's a result of putting focus on pure mathematical operations that are quickly compiled by V8 and processed on unboxed numbers in asm.js.

Space partitioning using Octree greatly reduces number of collisions (to less than 100 000) and execution time. To give meaningful results simulation time is increased from 1000 frames to 10000. Under these circumstances difference in run time changes to 20% for Javascript and stays similarly around 25% for Emscripten. This is result of small memory operations related to Octree areas.

Tablica 6.2: Spheres tests on different platforms

Platform	$O(n^2)$ spheres			Octree spheres		
	C++	JavaScript	Emscripten	C++	JavaScript	Emscripten
Fedora 19, Intel i7 2670QM, 4GB RAM, g++ 4.8.1	4.96s	9.02s	12.35s	3.44s	14.14s	11.20s
Windows 7, Intel i7 2670QM, 4GB RAM, g++ 4.7.3, Cygwin	9.52s	10.81s	11.82s	14.10s	16.95s	17.79s

Above results show how well written JavaScript or properly converted C++ are able to perform in browser with similar performance as native programs, rarely exceeding 100% overhead and sometimes getting as close as 15% to C++ execution time.

Conducted experiments show a gap between JavaScript and C++ performance. Significant language design differences result in code that is often easier to write but also easier to abuse. Benchmarks show differences between 15% and 100% overhead for correctly designed JavaScript code and over 500% for incorrect patterns. Considering Moore's law stating that computers double speed every 18 months it safe to say that JavaScript is very close to being suitable for any type of development.

Tests show clear pattern regarding dynamic variable types in JavaScript. Whenever boxing and unboxing happens, JIT compilation is not able to properly optimise code and bring it up to performance of C++. This affects both simple variables and properties and is especially visible for numbers. Transitions between integer and floats are expensive while easy to overlook.

Types affect significantly also method calls cost. Keeping methods monomorphic in core parts of physics engine is very important. Additional cost of polymorphism of parameters is not only boxing and unboxing of parameters but also time spent of optimising and deoptimising compiled method which makes initial warmup of engine longer. Exporting well defined methods to be called from polymorphic ones is an easy workaround for this performance bottleneck.

Lastly, memory management proven to be one of the most important problems in JavaScript. Automated garbage collection connected with popular pattern of creating and returning of arrays is an important problem. Memory allocation of objects is also a bottleneck, but not very dissimilar to one in C++. As shown in second version of particle system, usage of object pools and changing architecture to avoid array creation are techniques that can be employed to fight with it. It is worth mentioning that while garbage collection always introduces some overhead it is reasonable to avoid it at all costs. Sphere collision system with octree partitioning is also introducing and destroying objects, but overhead is significantly smaller than gained speedup. Advice for memory operations is to avoid objects living only for a single frame i.e. temporary variables and helpers. Long living objects are in general unavoidable and should be used whenever suitable.

General advice for programming in JavaScript is to use techniques similar to those found in asm.js – keep types static, method calls monomorphic and work carefully with memory.

Conducted tests show that while gap between JavaScript and native application exists and is not insignificant, there is a lot of potential in such approach. It is expected, that with growing community and interest from game industry new games will be released on browser within few years. Performance issues

may prevent works on AAA titles, but companies focused more on social aspect of games and new trends in monetisation may create games targeted for different users. With capabilities of browsers equal to having 18 months older machine, less graphically demanding titles like The Sims or World of Warcraft may certainly be ported to run in JavaScript.

## A. Acknowledgements

This publication expresses my personal experiences and opinions, not those of my employer or co-workers. No internal information was used in process of writing. Any errors in benchmark approach, code and factual content of publication are solely my responsibility.

Work is shared under MIT license and hosted online at <https://github.com/fridek/Thesis-physics>

The MIT License (MIT)

Copyright (c) 2013 Sebastian Poręba

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## B. Source code

### B.1. Math utilities

```
1 /**
2  * @fileoverview Math utils.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4  */
5
6 goog.provide('smash.math');
7
8
9 /**
10  * @param {number} x
11  * @return {number}
12  */
13 smash.math.square = function(x) {
14     return x * x;
15 };
16
17
18 /**
19  * @param {number} x1
20  * @param {number} y1
21  * @param {number} z1
22  * @param {number} x2
23  * @param {number} y2
24  * @param {number} z2
25  * @return {number}
26  */
27 smash.math.vectorDistance = function(x1, y1, z1, x2, y2, z2) {
28     return Math.sqrt(smash.math.square(x1 - x2) +
29                     smash.math.square(y1 - y2) +
30                     smash.math.square(z1 - z2));
31 };
32
33
34 /**
35  * @param {number} x
36  * @param {number} y
37  * @param {number} z
38  * @return {number}
39  */
```

```

40 smash.math.vectorLength = function(x, y, z) {
41   return Math.sqrt(smash.math.square(x) +
42     smash.math.square(y) +
43     smash.math.square(z));
44 };
45
46
47 /**
48 * @param {!smash.Sphere} sphere1
49 * @param {!smash.Sphere} sphere2
50 * @return {boolean}
51 */
52 smash.math.checkCollidingSpheres = function(sphere1, sphere2) {
53   return smash.math.vectorDistance(
54     sphere1.positionX, sphere1.positionY, sphere1.positionZ,
55     sphere2.positionX, sphere2.positionY, sphere2.positionZ) <
56     sphere1.radius + sphere2.radius;
57 };
58
59
60 /**
61 * @param {number} x1
62 * @param {number} y1
63 * @param {number} z1
64 * @param {number} x2
65 * @param {number} y2
66 * @param {number} z2
67 * @return {number}
68 */
69 smash.math.dot = function(x1, y1, z1, x2, y2, z2) {
70   return x1 * x2 + y1 * y2 + z1 * z2;
71 };

```

Listing B.1: Math utilities in JavaScript

```

1 #include "math.h"
2
3
4 /**
5 * @param {number} x
6 * @return {number}
7 */
8 float smash::math::square(float x) {
9   return x * x;
10 }
11
12
13 /**
14 * @param {number} x1
15 * @param {number} y1
16 * @param {number} z1
17 * @param {number} x2
18 * @param {number} y2
19 * @param {number} z2
20 * @return {number}

```

```

21  /*
22  float smash::math::vectorDistance(float x1, float y1, float z1, float x2, float y2, float z2) {
23      return sqrt(smash::math::square(x1 - x2) +
24                  smash::math::square(y1 - y2) +
25                  smash::math::square(z1 - z2));
26  };
27
28
29 /**
30 * @param {number} x
31 * @param {number} y
32 * @param {number} z
33 * @return {number}
34 */
35 float smash::math::vectorLength(float x, float y, float z) {
36     return sqrt(smash::math::square(x) +
37                 smash::math::square(y) +
38                 smash::math::square(z));
39 };
40
41 /**
42 * @param {number} x
43 * @param {number} y
44 * @param {number} z
45 * @return {number}
46 */
47 float smash::math::dot(float x1, float y1, float z1, float x2, float y2, float z2) {
48     return x1 * x2 + y1 * y2 + z1 * z2;
49 };
50
51
52 /**
53 * @param {!smash.Sphere} sphere1
54 * @param {!smash.Sphere} sphere2
55 * @return {boolean}
56 */
57 bool smash::math::checkCollidingSpheres(smash::Sphere* sphere1, smash::Sphere* sphere2) {
58     return smash::math::vectorDistance(
59         sphere1->positionX, sphere1->positionY, sphere1->positionZ,
60         sphere2->positionX, sphere2->positionY, sphere2->positionZ) <
61         sphere1->radius + sphere2->radius;
62 };

```

Listing B.2: Math utilities in C++

## B.2. Particle system

```
1 /**
2  * @fileoverview Particle object.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4  */
5
6 goog.provide('smash.Particle');
7
8
9
10 /**
11  * @struct
12  * @constructor
13  */
14 smash.Particle = function() {
15     /**
16      * @type {number}
17      */
18     this.positionX = 0.1;
19
20     /**
21      * @type {number}
22      */
23     this.positionY = 0.1;
24
25     /**
26      * @type {number}
27      */
28     this.velocityX = 0.1;
29
30     /**
31      * @type {number}
32      */
33     this.velocityY = 0.1;
34
35     /**
36      * @type {number}
37      */
38     this.age = 0;
39
40     /**
41      * In seconds.
42      * @type {number}
43      */
44     this.lifespan = 0;
45
46     /**
47      * @type {boolean}
48      */
49     this.isDead = false;
50 };
51
52 }
```

```

53 /**
54 *
55 */
56 smash.Particle.prototype.step = function() {
57   this.positionX += this.velocityX;
58   this.positionY += this.velocityY;
59   this.age++;
60 };
61
62
63 /**
64 * Recover defaults.
65 */
66 smash.Particle.prototype.reset = function() {
67   this.positionX = 0;
68   this.positionY = 0;
69   this.velocityX = 0;
70   this.velocityY = 0;
71   this.age = 0;
72   this.lifespan = 0;
73   this.isDead = false;
74 };

```

Listing B.3: Particle object in JavaScript

```

1 /**
2 * @fileoverview Particle object.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5 #include "particle.h"
6
7 smash::Particle::Particle() {
8   positionX = 0;
9   positionY = 0;
10  velocityX = 0;
11  velocityY = 0;
12  age = 0;
13  lifespan = 0;
14  isDead = false;
15 }
16
17 /**
18 * @param deltaTime
19 */
20 void smash::Particle::step() {
21   this->positionX += this->velocityX;
22   this->positionY += this->velocityY;
23   this->age++;
24 };
25
26
27 /**
28 * Recover defaults.
29 */
30 void smash::Particle::reset() {

```

```

31     this->positionX = 0;
32     this->positionY = 0;
33     this->velocityX = 0;
34     this->velocityY = 0;
35     this->age = 0;
36     this->lifespan = 0;
37     this->isDead = false;
38 }

```

Listing B.4: Particle object in C++

```

1 /**
2  * @fileoverview Particle emitter.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 goog.provide('smash.ParticleEmitter');
7
8 goog.require('smash.Particle');
9
10
11
12 /**
13  * @constructor
14 */
15 smash.ParticleEmitter = function() {
16 /**
17  * @type {number}
18 */
19 this.positionX = 0.1;
20
21 /**
22  * @type {number}
23 */
24 this.positionY = 0.1;
25
26 /**
27  * @type {number}
28 */
29 this.angle = 0.1;
30
31 /**
32  * @type {number}
33 */
34 this.velocity = 10.1;
35
36 /**
37  * @type {number}
38 */
39 this.velocitySpread = 0.2;
40
41 /**
42  * @type {number}
43 */
44 this.spread = Math.PI * 10 / 180;

```

```
45  /**
46   * In ticks.
47   * @type {number}
48   */
49
50  this.lifespan = 50;
51
52 /**
53  * @type {number}
54  */
55  this.productionRate = 10;
56 };
57
58
59 /**
60  * @param {number} angle
61  */
62 smash.ParticleEmitter.prototype.setAngle = function(angle) {
63   this.angle = Math.PI * angle / 180;
64 };
65
66
67 /**
68  * @param {number} velocity
69  */
70 smash.ParticleEmitter.prototype.setVelocity = function(velocity) {
71   this.velocity = velocity;
72 };
73
74
75 /**
76  * @param {number} velocitySpread
77  */
78 smash.ParticleEmitter.prototype.setVelocitySpread = function(velocitySpread) {
79   this.velocitySpread = velocitySpread;
80 };
81
82
83 /**
84  * @param {number} spread
85  */
86 smash.ParticleEmitter.prototype.setSpread = function(spread) {
87   this.spread = Math.PI * spread / 180;
88 };
89
90
91 /**
92  * @param {number} lifespan
93  */
94 smash.ParticleEmitter.prototype.setLifespan = function(lifespan) {
95   this.lifespan = lifespan;
96 };
97
98
99 /**
100 * @param {number} rate
101 */
```

```

102 | smash.ParticleEmitter.prototype.setProductionRate = function(rate) {
103 |   this.productionRate = rate;
104 | };
105 |
106 |
107 | /**
108 | * @return {!Array.<!smash.Particle>}
109 | */
110 | smash.ParticleEmitter.prototype.getNewParticles = function() {
111 |   var newParticles = [];
112 |   for (var i = 0; i < this.productionRate; i++) {
113 |     var p = new smash.Particle();
114 |     p.lifespan = this.lifespan;
115 |     p.positionX = this.positionX;
116 |     p.positionY = this.positionY;
117 |     p.velocityX = Math.sin(this.angle +
118 |       (Math.random() - 0.5) * this.spread) *
119 |         this.velocity * this.velocitySpread;
120 |     p.velocityY = Math.cos(this.angle +
121 |       (Math.random() - 0.5) * this.spread) *
122 |         this.velocity *
123 |         (1 + (Math.random() - 0.5) * this.velocitySpread);
124 |     newParticles.push(p);
125 |   }
126 |   return newParticles;
127 | };

```

Listing B.5: Particle emitter object in JavaScript

```

1 /**
2 * @fileoverview Particle emitter.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5 #include "particleEmitter.h"
6
7 smash::ParticleEmitter::ParticleEmitter() {
8   positionX = 0;
9   positionY = 0;
10  angle = 0;
11  velocity = 10;
12  velocitySpread = 0.2;
13  spread = M_PI * 10 / 180;
14  lifespan = 50;
15  productionRate = 10;
16 };
17
18
19 /**
20 * @param angle
21 */
22 void smash::ParticleEmitter::setAngle(float angle) {
23   this->angle = M_PI * angle / 180;
24 };
25
26

```

```
27 /**
28 * @param velocity
29 */
30 void smash::ParticleEmitter::setVelocity(float velocity) {
31     this->velocity = velocity;
32 }
33
34
35 /**
36 * @param velocitySpread
37 */
38 void smash::ParticleEmitter::setVelocitySpread(float velocitySpread) {
39     this->velocitySpread = velocitySpread;
40 }
41
42
43 /**
44 * @param spread
45 */
46 void smash::ParticleEmitter::setSpread(float spread) {
47     this->spread = M_PI * spread / 180;
48 }
49
50
51 /**
52 * @param lifespan
53 */
54 void smash::ParticleEmitter::setLifespan(float lifespan) {
55     this->lifespan = lifespan;
56 }
57
58
59 /**
60 * @param rate
61 */
62 void smash::ParticleEmitter::setProductionRate(int rate) {
63     this->productionRate = rate;
64 }
65
66
67 /**
68 * @return {!Array.<!smash::Particle>}
69 */
70 std::vector<smash::Particle*>* smash::ParticleEmitter::getNewParticles() {
71     std::vector<smash::Particle*> *newParticles = new std::vector<smash::Particle*>;
72     for (int i = 0; i < this->productionRate; i++) {
73         smash::Particle* p = new smash::Particle();
74         p->lifespan = this->lifespan;
75         p->positionX = this->positionX;
76         p->positionY = this->positionY;
77         p->velocityX = sin(this->angle +
78             ((float) rand() / (RAND_MAX)) - 0.5) * this->spread) *
79             this->velocity *
80             (1 + (((float) rand() / (RAND_MAX)) - 0.5) * this->velocitySpread);
81         p->velocityY = cos(this->angle +
82             ((float) rand() / (RAND_MAX)) - 0.5) * this->spread) *
83             this->velocity *
```

```

84     (1 + (((float) rand() / (RAND_MAX)) - 0.5) * this->velocitySpread);
85     newParticles->push_back(p);
86 }
87 return newParticles;
88 };

```

Listing B.6: Particle emitter object in C++

```

1 /**
2  * @fileoverview Particle system.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 goog.provide('smash.ParticleSystem');
7
8
9 goog.require('smash.flags');
10
11
12
13 /**
14  * @constructor
15 */
16 smash.ParticleSystem = function() {
17 /**
18  * @type {!Array.<!smash.Particle>}
19 */
20 this.particles = [];
21
22 /**
23  * @type {!Array.<!smash.ParticleEmitter>}
24 */
25 this.emitters = [];
26
27 if (smash.flags.DRAWING_ENABLED) {
28 /**
29  * @type {!Element}
30 */
31 this.canvas = window.document.createElement('canvas');
32 this.canvas.width = smash.ParticleSystem.CANVAS_WIDTH;
33 this.canvas.height = smash.ParticleSystem.CANVAS_HEIGHT;
34 window.document.body.appendChild(this.canvas);
35
36 /**
37  * @type {!CanvasRenderingContext2D}
38 */
39 this.context = this.canvas.getContext('2d');
40
41 /**
42  * @type {!ImageData}
43 */
44 this.imageData = this.context.getImageData(0, 0,
45     smash.ParticleSystem.CANVAS_WIDTH, smash.ParticleSystem.CANVAS_HEIGHT);
46
47 /**

```

```
48     * @type {!CanvasPixelArray}
49     */
50   this.pixels = this.imageData.data;
51 }
52 };
53
54
55 /**
56 * @const {number}
57 */
58 smash.ParticleSystem.CANVAS_WIDTH = 1200;
59
60
61 /**
62 * @const {number}
63 */
64 smash.ParticleSystem.CANVAS_HEIGHT = 400;
65
66
67 /**
68 *
69 */
70 smash.ParticleSystem.prototype.step = function() {
71   if (smash.flags.DRAWING_ENABLED) {
72     for (var i = 0; i < smash.ParticleSystem.CANVAS_WIDTH *
73       smash.ParticleSystem.CANVAS_HEIGHT * 4; i += 4) {
74       this.pixels[i] = 0;
75       this.pixels[i + 1] = 0;
76       this.pixels[i + 2] = 0;
77       this.pixels[i + 3] = 0;
78     }
79   }
80
81   this.emitters.forEach(function(emitter) {
82     this.particles.push.apply(this.particles,
83       emitter.getNewParticles());
84   }, this);
85
86   var newParticles = [];
87   this.particles.forEach(function(p) {
88     p.step();
89     if (p.positionX >= 0 &&
90       p.positionX < smash.ParticleSystem.CANVAS_WIDTH &&
91       p.positionY >= 0 &&
92       p.positionY < smash.ParticleSystem.CANVAS_HEIGHT &&
93       p.age < p.lifespan) {
94       newParticles.push(p);
95     }
96
97     if (smash.flags.DRAWING_ENABLED) {
98       var baseIndex =
99         (Math.round(p.positionY) *
100          smash.ParticleSystem.CANVAS_WIDTH +
101          Math.round(p.positionX)) * 4;
102       this.pixels[baseIndex] = 255;
103       this.pixels[baseIndex + 1] = 0;
104       this.pixels[baseIndex + 2] = 0;
```

```

105     this.pixels[baseIndex + 3] = 255;
106   }
107 }, this);
108 if (smash.flags.DRAWING_ENABLED) {
109   this.context.putImageData(this.imageData, 0, 0);
110 }
111
112 this.particles = newParticles;
113 };
114
115 /**
116 * @param {!smash.ParticleEmitter} emitter
117 */
118 smash.ParticleSystem.prototype.addEmitter = function(emitter) {
119   this.emitters.push(emitter);
120 };

```

Listing B.7: Initial particle system object in JavaScript

```

1 /**
2  * @fileoverview Particle system.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5 #include "particleSystem.h"
6
7 smash::ParticleSystem::ParticleSystem() {
8   this->particles = new std::vector<smash::Particle*>;
9   this->emitters = new std::vector<smash::ParticleEmitter*>;
10 }
11
12 smash::ParticleSystem::~ParticleSystem() {
13   this->particles->erase(this->particles->begin(), this->particles->end());
14   delete this->particles;
15   this->emitters->erase(this->emitters->begin(), this->emitters->end());
16   delete this->emitters;
17 }
18
19 void smash::ParticleSystem::step() {
20   for (std::vector<smash::ParticleEmitter*>::iterator it = this->emitters->begin(); it != this->emitters->end();
21     std::vector<smash::Particle*>* particleFromEmitters = (*it)->getNewParticles();
22     this->particles->insert(this->particles->end(), particleFromEmitters->begin(), particleFromEmitters->end());
23     delete particleFromEmitters;
24   }
25
26 std::vector<smash::Particle*> newParticles;
27
28 for (std::vector<smash::Particle*>::iterator it = this->particles->begin(); it != this->particles->end();
29   smash::Particle* p = *it;
30   p->step();
31   if (p->positionX >= 0 &&
32     p->positionX < smash::ParticleSystem::CANVAS_WIDTH &&
33     p->positionY >= 0 &&
34     p->positionY < smash::ParticleSystem::CANVAS_HEIGHT &&
35     p->age < p->lifespan) {

```

```

36     newParticles.push_back(p);
37 } else {
38     delete p;
39 }
40 };
41 this->particles->swap(newParticles);
42 newParticles.clear();
43 };
44
45 /**
46 * @param emitter
47 */
48 void smash::ParticleSystem::addEmitter(smash::ParticleEmitter* emitter) {
49     this->emitters->push_back(emitter);
50 }

```

Listing B.8: Initial particle system in C++

```

1 /**
2  * @fileoverview Particle system.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4  */
5
6 goog.provide('smash.ParticleSystem2');
7
8 goog.require('smash.Particle');
9 goog.require('smash.flags');
10
11
12
13 /**
14  * @constructor
15 */
16 smash.ParticleSystem2 = function() {
17 /**
18  * @type {!Array.<smash.Particle>}
19  */
20 this.particles = [];
21
22 /**
23  * @type {!Array.<number>}
24  */
25 this.deadParticles = [];
26
27 /**
28  * @type {!Array.<smash.ParticleEmitter>}
29  */
30 this.emitters = [];
31
32 if (smash.flags.DRAWING_ENABLED) {
33 /**
34  * @type {!Element}
35  */
36 this.canvas = window.document.createElement('canvas');
37 this.canvas.width = smash.ParticleSystem2.CANVAS_WIDTH;

```

```
38     this.canvas.height = smash.ParticleSystem2.CANVAS_HEIGHT;
39     window.document.body.appendChild(this.canvas);
40
41     /**
42      * @type {!CanvasRenderingContext2D}
43      */
44     this.context = this.canvas.getContext('2d');
45
46     /**
47      * @type {!ImageData}
48      */
49     this.imageData = this.context.getImageData(0, 0,
50         smash.ParticleSystem2.CANVAS_WIDTH,
51         smash.ParticleSystem2.CANVAS_HEIGHT);
52
53     /**
54      * @type {!CanvasPixelArray}
55      */
56     this.pixels = this.imageData.data;
57 }
58 };
59
60
61 /**
62  * @const {number}
63 */
64 smash.ParticleSystem2.CANVAS_WIDTH = 1200;
65
66
67 /**
68  * @const {number}
69 */
70 smash.ParticleSystem2.CANVAS_HEIGHT = 400;
71
72
73 /**
74  *
75 */
76 smash.ParticleSystem2.prototype.step = function() {
77   if (smash.flags.DRAWING_ENABLED) {
78     for (var i = 0; i < smash.ParticleSystem2.CANVAS_WIDTH *
79         smash.ParticleSystem2.CANVAS_HEIGHT * 4; i += 4) {
80       this.pixels[i] = 0;
81       this.pixels[i + 1] = 0;
82       this.pixels[i + 2] = 0;
83       this.pixels[i + 3] = 0;
84     }
85   }
86
87   for (var ei = 0; ei < this.emitters.length; ei++) {
88     var emitter = this.emitters[ei];
89     for (var i = 0; i < emitter.productionRate; i++) {
90       var pIndex = this.deadParticles.pop();
91       if (pIndex !== undefined) {
92         var p = this.particles[pIndex];
93         p.reset();
94       } else {
```

```

95     var p = new smash.Particle();
96     this.particles.push(p);
97 }
98
99     p.lifespan = emitter.lifespan;
100    p.positionX = emitter.positionX;
101    p.positionY = emitter.positionY;
102    p.velocityX = Math.sin(emitter.angle +
103        (Math.random() - 0.5) * emitter.spread) *
104        emitter.velocity * emitter.velocitySpread;
105    p.velocityY = Math.cos(emitter.angle +
106        (Math.random() - 0.5) * emitter.spread) *
107        emitter.velocity *
108        (1 + (Math.random() - 0.5) * emitter.velocitySpread);
109 }
110 }
111
112 for (var i = 0; i < this.particles.length; i++) {
113     var p = this.particles[i];
114     p.step();
115     if (p.positionX < 0 ||
116         p.positionX >= smash.ParticleSystem2.CANVAS_WIDTH ||
117         p.positionY < 0 ||
118         p.positionY >= smash.ParticleSystem2.CANVAS_HEIGHT ||
119         p.age > p.lifespan) {
120         this.deadParticles.push(i);
121         p.isDead = true;
122     }
123
124     if (smash.flags.DRAWING_ENABLED && !p.isDead) {
125         var baseIndex =
126             (Math.round(p.positionY) *
127                 smash.ParticleSystem2.CANVAS_WIDTH +
128                 Math.round(p.positionX)) * 4;
129         this.pixels[baseIndex] = Math.round(p.velocityX * 80);
130         this.pixels[baseIndex + 1] = Math.round(p.velocityX * 80);
131         this.pixels[baseIndex + 2] = 255 - Math.round(p.age / p.lifespan * 255);
132         this.pixels[baseIndex + 3] = 255;
133     }
134 }
135
136     if (smash.flags.DRAWING_ENABLED) {
137         this.context.putImageData(this.imageData, 0, 0);
138     }
139 };
140
141
142 /**
143 * @param {!smash.ParticleEmitter} emitter
144 */
145 smash.ParticleSystem2.prototype.addEmitter = function(emitter) {
146     this.emitters.push(emitter);
147 };

```

Listing B.9: Optimised particle system object in JavaScript

```

1  /**
2   * @fileoverview Particle system.
3   * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4   */
5 #include "particleSystem2.h"
6
7 smash::ParticleSystem2::ParticleSystem2() {
8     this->particles = new std::vector<smash::Particle*>;
9     this->deadParticles = new std::stack<smash::Particle*>;
10    this->emitters = new std::vector<smash::ParticleEmitter*>;
11 }
12
13 smash::ParticleSystem2::~ParticleSystem2() {
14     this->particles->erase(this->particles->begin(), this->particles->end());
15     delete this->particles;
16     while (!this->deadParticles->empty()) {
17         delete this->deadParticles->top();
18         this->deadParticles->pop();
19     }
20     delete this->deadParticles;
21     this->emitters->erase(this->emitters->begin(), this->emitters->end());
22     delete this->emitters;
23 }
24
25 void smash::ParticleSystem2::step() {
26     for (std::vector<smash::ParticleEmitter*>::iterator it = this->emitters->begin(); it != this->emitter
27         smash::ParticleEmitter* emitter = *it;
28         for (int i = 0; i < emitter->productionRate; i++) {
29             smash::Particle* p;
30             if (!this->deadParticles->empty()) {
31                 p = this->deadParticles->top();
32                 this->deadParticles->pop();
33                 p->reset();
34             } else {
35                 p = new smash::Particle();
36                 this->particles->push_back(p);
37             }
38
39             p->lifespan = emitter->lifespan;
40             p->positionX = emitter->positionX;
41             p->positionY = emitter->positionY;
42             p->velocityX = sin(emitter->angle +
43                 (((float) rand() / (RAND_MAX)) - 0.5) * emitter->spread) *
44                 emitter->velocity *
45                 (1 + (((float) rand() / (RAND_MAX)) - 0.5) * emitter->velocitySpread);
46             p->velocityY = cos(emitter->angle +
47                 (((float) rand() / (RAND_MAX)) - 0.5) * emitter->spread) *
48                 emitter->velocity *
49                 (1 + (((float) rand() / (RAND_MAX)) - 0.5) * emitter->velocitySpread);
50         }
51     }
52
53     for (std::vector<smash::Particle*>::iterator it = this->particles->begin(); it != this->particles->
54         smash::Particle* p = *it;
55         if (p->isDead) {
56             continue;

```

```
57    }
58    p->step();
59    if (p->positionX < 0 ||
60        p->positionX >= smash::ParticleSystem2::CANVAS_WIDTH ||
61        p->positionY < 0 ||
62        p->positionY >= smash::ParticleSystem2::CANVAS_HEIGHT ||
63        p->age > p->lifespan) {
64        this->deadParticles->push(p);
65        p->isDead = true;
66    }
67 }
68 };
69
70 /**
71 * @param emitter
72 */
73 void smash::ParticleSystem2::addEmitter(smash::ParticleEmitter* emitter) {
74     this->emitters->push_back(emitter);
75 }
```

Listing B.10: Optimised particle system in C++

## B.3. Spheres collision detection

```
1 /**
2 * @fileoverview Sphere file.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6
7 goog.provide('smash.Sphere');
8
9
10
11 /**
12 * @struct
13 * @constructor
14 */
15 smash.Sphere = function() {
16 /**
17 * @type {number}
18 */
19 this.positionX = 0.1;
20
21 /**
22 * @type {number}
23 */
24 this.positionY = 0.1;
25
26 /**
27 * @type {number}
28 */
29 this.positionZ = 0.1;
30
31 /**
32 * @type {number}
33 */
34 this.velocityX = 0.1;
35
36 /**
37 * @type {number}
38 */
39 this.velocityY = 0.1;
40
41 /**
42 * @type {number}
43 */
44 this.velocityZ = 0.1;
45
46 /**
47 * @type {number}
48 */
49 this.radius = 5.5;
50
51 /**
52 * @type {number}
```

```

53  /*
54   * @param {number} mass
55   */
56
57
58 /**
59  * @param {number} stepTime
60 */
61 smash.Sphere.prototype.step = function(stepTime) {
62   this.positionX += this.velocityX * stepTime;
63   this.positionY += this.velocityY * stepTime;
64   this.positionZ += this.velocityZ * stepTime;
65 };

```

Listing B.11: Sphere object in JavaScript

```

1 /**
2  * @fileoverview Sphere file.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 #include "sphere.h"
7
8 smash::Sphere::Sphere() {
9   positionX = 0;
10  positionY = 0;
11  positionZ = 0;
12  velocityX = 0;
13  velocityY = 0;
14  velocityZ = 0;
15  radius = 5.5;
16  mass = 3.5;
17 }
18
19 /**
20  * @param stepTime
21 */
22 void smash::Sphere::step(float stepTime) {
23   this->positionX += this->velocityX * stepTime;
24   this->positionY += this->velocityY * stepTime;
25   this->positionZ += this->velocityZ * stepTime;
26 }

```

Listing B.12: Sphere object in C++

```

1 /**
2  * @fileoverview Sphere collision detection system.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 goog.provide('smash.SphereSystem');
7
8 goog.require('smash.Sphere');
9 goog.require('smash.flags');

```

```
10 | goog.require('smash.math');
11 |
12 |
13 |
14 | /**
15 | * @constructor
16 | */
17 | smash.SphereSystem = function() {
18 |     var generalVelocity = 1;
19 |     /**
20 |      * @type {!Array.<!smash.Sphere>}
21 |     */
22 |     this.spheres = new Array(smash.SphereSystem.SPHERES_COUNT);
23 |     for (var i = 0; i < smash.SphereSystem.SPHERES_COUNT; i++) {
24 |         var sphere = new smash.Sphere();
25 |         sphere.positionX = (Math.random() - 0.5) * 400;
26 |         sphere.positionY = (Math.random() - 0.5) * 200;
27 |         sphere.positionZ = (Math.random() - 0.5) * 100;
28 |         sphere.velocityX = (Math.random() - 0.5) * generalVelocity;
29 |         sphere.velocityY = (Math.random() - 0.5) * generalVelocity;
30 |         sphere.velocityZ = (Math.random() - 0.5) * generalVelocity;
31 |         this.spheres[i] = sphere;
32 |     }
33 |
34 |     if (smash.flags.DRAWING_ENABLED) {
35 |         /**
36 |          * @type {!THREE.PerspectiveCamera}
37 |         */
38 |         this.camera = new THREE.PerspectiveCamera(20,
39 |             smash.SphereSystem.CANVAS_WIDTH /
40 |                 smash.SphereSystem.CANVAS_HEIGHT,
41 |                 1, 10000);
42 |         this.camera.position.z = 1000;
43 |
44 |         var controls = new THREE.OrbitControls(this.camera);
45 |         controls.addEventListener('change', goog.bind(function() {
46 |             this.renderer.render(this.scene, this.camera);
47 |         }, this));
48 |
49 |         /**
50 |          * @type {!THREE.Scene}
51 |         */
52 |         this.scene = new THREE.Scene();
53 |
54 |         var spotLight = new THREE.PointLight(0xffffffff);
55 |         spotLight.position.set(-40, 60, -10);
56 |         this.scene.add(spotLight);
57 |
58 |         var axes = new THREE.AxisHelper(20);
59 |         this.scene.add(axes);
60 |
61 |         var planeGeometry = new THREE.PlaneGeometry(
62 |             10000, 10000, 100, 100);
63 |         var planeMaterial = new THREE.MeshBasicMaterial({
64 |             color: 0xcccccc,
65 |             wireframe: true
66 |         });
67 |     }
68 | }
```

```

67
68     var plane = new THREE.Mesh(planeGeometry, planeMaterial);
69     plane.rotation.x = -0.5 * Math.PI;
70     plane.position.x = 0;
71     plane.position.y = smash.SphereSystem.FLOOR_LEVEL;
72     plane.position.z = 0;
73
74     this.scene.add(plane);
75
76
77
78     var material = new THREE.MeshLambertMaterial({
79         color: 0xff0000
80     });
81 /**
82 * @type {!Array.<!THREE.SphereGeometry>}
83 */
84 this.threeSpheres = new Array(smash.SphereSystem.SPHERES_COUNT);
85 for (var i = 0; i < smash.SphereSystem.SPHERES_COUNT; i++) {
86     var sphere = new THREE.SphereGeometry(this.spheres[i].radius, 10, 10);
87     var mesh = new THREE.Mesh(sphere, material);
88     mesh.position.x = this.spheres[i].positionX;
89     mesh.position.y = this.spheres[i].positionY;
90     mesh.position.z = this.spheres[i].positionZ;
91     this.threeSpheres[i] = mesh;
92
93     this.scene.add(mesh);
94 }
95
96
97
98 /**
99 * @type {!THREE.WebGLRenderer}
100 */
101 this.renderer = new THREE.WebGLRenderer();
102 this.renderer.setSize(smash.SphereSystem.CANVAS_WIDTH,
103                     smash.SphereSystem.CANVAS_HEIGHT);
104 document.body.appendChild(this.renderer.domElement);
105 this.renderer.render(this.scene, this.camera);
106 }
107
108 /**
109 * @type {number}
110 */
111 this.collisions = 0;
112 };
113
114
115 /**
116 * @const {number}
117 */
118 smash.SphereSystem.SPHERES_COUNT = 1000;
119
120
121 /**
122 * @const {boolean}
123 */

```

```
124 smash.SphereSystem.GRAVITY_ENABLED = true;
125
126
127 /**
128 * @const {number}
129 */
130 smash.SphereSystem.GRAVITY_FORCE = 0.1;
131
132
133 /**
134 * @const {number}
135 */
136 smash.SphereSystem.FLOOR_LEVEL = -100;
137
138
139 /**
140 * (1 - energy lost on floor hit)
141 * @const {number}
142 */
143 smash.SphereSystem.FLOOR_FRICTION = 0.8;
144
145
146 /**
147 * @const {number}
148 */
149 smash.SphereSystem.CANVAS_WIDTH = 1200;
150
151
152 /**
153 * @const {number}
154 */
155 smash.SphereSystem.CANVAS_HEIGHT = 400;
156
157
158 /**
159 * @param {!smash.Sphere} sphere1
160 * @param {!smash.Sphere} sphere2
161 */
162 smash.SphereSystem.collide = function(sphere1, sphere2) {
163   var distanceX = sphere1.positionX - sphere2.positionX;
164   var distanceY = sphere1.positionY - sphere2.positionY;
165   var distanceZ = sphere1.positionZ - sphere2.positionZ;
166   var distanceLength = smash.math.vectorLength(
167     distanceX, distanceY, distanceZ);
168
169   // normalize
170   distanceX /= distanceLength;
171   distanceY /= distanceLength;
172   distanceZ /= distanceLength;
173
174   var a1 = smash.math.dot(sphere1.velocityX, sphere1.velocityY,
175     sphere1.velocityZ, distanceX, distanceY, distanceZ);
176   var a2 = smash.math.dot(sphere2.velocityX, sphere2.velocityY,
177     sphere2.velocityZ, distanceX, distanceY, distanceZ);
178   var optimizedP = (2.0 * (a1 - a2)) / (sphere1.mass + sphere2.mass);
179
180   sphere1.velocityX -= optimizedP * sphere2.mass * distanceX;
```

```
181     sphere1.velocityY -= optimizedP * sphere2.mass * distanceY;
182     sphere1.velocityZ -= optimizedP * sphere2.mass * distanceZ;
183     sphere2.velocityX += optimizedP * sphere1.mass * distanceX;
184     sphere2.velocityY += optimizedP * sphere1.mass * distanceY;
185     sphere2.velocityZ += optimizedP * sphere1.mass * distanceZ;
186   };
187
188
189 /**
190  * @param {!smash.Sphere} sphere
191 */
192 smash.SphereSystem.prototype.applyGravity = function(sphere) {
193   if (smash.SphereSystem.GRAVITY_ENABLED) {
194     sphere.velocityY -= smash.SphereSystem.GRAVITY_FORCE;
195   }
196 };
197
198 /**
199  * @param {!smash.Sphere} sphere
200 */
201 smash.SphereSystem.prototype.applyFloor = function(sphere) {
202   if (sphere.positionY - sphere.radius <
203       smash.SphereSystem.FLOOR_LEVEL) {
204     sphere.velocityY *= -smash.SphereSystem.FLOOR_FRICTION;
205   }
206 };
207
208
209 /**
210  *
211 */
212 smash.SphereSystem.prototype.step = function() {
213   for (var i = 0; i < smash.SphereSystem.SPHERES_COUNT; i++) {
214     this.applyGravity(this.spheres[i]);
215     this.applyFloor(this.spheres[i]);
216
217
218     this.spheres[i].step(1);
219     for (var j = 0; j < smash.SphereSystem.SPHERES_COUNT; j++) {
220       if (i != j &&
221           smash.math.checkCollidingSpheres(this.spheres[i], this.spheres[j])) {
222         this.collisions++;
223         smash.SphereSystem.collide(this.spheres[i], this.spheres[j]);
224       }
225     }
226
227     if (smash.flags.DRAWING_ENABLED) {
228       this.threeSpheres[i].position.x = this.spheres[i].positionX;
229       this.threeSpheres[i].position.y = this.spheres[i].positionY;
230       this.threeSpheres[i].position.z = this.spheres[i].positionZ;
231     }
232   }
233
234   if (smash.flags.DRAWING_ENABLED) {
235     this.renderer.render(this.scene, this.camera);
236   }
237 }
```

238 };

Listing B.13: Sphere system object in JavaScript

```

1 /**
2 * @fileoverview Sphere collision detection system.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 #include "sphereSystem.h"
7
8 smash::SphereSystem::SphereSystem() {
9     this->spheres = new std::vector<smash::Sphere*>;
10    collisions = 0;
11
12    float generalVelocity = 1;
13    for (int i = 0; i < smash::SphereSystem::SPHERES_COUNT; i++) {
14        smash::Sphere* sphere = new smash::Sphere();
15        sphere->positionX = (((float) rand() / (RAND_MAX)) - 0.5) * 400;
16        sphere->positionY = (((float) rand() / (RAND_MAX)) - 0.5) * 200;
17        sphere->positionZ = (((float) rand() / (RAND_MAX)) - 0.5) * 100;
18        sphere->velocityX = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
19        sphere->velocityY = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
20        sphere->velocityZ = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
21        this->spheres->push_back(sphere);
22    }
23 };
24
25
26 smash::SphereSystem::~SphereSystem() {
27     this->spheres->erase(this->spheres->begin(), this->spheres->end());
28     delete this->spheres;
29 };
30
31
32 /**
33 * @param {smash::Sphere*} sphere1
34 * @param {smash::Sphere*} sphere2
35 */
36 void smash::SphereSystem::collide(smash::Sphere* sphere1, smash::Sphere* sphere2) {
37     float distanceX = sphere1->positionX - sphere2->positionX;
38     float distanceY = sphere1->positionY - sphere2->positionY;
39     float distanceZ = sphere1->positionZ - sphere2->positionZ;
40     float distanceLength = smash::math::vectorLength(
41         distanceX, distanceY, distanceZ);
42
43     // normalize
44     distanceX /= distanceLength;
45     distanceY /= distanceLength;
46     distanceZ /= distanceLength;
47
48     float a1 = smash::math::dot(sphere1->velocityX, sphere1->velocityY, sphere1->velocityZ,
49         distanceX, distanceY, distanceZ);
50     float a2 = smash::math::dot(sphere2->velocityX, sphere2->velocityY, sphere2->velocityZ,
51         distanceX, distanceY, distanceZ);

```

```

52     float optimizedP = (2.0 * (a1 - a2)) / (sphere1->mass + sphere2->mass);
53
54     sphere1->velocityX -= optimizedP * sphere2->mass * distanceX;
55     sphere1->velocityY -= optimizedP * sphere2->mass * distanceY;
56     sphere1->velocityZ -= optimizedP * sphere2->mass * distanceZ;
57     sphere2->velocityX += optimizedP * sphere1->mass * distanceX;
58     sphere2->velocityY += optimizedP * sphere1->mass * distanceY;
59     sphere2->velocityZ += optimizedP * sphere1->mass * distanceZ;
60 }
61
62 void smash::SphereSystem::applyGravity(smash::Sphere* sphere) {
63     if (smash::SphereSystem::GRAVITY_ENABLED) {
64         sphere->velocityY -= smash::SphereSystem::GRAVITY_FORCE;
65     }
66 }
67
68
69 void smash::SphereSystem::applyFloor(smash::Sphere* sphere) {
70     if (sphere->positionY - sphere->radius <
71         smash::SphereSystem::FLOOR_LEVEL) {
72         sphere->velocityY *= -smash::SphereSystem::FLOOR_FRICTION;
73     }
74 }
75
76
77 void smash::SphereSystem::step() {
78     for (std::vector<smash::Sphere*>::iterator it = this->spheres->begin(); it != this->spheres->end();
79         smash::Sphere* s = *it;
80         applyGravity(s);
81         applyFloor(s);
82
83
84         s->step(1);
85         for (std::vector<smash::Sphere*>::iterator it2 = this->spheres->begin(); it2 != this->spheres->end();
86             smash::Sphere* s2 = *it2;
87             if (s != s2 &&
88                 smash::math::checkCollidingSpheres(s, s2)) {
89                 this->collisions++;
90                 smash::SphereSystem::collide(s, s2);
91             }
92         }
93     }
94 }
```

Listing B.14: Sphere system in C++

```

1 /**
2  * @fileoverview Octree space partitioning.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 goog.provide('smash.Octree');
7
8 goog.require('goog.array');
```

```
10
11
12 /**
13 * @param {number} left
14 * @param {number} right
15 * @param {number} top
16 * @param {number} bottom
17 * @param {number} near
18 * @param {number} far
19 * @param {number} maxDepth
20 * @constructor
21 */
22 smash.Octree = function(left, right, top, bottom, near, far, maxDepth) {
23
24 /**
25 * @type {number}
26 */
27 this.maxDepth = maxDepth;
28
29 /**
30 * @type {Array.<!smash.Octree>}
31 */
32 this.childNodes = [];
33
34 /**
35 * @type {number}
36 */
37 this.left = left;
38
39 /**
40 * @type {number}
41 */
42 this.right = right;
43
44 /**
45 * @type {number}
46 */
47 this.top = top;
48
49 /**
50 * @type {number}
51 */
52 this.bottom = bottom;
53
54 /**
55 * @type {number}
56 */
57 this.near = near;
58
59 /**
60 * @type {number}
61 */
62 this.far = far;
63
64 /**
65 * @type {Array.<!smash.Sphere>}
66 */
```

```

67     this.objects = [];
68 };
69
70
71 /**
72 *
73 */
74 smash.Octree.prototype.split = function() {
75     var middleX = (this.left + this.right) / 2;
76     var middleY = (this.top + this.bottom) / 2;
77     var middleZ = (this.near + this.far) / 2;
78     var maxDepth = this.maxDepth - 1;
79
80     this.childNodes[0] = new smash.Octree(this.left, middleX,
81         this.top, middleY, this.near, middleZ, maxDepth);
82     this.childNodes[1] = new smash.Octree(middleX, this.right,
83         this.top, middleY, this.near, middleZ, maxDepth);
84
85     this.childNodes[2] = new smash.Octree(this.left, middleX,
86         middleY, this.bottom, this.near, middleZ, maxDepth);
87     this.childNodes[3] = new smash.Octree(middleX, this.right,
88         middleY, this.bottom, this.near, middleZ, maxDepth);
89
90     this.childNodes[4] = new smash.Octree(this.left, middleX,
91         this.top, middleY, middleZ, this.far, maxDepth);
92     this.childNodes[5] = new smash.Octree(middleX, this.right,
93         this.top, middleY, middleZ, this.far, maxDepth);
94
95     this.childNodes[6] = new smash.Octree(this.left, middleX,
96         middleY, this.bottom, middleZ, this.far, maxDepth);
97     this.childNodes[7] = new smash.Octree(middleX, this.right,
98         middleY, this.bottom, middleZ, this.far, maxDepth);
99 };
100
101
102 /**
103 *
104 * @return {boolean}
105 */
106 smash.Octree.prototype.hasAnyObjects = function() {
107     return this.objects.length > 0 ||
108         this.childNodes.some(function(node) {
109             return node.hasAnyObjects();
110         });
111 };
112
113
114 /**
115 *
116 * @param {number} left
117 * @param {number} right
118 * @param {number} top
119 * @param {number} bottom
120 * @param {number} near
121 * @param {number} far
122 * @return {Array.<number>}
123 */

```

```

124 smash.Octree.prototype.getAllOffsets = function(left, right, top, bottom,
125   near, far) {
126   var middleX = (this.left + this.right) / 2;
127   var middleY = (this.top + this.bottom) / 2;
128   var middleZ = (this.near + this.far) / 2;
129
130   var offset = 0;
131   var bothX = false, bothY = false, bothZ = false;
132
133   if (left < middleX && right < middleX) {
134     offset += 0;
135   } else if (left > middleX && right > middleX) {
136     offset += 1;
137   } else {
138     bothX = true;
139   }
140
141   if (top < middleY && bottom < middleY) {
142     offset += 0;
143   } else if (top > middleY && bottom > middleY) {
144     offset += 2;
145   } else {
146     bothY = true;
147   }
148
149   if (near < middleZ && far < middleZ) {
150     offset += 0;
151   } else if (near > middleZ && far > middleZ) {
152     offset += 4;
153   } else {
154     bothZ = true;
155   }
156
157   var allOffsets = [offset];
158   if (bothZ) {
159     for (var i = 0, l = allOffsets.length; i < l; i++) {
160       allOffsets.push(allOffsets[i] + 4);
161     }
162   }
163   if (bothY) {
164     for (var i = 0, l = allOffsets.length; i < l; i++) {
165       allOffsets.push(allOffsets[i] + 2);
166     }
167   }
168   if (bothX) {
169     for (var i = 0, l = allOffsets.length; i < l; i++) {
170       allOffsets.push(allOffsets[i] + 1);
171     }
172   }
173   return allOffsets;
174 };
175
176
177 /**
178 * @param {!smash.Sphere} sphere
179 * @return {boolean}
180 */

```

```

181 smash.Octree.prototype.sphereLeft = function(sphere) {
182   return (sphere.positionX + sphere.radius < this.left ||
183     sphere.positionX - sphere.radius > this.right ||
184     sphere.positionY + sphere.radius < this.top ||
185     sphere.positionY - sphere.radius > this.bottom ||
186     sphere.positionZ + sphere.radius < this.near ||
187     sphere.positionZ - sphere.radius > this.far);
188 };
189
190
191 /**
192 * @param {!smash.Sphere} sphere
193 */
194 smash.Octree.prototype.removeSphere = function(sphere) {
195   goog.array.remove(this.objects, sphere);
196 };
197
198
199 /**
200 * @param {!smash.Sphere} sphere
201 */
202 smash.Octree.prototype.addSphere = function(sphere) {
203   if (this.objects.indexOf(sphere) != -1) {
204     return; // this happens when sphere is re-added from two
205     // different nodes after removal.
206   }
207
208   var left = sphere.positionX - sphere.radius;
209   var right = sphere.positionX + sphere.radius;
210   var top = sphere.positionY - sphere.radius;
211   var bottom = sphere.positionY + sphere.radius;
212   var near = sphere.positionZ - sphere.radius;
213   var far = sphere.positionZ + sphere.radius;
214
215   if (this.maxDepth == 0 || this.objects.length == 0) {
216     this.objects.push(sphere);
217   } else {
218     if (this.childNodes.length == 0) {
219       this.split();
220     }
221     var offsets = this.getAllOffsets(left, right, top, bottom, near, far);
222     offsets.forEach(function(offset) {
223       this.childNodes[offset].addSphere(sphere);
224     }, this);
225   }
226 };
227
228
229 /**
230 *
231 */
232 smash.Octree.prototype.log = function() {
233   window.console.log('On level ', this.maxDepth,
234   ' octree node with ', this.objects.length, ' objects');
235   this.childNodes.forEach(function(node) {
236     node.log();
237   });

```

238 };

Listing B.15: Octree in JavaScript

```

1 /**
2 * @fileoverview Octree space partitioning.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 #include "octree.h"
7
8
9 smash::Octree::Octree(float left, float right,
10     float top, float bottom,
11     float near, float far,
12     int maxDepth) {
13     this->maxDepth = maxDepth;
14     this->childNodes = new std::vector<smash::Octree*>;
15     this->left = left;
16     this->right = right;
17     this->top = top;
18     this->bottom = bottom;
19     this->near = near;
20     this->far = far;
21     this->objects = new std::vector<smash::Sphere*>;
22 };
23
24 smash::Octree::~Octree() {
25     delete this->objects;
26     for (std::vector<smash::Octree*>::iterator it = this->childNodes->begin(); it != this->childNodes->end();
27         delete *it;
28     }
29     delete this->childNodes;
30 }
31
32 /**
33 *
34 */
35 void smash::Octree::split() {
36     float middleX = (this->left + this->right) / 2;
37     float middleY = (this->top + this->bottom) / 2;
38     float middleZ = (this->near + this->far) / 2;
39     int maxDepth = this->maxDepth - 1;
40
41     this->childNodes->push_back(new smash::Octree(this->left, middleX, this->top, middleY, this->near,
42     this->childNodes->push_back(new smash::Octree(middleX, this->right, this->top, middleY, this->near,
43
44     this->childNodes->push_back(new smash::Octree(this->left, middleX, middleY, this->bottom, this->near,
45     this->childNodes->push_back(new smash::Octree(middleX, this->right, middleY, this->bottom, this->near,
46
47     this->childNodes->push_back(new smash::Octree(this->left, middleX, this->top, middleY, middleZ, this->near,
48     this->childNodes->push_back(new smash::Octree(middleX, this->right, this->top, middleY, middleZ, this->near,
49
50     this->childNodes->push_back(new smash::Octree(this->left, middleX, middleY, this->bottom, middleZ, this->near,
51     this->childNodes->push_back(new smash::Octree(middleX, this->right, middleY, this->bottom, middleZ, this->near,
```

```
52 };
53
54 bool smash::Octree::hasAnyObjects() {
55     if (this->objects->size() > 0) {
56         return true;
57     }
58
59     for (std::vector<smash::Octree*>::iterator it = this->childNodes->begin(); it != this->childNodes->
60         if ((*it)->hasAnyObjects()) {
61             return true;
62         }
63     }
64     return false;
65 };
66
67
68 int smash::Octree::getTotalObjectCount() {
69     int count = this->objects->size();
70
71     for (std::vector<smash::Octree*>::iterator it = this->childNodes->begin(); it != this->childNodes->
72         count += (*it)->getTotalObjectCount();
73     }
74     return count;
75 };
76
77
78 int smash::Octree::getTotalTreeSize() {
79     int count = this->childNodes->size();
80     for (std::vector<smash::Octree*>::iterator it = this->childNodes->begin(); it != this->childNodes->
81         count += (*it)->getTotalTreeSize();
82     }
83     return count;
84 };
85
86
87
88 std::vector<int>* smash::Octree::getAllOffsets(float left, float right, float top, float bottom, float
89     float middleX = (this->left + this->right) / 2;
90     float middleY = (this->top + this->bottom) / 2;
91     float middleZ = (this->near + this->far) / 2;
92
93     float offset = 0;
94     bool bothX = false, bothY = false, bothZ = false;
95
96     if (left < middleX && right < middleX) {
97         offset += 0;
98     } else if (left > middleX && right > middleX) {
99         offset += 1;
100    } else {
101        bothX = true;
102    }
103
104    if (top < middleY && bottom < middleY) {
105        offset += 0;
106    } else if (top > middleY && bottom > middleY) {
107        offset += 2;
108    } else {
```

```

109     bothY = true;
110 }
111
112 if (near < middleZ && far < middleZ) {
113     offset += 0;
114 } else if (near > middleZ && far > middleZ) {
115     offset += 4;
116 } else {
117     bothZ = true;
118 }
119
120 std::vector<int>* allOffsets = new std::vector<int>;
121 allOffsets->push_back(offset);
122
123 if (bothZ) {
124     for (std::vector<int>::iterator it = allOffsets->begin(),
125          itEnd = allOffsets->end(); it != itEnd; it++) {
126         int n = *it;
127         allOffsets->push_back(n + 4);
128     }
129 }
130 if (bothY) {
131     for (std::vector<int>::iterator it = allOffsets->begin(),
132          itEnd = allOffsets->end(); it != itEnd; it++) {
133         int n = *it;
134         allOffsets->push_back(n + 2);
135     }
136 }
137 if (bothX) {
138     for (std::vector<int>::iterator it = allOffsets->begin(),
139          itEnd = allOffsets->end(); it != itEnd; it++) {
140         int n = *it;
141         allOffsets->push_back(n + 1);
142     }
143 }
144 /*
145 if (allOffsets->size() > 1) {
146     std::cout << "offsets ";
147     for (std::vector<int>::iterator it = allOffsets->begin(),
148          itEnd = allOffsets->end(); it != itEnd; it++) {
149         std::cout << *it << " ";
150     }
151     std::cout << std::endl;
152 }
153 return allOffsets;
154 };
155
156 bool smash::Octree::sphereLeft(smash::Sphere *sphere) {
157     return (sphere->positionX + sphere->radius < this->left ||
158            sphere->positionX - sphere->radius > this->right ||
159            sphere->positionY + sphere->radius < this->top ||
160            sphere->positionY - sphere->radius > this->bottom ||
161            sphere->positionZ + sphere->radius < this->near ||
162            sphere->positionZ - sphere->radius > this->far);
163 };
164
165

```

```

166 void smash::Octree::removeSphere(smash::Sphere *sphere) {
167     this->objects->erase(std::remove(this->objects->begin(), this->objects->end(), sphere));
168 }
169
170
171 void smash::Octree::addSphere(smash::Sphere *sphere) {
172     if (std::find(this->objects->begin(), this->objects->end(), sphere) !=
173         this->objects->end()) {
174         return; // this happens when sphere is re-added from two
175         // different nodes after removal.
176     }
177
178     float left = sphere->positionX - sphere->radius;
179     float right = sphere->positionX + sphere->radius;
180     float top = sphere->positionY - sphere->radius;
181     float bottom = sphere->positionY + sphere->radius;
182     float near = sphere->positionZ - sphere->radius;
183     float far = sphere->positionZ + sphere->radius;
184
185     if (this->maxDepth == 0 || this->objects->size() == 0) {
186         this->objects->push_back(sphere);
187     } else {
188         if (this->childNodes->size() == 0) {
189             this->split();
190         }
191         std::vector<int> *offsets = this->getAllOffsets(left, right, top, bottom, near, far);
192         for (std::vector<int>::iterator it = offsets->begin(); it != offsets->end(); it++) {
193             int offset = *it;
194             if (offset > 8) {
195                 // weird offset, investigate
196                 continue;
197             }
198             this->childNodes->at(offset)->addSphere(sphere);
199         }
200         offsets->clear();
201         delete offsets;
202     }
203 }

```

Listing B.16: Octree in C++

```

1 /**
2  * @fileoverview Sphere collision detection system.
3  * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 goog.provide('smash.SphereSystem2');
7
8 goog.require('smash.Octree');
9 goog.require('smash.Sphere');
10 goog.require('smash.flags');
11 goog.require('smash.math');
12
13
14

```

```
15  /**
16   * @constructor
17  */
18 smash.SphereSystem2 = function() {
19   var generalVelocity = 1;
20   /**
21    * @type {!Array.<!smash.Sphere>}
22   */
23   this.spheres = new Array(smash.SphereSystem2.SPHERES_COUNT);
24   for (var i = 0; i < smash.SphereSystem2.SPHERES_COUNT; i++) {
25     var sphere = new smash.Sphere();
26     sphere.positionX = (Math.random() - 0.5) * 400;
27     sphere.positionY = (Math.random() - 0.5) * 200;
28     sphere.positionZ = (Math.random() - 0.5) * 100;
29     sphere.velocityX = (Math.random() - 0.5) * generalVelocity;
30     sphere.velocityY = (Math.random() - 0.5) * generalVelocity;
31     sphere.velocityZ = (Math.random() - 0.5) * generalVelocity;
32     this.spheres[i] = sphere;
33   }
34
35   if (smash.flags.DRAWING_ENABLED) {
36     /**
37      * @type {!THREE.PerspectiveCamera}
38     */
39     this.camera = new THREE.PerspectiveCamera(20,
40       smash.SphereSystem2.CANVAS_WIDTH /
41         smash.SphereSystem2.CANVAS_HEIGHT,
42       1, 10000);
43     this.camera.position.z = 1000;
44
45     var controls = new THREE.OrbitControls(this.camera);
46     controls.addEventListener('change', goog.bind(function() {
47       this.renderer.render(this.scene, this.camera);
48     }, this));
49
50     /**
51      * @type {!THREE.Scene}
52     */
53     this.scene = new THREE.Scene();
54
55     var spotLight = new THREE.PointLight(0xffffffff);
56     spotLight.position.set(-40, 60, -10);
57     this.scene.add(spotLight);
58
59     var axes = new THREE.AxisHelper(20);
60     this.scene.add(axes);
61
62     var planeGeometry = new THREE.PlaneGeometry(
63       10000, 10000, 100, 100);
64     var planeMaterial = new THREE.MeshBasicMaterial({
65       color: 0xcccccc,
66       wireframe: true
67     });
68
69     var plane = new THREE.Mesh(planeGeometry, planeMaterial);
70     plane.rotation.x = -0.5 * Math.PI;
71     plane.position.x = 0;
```

```

72     plane.position.y = smash.SphereSystem2.FLOOR_LEVEL;
73     plane.position.z = 0;
74
75     this.scene.add(plane);
76
77
78
79     var material = new THREE.MeshLambertMaterial({
80         color: 0xff0000
81     });
82     /**
83      * @type {!Array.<!THREE.SphereGeometry>}
84      */
85     this.threeSpheres = new Array(smash.SphereSystem2.SPHERES_COUNT);
86     for (var i = 0; i < smash.SphereSystem2.SPHERES_COUNT; i++) {
87         var sphere = new THREE.SphereGeometry(this.spheres[i].radius, 10, 10);
88         var mesh = new THREE.Mesh(sphere, material);
89         mesh.position.x = this.spheres[i].positionX;
90         mesh.position.y = this.spheres[i].positionY;
91         mesh.position.z = this.spheres[i].positionZ;
92         this.threeSpheres[i] = mesh;
93
94         this.scene.add(mesh);
95     }
96
97
98
99     /**
100      * @type {!THREE.WebGLRenderer}
101      */
102     this.renderer = new THREE.WebGLRenderer();
103     this.renderer.setSize(smash.SphereSystem2.CANVAS_WIDTH,
104         smash.SphereSystem2.CANVAS_HEIGHT);
105     document.body.appendChild(this.renderer.domElement);
106     this.renderer.render(this.scene, this.camera);
107 }
108
109 /**
110  * @type {number}
111 */
112 this.collisions = 0;
113
114 /**
115  * @type {number}
116 */
117 this.collisionChecks = 0;
118
119 /**
120  * @type {smash.Octree}
121  * @private
122 */
123 this.octreeRoot_ = new smash.Octree(-1000, 1000, -1000, 1000,
124     -1000, 1000, smash.SphereSystem2.OCTREE_DEPTH);
125
126 for (var i = 0; i < smash.SphereSystem2.SPHERES_COUNT; i++) {
127     this.octreeRoot_.addSphere(this.spheres[i]);
128 }
```

```
129
130     if (smash.SphereSystem2.DRAWING_OCTREE_ENABLED) {
131         /**
132          * @type {Array}
133          * @private
134         */
135         this.octreeCubes_ = [];
136     }
137 };
138
139 /**
140  * @const {number}
141 */
142 smash.SphereSystem2.SPHERES_COUNT = 1000;
143
144
145 /**
146  * @const {boolean}
147 */
148 smash.SphereSystem2.DRAWING_OCTREE_ENABLED =
149     smash.flags.DRAWING_ENABLED && true;
150
151
152 /**
153  * @const {number}
154 */
155 smash.SphereSystem2.OCTREE_DEPTH = 5;
156
157
158 /**
159  * @const {boolean}
160 */
161 smash.SphereSystem2.GRAVITY_ENABLED = true;
162
163
164 /**
165  * @const {number}
166 */
167 smash.SphereSystem2.GRAVITY_FORCE = 0.1;
168
169
170 /**
171  * @const {number}
172 */
173 smash.SphereSystem2.FLOOR_LEVEL = -100;
174
175
176
177 /**
178  * (1 - energy lost on floor hit)
179  * @const {number}
180 */
181 smash.SphereSystem2.FLOOR_FRICTION = 0.8;
182
183
184 /**
185  * @const {number}
```

```

186  /*
187  smash.SphereSystem2.CANVAS_WIDTH = 1200;
188
189
190 /**
191 * @const {number}
192 */
193 smash.SphereSystem2.CANVAS_HEIGHT = 400;
194
195
196 /**
197 * @param {!smash.Sphere} sphere1
198 * @param {!smash.Sphere} sphere2
199 */
200 smash.SphereSystem2.collide = function(sphere1, sphere2) {
201   var distanceX = sphere1.positionX - sphere2.positionX;
202   var distanceY = sphere1.positionY - sphere2.positionY;
203   var distanceZ = sphere1.positionZ - sphere2.positionZ;
204   var distanceLength = smash.math.vectorLength(
205     distanceX, distanceY, distanceZ);
206   // normalize
207   distanceX /= distanceLength;
208   distanceY /= distanceLength;
209   distanceZ /= distanceLength;
210
211   var a1 = smash.math.dot(sphere1.velocityX, sphere1.velocityY,
212     sphere1.velocityZ, distanceX, distanceY, distanceZ);
213   var a2 = smash.math.dot(sphere2.velocityX, sphere2.velocityY,
214     sphere2.velocityZ, distanceX, distanceY, distanceZ);
215   var optimizedP = (2.0 * (a1 - a2)) / (sphere1.mass + sphere2.mass);
216
217   sphere1.velocityX -= optimizedP * sphere2.mass * distanceX;
218   sphere1.velocityY -= optimizedP * sphere2.mass * distanceY;
219   sphere1.velocityZ -= optimizedP * sphere2.mass * distanceZ;
220   sphere2.velocityX += optimizedP * sphere1.mass * distanceX;
221   sphere2.velocityY += optimizedP * sphere1.mass * distanceY;
222   sphere2.velocityZ += optimizedP * sphere1.mass * distanceZ;
223 };
224
225
226 /**
227 * @param {!smash.Sphere} sphere
228 */
229 smash.SphereSystem2.prototype.applyGravity = function(sphere) {
230   if (smash.SphereSystem2.GRAVITY_ENABLED) {
231     sphere.velocityY -= smash.SphereSystem2.GRAVITY_FORCE;
232   }
233 };
234
235
236 /**
237 * @param {!smash.Sphere} sphere
238 */
239 smash.SphereSystem2.prototype.applyFloor = function(sphere) {
240   if (sphere.positionY - sphere.radius <
241     smash.SphereSystem2.FLOOR_LEVEL) {
242     sphere.velocityY *= -smash.SphereSystem2.FLOOR_FRICTION;

```

```

243     }
244 };
245
246
247 /**
248 * @param {!smash.Octree} node
249 */
250 smash.SphereSystem2.prototype.addOctreeMesh = function(node) {
251   if (!node.debugMesh) {
252     var width = node.right - node.left;
253     var height = node.bottom - node.top;
254     var depth = node.far - node.near;
255     var geom = new THREE.CubeGeometry(width, height, depth);
256     geom.applyMatrix(
257       new THREE.Matrix4().makeTranslation(
258         node.left + width / 2,
259         node.top + height / 2,
260         node.near + depth / 2
261       )
262     );
263
264     node.debugMesh = new THREE.BoxHelper(new THREE.Mesh(geom));
265     this.octreeCubes_.push(node.debugMesh);
266
267     this.scene.add(node.debugMesh);
268   }
269
270   for (var i = 0; i < node.childNodes.length; i++) {
271     this.addOctreeMesh(node.childNodes[i]);
272   }
273 };
274
275
276 /**
277 * @param {!smash.Octree} node
278 * @private
279 */
280 smash.SphereSystem2.prototype.collideFromOctree_ = function(node) {
281   for (var i = 0; i < node.objects.length; i++) {
282     for (var j = 0; j < node.objects.length; j++) {
283       this.collisionChecks++;
284       if (i != j &&
285           smash.math.checkCollidingSpheres(
286             node.objects[i], node.objects[j])) {
287         this.collisions++;
288         smash.SphereSystem2.collide(
289           node.objects[i], node.objects[j]);
290       }
291     }
292   }
293   for (var i = 0; i < node.childNodes.length; i++) {
294     this.collideFromOctree_(node.childNodes[i]);
295   }
296 };
297
298
299 /**

```

```

300 * @param {!smash.Octree} node
301 * @private
302 */
303 smash.SphereSystem2.prototype.stepOctree_ = function(node) {
304   var removedSpheres = [];
305   for (var i = 0; i < node.objects.length; i++) {
306     var sphere = node.objects[i];
307     if (node.sphereLeft(sphere)) {
308       node.removeSphere(sphere);
309       removedSpheres.push(sphere);
310     }
311   }
312
313   for (var i = 0; i < node.childNodes.length; i++) {
314     this.stepOctree_(node.childNodes[i]);
315   }
316
317   if (node !== this.octreeRoot_) {
318     for (var i = 0; i < removedSpheres.length; i++) {
319       this.octreeRoot_.addSphere(removedSpheres[i]);
320     }
321   }
322
323   if (!node.hasAnyObjects()) {
324     if (smash.SphereSystem2.DRAWING_OCTREE_ENABLED) {
325       for (var i = 0; i < node.childNodes.length; i++) {
326         this.scene.remove(node.childNodes[i].debugMesh);
327       }
328     }
329     node.childNodes.length = 0;
330   }
331 };
332
333
334 /**
335 *
336 */
337 smash.SphereSystem2.prototype.step = function() {
338   this.stepOctree_(this.octreeRoot_);
339   this.collideFromOctree_(this.octreeRoot_);
340
341   for (var i = 0; i < smash.SphereSystem2.SPHERES_COUNT; i++) {
342     this.applyGravity(this.spheres[i]);
343     this.applyFloor(this.spheres[i]);
344
345     this.spheres[i].step(1);
346
347
348     if (smash.flags.DRAWING_ENABLED) {
349       this.threeSpheres[i].position.x = this.spheres[i].positionX;
350       this.threeSpheres[i].position.y = this.spheres[i].positionY;
351       this.threeSpheres[i].position.z = this.spheres[i].positionZ;
352     }
353   }
354
355   if (smash.SphereSystem2.DRAWING_OCTREE_ENABLED) {
356     this.addOctreeMesh(this.octreeRoot_);

```

```

357     }
358
359     if (smash.flags.DRAWING_ENABLED) {
360         this.renderer.render(this.scene, this.camera);
361     }
362 };

```

Listing B.17: Octree-based sphere system object in JavaScript

```

1 /**
2 * @fileoverview Sphere collision detection system.
3 * @author sebastian.poreba@gmail.com (Sebastian Poreba)
4 */
5
6 #include "sphereSystem2.h"
7
8 smash::SphereSystem2::SphereSystem2() {
9     this->spheres = new std::vector<smash::Sphere*>;
10    collisions = 0;
11    collisionChecks = 0;
12
13    octreeRoot = new smash::Octree(-1000, 1000, -1000, 1000,
14        -1000, 1000, smash::SphereSystem2::OCTREE_DEPTH);
15
16    float generalVelocity = 1;
17    for (int i = 0; i < smash::SphereSystem2::SPHERES_COUNT; i++) {
18        smash::Sphere* sphere = new smash::Sphere();
19        sphere->positionX = (((float) rand() / (RAND_MAX)) - 0.5) * 400;
20        sphere->positionY = (((float) rand() / (RAND_MAX)) - 0.5) * 200;
21        sphere->positionZ = (((float) rand() / (RAND_MAX)) - 0.5) * 100;
22        sphere->velocityX = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
23        sphere->velocityY = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
24        sphere->velocityZ = (((float) rand() / (RAND_MAX)) - 0.5) * generalVelocity;
25        this->spheres->push_back(sphere);
26        this->octreeRoot->addSphere(sphere);
27    }
28}
29
30
31 smash::SphereSystem2::~SphereSystem2() {
32     this->spheres->clear();
33     delete this->spheres;
34     delete this->octreeRoot;
35 }
36
37
38 /**
39 * @param {smash::Sphere*} sphere1
40 * @param {smash::Sphere*} sphere2
41 */
42 void smash::SphereSystem2::collide(smash::Sphere* sphere1, smash::Sphere* sphere2) {
43     float distanceX = sphere1->positionX - sphere2->positionX;
44     float distanceY = sphere1->positionY - sphere2->positionY;
45     float distanceZ = sphere1->positionZ - sphere2->positionZ;
46     float distanceLength = smash::math::vectorLength(

```

```

47     distanceX, distanceY, distanceZ);
48
49 // normalize
50 distanceX /= distanceLength;
51 distanceY /= distanceLength;
52 distanceZ /= distanceLength;
53
54 float a1 = smash::math::dot(sphere1->velocityX, sphere1->velocityY, sphere1->velocityZ,
55     distanceX, distanceY, distanceZ);
56 float a2 = smash::math::dot(sphere2->velocityX, sphere2->velocityY, sphere2->velocityZ,
57     distanceX, distanceY, distanceZ);
58 float optimizedP = (2.0 * (a1 - a2)) / (sphere1->mass + sphere2->mass);
59
60 sphere1->velocityX -= optimizedP * sphere2->mass * distanceX;
61 sphere1->velocityY -= optimizedP * sphere2->mass * distanceY;
62 sphere1->velocityZ -= optimizedP * sphere2->mass * distanceZ;
63 sphere2->velocityX += optimizedP * sphere1->mass * distanceX;
64 sphere2->velocityY += optimizedP * sphere1->mass * distanceY;
65 sphere2->velocityZ += optimizedP * sphere1->mass * distanceZ;
66 };
67
68
69 void smash::SphereSystem2::applyGravity(smash::Sphere* sphere) {
70     if (smash::SphereSystem2::GRAVITY_ENABLED) {
71         sphere->velocityY -= smash::SphereSystem2::GRAVITY_FORCE;
72     }
73 };
74
75
76 void smash::SphereSystem2::applyFloor(smash::Sphere* sphere) {
77     if (sphere->positionY - sphere->radius <
78         smash::SphereSystem2::FLOOR_LEVEL) {
79         sphere->velocityY *= -smash::SphereSystem2::FLOOR_FRICTION;
80     }
81 };
82
83
84 void smash::SphereSystem2::collideFromOctree(smash::Octree *node) {
85     for (std::vector<smash::Sphere*>::iterator it = node->objects->begin(); it != node->objects->end();
86         for (std::vector<smash::Sphere*>::iterator it2 = node->objects->begin(); it2 != node->objects->end();
87             this->collisionChecks++;
88             smash::Sphere* s = *it;
89             smash::Sphere* s2 = *it2;
90             if (s != s2 &&
91                 smash::math::checkCollidingSpheres(s, s2)) {
92                 this->collisions++;
93                 smash::SphereSystem2::collide(s, s2);
94             }
95         }
96     }
97     for (std::vector<smash::Octree*>::iterator it = node->childNodes->begin(); it != node->childNodes->end();
98         this->collideFromOctree(*it);
99     }
100 };
101
102 void smash::SphereSystem2::stepOctree(smash::Octree *node) {
103     std::vector<smash::Sphere*> removedSpheres;

```

```

104
105     for (std::vector<smash::Sphere*>::iterator it = node->objects->begin(); it != node->objects->end();)
106         smash::Sphere* s = *it;
107         if (node->sphereLeft(s)) {
108             removedSpheres.push_back(s);
109             it = node->objects->erase(it);
110             if (s == *it) {
111                 break; // last element removal
112             }
113         }
114     }
115
116     for (std::vector<smash::Octree*>::iterator it = node->childNodes->begin(); it != node->childNodes->
117         this->stepOctree(*it);
118     }
119
120     if (node != this->octreeRoot) {
121         for (std::vector<smash::Sphere*>::iterator it = removedSpheres.begin(); it != removedSpheres.end();
122             this->octreeRoot->addSphere(*it);
123         }
124     }
125
126     if (!node->hasAnyObjects()) {
127         for (std::vector<smash::Octree*>::iterator it = node->childNodes->begin(); it != node->childNodes->
128             delete *it;
129         }
130         node->childNodes->clear();
131     }
132 };
133
134
135 void smash::SphereSystem2::step() {
136     this->stepOctree(this->octreeRoot);
137     this->collideFromOctree(this->octreeRoot);
138     for (std::vector<smash::Sphere*>::iterator it = this->spheres->begin(); it != this->spheres->end();
139         smash::Sphere* s = *it;
140         applyGravity(s);
141         applyFloor(s);
142         s->step(1);
143     }
144 };

```

Listing B.18: Octree-based sphere system in C++

## Bibliografia

- [1] Gartner says worldwide pc, tablet and mobile phone combined shipments to reach 2.4 billion units in 2013.
- [2] Gta v dev costs over \$137 million, says analyst.
- [3] Pool hall lessons: Fast, accurate collision detection between circles or spheres.
- [4] V8 documentation.
- [5] M. Ager. Google i/o 2009 – v8: High performance javascript engine. 2009.
- [6] casualconnect.org. Social network games 2012 casual games sector report. 2013.
- [7] D. Clifford. Google i/o 2012 – breaking the javascript speed limit with v8. 2012.
- [8] J. Conrod. A tour of v8: full compiler.
- [9] D. Crockford. *JavaScript: The Good Parts*. O'Reilly, 2008.
- [10] J. Dalziel. The race for speed series.
- [11] V. Egorov. Series of articles on v8.
- [12] V. Egorov. Understanding v8. 2011.
- [13] C. Ericson. *Real-Time Collision Detection*. CRC Press, 2004.
- [14] F. Loitsch. Optimizing fo v8 series.
- [15] I. Millington. *Game physics engine development*. CRC Press, 2010.
- [16] J. Resig. Asm.js: The javascript compile target.
- [17] L. Thompson. Gdc 2012: From console to chrome. 2012.
- [18] G. Trefry. *Casual Game Design: Designing Play for the Gamer in ALL of Us*. CRC Press, 2010.
- [19] V. Vukicevic. Javascript developers conference taiwan 2013 – high performance games and more in javascript with asm.js. 2013.
- [20] A. Wingo. Series of articles on v8.
- [21] N. C. Zakas. *High Performance JavaScript*. O'Reilly, 2010.