

<p>Steps Performed</p>	<p>Based on results from 2-0 the following steps where performed:</p> <ol style="list-style-type: none"> 1. XSL Transformation from original base XML to value SQL entries. The following 3 XSL sheets where used to create the integer and string value tables: <ol style="list-style-type: none"> a. 1 createDBValueTables.xsl: to create a flat list of values from the XML using attribute values and text node values. Using the generate-id function in XSL, IDs for each node are assigned. OUTPUT: value_output_step1_pretty.xml b. 1a createUniqueDBValueTables.xsl: to eliminate duplicates in the result from a), keys are introduced OUTPUT: value_output_step2_pretty.xml c. 1b createUniqueDB_INSERTINTO.xsl Based on the output of b) the respective INSERT INTO statements are created. OUTPUT: importSQLValueTables.sql https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%2021%20XML2RDBMS/importSQLValueTables.sql d. Execution of the SQL statement in DB2. Necessary DROP/CREATE statements are available at the beginning of the script, written in step c. <p>All transformations and formatting are performed using xsltproc and xmllint statements.</p> 2. Based on the results of 1) the actual EDGE table is created using 2 createDBFromXML.xsl, the hierarchy is transformed into the necessary INSERT INTO statements (as bulk) and for values a matching to the results of b) is performed using the document() function in XSL. As a clean-up action, the SQL statement is manually modified to allow import (since 90.000 lines as bulk is too large). OUTPUT: importSQLEdgeTable.sql https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%2021%20XML2RDBMS/importSQLEdgeTable.sql
----------------------------	---

[illegible]

DEV ENVIRONMENT:
<https://github.com/fridlutz/UNIVIE/tree/master/INTERROP/Session%202021%20XML2RDBMS>

Aufgabe 2-1b 1: SQL Query:

Die am längsten pro Einheit dauernde(n) Lehrveranstaltungen(n) (Stunden, Gruppe, LV-Leiter)

Steps Performed	<p>Since it is not clear what the query means semantically, the following assumptions have been made:</p> <ul style="list-style-type: none"> a) Query the course that has the longest appointment/lecture in the set of lectures b) Since for the dataset, no further information on the group is available (only single group courses are offered), the group information is not considered, since similar as with the other attributes. c) Stunden: the weekhours of the course are returned d) LV-Leiter: since multiple "Leiter" (in role of V_Verantwortlich) are possible, all lecturers are returned, resulting in duplicate entries (in case a course has 2 lecturers)
-----------------	--

Solution

```

SELECT DISTINCT COURSEIDATTRVAL.INTEGERVALUE AS COURSEID,
                DURATION_MINATTR.INTEGERVALUE AS MAXAPPOINTMENTMIN,
                COURSENAMEVAL.STRINGVALUE AS COURSETITLE,
                COURSEWEEKHOURS.INTEGERVALUE AS COURSEWEEKHOURS,
                LECTURERNAMEVAL.STRINGVALUE AS LECTURERNAME

FROM EDGETABLE COURSE,
     EDGETABLE GROUP,
     EDGETABLE APPOINTMENT,
     EDGETABLE LECTURER,
     EDGETABLE LECTURERNAMEATTR,
     EDGETABLE DURATION,
     EDGETABLE COURSEIDATTR,
     EDGETABLE COURSENAMEATTR,
     EDGETABLE COURSEWEEKHOURSATTR,
     EDGEVALUE_TABLE_INT DURATION_MINATTR,
     EDGEVALUE_TABLE_INT COURSEIDATTRVAL,
     EDGEVALUE_TABLE_INT COURSEWEEKHOURS,
     EDGEVALUE_TABLE_STRING COURSENAMEVAL,
     EDGEVALUE_TABLE_STRING LECTURERNAMEVAL

WHERE
    -- get only starting from course tag
    COURSE.EDGENAME = 'course'
    -- join in the attribute @id
    AND COURSE.TARGETID = COURSEIDATTR.SOURCEID
    AND COURSEIDATTR.TARGETID = COURSEIDATTRVAL.INTEGERVALUEID
    AND COURSEIDATTR.EDGENAME = '@id'
    -- join in the attribute @title
    AND COURSE.TARGETID = COURSENAMEATTR.SOURCEID
    AND COURSENAMEATTR.TARGETID = COURSENAMEVAL.STRINGVALUEID
    AND COURSENAMEATTR.EDGENAME = '@title'
    -- join in the attribute @weekhours
    AND COURSE.TARGETID = COURSEWEEKHOURSATTR.SOURCEID
    AND COURSEWEEKHOURSATTR.TARGETID =
    COURSEWEEKHOURS.INTEGERVALUEID
    AND COURSEWEEKHOURSATTR.EDGENAME = '@weekhours'
    -- join in the group tag
    AND COURSE.TARGETID = GROUP.SOURCEID
    AND GROUP.EDGENAME = 'group'
    -- join in the appointment
    AND GROUP.TARGETID = APPOINTMENT.SOURCEID
    AND APPOINTMENT.EDGENAME = 'appointment'
    -- join in the attribute @duration_min
    AND APPOINTMENT.TARGETID = DURATION.SOURCEID
  
```

	<pre> AND DURATION.EDGENAME = '@duration_min' AND DURATION.TARGETID = DURATION_MINATTR.INTEGERVALUEID AND DURATION_MINATTR.INTEGERVALUE = (-- subquery to get the max value for the duration of an appointment SELECT MAX(EDGEVALUE_TABLE_INT.INTEGERVALUE) FROM EDGETABLE INNER JOIN EDGEVALUE_TABLE_INT ON EDGETABLE.TARGETID = EDGEVALUE_TABLE_INT.INTEGERVALUEID WHERE EDGETABLE.EDGENAME = '@duration_min') -- join in the lecturer AND GROUP.TARGETID = LECTURER.SOURCEID AND LECTURER.EDGENAME = 'lecturer' -- join in the attribute @name AND LECTURER.TARGETID = LECTURERNAMEATTR.SOURCEID AND LECTURERNAMEATTR.EDGENAME = '@name' AND LECTURERNAMEATTR.TARGETID = LECTURERNAMEVAL.STRINGVALUEID ; </pre>
Result	<p>The max length for of appointments in the basexml is 615min. 2 courses match, details below.</p> <p>COURSEID: 70197 MAXAPPOINTMENTMIN: 615 COURSETITLE: Cultural history: Practice of methods in cultural history primary sources COURSEWEEKHOURS: 20 LECTURERNAME: Diesenberger AND Schmale</p> <p>COURSEID: 70280 MAXAPPOINTMENTMIN: 615 COURSETITLE: Workshop - Practicing Digital Methods in Historical Research COURSEWEEKHOURS: 20 LECTURERNAME: König</p>
Source Files	<p>DEV ENVIRONMENT: https://github.com/fridlutz/UNIVIE/tree/master/INTERROP/Session%202/1%20XML2RDBMS</p> <p>SQL: https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_1%20SQL%20SELECT%20STATEMENT.sql</p> <p>ResultSet (TXT): https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_1%20RESULTSET.txt</p>

Aufgabe 2-1b 2: SQL Query:

Die am längsten pro Semester dauernde(n) Lehrveranstaltungen(n) (Stunden, Gruppe, LV-Leiter)

Steps Performed	<p>Since it is not clear what the query means semantically, the following assumptions have been made:</p> <ul style="list-style-type: none"> a) Query the course that has the longest overall durations (summed up) b) Group information, see above. c) Stunden: the weekhours of the course are returned d) LV-Leiter: since multiple "Leiter" (in role of V_Verantwortlich) are possible, all lecturers are returned, resulting in duplicate entries (in case a course has 2 lecturers)
-----------------	---

Solution	<pre> SELECT DISTINCT COURSEIDATTRVAL.INTEGERVALUE AS COURSEID, DURATION_MINATTR.INTEGERVALUE AS MAXAPPOINTMENTMIN, COURSENAMEVAL.STRINGVALUE AS COURSETITLE, COURSEWEEKHOURS.INTEGERVALUE AS COURSEWEEKHOURS, LECTURERNAMEVAL.STRINGVALUE AS LECTURERNAME FROM EDGETABLE COURSE, EDGETABLE GROUP, EDGETABLE LECTURER, EDGETABLE LECTURERNAMEATTR, EDGETABLE DURATION, EDGETABLE COURSEIDATTR, EDGETABLE COURSENAMEATTR, EDGETABLE COURSEWEEKHOURSATTR, EDGEVALUE_TABLE_INT DURATION_MINATTR, EDGEVALUE_TABLE_INT COURSEIDATTRVAL, EDGEVALUE_TABLE_INT COURSEWEEKHOURS, EDGEVALUE_TABLE_STRING COURSENAMEVAL, EDGEVALUE_TABLE_STRING LECTURERNAMEVAL WHERE -- get only starting from course tag COURSE.EDGENAME = 'course' -- join in the attribute @id AND COURSE.TARGETID = COURSEIDATTR.SOURCEID AND COURSEIDATTR.TARGETID = COURSEIDATTRVAL.INTEGERVALUEID AND COURSEIDATTR.EDGENAME = '@id' -- join in the attribute @title AND COURSE.TARGETID = COURSENAMEATTR.SOURCEID AND COURSENAMEATTR.TARGETID = COURSENAMEVAL.STRINGVALUEID AND COURSENAMEATTR.EDGENAME = '@title' -- join in the attribute @weekhours AND COURSE.TARGETID = COURSEWEEKHOURSATTR.SOURCEID AND COURSEWEEKHOURSATTR.TARGETID = COURSEWEEKHOURS.INTEGERVALUEID AND COURSEWEEKHOURSATTR.EDGENAME = '@weekhours' -- join in the group tag AND COURSE.TARGETID = GROUP.SOURCEID AND GROUP.EDGENAME = 'group' -- join in the attribute @duration_min_sum AND GROUP.TARGETID = DURATION.SOURCEID AND DURATION.EDGENAME = '@duration_min_sum' AND DURATION.TARGETID = DURATION_MINATTR.INTEGERVALUEID AND DURATION_MINATTR.INTEGERVALUE = (-- subquery to get the max value for the duration of an appointment SELECT MAX(EDGEVALUE_TABLE_INT.INTEGERVALUE) FROM EDGETABLE </pre>
----------	--

	<pre> INNER JOIN EDGEVALUE_TABLE_INT ON EDGETABLE.TARGETID = EDGEVALUE_TABLE_INT.INTEGERVALUEID WHERE EDGETABLE.EDGENAME = '@duration_min_sum') -- join in the lecturer AND GROUP.TARGETID = LECTURER.SOURCEID AND LECTURER.EDGENAME = 'lecturer' -- join in the attribute @name AND LECTURER.TARGETID = LECTURERNAMEATTR.SOURCEID AND LECTURERNAMEATTR.EDGENAME = '@name' AND LECTURERNAMEATTR.TARGETID = LECTURERNAMEVAL.STRINGVALUEID ; </pre>
Result	<p>The max length for of appointments in the basexml is 4680min (this is the sum of all appointments). 1 course matches, details below.</p> <p>COURSEID: 70240 MAXCOURSEMIN: 4680 COURSETITLE: Diplomats and Chronology COURSEWEEKHOURS: 60 LECTURERNAME: Lackner, Schwarcz, Scharer</p>
Source Files	<p>DEV ENVIRONMENT: https://github.com/fridlutz/UNIVIE/tree/master/INTERROP/Session%202/1%20XML2RDBMS SQL: https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_2%20SQL%20SELECT%20STATEMENT.sql ResultSet (TXT): https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_2%20RESULTSET.txt</p>

Aufgabe 2-1b 3: SQL Query:

Alle nach 18 Uhr stattfindenden LVs, die pruefungsimmanent sind, und nur einen LV-Leiter haben.

Steps Performed Since no specific information is requested, the left join needed to also show all other values as above is skipped.

Solution

```

SELECT COURSEID, COUNT(COURSEID) AS LECTURERCOUNT FROM (

SELECT DISTINCT COURSEIDATTRVAL.INTEGERVALUE AS COURSEID,
                STARTATTR.INTEGERVALUE AS STARTTIME,
                COURSENAMEVAL.STRINGVALUE AS COURSETITLE,
                ASSESSMENTATTRVAL.STRINGVALUE AS ASSESSMENTTYPE,
                COURSEWEEKHOURS.INTEGERVALUE AS COURSEWEEKHOURS,
                LECTURERNAMEVAL.STRINGVALUE AS LECTURERNAME

FROM EDGETABLE COURSE,
     EDGETABLE GROUP,
     EDGETABLE APPOINTMENT,
     EDGETABLE LECTURER,
     EDGETABLE LECTURERNAMEATTR,
     EDGETABLE START,
     EDGETABLE COURSEIDATTR,
     EDGETABLE COURSENAMEATTR,
     EDGETABLE ASSESSMENTATTR,
     EDGETABLE COURSEWEEKHOURSATTR,
     EDGEVALUE_TABLE_INT STARTATTR,
     EDGEVALUE_TABLE_INT COURSEIDATTRVAL,
     EDGEVALUE_TABLE_INT COURSEWEEKHOURS,
     EDGEVALUE_TABLE_STRING COURSENAMEVAL,
     EDGEVALUE_TABLE_STRING ASSESSMENTATTRVAL,
     EDGEVALUE_TABLE_STRING LECTURERNAMEVAL

WHERE
    -- get only starting from course tag
    COURSE.EDGENAME = 'course'
    -- join in the attribute @id
    AND COURSE.TARGETID = COURSEIDATTR.SOURCEID
    AND COURSEIDATTR.TARGETID = COURSEIDATTRVAL.INTEGERVALUEID
    AND COURSEIDATTR.EDGENAME = '@id'
    -- join in the attribute @title
    AND COURSE.TARGETID = COURSENAMEATTR.SOURCEID
    AND COURSENAMEATTR.TARGETID = COURSENAMEVAL.STRINGVALUEID
    AND COURSENAMEATTR.EDGENAME = '@title'
    -- join in the attribute @continuousassessment
    AND COURSE.TARGETID = ASSESSMENTATTR.SOURCEID
    AND ASSESSMENTATTR.TARGETID = ASSESSMENTATTRVAL.STRINGVALUEID
    AND ASSESSMENTATTR.EDGENAME = '@continuousassessment'
    AND ASSESSMENTATTRVAL.STRINGVALUE = 'Yes'

    -- join in the attribute @weekhours
    AND COURSE.TARGETID = COURSEWEEKHOURSATTR.SOURCEID
    AND COURSEWEEKHOURSATTR.TARGETID =
    COURSEWEEKHOURS.INTEGERVALUEID
    AND COURSEWEEKHOURSATTR.EDGENAME = '@weekhours'
    -- join in the group tag
    AND COURSE.TARGETID = GROUP.SOURCEID

```

	<pre> AND GROUP.EDGENAME = 'group' -- join in the appointment AND GROUP.TARGETID = APPOINTMENT.SOURCEID AND APPOINTMENT.EDGENAME = 'appointment' -- join in the attribute @START_min AND APPOINTMENT.TARGETID = START.SOURCEID AND START.EDGENAME = '@start' AND START.TARGETID = STARTATTR.INTEGERVALUEID -- only get those that start later then 18:00 AND STARTATTR.INTEGERVALUE > 1800 -- join in the lecturer AND GROUP.TARGETID = LECTURER.SOURCEID AND LECTURER.EDGENAME = 'lecturer' -- join in the attribute @name AND LECTURER.TARGETID = LECTURERNAMEATTR.SOURCEID AND LECTURERNAMEATTR.EDGENAME = '@name' AND LECTURERNAMEATTR.TARGETID = LECTURERNAMEVAL.STRINGVALUEID) GROUP BY COURSEID HAVING COUNT(COURSEID) = 1 ; </pre>
Result	<p>3 courses match the above request:</p> <p>COURSEID: 70068 COURSEID: 70086 COURSEID: 70117</p>
Source Files	<p>DEV ENVIRONMENT: https://github.com/fridlutz/UNIVIE/tree/master/INTERROP/Session%202/1%20XML2RDBMS</p> <p>SQL: https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_3%20SQL%20SELECT%20STATEMENT.sql</p> <p>ResultSet (TXT): https://github.com/fridlutz/UNIVIE/blob/master/INTERROP/Session%202/1%20XML2RDBMS/2_1b_3%20RESULTSET.txt</p>