

**Concept for an mobile assisting system for field engineers by the
example of structural health monitoring**

EXPOSE: Master Thesis Euteneuer

Technical University of Berlin

Institute for Geodesy and Geoinformation Science

Chair of Geoinformation Technology

supervised by:

Prof. Frank Neitzel

Thomas Becker

by

Frieder H. Euteneuer

Berlin, August 7, 2013

Contents

List of Figures

1

List of Tables

1

1 Introduction and Motivation

1

2 Methods

2

2.1 Feature Extraction

2

2.2 Complex Data

2

2.3 Time Series

3

2.4 Data Streaming

3

2.5 Data Analysis

3

3 relevant studies

4

4 Expected Results

4

5 Expected Problems

4

akmalisire

1 Introduction and Motivation

This master thesis will first describe potential user needs in a graphical management and analysis tool for the structural health monitoring and secondly develop a system which will meet the described needs. This system will help field engineers in:

- planning their field work,
- correspond with the office,
- and quickly evaluate measured values.

Classical work in survey engineering consist of the measuring tasks in the field, and its evaluation, analysis and correction in the office. This subdivision into two spatially different, but often very cooperating tasks leads to inefficiency of the work, time delay and avoidable mistakes in the procedures. *work flow*

For the sake of completeness, however, it should also be pointed out that not all working tasks of field engineers can be done in the field, therewith the system is limited to this existing frame. Nowadays a close interaction of different activities every time and everywhere is not any more a vision, it is common to our society and people get used to it. Field work today already contains usages of mobile devices which help organising the work flow.

There are three main advantages of using such a system following this approach:

- The Systems core functionality will be the assistance of the ~~measurement~~ *survey* engineer. This means it helps with 'understanding' the measurements e.g. in comparison to former epochs. → The sharing of information between field and office leads to a better knowledge in field. *to get a better*
- It is avoiding "mis-measurements" caused due to an incomplete knowledge of the measurement network by validation of measurement "on the fly" directly after the upload to the systems database.
- For a field exploration existing results of the former measures have not to be exported from the office infrastructure, the mobile system is linking real time data with existing results.

There is a need of such a system, the combination of used techniques like "Sensor Web Enablement", OGCs Web Services and mobile advanced IT platforms like tablet computers for a streaming of data from the field to the field is up to now an unanswered question. This master thesis will explore possible solutions and the real need of potential users.

It will not be an alternative for engineering management systems which are already running on

classical survey

sensor observation

new possibilities = field work?

mobile devices, the real benefit of this system being designed with this thesis will be a direct linkage of the sensors to the systems, from data streaming up to augmented reality.

2 Methods

Based on existing developments like IT-Architectures and Data-formats the system will be formed by the actual need of working field engineers. Use case models and research on already existing systems will help in finding a technically and financially optimal solution.

Main questions on the concept will be:

- Which Sensors will be linked, and what kind of data will be used (in case of e.g. interval)?
- How will the data be transferred (from the sensors to the office and to the mobile device), and where will they be stored?
- How will the graphical user interface be structured and designed?
- What kind of it-architecture and which protocols will be used?

To find a working and operationally usable solution following problems and concepts have to been reviewed, discussed and evaluated:

2.1 Feature Extraction

When talking about an structural health monitoring system, the data of different kind of sensors are part of the evaluation calculations. The System has to be able to access the Sensors and to translate the data in to machine readable and understandable information. The data of e.g. a terrestrial laser scanner is a point cloud which is unique in each epoch. Therewith the relevant absolute information have to be extracted, mostly in this case geometrical features. The RANdom Sample Consensus (RANSAC) approach has been turned out as one feasible solution for the extraction of geometric Features [11]. And for the recognition of semantic features there are existing different approaches e.g. [10][4].

but he use (Schubert, 2010)

just valid for TLS

what about the rest?

2.2 Complex Data

The used database then has to be able to store those different kind of data: Starting with point clouds from terrestrial laser scanners up to feature models of the observed structure. And also the raw material might be important for future scientific work, therewith maybe also pictures have to be stored. Projects like the German Indonesian Tsunami Early Warning System have already developed examples for databases storing complex data [12].

2.3 Time Series

Second problem in case of the database will be the storage of time-series of the data. Monitoring means changes of values in comparison to former epochs. In our case most changing values are spatial information, and therewith the problem describes the storage of moving objects in a database. Several approaches exist dealing with this problem, first: For every change of one parameter a full snapshot of all data will be stored in the database but this would lead to a big amount of data. Second: Only the changed parameter will be stored, but then the relationship model of the database entities and therewith the managing system will become very complex. [2][7][14]

2.4 Data Streaming

The System then has to be able to stream and visualise the data on a certain platform. Webservices might be the actually best solution and they fit to the trend offering software as a service. The service oriented Architecture paradigm described in [?] describes the method how to serve the relevant information without having a monolithic static system. With geometric data, as for example geometric primitives, the encoding of the data in CityGML [3][6] would be the best solution. With the help of Services defined by the Open Geospatial Consortium (OGC) like for example the Web Feature Service [8] [5][1][9][13] the related data could be visualised.

2.5 Data Analysis

Not as a central part of this master thesis but at least partially the analysis of the used data should be described. The development of appropriate algorithms might not be a task, but the way how to integrate them into the structure. The Finite Element Method (FEM see e.g. [15]) should be mentioned here as an example relevant analysis tool.

3 relevant studies

4 Expected Results

As an overall output an demonstrating prototype of the system will be developed based on one concrete example. Most open questions will in the end be answered and evaluated, based on the developed prototype.

The demonstrating example will contain data from different sensors like Levelling Instruments, Total Stations and possibly also data from Accelerometers and other permanent observation sensors or Terrestrial Laser Scanners.

The data will be transferred to and central database in such a quality and short interval that a direct an continuous observation of changes in the measurements on a mobile device can be done. On the structural health monitoring test side for this prototype, experiments should be part of the evaluation of the developed system. Such like observation of loading test on the monitored construction (e.g. a bridge).

Changes in the measured data should be illustrated in a practicable way. An interpretation of numeric results by the user is not an option. Better would be a graphical symbolisation of changes and it pre-evaluation. What kind and which statistical interpretation of the measurements will be part of the algorithms will not be part of the development of this prototype and should be offered by the partnered scientists or parallel master thesis. This master thesis will simply develop the technological structure as a basis for any implementation of adjustment and statistical evaluation algorithms.

5 Expected Problems

With the implementation but also with the theoretical questions several problems could occur. First of all and biggest problem would be if there are no data for any testing available. Either due to the fact that there is not appropriate project taking place or because of data-rights problems. If there is a fitting project willing to provide its data, the used sensors might not be able to connect to the Web, and therewith one important part of the developed System cannot be tested or even worse not been developed.

For the streaming aspect of the System it is important that the used data are small enough for a

data
as for
used from
16h shifts project

What about GML-creativity?

time efficient sending via the web. In case of e.g. raw-data from TLS this would not be the case.

Since the full system is depending on a database which should be given by previous work, one big problem could occur when the design of the database is inefficient for the planned tasks, or when the design is covering the full bandwidth of data the System is going to handle.

In the end the system will run on mobile devices. Up to now there have been three platforms established on the Smartphone and Tablet-PC marked: Googles Android, Apples iOS and Microsofts Windows. The development in context of this master thesis will at the most consider only on of these operating systems as a testing platform. The problem here would be a incompatibility to some existing platforms.