- $Discuss\ VPU/TPU/APU/GPU/FPGA/ASIC\ memory\ arcitecture\ and\ how\ it\ handles\ matrix\ sparsity$
- Show ineffectivity of pruning on hardware without optimisations for sparse matrices

0.0.1 Memory Allocation




Figure 1: vDNN performance, showing the throughput using various memory allocation strategies. (Adopted figure from [1])

While designed specifically for training networks that would otherwise be to large for a GPU, the memory manager vDNN proposed by Rhu et al [1] does provide some insight into the importance of memory locality to neural network throughput. Fig. 1 summarizes the performance of neural networks using vDNN to manage memory compared to a baseline memory management policy (base). The vDNN policies include: static policies (denoted as all and conv) and a dynamic policy (dyn). base simply loads the full model into the GPU memory, consequently providing optimal memory locality. all refers to a policy of moving all Xs out of GPU memory, and conv only offloads Xs from convolutional layers, Xs are the input matrices to each layer, denoted by the red arrows in Fig. 2. Each of base, conv and all are evaluated using two distinct convolutional algorithms - memory-optimal (m) and performance-optimal (p). Finally the dyn allocation policy chooses (m) and (p) dynamically at runtime.

Observing the results in Fig. 1 a significant (58% and 55%) performance loss is evident compared to baseline, this loss is caused because no effort is made to optimise location of network parameters in memory. In this example the memory locality is compared between memory in the GPU (VRAM) and host memory (DRAM) accessed via the PCI lanes.




Figure 2: Memory allocations required for linear networks. All green (W) and red (X) arrows are allocated during inference, the blue and yellow arrows are allocated during training. (Adopted figure from [1])

Justifies the need for compression ... pruning

0.0.2 Memory Access




Figure 3: Complexity distribution of CNN models (Adopted figure from [2])

A significant portion of DNN computation is matrix-vector multiplication, ideally weight reuse techniques can speed up these operations. However some DNNs feature FC layers with more than a hundred million weights (Fig. 3), memory bandwidth here can be an issue since loading these weights can be a significant bottleneck [2]. When the cache capacity is insufficient to store the weight matrix this bottleneck is expounded, causing memory accesses for every operation since the weight matrix cannot be reused [3]. As observed in Section 0.0.1 this indicates that compression techniques should help alliviate this bottleneck by making more parameters avaliable for cache reuse. The paper proposing EIE (an inference engine for compressed networks [3]) shows that while compression does reduce the total number of operations, the irregular memory access patterns required when accessing sparse matrices mitigates improvements in inference performance, see Fig. 4.

Platform	Batch	Matrix	AlexNet			VGG16			NT-		
	Size	Type	FC6	FC7	FC8	FC6	FC7	FC8	We	Wd	LSTM
CPU (Core i7-5930k) GPU (Titan X)	1	dense	7516.2	6187.1	1134.9	35022.8	5372.8	774.2	605.0	1361.4	470.5
	64	sparse	3066.5	1282.1	890.5	3774.3	545.1	777.3	261.2	437.4	260.0
		dense	318.4	188.9	45.8	1056.0	188.3	45.7	28.7	69.0	28.8
		sparse	1417.6	682.1	407.7	1780.3	274.9	363.1	117.7	176.4	107.4
		dense	541.5	243.0	80.5	1467.8	243.0	80.5	65	90.1	51.9
	64	sparse	134.8	65.8	54.6	167.0	39.8	48.0	17.7	41.1	18.5
		dense	19.8	8.9	5.9	53.6	8.9	5.9	3.2	2.3	2.5
		sparse	94.6	51.5	23.2	121.5	24.4	22.0	10.9	11.0	9.0
mGPU (Tegra K1)	1	dense	12437.2	5765.0	2252.1	35427.0	5544.3	2243.1	1316	2565.5	956.9
	64	sparse	2879.3	1256.5	837.0	4377.2	626.3	745.1	240.6	570.6	315
		dense	1663.6	2056.8	298.0	2001.4	2050.7	483.9	87.8	956.3	95.2
		sparse	4003.9	1372.8	576.7	8024.8	660.2	544.1	236.3	187.7	186.5
EIE	Theoretical Time		28.1	11.7	8.9	28.1	7.9	7.3	5.2	13.0	6.5
	Actual Time		30.3	12.2	9.9	34.4	8.7	8.4	8.0	13.9	7.5

Figure 4: Wall clock time comparison for sparse and dense matrices between CPU, GPU, mGPU and EIE (an FPGA custom accelerator)
(Adopted figure from [3])

Han et al [3] provide a clear description of a technique for exploiting the sparity of activations by storing an encoded sparse weight matrix in a variant of compressed sparse column format [4].