Slide Stack

13 looks for Slidev. Set one deck-wide with `themeConfig.look`, or per slide with `look:`.

looks	
`orbital` · `mission` · `ledger` · `nightshift` · `grid`	→ 2
`cloudflare` · `clay` · `tactical`	→ 22
`dotmatrix` · `mono` · `mercury`	→ 35
`manuscript` · `plain`	→ 47

BEYOND LOW ORBIT

MISSION BRIEFING / FLIGHT 12



FLIGHT PROFILE

- Liftoff and ascent on all engines
- Hot staging at T+2:41, booster begins boostback
- Booster returns to the tower for catch
- Ship continues to orbital insertion

ブースターは発射台へ戻り、そのまま次の飛行に備える。

33

ENGINES FIRING AT LIFTOFF

FLY. LAND.
REFLY.

A SPORTS CAR.

AUTHENTIC. CONSEQUENT. TIMELESS.

FOCUS ON WHAT MATTERS.

- Mid-engine architecture for characteristic proportions
- Five round instruments with an analogue rev counter
- Nothing distracts the driver; everything serves a purpose

運転に必要なものだけを、明確に配置する。

5

Round instruments. One rev counter at the centre.



FORM FOLLOWS FUNCTION.

Q3 spend review

Finance team, October 2026

$4.2M

Saved this quarter by catching duplicate software subscriptions

Where the money went

CATEGORY	Q2	Q3	CHANGE
Software	$1,240,000	$980,000	−21%
Travel	$610,000	$655,000	+7%
Cloud	$2,100,000	$1,870,000	−11%
Total	$3,950,000	$3,505,000	−11%

Cloud costs fell after we **moved batch jobs to spot instances**.

来期にやること

- 承認フローを **2ステップから1ステップへ**
- 月次の締めを5営業日から2営業日に短縮
- 経費の90%を **自動で仕訳**

Planning the next cycle

Product engineering sync

Issue sync, simplified

```
const issues = await client.issues({
  filter: { state: { type: { eq: 'started' } } },
  orderBy: 'updatedAt',
})

for (const issue of issues.nodes)
  console.log(issue.identifier, issue.title)
```

Every client keeps a local copy and syncs **only the deltas**.

Shipped

- Offline mode for the desktop app
- Sub-issues with progress rollup
- Keyboard-first triage

Next

- Project health updates
- Customer requests inbox
- 検索の高速化

Build momentum, not backlog

Ship the frontend

deploy --prod / 2026-10-22

Render at the edge

```ts
export const runtime = 'edge'

export async function GET(request: Request) {
  const country = request.headers.get('x-country') ?? 'US'
  return Response.json({ greeting: greet(country) })
}
```

Responses are generated in the region **closest to the visitor**.

42ms

p95 time to first byte at
the edge

What changed in this release

- Preview deployments for every pull request
- Faster cold starts with bytecode caching
- 環境変数をブランチごとに切り替え

Run code everywhere, without managing a single server

Developer platform update

A Worker in eight lines

```
export default {
  async fetch(request, env) {
    const url = new URL(request.url)
    const hit = await env.CACHE.get(url.pathname)
    return new Response(hit ?? 'miss', { status: hit ? 200 : 404 })
  },
}
```

Deployed to every location **in under 30 seconds**.

330+

Cities with a data center within 50 ms of most people online

Security by default

ネットワークの端で攻撃を止める

Reading a model's mind, one feature at a time

Interpretability research update

What we found

Each feature fires on a single, human-readable concept: a city, a programming bug, a tone of voice.

モデル内部の特徴を一つずつ取り出すと、その多くは人間が名前をつけられる概念に対応していた。

> Features can be turned up or down, and the model's behavior changes accordingly.

Methods

Sparse autoencoders trained on the residual stream

Results

解釈可能性の評価へ

The goal is not to remove the uncertainty, but to see it clearly.

Lab notebook, entry 214

AUTONOMOUS PERIMETER

PROGRAM REVIEW / UNCLASSIFIED

SYSTEM OVERVIEW

- Sensor towers fuse radar, EO/IR, and RF detection
- Tracks are classified on the edge, not in the cloud
- One operator supervises **dozens of assets**
- 通信が途絶えても自律運用を継続

1,200 KM²

AREA COVERED PER
SENSOR TOWER

READINESS

SUBSYSTEM	STATUS	LAST TEST
Radar	Nominal	2026-10-18
EO/IR	Nominal	2026-10-19
Datalink	Degraded	2026-10-20
Power	Nominal	2026-10-20

Signal over noise.

Product drop 03

A quieter interface

- Notifications show as light, not sound
- Only the apps you choose can interrupt
- 画面を見なくても状態がわかる

Designed to be put down

120Hz

ADAPTIVE REFRESH, DOWN TO 1HZ
AT REST

Light patterns

```
glyph.play({
  pattern: 'pulse',
  zones: ['ring', 'dot'],
  brightness: 0.6,
})
```

Design in code, code in design

Workshop notes, v1.0

Tokens, not pixels

```
:root {
  --space-1: 4px;
  --space-2: 8px;
  --radius: 0;
  --font: 'Paper Mono', monospace;
}
```

Every value on the canvas **is a CSS value.**

The typeface

Metric	Value
Glyphs	800
Weights	8 (100 to 800)
Feature sets	6
Languages	100+

for the love of type

Banking that runs itself

Founder update, Q3

Where cash sits today

Account	Balance	Yield
Operating	$412,800	0.00%
Treasury	$2,150,000	4.12%
Payroll	$96,400	0.00%

Idle cash above **three months of runway** moves to treasury automatically.

18 months

Runway at the current burn rate

Next quarter

採用計画と支出の見通し

Attention Is All You Need

Vaswani et al.

NeurIPS 2017

論文紹介, 2026-10-22

問題設定

系列変換モデルの多くは再帰構造に依存しており、系列長に比例した逐次計算が学習の並列化を妨げていた[1]。

本論文は再帰も畳み込みも使わず、*attention* だけで入力と出力の依存関係を表現する。

主張

並列化しやすく、翻訳品質でも当時の最高性能を上回る。

結果

モデル / Model	EN-DE BLEU	EN-FR BLEU
ConvS2S	25.16	40.46
Transformer (base)	27.3	38.1
Transformer (big)	28.4	41.8

Figure 1. WMT 2014 での BLEU スコア。原論文 Table 2 より抜粋。

注意機構の定義

$$\mathrm{Attention}(Q, K, V) = \mathrm{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right)V$$

インラインの数式も使える。$d_k = 64$、ヘッド数 $h = 8$。$\sqrt{d_k}$ で割ることで、内積が大きくなりすぎて softmax が飽和するのを防ぐ。

We are excited about the future of attention-based models.

Vaswani et al., 2017, §7

使い方

```
---
theme: ./themes/stack
themeConfig:
  look: ledger   # デッキ全体の既定
---

---
look: clay       # このスライドだけ切り替え
layout: fact
---
```

使えるレイアウト

- `cover` / `section`
- `statement` / `fact`
- `quote` / `two-cols`
- `default` / `end`

部品

- `<CountUp :to="4.2" />` 数字のカウントアップ
- `<Scramble text="..." />` 文字のデコード演出
- ページ番号は全スライドに自動で付く

Thanks