HOORVIA - WOOD MOISTURE CHART: PRINTABLE TARGET GUIDE

Quick Reference Cheat Sheet · US Letter Printable

Crafting & DIY · Sheet #1

Use	Target Moisture	Why	Check
Indoor furniture	6-8%	Matches heated indoor air	Meter before building
Outdoor furniture	12-15%	Matches outdoor humidity	Acclimate outside
Flooring (indoor)	6-9%	Prevents gaps and cupping	Acclimate in the room
Firewood	Below 20%	Burns clean, less smoke	Split and season 6-12 months
Framing lumber	15-19%	Dries in place without warping	Check before closing walls
Turning (bowls)	6-8%	Stable after turning	Rough turn, then dry
Carving	8-12%	Cuts clean, holds detail	Green wood carves easier
Guitar / instruments	6-8%	Stable tone, no cracks	Climate-controlled storage
Boat building	12-15%	Swells tight in water	Marine-grade stock
Cutting boards	6-8%	Food-safe, stable	Oil after drying
Deck boards	12-15%	Outdoor exposure	Gap for expansion
Kiln-dried stock	6-8%	Ready to use	Check with a meter

PRO TIP: Acclimate in the room: Let lumber sit in the room it will live in for two weeks before building. Wood that acclimates in the shop moves again in the house.