HOORVIA - MOTOR OIL VISCOSITY CHART: PRINTABLE SAE GRADE GUIDE

Quick Reference Cheat Sheet · US Letter Printable

Reference Charts · Sheet #1

SAE Grade	Winter (W) Rating	Viscosity @ 100°C (cSt)	Cold-Crank Limit	Typical Use
0W-16	0W	6.1-8.2	-35°C	Latest-model hybrids chasing maximum fuel economy
0W-20	0W	5.6-9.3	-35°C	Most new gasoline cars and hybrids (check manual)
5W-20	5W	5.6-9.3	-30°C	Many American and Asian sedans and SUVs
5W-30	5W	9.3-12.5	-30°C	The common all-rounder for moderate climates
10W-30	10W	9.3-12.5	-25°C	Older engines and warmer regions
0W-40	0W	12.5-16.3	-35°C	European performance cars, wide-temp range
5W-40	5W	12.5-16.3	-30°C	European and turbocharged engines
10W-40	10W	12.5-16.3	-25°C	High-mileage or older gasoline engines
15W-40	15W	12.5-16.3	-20°C	Diesel trucks, tractors, heavy equipment
15W-50	15W	16.3-21.9	-20°C	Sport bikes, air-cooled engines, hot climates
20W-50	20W	16.3-21.9	-15°C	Classic cars, racing, very hot weather
10W-60	10W	21.9-26.1	-25°C	Track cars and extreme heat duty

PRO TIP: Cold starts rule: A 0W oil cranks at -35°C while 15W quits near -20°C. Buy for your winter, not your summer.