HOORVIA - JAVASCRIPT PROMISES CHART: PRINTABLE METHODS & STATES GUIDE

Quick Reference Cheat Sheet · US Letter Printable

Tech & Software · Sheet #1

Method / State	Syntax	What It Does	When to Use It
Pending	new Promise(() => {})	Initial state: not settled yet	Describing a promise in flight
Fulfilled	resolve(value)	Settled successfully with a value	When the async work completes
Rejected	reject(error)	Settled with a failure reason	When the async work fails
new Promise()	new Promise((resolve, reject) => {})	Creates a promise around async work	Wrapping callbacks or timers
.then()	promise.then(value => {})	Runs when the promise fulfills	Using the result value
.catch()	promise.catch(error => {})	Runs when the promise rejects	Handling errors in a chain
.finally()	promise.finally(() => {})	Runs whether it fulfills or rejects	Cleanup like hiding a spinner
Promise.all()	Promise.all([p1, p2])	Waits for all; rejects on the first failure	Loading several things together
Promise.allSettled()	Promise.allSettled([p1, p2])	Waits for all, reporting each outcome	Needing every result, failures included
Promise.race()	Promise.race([p1, p2])	Settles with the first promise to settle	Timeouts and fastest-response wins
Promise.any()	Promise.any([p1, p2])	Fulfills with the first success; rejects if all fail	Trying several sources for one answer
async / await	const x = await fetch(url)	Pauses the function until the promise settles	Writing async code that reads top to bottom

PRO TIP: Catch at the end of the chain: One .catch() at the end handles errors from every step above it.