# Proteomics data analysis in cancer biology with Matlab

#### **Table of Contents**

Summary	1
Loading pre-processed dataset	1
Initializing variables	
Visualizing a set of the samples	
Ranking features	
Other possible approaches	

#### **Summary**

This report represents an example Matlab proteomic data analysis. The dataset analyzed in this report can be found <a href="https://www.nee.google.com">here</a>, which is the FDA-NCI Clinical Proteomics Program Databank. The samples downloaded from the FDA-NIC Proteomics Programa Databank correspond to SELDI Mass-Spec profiles of ovarian cancer samples: Cancer Group vs Normal Group. The study related to this dataset was published, in 2004, in the Endocrine Related Cancer journal. Briefly, after transforming the Mass-Spec data, some \_variables were initialized \_ to facilitate the downstream workflow, \*visualization of Mass-Spec profiles \*performed, and lastly the \*features ranked \* with t-test statistic."

#### Loading pre-processed dataset

After preprocessing the dataset into .mat format (find the code here, the dataset was loaded.

load OvarianCancerQAQCdataset
whos

Name	Size	Bytes	Class	Attributes
MZ	15000x1		double	
Y	15000x216	25920000	double	
grp	216x1	26784	cell	

#### Initializing variables


A set of vector variables, which will be used in the downstream workflow, are initialized.


### Visualizing a set of the samples

Fine below the spectogram of 10 samples. Figure 1 corresponds to original spectogram, while figure 2 to a zoomed spectrogram.

```
figure; hold on;
hC = plot(MZ,Y(:,Cvec(1:10)),'b');
hN = plot(MZ,Y(:,Nvec(1:10)),'g');
xlabel(xAxisLabel); ylabel(yAxisLabel);
axis([2000 12000 -5 60])
legend([hN(1),hC(1)],{'Control Group','Ovarian Cancer'})
title('Spectrograms of 10 Samples')

figure; hold on;
hC = plot(MZ,Y(:,Cvec(1:10)),'b');
hN = plot(MZ,Y(:,Nvec(1:10)),'g');
xlabel(xAxisLabel); ylabel(yAxisLabel);
axis([8000 9000 -1 7])
legend([hN(1),hC(1)],{'Control Group','Ovarian Cancer'})
title('Zoomed Spectrograms of 10 Samples')
```






#### **Ranking features**

Significant masses were identified using a two-way t-statistic. After ranking the features, a set of variables were initialized to generate the plot for the spectogram with two-way t-statistic.

```
[feat,stat] = rankfeatures(Y,grp,'CRITERION','ttest','NUMBER',100);
sig Masses = MZ(feat);
sig_Masses(1:10)' %display the first 10 significant masses
mean_N = mean(Y(:,Nidx),2); % group average for control samples
\max_{N} = \max(Y(:,Nidx),[],2); % top envelopes of the control samples
\min_{N} = \min(Y(:,Nidx),[],2); % bottom envelopes of the control samples
\max_{C} = \max(Y(:,Cidx),[],2); % top envelopes of the control samples
\min_{C} = \min(Y(:,Cidx),[],2); % bottom envelopes of the control samples
figure;
yyaxis left
plot(MZ, [mean_N mean_C]);
ylim([-1,20])
xlim([8000,9000])
title('Significant M/Z Values')
xlabel(xAxisLabel);
ylabel(yAxisLabel);
```

```
yyaxis right
plot(MZ,stat);
ylim([-1,22])
ylabel('Test Statistic');
legend({'Control Group Avg.', 'Cancer Group Avg.', 'Test Statistics'})
ans =
   1.0e+03 *
  Columns 1 through 7
    8.1009
              8.1016
                         8.1024
                                    8.1001
                                              8.1032
                                                        7.7366
                                                                   7.7359
  Columns 8 through 10
    7.7374
              7.7253
                         7.7245
```



## Other possible approaches

Although not performed in this example proteomic data analysis, other approaches that could have been added include:

# Proteomics data analysis in cancer biology with Matlab

- 1. identify the amino acid sequences of the statistically significant features
- 2. and identify the proteins by matching amino acid sequences to databases.

In future \*"omics" data analysis in Matlab, as well as in R and Python more thorough and detailed workflow will be shared.

Author: Felix E. Rivera-Mariani, PhD

Published with MATLAB® R2017a