

# Configure and Use an Auth Method from the CLI



**Ned Bellavance**

HashiCorp Certified Instructor

@nedinthecloud | [nedinthecloud.com](https://nedinthecloud.com)



# Vault CLI Basics

```
$ vault -h
```

```
Usage: vault <command> [args]
```

Common commands:

read	Read data and retrieves secrets
write	Write data, configuration, and secrets
delete	Delete secrets and configuration
list	List data or secrets
login	Authenticate locally
agent	Start a Vault agent
server	Start a Vault server
status	Print seal and HA status
unwrap	Unwrap a wrapped secret



# Vault CLI Basics

```
$ vault path-help -h
```

```
Usage: vault path-help [options] PATH
```

Retrieves API help for paths. All endpoints in Vault provide built-in help in markdown format. This includes system paths, secret engines, and auth methods.



# Environment Variables

# Vault Server Address


VAULT\_ADDR="https://vault.yolo.local:8200"

# Vault Token

VAULT\_TOKEN=hvs.NJI87YHJHY78UHJU87678UJHGY678



# Userpass Method



**Username and password**

**Stored locally in Vault**

**Break glass scenarios and development**



# Auth Commands

# List existing auth methods

```
vault auth list
```

# Enable an auth method

```
vault auth enable [options] TYPE
```

```
vault auth enable -path=admins userpass
```

# Tune an auth method

```
vault auth tune [options] PATH
```

```
vault auth tune -description="Admins only userpass" admins
```



# Auth Commands

# Move an auth method

```
vault auth move [options] SOURCE DESTINATION
```

```
vault auth move "auth/admins" "auth/administrators"
```

# Disable an auth method

```
vault auth disable [options] PATH
```

```
vault auth disable administrators
```

# Get help on logging in

```
vault auth help [options] PATH
```

```
vault auth help administrators
```



# Configuration Commands

```
# Configuring an auth method
```

```
vault read
```

```
vault write
```

```
vault list
```

```
vault delete
```

```
vault path-help
```





# Login Command

# Log in with a token

```
vault login
```

# Log in with userpass

```
vault login -method=userpass -path=administrators username=ford
```

