

Exploring Terraform State




Ned Bellavance

HashiCorp Certified Instructor


nedinthecloud.com



State Data



Planning Process



Backend Options

{JSON}

Local backend

- Default setting

Remote backend

- S3, Azure Storage, Google Cloud Storage
- HCP Terraform and Consul

Features

- Locking
- Workspaces

Data encryption

Access control



Backend Block

backend.tf

```
terraform {  
  backend "backend_type" {  
    IDENTIFIER = LITERAL_VALUE  
  }  
}
```



Backend Block

backend.tf

```
terraform {  
  
    backend "s3" {  
        bucket      = "globo-state-12345"  
        key          = "dev/terraform.tfstate"  
        region       = "us-east-1"  
        access_key   = "HGT657UHT56786YUHT6"  
        secret_key   = "ytgvbJU&*ijhgt6%TYUijhy"  
    }  
}
```



Backend Block

backend.tf

```
terraform {  
  backend "s3" {  
    bucket = "globo-state-12345"  
    key    = "dev/terraform.tfstate"  
  }  
}
```



```
terraform {  
    backend "s3" {}  
}
```

Partial Configuration

Using in-line settings

```
terraform init -backend-config="bucket=globo-state-12345"
```

Using a backend config file

```
terraform init -backend-config="backend-settings.txt"
```



State Data Migration



Use S3 bucket provided by Ops

Migrate existing state data

Use a partial configuration



State Inspection Commands

Display all state data

```
terraform show
```

List all resources and data sources

```
terraform state list
```

List all attributes of a single object

```
terraform state show ADDR
```

```
terraform state show aws_vpc.main
```

Show outputs stored in state

```
terraform output NAME
```



Moved Block

moved.tf

```
moved {  
  from = ADDRESS  
  to   = ADDRESS  
}
```



Import Block

imports.tf

```
import {  
  to = ADDRESS  
  id = "UNIQUE_IDENTIFIER"  
}
```



Removed Block

removed.tf

```
removed {  
  from = ADDRESS  
  
  lifecycle {  
    prevent_destroy = false  
  }  
}
```

