
Managing Leases



Ned Bellavance

HashiCorp Certified Instructor

@nedinthecloud | nedinthecloud.com



Vault CLI Basics

\$ vault -h

```
Usage: vault <command> [args]
Common commands:
                Read data and retrieves secrets
    read
    write
                Write data, configuration, and secrets
    delete
                Delete secrets and configuration
    list
                List data or secrets
    login
                Authenticate locally
                Start a Vault agent
    agent
                Start a Vault server
    server
                Print seal and HA status
    status
                Unwrap a wrapped secret
    unwrap
```



Environment Variables

```
# Vault Server Address

VAULT_ADDR="https://vault.yolo.local:8200"

# Vault Token

VAULT_TOKEN=hvs.NJI87YHJHY78UHJU87678UJHGY678
```



Lease Commands


```
# Lookup an existing lease
vault lease lookup LEASE_ID
vault token lookup database/creds/readonly/y0pnZCQjG3yQlbmBqgkYm5iM

# Renew a lease by a given increment
vault lease renew LEASE_ID
vault lease renew -increment=1h database/creds/readonly/y0pnZCQjG3yQlbmBqgkYm5iM

# Revoke a lease by ID or prefix
vault lease revoke LEASE_ID
vault token revoke -prefix database/creds/readonly
```



Dynamic Secrets Engines




Provision dynamic secrets on-demand


Manage lifecycle of secrets

Secrets deleted when lease ends

Lease Revocation



TTL expires





Token expires or revoked





Lease is revoked
















Force Operation





Lease Properties

