Induction Heads and Model Collapse: How the Real-to-Synthetic Data Ratio Shapes In-Context Learning Circuits

Lily de Melo 2545080
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Gopolang Mohlakola 2680747
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Tawananyasha Kadango 2588206
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Abstract

Roughly 20 lines. It should follow the format of the paper where each section is summarised as a sentence (not a fixed rule but a bit of a heuristic).

Keywords: 3 Words or phrases that give the main categories or topics of the work

Introduction

Large language models (LLMs) are trained on internet data increasingly generated by other models. Shumailov et al. (2024) showed that recursive training on such data causes *model collapse*, in which successive generations lose information about the true data distribution, beginning with its tails. In practice, real and synthetic data tend to accumulate, and Gerstgrasser et al. (2024) found that retaining real data avoids collapse. However, both studies measure collapse through model outputs. If recursive training damages a model's internal mechanisms before its outputs degrade, output metrics would understate collapse.

In-context learning (ICL) lets models adapt to new tasks from prompt examples without parameter updates (Olsson et al., 2022; Singh et al., 2024), making its robustness to collapse important for future LLMs. In the task of Singh et al. (2024), a model outputs the label paired with a query symbol, with labels reassigned per sequence so that only the context holds the answer. The task is solved by an induction circuit: a previous-token head and an induction head match the query to its earlier occurrence and copy the following label. As each component is known, damage from recursive training can be traced to specific heads and connections rather than inferred from accuracy.

This study therefore trains transformers on this task over generations whose training data are partly or wholly labelled by the previous generation's model, comparing the replacement of 50–100% of the real data with accumulation, for a base model and an extended model that also generates part of each sequence (Figure 1). The circuit of every generation is traced and tested causally. A well-trained model reproduces its own labels almost exactly, so collapse appears only once sampling noise introduces errors. The circuit's margin for the correct label then halves while accuracy is unchanged, and this erosion appears to set the error rate of the next generation's data, whereas accumulating real data keeps accuracy at 0.99 and the circuit compact, although its margin still declines.




Figure 1: Base (left) and extended (right) models. The base model predicts the query's label ℓ_q from two symbol–label pairs and query x_q. The extended model additionally predicts the next symbol x_n and its label ℓ_n. Shaded boxes indicate model outputs, while dashed inputs represent true tokens during training and generated tokens during recursive training.

Background

Induction heads The previous-token head copies each symbol into the label that follows it, and the induction head then matches the query against these copies through its key input and copies the matching label to the output (Singh et al., 2024). Several induction heads can form and contribute additively (Singh et al., 2024), so the circuit can spread across heads rather than rely on one, and interventions on their formation change ICL ability with them (Chen et al., 2026).

Model collapse Shumailov et al. (2024) identify sampling error as the primary cause of collapse: finite samples rarely reproduce low-probability events, so the tails of the distribution vanish first, and each model's errors compound in the data of the next. In fine-tuned OPT-125m, preserving 10% of the original data led to only minor degradation.

Accumulating data Gerstgrasser et al. (2024) found that replacing real data causes test error to grow with every iteration, whereas accumulating synthetic data alongside it keeps the error bounded, across language, diffusion, and autoencoder models. This study tests whether the same contrast holds for the induction circuit.

Methods

This study varies the share of real data in the training pool and measures its effect on the induction circuit. It uses the setup of Singh et al. (2024), whose circuit is known to form: each sequence holds two exemplar–label pairs and a query, with Omniglot exemplars encoded by a frozen ResNet18 and five labels reassigned per sequence. The model, a causal two-layer attention-only transformer with eight heads per layer, trains on 50 classes and is tested on 100 unseen classes, so that accuracy reflects ICL alone.

Base and extended models The base model predicts the query's label. The extended model also predicts the next symbol, through a separate symbol head, and that symbol's label (Figure 1), so that three tokens per sequence become synthetic rather than one.

Next-symbol selection By default, the next symbol is a context symbol chosen uniformly, a conservative baseline in which every target remains solvable by the induction circuit. A second condition draws it from all training classes, so that the model must learn an unconditional distribution. Generated tokens are sampled from the softmax at temperature T, the source of error described above; argmax removes it and serves as an ablation.

Real-to-synthetic ratio Each run trains on a fixed pool of $N = 20{,}000$ sequences over six generations, the first on real data. The previous model then regenerates the targets of 0%, 50%, 90%, or 100% of the pool from their real prompts, where 0% is a real-only control and 90% matches the 10% of real data kept by Shumailov et al. (2024). Accumulation instead keeps every item and adds N synthetic sequences per generation (Gerstgrasser et al., 2024), matching 50% replacement at generation 1, so that keeping earlier data can be separated from the real share itself. A fixed initialisation and training length ensure that conditions differ only in their pool.

Forcing synthetic errors At $T = 1$, the tuned model regenerates its labels almost perfectly, with 0.01% wrong after 20 generations, so every ratio yields an essentially real pool. Each regenerating condition is therefore also run at $T = 3$ and $T = 5$, which introduce 0.5% and 6.5% wrong labels, so that the ratio acts at a known error rate.

Tuning As collapse can only alter a circuit that has formed, the learning rate and training length are tuned per model on generation 0, using 1,473 validation classes so that the test classes remain unseen. This gives $\eta = 10^{-4}$ for the base model and 3×10^{-4} for the extended model, both for one million sequences.

Burstiness and class distribution Two sweeps at $T = 1$ test whether properties of the data admit errors without forcing. Burstiness, $B \in \{1, 2, 4\}$, sets how many of eight context items share the query's class: a low B leaves the induction head a single match among many items, which aims to elicit a less confident model whose own errors enter the pool, while a high B provides redundant matches. Zipfian class frequencies, $\alpha \in \{0.5, 1, 1.5\}$, create a long tail of rare symbols.

Circuit analysis Each generation's model is analysed on the same real sequences, so that changes reflect the model rather than the data. The logit difference measures how strongly the circuit separates the correct label, the number of connections Automatic Circuit DisCovery (ACDC) (Conmy et al., 2023) keeps at a fixed $\tau = 0.001$ measures whether it stays sparse, and the induction score measures whether the induction head still attends to the match. Patching the previous-token head's output alone into the induction head tests whether the circuit still routes through it, and test accuracy is reported alongside, since it can stay high while the logit difference falls.

Results

Table 1 summarises every condition at its final generation, and the paragraphs below follow the questions in turn.

No errors, no collapse At $T = 1$, the tuned base model regenerates its labels almost exactly, and the 50%, 90%, and 100% replacement runs produce identical models, as does argmax sampling relative to the real-only control. Accuracy therefore stays at 0.99 under every ratio. The circuit nonetheless drifts over 20 generations of full replacement: its margin falls from 19.9 to 12.5 and its ACDC circuit grows from 17 to 35 edges (Figure 2a–b), whereas the real-only margin varies only between 16.9 and 20.0 across generations. This suggests that the circuit changes before accuracy even when almost no errors enter the data.

Table 1: Final generation of each condition. Without forced errors, accuracy holds everywhere except the least bursty context, while the margin falls and the circuit grows. With errors forced at $T = 3$, accumulation keeps accuracy and the induction score near the real-only level for five generations, but declines slowly over 20, whereas each replacement level settles at an accuracy set by its real share. The real-only row never samples and serves as the control at every temperature. †Margin below 1, where the circuit size is less reliable. Induction scores are omitted for eight-item contexts, where they vary between real-only retrains.

		Real	Label	Base model				Extended model	
Condition	Gen.	share	error	Acc.	Margin	Edges	Ind.	Margin	KL
No forced errors ($T = 1$)									
Real only	5	100%	0.00	0.99	20.0	19	0.97	16.0	0.00
100% replaced	19	0%	0.01	0.99	12.5	35	0.87	13.8	0.03
Accumulate	19	5%	0.00	1.00	10.4	22	0.91	6.3	0.01
100% replaced, $B = 1$	5	0%	0.06	0.75	11.0	49	–	7.1	0.12
100% replaced, $B = 4$	5	0%	0.00	0.99	13.2	21	–	12.5	0.02
Forced errors ($T = 3$)									
50% replaced	5	50%	0.30	0.80	3.0	198	0.84	4.6	0.00
90% replaced	5	10%	0.66	0.38	0.6	218†	0.27	0.2	0.00
100% replaced	5	0%	0.75	0.25	0.1	209†	0.05	0.0	0.00
Accumulate	5	17%	0.31	0.99	2.1	23	0.95	3.1	0.00
Forced errors over 20 generations ($T = 3$, base model only)									
50% replaced	19	50%	0.33	0.78	2.7	190	0.85	–	–
90% replaced	19	10%	0.69	0.31	0.4	204†	0.16	–	–
100% replaced	19	0%	0.79	0.19	0.1	210†	0.04	–	–
Accumulate	19	5%	0.59	0.93	0.8	12†	0.80	–	–




Figure 2: ACDC circuits of the base model on a fixed layout of the input, the eight heads of each layer, and the output, with filled nodes marking heads in the circuit and edge width growing with its effect on the output. At generation 0 (a), the circuit routes the input through the previous-token head A0.2 into the key input of the induction head A1.3. Twenty error-free generations of full replacement (b) double its size while accuracy holds, and

The circuit fails before accuracy When sampling at $T = 3$ introduces errors, the circuit degrades in a consistent order under full replacement. The margin halves by generation 1, from 19.9 to 10.8, while accuracy holds at 0.99. By generation 2, the circuit has grown from 17 to 188 edges, spreading across every head and into query inputs that the original circuit did not use (Figure 2c), while accuracy is still 0.88. Accuracy then falls to 0.25 by generation 5, and the induction score falls last, from 0.75 at generation 3 to 0.05, with the previous-token head holding until generation 4. Accuracy then settles near chance, at 0.19 by generation 19, once 79% of the pool's labels are wrong, close to the 80% expected from five labels assigned at random. This order is likely because noisy labels make the label only partly predictable from the context, so that the model lowers its confidence and spreads the computation across more connections, consistent with the additive contribution of several heads reported by Singh et al. (2024). The extended model follows the same order, with its circuit growing from 46 to 179 edges while accuracy is still 0.88.

The margin sets the next generation's errors If the correct label leads each of the four wrong labels by the margin D_g of generation g's model, sampling at temperature T produces wrong labels at a rate of

$$\hat{\varepsilon}_{g+1} = \frac{4\,e^{-D_g/T}}{1+4\,e^{-D_g/T}}. \tag{1}$$

The observed error rate of each generation's new samples closely matches Equation 1 across both models, both temperatures, and every condition, with a correlation of 0.994 and a

mean absolute error of 0.021. At $T = 3$, the generation 0 margin of 19.9 predicts 0.5% wrong labels, while the margin of 5.3 at generation 2 predicts 41% against an observed 44%. The eroding margin is therefore not only a symptom of collapse: it determines how many errors the next generation inherits, which explains why errors compound once they begin.

Retaining real data Over 20 generations at $T = 3$, each replacement level settles at an accuracy set by its real share, at 0.78 with 50% real data, 0.31 with 10%, and 0.19 with none (Figure 3). With 50% real data, the pool's label error levels off at 33% and the margin at about 2.7, so that retaining half the real data bounds the collapse but does not prevent the circuit from spreading to 190 edges. Accumulation holds accuracy at 0.97 or above for 15 generations, even though its real share falls to 6% by then, and at generation 19 it still reaches 0.93 with only 5% real data, against 0.78 for 50% replacement. As both conditions hold 50% real data at generation 1, keeping earlier data appears to matter more than the real share itself, likely because each real prompt keeps its correct label while errors scatter across the four wrong labels. However, accumulation delays collapse rather than preventing it: its margin falls steadily from 19.9 to 0.77, the share of wrong labels in its pool rises to 59%, and accuracy begins to decline once the margin drops below 1 at generation 16. Its circuit contracts to 12 edges rather than spreading (Figure 2d), although at a margin below 1 this count is less reliable. This contrasts with Gerstgrasser et al. (2024), who found that accumulation keeps the error bounded, and suggests that the margin of the circuit erodes even when its behaviour is protected.




Figure 3: Test accuracy of the base model per generation at $T = 3$ for each condition over 20 generations. Each replacement level settles at an accuracy set by its real share, while accumulation stays with the real-only control for 15 generations before declining slowly. Hollow markers indicate a margin below 1.

Symbol distribution and data properties The extended model's symbol distribution does not narrow: its divergence from generation 0 stays at or below 0.02, even when 96% of its next symbols fall outside the context at $T = 3$, so that it collapses through wrong copying rather than a lost tail. Burstiness shows the clearest effect of the data without forced errors. Under full replacement at $T = 1$, the extended model loses 57%, 39%, and 14% of its margin relative to real-only retraining as B rises from 1 to 4, and its symbol divergence falls from 0.12 to 0.02, while only the base model at $B = 1$ admits enough errors to lose accuracy, from 0.83 to 0.75. Redundant matches in the context therefore appear to protect the circuit, likely because they keep the model confident enough that its own samples remain correct. The Zipfian sweeps, in contrast, leave accuracy and the tail mass of the symbol distribution unchanged, likely because the next symbol is copied from real prompts, which preserve rare symbols by construction.

Discussion

Take a broader perspective of your results and recontextualise them in terms of the field and your community. Your research should aim to be helpful to your community and you will stand better chances of gaining readers if you take this tone. So how has your work helped and what should a reader leave remembering?

Acknowledgements (Not in Page Limit – you will probably not have one)

Computations were performed using High Performance Computing infrastructure provided by the Mathematical Sciences Support Unit at the University of the Witwatersrand.

Contribution Statements (Not in Page Limit)

We, Lily de Melo, Tawananyasha Kadango, and Gopolang Mohlakola, worked together fairly on this project.

References

Chen, J., Luo, Y., & Pan, L. (2026). Mechanistic data attribution: Tracing the training origins of interpretable LLM units. In *International conference on machine learning* (Vol. 306). PMLR.

Conmy, A., Mavor-Parker, A., Lynch, A., Heimersheim, S., & Garriga-Alonso, A. (2023). Towards automated circuit discovery for mechanistic interpretability. In *Advances in neural information processing systems* (Vol. 36, pp. 16318–16352).

Gerstgrasser, M., Schaeffer, R., Dey, A., Rafailov, R., Pai, D., Sleight, H., ... Koyejo, S. (2024). Is model collapse inevitable? Breaking the curse of recursion by accumulating real and synthetic data. *arXiv preprint arXiv:2404.01413*.

Olsson, C., Elhage, N., Nanda, N., Joseph, N., DasSarma, N., Henighan, T., ... others (2022). In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*.

Shumailov, I., Shumaylov, Z., Zhao, Y., Papernot, N., Anderson, R., & Gal, Y. (2024). AI models collapse when trained on recursively generated data. *Nature*, *631*(8022), 755–759. doi: 10.1038/s41586-024-07566-y

Singh, A. K., Moskovitz, T., Hill, F., Chan, S. C. Y., & Saxe, A. M. (2024). What needs to go right for an induction head? A mechanistic study of in-context learning circuits and their formation. In *International conference on machine learning* (Vol. 235, pp. 45637–45662). PMLR.

NeurIPS Paper Checklist

The checklist is designed to encourage best practices for responsible machine learning research, addressing issues of reproducibility, transparency, research ethics, and societal impact. Do not remove the checklist: **The papers not including the checklist will be desk rejected.** The checklist should follow the references and follow the (optional) supplemental material. The checklist does NOT count towards the page limit.

Please read the checklist guidelines carefully for information on how to answer these questions. For each question in the checklist:

- You should answer [Yes] , [No] , or [NA] .
- [NA] means either that the question is Not Applicable for that particular paper or the relevant information is Not Available.
- Please provide a short (1–2 sentence) justification right after your answer (even for NA).

The checklist answers are an integral part of your paper submission. They are visible to the reviewers, area chairs, senior area chairs, and ethics reviewers. You will be asked to also include it (after eventual revisions) with the final version of your paper, and its final version will be published with the paper.

The reviewers of your paper will be asked to use the checklist as one of the factors in their evaluation. While "[Yes] " is generally preferable to "[No] ", it is perfectly acceptable to answer "[No] " provided a proper justification is given (e.g., "error bars are not reported because it would be too computationally expensive" or "we were unable to find the license for the dataset we used"). In general, answering "[No] " or "[NA] " is not grounds for rejection. While the questions are phrased in a binary way, we acknowledge that the true answer is often more nuanced, so please just use your best judgment and write a justification to elaborate. All supporting evidence can appear either in the main paper or the supplemental material, provided in appendix. If you answer [Yes] to a question, in the justification please point to the section(s) where related material for the question can be found.

IMPORTANT, please:

- **Delete this instruction block, but keep the section heading "NeurIPS paper checklist"**,
- **Keep the checklist subsection headings, questions/answers and guidelines below.**
- **Do not modify the questions and only use the provided macros for your answers**.

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.

- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory Assumptions and Proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
   - Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental Result Reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.

- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example

(a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
(b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
(c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental Setting/Details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment Statistical Significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments Compute Resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code Of Ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: **[TODO]**

   Justification: **[TODO]**

   Guidelines:

   - The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader Impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: **[TODO]**

Justification: **[TODO]**

Guidelines:

- The answer NA means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.

- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New Assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: **[TODO]**

    Justification: **[TODO]**

    Guidelines:

    - The answer NA means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and Research with Human Subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: **[TODO]**

    Justification: **[TODO]**

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional Review Board (IRB) Approvals or Equivalent for Research with Human Subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: **[TODO]**

    Justification: **[TODO]**

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

Wits University Faculty of Science post-graduate student AI declaration

I understand that the use of generative AI tools (such as ChatGPT or similar) without explicitly declaring such use constitutes a form of plagiarism and is classified by Wits University as academic misconduct.

I declare that in the course of conducting the research towards my degree or in the preparation of this thesis/dissertation/research report (select one by marking with an X):

I **did not** make use of generative AI tools ☐

I **did** make use of generative AI tools for the following (tick all that apply):

1. Idea Generation (research problem/design, hypothesis) ☐
2. Sourcing Related Work (summarising, identifying sources) ☐
3. Methods and Experiment Design (experiment setup, model tuning) ☐
4. Data Analysis (presentation, coding, interpretation) ☐
5. Theoretical Development (theorem proving, conceptual analysis) ☐
6. Code Development (generating algorithms, writing scripts) ☐
7. Presentation (rendering graphics, formatting) ☐
8. Editing (grammar, readability) ☐
9. Writing (text generation, document structuring) ☐
10. Citation Formatting (structuring, organising) ☐

If other uses were involved, please specify below:

Generative AI tool used (list all)	**Used for?**

If generative AI tools were used as an integral part of the experimental design or in the direct execution of my research, I confirm that details of this use are clearly outlined in the relevant experimental/methodology chapters of my thesis/dissertation/research report.

Student number:

Candidate signature:

Date: