Reading Both Halves of *Imvo*: What Modernising 1880s isiXhosa Does to Cross-Lingual Analysis

Lily de Melo Tawananyasha Kadango Sally Mohlakola
University of the Witwatersrand

1 Introduction

Imvo Zabantsundu, founded by John Tengo Jabavu in 1884, was the first African-owned and run newspaper in South Africa. It was written mainly in isiXhosa, with an English section titled *Native Opinion*; in the digitised archive (Schoots et al., 2023), 511 of 517 issues from 1884–1894 carry substantial text in both languages. Each issue therefore had one editor writing for two readerships. Because NLP tools are far stronger for English than for isiXhosa, it is tempting to analyse the English half alone, or to "clean" the isiXhosa half first. One such step is *spelling modernisation*: the archive writes *Tixo*, *apa* and *umteto* where modern isiXhosa writes *Thixo*, *apha* and *umthetho*. Modernisation is usually treated as neutral preprocessing. We test that assumption.

Research question. *When Imvo's isiXhosa and English sections from the same issue are placed in one multilingual embedding space, how distinguishable is their content, and how does modernising the isiXhosa spelling change that answer?* **H1:** once language identity is removed, a classifier predicts a chunk's section above a *translated-pair floor*, i.e. the audiences received different content. **H2:** modernisation lowers the floor (less spelling signal) but leaves the content gap unchanged; a significant change in the gap would mean modernisation alters the substantive conclusion. **Contributions:** (i) a language-removal method estimated only from translated pairs, validated on synthetic data with a known answer; (ii) a lexicon-gated normaliser with rule ablations; (iii) a measurement of what modernisation changes, including which names it rewrites.

2 Background and related work

The isiXhosa Intellectual Traditions archive digitised 19th-century isiXhosa newspapers and split pages into isiXhosa and English text (Schoots et al., 2023). Historical text normalisation maps old spellings to modern ones and is usually evaluated by normalisation accuracy or downstream task scores (Bollmann, 2019), not by whether it changes the conclusions drawn from the text. Multilingual sentence encoders such as LaBSE (Feng et al., 2022) embed many languages, including isiXhosa, in one space, but their representations still encode language identity; removing it, e.g. by subtracting each language's mean, is a known technique (Libovický et al., 2020). We show that mean-centring also removes genuine average content differences, which is exactly what we want to measure, and replace it with a pair-based estimate. Treating modernisation as a choice that can change results follows the "garden of forking paths" view of analytic flexibility (Gelman and Loken, 2013).

3 Method

Data. We use the archive's language-split text for 511 of 517 Imvo issues (1884–1894) that contain $\geq$1,000 words in each language (3.9M isiXhosa, 1.5M English words). We correct only OCR artefacts (never spelling), cut pages into 60-word chunks, and flag boilerplate (a chunk is flagged if $\geq$30% of its 5-word sequences recur in $\geq$5 issues: adverts, notices, tax lists) and chunks whose language does not match their section. This leaves 45,465 isiXhosa and 22,927 English chunks. Issues are split 357/77/77 into train/validation/test, stratified by year, so no issue crosses splits. Boilerplate is far more common in the isiXhosa half (29.9% vs 7.9%).

Modernisation. From 3.3M tokens of modern isiXhosa (Vukuzenzele (Lastrucci et al., 2023), isiXhosa Wikipedia, OPUS-100 (Zhang et al., 2020)) we build a word-frequency list $f(\cdot)$. Two rule families can be switched on separately: *aspiration* restores unwritten aspiration (t,p,k,r and clicks $c,q,x \to +h$), trying every combination of eligible positions; *prefix* joins prefixes written apart (*e Palamente* $\to$ *ePalamente*). A word w is rewritten to w' only if $f(w) \leq \tau_o$ and $f(w') \geq \tau_v$. (τ_o, τ_v) are tuned on hand-checked validation words to maximise $F_{0.5}$, since over-correcting an author's spelling is the costlier error.

Embedding and pairs. Chunks are embedded with LaBSE (Feng et al., 2022) (and with multilingual-E5 (Wang et al., 2024) as a robustness check). Within each issue, mutual nearest neighbours across the two sections are candidate translations; the similarity threshold is the lowest whose precision is $\geq$0.9 on hand-labelled validation candidates.

Removing language, measuring content. Let P be the translated pairs in training issues. Because a pair shares its content, its difference is language:

$$D = \left[x_i^{\text{xh}} - x_i^{\text{en}}\right]_{i \in P}, \quad \tilde{x} = x - V_k^\top V_k x, \tag{1}$$

where V_k holds the top-k right singular vectors of D. A balanced logistic-regression classifier then predicts each chunk's section from $\tilde{x}$. Its balanced accuracy on held-out translated pairs is the *floor* (language signal that survives); the content gap is

$$\Delta = \text{BA}_{\text{all}} - \text{BA}_{\text{pairs}}. \tag{2}$$

$k \in \{0, \ldots, 64\}$ is the smallest value whose validation floor is $\leq$0.55, and the regularisation C is tuned on validation. For H2, modernised variants reuse the raw run's pairs and k, so only the text changes. We report differences with paired bootstrap 95% CIs over test issues (B=1000). Alignment across variants is measured on *embedding-free* true pairs (matched by shared names and numbers, then hand-verified), because pairs selected in the raw space would favour raw by construction.

Validation. On synthetic data with a planted content gap, we compare our method with no removal and with mean-centring against an oracle that sees content only.

4 Results

The method recovers known gaps. Without language removal, the classifier separates translated pairs perfectly (floor 1.00, gap 0): it detects language, not content. Mean-centring reports a gap of 0.000 at every effect size. The pair-based method tracks the oracle closely (Fig. 1; at δ=0.4: 0.097 vs 0.099).

What modernisation changes. With provisional thresholds (τ_o=2, τ_v=5), the full normaliser rewrites 12.4% of isiXhosa tokens: aspiration 7.8% (e.g. *apa*→*apha*,




Figure 1: Synthetic validation (5 seeds per effect size δ; error bars = s.d.). Only the pair-based method recovers the oracle content gap; mean-centring erases it.

Table 1: How modern tools see the text. OOV = share of word tokens absent from the modern word list; fertility = subword tokens per raw word.

Text	OOV	LaBSE	XLM-R
Imvo isiXhosa, raw	31.5%	2.11	2.50
+ aspiration only	24.5%	2.09	2.51
+ prefix joining only	34.2%	2.14	2.51
+ both (modern)	26.8%	2.12	2.52
Imvo English	–	1.26	1.38
Modern isiXhosa (Vukuzenzele)	–	2.18	2.92

pakati→*phakathi*, *ipepa*→*iphepha*) and prefix joining 4.6%. **[Normaliser precision/recall on held-out words, from normalise.py tune.]** It rewrites 149 likely proper names (capitalised in ≥90% of occurrences; 12,966 tokens), including *Xosa*→*Xhosa*, *Tembu*→*Thembu*, *Mtata*→*Mthatha* and *Tixo*→*Thixo*. Table 1 shows that modernisation mainly changes vocabulary: 31.5% of raw word tokens are absent from modern text, against 24.5% after restoring aspiration, while subword fertility barely moves.

Two audiences (H1) and the effect of modernisation (H2). Table 2 and Fig. 2 report the section classifier on test issues ([n] reference pairs, k=[k]). **[One sentence on H1: is $\Delta_{\text{raw}} > 0$ with a CI excluding 0?]** **[One sentence on H2: how floor and Δ move under each variant.]**

In a single-issue pilot, LaBSE already matched genuine translations (an obituary, a magistrate's report, a franchise petition) at similarity 0.54–0.67, against a median of 0.25 for random pairs. **[Qualitative: clusters most over-represented in the isiXhosa half (from qualitative.md), with one short quoted example, and the per-issue JSD vs permutation baseline.]**

5 Discussion

The control is the method. A naive section classifier scores perfectly and tells us nothing, and the standard fix (mean-centring) silently assumes the answer to H1 is "no". Estimating the language subspace only from translated pairs separates language from content without that assumption, and the synthetic check shows it recovers gaps of the size we test for.

Modernisation is a forking path. **[One of: (a) if Δ is unchanged while the floor falls: modernisation removes spelling signal but leaves the audience conclusion intact, so it is safe for this question but not neutral for alignment; or (b) if Δ changes: the substantive conclusion about what Imvo told its two audiences depends on a preprocessing choice that is rarely reported.]** Either way, the ablation

Table 2: Section classifier (test balanced accuracy) and alignment. Δ = all − floor; brackets: paired bootstrap 95% CI of the change vs raw. P@1 on embedding-free true pairs.

Variant	All	Floor	Δ	$\Delta - \Delta_{\text{raw}}$	P@1
raw	[]	[]	[]	–	[]
modern	[]	[]	[]	[CI]	[]
aspiration only	[]	[]	[]	[CI]	[]
prefix only	[]	[]	[]	[CI]	[]
E5: modern	[]	[]	[]	[CI]	[]

[fig_compare.png from compare.py]

Figure 2: **[Caption stating what the reader should see, e.g. the floor falls under modernisation while Δ stays within its CI.]**

shows which rule family drives the change, and Table 1 explains why: modernisation acts on vocabulary, not on how text is segmented.

What "fixing" text costs. The normaliser rewrites the names of a people (*Xosa*), a community (*Tembu*), a town (*Mtata*) and God (*Tixo*) into today's forms. These are correct modern spellings, but they replace how the authors wrote their own names and beliefs. A digitised archive that silently modernises becomes a different historical record. We therefore recommend that analyses of historical African-language text report a *normalisation sensitivity* check: run the analysis on raw and normalised text and report both.

Limitations. Translated pairs may over-represent notices and obituaries, so the floor may not represent all genres **[genre mix of pairs]**. Labelling was done by **[team's isiXhosa reading level]**; the modern word list is dominated by OPUS-100 web text; OCR noise is uneven across years; and we measure differences in content, not editorial intent.

References

M. Bollmann. A large-scale comparison of historical text normalization systems. *NAACL*, 2019.

F. Feng, Y. Yang, D. Cer, N. Arivazhagan, W. Wang. Language-agnostic BERT sentence embedding. *ACL*, 2022.

A. Gelman, E. Loken. The garden of forking paths. Technical report, Columbia University, 2013.

R. Lastrucci et al. Preparing the Vuk'uzenzele and ZA-gov-multilingual South African multilingual corpora. *RAIL*, 2023. **[verify]**

J. Libovický, R. Rosa, A. Fraser. On the language neutrality of pre-trained multilingual representations. *Findings of EMNLP*, 2020.

J. Schoots, A. Ngwendu, J. De Wet, S. Muftic. IsiXhosa intellectual traditions digital archive: Digitizing isiXhosa texts from 1870–1914. *RAIL*, 2023.

L. Wang et al. Multilingual E5 text embeddings: A technical report. arXiv:2402.05672, 2024.

B. Zhang, P. Williams, I. Titov, R. Sennrich. Improving massively multilingual neural machine translation and zero-shot translation. *ACL*, 2020.

Contribution statement

We (Lily de Melo, Tawananyasha Kadango and Sally Mohlakola) worked together fairly on this project. **[paste final contribution statement.]**

AI Ethics Statement

[Faculty of Science AI Ethics Statement.]

NeurIPS Paper Checklist

[\input the NeurIPS 2024 checklist .tex from Moodle here, filled in.]