Induction Heads and Model Collapse: How the Real-to-Synthetic Data Ratio Shapes In-Context Learning Circuits

Lily de Melo 2545080
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Gopolang Mohlakola 2680747
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Tawananyasha Kadango 2588206
University of the Witwatersrand, 1 Jan Smuts Ave,
Braamfontein, Johannesburg, 2000, South Africa

Abstract

Model collapse has so far been measured through outputs, which may understate it if internal mechanisms degrade first. This study therefore traces the induction circuit behind in-context learning (ICL) in two-layer transformers retrained on data that the previous model partly or wholly relabels, or that accumulates alongside the real data. A tuned model reproduces its own labels almost exactly, so that accuracy holds under every real-to-synthetic ratio. Once errors are forced through a raised sampling temperature, however, the circuit degrades first: its logit margin halves while accuracy is unchanged and predicts the next generation's error rate, so that errors compound through the circuit. Retaining real data limits how far accuracy falls, and accumulation delays its decline, but neither stops the margin's erosion. Overall, retaining real data protects a model's behaviour for longer than its circuit, so that collapse may be detected in circuits before outputs.

Keywords: model collapse; induction heads; mechanistic interpretability

Introduction

Recursively training large language models (LLMs) on data generated by other models causes *model collapse*, a loss of information about the true data distribution (Shumailov et al., 2024), which retaining real data appears to avoid (Gerstgrasser et al., 2024). Both findings, however, rest on model outputs, which would understate collapse if internal mechanisms degrade first.

In-context learning (ICL) lets models adapt to new tasks from prompt examples without parameter updates (Olsson et al., 2022; Singh et al., 2024), and in the task of Singh et al. (2024) it is carried out by an induction circuit whose components are known, so that damage from recursive training can be traced to specific heads rather than inferred from accuracy. This study therefore asks how the share of real data in each generation's training pool shapes this circuit.

Background

Induction heads A previous-token head copies each symbol into the label that follows it, and an induction head matches the query against these copies through its key input and copies the matching label to the output; several such heads can contribute additively (Singh et al., 2024), and their formation tracks ICL ability (Chen et al., 2026).

Collapse and accumulation Collapse arises mainly from sampling error, which loses the tails of the distribution first and compounds each model's errors in the data of the next (Shumailov et al., 2024). Replacing real data makes test error grow with every iteration, whereas accumulating synthetic data alongside it keeps the error bounded (Gerstgrasser et al., 2024), and this study tests whether the same contrast holds for the induction circuit.

Methods

This study uses the setup of Singh et al. (2024): each sequence holds two exemplar–label pairs and a query, with Omniglot exemplars (Lake et al., 2015) encoded by a frozen ResNet18 (He et al., 2016) and five labels reassigned per sequence, so that only the context holds the answer. A causal two-layer attention-only transformer with eight heads per layer trains on 50 classes for one million sequences, at learning rates of 10^{-4} (base) and 3×10^{-4} (extended) tuned on 1,473 validation classes, and is tested on 100 unseen classes. The base model predicts the query's label, while the extended model also predicts a next symbol, chosen from the context, and its label, so that three tokens per sequence become synthetic.

Real-to-synthetic ratio Each run trains on a pool of $N = 20{,}000$ sequences for up to 20 generations, the first real, with initialisation and training length fixed. The previous model then regenerates the targets of 0%, 50%, 90%, or 100% of the pool from their real prompts, where 90% matches the 10% of real data kept by Shumailov et al. (2024). Accumulation instead adds N synthetic sequences per generation (Gerstgrasser et al., 2024), matching 50% replacement at generation 1, so that keeping earlier data can be separated from the real share. Targets are sampled at temperature T, and as the tuned model makes almost no errors at $T = 1$, errors are also forced at $T = 3$ and 5.

Circuit analysis Each generation is analysed on the same real sequences through its margin, the logit lead of the correct label over the other label in the context, and the edges that Automatic Circuit DisCovery (ACDC) (Conmy et al., 2023) keeps at $\tau = 0.001$, which measure how strongly and how sparsely the circuit separates the answer. The induction head's attention to the matching label measures whether it finds the answer, and its direct effect, the margin its output alone contributes, how strongly it copies it.

Results

Table 1: Generation 19 of every 20-generation run, under full replacement unless stated. †Margin below 1, where the circuit size is less reliable.

		Base model			Extended	
Condition	Real	Acc.	Margin	Edges	Margin	Edges
No forced errors ($T = 1$)						
Real only	100%	0.99	20.0	18	15.4	44
100% replaced	0%	0.99	12.5	35	13.8	55
Accumulate	5%	1.00	10.4	22	6.3	30
Forced errors ($T = 3$)						
50% replaced	50%	0.78	2.7	190	4.1	111
90% replaced	10%	0.31	0.4	204†	0.1	180†
100% replaced	0%	0.19	0.1	210†	−0.1	167†
Accumulate	5%	0.93	0.8	12†	0.6	13†

No errors, no collapse At generation 0, both models solve the task by ICL, with test accuracies of 0.98 and 0.97,




Figure 1: ACDC circuits of the base model; filled nodes are heads in the circuit, and wider edges have larger effects. The previous-token head A0.2 feeds the induction head A1.3 (a), and one generation of full replacement at $T = 3$ triples it (b).




Figure 2: The induction head's attention to the match and direct effect at $T = 3$, relative to generation 0: the copy weakens first.

perplexities of 1.10 and 1.27, and validation accuracies of 0.99 and 0.97 for the base and extended models. At $T = 1$, only 0.01% of labels are wrong after 20 generations, so that every replacement level yields the same model and accuracy stays at 0.99 (Table 1), although under full replacement the circuit grows from 17 edges (Figure 1a) to as many as 48 as its margin falls from 19.9 to 12.5.

The circuit fails before accuracy With errors forced at $T = 3$, full replacement halves the margin by generation 1, from 19.9 to 10.8, and triples the circuit to 55 edges while accuracy holds at 0.99 (Figure 1b). By generation 3, the circuit spans 209 edges across every head as accuracy falls to 0.70, and the extended model follows the same order, from 46 to 179 edges.

The induction head: the match holds, the copy weakens The induction head fails in two stages (Figure 2). Under full replacement, its attention to the matching label falls only from 0.96 to 0.88 by generation 2, whereas its direct effect falls from 5.3 to 2.8, so that the head still finds the correct label but copies it about half as strongly, and its attention collapses only at generation 4, after accuracy. Accumulation separates the two most clearly: attention to the match stays between 0.90 and 0.98 for 15 generations, whereas the direct effect falls by 84%, so that real data preserve where the head looks but not how strongly it copies.

The margin sets the next generation's errors Each model labels the next generation's data, and if its correct label leads the four wrong labels by its margin D_g, sampling at T makes a share

$$\hat{\varepsilon}_{g+1} = \frac{4\,e^{-D_g/T}}{1+4\,e^{-D_g/T}} \tag{1}$$

of these labels wrong, small while D_g is several times T but rising steeply as it shrinks. This predicts the observed share across both models, temperatures, and conditions to within 2.1 percentage points on average ($r = 0.994$), so that a falling margin writes more errors into the next pool and so lowers the next margin, a loop that only real data, whose labels stay correct, can slow.

The real share sets how far collapse goes Over 20 generations at $T = 3$, each replacement level settles at an accuracy set by its real share, 0.78 with half of the real data, 0.31 with a tenth, and 0.19 with none, with both models' margins in the same order (Table 1), although even half leaves the circuit spread across 190 edges. Accumulation holds accuracy at or above 0.97 for 15 generations as its real share falls to 6%, yet its margin falls by 96%, and accuracy declines once it drops below 1 at generation 16.

Discussion

The real-to-synthetic ratio shaped the induction circuit mainly once the synthetic data carried errors, as a tuned model reproduces its own labels almost exactly, and the margin then became the route through which collapse compounds, which extends Shumailov et al. (2024) with the internal quantity that sets the sampling error. Within the induction head, the copy failed before the match, which suggests that the copying operation of Singh et al. (2024) is the more fragile, likely because noisy labels lower its confidence rather than its ability to find the match. Accumulation protected accuracy, likely because every real prompt keeps its correct label, but not the margin, so that, unlike in Gerstgrasser et al. (2024), it delayed collapse rather than preventing it. The margin of an identified circuit could therefore flag collapse early. These conclusions are bounded by forcing errors through the sampling temperature rather than through a weaker model.

Conclusion

This investigation showed that, once synthetic data carry errors, the induction circuit degrades before accuracy does, while the share of real data sets only how far accuracy falls, from 0.78 with half to chance with none. Overall, retaining real data protects what a model does for longer than how confidently it does it, so that collapse is better detected in circuits than in outputs.

Contribution Statements

We, Lily de Melo, Tawananyasha Kadango, and Gopolang Mohlakola, worked together fairly on this project.

References

Chen, J., Luo, Y., & Pan, L. (2026). Mechanistic data attribution: Tracing the training origins of interpretable LLM units. In *International conference on machine learning* (Vol. 306). PMLR.

Conmy, A., Mavor-Parker, A., Lynch, A., Heimersheim, S., & Garriga-Alonso, A. (2023). Towards automated circuit discovery for mechanistic interpretability. In *Advances in neural information processing systems* (Vol. 36, pp. 16318–16352).

Gerstgrasser, M., Schaeffer, R., Dey, A., Rafailov, R., Pai, D., Sleight, H., ... Koyejo, S. (2024). Is model collapse inevitable? Breaking the curse of recursion by accumulating real and synthetic data. *arXiv preprint arXiv:2404.01413*.

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep residual learning for image recognition. In *Proceedings of the ieee conference on computer vision and pattern recognition* (pp. 770–778).

Lake, B. M., Salakhutdinov, R., & Tenenbaum, J. B. (2015). Human-level concept learning through probabilistic program induction. *Science*, *350*(6266), 1332–1338.

Olsson, C., Elhage, N., Nanda, N., Joseph, N., DasSarma, N., Henighan, T., ... others (2022). In-context learning and induction heads. *arXiv preprint arXiv:2209.11895*.

Shumailov, I., Shumaylov, Z., Zhao, Y., Papernot, N., Anderson, R., & Gal, Y. (2024). AI models collapse when trained on recursively generated data. *Nature*, *631*(8022), 755–759. doi: 10.1038/s41586-024-07566-y

Singh, A. K., Moskovitz, T., Hill, F., Chan, S. C. Y., & Saxe, A. M. (2024). What needs to go right for an induction head? A mechanistic study of in-context learning circuits and their formation. In *International conference on machine learning* (Vol. 235, pp. 45637–45662). PMLR.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract states the three main findings of this study, and the introduction the question that they answer, namely that the induction circuit degrades before accuracy once synthetic data carry errors, that the margin of each generation's model sets the error rate of the next generation's data, and that retaining real data delays rather than prevents collapse. Each claim is supported in the Results (Table 1, Figures 1 and 2, and Equation 1), and the abstract states that errors were forced by raising the sampling temperature, so that the scope of the claims is clear.

   Guidelines:

   - The answer NA means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A No or NA answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: The Discussion states that errors were forced by raising the sampling temperature rather than arising from a weaker model. In addition, the Results note that circuit sizes are less reliable once the margin falls below 1 (Table 1). This study is also limited to a single two-layer attention-only model, a single synthetic task, and one initialisation per condition.

   Guidelines:

   - The answer NA means that the paper has no limitation while the answer No means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory Assumptions and Proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [NA]

Justification: This study contains no theorems. Equation 1 follows directly from the softmax under the assumption stated before it, namely that the correct label leads each of the four wrong labels by the same margin, and is tested empirically rather than proven.

Guidelines:

- The answer NA means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental Result Reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: The Methods specify the task, architecture, class splits, pool size, real-to-synthetic ratios, sampling temperatures, tuned learning rates, training length, and Automatic Circuit DisCovery (ACDC) threshold. The remaining settings, namely the Adam optimiser, a batch size of 32, a model width of 64, and the initialisation seed, are fixed in the released run scripts, so that each run can be repeated under the same configuration.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - If the paper includes experiments, a No answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
   - While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
   (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
   (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
   (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
   (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [Yes]

Justification: The code, the preprocessed Omniglot features, and the scripts that run every experiment and produce every figure are available at `https://github.com/froggomelo/nlp-project-1`. The repository's README specifies the environment and the exact command for each experiment.

Guidelines:

- The answer NA means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so "No" is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://nips.cc/public/guides/CodeSubmissionPolicy`) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental Setting/Details**

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer, etc.) necessary to understand the results?

Answer: [Yes]

Justification: The Methods state that the model trains on 50 Omniglot classes and is tested on 100 unseen classes, so that test accuracy reflects ICL alone. The learning rate and training length were tuned per model on 1,473 separate validation classes, so that the test classes remain unseen during tuning, and the chosen values are reported.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment Statistical Significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [No]

Justification: Each condition was run once from a fixed initialisation, so that conditions differ only in their training pool, and error bars are therefore not reported. As a reference for change without synthetic data, Table 1 reports a real-only control retrained on real data for 20 generations, and the fit of Equation 1 is reported as a correlation and an average absolute gap across every generation and condition.

Guidelines:

- The answer NA means that the paper does not include experiments.
- The authors should answer "Yes" if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.

- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g. negative error rates).
- If error bars are reported in tables or plots, The authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments Compute Resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [Yes]

   Justification: Every experiment was run on the CPU of a single desktop computer (AMD Ryzen 7 7800X3D, 32 GB of RAM). Training on one million sequences took approximately 2.2 minutes, so that the 580 trainings of the full run script take roughly a day, with circuit discovery and the longer eight-item contexts adding to this. Development runs not reported in this study used additional compute of a similar scale.

   Guidelines:

   - The answer NA means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code Of Ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes]

   Justification: This study uses a public dataset of handwritten characters and small models trained for analysis. It involves no human subjects or personal data and releases no model with a risk of misuse.

   Guidelines:

   - The answer NA means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer No, they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader Impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [NA]

    Justification: This study is foundational research on a small model trained on a synthetic task and has no direct path to harmful applications. Its one implied application, namely using the margin of an identified circuit to flag collapse before accuracy falls, is a positive use and is considered in the Discussion.

Guidelines:

- The answer NA means that there is no societal impact of the work performed.
- If the authors answer NA or No, they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pretrained language models, image generators, or scraped datasets)?

    Answer: [NA]

    Justification: The released models are two-layer transformers trained on Omniglot features and therefore pose no risk of misuse.

    Guidelines:

    - The answer NA means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: Omniglot (Lake et al., 2015) is used under the MIT License, and the ResNet18 ImageNet weights (He et al., 2016) are taken from torchvision under the BSD-3-Clause License. Circuit discovery uses ACDC (Conmy et al., 2023) through the auto-circuit (version 1.0.1) and TransformerLens (version 2.9.0) libraries, both under the MIT License. The training code extends the released codebase of Singh et al. (2024), which is credited in the repository.

    Guidelines:

    - The answer NA means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.

- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New Assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The released code is documented in the repository's README and in the files of `docs/`, which describe each experiment, its settings, and how it is reproduced. No data were collected from people, so that consent does not apply.

    Guidelines:

    - The answer NA means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and Research with Human Subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [NA]

    Justification: This study involves neither crowdsourcing nor research with human subjects.

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional Review Board (IRB) Approvals or Equivalent for Research with Human Subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [NA]

    Justification: This study involves neither crowdsourcing nor research with human subjects.

    Guidelines:

    - The answer NA means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

Wits University Faculty of Science post-graduate student AI declaration

I understand that the use of generative AI tools (such as ChatGPT or similar) without explicitly declaring such use constitutes a form of plagiarism and is classified by Wits University as academic misconduct.

I declare that in the course of conducting the research towards my degree or in the preparation of this thesis/dissertation/research report (select one by marking with an X):

I **did not** make use of generative AI tools ☐

I **did** make use of generative AI tools for the following (tick all that apply):

1. Idea Generation (research problem/design, hypothesis) ☐
2. Sourcing Related Work (summarising, identifying sources) ☐
3. Methods and Experiment Design (experiment setup, model tuning) ☐
4. Data Analysis (presentation, coding, interpretation) ☐
5. Theoretical Development (theorem proving, conceptual analysis) ☐
6. Code Development (generating algorithms, writing scripts) ☐
7. Presentation (rendering graphics, formatting) ☐
8. Editing (grammar, readability) ☐
9. Writing (text generation, document structuring) ☐
10. Citation Formatting (structuring, organising) ☐

If other uses were involved, please specify below:

Generative AI tool used (list all)	**Used for?**

If generative AI tools were used as an integral part of the experimental design or in the direct execution of my research, I confirm that details of this use are clearly outlined in the relevant experimental/methodology chapters of my thesis/dissertation/research report.

Student number:

Candidate signature:

Date: