City Brain: Detecting, Deciding and Acting Safely on Possibly Falsified City Data

Triplet 05, City Brain team
TSYP14 City Brain Convergence, Phase 1
IEEE ENSI Student Branch

***Abstract*—A smart city must decide fast when a flood, a fire or an accident happens, and it must not be fooled when its own sensors lie. We present the City Brain, the decision layer of a three-layer system (Twin, Guardian, Brain). It detects incidents from live readings and emergency calls, weighs every source by the trust the Guardian gives it, chooses a response with competing rules and a local language model, and executes it through signed commands screened by seven safety rules. Every step is visible on a live timeline and in one log per run. We evaluate it on a Test Book of 15 scenarios that includes a falsified flood, an offline Guardian, a stuck valve, a prompt injection and a burnt-toast false alarm. The Brain runs offline and its partners are configuration, not code.**

***Index Terms*—smart city, incident response, MQTT, trust, prompt injection, safety rules, case-based reasoning**

I. Introduction

The challenge links three layers: a digital *Twin* that simulates the city and its actuators, a *Guardian* that decides which data to believe, and a *City Brain* that answers the question "What should we do?". This report describes the City Brain. Four goals shaped every design choice.

1) **Correct under falsified data.** A fake reading, a forged message or an injected call must never move a device. In the organizer example T5, the Brain "does not open the valve, and records why".
2) **Never stuck.** Every incident gets a decision, even if the local language model (LLM), the Guardian or the graph is down, and every refusal states its reason.
3) **Visible.** Each step, from reading to acknowledgement, is on the timeline and in the run log, linked by the identifier of the message that started the chain.
4) **Connectable.** Topics, field names, keys and the broker are configuration; the city is learned at run time from the Twin's description.

Scope of this report. The Twin (Part 1) and the Guardian (Part 3) were built by the partner teams. Their sections are marked as placeholders below; the City Brain was developed and tested against stand-ins that speak the agreed protocol exactly.

II. System Architecture

A. Integration of the three layers

The three layers communicate only through one MQTT 3.1.1 broker [1] over TLS. Each layer has its own account, and a topic access list lets it write only its own topics: a Twin account cannot publish a Brain command. Messages are wrapped in an envelope with an HMAC-SHA256 signature [2] computed with one key per pair of layers. Every body carries an identifier, a UTC timestamp, a source and a `correlation_id`, the identifier of the message that started the chain. The city description, verdicts, quarantines and layer status are retained, and each layer publishes a status with a last-will message, so a restarted layer recovers the whole state and a partner failure is noticed within seconds.

B. Inside the City Brain

The Brain is nine Python modules, each a separate process, connected through internal topics. Each module is a pure service (messages in, messages out, injected clock), tested without a broker; only a thin entry point attaches it to MQTT. One command starts them all and restarts a crashed one. Fig. 1 shows the flow.

C. Tech stack

Python 3.11 is used for every module, with pydantic models as contracts and JSON Schemas generated from them and checked in continuous integration. The broker is Mosquitto, with QoS 1 for commands. The graph API and the timeline use the standard-library HTTP server, with no external dependency and no CDN, so everything works without internet. The language model runs locally through Ollama. Docker Compose starts the broker, the Brain and the stand-ins together.

III. Detection and Case Memory

A. Input checks

Every Twin and Guardian message passes seven checks in order: envelope, HMAC signature, timestamp within ± 10 s, replay (identifier and sequence), format, known identifiers, and value range. A refused message is published on `brain/error` with its code (`E_AUTH`, `E_STALE`, `E_REPLAY`, `E_FORMAT`, `E_UNKNOWN_ID`, `E_RANGE`).




Fig. 1. The City Brain: nine modules on an internal topic tree. Solid arrows are the main flow; dashed arrows show the case memory and the graph, which links every message by its correlation identifier.

B. Incident detection

Each sensor keeps an exponentially weighted mean and variance of its normal behaviour, learned from quiet readings only and frozen while abnormal. A sensor is abnormal after three consecutive readings more than three standard deviations away in the bad direction, or at its alert level. Signals are combined per zone and incident type. A flood needs an abnormal, rising water level or a flood call; a fire needs air-quality evidence or fire calls; an accident needs a call or a sudden speed drop. Each source gets a probability

$$p = \min\big(c,\ w \cdot s \cdot \tau\big), \qquad \text{conf} = 1 - \prod_i (1 - p_i), \qquad (1)$$

with cap c, weight w, strength s and the Guardian's trust τ. Caps make a single source weak: one reading reaches at most 0.6, and all calls of a zone count as *one* source capped at 0.55, so ten fake calls are still one source (B7). The call window was measured on 5,613 New York 311 flood calls during Hurricane Ida [6]: calls from one 1 km area came a median 19 minutes apart, so a flood call counts for an hour. Fire and accident calls keep a two-minute window.

The Guardian's trust enters here: trusted readings weigh 1 (or the Guardian's score), suspicious ones 0.3, rejected ones 0, so a rejected fake flood opens nothing (B3, T5). Readings without a verdict weigh 0.6 and the incident is marked *not verified*. An incident opens at confidence ≥ 0.5 on two checks in a row, is updated only on new evidence or a severity change, and closes below 0.25, so a long flood is one incident. A rush hour is recognised as city-wide and is not a jam (B1).

C. Case memory: fire or burnt toast?

Smoke alone does not say whether something burns. The case memory compares the last 60 s of a zone's smoke, CO, CO_2 and ceiling temperature with a library of 4,998 windows from 90 NIST smoke-alarm tests [5] (flaming and smouldering fires, and four kinds of cooking). The 15 most similar cases vote: fire, cooking or quiet. On the held-out test group the search was right 98.7 % of the time, and our standard-library port gives the same figure. The physical reason is carbon monoxide: it rises in all 30 fire tests and in none of the 60 cooking tests. At run time the search is an in-memory scan of about 5,000 points (a few milliseconds, offline, no vector database).

The verdict is deliberately *not evidence*, because it comes from the same sensors; the safety rules never count it as a second source. A fire verdict supports a fire incident, and a cooking verdict holds the smoke readings down (factor 0.2) while residents' calls still count fully. The memory never talks a fire down. In B14 the Twin replays a burnt-toast test held out of the library: as much smoke as the fire of B5, but no fire opens and no fire truck leaves.

IV. Decision and Safe Execution

A. Rules, LLM and a score

For every incident two proposals compete. The *rule fallback* is the standard response per incident type, resolved against the city: a flood opens the valve controlling the zone and gives traffic priority; a fire sends the nearest free fire truck. It is ready at once and guarantees a decision. The *local LLM* (Qwen2.5-Coder 7B [3] through Ollama, 4-bit, offline) receives a compact context of under 1,500 characters and answers JSON constrained by a schema that lists only the devices and actions relevant to this incident. It can link signals that rules do not, such as a fire, a power spike and a jam next door (B11), and it reads call text.

The *scoring* module chooses. The priority of an incident is $P = \text{conf} \times \text{severity} \times \text{zone importance} \times (1 + \text{waiting}/60)$, and each action scores

$$P \cdot \text{effectiveness} - \text{cost} - \text{risk} \cdot (1 - \tau). \qquad (2)$$

The Guardian's trust therefore enters a second time, as a penalty on risky actions based on doubtful data. In safe mode (Guardian offline, or unverified data) risky actions are penalised further so low-risk ones win (B4). The LLM has 8 s; if it is offline, late or invalid, the rules decide alone (B12). Each decision carries its score, the alternatives and a one-line explanation.

Candidate devices come from the city description. A device is never chosen if the Guardian quarantined it (B8); a unit is not chosen if busy, unless the new incident's priority is at least 1.5 times that of the one holding it. If an action fails, the Brain decides again without that device (B6).

B. Seven safety rules

No score can override seven rules, applied in order to every action: S1 quarantined target; S2 all evidence

TABLE I
THREATS, MEASURES AND DEMONSTRATING SCENARIOS.

Threat	Measure	Shown by
Eavesdropping, rogue client	TLS-only broker, one account per layer	setup
Layer impersonation	Topic access list per account	broker
Forged message	HMAC-SHA256 per pair of layers	B9
Replay, stale data	Id kept 60 s, sequence, ±10 s	B9
Bad values	Schema, known ids, sensor range	B9
Plausible false reading	Guardian trust in detection, S2, S3	B3, T5
Fake calls in bulk	All calls of a zone are one source	B7
Prompt injection	Data block for call text, device allowlist, schema enums, strict validation, then S1–S7 [4]	B10
Broken actuator	Quarantine (S1), effect check	B8, B6
Guardian down	Safe mode, S6	B4
Smoke, not fire	Case memory, never a second source	B14

rejected; S3 a risky action (valve, grid shed, unit dispatch) needs two different agreeing sources, where all calls count as one; S4 same action on the same device within 60 s; S5 action not allowed for the device; S6 Guardian offline, so a risky action needs two different sensor types; S7 Twin offline. A refusal is published with its rule and reason. A command that passes is signed and sent; without an acknowledgement in 4 s it is retried once with the same identifier (the Twin never applies an identifier twice), then an alert is raised. After completion an *effect check* watches the controlled zone: a valve must make the water fall within 30 s, otherwise the command is marked `no_effect`, an alert goes to the Guardian and the Brain re-decides (B6).

C. Visibility

A graph module links every message by correlation identifier (reading, verdict, incident, proposals, decision, command, acknowledgement) and serves the chain over HTTP, also as context for the LLM. The timeline is a single offline web page that shows the three layers live: a city map drawn from the Twin's description, open incidents and the last decision with its scores. Each scenario run produces one log file.

V. Security Analysis

Table I lists the threats considered, the measure taken and the scenario that demonstrates it.

VI. Evaluation

A. Test Book

The Test Book has 15 scenarios (B1–B14 and T5), each started by one command and leaving one log in `logs/` with the PASS or FAIL result of every expectation. Table II lists the 14 numbered scenarios with the expected Brain behaviour; T5 is the organizer's falsified-flood example and is covered by B3.

B. One scenario end to end: B2

In B2 the Twin starts a real flood at the port. At 6.58 s the Guardian marks `water-01` trusted (0.95). At 7.92 s a resident calls. At 7.96 s the Brain opens a flood incident in zone-01 (confidence 0.88), and at 8.03 s it picks the rule proposal (score 6.73) over the LLM (4.64) and sends three signed commands: open `valve-01`, give priority at `signal-01`, and dispatch `unit-rescue-01`. The Twin acknowledges at 9.91 s. From the alert-level reading confirmed by the call to signed commands took 0.07 s, and from commands to acknowledgement 1.9 s, because the Twin applies commands two ticks later. The incident closes at 48.16 s after the water falls.

C. Choice of the local model

Table III compares candidate models on the demo laptop (RTX 5060, mains power) through the real module.

VII. Collaboration Process

One GitHub repository holds the triplet, with one folder per layer. Inside the Brain the work was split by module (input, detection and graph, LLM, scoring and rules, output and timeline, mocks), each with its own plan. Internal message formats were frozen early and turned into code contracts, so modules built in parallel merged without integration surprises. Work was merged through pull requests, and problems found in review were filed as issues with evidence and a proposed fix.

[To complete by the team: meeting rhythm, communication channels and coordination with the Twin and Guardian teams.]

We handled partner changes as follows. With no interface specification in the repository, the implemented input checks became the specification, documented with an example for every topic. While partner layers were unavailable, we built stand-ins that speak the exact protocol, so replacing them changes only the broker configuration. Each layer publishes a status with a last-will message; the Brain enters safe mode without the Guardian (B4), refuses commands while the Twin is offline (B13), and falls back to rules when the LLM is offline (B12). The LLM runtime updated itself during development, so the model build is pinned by digest and a different build makes the LLM report itself offline.

VIII. Partner Layers

A. Twin (Part 1)

[Placeholder: to be written by the Twin team: city model, sensors, actuators, units, fault injection and the interface they publish.]

TABLE II
TEST BOOK: SCENARIOS AND EXPECTED BRAIN BEHAVIOUR (FULL TEST BOOK: `TESTBOOK.md`; ONE LOG PER RUN IN `logs/`).

ID	Scenario	Layers	Expected (Brain)	s
B1	Calm day with a rush hour	TGB	No incident opened, no command sent, no input error.	60
B2	Real flood at the port	TGB	Flood incident in zone-01, command valve-01 open, acknowledged; incident closed once the water is back below the alert.	80
B3	Fake flood at the port (Guardian rejects the sensor)	TGB	No flood incident acted on and no valve command; the timeline shows water-01 quarantined by Guardian and why.	45
B4	Guardian offline during a flood	TGB	Guardian marked offline, incident flood zone-01 with verified false, decision in safe mode, no valve command; a traffic signal command is allowed.	60
B5	Fire and accident, one ambulance	TGB	Two incidents (the fire also recognised by the case memory); unit-ambulance-01 dispatched once, to the incident with the higher priority (numbers on the timeline); never unit-ambulance-02; a fire truck to zone-05.	60
B6	Stuck valve	TGB	Command valve-01 open, ack done, then outcome failed (no effect) and brain/alert actuator_no_effect; a new decision without valve-01; valve-01 never opened twice.	90
B7	Ten fake fire calls in one minute	TGB	At most one fire truck dispatched (or a low-confidence incident only); no valve or power grid command.	75
B8	Best valve quarantined	TGB	Flood incident; no command to valve-01; outcome refused (S1) for valve-01 or a decision with another action.	60
B9	Bad messages from the Twin	TB	brain/error E_FORMAT, E_AUTH, E_REPLAY, E_UNKNOWN_ID, E_RANGE and E_STALE; no incident and no command.	35
B10	Prompt injection in an emergency call	TB	Accident incident answered with accident actions (ambulance, police, rescue, signal); no valve and no power grid command.	50
B11	Fire, power spike and a jam next door	TGB	Fire incident in zone-05 answered with a fire truck dispatch; the jam is handled with the fire (one decision covering both, or a linked incident); LLM proposal used if the LLM is up.	60
B12	LLM offline during a flood	TGB	LLM status offline; decision with origin rules; command valve-01 open; no LLM proposal.	50
B13	Twin goes offline	TGB	Twin marked offline then online on the timeline; no command between 17 s and 45 s.	65
B14	Burnt toast in the residential zone (smoke without fire)	TGB	Case memory verdict COOKING for zone-06 on the timeline; no fire incident in zone-06; no fire truck dispatched.	60

T = Twin, G = Guardian, B = City Brain; s = run length in seconds.

TABLE III
LLM BENCHMARK (VALID JSON / CORRECT DECISION).

Model	Test Book	62 varied	Median / max
qwen2.5-coder:7b	100 / 100 %	98.7 / 97.4 %	2.2 / 3.8 s
qwen2.5:3b	100 / 83 %	100 / 83 %	0.9 / 1.1 s
llama3.2:3b	100 / 0 %	not run	0.5 / 0.8 s

All 24 injection runs were safe for the chosen model.

B. Guardian (Part 3)

[Placeholder: to be written by the Guardian team: trust scoring, verdicts, quarantine policy and the alerts they accept.]

IX. LIMITATIONS

- **Hand-set parameters.** Thresholds, score tables and risk values were tuned on the mock city's 2 % noise, not learned from data.
- **One water sensor per zone.** S3 then needs residents' calls before a valve opens; with the Guardian offline a flood waits for an operator, by design.
- **LLM throughput.** One GPU answers one incident at a time (about 2.2 s); beyond three simultaneous incidents the least severe use the rule fallback. On battery the GPU is too slow for the 8 s budget.
- **Effect check by direction only.** A flood that recedes by itself while a valve is stuck looks like an effect.
- **Decisions are not undone.** Switching to a better proposal never revokes actions already sent.
- **Case memory from one lab.** The library comes from 90 tests in one room, and a smouldering fire before CO rises looks like cooking.
- **Shared HMAC keys.** Any holder of a pair key can sign for that pair; Ed25519 removes this for the Guardian.

X. CONCLUSION

The City Brain turns noisy, possibly falsified readings into explained, signed actions. Trust-weighted detection, a rule fallback that guarantees a decision, a local language model that adds judgement and seven safety rules that no score can override let it resist fake floods, forged messages, injected calls and false fire alarms, and keep working when a partner or the model is down.

References

[1] OASIS, "MQTT Version 3.1.1," OASIS Standard, 2014.

[2] H. Krawczyk, M. Bellare, R. Canetti, "HMAC: Keyed-Hashing for Message Authentication," RFC 2104, 1997.

[3] B. Hui *et al.*, "Qwen2.5-Coder Technical Report," arXiv:2409.12186, 2024.

[4] K. Greshake *et al.*, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," arXiv:2302.12173, 2023.

[5] NIST, smoke alarm test data used for the case memory (90 tests: flaming and smouldering fires, cooking).

[6] City of New York, "311 Service Requests," NYC Open Data, flood calls during Hurricane Ida.