

Ace your JavaScript Interview. [Get my ebook](#). 100 solved Javascript, 20 solved React, & 2 frontend system design questions (**1160+ copies sold**). Get a [Free preview](#).



Advertisements

Reverse a stack using recursion.

Posted on [February 5, 2019](#) | by [Prashant Yadav](#)

Posted in [Algorithms](#), [Stack](#) | Tagged [medium](#)

An algorithm to reverse a [stack](#) using recursion.

We will implement an algorithm to reverse a [stack](#) using recursion in javascript. Everything will be written in [ES6](#).

Example

Input:

5 4 3 2 1

Output:

1 2 3 4 5

Copy

Practically
prepare for
your
JavaScript
interview

[JavaScript
Revision](#)

[JavaScript-
Concept Based
Problems](#)

[Data Structures](#)

[Algorithms](#)

[Machine
Coding](#)

[Web
Fundamentals](#)

Advertisements

Implementation

- We will be using two functions which will be calling one another recursively to reverse the [stack](#).
- First function will be used to remove each item from the [stack](#) and pass it to the second function to add it at the top of the [stack](#).
- Then the second function will check if [stack](#) is empty or not. If it is empty then add the items in the [stack](#) else call the first function.

[Copy](#)

```
//First function to reverse the stack
let reverseStack = (stack) => {
  //If stack has value then call it recursively
  if(!stack.isEmpty()){
    let temp = stack.pop();
    reverseStack(stack);

    //Pass the element to second function to add it at top
    insertAtBottom(temp, stack);
  }
}

//Second function to add the items at the bottom
let insertAtBottom = (temp, stack) => {
  //If stack is empty then add the item
  if(stack.isEmpty()){
    stack.push(temp);
  }else{

    //Else call the same function recursively
    let x = stack.pop();
    insertAtBottom(temp, stack);
    stack.push(x);
  }
}
```

[Copy](#)

Input:

```
let stack = new Stack();
stack.push(1);
stack.push(2);
stack.push(3);
stack.push(4);
stack.push(5);

reverseStack(stack); //call the function

//Print the stack
while(!stack.isEmpty()){
  console.log(stack.pop());
}
```

Output:

```
1
2
3
4
5
```

Time complexity: $O(n^2)$.

Space complexity: $O(n)$.

Time and Space complexity

- We are using two functions in which first function is calling itself recursively as well as the second function in each call. Also the second function is calling itself recursively, so Time complexity is $O(n^2)$.

- We are storing both the functions in call stack one after another, so Space complexity is $O(2n) = O(n)$.

Prepare for your **JavaScript Interview** practically on each Interview rounds and grab that job.

BEGIN LEARNING

Recommended Posts:

- [Bubble sort using two stacks](#)
- [3Sum closest](#)
- [Check if binary tree has path sum](#)
- [Print all subarrays with a given sum k in an array](#)
- [Insertion sort algorithm in javascript](#)
- [Print right view of a binary tree](#)
- [Top view of a binary tree](#)
- [Find least frequent number from an array](#)
- [Program to print the diamond pattern](#)
- [Count number of sub-string occurrence in a string](#)

[Prev](#)

[Next](#)

Comments

sr says:

[July 22, 2020 At 2:19 Pm](#)

hey prashant!
could u please explain the space complexity part.....i think it should be o(n) because at a time only one of the 2 functions will be on stack trace.

[Reply](#)

[Prashant Yadav](#) says:

[July 22, 2020 At 6:54 Pm](#)

Yes, thanks for pointing it out. Updated it.

[Reply](#)

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment

Start typing...



Name*

Name

Email*

Email

POST COMMENT

Advertisements



[About Us](#)

[Contact Us](#)

[Privacy Policy](#)

[Advertise](#)



Handcrafted with  somewhere in **Mumbai**

© 2023 [LearnersBucket](#) | [Prashant Yadav](#)

